

Report No.: 190505003RFC-2

# SAR TEST EXCLUSION **EVALUATION REPORT**

Product Name: Truly Wireless Stereo Earbuds

Trade Mark: EDIFIER

Model No. / HVIN: TWS1

Add. Model No. / HVIN: N/A

Report Number: 190505003RFC-2

FCC 47 CFR Part 2.1093 **Test Standards:** 

RSS-102 Issue 5

FCC ID: Z9G-EDF87

IC: 10004A-EDF87

Test Result: PASS

Date of Issue: June 3, 2019

#### Prepared for:

## **Edifier International Limited** P.O. Box 6264 General Post Office Hong Kong


#### Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd. 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

> TEL: +86-755-2823 0888 FAX: +86-755-2823 0886

| Prepared by: | Tonn                                    | Reviewed by: | 4                 | _ |
|--------------|---|--------------|-------------------|---|
|              | Tony Kang                               |              | Kevin Liang       |   |
|              | Project Engineer                        |              | Assistant Manager |   |
|              | (S UnionTrust ")                        |              |                   |   |
| Approved by: | *************************************** | Date:        | June 3, 2019      |   |
| 32 T         | Billy LE                                | _            |                   |   |

**Technical Director** 





**Version** 

| Version No. | Date         | Description |
|-------------|--------------|-------------|
| V1.0        | June 3, 2019 | Original    |

Report No.: 190505003RFC-2



Report No.: 190505003RFC-2



## **CONTENTS**

| 1.  | GENERAL INFORMATION |   |  |  |  |  |  |  |
|-----|---------------------|---|--|--|--|--|--|--|
|     | 1.1<br>1.2          | CLIENT INFORMATION                          |  |  |  |  |  |  |
|     | 1.3                 | EUT Information                             |  |  |  |  |  |  |
|     | 1.4                 | OTHER INFORMATION                           |  |  |  |  |  |  |
|     | 1.5                 | GENERAL DESCRIPTION OF APPLIED STANDARDS    |  |  |  |  |  |  |
|     | 1.6                 | DEVIATION FROM STANDARDS                    |  |  |  |  |  |  |
|     | 1.7                 | ABNORMALITIES FROM STANDARD CONDITIONS      |  |  |  |  |  |  |
|     | 1.8                 | OTHER INFORMATION REQUESTED BY THE CUSTOMER |  |  |  |  |  |  |
| 2.  | EQUI                | PMENT LIST                                  |  |  |  |  |  |  |
| 3.  | SAR                 | TEST EXCLUSION EVALUATION                   |  |  |  |  |  |  |
|     | 3.1                 | REFERENCE DOCUMENTS FOR EVALUATION          |  |  |  |  |  |  |
|     | 3.2                 | REFERENCE DOCUMENTS FOR EVALUATION          |  |  |  |  |  |  |
|     |                     | 3.2.1 SAR TEST EXCLUSION THRESHOLD          |  |  |  |  |  |  |
|     |                     | 3.2.2 TEST PROCEDURE                        |  |  |  |  |  |  |
|     | 3.3                 | MPE CALCULATION RESULTS                     |  |  |  |  |  |  |
|     |                     | 3.3.1 FOR BT                                |  |  |  |  |  |  |
| API | PENDI               | X 1 PHOTOS OF TEST SETUP10                  |  |  |  |  |  |  |
|     |                     | X 1 PHOTOS OF EUT CONSTRUCTIONAL DETAILS    |  |  |  |  |  |  |



Page 4 of 10 Report No.: 190505003RFC-2

# 1. GENERAL INFORMATION 1.1 CLIENT INFORMATION

| Applicant:               | Edifier International Limited               |  |
|--------------------------|---|--|
| Address of Applicant:    | P.O. Box 6264 General Post Office Hong Kong |  |
| Manufacturer:            | Edifier International Limited               |  |
| Address of Manufacturer: | P.O. Box 6264 General Post Office Hong Kong |  |

#### 1.2 EUT INFORMATION

| Product Name:          | Truly Wireless Stereo Earbuds |  |  |  |  |
|------------------------|-------------------------------|--|--|--|--|
| Model No. / HVIN:      | TWS1                          |  |  |  |  |
| Add. Model No. / HVIN: | N/A                           |  |  |  |  |
| Trade Mark:            | EDIFIER                       |  |  |  |  |
| DUT Stage:             | Identical Prototype           |  |  |  |  |
| EUT Supports Function: | 2.4 GHz ISM Band:             | Bluetooth 5.0 (LE/ 2LE/ LE Code mode is not supported) |  |  |  |
| Software Version:      | V1.0                          |  |  |  |  |
| Hardware Version:      | V1.0                          |  |  |  |  |
| Sample Received Date:  | May 10, 2019                  |  |  |  |  |
| Sample Tested Date:    | May 10, 2019 to June 3        | 3, 2019  |  |  |  |

#### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

| For BT_EDR            |   |           |  |  |  |
|-----------------------|---|-----------|--|--|--|
| Frequency Band:       | 2400 MHz to 2483.5 MHz                  |           |  |  |  |
| Frequency Range:      | 2402 MHz to 2480 MHz                    |           |  |  |  |
| Bluetooth Version:    | Bluetooth BR + EDR                      |           |  |  |  |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |           |  |  |  |
| Type of Modulation:   | GFSK, π/4DQPSK, 8DPSK                   |           |  |  |  |
| Number of Channels:   | 79                                      |           |  |  |  |
| Channel Separation:   | 1 MHz                                   |           |  |  |  |
| Antenna Type:         | LDS Antenna                             |           |  |  |  |
| Antenna Gain:         | Right Ear                               | 1.11 dBi  |  |  |  |
| Antenna Gaill:        | Left Ear                                | -0.06 dBi |  |  |  |
| Maximum Peak Power:   | 10.695 dBm                              |           |  |  |  |

### 1.4 OTHER INFORMATION

| Test channels for BT_EDR |                          |                       |            |            |  |  |
|--------------------------|--------------------------|-----------------------|------------|------------|--|--|
| Mode                     | Ty/Dy Eroguanov          | Test RF Channel Lists |            |            |  |  |
| Mode                     | Tx/Rx Frequency          | Lowest(L)             | Middle(M)  | Highest(H) |  |  |
| GFSK                     | 2402 MHz to 2480 MHz     | Channel 0             | Channel 39 | Channel 78 |  |  |
| (DH1, DH3, DH5)          |                          | 2402 MHz              | 2441 MHz   | 2480 MHz   |  |  |
| π/4DQPSK                 | 2402 MHz to 2480 MHz     | Channel 0             | Channel 39 | Channel 78 |  |  |
| (DH1, DH3, DH5)          |                          | 2402 MHz              | 2441 MHz   | 2480 MHz   |  |  |
| 8DPSK                    | 2402 MHz to 2480 MHz     | Channel 0             | Channel 39 | Channel 78 |  |  |
| (DH1, DH3, DH5)          | 2402 IVITZ (0 2400 IVITZ | 2402 MHz              | 2441 MHz   | 2480 MHz   |  |  |



Page 5 of 10 Report No.: 190505003RFC-2

## 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 2.1093 RSS-102 Issue 5

All test items have been performed and recorded as per the above standards

#### 1.6 DEVIATION FROM STANDARDS

None.

## 1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None

## 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

Page 6 of 10 Report No.: 190505003RFC-2

# 3. SAR TEST EXCLUSION EVALUATION 3.1 REFERENCE DOCUMENTS FOR EVALUATION

| No. | Identity   | Document Title   |  |  |  |  |  |
|-----|--|--|--|--|--|--|--|
| 1   | FCC 47 CFR Part 2.1093                             | Radiofrequency radiation exposure evaluation: portable devices.                                |  |  |  |  |  |
| 2   | RSS-102 Issue 5                                    | Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) |  |  |  |  |  |
| 3   | KDB 447498 D01 General RF<br>Exposure Guidance v06 | RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES    |  |  |  |  |  |

## 3.2 EXEMPTION LIMITS FOR ROUTINE EVALUATION - SAR EVALUATION

#### 3.2.1 SAR Test Exclusion Threshold

3.2.1.1 KDB 447498 D01 v06

#### Appendix A

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

| 1 | MHz  | 5  | 10 | 15  | 20  | 25  | mm                                |
|---|------|----|----|-----|-----|-----|-----------------------------------|
|   | 150  | 39 | 77 | 116 | 155 | 194 |                                   |
|   | 300  | 27 | 55 | 82  | 110 | 137 |                                   |
|   | 450  | 22 | 45 | 67  | 89  | 112 |                                   |
|   | 835  | 16 | 33 | 49  | 66  | 82  |                                   |
|   | 900  | 16 | 32 | 47  | 63  | 79  | SAR Test Exclusion Threshold (mW) |
|   | 1500 | 12 | 24 | 37  | 49  | 61  |                                   |
|   | 1900 | 11 | 22 | 33  | 44  | 54  |                                   |
|   | 2450 | 10 | 19 | 29  | 38  | 48  | 2 (22)                            |
|   | 3600 | 8  | 16 | 24  | 32  | 40  |                                   |
|   | 5200 | 7  | 13 | 20  | 26  | 33  |                                   |
|   | 5400 | 6  | 13 | 19  | 26  | 32  |                                   |
|   | 5800 | 6  | 12 | 19  | 25  | 31  |                                   |

| MHz  | 30  | 35  | 40  | 45  | 50  | mm                    |
|------|-----|-----|-----|-----|-----|-----------------------|
| 150  | 232 | 271 | 310 | 349 | 387 |                       |
| 300  | 164 | 192 | 219 | 246 | 274 |                       |
| 450  | 134 | 157 | 179 | 201 | 224 |                       |
| 835  | 98  | 115 | 131 | 148 | 164 |                       |
| 900  | 95  | 111 | 126 | 142 | 158 | SAR Test<br>Exclusion |
| 1500 | 73  | 86  | 98  | 110 | 122 |                       |
| 1900 | 65  | 76  | 87  | 98  | 109 | Threshold (mW)        |
| 2450 | 57  | 67  | 77  | 86  | 96  | 2 65.761.0 (22.11)    |
| 3600 | 47  | 55  | 63  | 71  | 79  |                       |
| 5200 | 39  | 46  | 53  | 59  | 66  |                       |
| 5400 | 39  | 45  | 52  | 58  | 65  |                       |
| 5800 | 37  | 44  | 50  | 56  | 62  |                       |

<u>Note</u>: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

#### 3.2.1.2 RSS-102 Issue 5

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>

| Frequency | Exemption Limits (mW)               |               |                    |                  |               |  |  |  |
|-----------|-------------------------------------|---------------|--------------------|------------------|---------------|--|--|--|
| (MHz)     | At separation                       | At separation | At separation      | At separation    | At separation |  |  |  |
|           | distance of                         | distance of   | distance of        | distance of      | distance of   |  |  |  |
|           | ≤ <b>5 mm</b>                       | 10 mm         | 15 mm              | 20 mm            | 25 mm         |  |  |  |
| ≤300      | 71 mW                               | 101 mW        | 132 mW             | 162 mW           | 193 mW        |  |  |  |
| 450       | 52 mW                               | 70 mW         | 88 mW              | 106 mW           | 123 mW        |  |  |  |
| 835       | 17 mW                               | 30 mW         | 42 mW              | 55 mW            | 67 mW         |  |  |  |
| 1900      | 7 mW                                | 10 mW         | 18 mW              | 34 mW            | 60 mW         |  |  |  |
| 2450      | 2450 4 mW<br>3500 2 mW<br>5800 1 mW |               | 15 mW              | $30~\mathrm{mW}$ | 52 mW         |  |  |  |
| 3500      |                                     |               | 16 mW              | 32 mW            | 55 mW         |  |  |  |
| 5800      |                                     |               | 6 mW 15 mW         |                  | 41 mW         |  |  |  |
| Frequency |                                     | Exe           | nption Limits (mW) |                  |               |  |  |  |
| (MHz)     | At separation                       | At separation | At separation      | At separation    | At separation |  |  |  |
|           | distance of                         | distance of   | distance of        | distance of      | distance of   |  |  |  |
|           | 30 mm                               | 35 mm         | 40 mm              | 45 mm            | ≥50 mm        |  |  |  |
| ≤300      | 223 mW                              | 254 mW        | $284~\mathrm{mW}$  | 315  mW          | 345 mW        |  |  |  |
| 450       | 141 mW                              | 159 mW        | 177 mW             | 195 mW           | 213 mW        |  |  |  |
| 835       | 80 mW                               | 92 mW         | 105 mW             | 117 mW           | 130 mW        |  |  |  |
| 1900      | 99 mW                               | 153 mW        | 225 mW             | 316 mW           | 431 mW        |  |  |  |
| 2450      | 2450 83 mW 123 mW                   |               | 173 mW             | 235 mW           | 309 mW        |  |  |  |
| 3500      | 86 mW 124 mW                        |               | 170 mW             | 225 mW           | 290 mW        |  |  |  |
| 5800      | 56 mW 71 mW                         |               | 85 mW              | 97 mW            | 106 mW        |  |  |  |

<sup>4</sup> The exemption limits in Table 1 are based on measurements and simulations of half-wave dipole antennas at separation distances of 5 mm to 25 mm from a flat phantom, providing a SAR value of approximately 0.4 W/kg for 1 g of tissue. For low frequencies (300 MHz to 835 MHz), the exemption limits are derived from a linear fit. For high frequencies (1900 MHz and above), the exemption limits are derived from a third order polynomial fit.

<sup>5</sup> Transmitters operating between 0.003-10 MHz, meeting the exemption from routine SAR evaluation, shall

Page 8 of 10 Report No.: 190505003RFC-2

demonstrate compliance to the instantaneous limits in Section 4.

#### 3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

#### 3.3 MPE CALCULATION RESULTS

**Note:** For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

#### 3.3.1 For BT

For BT\_BR & EDR function, operating at 2402MHz to 2480 MHz for GFSK,  $\pi/4$  DQPSK, 8DPSK

#### 3.3.1.1 Antenna Type:


Chain 0: LDS antenna

#### 3.3.1.2 Antenna Gain:

Chain 0: 2402MHz to 2480 MHz: 1.11 dBi

#### 3.3.1.3 Minimum contact distance:

The following is the product antenna location.



The minimum contact distance is more than 10 mm. So, the 10 mm separation distance applies.



#### 3.3.1.4 Results for FCC 47 CFR Part 2.1093

| Operating Mode | Frequency | Tune-up<br>Power<br>(Average) | Tolerance | Maximum Tune-up<br>Power |        | Separation<br>Distance | SAR Test<br>Exclusion<br>Threshold |
|----------------|-----------|-------------------------------|-----------|--------------------------|--------|------------------------|------------------------------------|
|                | (MHz)     | (dBm)                         | (dBm)     | (dBm)                    | (mW)   | (mm)                   | (mW)                               |
| EDR            | 2402-2480 | 5.5                           | 2         | 7.5                      | 5.6234 | 10                     | 19                                 |

Report No.: 190505003RFC-2

So the transmitter complies with the RF exposure requirements and the SAR is not required.

### 3.3.1.5 Results for RSS-102 Issue 5

| Operating Mode | Frequency | Tune-up<br>Power<br>(Average) | Tolerance | Maximum Tune-up<br>Power |        | Separation<br>Distance | SAR Test<br>Exclusion<br>Threshold |
|----------------|-----------|-------------------------------|-----------|--------------------------|--------|------------------------|------------------------------------|
|                | (MHz)     | (dBm)                         | (dBm)     | (dBm)                    | (mW)   | (mm)                   | (mW)                               |
| EDR            | 2402-2480 | 5.5                           | 2         | 7.5                      | 5.6234 | 10                     | 7                                  |

So the transmitter complies with the RF exposure requirements and the SAR is not required.




Page 10 of 10

## **APPENDIX 1 PHOTOS OF TEST SETUP**

N/A

Report No.: 190505003RFC-2

### **APPENDIX 1 PHOTOS OF EUT CONSTRUCTIONAL DETAILS**



The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.