



FCC RADIO TEST REPORT

Report Reference No. : NTEK-2011NT1219844E

Compiled by (+ signature) : Tom Zhang



Approved by (+ signature) : Bovey Yang



Applicant's name : Shenzhen Ployer Electronics Co.,Ltd

Address..... : 6F, Building 8, Yusheng Industrial Park, Gushu, Xixiang Town, Baoan District, Shenzhen, China

Manufacture's Name : Shenzhen Ployer Electronics Co.,Ltd

Address..... : 6F, Building 8, Yusheng Industrial Park, Gushu, Xixiang Town, Baoan District, Shenzhen, China

Test specification:

Standard : FCC Part15.247

Test procedure : ANSI C63.4-2003

Test item description

Product name : Tablet PC

FCC ID : Z9UCM008

Trademark : N/A

Model and/or type reference : MOMO15, CM008, MOMO15N

Rating(s) : DC 5V, 2A

Testing Laboratory information:

Testing Laboratory Name : NTEK Testing Technology Co., Ltd

Address : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao ' an District, Shenzhen P.R. China.

This device described above has been tested by NTEK Testing Technology Co., Ltd, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd, this document may be altered or revised by NTEK Testing Technology Co., Ltd, personal only, and shall be noted in the revision of the document

Testing :

Date of receipt of test item : 15 Dec. 2011

Date (s) of performance of tests : 15 Dec. 2011 ~28 Dec. 2011

Date of Issue : 28 Dec. 2011

Test Result..... : **Pass**

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.1.2 TEST PROCEDURE	13
3.1.3 DEVIATION FROM TEST STANDARD	13
3.1.4 TEST SETUP	13
3.1.5 EUT OPERATING CONDITIONS	13
3.1.6 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	17
3.2.4 TEST SETUP	18
3.2.5 EUT OPERATING CONDITIONS	19
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	20
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	21
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	23
3.2.9 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	47
4 . POWER SPECTRAL DENSITY TEST	63
4.1 APPLIED PROCEDURES / LIMIT	63
4.1.1 TEST PROCEDURE	63
4.1.2 DEVIATION FROM STANDARD	63
4.1.3 TEST SETUP	63
4.1.4 EUT OPERATION CONDITIONS	63
4.1.5 TEST RESULTS	64
5 . BANDWIDTH TEST	72
5.1 APPLIED PROCEDURES / LIMIT	72

Table of Contents	
	Page
5.1.1 TEST PROCEDURE	72
5.1.2 DEVIATION FROM STANDARD	72
5.1.3 TEST SETUP	72
5.1.4 EUT OPERATION CONDITIONS	72
5.1.5 TEST RESULTS	73
6 . PEAK OUTPUT POWER TEST	81
6.1 APPLIED PROCEDURES / LIMIT	81
6.1.1 TEST PROCEDURE	81
6.1.2 DEVIATION FROM STANDARD	81
6.1.3 TEST SETUP	81
6.1.4 EUT OPERATION CONDITIONS	81
6.1.5 TEST RESULTS	82
7 . EUT TEST PHOTO	83
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC FRN Registration Nombre:238937; IC Registration Nombre:9270A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	Radiated Emission Test	$\pm 3.17\text{dB}$
3	RF power,conducted	$\pm 0.16\text{dB}$
4	Spurious emissions,conducted	$\pm 0.21\text{dB}$
5	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
6	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet PC	
Trade Name	N/A	
Model Name	MOMO15, CM008, MOMO15N	
OEM Brand/Model Name	N/A	
Model Difference	All the model are identical except the model name.	
Product Description	The EUT is a Tablet PC	
	Operation Frequency:	2412~2462 MHz
	Modulation Type:	CCK, DQPSK, DBPSK, OFDM
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n(20M):54/48/36/24/18/12/9/6 Mbps 802.11n(40M): /150/120/108/90 Mbps
	Number Of Channel	11 CH, Please see Note 2.
	Antenna Designation:	Please see Note 3.
	Antenna Gain(Peak)	Please see Note 3.
	Output Power(Conducted):	802.11b: 10.32 dBm (Max.) 802.11g: 10.66 dBm (Max.) 802.11n(20M): 10.79 dBm (Max.) 802.11n(40M): 9.97 dBm (Max.)
	Antenna Gain (dBi)	1
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Power Source	DC Voltage supplied from Adapter	
Power Rating	DC 5V, 2A	
Connecting I/O Port(s)	Please refer to the User's Manual	
Products Covered	N/A	

Note

:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Printed Antenna	NA	1	N/A

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n(20M) CH1/ CH6/ CH11
Mode 4	802.11n(40M) CH3/ CH6/ CH9
Mode 5	NORMAL LINK


For Conducted Emission	
Final Test Mode	Description
Mode 5	NORMAL LINK

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n(20M) CH1/ CH6/ CH11
Mode 4	802.11n(40M) CH3/ CH6/ CH9

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Tablet PC	N/A	MOMO15	N/A	EUT
E-2	Earphone	N/A	ABD567	3490754	
E-3	Adapter	N/A	HNC050200C	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	80cm	
C2	NO	NO	120cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2012
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2012
3	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06. 2012
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2012
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2012
6	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2012
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2012
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2012
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2012
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2012

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2012
2	LISN	R&S	ENV216	101313	Jul. 06. 2012
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2012
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2012
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2012
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2012

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	Tablet PC	Model Name. :	MOMO15
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2011-12-17
Test Mode :	NORMAL LINK	Phase :	L
Test Voltage :	DC 5V from adapter AC 120V/60Hz		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.878	28	10.41	38.41	46	-7.59	AVG
0.9379	35.89	10.41	46.3	56	-9.7	QP
2.2259	40.25	10.42	50.67	56	-5.33	QP
3.438	34.22	10.6	44.82	56	-11.18	QP
3.5539	26.44	10.61	37.05	46	-8.95	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. "*" means the worst case
4. N/A means All Data have pass Limit




EUT :	Tablet PC	Model Name. :	MOMO15
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2011-12-17
Test Mode :	NORMAL LINK	Phase :	N
Test Voltage :	DC 5V from adapter AC 120V/60Hz		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.466	29.76	10.41	40.17	46.58	-6.41	AVG
1.286	36.44	10.45	46.89	56	-9.11	QP
1.346	29.54	10.45	39.99	46	-6.01	AVG
2.222	39.98	10.44	50.42	56	-5.58	QP
3.154	30.56	10.45	41.01	46	-4.99	AVG
3.622	35.85	10.64	46.49	56	-9.51	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. '*' means the worst case
4. N/A means All Data have pass Limit



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT :	Tablet PC	Model Name. :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
34.6385	20.29	15.85	36.14	40	-3.86	QP
119.8556	20.27	11.77	32.04	43.5	-11.46	QP
721.7259	17.04	23.14	40.18	46	-5.82	QP
34.6385	20.29	15.85	36.14	40	-3.86	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
34.1561	8.05	16.11	24.16	40	-15.84	QP
82.9385	15.21	8.29	23.5	40	-16.5	QP
324.4561	6.32	14.83	21.15	47	-25.85	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH1 (802.11b Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	66.38	-8.12	58.26	74	-15.74	peak
4824	49.31	-8.12	41.19	54	-12.81	AVG
7239	62.14	-7.47	54.67	74	-19.33	peak
7239	47.75	-7.47	40.28	54	-13.72	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH1 (802.11b Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	67.99	-8.12	59.87	74	-14.13	peak
4824	53.8	-8.12	45.68	54	-8.32	AVG
7239	62.01	-7.47	54.54	74	-19.46	peak
7239	51.44	-7.47	43.97	54	-10.03	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 (802.11b Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	68.85	-8.19	60.66	74	-13.34	peak
4874	55.67	-8.19	47.48	54	-6.52	AVG
7311	58.43	-7.21	51.22	74	-22.78	peak
7311	49.62	-7.21	42.41	54	-11.59	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 (802.11b Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	62.51	-8.19	54.32	74	-19.68	peak
4874	51.52	-8.19	43.33	54	-10.67	AVG
7311	57.39	-7.21	50.18	74	-23.82	peak
7311	49.99	-7.21	42.78	54	-11.22	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH11 (802.11b Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	60.58	-8.22	52.36	74	-21.64	peak
4924	51	-8.22	42.78	54	-11.22	AVG
7386	60.57	-7.39	53.18	74	-20.82	peak
7386	48.36	-7.39	40.97	54	-13.03	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH11 (802.11b Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924	60.58	-8.22	52.36	74	-21.64	peak
4924	48.6	-8.22	40.38	54	-13.62	AVG
7386	56.88	-7.39	49.49	74	-24.51	peak
7386	47.57	-7.39	40.18	54	-13.82	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH1 (802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4824	68.76	-8.12	60.64	74	-13.36	peak
4824	58.3	-8.12	50.18	54	-3.82	AVG
7239	63.44	-7.47	55.97	74	-18.03	peak
7239	49.95	-7.47	42.48	54	-11.52	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH1 (802.11g Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4824	64.6	-8.12	56.48	74	-17.52	peak
4824	53.67	-8.12	45.55	54	-8.45	AVG
7239	57.61	-7.47	50.14	74	-23.86	peak
7239	50.89	-7.47	43.42	54	-10.58	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 (802.11g Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	67.55	-8.19	59.36	74	-14.64	peak
4874	55.83	-8.19	47.64	54	-6.36	AVG
7311	61.83	-7.21	54.62	74	-19.38	peak
7311	50.43	-7.21	43.22	54	-10.78	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 (802.11g Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874	59.37	-8.19	51.18	74	-22.82	peak
4874	48.54	-8.19	40.35	54	-13.65	AVG
7311	59.54	-7.21	52.33	74	-21.67	peak
7311	48.39	-7.21	41.18	54	-12.82	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH11 (802.11g Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	61.2	-8.22	52.98	74	-21.02	peak
4924	51.51	-8.22	43.29	54	-10.71	AVG
7386	57.57	-7.39	50.18	74	-23.82	peak
7386	47.76	-7.39	40.37	54	-13.63	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH11(802.11g Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924	61.51	-8.22	53.29	74	-20.71	peak
4924	50.9	-8.22	42.68	54	-11.32	AVG
7386	58.55	-7.39	51.16	74	-22.84	peak
7386	46.77	-7.39	39.38	54	-14.62	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH1 802.11n(20M)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	66.69	-8.12	58.57	74	-15.43	peak
4824	53.29	-8.12	45.17	54	-8.83	AVG
7239	59.14	-7.47	51.67	74	-22.33	peak
7239	53.83	-7.47	46.36	54	-7.64	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH1 802.11n(20M)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	62.71	-8.12	54.59	74	-19.41	peak
4824	54.47	-8.12	46.35	54	-7.65	AVG
7239	60.03	-7.47	52.56	74	-21.44	peak
7239	51.84	-7.47	44.37	54	-9.63	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 802.11n(20M)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	62.5	-8.19	54.31	74	-19.69	peak
4874	53.54	-8.19	45.35	54	-8.65	AVG
7311	59.52	-7.21	52.31	74	-21.69	peak
7311	48.39	-7.21	41.18	54	-12.82	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 802.11n(20M)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	67.45	-8.19	59.26	74	-14.74	peak
4874	56.85	-8.19	48.66	54	-5.34	AVG
7311	62.4	-7.21	55.19	74	-18.81	peak
7311	53.69	-7.21	46.48	54	-7.52	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH11 802.11n(20M)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	63.29	-8.22	55.07	74	-18.93	peak
4924	53.77	-8.22	45.55	54	-8.45	AVG
7386	60.97	-7.39	53.58	74	-20.42	peak
7386	51.33	-7.39	43.94	54	-10.06	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH11 802.11n(20M)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	64.44	-8.22	56.22	74	-17.78	peak
4924	53.32	-8.22	45.1	54	-8.9	AVG
7386	60.21	-7.39	52.82	74	-21.18	peak
7386	51.12	-7.39	43.73	54	-10.27	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH3 802.11n(40M)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4844	63.71	-8.07	55.64	74	-18.36	peak
4844	50.72	-8.07	42.65	54	-11.35	AVG
7266	61.67	-7.4	54.27	74	-19.73	peak
7266	48.76	-7.4	41.36	54	-12.64	AVG

Remark:

5. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

6. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH3 802.11n(40M)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4844	64.21	-8.07	56.14	74	-17.86	peak
4844	55.18	-8.07	47.11	54	-6.89	AVG
7266	62.07	-7.4	54.67	74	-19.33	peak
7266	53.75	-7.4	46.35	54	-7.65	AVG

Remark:

5. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
6. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 802.11n(40M)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	69.99	-8.19	61.8	74	-12.2	peak
4874	53.87	-8.19	45.68	54	-8.32	AVG
7311	66.41	-7.21	59.2	74	-14.8	peak
7311	51.51	-7.21	44.3	54	-9.7	AVG

Remark:

5. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

6. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH6 802.11n(40M)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	70.14	-8.19	61.95	74	-12.05	peak
4874	53.22	-8.19	45.03	54	-8.97	AVG
7311	66.44	-7.21	59.23	74	-14.77	peak
7311	51.48	-7.21	44.27	54	-9.73	AVG

Remark:

5. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

6. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH9 802.11n(40M)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4904	67.45	-8.31	59.14	74	-14.86	peak
4904	50.34	-8.31	42.03	54	-11.97	AVG
7356	63.24	-7.24	56	74	-18	peak
7356	51.09	-7.24	43.85	54	-10.15	AVG

Remark:

7. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

8. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	CH9 802.11n(40M)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4904	67.88	-8.31	59.57	74	-14.43	peak
4904	51.22	-8.31	42.91	54	-11.09	AVG
7356	62.58	-7.24	55.34	74	-18.66	peak
7356	52.47	-7.24	45.23	54	-8.77	AVG

Remark:

7. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

8. No emission detected above 18GHz



3.2.9 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11b CH1		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2397.03	81.52	-17.48	64.04	74	-9.96	peak
2397.03	66.23	-17.48	48.75	54	-5.25	AVG
2399.37	64.72	-17.46	47.26	54	-6.74	AVG
2399.5	79.5	-17.46	62.04	74	-11.96	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11b CH1		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2397.03	82.75	-17.48	65.27	74	-8.73	peak
2397.03	63.17	-17.48	45.69	54	-8.31	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11b CH11		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	79.26	-17.35	61.91	74	-12.09	peak
2483.5	64.12	-17.35	46.77	54	-7.23	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11b CH11		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	80.47	-17.35	63.12	74	-10.88	peak
2483.5	62.01	-17.35	44.66	54	-9.34	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11g CH1		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2397.03	87.23	-17.48	69.75	74	-4.25	
2397.03	63.16	-17.48	45.68	54	-8.32	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11g CH1		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2398.2	87.67	-17.47	70.2	74	-3.8	peak
2398.2	65.63	-17.47	48.16	54	-5.84	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11g CH11		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2481.75	67.51	-17.35	50.16	54	-3.84	
2482.075	84.62	-17.35	67.27	74	-6.73	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11g CH11		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2481.425	85.99	-17.35	68.64	74	-5.36	peak
2481.425	66.54	-17.35	49.19	54	-4.81	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11n CH1		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2399.61	85.08	-17.46	67.62	74	-6.38	peak
2399.61	63.24	-17.46	45.78	54	-8.22	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11n CH1		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2399.2	64.62	-17.46	47.16	54	-6.84	AVG
2399.61	84.89	-17.46	67.43	74	-6.57	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11n CH11		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2482.725	89.3	-17.35	71.95	74	-2.05	peak
2482.725	70.04	-17.35	52.69	54	-1.31	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11n CH11		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2484.35	58.54	-17.35	41.19	54	-12.81	AVG
2484.675	77.81	-17.35	60.46	74	-13.54	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11n(40M) CH3		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2401	84.81	-17.46	67.35	74	-6.65	peak
2401	60.15	-17.46	42.69	54	-11.31	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11n(40M) CH3		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2401	84.62	-17.46	67.16	74	-6.84	peak
2401	58.64	-17.46	41.18	54	-12.82	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	11n(40M) CH9		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2484.025	84.49	-17.35	67.14	74	-6.86	peak
2484.025	67.03	-17.35	49.68	54	-4.32	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Polarization :	Vertical
	DC 5V		
Test Mode :	11n(40M) CH9		
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.		


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2484.675	77.65	-17.35	60.3	74	-13.7	peak
2484.675	66.04	-17.35	48.69	54	-5.31	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode

During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	500 s
Span Frequency	> Operating Frequency Range
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500 s

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 3KHz, VBW=30KHz, Sweep time = 500 s.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-19.22	8	PASS
2437 MHz	-18.17	8	PASS
2462 MHz	-18.17	8	PASS







EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-23.35	8	PASS
2437MHz	-21.28	8	PASS
2462 MHz	-21.15	8	PASS







EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX n(20m) Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-29.14	8	PASS
2437MHz	-24.97	8	PASS
2462 MHz	-23.76	8	PASS







EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX n(40m) Mode /CH03, CH06, CH9		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-21.15	8	PASS
2437 MHz	-25.51	8	
2452MHz	-27.19	8	PASS





5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	10.08	14.56	>=500KHz	PASS
2437 MHz	10.08	14.65	>=500KHz	PASS
2462 MHz	10.11	14.68	>=500KHz	PASS






Trace/View
Trace 1 2 3
Clear Write
Max Hold
Min Hold
View
Blank
More 1 of 2

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	16.66	16.52	>=500KHz	PASS
2437 MHz	16.61	16.50	>=500KHz	PASS
2462 MHz	16.63	16.48	>=500KHz	PASS







EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX n(20M) Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	17.86	17.70	>=500KHz	PASS
2437 MHz	17.87	17.71	>=500KHz	PASS
2462 MHz	17.85	17.69	>=500KHz	PASS







EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX n(40M) Mode /CH03, CH06, CH9		

Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2422 MHz	36.54	35.99	>=500KHz	PASS
2437 MHz	36.53	35.98	>=500KHz	PASS
2452 MHz	36.55	35.99	>=500KHz	PASS





6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Test Channel	Frequency (MHz)	output power (dBm)	LIMIT (dBm)	LIMIT (W)
CH01	2412	10.32	30	1
CH06	2437	10.29	30	1
CH11	2462	10.18	30	1

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX g Mode /CH01, CH06, CH11		

Test Channel	Frequency (MHz)	output power (dBm)	LIMIT (dBm)	LIMIT (W)
CH01	2412	10.59	30	1
CH06	2437	10.48	30	1
CH11	2462	10.66	30	1

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX n(20M) Mode /CH01, CH06, CH11		


Test Channel	Frequency (MHz)	output power (dBm)	LIMIT (dBm)	LIMIT (W)
CH01	2412	10.48	30	1
CH06	2437	10.79	30	1
CH11	2462	10.69	30	1

EUT :	Tablet PC	Model Name :	MOMO15
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX n(40M) Mode /CH03, CH06, CH9		

Test Channel	Frequency (MHz)	output power (dBm)	LIMIT (dBm)	LIMIT (W)
CH03	2422	9.97	30	1
CH06	2437	9.38	30	1
CH09	2452	9.29	30	1

7. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos

