

FCC REPORT

Applicant: Shenzhen Banngo Technology Co., Ltd.

Address of Applicant: B Building, Huafeng Industrial (Gongle) Xixiang, Baoan District, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Bluetooth Dog

Model No.: BA11-W, BA11-B, BA11-WB, BA11-BW

FCC ID: ZBB-BANNGO2011BC3

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249:2009

Date of sample receipt: 23 Feb., 2011

Date of Test: 24 Feb., 2011

Date of report issued: 25 Feb., 2011

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature in black ink, appearing to read 'Robinson Lo', with a stylized flourish at the end.

ROBINSON LO
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 TEST SUMMARY	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF E.U.T.	4
4.3 TEST ENVIRONMENT AND MODE.....	6
4.4 TEST FACILITY.....	6
4.5 TEST LOCATION	6
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4.7 TEST INSTRUMENTS LIST:	7
5 TEST RESULTS AND MEASUREMENT DATA.....	8
5.1 ANTENNA REQUIREMENT:	8
5.2 CONDUCTED EMISSIONS.....	9
5.3 RADIATED EMISSION.....	12
5.3.1 <i>Field Strength Of The Fundamental Signal</i>	14
5.3.2 <i>Spurious Emissions</i>	14
5.3.3 <i>Band edge (Radiated Emission)</i>	18
5.4 20dB BANDWIDTH.....	20

3 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	PASS
AC Power Line Conducted Emission	15.207	PASS
Field strength of the fundamental signal	15.249 (a)	PASS
Spurious emissions	15.249 (a) (d)/15.209	PASS
Band edge (Radiated Emission)	15.249 (d)/15.205	PASS
20dB Occupied Bandwidth	15.215 (c)	PASS

Remark:

- *Pass: The EUT complies with the essential requirements in the standard.*
- *Fail: The EUT does not comply with the essential requirements in the standard.*
- *Tx: In this whole report Tx (or tx) means Transmitter.*
- *Rx: In this whole report Rx (or rx) means Receiver.*

4 General Information

4.1 Client Information

Applicant:	Shenzhen Banngo Technology Co., Ltd.
Address of Applicant:	B Building, Huafeng Industrial (Gongle) Xixiang, Baoan District, Shenzhen, China
Manufacturer/ Factory:	Shenzhen Banngo Technology Co., Ltd.
Address of Manufacturer/ Factory:	B Building, Huafeng Industrial (Gongle) Xixiang, Baoan District, Shenzhen, China

4.2 General Description of E.U.T.

Product Name:	Bluetooth Dog
Model No.:	BA11-W, BA11-B, BA11-WB, BA11-BW
Operation Frequency:	2402MHz to 2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK
Antenna Type:	Integral
Antenna gain:	2dBi
Power supply:	DC 3.6V charge Battery
Remark:	Only the model No. BA11-W was tested. BA11-W, BA11-B, BA11-WB and BA11-BW are identical in interior structure, electrical circuits, and components, with different color for the appearance.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

4.3 Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with modulation.

GTS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Operating Environment:

Pre-Test Mode: (lowest channel=2402MHz)			
Axis	X	Y	Z
Field Strength(dBuV/m)	95.24	97.31	93.25
Final Test Mode:			
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”			
Y axis (see the test setup photo)			

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, July 20, 2010.

● **Industry Canada (IC)**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.

4.5 Test Location

All tests were performed at:	
Global United Technology Services Co., Ltd.	
Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China	
Tel: 0755-27798480	Fax:
0755-27798960	

4.6 Other Information Requested by the Customer

None.


4.7 Test Instruments list:

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS201	Mar. 30 2010	Mar. 30 2011
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS202	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Sep. 10 2010	Sep. 10 2011
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS204	Feb. 26 2011	Feb. 26 2012
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS205	June 30 2010	June 30 2011
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Coaxial Cable	GTS	N/A	GTS400	Apr. 01 2010	Apr. 01 2011
8	Coaxial Cable	GTS	N/A	GTS401	Apr. 01 2010	Apr. 01 2011
9	Coaxial cable	GTS	N/A	GTS402	Apr. 01 2010	Apr. 01 2011
10	Coaxial Cable	GTS	N/A	GTS407	Apr. 01 2010	Apr. 01 2011
11	Coaxial Cable	GTS	N/A	GTS408	Apr. 01 2010	Apr. 01 2011
12	Amplifier(10KHz-5GHz)	Sonnoma Instrument	305-1052	GTS210	Aug. 03 2010	Aug. 03 2011
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS231	Aug. 03 2010	Aug. 03 2011

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS206	Apr. 10 2010	Apr. 10 2011
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS208	Sep. 14 2010	Sep. 14 2011
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS209	Sep. 14 2010	Sep. 14 2011
4	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS207	Apr. 14 2010	Apr. 14 2011
5	Coaxial Cable	GTS	N/A	GTS406	Apr. 01 2010	Apr. 01 2011
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

5 Test results and Measurement Data

5.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
The antenna is no consideration of replacement. The best case gain of the antenna is 2dBi.	
	


5.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.4: 2003																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz																
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> <p>* Decreases with the logarithm of the frequency.</p>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
Test procedure	<p>The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.</p>																
Test setup:	<div><p style="text-align: center;">Reference Plane</p><p style="text-align: center;">Test table/Insulation plane</p><p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div>																
Test Instruments:	Refer to section 4.7 for details																
Test mode:	Refer to section 4.3 for details																
Test results:	Passed																

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line:



Condition : FCC QP LISN(2011) LINE
Job No : 087RF
EUT : Bluetooth Dog
Test Mode : Charge mode
Test Engineer: Collin

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.159	33.61	0.68	0.10	34.39	55.52	-21.13	Average
2	0.159	39.81	0.68	0.10	40.59	65.52	-24.93	QP
3	0.227	30.41	0.64	0.10	31.15	52.57	-21.42	Average
4	0.227	37.11	0.64	0.10	37.85	62.57	-24.72	QP
5	0.914	20.21	0.49	0.10	20.80	46.00	-25.20	Average
6	0.914	27.45	0.49	0.10	28.04	56.00	-27.96	QP
7	2.190	23.43	0.39	0.10	23.92	46.00	-22.08	Average
8	2.190	35.84	0.39	0.10	36.33	56.00	-19.67	QP
9	5.623	24.51	0.29	0.11	24.91	50.00	-25.09	Average
10	5.623	34.85	0.29	0.11	35.25	60.00	-24.75	QP
11	14.986	24.52	0.18	0.20	24.90	50.00	-25.10	Average
12	14.986	38.66	0.18	0.20	39.04	60.00	-20.96	QP

Neutral Line:



Condition : FCC QP LISN(2011) NEUTRAL
 Job No : 087RF
 EUT : Bluetooth Dog
 Test Mode : Charge mode
 Test Engineer: Collin



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.168	34.71	0.68	0.10	35.49	55.08	-19.59	Average
2	0.168	41.51	0.68	0.10	42.29	65.08	-22.79	QP
3	0.387	24.01	0.58	0.10	24.69	48.12	-23.43	Average
4	0.387	31.91	0.58	0.10	32.59	58.12	-25.53	QP
5	0.914	21.01	0.49	0.10	21.60	46.00	-24.40	Average
6	0.914	28.93	0.49	0.10	29.52	56.00	-26.48	QP
7	3.509	27.64	0.34	0.10	28.08	46.00	-17.92	Average
8	3.509	35.74	0.34	0.10	36.18	56.00	-19.82	QP
9	5.774	27.32	0.28	0.11	27.71	50.00	-22.29	Average
10	5.774	36.82	0.28	0.11	37.21	60.00	-22.79	QP
11	15.146	28.02	0.18	0.20	28.40	50.00	-21.60	Average
12	15.146	38.74	0.18	0.20	39.12	60.00	-20.88	QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

5.3 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.249 and 15.209																								
Test Method:	ANSI C63.4: 2003																								
Test Frequency Range:	30MHz to 25000MHz																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	Peak	1MHz	10Hz	Average Value																					
Limit: (Field strength of the fundamental signal)	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td rowspan="2">2400MHz-2483.5MHz</td><td>94.0</td><td>Average Value</td></tr><tr><td>114.0</td><td>Peak Value</td></tr></table>					Frequency	Limit (dBuV/m @3m)	Remark	2400MHz-2483.5MHz	94.0	Average Value	114.0	Peak Value												
Frequency	Limit (dBuV/m @3m)	Remark																							
2400MHz-2483.5MHz	94.0	Average Value																							
	114.0	Peak Value																							
Limit: (Spurious Emissions)	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>74.0</td><td>Peak Value</td></tr></table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	74.0	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	74.0	Peak Value																							
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.																								
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values</p>																								

	of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p> 
Test Instruments:	Refer to section 4.7 for details
Test mode:	Refer to section 4.3 for details
Test results:	Passed

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$

Measurement Data
5.3.1 Field Strength Of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	95.97	27.58	3.37	30.10	96.82	114.00	-17.18	Horizontal
2402.00	92.12	27.58	3.37	30.10	92.97	114.00	-21.03	Vertical
2441.00	93.48	27.48	3.43	29.99	94.40	114.00	-19.60	Horizontal
2441.00	90.24	27.48	3.43	29.99	91.16	114.00	-22.84	Vertical
2480.00	96.23	27.52	3.49	29.93	97.31	114.00	-16.69	Horizontal
2480.00	92.32	27.52	3.49	29.93	93.40	114.00	-20.60	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	82.95	27.58	3.37	30.10	83.80	94.00	-10.20	Horizontal
2402.00	79.84	27.58	3.37	30.10	80.69	94.00	-13.31	Vertical
2441.00	80.57	27.48	3.43	29.99	81.49	94.00	-12.51	Horizontal
2441.00	75.61	27.48	3.43	29.99	75.53	94.00	-18.47	Vertical
2480.00	82.58	27.52	3.49	29.93	83.66	94.00	-10.34	Horizontal
2480.00	79.41	27.52	3.49	29.93	80.49	94.00	-13.51	Vertical

5.3.2 Spurious Emissions
30MHz~1GHz

Test mode: Transmitting

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
39.70	0.60	11.30	28.09	40.20	24.01	40.00	-15.99	Vertical
118.27	1.25	8.02	27.70	46.99	28.56	43.50	-14.94	Vertical
129.91	1.28	7.70	27.61	49.29	30.66	43.50	-12.84	Vertical
144.46	1.31	8.53	27.49	46.35	28.70	43.50	-14.80	Vertical
432.55	2.34	16.56	27.52	42.40	33.78	46.00	-12.22	Vertical
78.50	1.05	7.59	28.00	39.12	19.76	40.00	-20.24	Horizontal
118.27	1.25	8.02	27.70	43.50	25.07	43.50	-18.43	Horizontal
129.91	1.28	7.70	27.61	51.67	33.04	43.50	-10.46	Horizontal
144.46	1.31	8.53	27.49	41.60	23.95	43.50	-19.55	Horizontal
710.94	2.94	21.60	27.24	37.50	34.80	46.00	-11.20	Horizontal

Above 1GHz

Test mode:	Transmitting	Test channel:	Lowest	Remark:	Peak
------------	--------------	---------------	--------	---------	------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	35.00	31.78	5.32	24.09	48.29	74.00	-25.71	Vertical
7206.00	32.99	36.15	6.87	26.38	50.09	74.00	-23.91	Vertical
9608.00	30.27	37.95	8.94	25.40	52.40	74.00	-21.60	Vertical
12010.00	27.69	39.08	10.34	25.19	52.74	74.00	-21.26	Vertical
14412.00	24.74	42.41	11.64	24.28	55.51	74.00	-18.49	Vertical
16814.00	25.23	41.78	14.46	25.45	57.20	74.00	-16.80	Vertical
4804.00	36.88	31.78	5.32	24.09	49.89	74.00	-24.11	Horizontal
7206.00	33.77	36.15	6.87	26.38	50.41	74.00	-23.59	Horizontal
9608.00	32.12	37.95	8.94	25.40	53.61	74.00	-20.39	Horizontal
12010.00	29.56	39.08	10.34	25.19	53.79	74.00	-20.21	Horizontal
14412.00	26.51	42.41	11.64	24.28	56.28	74.00	-17.72	Horizontal
16814.00	26.15	41.78	14.46	25.45	56.94	74.00	-17.06	Horizontal

Test mode:	Transmitting	Test channel:	Lowest	Remark:	average
------------	--------------	---------------	--------	---------	---------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	24.23	31.78	5.32	24.09	37.52	54.00	-16.48	Vertical
7206.00	19.65	36.15	6.87	26.38	36.75	54.00	-17.25	Vertical
9608.00	18.00	37.95	8.94	25.40	40.13	54.00	-13.87	Vertical
12010.00	15.26	39.08	10.34	25.19	40.31	54.00	-13.69	Vertical
14412.00	11.54	42.41	11.64	24.28	42.31	54.00	-11.69	Vertical
16814.00	10.37	41.78	14.46	25.45	42.34	54.00	-11.66	Vertical
4804.00	24.03	31.78	5.32	24.09	37.04	54.00	-16.96	Horizontal
7206.00	20.45	36.15	6.87	26.38	37.09	54.00	-16.91	Horizontal
9608.00	16.32	37.95	8.94	25.40	37.81	54.00	-16.19	Horizontal
12010.00	15.89	39.08	10.34	25.19	40.12	54.00	-13.88	Horizontal
14412.00	11.37	42.41	11.64	24.28	41.14	54.00	-12.86	Horizontal
16814.00	11.13	41.78	14.46	25.45	41.92	54.00	-12.08	Horizontal

Test mode:	Transmitting	Test channel:	Middle	Remark:	Peak
------------	--------------	---------------	--------	---------	------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	35.94	31.85	5.40	24.01	49.46	74.00	-24.54	Vertical
7323.00	34.10	36.37	6.91	26.62	51.22	74.00	-22.78	Vertical
9764.00	30.69	38.35	9.01	25.29	53.40	74.00	-20.60	Vertical
12205.00	29.56	38.92	10.39	25.02	54.67	74.00	-19.33	Vertical
14480.00	26.32	42.51	11.71	24.33	57.21	74.00	-16.79	Vertical
17087.00	24.49	44.30	14.54	25.57	58.94	74.00	-15.06	Vertical
4882.00	37.89	31.85	5.40	24.01	51.13	74.00	-22.87	Horizontal
7323.00	32.90	36.37	6.91	26.62	49.56	74.00	-24.44	Horizontal
9764.00	30.95	38.35	9.01	25.29	53.02	74.00	-20.98	Horizontal
12205.00	29.03	38.92	10.39	25.02	53.32	74.00	-20.68	Horizontal
14480.00	27.16	42.51	11.71	24.33	57.05	74.00	-16.95	Horizontal
17087.00	25.13	44.30	14.54	25.57	58.40	74.00	-15.60	Horizontal

Test mode:	Transmitting	Test channel:	Middle	Remark:	average
------------	--------------	---------------	--------	---------	---------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	25.37	31.85	5.40	24.01	38.89	54.00	-15.11	Vertical
7323.00	20.86	36.37	6.91	26.62	37.98	54.00	-16.02	Vertical
9764.00	16.99	38.35	9.01	25.29	39.70	54.00	-14.30	Vertical
12205.00	15.74	38.92	10.39	25.02	40.85	54.00	-13.15	Vertical
14480.00	12.32	42.51	11.71	24.33	43.21	54.00	-10.79	Vertical
17087.00	9.51	44.30	14.54	25.57	43.96	54.00	-10.04	Vertical
4882.00	22.93	31.85	5.40	24.01	36.17	54.00	-17.83	Horizontal
7323.00	20.06	36.37	6.91	26.62	36.72	54.00	-17.28	Horizontal
9764.00	16.63	38.35	9.01	25.29	38.70	54.00	-15.30	Horizontal
12205.00	14.87	38.92	10.39	25.02	39.16	54.00	-14.84	Horizontal
14480.00	12.87	42.51	11.71	24.33	42.76	54.00	-11.24	Horizontal
17087.00	8.80	44.30	14.54	25.57	42.07	54.00	-11.93	Horizontal

Test mode:	Transmitting	Test channel:	Highest	Remark:	Peak
------------	--------------	---------------	---------	---------	------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	35.64	31.93	5.47	23.93	49.39	74.00	-24.61	Vertical
7440.00	33.18	36.59	6.95	26.95	50.23	74.00	-23.77	Vertical
9920.00	31.07	38.81	9.07	25.22	54.37	74.00	-19.63	Vertical
12400.00	30.65	38.76	10.44	24.74	55.93	74.00	-18.07	Vertical
14646.00	25.43	42.21	11.94	24.47	56.11	74.00	-17.89	Vertical
17360.00	23.16	46.19	14.64	25.95	59.22	74.00	-14.78	Vertical
4960.00	38.03	31.93	5.47	23.93	51.50	74.00	-22.50	Horizontal
7440.00	34.11	36.59	6.95	26.95	50.70	74.00	-23.30	Horizontal
9920.00	30.52	38.81	9.07	25.22	53.18	74.00	-20.82	Horizontal
12400.00	30.56	38.76	10.44	24.74	55.02	74.00	-18.98	Horizontal
14646.00	26.78	42.21	11.94	24.47	56.46	74.00	-17.54	Horizontal
17360.00	23.92	46.19	14.64	25.95	58.80	74.00	-15.20	Horizontal

Test mode:	Transmitting	Test channel:	Highest	Remark:	average
------------	--------------	---------------	---------	---------	---------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	23.45	31.93	5.47	23.93	37.20	54.00	-16.80	Vertical
7440.00	20.92	36.59	6.95	26.95	37.97	54.00	-16.03	Vertical
9920.00	15.69	38.81	9.07	25.22	38.99	54.00	-15.01	Vertical
12400.00	13.09	38.76	10.44	24.74	38.37	54.00	-15.63	Vertical
14646.00	9.13	42.21	11.94	24.47	39.81	54.00	-14.19	Vertical
17360.00	8.93	46.19	14.64	25.95	44.99	54.00	-9.01	Vertical
4960.00	22.68	31.93	5.47	23.93	36.15	54.00	-17.85	Horizontal
7440.00	19.46	36.59	6.95	26.95	36.05	54.00	-17.95	Horizontal
9920.00	15.99	38.81	9.07	25.22	38.65	54.00	-15.35	Horizontal
12400.00	14.30	38.76	10.44	24.74	38.76	54.00	-15.24	Horizontal
14646.00	12.47	42.21	11.94	24.47	42.15	54.00	-11.85	Horizontal
17360.00	8.07	46.19	14.64	25.95	42.95	54.00	-11.05	Horizontal

5.3.3 Band edge (Radiated Emission)

Test mode:	Transmitting	Test channel:	Lowest	Remark:	Peak
------------	--------------	---------------	--------	---------	------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	49.70	27.22	3.14	30.76	48.02	74.00	-25.98	Horizontal
2400.00	55.12	27.58	3.37	30.10	54.69	74.00	-19.31	Horizontal
2390.00	48.20	27.22	3.14	30.76	46.52	74.00	-27.48	Vertical
2400.00	51.56	27.58	3.37	30.10	51.13	74.00	-22.87	Vertical

Test mode:	Transmitting	Test channel:	Lowest	Remark:	Average
------------	--------------	---------------	--------	---------	---------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	32.87	27.22	3.14	30.76	31.78	54.00	-22.22	Horizontal
2400.00	36.63	27.58	3.37	30.10	36.79	54.00	-17.21	Horizontal
2390.00	31.06	27.22	3.14	30.76	29.97	54.00	-24.03	Vertical
2400.00	34.83	27.58	3.37	30.10	34.99	54.00	-19.01	Vertical


Test mode:	Transmitting	Test channel:	Highest	Remark:	Peak
------------	--------------	---------------	---------	---------	------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.11	27.53	3.49	29.93	52.20	74.00	-21.80	Horizontal
2500.00	48.59	27.58	3.52	29.98	49.71	74.00	-24.29	Horizontal
2483.50	48.61	27.53	3.49	29.93	49.70	74.00	-24.30	Vertical
2500.00	46.24	27.58	3.52	29.98	47.36	74.00	-26.64	Vertical

Test mode:	Transmitting	Test channel:	Highest	Remark:	Average
------------	--------------	---------------	---------	---------	---------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	31.57	27.53	3.49	29.93	32.66	54.00	-21.34	Horizontal
2500.00	28.75	27.58	3.52	29.98	29.87	54.00	-24.13	Horizontal
2483.50	28.45	27.53	3.49	29.93	29.54	54.00	-24.46	Vertical
2500.00	26.39	27.58	3.52	29.98	27.51	54.00	-26.49	Vertical

5.4 20dB Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.4:2003
Receiver setup:	RBW=10KHz, VBW=30KHz, detector: Peak
Limit:	Operation Frequency range 2400MHz-2483.5MHz
Test Procedure:	<ol style="list-style-type: none"> 1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 4.7 for details
Test mode:	Refer to section 4.3 for details
Test results:	Passed

Measurement Data


Test channel	20dB bandwidth (MHz)	Results
Lowest	1.348	Pass
Middle	1.348	Pass
Highest	1.348	Pass

Test plot as follows:

Test channel:	Lowest	
---------------	--------	--



Test channel:	Middle	
---------------	--------	--



Test channel:	Highest	
---------------	---------	--

