

FCC SAR Test Report

Report No. : SA150508C07

Applicant : CORPORATIVO LANIX, S.A. DE C.V.

Address : CARRETERA INTERNACIONAL A NOGALES KM.8.5, SAN LUIS. HERMOSILLO, SONORA, MÉXICO. CP. 83160

Product : ILIUM PAD L8

FCC ID : ZC4L8

Brand : LANIX

Model No. : ILIUM PAD L8

Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2003
IEEE 1528a-2005 / KDB 865664 D01 v01r03 / KDB 865664 D02 v01r01
KDB 248227 D01 v02r01 / KDB 447498 D01 v05r02 / KDB 616217 D04 v01r01
KDB 941225 D01 v03 / KDB 941225 D05 v02r03

Sample Received Date : May 08, 2015

Date of Testing : May 20, 2015 ~ Jun. 01, 2015

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., China Branch - Dongguan Lab**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :



Ivonne Wu / Supervisor

Approved By :



Gordon Lin / Assistant Manager



No: 2951.01

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

FCC SAR Test Report

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	6
3.1 Definition of Specific Absorption Rate (SAR)	6
3.2 SPEAG DASY System	6
3.2.1 Robot.....	7
3.2.2 Probes.....	8
3.2.3 Data Acquisition Electronics (DAE)	8
3.2.4 Phantoms	9
3.2.5 Device Holder.....	9
3.2.6 System Validation Dipoles.....	10
3.2.7 Tissue Simulating Liquids.....	10
3.3 SAR System Verification	13
3.4 SAR Measurement Procedure	14
3.4.1 Area & Zoom Scan Procedure	14
3.4.2 Volume Scan Procedure.....	14
3.4.3 Power Drift Monitoring.....	15
3.4.4 Spatial Peak SAR Evaluation	15
3.4.5 SAR Averaged Methods	15
4. SAR Measurement Evaluation	16
4.1 EUT Configuration and Setting.....	16
4.2 EUT Testing Position	18
4.3 Tissue Verification	22
4.4 System Validation.....	22
4.5 System Verification.....	23
4.6 Maximum Output Power.....	23
4.6.1 Maximum Conducted Power	23
4.6.2 Measured Conducted Power Result.....	24
4.7 SAR Testing Results	29
4.7.1 SAR Results for Head	29
4.7.2 SAR Results for Body-Worn (Separation Distance is 0 cm Gap)	31
4.7.3 SAR Measurement Variability.....	33
4.7.4 Simultaneous Multi-band Transmission Evaluation	34
5. Calibration of Test Equipment.....	39
6. Measurement Uncertainty	40
7. Information on the Testing Laboratories.....	42
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate for Probe and Dipole	
Appendix D. Photographs of EUT and Setup	



Release Control Record

Report No.	Reason for Change	Date Issued
SA150508C07	Initial release	Jun. 10, 2015

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR _{1g} (W/kg)	Highest Reported Body SAR _{1g} (0 cm Gap) (W/kg)
PCE	GSM850	0.00	0.94
	GSM1900	0.02	0.47
	WCDMA II	0.03	0.38
	WCDMA V	0.00	0.22
	LTE 2	0.06	0.32
	LTE 4	0.01	0.09
	LTE 7	0.02	0.40
DTS	2.4G WLAN	N/A	N/A
DSS	Bluetooth	N/A	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body (W/kg)
PCE+DTS		0.45	1.33
PCE+DSS		N/A	1.27

Note:

- The SAR limit (**Head & Body: SAR_{1g} 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

2. Description of Equipment Under Test

EUT Type	ILIUM PAD L8
FCC ID	ZC4L8
Brand Name	LANIX
Model Name	ILIUM PAD L8
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 GSM1900 : 1850.2 ~ 1909.8 WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) WLAN : 2412 ~ 2462 Bluetooth : 2402 ~ 2480
Uplink Modulations	GSM & GPRS : GMSK EDGE : 8PSK WCDMA : QPSK LTE : QPSK, 16QAM 802.11b : DSSS 802.11g/n : OFDM Bluetooth : GFSK
Maximum Tune-up Conducted Power (Unit: dBm)	GSM850 : 34.0 GSM1900 : 31.0 WCDMA Band II : 23.5 WCDMA Band V : 23.5 LTE Band 2 : 24.0 LTE Band 4 : 24.0 LTE Band 7 : 23.0 WLAN 2.4G : 9.7 Bluetooth : 9.0
Antenna Type	Fixed Internal Antenna
EUT Stage	Identical Prototype

Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

List of Accessory:

Battery	Brand Name	TCL
	Model Name	PR-3493106N
	Power Rating	3.7Vdc, 3800mAh
	Type	Li-ion

FCC SAR Test Report

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

FCC SAR Test Report




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)





Fig-3.2 DASY5

FCC SAR Test Report


3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	


Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	


3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	


FCC SAR Test Report

3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	


Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


FCC SAR Test Report

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

FCC SAR Test Report

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

The following table gives the recipes for tissue simulating liquids.


Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

FCC SAR Test Report

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

FCC SAR Test Report

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

FCC SAR Test Report

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

The EUT is a voice/data transmitter device that contains one WWAN transmitter. Confirming the LTE transmitter follows 3GPP standards, is category 3, FDD-LTE band 2 (BW 1.4/3/5/10/15/20 MHz), FDD-LTE band 4 (BW 1.4/3/5/10/15/20 MHz), FDD-LTE band 7 (BW 5/10/15/20 MHz), and supports QPSK / 16QAM modulations. Tested per 3GPP 36.521 maximum transmit procedures for both QPSK / 16QAM.

LTE Maximum Power Reduction in accordance with 3GPP 36.101: Power Reduction in accordance to 3GPP is active all times during LTE operation.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with A-MPR requirements defined in 36.101 section 6.2.4 that may be required to meet 3GPP Adjacent Channel Leakage Ratio ("ACLR") requirements. A-MPR was disabled for all FCC compliance testing.

The simultaneous transmission possibilities are listed as below.

Simultaneous TX Combination	Configuration	Head (Voice / VoIP)	Body Worn (Voice / VoIP)
1	GSM850 (Voice / Data) + WLAN (Data)	Yes	Yes
2	GSM1900 (Voice / Data) + WLAN (Data)	Yes	Yes
3	WCDMA II (Voice / Data) + WLAN (Data)	Yes	Yes
4	WCDMA V (Voice / Data) + WLAN (Data)	Yes	Yes
5	LTE 2 (Data) + WLAN (Data)	Yes	Yes
6	LTE 4 (Data) + WLAN (Data)	Yes	Yes
7	LTE 7 (Data) + WLAN (Data)	Yes	Yes
8	GSM850 (Voice / Data) + BT (Data)	No	Yes
9	GSM1900 (Voice / Data) + BT (Data)	No	Yes
10	WCDMA II (Voice / Data) + BT (Data)	No	Yes
11	WCDMA V (Voice / Data) + BT (Data)	No	Yes
12	LTE 2 (Data) + BT (Data)	No	Yes
13	LTE 4 (Data) + BT (Data)	No	Yes
14	LTE 7 (Data) + BT (Data)	No	Yes

Note :

1. The WLAN and BT cannot transmit simultaneously, so there is no co-location test requirement for WLAN and BT.

FCC SAR Test Report

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

For GSM850, the power control level is set to 5. For GPRS850 (GMSK, CS1), the power control level is set to 5. For EDGE850 (GMSK: MCS1, 8PSK:MCS9), the power control level is set to 8. For GSM1900, the power control level is set to 0. For GPRS1900 (GMSK, CS1), the power control level is set to 0. For EDGE1900 (GMSK: MCS1, 8PSK:MCS9), the power control level is set to 2.

For WCDMA, head and body SAR is tested under 12.2k RMC mode with power control set all up bits. SAR for AMR is not required since its power is less than 1/4 dB higher than RMC. SAR for HSDPA/HSUPA is not required since its power is less than 1/4 dB higher than RMC without HSDPA/HSUPA and SAR for 12.2 kbps RMC is less than 75% of the SAR limit (1.2 W/kg).

For LTE, set the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB in base station simulator. When the EUT has registered and communicated to base station simulator, set the simulator to make EUT transmitting the maximum radiated power. The steps for system simulator (Anritsu MT8820C) setup are as below.

1. Press the "Std" button to select "LTE 22.20S" function
2. Choose the "Screen Select" item to "Fundamental Measurement"
3. Enter the "Common" item
4. Set the Operating Band
5. Set the Channel Bandwidth
6. Set the UL Channel & Frequency
7. Set the Modulation
8. Set the RB number and RB shift
9. Press "Start Call" button when EUT register to the system simulator
10. Set the TX-1 Max. Power to make the EUT transmit maximum output power

For WLAN SAR testing, the EUT has installed WLAN engineering testing software which can provide continuous transmitting RF signal. According to KDB 248227 D01, WLAN SAR for this device was performed at the lowest data rate.

FCC SAR Test Report

4.2 EUT Testing Position

Since this tablet has receiver and it can be used in close proximity to the ear as handset. According to technical standards, this tablet is tested for SAR compliance in head described in the following subsections.

4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2003 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
 - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
 - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
 - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

FCC SAR Test Report

2. Cheek Position

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

3. Tilted Position

- To position the device in the "cheek" position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).




Fig-4.3 Illustration for Tilted Position

FCC SAR Test Report

According to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.




Fig-4.4 Illustration for Tablet Setup

FCC SAR Test Report

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

- For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

- For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Top Side			Bottom Side			Left Side			Right Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
GSM 850	30.0	1000	5	184.3	Yes	182	910	YES	5	184.3	Yes	5	184.3	Yes	40	23	Yes
GSM 1900	27.5	562	5	155.3	Yes	182	1429 Mw	No	5	155.3	Yes	5	155.3	Yes	40	19.4	Yes
WCDMA II	23.5	224	5	61.9	Yes	182	1429 mw	No	5	61.9	Yes	5	61.9	Yes	40	7.7	Yes
WCDMA V	23.5	224	5	41.2	Yes	182	908 mw	No	5	41.2	Yes	5	41.2	Yes	40	5.2	Yes
LTE 2	24.0	251	5	69.3	Yes	182	1429 mw	No	5	69.3	Yes	5	69.3	Yes	40	8.7	Yes
LTE 4	24.0	251	5	66.5	Yes	182	1433 mw	No	5	66.5	Yes	5	66.5	Yes	40	8.3	Yes
LTE 7	23.0	200	5	64.1	Yes	182	1416 mw	No	5	64.1	Yes	5	64.1	Yes	40	7.8	Yes
WLAN 2.4G	9.7	9	5	2.8	No	186	1456 mw	No	5	2.8	No	82	416 mw	No	5	2.8	No
BT	9.0	8	5	2.5	No	186	1455 mw	No	5	2.5	No	82	415 mw	No	5	2.5	No

Note:

- When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 , the SAR testing exclusion is applied.
- When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.
- Since GSM has multi-slot operation, the maximum tune-up power shown in above table for GSM is source-based time-averaged maximum power.

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
May 27, 2015	Head	835	20.7	0.89	42.35	0.90	41.5	-1.11	2.05
May 28, 2015	Head	1750	21.3	1.342	40.401	1.37	40.1	-2.04	0.75
May 20, 2015	Head	1900	20.9	1.415	41.02	1.4	40	1.07	2.55
May 26, 2015	Head	2600	21.4	1.987	37.616	1.96	39	1.38	-3.55
May 29, 2015	Body	835	21.5	0.992	55.615	0.97	55.2	2.27	0.75
May 31, 2015	Body	1750	20.8	1.479	52.382	1.49	53.4	-0.74	-1.91
May 31, 2015	Body	1900	20.9	1.554	54.479	1.52	53.3	2.24	2.21
Jun. 1, 2015	Body	2600	21.4	2.2	52.401	2.16	52.5	1.85	-0.19

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
May 27, 2015	3873	Head	835	0.89	42.35	Pass	Pass	Pass	GMSK	Pass	N/A
May 28, 2015	3873	Head	1750	1.342	40.401	Pass	Pass	Pass	N/A	N/A	N/A
May 20, 2015	3873	Head	1900	1.415	41.02	Pass	Pass	Pass	GMSK	Pass	N/A
May 26, 2015	3873	Head	2600	1.987	37.616	Pass	Pass	Pass	N/A	N/A	N/A
May 29, 2015	3873	Body	835	0.992	55.615	Pass	Pass	Pass	GMSK	Pass	N/A
May 31, 2015	3873	Body	1750	1.479	52.382	Pass	Pass	Pass	N/A	N/A	N/A
May 31, 2015	3873	Body	1900	1.554	54.479	Pass	Pass	Pass	GMSK	Pass	N/A
Jun. 1, 2015	3873	Body	2600	2.2	52.401	Pass	Pass	Pass	N/A	N/A	N/A

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
May 27, 2015	Head	835	9.52	2.48	9.92	4.20	4d139	3873	1341
May 28, 2015	Head	1900	36.90	9.65	38.60	4.61	1071	3873	1341
May 20, 2015	Head	1900	40.10	10.2	40.80	1.75	5d159	3873	1341
May 26, 2015	Head	2600	57.50	15.1	60.40	5.04	1020	3873	1341
May 29, 2015	Body	835	9.53	2.41	9.64	1.15	4d139	3873	1341
May 31, 2015	Body	1750	40.10	10.6	42.40	5.74	1071	3873	1341
May 31, 2015	Body	1900	41.10	9.57	38.28	-6.86	5d159	3873	1341
Jun. 1, 2015	Body	2600	56.50	14.2	56.80	0.53	1020	3873	1341

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	GSM850	GSM1900
GSM (GMSK, 1Tx-slot)	34.0	31.0
GPRS (GMSK, 1Tx-slot)	34.0	31.0
GPRS (GMSK, 2Tx-slot)	33.5	31.0
GPRS (GMSK, 3Tx-slot)	33.5	31.0
GPRS (GMSK, 4Tx-slot)	33.0	30.5
EDGE (8PSK, 1Tx-slot)	27.5	27.0
EDGE (8PSK, 2Tx-slot)	27.5	27.0
EDGE (8PSK, 3Tx-slot)	27.5	27.0
EDGE (8PSK, 4Tx-slot)	27.5	27.0

Mode	WCDMA Band II	WCDMA Band V
RMC 12.2K	23.5	23.5
HSDPA	23.0	23.0
HSUPA	23.0	23.0

Mode	LTE 2	LTE 4	LTE 7
QPSK / 16QAM	24.0	24.0	23.0

FCC SAR Test Report

A D T

Mode	2.4G WLAN
802.11b	9.7
802.11g	8.5
802.11n HT20	8.5
802.11n HT40	8.5

Mode	Bluetooth
All	9.0

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	33.61	33.60	33.57	30.42	30.41	30.60
GPRS (GMSK, 1Tx-slot)	33.47	33.47	33.48	30.42	30.41	30.55
GPRS (GMSK, 2Tx-slot)	33.13	33.16	33.28	30.40	30.39	30.54
GPRS (GMSK, 3Tx-slot)	32.81	32.87	32.96	30.35	30.31	30.44
GPRS (GMSK, 4Tx-slot)	32.55	32.60	32.62	30.26	30.17	30.34
EDGE (8PSK, 1Tx-slot)	27.25	27.37	27.25	26.76	26.63	26.77
EDGE (8PSK, 2Tx-slot)	27.25	27.30	27.10	26.73	26.64	26.75
EDGE (8PSK, 3Tx-slot)	27.05	27.13	27.02	26.69	26.60	26.69
EDGE (8PSK, 4Tx-slot)	26.91	26.90	26.85	26.64	26.54	26.61
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	24.61	24.60	24.57	21.42	21.41	21.60
GPRS (GMSK, 1Tx-slot)	24.47	24.47	24.48	21.42	21.41	21.55
GPRS (GMSK, 2Tx-slot)	27.13	27.16	27.28	24.40	24.39	24.54
GPRS (GMSK, 3Tx-slot)	28.55	28.61	28.70	26.09	26.05	26.18
GPRS (GMSK, 4Tx-slot)	29.55	29.60	29.62	27.26	27.17	27.34
EDGE (8PSK, 1Tx-slot)	18.25	18.37	18.25	17.76	17.63	17.77
EDGE (8PSK, 2Tx-slot)	21.25	21.30	21.10	20.73	20.64	20.75
EDGE (8PSK, 3Tx-slot)	22.79	22.87	22.76	22.43	22.34	22.43
EDGE (8PSK, 4Tx-slot)	23.91	23.90	23.85	23.64	23.54	23.61

Note:

- SAR testing was performed on the maximum frame-averaged power mode.
- The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:
Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)

FCC SAR Test Report

A D T

Band	WCDMA Band II			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6	
RMC 12.2K	23.12	23.20	23.24	23.04	23.16	22.91	-
HSDPA Subtest-1	22.33	22.37	22.60	22.21	22.33	22.17	0
HSDPA Subtest-2	22.47	22.36	22.53	22.20	22.34	22.45	0
HSDPA Subtest-3	21.91	21.88	22.09	21.79	21.93	21.81	0.5
HSDPA Subtest-4	21.93	21.85	22.04	21.85	21.91	21.62	0.5
HSUPA Subtest-1	22.07	22.04	22.31	21.97	22.10	22.10	0
HSUPA Subtest-2	20.33	19.93	20.53	20.27	20.08	20.20	2
HSUPA Subtest-3	21.00	21.19	21.26	20.88	21.15	20.94	1
HSUPA Subtest-4	20.19	20.15	20.13	19.78	19.91	20.16	2
HSUPA Subtest-5	22.30	22.31	22.47	22.17	22.36	22.23	0

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	23.11	23.12	23.26	0	22.06	21.83	22.23	1
	1	2	23.10	22.79	23.25	0	22.00	21.82	22.35	1
	1	5	22.70	22.65	23.00	0	22.05	21.66	22.22	1
	3	0	22.55	22.73	23.10	0	21.91	21.69	22.22	1
	3	1	22.91	22.75	23.08	0	21.72	21.70	22.08	1
	3	3	22.99	22.79	23.25	0	21.50	21.71	22.26	1
	6	0	21.76	21.66	22.24	1	20.80	20.63	21.22	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	23.15	23.16	23.30	0	22.10	21.87	22.27	1
	1	7	23.14	22.83	23.29	0	22.04	21.86	22.39	1
	1	14	22.74	22.69	23.04	0	22.09	21.70	22.26	1
	8	0	21.59	21.77	22.14	1	20.95	20.73	21.26	2
	8	3	21.95	21.79	22.12	1	20.76	20.74	21.12	2
	8	7	22.03	21.83	22.30	1	20.54	20.75	21.30	2
	15	0	21.80	21.70	22.28	1	20.84	20.67	21.26	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	23.21	23.22	23.36	0	22.16	21.93	22.33	1
	1	12	23.20	22.89	23.35	0	22.10	21.92	22.45	1
	1	24	22.80	22.75	23.10	0	22.15	21.76	22.32	1
	12	0	21.65	21.83	22.20	1	21.01	20.79	21.32	2
	12	6	22.01	21.85	22.18	1	20.82	20.80	21.18	2
	12	13	22.09	21.89	22.36	1	20.60	20.81	21.36	2
	25	0	21.86	21.76	22.34	1	20.90	20.73	21.32	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
2 / 10M	1	0	23.26	23.27	23.41	0	22.21	21.98	22.38	1
	1	24	23.25	22.94	23.40	0	22.15	21.97	22.50	1
	1	49	22.85	22.80	23.15	0	22.20	21.81	22.37	1
	25	0	21.70	21.88	22.25	1	21.06	20.84	21.37	2
	25	12	22.06	21.90	22.23	1	20.87	20.85	21.23	2
	25	25	22.14	21.94	22.41	1	20.65	20.86	21.41	2
	50	0	21.91	21.81	22.39	1	20.95	20.78	21.37	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18675	Mid CH 18900	High CH 19125		Low CH 18675	Mid CH 18900	High CH 19125	
			1857.5 MHz	1880.0 MHz	1902.5 MHz		1857.5 MHz	1880.0 MHz	1902.5 MHz	
2 / 15M	1	0	23.32	23.33	23.47	0	22.27	22.04	22.44	1
	1	37	23.31	23.00	23.46	0	22.21	22.03	22.56	1
	1	74	22.91	22.86	23.21	0	22.26	21.87	22.43	1
	36	0	21.76	21.94	22.31	1	21.12	20.90	21.43	2
	36	19	22.12	21.96	22.29	1	20.93	20.91	21.29	2
	36	39	22.20	22.00	22.47	1	20.71	20.92	21.47	2
	75	0	21.97	21.87	22.45	1	21.01	20.84	21.43	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18700	Mid CH 18900	High CH 19100		Low CH 18700	Mid CH 18900	High CH 19100	
			1860.0 MHz	1880.0 MHz	1900.0 MHz		1860.0 MHz	1880.0 MHz	1900.0 MHz	
2 / 20M	1	0	23.36	23.37	23.51	0	22.31	22.08	22.48	1
	1	50	23.35	23.04	23.50	0	22.25	22.07	22.60	1
	1	99	22.95	22.90	23.25	0	22.30	21.91	22.47	1
	50	0	21.80	21.98	22.35	1	21.16	20.94	21.47	2
	50	25	22.16	22.00	22.33	1	20.97	20.95	21.33	2
	50	50	22.24	22.04	22.51	1	20.75	20.96	21.51	2
	100	0	22.01	21.91	22.49	1	21.05	20.88	21.47	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	23.37	22.95	22.68	0	21.93	21.87	21.51	1
	1	2	23.28	22.56	22.58	0	21.87	21.73	21.59	1
	1	5	22.83	22.55	22.61	0	21.86	22.00	21.72	1
	3	0	22.96	22.64	22.41	0	22.01	21.61	21.46	1
	3	1	22.86	22.50	22.36	0	21.94	21.49	21.43	1
	3	3	22.80	22.32	22.36	0	21.74	21.28	21.41	1
	6	0	21.85	21.55	21.42	1	20.95	20.55	20.39	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	23.41	22.99	22.72	0	21.97	21.91	21.55	1
	1	7	23.32	22.60	22.62	0	21.91	21.77	21.63	1
	1	14	22.87	22.59	22.65	0	21.90	22.04	21.76	1
	8	0	22.00	21.68	21.45	1	21.05	20.65	20.50	2
	8	3	21.90	21.54	21.40	1	20.98	20.53	20.47	2
	8	7	21.84	21.36	21.40	1	20.78	20.32	20.45	2
	15	0	21.89	21.59	21.46	1	20.99	20.59	20.43	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	23.44	23.02	22.75	0	22.00	21.94	21.58	1
	1	12	23.35	22.63	22.65	0	21.94	21.80	21.66	1
	1	24	22.90	22.62	22.68	0	21.93	22.07	21.79	1
	12	0	22.03	21.71	21.48	1	21.08	20.68	20.53	2
	12	6	21.93	21.57	21.43	1	21.01	20.56	20.50	2
	12	13	21.87	21.39	21.43	1	20.81	20.35	20.48	2
	25	0	21.92	21.62	21.49	1	21.02	20.62	20.46	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	23.49	23.07	22.80	0	22.05	21.99	21.63	1
	1	24	23.40	22.68	22.70	0	21.99	21.85	21.71	1
	1	49	22.95	22.67	22.73	0	21.98	22.12	21.84	1
	25	0	22.08	21.76	21.53	1	21.13	20.73	20.58	2
	25	12	21.98	21.62	21.48	1	21.06	20.61	20.55	2
	25	25	21.92	21.44	21.48	1	20.86	20.40	20.53	2
	50	0	21.97	21.67	21.54	1	21.07	20.67	20.51	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	23.55	23.13	22.86	0	22.11	22.05	21.69	1
	1	37	23.46	22.74	22.76	0	22.05	21.91	21.77	1
	1	74	23.01	22.73	22.79	0	22.04	22.18	21.90	1
	36	0	22.14	21.82	21.59	1	21.19	20.79	20.64	2
	36	19	22.04	21.68	21.54	1	21.12	20.67	20.61	2
	36	39	21.98	21.50	21.54	1	20.92	20.46	20.59	2
	75	0	22.03	21.73	21.60	1	21.13	20.73	20.57	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	23.59	23.17	22.90	0	22.15	22.09	21.73	1
	1	50	23.50	22.78	22.80	0	22.09	21.95	21.81	1
	1	99	23.05	22.77	22.83	0	22.08	22.22	21.94	1
	50	0	22.18	21.86	21.63	1	21.23	20.83	20.68	2
	50	25	22.08	21.72	21.58	1	21.16	20.71	20.65	2
	50	50	22.02	21.54	21.58	1	20.96	20.50	20.63	2
	100	0	22.07	21.77	21.64	1	21.17	20.77	20.61	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	22.49	22.38	22.41	0	21.21	21.51	21.39	1
	1	12	22.41	22.37	22.37	0	21.23	21.43	21.37	1
	1	24	21.92	22.25	22.30	0	21.28	21.48	21.52	1
	12	0	20.86	21.29	21.23	1	19.99	20.38	20.54	2
	12	6	21.02	21.40	21.43	1	20.15	20.36	20.47	2
	12	13	21.30	21.45	21.44	1	20.14	20.08	20.41	2
	25	0	20.94	21.39	21.42	1	20.04	20.33	20.52	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	22.55	22.44	22.47	0	21.27	21.57	21.45	1
	1	24	22.47	22.43	22.43	0	21.29	21.49	21.43	1
	1	49	21.98	22.31	22.36	0	21.34	21.54	21.58	1
	25	0	20.92	21.35	21.29	1	20.05	20.44	20.60	2
	25	12	21.08	21.46	21.49	1	20.21	20.42	20.53	2
	25	25	21.36	21.51	21.50	1	20.20	20.14	20.47	2
	50	0	21.00	21.45	21.48	1	20.10	20.39	20.58	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	22.58	22.47	22.50	0	21.30	21.60	21.48	1
	1	37	22.50	22.46	22.46	0	21.32	21.52	21.46	1
	1	74	22.01	22.34	22.39	0	21.37	21.57	21.61	1
	36	0	20.95	21.38	21.32	1	20.08	20.47	20.63	2
	36	19	21.11	21.49	21.52	1	20.24	20.45	20.56	2
	36	39	21.39	21.54	21.53	1	20.23	20.17	20.50	2
	75	0	21.03	21.48	21.51	1	20.13	20.42	20.61	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	22.62	22.51	22.54	0	21.34	21.64	21.52	1
	1	50	22.54	22.50	22.50	0	21.36	21.56	21.50	1
	1	99	22.05	22.38	22.43	0	21.41	21.61	21.65	1
	50	0	20.99	21.42	21.36	1	20.12	20.51	20.67	2
	50	25	21.15	21.53	21.56	1	20.28	20.49	20.60	2
	50	50	21.43	21.58	21.57	1	20.27	20.21	20.54	2
	100	0	21.07	21.52	21.55	1	20.17	20.46	20.65	2

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	9.10	9.45	9.51
Mode	802.11g		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	8.02	8.39	8.06
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	8.01	8.40	8.05
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	3 (2422)	6 (2437)	9 (2452)
Average Power	7.86	7.98	7.88

4.7 SAR Testing Results

4.7.1 SAR Results for Head

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
01	GSM850	GPRS12	Right Cheek	251	33.0	32.62	1.09	0.09	0.00256	0.00
	GSM850	GPRS12	Right Tilted	251	33.0	32.62	1.09	0.04	0.00252	0.00
	GSM850	GPRS12	Left Cheek	251	33.0	32.62	1.09	0.05	0.00351	0.00
	GSM850	GPRS12	Left Tilted	251	33.0	32.62	1.09	0.1	0.00191	0.00
02	GSM1900	GPRS12	Right Cheek	810	30.5	30.34	1.04	0.14	0.018	0.02
	GSM1900	GPRS12	Right Tilted	810	30.5	30.34	1.04	-0.05	0.01	0.01
	GSM1900	GPRS12	Left Cheek	810	30.5	30.34	1.04	0.12	0.016	0.02
	GSM1900	GPRS12	Left Tilted	810	30.5	30.34	1.04	0.08	0.00853	0.01
03	WCDMA II	RMC12.2K	Right Cheek	9538	23.5	23.24	1.06	-0.14	0.019	0.02
	WCDMA II	RMC12.2K	Right Tilted	9538	23.5	23.24	1.06	-0.13	0.021	0.02
	WCDMA II	RMC12.2K	Left Cheek	9538	23.5	23.24	1.06	-0.06	0.026	0.03
	WCDMA II	RMC12.2K	Left Tilted	9538	23.5	23.24	1.06	-0.09	0.012	0.01
04	WCDMA V	RMC12.2K	Right Cheek	4182	23.5	23.16	1.08	-0.01	0.00196	0.00
	WCDMA V	RMC12.2K	Right Tilted	4182	23.5	23.16	1.08	0.1	0.00158	0.00
	WCDMA V	RMC12.2K	Left Cheek	4182	23.5	23.16	1.08	0.01	0.00179	0.00
	WCDMA V	RMC12.2K	Left Tilted	4182	23.5	23.16	1.08	0.01	0.00166	0.00

Note:

- SAR is performed on the highest power channel. When the reported SAR value of highest power channel is ≤ 0.8 W/kg, SAR testing for optional channel is not required.
- Since GPRS/EDGE of this device supports VOIP capability through 3rd party apps software, we have evaluated data mode for head SAR.

FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
05	LTE 2	QPSK20M	Right Cheek	19100	1	0	24.0	23.51	1.12	0.03	0.028	0.03
	LTE 2	QPSK20M	Right Tilted	19100	1	0	24.0	23.51	1.12	0.01	0.025	0.03
	LTE 2	QPSK20M	Left Cheek	19100	1	0	24.0	23.51	1.12	-0.06	0.050	0.06
	LTE 2	QPSK20M	Left Tilted	19100	1	0	24.0	23.51	1.12	0.03	0.019	0.02
	LTE 2	QPSK20M	Right Cheek	19100	50	50	23.0	22.51	1.12	0.05	0.025	0.03
	LTE 2	QPSK20M	Right Tilted	19100	50	50	23.0	22.51	1.12	-0.01	0.027	0.03
	LTE 2	QPSK20M	Left Cheek	19100	50	50	23.0	22.51	1.12	0.02	0.043	0.05
	LTE 2	QPSK20M	Left Tilted	19100	50	50	23.0	22.51	1.12	0.18	0.018	0.02
06	LTE 4	QPSK20M	Right Cheek	20050	1	0	24.0	23.59	1.10	0.08	0.0076	0.01
	LTE 4	QPSK20M	Right Tilted	20050	1	0	24.0	23.59	1.10	0.06	0.00632	0.01
	LTE 4	QPSK20M	Left Cheek	20050	1	0	24.0	23.59	1.10	0.01	0.00666	0.01
	LTE 4	QPSK20M	Left Tilted	20050	1	0	24.0	23.59	1.10	0.16	0.00406	0.00
	LTE 4	QPSK20M	Right Cheek	20050	50	0	23.0	22.18	1.21	-0.04	0.00581	0.01
	LTE 4	QPSK20M	Right Tilted	20050	50	0	23.0	22.18	1.21	0.08	0.00548	0.01
	LTE 4	QPSK20M	Left Cheek	20050	50	0	23.0	22.18	1.21	0.07	0.00511	0.01
	LTE 4	QPSK20M	Left Tilted	20050	50	0	23.0	22.18	1.21	-0.02	0.00324	0.00
07	LTE 7	QPSK20M	Right Cheek	20850	1	0	23.0	22.62	1.09	0.03	0.011	0.01
	LTE 7	QPSK20M	Right Tilted	20850	1	0	23.0	22.62	1.09	-0.05	0.014	0.02
	LTE 7	QPSK20M	Left Cheek	20850	1	0	23.0	22.62	1.09	0.02	0.016	0.02
	LTE 7	QPSK20M	Left Tilted	20850	1	0	23.0	22.62	1.09	-0.04	0.011	0.01
	LTE 7	QPSK20M	Right Cheek	21100	50	50	22.0	21.58	1.10	0.09	0.00679	0.01
	LTE 7	QPSK20M	Right Tilted	21100	50	50	22.0	21.58	1.10	0.18	0.00886	0.01
	LTE 7	QPSK20M	Left Cheek	21100	50	50	22.0	21.58	1.10	0.02	0.00959	0.01
	LTE 7	QPSK20M	Left Tilted	21100	50	50	22.0	21.58	1.10	-0.14	0.00733	0.01

Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

FCC SAR Test Report

A D T

4.7.2 SAR Results for Body-Worn (Separation Distance is 0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
08	GSM850	GPRS12	Rear Face	251	33.0	32.62	1.09	0.07	0.862	0.94
	GSM850	GPRS12	Left Side	251	33.0	32.62	1.09	0.16	0.012	0.01
	GSM850	GPRS12	Right Side	251	33.0	32.62	1.09	0.04	0.00399	0.00
	GSM850	GPRS12	Top Side	251	33.0	32.62	1.09	0.08	0.00211	0.00
	GSM850	GPRS12	Bottom Side	251	33.0	32.62	1.09	0.05	0.086	0.09
	GSM850	GPRS12	Rear Face	128	33.0	32.55	1.11	0.09	0.393	0.44
	GSM850	GPRS12	Rear Face	189	33.0	32.6	1.10	0.07	0.590	0.65
	GSM850	GPRS12	Rear Face	251	33.0	32.62	1.09	0.08	0.843	0.92
09	GSM1900	GPRS12	Rear Face	810	30.5	30.34	1.04	0.09	0.449	0.47
	GSM1900	GPRS12	Left Side	810	30.5	30.34	1.04	-0.04	0.414	0.43
	GSM1900	GPRS12	Right Side	810	30.5	30.34	1.04	-0.7	0.00797	0.01
	GSM1900	GPRS12	Bottom Side	810	30.5	30.34	1.04	0.08	0.199	0.21
	WCDMA II	RMC12.2K	Rear Face	9538	23.5	23.24	1.06	0.01	0.305	0.32
10	WCDMA II	RMC12.2K	Left Side	9538	23.5	23.24	1.06	0.17	0.360	0.38
	WCDMA II	RMC12.2K	Right Side	9538	23.5	23.24	1.06	0.02	0.00576	0.01
	WCDMA II	RMC12.2K	Bottom Side	9538	23.5	23.24	1.06	0.11	0.136	0.14
11	WCDMA V	RMC12.2K	Rear Face	4182	23.5	23.16	1.08	0.15	0.201	0.22
	WCDMA V	RMC12.2K	Left Side	4182	23.5	23.16	1.08	0.08	0.00407	0.00
	WCDMA V	RMC12.2K	Right Side	4182	23.5	23.16	1.08	0.13	0.00194	0.00
	WCDMA V	RMC12.2K	Bottom Side	4182	23.5	23.16	1.08	-0.03	0.022	0.02

Note:

- SAR is performed on the highest power channel. When the reported SAR value of highest power channel is ≤ 0.8 W/kg, SAR testing for optional channel is not required.

FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 2	QPSK20M	Rear Face	19100	1	0	24.0	23.51	1.12	0.05	0.271	0.30
	LTE 2	QPSK20M	Left Side	19100	1	0	24.0	23.51	1.12	0.09	0.26	0.29
	LTE 2	QPSK20M	Right Side	19100	1	0	24.0	23.51	1.12	0.05	0.011	0.01
	LTE 2	QPSK20M	Bottom Side	19100	1	0	24.0	23.51	1.12	-0.04	0.113	0.13
	LTE 2	QPSK20M	Rear Face	19100	50	50	23.0	22.51	1.12	0.06	0.253	0.28
12	LTE 2	QPSK20M	Left Side	19100	50	50	23.0	22.51	1.12	0.04	0.285	0.32
	LTE 2	QPSK20M	Right Side	19100	50	50	23.0	22.51	1.12	0.05	0.00632	0.01
	LTE 2	QPSK20M	Bottom Side	19100	50	50	23.0	22.51	1.12	0.03	0.12	0.13
13	LTE 4	QPSK20M	Rear Face	20050	1	0	24.0	23.59	1.10	0.03	0.084	0.09
	LTE 4	QPSK20M	Left Side	20050	1	0	24.0	23.59	1.10	0.14	0.015	0.02
	LTE 4	QPSK20M	Right Side	20050	1	0	24.0	23.59	1.10	0.02	0.016	0.02
	LTE 4	QPSK20M	Bottom Side	20050	1	0	24.0	23.59	1.10	0.17	0.031	0.03
	LTE 4	QPSK20M	Rear Face	20050	50	0	23.0	22.18	1.21	0.01	0.062	0.07
	LTE 4	QPSK20M	Left Side	20050	50	0	23.0	22.18	1.21	0.17	0.011	0.01
	LTE 4	QPSK20M	Right Side	20050	50	0	23.0	22.18	1.21	0.1	0.012	0.01
	LTE 4	QPSK20M	Bottom Side	20050	50	0	23.0	22.18	1.21	0.02	0.022	0.03
14	LTE 7	QPSK20M	Rear Face	20850	1	0	23.0	22.62	1.09	0.09	0.370	0.40
	LTE 7	QPSK20M	Left Side	20850	1	0	23.0	22.62	1.09	0.06	0.109	0.12
	LTE 7	QPSK20M	Right Side	20850	1	0	23.0	22.62	1.09	-0.06	0.00446	0.00
	LTE 7	QPSK20M	Bottom Side	20850	1	0	23.0	22.62	1.09	0.16	0.156	0.17
	LTE 7	QPSK20M	Rear Face	21100	50	50	22.0	21.58	1.10	0.07	0.230	0.25
	LTE 7	QPSK20M	Left Side	21100	50	50	22.0	21.58	1.10	0.01	0.072	0.08
	LTE 7	QPSK20M	Right Side	21100	50	50	22.0	21.58	1.10	-0.03	0.00464	0.01
	LTE 7	QPSK20M	Bottom Side	21100	50	50	22.0	21.58	1.10	0.06	0.100	0.11

Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
GSM850	GPRS12	Rear Face	251	0.862	0.843	1.02	N/A	N/A	N/A	N/A

4.7.4 Simultaneous Multi-band Transmission Evaluation

<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
WLAN (DTS)	2.462	9.7	Head	5	0.39
GSM850	0.835	30.0	Body	5	0.40
GSM1900	1.909	27.5	Body	5	0.40
WCDMA II	1.907	23.5	Body	5	0.40
WCDMA V	0.846	23.5	Body	5	0.40
LTE 2	1.908	24.0	Body	5	0.40
LTE 4	1.752	24.0	Body	5	0.40
LTE 7	2.57	23.0	Body	5	0.40
WLAN (DTS)	2.462	9.7	Body	5	0.39
BT (DSS)	2.48	9.0	Body	5	0.33

Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	GSM850 + WLAN (DTS)	Head	Right Cheek	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Right Tilted	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Left Cheek	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Left Tilted	0.00	0.39	0.39	Σ SAR < 1.6, Not required
		Body	Rear Face	0.94	0.39	1.33	Σ SAR < 1.6, Not required
			Top Side	0.40	0.39	0.79	Σ SAR < 1.6, Not required
			Bottom Side	0.09	0.39	0.48	Σ SAR < 1.6, Not required
			Left Side	0.01	0.39	0.40	Σ SAR < 1.6, Not required
			Right Side	0.00	0.39	0.39	Σ SAR < 1.6, Not required
2	GSM850 + BT (DSS)	Body	Rear Face	0.94	0.33	1.27	Σ SAR < 1.6, Not required
			Top Side	0.40	0.33	0.73	Σ SAR < 1.6, Not required
			Bottom Side	0.09	0.33	0.42	Σ SAR < 1.6, Not required
			Left Side	0.01	0.33	0.34	Σ SAR < 1.6, Not required
			Right Side	0.00	0.33	0.33	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
3	GSM1900 + WLAN (DTS)	Head	Right Cheek	0.02	0.39	0.41	$\Sigma \text{ SAR} < 1.6$, Not required
			Right Tilted	0.01	0.39	0.40	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Cheek	0.02	0.39	0.41	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Tilted	0.01	0.39	0.40	$\Sigma \text{ SAR} < 1.6$, Not required
		Body	Rear Face	0.47	0.39	0.86	$\Sigma \text{ SAR} < 1.6$, Not required
			Top Side	0.40	0.39	0.79	$\Sigma \text{ SAR} < 1.6$, Not required
			Bottom Side	0.21	0.39	0.60	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Side	0.43	0.39	0.82	$\Sigma \text{ SAR} < 1.6$, Not required
			Right Side	0.01	0.39	0.40	$\Sigma \text{ SAR} < 1.6$, Not required
4	GSM1900 + BT (DSS)	Body	Rear Face	0.47	0.33	0.80	$\Sigma \text{ SAR} < 1.6$, Not required
			Top Side	0.40	0.33	0.73	$\Sigma \text{ SAR} < 1.6$, Not required
			Bottom Side	0.21	0.33	0.54	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Side	0.43	0.33	0.76	$\Sigma \text{ SAR} < 1.6$, Not required
			Right Side	0.01	0.33	0.34	$\Sigma \text{ SAR} < 1.6$, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
5	WCDMA II + WLAN (DTS)	Head	Right Cheek	0.02	0.39	0.41	$\Sigma \text{ SAR} < 1.6$, Not required
			Right Tilted	0.02	0.39	0.41	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Cheek	0.03	0.39	0.42	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Tilted	0.01	0.39	0.40	$\Sigma \text{ SAR} < 1.6$, Not required
		Body	Rear Face	0.32	0.39	0.71	$\Sigma \text{ SAR} < 1.6$, Not required
			Top Side	0.40	0.39	0.79	$\Sigma \text{ SAR} < 1.6$, Not required
			Bottom Side	0.14	0.39	0.53	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Side	0.38	0.39	0.77	$\Sigma \text{ SAR} < 1.6$, Not required
			Right Side	0.01	0.39	0.40	$\Sigma \text{ SAR} < 1.6$, Not required
6	WCDMA II + BT (DSS)	Body	Rear Face	0.32	0.33	0.65	$\Sigma \text{ SAR} < 1.6$, Not required
			Top Side	0.40	0.33	0.73	$\Sigma \text{ SAR} < 1.6$, Not required
			Bottom Side	0.14	0.33	0.47	$\Sigma \text{ SAR} < 1.6$, Not required
			Left Side	0.38	0.33	0.71	$\Sigma \text{ SAR} < 1.6$, Not required
			Right Side	0.01	0.33	0.34	$\Sigma \text{ SAR} < 1.6$, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
7	WCDMA V + WLAN (DTS)	Head	Right Cheek	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Right Tilted	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Left Cheek	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Left Tilted	0.00	0.39	0.39	Σ SAR < 1.6, Not required
		Body	Rear Face	0.22	0.39	0.61	Σ SAR < 1.6, Not required
			Top Side	0.40	0.39	0.79	Σ SAR < 1.6, Not required
			Bottom Side	0.02	0.39	0.41	Σ SAR < 1.6, Not required
			Left Side	0.00	0.39	0.39	Σ SAR < 1.6, Not required
			Right Side	0.00	0.39	0.39	Σ SAR < 1.6, Not required
8	WCDMA V + BT (DSS)	Body	Rear Face	0.22	0.33	0.55	Σ SAR < 1.6, Not required
			Top Side	0.40	0.33	0.73	Σ SAR < 1.6, Not required
			Bottom Side	0.02	0.33	0.35	Σ SAR < 1.6, Not required
			Left Side	0.00	0.33	0.33	Σ SAR < 1.6, Not required
			Right Side	0.00	0.33	0.33	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
9	LTE 2 + WLAN (DTS)	Head	Right Cheek	0.03	0.39	0.42	Σ SAR < 1.6, Not required
			Right Tilted	0.03	0.39	0.42	Σ SAR < 1.6, Not required
			Left Cheek	0.06	0.39	0.45	Σ SAR < 1.6, Not required
			Left Tilted	0.02	0.39	0.41	Σ SAR < 1.6, Not required
		Body	Rear Face	0.30	0.39	0.69	Σ SAR < 1.6, Not required
			Top Side	0.40	0.39	0.79	Σ SAR < 1.6, Not required
			Bottom Side	0.13	0.39	0.52	Σ SAR < 1.6, Not required
			Left Side	0.32	0.39	0.71	Σ SAR < 1.6, Not required
			Right Side	0.01	0.39	0.40	Σ SAR < 1.6, Not required
10	LTE 2 + BT (DSS)	Body	Rear Face	0.30	0.33	0.63	Σ SAR < 1.6, Not required
			Top Side	0.40	0.33	0.73	Σ SAR < 1.6, Not required
			Bottom Side	0.13	0.33	0.46	Σ SAR < 1.6, Not required
			Left Side	0.32	0.33	0.65	Σ SAR < 1.6, Not required
			Right Side	0.01	0.33	0.34	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
11	LTE 4 + WLAN (DTS)	Head	Right Cheek	0.01	0.39	0.40	Σ SAR < 1.6, Not required
			Right Tilted	0.01	0.39	0.40	Σ SAR < 1.6, Not required
			Left Cheek	0.01	0.39	0.40	Σ SAR < 1.6, Not required
			Left Tilted	0.00	0.39	0.39	Σ SAR < 1.6, Not required
		Body	Rear Face	0.09	0.39	0.48	Σ SAR < 1.6, Not required
			Top Side	0.40	0.39	0.79	Σ SAR < 1.6, Not required
			Bottom Side	0.03	0.39	0.42	Σ SAR < 1.6, Not required
			Left Side	0.02	0.39	0.41	Σ SAR < 1.6, Not required
			Right Side	0.02	0.39	0.41	Σ SAR < 1.6, Not required
12	LTE 4 + BT (DSS)	Body	Rear Face	0.09	0.33	0.42	Σ SAR < 1.6, Not required
			Top Side	0.40	0.33	0.73	Σ SAR < 1.6, Not required
			Bottom Side	0.03	0.33	0.36	Σ SAR < 1.6, Not required
			Left Side	0.02	0.33	0.35	Σ SAR < 1.6, Not required
			Right Side	0.02	0.33	0.35	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
13	LTE 7 + WLAN (DTS)	Head	Right Cheek	0.01	0.39	0.40	Σ SAR < 1.6, Not required
			Right Tilted	0.02	0.39	0.41	Σ SAR < 1.6, Not required
			Left Cheek	0.02	0.39	0.41	Σ SAR < 1.6, Not required
			Left Tilted	0.01	0.39	0.40	Σ SAR < 1.6, Not required
		Body	Rear Face	0.40	0.39	0.79	Σ SAR < 1.6, Not required
			Top Side	0.40	0.39	0.79	Σ SAR < 1.6, Not required
			Bottom Side	0.17	0.39	0.56	Σ SAR < 1.6, Not required
			Left Side	0.12	0.39	0.51	Σ SAR < 1.6, Not required
			Right Side	0.01	0.39	0.40	Σ SAR < 1.6, Not required
14	LTE 7 + BT (DSS)	Body	Rear Face	0.40	0.33	0.73	Σ SAR < 1.6, Not required
			Top Side	0.40	0.33	0.73	Σ SAR < 1.6, Not required
			Bottom Side	0.17	0.33	0.50	Σ SAR < 1.6, Not required
			Left Side	0.12	0.33	0.45	Σ SAR < 1.6, Not required
			Right Side	0.01	0.33	0.34	Σ SAR < 1.6, Not required

Test Engineer : Yihu Xiong

5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D835V2	4d139	Nov. 04, 2014	1 Years
System Validation Dipole	SPEAG	D1750V2	1071	Nov. 06, 2014	1 Years
System Validation Dipole	SPEAG	D1900V2	5d159	Nov. 05, 2014	1 Years
System Validation Dipole	SPEAG	D2600V2	1020	Aug. 21, 2014	1 Years
Dosimetric E-Field Probe	SPEAG	EX3DV4	3873	Aug. 26, 2014	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1341	Aug. 26, 2014	1 Year
Radio Communication Analyzer	ANRITSU	MT8820C	6201300717	Oct. 09, 2014	1 Year
Wireless Communication Test Set	Agilent	E5515C	MY50267377	Nov. 12, 2014	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214638	Sep. 20, 2014	1 Year
EXA Spectrum Analyzer	Agilent	E5071C	MY46214638	Sep. 20, 2014	1 Year
MXG Analog Signal Generator	Agilent	N5183A	MY50140980	Nov. 10, 2014	1 Year
Power Meter	Agilent	N1914A	MY52180044	Aug. 28, 2014	1 Year
Power Sensor	Agilent	E9304A H18	MY52050011	Oct. 14, 2014	1 Year
Temp. & Humi. Recorder	HUATO	A2000TH	HE20107684	Jul. 21, 2014	1 Year
Electronic Thermometer	YONGFA	YF-160A	120100323	Oct. 21, 2014	1 Year

6. Measurement Uncertainty

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)	Vi
Measurement System						
Probe Calibration	6.0	Normal	1	1	± 6.0 %	∞
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %	∞
Boundary Effects	1.0	Rectangular	√3	1	± 0.6 %	∞
Linearity	4.7	Rectangular	√3	1	± 2.7 %	∞
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %	∞
Readout Electronics	0.6	Normal	1	1	± 0.6 %	∞
Response Time	0.0	Rectangular	√3	1	± 0.0 %	∞
Integration Time	1.7	Rectangular	√3	1	± 1.0 %	∞
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %	∞
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %	∞
Probe Positioner	0.5	Rectangular	√3	1	± 0.3 %	∞
Probe Positioning	2.9	Rectangular	√3	1	± 1.7 %	∞
Max. SAR Eval.	2.3	Rectangular	√3	1	± 1.3 %	∞
Test Sample Related						
Device Positioning	3.9	Normal	1	1	± 3.9 %	31
Device Holder	2.7	Normal	1	1	± 2.7 %	19
Power Drift	5.0	Rectangular	√3	1	± 2.9 %	∞
Phantom and Setup						
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %	∞
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %	∞
Liquid Conductivity (Meas.)	5.0	Normal	1	0.64	± 3.2 %	29
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %	∞
Liquid Permittivity (Meas.)	5.0	Normal	1	0.6	± 3.0 %	29
Combined Standard Uncertainty					± 11.7 %	
Expanded Uncertainty (K=2)					± 23.4 %	

Uncertainty budget for frequency range 300 MHz to 3 GHz

FCC SAR Test Report

A D T

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)	Vi
Measurement System						
Probe Calibration	6.55	Normal	1	1	± 6.55 %	∞
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %	∞
Boundary Effects	2.0	Rectangular	√3	1	± 1.2 %	∞
Linearity	4.7	Rectangular	√3	1	± 2.7 %	∞
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %	∞
Readout Electronics	0.3	Normal	1	1	± 0.3 %	∞
Response Time	0.8	Rectangular	√3	1	± 0.5 %	∞
Integration Time	2.6	Rectangular	√3	1	± 1.5 %	∞
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %	∞
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %	∞
Probe Positioner	0.8	Rectangular	√3	1	± 0.5 %	∞
Probe Positioning	9.9	Rectangular	√3	1	± 5.7 %	∞
Max. SAR Eval.	4.0	Rectangular	√3	1	± 2.3 %	∞
Test Sample Related						
Device Positioning	3.9	Normal	1	1	± 3.9 %	31
Device Holder	2.7	Normal	1	1	± 2.7 %	19
Power Drift	5.0	Rectangular	√3	1	± 2.9 %	∞
Phantom and Setup						
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %	∞
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %	∞
Liquid Conductivity (Meas.)	5.0	Normal	1	0.64	± 3.2 %	30
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %	∞
Liquid Permittivity (Meas.)	5.0	Normal	1	0.6	± 3.0 %	30
Combined Standard Uncertainty					± 13.4 %	
Expanded Uncertainty (K=2)					± 26.8 %	

Uncertainty budget for frequency range 3 GHz to 6 GHz

FCC SAR Test Report

7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., China Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

China Dongguan Lab:

No. 34, Guantai Rd., Houjie Town, Dongguan, Guangdong 523942, China

Tel: 86-769-8593-5656

Fax: 86-769-8599-1080

Email: service.dg@cn.bureauveritas.com

Web Site: www.adt.com.tw

The road map of all our labs can be found in our web site also.

---END---



Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

System Check_H835_150527**DUT: Dipole:835 MHz; Type:D835V2; SN;4d139**

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium: H835-A_0527 Medium parameters used: $f = 835$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 42.35$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.77, 9.77, 9.77); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)


Pin=250mW/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 3.11 W/kg**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 58.41 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 3.73 W/kg

SAR(1 g) = 2.48 W/kg; SAR(10 g) = 1.63 W/kg

Maximum value of SAR (measured) = 3.16 W/kg



System Check_H1750_150528

DUT: Dipole 1750 MHz ;Type:D1750V2; SN:1071

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1

Medium: H1750-A_0528 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.342$ S/m; $\epsilon_r = 40.401$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.06, 8.06, 8.06); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.2 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 86.70 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 17.3 W/kg

SAR(1 g) = 9.65 W/kg; SAR(10 g) = 5.18 W/kg

Maximum value of SAR (measured) = 13.4 W/kg



System Check_H1900_150520**DUT: Dipole 1900 MHz;Type: D1900V2; SN: 5d159**

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1

Medium: H1900-A_0520 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.415$ S/m; $\epsilon_r = 41.02$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.82, 7.82, 7.82); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.4 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 94.47 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.26 W/kg

Maximum value of SAR (measured) = 14.7 W/kg



System Check_H2600_150526**DUT: Dipole 2600 MHz; Type: D2600V2; SN: 1020**

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: H2600-A_0526 Medium parameters used: $f = 2600$ MHz; $\sigma = 1.987$ S/m; $\epsilon_r = 37.616$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.05, 7.05, 7.05); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 23.6 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 111.1 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 32.3 W/kg

SAR(1 g) = 15.1 W/kg; SAR(10 g) = 6.66 W/kg

Maximum value of SAR (measured) = 23.7 W/kg



System Check_B835_150529**DUT: Dipole:835 MHz; Type:D835V2; SN:4d139**

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium: B835-A_0529 Medium parameters used: $f = 835$ MHz; $\sigma = 0.992$ S/m; $\epsilon_r = 55.615$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.5, 9.5, 9.5); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.97 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.59 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 3.49 W/kg

SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.61 W/kg

Maximum value of SAR (measured) = 3.01 W/kg



System Check_B1750_150531**DUT: Dipole 1750 MHz ;Type:D1750V2; SN:1071**

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1

Medium: B1750-A_0531 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.479$ S/m; $\epsilon_r = 52.382$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C ; Liquid Temperature : 20.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.72, 7.72, 7.72); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.8 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 99.93 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 18.3 W/kg

SAR(1 g) = 10.6 W/kg; SAR(10 g) = 5.74 W/kg

Maximum value of SAR (measured) = 14.7 W/kg



System Check_B1900_150531**DUT: Dipole:1900MHz; Type:D1900V2; SN:5d159**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: B1900-A_0531 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.554$ S/m; $\epsilon_r = 54.479$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.7 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 93.71 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 9.57 W/kg; SAR(10 g) = 5.01 W/kg

Maximum value of SAR (measured) = 13.6 W/kg



System Check_B2600_150601**DUT: Dipole 2600 MHz; Type: D2600V2; SN: 1020**

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: B2600-A_0601 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.2$ S/m; $\epsilon_r = 52.401$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(6.94, 6.94, 6.94); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 22.3 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.67 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 31.2 W/kg

SAR(1 g) = 14.2 W/kg; SAR(10 g) = 6.28 W/kg

Maximum value of SAR (measured) = 22.4 W/kg





Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

P01 GSM850_GPRS12_Left Cheek_Ch251**DUT: 150512N006**

Communication System: GPRS12; Frequency: 848.8 MHz; Duty Cycle: 1:2

Medium: H835-A_0527 Medium parameters used: $f = 849$ MHz; $\sigma = 0.903$ S/m; $\epsilon_r = 42.17$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.77, 9.77, 9.77); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.00594 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.302 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.00730 W/kg

SAR(1 g) = 0.00351 W/kg; SAR(10 g) = 0.00292 W/kg

Maximum value of SAR (measured) = 0.00372 W/kg



P02 GSM1900_GPRS12_Right Cheek_Ch810**DUT: 150512N006**

Communication System: GPRS12; Frequency: 1909.8 MHz; Duty Cycle: 1:2

Medium: H1900-A_0520 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.444$ S/m; $\epsilon_r = 40.842$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.82, 7.82, 7.82); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0189 W/kg



- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.535 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.0260 W/kg

SAR(1 g) = 0.018 W/kg; SAR(10 g) = 0.013 W/kg

Maximum value of SAR (measured) = 0.0233 W/kg



P03 WCDMA II_RMC12.2K_Left Cheek_Ch9538**DUT: 150512N006**

Communication System: WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: H1900-A_0520 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.438$ S/m; $\epsilon_r = 40.879$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.82, 7.82, 7.82); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0484 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.831 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.0360 W/kg

SAR(1 g) = 0.026 W/kg; SAR(10 g) = 0.017 W/kg

Maximum value of SAR (measured) = 0.0321 W/kg



P04 WCDMA V_RMC12.2K_Right Cheek_Ch4182**DUT: 150512N006**

Communication System: WCDMA; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: H835-A_0527 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.892$ S/m; $\epsilon_r = 42.333$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.77, 9.77, 9.77); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.00341 W/kg

- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.384 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.00544 W/kg

SAR(1 g) = 0.00196 W/kg; SAR(10 g) = 0.00184 W/kg

Maximum value of SAR (measured) = 0.00221 W/kg



P05 LTE 2_QPSK20M_Left Cheek_Ch19100_1RB_OS0**DUT: 150512N006**

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: H1900-A_0520 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.415$ S/m; $\epsilon_r = 41.02$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.82, 7.82, 7.82); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0692 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.075 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.0700 W/kg

SAR(1 g) = 0.050 W/kg; SAR(10 g) = 0.033 W/kg

Maximum value of SAR (measured) = 0.0607 W/kg



P06 LTE 4_QPSK20M_Right Cheek_Ch20050_1RB_OS0**DUT: 150512N006**

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: H1750-A_0528 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.315$ S/m; $\epsilon_r = 40.558$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.06, 8.06, 8.06); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.00772 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.315 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.0100 W/kg

SAR(1 g) = 0.0076 W/kg; SAR(10 g) = 0.00554 W/kg

Maximum value of SAR (measured) = 0.00901 W/kg



P07 LTE 7_QPSK20M_Left Cheek_Ch20850_1RB_OS0**DUT: 150512N006**

Communication System: LTE; Frequency: 2510 MHz; Duty Cycle: 1:1

Medium: H2600-A_0526 Medium parameters used: $f = 2510$ MHz; $\sigma = 1.883$ S/m; $\epsilon_r = 38.053$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.05, 7.05, 7.05); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: Right Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0253 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.602 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0260 W/kg

SAR(1 g) = 0.016 W/kg; SAR(10 g) = 0.00933 W/kg

Maximum value of SAR (measured) = 0.0203 W/kg



P08 GSM850_GPRS12_Rear Face_0cm_Ch251**DUT: 150512N006**

Communication System: GPRS12; Frequency: 848.8 MHz; Duty Cycle: 1:2

Medium: B835-A_0529 Medium parameters used: $f = 849$ MHz; $\sigma = 1.006$ S/m; $\epsilon_r = 55.471$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.5, 9.5, 9.5); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.966 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.206 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 2.33 W/kg

SAR(1 g) = 0.862 W/kg; SAR(10 g) = 0.352 W/kg

Maximum value of SAR (measured) = 1.34 W/kg



P09 GSM1900_GPRS12_Rear Face_0cm_Ch810**DUT: 150512N006**

Communication System: GPRS12; Frequency: 1909.8 MHz; Duty Cycle: 1:2

Medium: B1900-A_0531 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.565$ S/m; $\epsilon_r = 54.452$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.767 W/kg



- Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.295 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.857 W/kg

SAR(1 g) = 0.449 W/kg; SAR(10 g) = 0.258 W/kg

Maximum value of SAR (measured) = 0.586 W/kg



P10 WCDMA II_RMC12.2K_Left Side_0cm_Ch9538**DUT: 150512N006**

Communication System: WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: B1900-A_0531 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.562$ S/m; $\epsilon_r = 54.46$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.574 W/kg



- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.625 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.778 W/kg

SAR(1 g) = 0.360 W/kg; SAR(10 g) = 0.172 W/kg

Maximum value of SAR (measured) = 0.586 W/kg



P11 WCDMA V_RMC12.2K_Rear Face_0cm_Ch4182**DUT: 150512N006**

Communication System: WCDMA; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: B835-A_0529 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.993$ S/m; $\epsilon_r = 55.599$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.5, 9.5, 9.5); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.327 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.206 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.527 W/kg

SAR(1 g) = 0.201 W/kg; SAR(10 g) = 0.083 W/kg

Maximum value of SAR (measured) = 0.360 W/kg



P12 LTE 2_QPSK20M_Left Side_0cm_Ch19100_50RB_OS50**DUT: 150512N006**

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: B1900-A_0531 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.554$ S/m; $\epsilon_r = 54.479$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (81x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.329 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.619 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.638 W/kg

SAR(1 g) = 0.285 W/kg; SAR(10 g) = 0.134 W/kg

Maximum value of SAR (measured) = 0.475 W/kg



P13 LTE 4_QPSK20M_Rear Face_0cm_Ch20050_1RB_OS0**DUT: 150512N006**

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: B1750-A_0531 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.446$ S/m; $\epsilon_r = 52.485$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.72, 7.72, 7.72); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.125 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.339 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.152 W/kg

SAR(1 g) = 0.084 W/kg; SAR(10 g) = 0.043 W/kg

Maximum value of SAR (measured) = 0.114 W/kg



P14 LTE 7_QPSK20M_Rear Face_0cm_Ch20850_1RB_OS0**DUT: 150512N006**

Communication System: LTE; Frequency: 2510 MHz; Duty Cycle: 1:1

Medium: B2600-A_0601 Medium parameters used: $f = 2510$ MHz; $\sigma = 2.076$ S/m; $\epsilon_r = 52.656$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(6.94, 6.94, 6.94); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (101x161x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.756 W/kg

- Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.032 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.370 W/kg; SAR(10 g) = 0.146 W/kg

Maximum value of SAR (measured) = 0.560 W/kg

