



BUREAU
VERITAS

Test Report No.: RF170906W002-2



FCC TEST REPORT

(Part 15, Subpart C)

Product: smart phone

Model Name: Alpha 950/ α950

FCC ID: ZC4ALPHA950

Applicant: Corporativo Lanix S.A. de C.V.

Address: Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo
Sonora, Mexico

Manufacturer: Corporativo Lanix S.A. de C.V.

Address: Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo
Sonora, Mexico

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue,
North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen,
Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: RF170906W002-2

Received Date: Sep. 06, 2017

Test Date: Sep. 07, 2017 ~ Sep. 20, 2017

Issued Date: Sep. 21, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 CERTIFICATION	5
2 SUMMARY OF TEST RESULTS.....	6
2.1 MEASUREMENT UNCERTAINTY	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	9
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	10
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
3.3 DUTY CYCLE OF TEST SIGNAL	13
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.5 DESCRIPTION OF SUPPORT UNITS	14
4 TEST TYPES AND RESULTS.....	15
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	15
4.1.2 TEST INSTRUMENTS.....	15
4.1.3 TEST PROCEDURES	16
4.1.4 DEVIATION FROM TEST STANDARD	16
4.1.5 TEST SETUP.....	17
4.1.6 EUT OPERATING CONDITIONS	17
4.1.7 TEST RESULTS	18
4.2 RADIATED EMISSION MEASUREMENT	20
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	20
4.2.2 TEST INSTRUMENTS.....	21
4.2.3 TEST PROCEDURES	22
4.2.4 DEVIATION FROM TEST STANDARD	22
4.2.5 TEST SETUP.....	23
4.2.6 EUT OPERATING CONDITIONS	24
4.2.7 TEST RESULTS	25
4.3 6 DB BANDWIDTH MEASUREMENT	44
4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	44
4.3.2 TEST INSTRUMENTS.....	44
4.3.3 TEST PROCEDURE.....	44
4.3.4 DEVIATION FROM TEST STANDARD	45



4.3.5	TEST SETUP	45
4.3.6	EUT OPERATING CONDITIONS	45
4.3.7	TEST RESULTS	46
4.4	CONDUCTED OUTPUT POWER.....	51
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	51
4.4.2	TEST SETUP	51
4.4.3	TEST INSTRUMENTS.....	51
4.4.4	TEST PROCEDURES	51
4.4.5	DEVIATION FROM TEST STANDARD	51
4.4.6	EUT OPERATING CONDITIONS	51
4.4.7	TEST RESULTS	52
4.4.7.1	MAXIMUM PEAK OUTPUT POWER	52
4.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	54
4.5	POWER SPECTRAL DENSITY MEASUREMENT	56
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	56
4.5.2	TEST SETUP	56
4.5.3	TEST INSTRUMENTS.....	56
4.5.4	TEST PROCEDURE.....	56
4.5.5	DEVIATION FROM TEST STANDARD	56
4.5.6	EUT OPERATING CONDITION	56
4.5.7	TEST RESULTS	57
4.6	OUT OF BAND EMISSION MEASUREMENT	62
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	62
4.6.2	TEST SETUP	62
4.6.3	TEST INSTRUMENTS.....	62
4.6.4	TEST PROCEDURE.....	62
4.6.5	DEVIATION FROM TEST STANDARD	63
4.6.6	EUT OPERATING CONDITION	63
4.6.7	TEST RESULTS	63
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	74
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	75



Test Report No.: RF170906W002-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF170906W002-2	Original release	Sep. 21, 2017



Test Report No.: RF170906W002-2

1 CERTIFICATION

PRODUCT: smart phone
BRAND NAME: LANIX
MODEL NAME: Alpha 950/ α950
APPLICANT: Corporativo Lanix S.A. de C.V.
TESTED: Sep. 07, 2017 ~ Sep. 20, 2017
TEST SAMPLE: Identical Prototype
STANDARDS: **FCC Part 15, Subpart C. Section 15.247**
ANSI C63.10-2013

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Yuqiang Yin, **DATE:** Sep. 21, 2017
(Yuqiang Yin/ Engineer)

APPROVED BY : Bill Yao, **DATE:** Sep. 21, 2017
(Bill Yao / Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.60dB at 0.636000MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -2.2dB at 2390MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GMHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	smart phone
BRAND NAME	LANIX
MODEL NAME	Alpha 950/ α950
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 135 Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 90.782mW (Maximum) BT-LE: 1.770mW (Maximum)
ANTENNA TYPE	PIFA Antenna with 1.2dBi gain
HW VERSION	V1.0
SW VERSION	Alpha 950_SW_01
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.0m

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
802.11n (40MHz)	1TX /1RX
BT_LE	1TX /1RX



3. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	LANIX
MODEL:	Alpha 950-C
INPUT:	AC 100-240V, 250mA
OUTPUT:	DC 5V, 1550mA

4. The EUT matched the following USB cable and Earphone:

USB CABLE	
BRAND:	N/A
MODEL:	Alpha 950
SIGNAL LINE:	1.0 METER

EARPHONE	
BRAND:	LANIX
MODEL:	Alpha 950
SIGNAL LINE:	1.0 METER

5. The above models are identical except the model name for marketing purpose.
6. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n HT40	3 to 9	3	OFDM	BPSK	13.5
BT-LE	0 to 39	39	DTS	GFSK	1

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n HT40	3 to 9	3	OFDM	BPSK	13.5

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 39	DTS	GFSK	1

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Simon Yang
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Simon Yang
PLC	24deg. C, 55%RH	DC 5V from adaptor	Jocan Guo
APCM	25deg. C, 60%RH	3.85Vdc from battery	Wenliang Wu



3.3 DUTY CYCLE OF TEST SIGNAL


WIFI 2.4GHz

802.11b: Duty cycle = $1.362/1.578 = 0.863 < 98\%$, Duty factor = $10 * \log(1/0.863) = 0.639$

802.11g: Duty cycle = $1.361/1.592 = 0.855 < 98\%$, Duty factor = $10 * \log(1/0.855) = 0.681$

802.11n (HT20): Duty cycle = $1.275/1.476 = 0.864 < 98\%$, Duty factor = $10 * \log(1/0.864) = 0.636$

802.11n (HT40): Duty cycle = $0.635/0.836 = 0.760 < 98\%$, Duty factor = $10 * \log(1/0.760) = 1.194$





3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Jun. 28,17	Jun. 27,18
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 21, 16	Sep. 20, 17

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



4.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2017/09/12

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.644000	---	40.12	46.00	-5.88	L	ON	9.7
0.644000	49.41	---	56.00	-6.59	L	ON	9.7
0.776000	---	34.77	46.00	-11.23	L	ON	9.7
0.776000	44.24	---	56.00	-11.76	L	ON	9.7
1.432000	---	32.05	46.00	-13.95	L	ON	9.7
1.432000	42.32	---	56.00	-13.68	L	ON	9.7
3.136000	---	34.58	46.00	-11.42	L	ON	9.7
3.136000	43.77	---	56.00	-12.23	L	ON	9.7
13.864000	---	36.42	50.00	-13.58	L	ON	9.9
13.864000	47.13	---	60.00	-12.87	L	ON	9.9
17.620000	---	33.58	50.00	-16.42	L	ON	9.9
17.620000	44.48	---	60.00	-15.52	L	ON	9.9

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2017/09/12

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.636000	---	42.40	46.00	-3.60	N	ON	10.0
0.636000	52.04	---	56.00	-3.96	N	ON	10.0
0.780000	---	36.62	46.00	-9.38	N	ON	10.0
0.780000	45.44	---	56.00	-10.56	N	ON	10.0
1.412000	---	37.95	46.00	-8.05	N	ON	9.9
1.412000	48.17	---	56.00	-7.83	N	ON	9.9
3.184000	---	36.41	46.00	-9.59	N	ON	9.8
3.184000	46.41	---	56.00	-9.59	N	ON	9.8
4.112000	---	31.95	46.00	-14.05	N	ON	9.8
4.112000	42.12	---	56.00	-13.88	N	ON	9.8
12.640000	---	37.42	50.00	-12.58	N	ON	9.9
12.640000	48.02	---	60.00	-11.98	N	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May 06,17	May 05,18
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 28,16	Nov. 27,17
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Dec. 16,16	Dec. 15,17
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 24,17	Jul. 23,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,17	Mar. 09,18
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation




4.2.5 TEST SETUP

< Frequency Range below 30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
58.13	35.31	65.06	40	-4.69	6.42	1.16	37.33	100	56	QP
107.6	38.85	66.5	43.5	-4.65	7.73	1.59	36.97	100	118	QP
159.98	39.91	64.52	43.5	-3.59	10.2	1.93	36.74	100	244	QP
221.09	37.21	60.38	46	-8.79	11.07	2.29	36.53	100	276	QP
302.57	40.61	61.28	46	-5.39	13.11	2.73	36.51	100	95	QP
394.72	33.85	50.45	46	-12.15	16.98	3.13	36.71	100	168	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.






CHANNEL	TX Channel 3	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
50.37	35	64.81	40	-5	6.5	1.07	37.38	100	142	QP
96.93	38.93	66.76	43.5	-4.57	7.66	1.52	37.01	100	295	QP
169.68	37.52	62.2	43.5	-5.98	10.05	1.99	36.72	100	48	QP
197.81	39.48	63.8	43.5	-4.02	10.08	2.16	36.56	100	177	QP
266.68	39.45	60.82	46	-6.55	12.6	2.54	36.51	100	304	QP
384.05	35.52	52.59	46	-10.48	16.53	3.08	36.68	100	215	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	39.37	44.85	54	-14.63	32.29	8.15	45.92	210	315	Average
2390	50.75	56.23	74	-23.25	32.29	8.15	45.92	210	315	Peak
2412	102.92	108.33			32.31	8.19	45.91	210	315	Average
2412	106	111.41			32.31	8.19	45.91	210	315	Peak
2483.5	33.63	38.82	54	-20.37	32.38	8.32	45.89	210	315	Average
2483.5	45.87	51.06	74	-28.13	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	40.28	45.76	54	-13.72	32.29	8.15	45.92	115	312	Average
2390	49.98	55.46	74	-24.02	32.29	8.15	45.92	115	312	Peak
2412	103.77	109.18			32.31	8.19	45.91	115	312	Average
2412	106.51	111.92			32.31	8.19	45.91	115	312	Peak
2483.5	33.14	38.33	54	-20.86	32.38	8.32	45.89	115	312	Average
2483.5	46.2	51.39	74	-27.8	32.38	8.32	45.89	115	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.33	40.81	54	-18.67	32.29	8.15	45.92	210	315	Average
2390	45.5	50.98	74	-28.5	32.29	8.15	45.92	210	315	Peak
2437	101.3	106.63			32.34	8.24	45.91	210	315	Average
2437	103.26	108.59			32.34	8.24	45.91	210	315	Peak
2483.5	34.53	39.72	54	-19.47	32.38	8.32	45.89	210	315	Average
2483.5	47.03	52.22	74	-26.97	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.38	39.86	54	-19.62	32.29	8.15	45.92	115	312	Average
2390	45.45	50.93	74	-28.55	32.29	8.15	45.92	115	312	Peak
2437	100.55	105.88			32.34	8.24	45.91	115	312	Average
2437	103.56	108.89			32.34	8.24	45.91	115	312	Peak
2483.5	34.47	39.66	54	-19.53	32.38	8.32	45.89	115	312	Average
2483.5	46.67	51.86	74	-27.33	32.38	8.32	45.89	115	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.37	38.85	54	-20.63	32.29	8.15	45.92	205	315	Average
2390	46.41	51.89	74	-27.59	32.29	8.15	45.92	205	315	Peak
2462	100.95	106.21			32.36	8.28	45.9	205	315	Average
2462	103.42	108.68			32.36	8.28	45.9	205	315	Peak
2483.5	36.49	41.68	54	-17.51	32.38	8.32	45.89	205	315	Average
2483.5	49.58	54.77	74	-24.42	32.38	8.32	45.89	205	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.47	38.95	54	-20.53	32.29	8.15	45.92	113	312	Average
2390	46.04	51.52	74	-27.96	32.29	8.15	45.92	113	312	Peak
2462	101.16	106.42			32.36	8.28	45.9	113	312	Average
2462	103.71	108.97			32.36	8.28	45.9	113	312	Peak
2483.5	37.49	42.68	54	-16.51	32.38	8.32	45.89	113	312	Average
2483.5	51.63	56.82	74	-22.37	32.38	8.32	45.89	113	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.04	54.52	54	-4.96	32.29	8.15	45.92	210	315	Average
2390	62.98	68.46	74	-11.02	32.29	8.15	45.92	210	315	Peak
2412	96.4	101.81			32.31	8.19	45.91	210	315	Average
2412	106.74	112.15			32.31	8.19	45.91	210	315	Peak
2483.5	34.75	39.94	54	-19.25	32.38	8.32	45.89	210	315	Average
2483.5	47.28	52.47	74	-26.72	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.05	54.53	54	-4.95	32.29	8.15	45.92	115	312	Average
2390	63.99	69.47	74	-10.01	32.29	8.15	45.92	115	312	Peak
2412	96.73	102.14			32.31	8.19	45.91	115	312	Average
2412	107.23	112.64			32.31	8.19	45.91	115	312	Peak
2483.5	33.77	38.96	54	-20.23	32.38	8.32	45.89	115	312	Average
2483.5	46.76	51.95	74	-27.24	32.38	8.32	45.89	115	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.85	39.33	54	-20.15	32.29	8.15	45.92	205	315	Average
2390	46.03	51.51	74	-27.97	32.29	8.15	45.92	205	315	Peak
2437	96.98	102.31			32.34	8.24	45.91	205	315	Average
2437	107.54	112.87			32.34	8.24	45.91	205	315	Peak
2483.5	39.49	44.68	54	-14.51	32.38	8.32	45.89	205	315	Average
2483.5	50.16	55.35	74	-23.84	32.38	8.32	45.89	205	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.87	39.35	54	-20.13	32.29	8.15	45.92	112	312	Average
2390	46.94	52.42	74	-27.06	32.29	8.15	45.92	112	312	Peak
2437	96.94	102.27			32.34	8.24	45.91	112	312	Average
2437	106.92	112.25			32.34	8.24	45.91	112	312	Peak
2483.5	40.63	45.82	54	-13.37	32.38	8.32	45.89	112	312	Average
2483.5	50.43	55.62	74	-23.57	32.38	8.32	45.89	112	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.34	39.82	54	-19.66	32.29	8.15	45.92	210	315	Average
2390	46.66	52.14	74	-27.34	32.29	8.15	45.92	210	315	Peak
2462	96.69	101.95			32.36	8.28	45.9	210	315	Average
2462	107.12	112.38			32.36	8.28	45.9	210	315	Peak
2483.5	48.37	53.56	54	-5.63	32.38	8.32	45.89	210	315	Average
2483.5	68.91	74.1	74	-5.09	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.04	39.52	54	-19.96	32.29	8.15	45.92	112	312	Average
2390	46.35	51.83	74	-27.65	32.29	8.15	45.92	112	312	Peak
2462	96.98	102.24			32.36	8.28	45.9	112	312	Average
2462	106.52	111.78			32.36	8.28	45.9	112	312	Peak
2483.5	49.99	55.18	54	-4.01	32.38	8.32	45.89	112	312	Average
2483.5	70.92	76.11	74	-3.08	32.38	8.32	45.89	112	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	48.11	53.59	54	-5.89	32.29	8.15	45.92	315	210	Average
2390	62.47	67.95	74	-11.53	32.29	8.15	45.92	315	210	Peak
2412	95.34	100.75			32.31	8.19	45.91	315	210	Average
2412	105.55	110.96			32.31	8.19	45.91	315	210	Peak
2483.5	33.91	39.1	54	-20.09	32.38	8.32	45.89	315	210	Average
2483.5	47.22	52.41	74	-26.78	32.38	8.32	45.89	315	210	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	48.03	53.51	54	-5.97	32.29	8.15	45.92	115	312	Average
2390	62.69	68.17	74	-11.31	32.29	8.15	45.92	115	312	Peak
2412	94.96	100.37			32.31	8.19	45.91	115	312	Average
2412	106.41	111.82			32.31	8.19	45.91	115	312	Peak
2483.5	33.96	39.15	54	-20.04	32.38	8.32	45.89	115	312	Average
2483.5	47.32	52.51	74	-26.68	32.38	8.32	45.89	115	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.47	39.95	54	-19.53	32.29	8.15	45.92	210	315	Average
2390	46.08	51.56	74	-27.92	32.29	8.15	45.92	210	315	Peak
2437	95.78	101.11			32.34	8.24	45.91	210	315	Average
2437	106.34	111.67			32.34	8.24	45.91	210	315	Peak
2483.5	39.74	44.93	54	-14.26	32.38	8.32	45.89	210	315	Average
2483.5	50.21	55.4	74	-23.79	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.47	39.95	54	-19.53	32.29	8.15	45.92	112	312	Average
2390	46.98	52.46	74	-27.02	32.29	8.15	45.92	112	312	Peak
2437	96.22	101.55			32.34	8.24	45.91	112	312	Average
2437	106.25	111.58			32.34	8.24	45.91	112	312	Peak
2483.5	41.35	46.54	54	-12.65	32.38	8.32	45.89	112	312	Average
2483.5	51.63	56.82	74	-22.37	32.38	8.32	45.89	112	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.2	39.68	54	-19.8	32.29	8.15	45.92	210	315	Average
2390	45.81	51.29	74	-28.19	32.29	8.15	45.92	210	315	Peak
2462	96.56	101.82			32.36	8.28	45.9	210	315	Average
2462	106.61	111.87			32.36	8.28	45.9	210	315	Peak
2483.5	48.85	54.04	54	-5.15	32.38	8.32	45.89	210	315	Average
2483.5	70.38	75.57	74	-3.62	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.9	39.38	54	-20.1	32.29	8.15	45.92	112	312	Average
2390	46.66	52.14	74	-27.34	32.29	8.15	45.92	112	312	Peak
2462	95.68	100.94			32.36	8.28	45.9	112	312	Average
2462	106.45	111.71			32.36	8.28	45.9	112	312	Peak
2483.5	50.9	56.09	54	-3.1	32.38	8.32	45.89	112	312	Average
2483.5	70.92	76.11	74	-3.08	32.38	8.32	45.89	112	312	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.99	56.47	54	-3.01	32.29	8.15	45.92	210	315	Average
2390	65.75	71.23	74	-8.25	32.29	8.15	45.92	210	315	Peak
2422	90.66	96.04			32.32	8.21	45.91	210	315	Average
2422	102.85	108.23			32.32	8.21	45.91	210	315	Peak
2483.5	36.16	41.35	54	-17.84	32.38	8.32	45.89	210	315	Average
2483.5	50.4	55.59	74	-23.6	32.38	8.32	45.89	210	315	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.8	57.28	54	-2.2	32.29	8.15	45.92	115	312	Average
2390	67.46	72.94	74	-6.54	32.29	8.15	45.92	115	312	Peak
2422	91.14	96.52			32.32	8.21	45.91	115	312	Average
2422	103.03	108.41			32.32	8.21	45.91	115	312	Peak
2483.5	36.13	41.32	54	-17.87	32.38	8.32	45.89	115	312	Average
2483.5	50.46	55.65	74	-23.54	32.38	8.32	45.89	115	312	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2422MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	40.78	46.26	54	-13.22	32.29	8.15	45.92	272	307	Average
2390	58.35	63.83	74	-15.65	32.29	8.15	45.92	272	307	Peak
2437	89.9	95.23			32.34	8.24	45.91	272	307	Average
2437	101.35	106.68			32.34	8.24	45.91	272	307	Peak
2483.5	45.83	51.02	54	-8.17	32.38	8.32	45.89	272	307	Average
2483.5	64.38	69.57	74	-9.62	32.38	8.32	45.89	272	307	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.03	48.51	54	-10.97	32.29	8.15	45.92	115	280	Average
2390	61.55	67.03	74	-12.45	32.29	8.15	45.92	115	280	Peak
2437	90.35	95.68			32.34	8.24	45.91	115	280	Average
2437	101.77	107.1			32.34	8.24	45.91	115	280	Peak
2483.5	45.22	50.41	54	-8.78	32.38	8.32	45.89	115	280	Average
2483.5	61.32	66.51	74	-12.68	32.38	8.32	45.89	115	280	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.45	39.93	54	-19.55	32.29	8.15	45.92	272	307	Average
2390	49.39	54.87	74	-24.61	32.29	8.15	45.92	272	307	Peak
2452	90.77	96.06			32.35	8.26	45.9	272	307	Average
2452	103.08	108.37			32.35	8.26	45.9	272	307	Peak
2483.5	50.91	56.1	54	-3.09	32.38	8.32	45.89	272	307	Average
2483.5	68.04	73.23	74	-5.96	32.38	8.32	45.89	272	307	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.41	40.89	54	-18.59	32.29	8.15	45.92	115	280	Average
2390	50.38	55.86	74	-23.62	32.29	8.15	45.92	115	280	Peak
2452	91.11	96.4			32.35	8.26	45.9	115	280	Average
2452	102.92	108.21			32.35	8.26	45.9	115	280	Peak
2483.5	49.69	54.88	54	-4.31	32.38	8.32	45.89	115	280	Average
2483.5	66.42	71.61	74	-7.58	32.38	8.32	45.89	115	280	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2452MHz: Fundamental frequency.

**BELOW 1GHz WORST-CASE DATA:**

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


BT-LE (GFSK)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
46.49	33.98	62.57	40	-6.02	7.8	1.03	37.42	100	114	QP
94.02	37.84	66.03	43.5	-5.66	7.34	1.49	37.02	100	336	QP
168.71	38.88	63.54	43.5	-4.62	10.07	1.99	36.72	100	295	QP
233.7	34.36	56.88	46	-11.64	11.65	2.36	36.53	100	57	QP
299.66	29.39	50.17	46	-16.61	13	2.72	36.5	100	271	QP
379.2	36.9	54.18	46	-9.1	16.33	3.06	36.67	100	198	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
46.49	33.47	62.06	40	-6.53	7.8	1.03	37.42	100	245	QP
139.61	39.5	66.54	43.5	-4	7.98	1.82	36.84	100	148	QP
205.57	35.63	59.61	43.5	-7.87	10.36	2.2	36.54	100	74	QP
288.02	38.36	59.34	46	-7.64	12.86	2.66	36.5	100	266	QP
378.23	25.33	42.65	46	-20.67	16.29	3.06	36.67	100	308	QP
506.27	27.04	42.01	46	-18.96	18.52	3.49	36.98	100	59	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.04	39.52	54	-19.96	32.29	8.15	45.92	282	308	Average
2390	47.04	52.52	74	-26.96	32.29	8.15	45.92	282	308	Peak
2402	91.74	97.19			32.3	8.17	45.92	282	308	Average
2402	96.93	102.38			32.3	8.17	45.92	282	308	Peak
2483.5	33.46	38.65	54	-20.54	32.38	8.32	45.89	282	308	Average
2483.5	46.56	51.75	74	-27.44	32.38	8.32	45.89	282	308	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34	39.48	54	-20	32.29	8.15	45.92	101	286	2390
2390	45.76	51.24	74	-28.24	32.29	8.15	45.92	101	286	2390
2402	92.21	97.66			32.3	8.17	45.92	101	286	2402
2402	97.15	102.6			32.3	8.17	45.92	101	286	2402
2483.5	33.77	38.96	54	-20.23	32.38	8.32	45.89	101	286	2483.5
2483.5	46.63	51.82	74	-27.37	32.38	8.32	45.89	101	286	2483.5

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.56	39.04	54	-20.44	32.29	8.15	45.92	282	308	Average
2390	46.05	51.53	74	-27.95	32.29	8.15	45.92	282	308	Peak
2440	93.69	99.02			32.34	8.24	45.91	282	308	Average
2440	98.61	103.94			32.34	8.24	45.91	282	308	Peak
2483.5	33.43	38.62	54	-20.57	32.38	8.32	45.89	282	308	Average
2483.5	46.16	51.35	74	-27.84	32.38	8.32	45.89	282	308	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.28	38.76	54	-20.72	32.29	8.15	45.92	115	286	Average
2390	50.05	55.53	74	-23.95	32.29	8.15	45.92	115	286	Peak
2440	93.31	98.64			32.34	8.24	45.91	115	286	Average
2440	98.39	103.72			32.34	8.24	45.91	115	286	Peak
2483.5	33.49	38.68	54	-20.51	32.38	8.32	45.89	115	286	Average
2483.5	46.82	52.01	74	-27.18	32.38	8.32	45.89	115	286	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.28	38.76	54	-20.72	32.29	8.15	45.92	270	308	Average
2390	46.67	52.15	74	-27.33	32.29	8.15	45.92	270	308	Peak
2480	95.42	100.63			32.38	8.31	45.9	270	308	Average
2480	100.58	105.79			32.38	8.31	45.9	270	308	Peak
2483.5	34.79	39.98	54	-19.21	32.38	8.32	45.89	270	308	Average
2483.5	51.66	56.85	74	-22.34	32.38	8.32	45.89	270	308	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.45	38.93	54	-20.55	32.29	8.15	45.92	111	286	Average
2390	52.35	57.83	74	-21.65	32.29	8.15	45.92	111	286	Peak
2480	94.53	99.74			32.38	8.31	45.9	111	286	Average
2480	99.75	104.96			32.38	8.31	45.9	111	286	Peak
2483.5	34.66	39.85	54	-19.34	32.38	8.32	45.89	111	286	Average
2483.5	51.23	56.42	74	-22.77	32.38	8.32	45.89	111	286	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



4.3 6 dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510523	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Mar. 01,17	Feb. 28,18
Power Sensor	ANRITSU	MA2411B	1339352	Mar. 01,17	Feb. 28,18

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

4.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

802.11b


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.55	0.5	PASS
6	2437	9.01	0.5	PASS
11	2462	9.03	0.5	PASS





802.11g


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.35	0.5	PASS
6	2437	16.39	0.5	PASS
11	2462	15.09	0.5	PASS





802.11n (20MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.57	0.5	PASS
6	2437	17.60	0.5	PASS
11	2462	16.55	0.5	PASS





802.11n (40MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	35.14	0.5	PASS
6	2437	35.45	0.5	PASS
9	2452	35.14	0.5	PASS





BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.69	0.5	PASS
19	2440	0.70	0.5	PASS
39	2480	0.70	0.5	PASS






4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

**4.4.7 TEST RESULTS****4.4.7.1 MAXIMUM PEAK OUTPUT POWER****802.11b**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	16.78	47.643	1	PASS
6	2437	15.94	39.264	1	PASS
11	2462	15.69	37.068	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	18.98	79.068	1	PASS
6	2437	19.58	90.782	1	PASS
11	2462	18.73	74.645	1	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	18.18	65.766	1	PASS
6	2437	18.29	67.453	1	PASS
11	2462	18.50	70.795	1	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
3	2422	16.86	48.529	1	PASS
6	2437	18.33	68.077	1	PASS
9	2452	18.23	66.527	1	PASS



BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	1.11	1.291	1	PASS
19	2440	2.48	1.770	1	PASS
39	2480	1.57	1.435	1	PASS

**4.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)**

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.95	N/A
6	2437	13.56	N/A
11	2462	13.84	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	12.25	N/A
6	2437	12.68	N/A
11	2462	12.56	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	11.28	N/A
6	2437	11.63	N/A
11	2462	11.58	N/A

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
3	2422	10.14	N/A
6	2437	10.98	N/A
9	2452	10.48	N/A



Test Report No.: RF170906W002-2

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	0.71	N/A
19	2440	2.14	N/A
39	2480	1.21	N/A



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.5.7 TEST RESULTS

802.11b


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-6.59	8	PASS
6	2437	-8.86	8	PASS
11	2462	-9.79	8	PASS





802.11g


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-11.33	8	PASS
6	2437	-11.61	8	PASS
11	2462	-11.01	8	PASS





802.11n (20MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-12.06	8	PASS
6	2437	-14.41	8	PASS
11	2462	-11.63	8	PASS





802.11n (40MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-16.77	8	PASS
6	2437	-16.44	8	PASS
9	2452	-15.05	8	PASS





BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-11.25	8	PASS
19	2440	-10.44	8	PASS
39	2480	-10.65	8	PASS






4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BUREAU
VERITAS


Test Report No.: RF170906W002-2

802.11b


CH 1



CH 6



CH 11







BUREAU
VERITAS

Test Report No.: RF170906W002-2

CH 1 Band Edge



CH 11 Band Edge






BUREAU
VERITAS


Test Report No.: RF170906W002-2

802.11g


CH 1



CH 6



CH 11







BUREAU
VERITAS

Test Report No.: RF170906W002-2

CH 1 Band Edge



CH 11 Band Edge







BUREAU
VERITAS



Test Report No.: RF170906W002-2

802.11n (20MHz)



CH 1



CH 6



CH 11







BUREAU
VERITAS

Test Report No.: RF170906W002-2

CH 1 Band Edge



CH 11 Band Edge







BUREAU
VERITAS



Test Report No.: RF170906W002-2

802.11n (40MHz)



CH 3



CH 6




CH 9





BUREAU
VERITAS

Test Report No.: RF170906W002-2







**BUREAU
VERITAS**



Test Report No.: RF170906W002-2

BT-LE (GFSK)



CH 0



CH 19



CH 39







BUREAU
VERITAS

Test Report No.: RF170906W002-2

CH 0 Band Edge



CH 39 Band Edge





Test Report No.: RF170906W002-2

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---