



Test Report No.: RF150512N006-5



FCC TEST REPORT (PART 27)

Product: ILIUM PAD L8
Model Name: ILIUM PAD L8
FCC ID: ZC4L8
Applicant: CORPORATIVO LANIX, S.A. DE C.V.
Address: CARRETERA INTERNACIONAL A NOGALES KM.8.5, SAN LUIS. HERMOSILLO, SONORA, MÉXICO. CP. 83160
Manufacturer: Foxda Technology Industrial(Shenzhen) Co., Ltd
1F of 1st Building&1F-3F of 2nd Building, Foxda Industrial
Address: Zone,North of Lanzhu Road,Pingshan New District,Shenzhen City,Guangdong Province,P.R. China
Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China
TEL: +86 769 8593 5656
FAX: +86 769 8593 1080
E-MAIL: customerservice.dg@cn.bureauveritas.com
Report No.: RF150512N006-5
Received Date: May 12, 2015
Test Date: May 12, 2015 ~ Jun. 04, 2015
Issued Date: Jun. 05, 2015

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 CERTIFICATION	5
2 SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	6
2.2 TEST SITE AND INSTRUMENTS	7
3 GENERAL INFORMATION.....	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 CONFIGURATION OF SYSTEM UNDER TEST	10
3.3 DESCRIPTION OF SUPPORT UNITS	11
3.4 DESCRIPTION OF TEST MODES	11
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
4 TEST TYPES AND RESULTS	15
4.1 OUTPUT POWER MEASUREMENT	15
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	15
4.1.2 TEST PROCEDURES	15
4.1.3 TEST SETUP	16
4.1.4 TEST RESULTS	17
4.2 FREQUENCY STABILITY MEASUREMENT	27
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	27
4.2.2 TEST PROCEDURE	27
4.2.3 TEST SETUP	27
4.2.4 TEST RESULTS	28
4.3 OCCUPIED BANDWIDTH MEASUREMENT	29
4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	29
4.3.2 TEST SETUP	29
4.3.3 TEST PROCEDURES	29
4.3.4 TEST RESULTS	30
4.4 PEAK TO AVERAGE RATIO	33
4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	33
4.4.2 TEST SETUP	33
4.4.3 TEST PROCEDURES	33
4.4.4 TEST RESULTS	34
4.5 BAND EDGE MEASUREMENT	37
4.5.1 LIMITS OF BAND EDGE MEASUREMENT	37
4.5.2 TEST SETUP	37
4.5.3 TEST PROCEDURES	37
4.5.4 TEST RESULTS	39
4.6 CONDUCTED SPURIOUS EMISSIONS	45
4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	45
4.6.2 TEST PROCEDURE	45
4.6.3 TEST SETUP	45
4.6.4 TEST RESULTS	46
4.7 RADIATED EMISSION MEASUREMENT	48
4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT	48
4.7.2 TEST PROCEDURES	48
4.7.3 DEVIATION FROM TEST STANDARD	48
4.7.4 TEST SETUP	49



Test Report No.: RF150512N006-5

4.7.5	TEST RESULTS	50
5	INFORMATION ON THE TESTING LABORATORIES	64
6	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	65



Test Report No.: RF150512N006-5

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150512N006-5	Original release	Jun. 05, 2015




Test Report No.: RF150512N006-5

1 CERTIFICATION

PRODUCT: ILIUM PAD L8
BRAND NAME: LANIX
MODEL NAME: ILIUM PAD L8
APPLICANT: CORPORATIVO LANIX, S.A. DE C.V.
TESTED: May 12, 2015 ~ Jun. 04, 2015
TEST SAMPLE: Production unit
TEST STANDARDS: **FCC Part 27, Subpart C, L**
FCC Part 2
ANSI C63.4-2003

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

TESTED BY :  , **DATE :** Jun. 05, 2015
Glyn He/ Project Engineer

APPROVED BY :  , **DATE :** Jun. 05, 2015
Sam Tung / Technical Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 27 & Part 2			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
2.1046 27.50(d)(4)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to average ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -43.02dB at 5220.29MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.74dB
	30MHz ~ 1GMHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU 26	100005	May 11,15	May 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 15
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 25, 14	Jul. 24, 15
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 30, 14	May 29, 16
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,15	Mar. 03, 16
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,14	Nov. 19,15
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 11,15	May 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 15
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Apr. 19,14	Apr. 18,16
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Spectrum Analyzer (10Hz-40GHz)	Rohde&Schwarz	FSV40	101003	Apr. 07,15	Apr. 06,16
Power Meter	Anritsu	ML2495A	1139001	Feb. 20,15	Feb. 19,16
Power Sensor	Anritsu	MA2411B	1126068	Feb. 20,15	Feb. 19,16
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 27,14	Oct. 26,15
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.04,14	Sep. 03,15
Oscilloscope	Agilent	DSO9254A	MY51260160	Oct. 17, 14	Oct. 16, 15
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 05,14	Nov. 04,15
Signal Generator	Agilent	N5183A	MY50140980	Nov. 05,14	Nov. 04,15
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Mar.13, 15	Mar.12, 16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 04,14	Sep. 03,15

- NOTE:** 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in Dongguan 966 Chamber.
3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 502831.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	ILIUM PAD L8	
MODEL NAME	ILIUM PAD L8	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.7Vdc (battery)	
MODULATION TECHNOLOGY	LTE Band 4	QPSK, 16QAM
FREQUENCY RANGE	LTE Band 4 Channel Bandwidth: 1.4MHz	1710.7MHz ~ 1754.3MHz
	LTE Band 4 Channel Bandwidth: 3MHz	1711.5MHz ~ 1753.5MHz
	LTE Band 4 Channel Bandwidth: 5MHz	1712.5MHz ~ 1752.5MHz
	LTE Band 4 Channel Bandwidth: 10MHz	1715.0MHz ~ 1750.0MHz
	LTE Band 4 Channel Bandwidth: 15MHz	1717.5MHz ~ 1747.5MHz
	LTE Band 4 Channel Bandwidth: 20MHz	1720.0MHz ~ 1745.0MHz
EMISSION DESIGNATOR	LTE Band 4 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
	LTE Band 4 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M68W7D
	LTE Band 4 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M49W7D
	LTE Band 4 Channel Bandwidth: 10MHz	QPSK: 8M94G7D
		16QAM: 8M97W7D
MAX. ERP/EIRP POWER	LTE Band 4 Channel Bandwidth: 1.4MHz	122mW
	LTE Band 4 Channel Bandwidth: 3MHz	112mW
	LTE Band 4 Channel Bandwidth: 5MHz	106mW
	LTE Band 4 Channel Bandwidth: 10MHz	134mW



**BUREAU
VERITAS**

Test Report No.: RF150512N006-5

	LTE Band 4 Channel Bandwidth: 15MHz	147mW
	LTE Band 4 Channel Bandwidth: 20MHz	124mW
ANTENNA TYPE	Fixed Internal antenna with 0dBi gain	
HW VERSION	V03	
SW VERSION	Android version 4.4.4; ILIUM PAD L8_TELCEL_SW_01	
I/O PORTS	Refer to user's manual	
DATA CABLE	USB cable: Unshielded, detachable, 0.8m	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	HJ
MODEL:	HJ-0501500-ZT
INPUT:	AC 100-240V, 250mA
OUTPUT:	DC 5V, 1500mA


3. The EUT matched the following USB cable:

USB CABLE	
BRAND:	ACH
MODEL:	USB 2.0 AM TO Micro B 5P
SIGNAL LINE:	0.8 METER


4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.R.P./E.I.R.P TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X-plane for ERP/EIRP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with LTE link
B	EUT + Battery + USB Cable with LTE link

LTE BAND 4

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	19957 to 20393	19957	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
		19965 to 20385	20393	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		19975 to 20375	19965	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
		20000 to 20350	20385	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		20025 to 20325	19975	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
		20050 to 20300	20375	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
		20025 to 20325	20350	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset

B	BAND EDGE	20025 to 20325	20025	15MHz	QPSK	1 RB / 0 RB Offset
			20325	15MHz	QPSK	75 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK	1 RB / 74 RB Offset
			20300	20MHz	QPSK	75 RB / 0 RB Offset
			20050	20MHz	QPSK	1 RB / 0 RB Offset
			20300	20MHz	QPSK	100 RB / 0 RB Offset
B	CONDCUDETED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP(ERP)	24deg. C, 60%RH	3.7Vdc from Battery	Blue Zheng
FREQUENCY STABILITY	24deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
OCCUPIED BANDWIDTH	24deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
PEAK TO AVERAGE RATIO	24deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
BAND EDGE	24deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
CONDCUDETED EMISSION	24deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
RADIATED EMISSION	24deg. C, 60%RH	5Vdc from adapter	Blue Zheng



Test Report No.: RF150512N006-5

3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 699-716 MHz band are limited to 3 watts ERP.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:


- a. The EUT was set up for the maximum power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range). RBW and VBW is 10MHz for LTE.
- b. E.I.R.P power measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$
- e. $E.R.P = E.I.R.P - 2.15 \text{ dB}$

CONDUCTED POWER MEASUREMENT:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 TEST RESULTS

AVERAGE CONDUCTED OUTPUT POWER (dBm)

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19957	Mid CH 20175	High CH 20393	MPR
				Frequency 1710.7 MHz	Frequency 1732.5 MHz	Frequency 1754.3 MHz	
1.4MHz	QPSK	1	0	23.37	22.95	22.68	0
		1	2	23.28	22.56	22.58	0
		1	5	22.83	22.55	22.61	0
		3	0	22.96	22.64	22.41	0
		3	1	22.86	22.5	22.36	0
		3	3	22.8	22.32	22.36	0
		6	0	21.85	21.55	21.42	1
	16QAM	1	0	21.93	21.87	21.51	1
		1	2	21.87	21.73	21.59	1
		1	5	21.86	22	21.72	1
		3	0	22.01	21.61	21.46	1
		3	1	21.94	21.49	21.43	1
		3	3	21.74	21.28	21.41	1
		6	0	20.95	20.55	20.39	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19965	Mid CH 20175	High CH 20385	MPR
				Frequency 1711.5 MHz	Frequency 1732.5 MHz	Frequency 1753.5 MHz	
3 MHz	QPSK	1	0	23.41	22.99	22.72	0
		1	7	23.32	22.6	22.62	0
		1	14	22.87	22.59	22.65	0
		8	0	22	21.68	21.45	1
		8	3	21.9	21.54	21.4	1
		8	7	21.84	21.36	21.4	1
		15	0	21.89	21.59	21.46	1
	16QAM	1	0	21.97	21.91	21.55	1
		1	7	21.91	21.77	21.63	1
		1	14	21.9	22.04	21.76	1
		8	0	21.05	20.65	20.5	2
		8	3	20.98	20.53	20.47	2
		8	7	20.78	20.32	20.45	2
		15	0	20.99	20.59	20.43	2
BW	Modulation	RB Size	RB Offset	Low CH 19975	Mid CH 20175	High CH 20375	MPR
				Frequency 1712.5 MHz	Frequency 1732.5 MHz	Frequency 1752.5 MHz	
5 MHz	QPSK	1	0	23.44	23.02	22.75	0
		1	12	23.35	22.63	22.65	0
		1	24	22.9	22.62	22.68	0
		12	0	22.03	21.71	21.48	1
		12	6	21.93	21.57	21.43	1
		12	13	21.87	21.39	21.43	1
		25	0	21.92	21.62	21.49	1
	16QAM	1	0	22	21.94	21.58	1
		1	12	21.94	21.8	21.66	1
		1	24	21.93	22.07	21.79	1
		12	0	21.08	20.68	20.53	2
		12	6	21.01	20.56	20.5	2
		12	13	20.81	20.35	20.48	2
		25	0	21.02	20.62	20.46	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20000	Mid CH 20175	High CH 20350	MPR
				Frequency 1715 MHz	Frequency 1732.5 MHz	Frequency 1750 MHz	
10 MHz	QPSK	1	0	23.49	23.07	22.8	0
		1	24	23.4	22.68	22.7	0
		1	49	22.95	22.67	22.73	0
		25	0	22.08	21.76	21.53	1
		25	12	21.98	21.62	21.48	1
		25	25	21.92	21.44	21.48	1
		50	0	21.97	21.67	21.54	1
	16QAM	1	0	22.05	21.99	21.63	1
		1	24	21.99	21.85	21.71	1
		1	49	21.98	22.12	21.84	1
		25	0	21.13	20.73	20.58	2
		25	12	21.06	20.61	20.55	2
		25	25	20.86	20.4	20.53	2
		50	0	21.07	20.67	20.51	2
BW	Modulation	RB Size	RB Offset	Low CH 20025	Mid CH 20175	High CH 20325	MPR
				Frequency 1717.5 MHz	Frequency 1732.5 MHz	Frequency 1747.5 MHz	
15 MHz	QPSK	1	0	23.55	23.13	22.86	0
		1	37	23.46	22.74	22.76	0
		1	74	23.01	22.73	22.79	0
		36	0	22.14	21.82	21.59	1
		36	19	22.04	21.68	21.54	1
		36	39	21.98	21.5	21.54	1
		75	0	22.03	21.73	21.6	1
	16QAM	1	0	22.11	22.05	21.69	1
		1	37	22.05	21.91	21.77	1
		1	74	22.04	22.18	21.9	1
		36	0	21.19	20.79	20.64	2
		36	19	21.12	20.67	20.61	2
		36	39	20.92	20.46	20.59	2
		75	0	21.13	20.73	20.57	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20050	Mid CH 20175	High CH 20300	MPR
				Frequency 1720 MHz	Frequency 1732.5 MHz	Frequency 1745 MHz	
20MHz	QPSK	1	0	23.59	23.17	22.9	0
		1	50	23.5	22.78	22.8	0
		1	99	23.05	22.77	22.83	0
		50	0	22.18	21.86	21.63	1
		50	25	22.08	21.72	21.58	1
		50	50	22.02	21.54	21.58	1
		100	0	22.07	21.77	21.64	1
	16QAM	1	0	22.15	22.09	21.73	1
		1	50	22.09	21.95	21.81	1
		1	99	22.08	22.22	21.94	1
		50	0	21.23	20.83	20.68	2
		50	25	21.16	20.71	20.65	2
		50	50	20.96	20.5	20.63	2
		100	0	21.17	20.77	20.61	2

EIRP

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-20.01	40.25	20.24	105.68	H	1
20175	1732.5	-20.17	40.86	20.69	117.22	H	1
20393	1754.3	-20.36	41.22	20.86	121.90	H	1
19957	1710.7	-26.34	44.36	18.02	63.39	V	1
20175	1732.5	-26.45	44.08	17.63	57.94	V	1
20393	1754.3	-26.64	44.91	18.27	67.14	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-21.13	40.25	19.12	81.66	H	1
20175	1732.5	-21.34	40.86	19.52	89.54	H	1
20393	1754.3	-21.57	41.22	19.65	92.26	H	1
19957	1710.7	-27.33	44.36	17.03	50.47	V	1
20175	1732.5	-27.24	44.08	16.84	48.31	V	1
20393	1754.3	-27.02	44.91	17.89	61.52	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)



**BUREAU
VERITAS**

Test Report No.: RF150512N006-5

LTE BAND 4

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-20.33	40.18	19.85	96.61	H	1
20175	1732.5	-20.55	40.86	20.31	107.40	H	1
20385	1753.5	-20.67	41.15	20.48	111.69	H	1
19965	1711.5	-26.24	44.29	18.05	63.83	V	1
20175	1732.5	-26.37	44.08	17.71	59.02	V	1
20385	1753.5	-26.64	44.83	18.19	65.92	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-21.42	40.18	18.76	75.16	H	1
20175	1732.5	-21.58	40.86	19.28	84.72	H	1
20385	1753.5	-21.64	41.15	19.51	89.33	H	1
19965	1711.5	-27.62	44.29	16.67	46.45	V	1
20175	1732.5	-27.41	44.08	16.67	46.45	V	1
20385	1753.5	-27.25	44.83	17.58	57.28	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)



**BUREAU
VERITAS**

Test Report No.: RF150512N006-5

LTE BAND 4

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-20.45	40.34	19.89	97.50	H	1
20175	1732.5	-20.62	40.86	20.24	105.68	H	1
20375	1752.5	-20.75	40.96	20.21	104.95	H	1
19975	1712.5	-26.55	44.19	17.64	58.08	V	1
20175	1732.5	-26.41	44.08	17.67	58.48	V	1
20375	1752.5	-26.32	44.82	18.50	70.79	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-21.11	40.34	19.23	83.75	H	1
20175	1732.5	-21.24	40.86	19.62	91.62	H	1
20375	1752.5	-21.38	40.96	19.58	90.78	H	1
19975	1712.5	-27.14	44.19	17.05	50.70	V	1
20175	1732.5	-27.32	44.08	16.76	47.42	V	1
20375	1752.5	-27.97	44.82	16.85	48.42	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)



**BUREAU
VERITAS**

Test Report No.: RF150512N006-5

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-20.11	41.10	20.99	125.60	H	1
20175	1732.5	-19.96	40.86	20.90	123.03	H	1
20350	1750.0	-19.87	41.14	21.27	133.97	H	1
20000	1715.0	-25.36	44.16	18.80	75.86	V	1
20175	1732.5	-25.46	44.08	18.62	72.78	V	1
20350	1750.0	-25.76	44.73	18.97	78.89	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-21.36	41.10	19.74	94.19	H	1
20175	1732.5	-21.45	40.86	19.41	87.30	H	1
20350	1750.0	-21.64	41.14	19.50	89.13	H	1
20000	1715.0	-26.87	44.16	17.29	53.58	V	1
20175	1732.5	-26.62	44.08	17.46	55.72	V	1
20350	1750.0	-26.34	44.73	18.39	69.02	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)



**BUREAU
VERITAS**

Test Report No.: RF150512N006-5

LTE BAND 4

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-20.44	41.35	20.91	123.31	H	1
20175	1732.5	-20.32	41.16	20.84	121.34	H	1
20325	1747.5	-20.12	41.78	21.66	146.55	H	1
20025	1717.5	-25.99	44.08	18.09	64.42	V	1
20175	1732.5	-25.68	44.08	18.40	69.18	V	1
20325	1747.5	-25.46	44.87	19.41	87.30	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-21.34	41.35	20.01	100.23	H	1
20175	1732.5	-21.45	41.16	19.71	93.54	H	1
20325	1747.5	-21.24	41.78	20.54	113.24	H	1
20025	1717.5	-26.62	44.08	17.46	55.72	V	1
20175	1732.5	-26.47	44.08	17.61	57.68	V	1
20325	1747.5	-26.69	44.87	18.18	65.77	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)



**BUREAU
VERITAS**

Test Report No.: RF150512N006-5

LTE BAND 4

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-20.44	41.04	20.60	114.82	H	1
20175	1732.5	-20.53	40.86	20.33	107.89	H	1
20300	1745.0	-20.64	41.59	20.95	124.45	H	1
20050	1720.0	-25.87	43.26	17.39	54.83	V	1
20175	1732.5	-25.64	44.08	18.44	69.82	V	1
20300	1745.0	-25.43	44.33	18.90	77.62	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-21.24	41.04	19.80	95.50	H	1
20175	1732.5	-21.12	40.86	19.74	94.19	H	1
20300	1745.0	-20.98	41.59	20.61	115.08	H	1
20050	1720.0	-26.14	43.26	17.12	51.52	V	1
20175	1732.5	-26.36	44.08	17.72	59.16	V	1
20300	1745.0	-26.64	44.33	17.69	58.75	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

LTE BAND 4

AFC FREQUENCY ERROR vs. VOLTAGE							
VOLTAGE (Volts)	FREQUENCY ERROR (ppm)						LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
3.7	-0.007	-0.003	-0.003	0.002	-0.007	0.001	2.5
3.6	-0.004	-0.007	0.004	-0.001	-0.003	0.003	2.5
4.2	-0.002	-0.002	0.005	-0.004	0.002	0.005	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.2Vdc.


AFC FREQUENCY ERROR vs. TEMPERATURE							
TEMP. (°C)	FREQUENCY ERROR (ppm)						LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
-30	-0.009	-0.005	-0.007	-0.007	-0.008	-0.005	2.5
-20	-0.008	-0.004	-0.007	-0.005	-0.007	-0.005	2.5
-10	-0.007	-0.003	-0.006	-0.004	-0.006	-0.004	2.5
0	-0.006	-0.004	-0.005	-0.003	-0.004	-0.004	2.5
10	-0.005	-0.003	-0.004	-0.004	-0.003	-0.004	2.5
20	-0.003	-0.002	-0.004	0.002	-0.003	-0.003	2.5
30	0.002	0.002	0.001	0.003	0.002	0.001	2.5
40	0.003	0.003	0.002	0.003	0.002	0.002	2.5
50	0.003	0.004	0.003	0.004	0.003	0.003	2.5
60	0.004	0.004	0.004	0.005	0.005	0.004	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.3.2 TEST SETUP




4.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.4 TEST RESULTS


LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.088	1.082	19965	1711.5	2.692	2.685
20175	1732.5	1.088	1.082	20175	1732.5	2.684	2.677
20393	1754.3	1.088	1.085	20385	1753.5	2.684	2.677




LTE BAND 4

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.486	4.486	20000	1715	8.944	8.944
20175	1732.5	4.471	4.471	20175	1732.5	8.943	8.973
20375	1752.5	4.486	4.471	20350	1750	8.943	8.972



LTE BAND 4

CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.415	13.415	20050	1720	17.887	17.829
20175	1732.5	13.415	13.415	20175	1732.5	17.887	17.829
20325	1747.5	13.415	13.371	20300	1745	17.887	17.829




4.4 PEAK TO AVERAGE RATIO

4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.


4.4.4 TEST RESULTS

LTE BAND 4


CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	3.68	4.70	19965	1711.5	3.88	4.72
20175	1732.5	5.30	6.00	20175	1732.5	5.19	6.06
20393	1754.3	4.20	4.99	20385	1753.5	4.29	5.04



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	3.86	4.81	20000	1715	3.94	4.72
20175	1732.5	4.90	5.88	20175	1732.5	5.30	5.94
20375	1752.5	4.29	5.28	20350	1750	4.43	5.28



CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	4.14	4.99	20050	1720	4.35	5.28
20175	1732.5	5.13	5.97	20175	1732.5	4.84	5.80
20325	1747.5	4.52	5.45	20300	1745	4.64	5.54




4.5 BAND EDGE MEASUREMENT

4.5.1 LIMITS OF BAND EDGE MEASUREMENT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

4.5.2 TEST SETUP



4.5.3 TEST PROCEDURES

- The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 20kHz and VB of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)
- The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz. (LTE bandwidth 3MHz)

- e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 50kHz and VB of the spectrum is 200kHz. (LTE bandwidth 5MHz)
- f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz. (LTE bandwidth 10MHz)
- g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 15MHz)
- h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 20MHz)
- i. Record the max trace plot into the test report.




BUREAU
VERITAS

Test Report No.: RF150512N006-5

4.5.4 TEST RESULTS

LTE BAND 4




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

LTE BAND 4






BUREAU
VERITAS

Test Report No.: RF150512N006-5

LTE BAND 4




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

LTE BAND 4




LTE BAND 4



LTE BAND 4

Channel Bandwidth: 20MHz



4.6 CONDUCTED SPURIOUS EMISSIONS


4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm

4.6.2 TEST PROCEDURE


- The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.
- Measuring frequency range is from 30 MHz to 19.1GHz for LTE Band 4 and 30 MHz to 9GHz for LTE Band 12&17. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.3 TEST SETUP




4.6.4 TEST RESULTS


LTE BAND 4



LTE BAND 4



LTE BAND 4



4.7 RADIATED EMISSION MEASUREMENT

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm

4.7.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}.$

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 DEVIATION FROM TEST STANDARD

No deviation

4.7.4 TEST SETUP




For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA


LTE Band 4:

MODE	TX channel20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	30.00	-12.55	-78.30	-90.85	-13.00	-77.85	100	0
2	82.01	-23.15	-72.51	-95.66	-13.00	-82.66	100	0
3	184.84	-20.50	-72.03	-92.53	-13.00	-79.53	100	0
4	259.14	-15.67	-71.38	-87.05	-13.00	-74.05	100	0
5	419.41	-10.87	-74.71	-85.58	-13.00	-72.58	100	0
* 6	533.28	-7.56	-69.91	-77.47	-13.00	-64.47	100	0

MODE	TX channel20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			




No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
*	1	-12.55	-65.47	-78.02	-13.00	-65.02	100	0
	2	-19.01	-73.57	-92.58	-13.00	-79.58	100	0
	3	-20.84	-73.96	-94.80	-13.00	-81.80	100	0
	4	-12.50	-76.37	-88.87	-13.00	-75.87	100	0
	5	-10.87	-75.18	-86.05	-13.00	-73.05	100	0
	6	-6.12	-78.58	-84.70	-13.00	-71.70	100	0

ABOVE 1GHz

LTE BAND 4


CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3478.26 (PK)	5.90	-67.64	-61.74	-13.00	-48.74	100	0
* 2	5157.97 (PK)	8.98	-67.01	-58.03	-13.00	-45.03	100	0


MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3478.26 (PK)	5.90	-67.65	-61.75	-13.00	-48.75	100	0
* 2	5213.04 (PK)	9.10	-65.71	-56.61	-13.00	-43.61	100	0


CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3505.80 (PK)	5.95	-67.41	-61.46	-13.00	-48.46	100	0
* 2	5185.51 (PK)	9.04	-67.50	-58.46	-13.00	-45.46	100	0


MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3505.80 (PK)	5.95	-68.06	-62.11	-13.00	-49.11	100	0
* 2	5213.04 (PK)	9.10	-66.15	-57.05	-13.00	-44.05	100	0


CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3450.72 (PK)	5.85	-67.15	-61.30	-13.00	-48.30	100	0
* 2	5185.51 (PK)	9.04	-66.36	-57.32	-13.00	-44.32	100	0


MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3450.72 (PK)	5.85	-66.17	-60.32	-13.00	-47.32	100	0
* 2	5185.51 (PK)	9.04	-66.18	-57.14	-13.00	-44.14	100	0


CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3486.96 (PK)	5.92	-66.36	-60.44	-13.00	-47.44	100	0
* 2	5220.29 (PK)	9.12	-65.14	-56.02	-13.00	-43.02	100	0


MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.		Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
		MHz	dB	dBm	dBm	dBm	dB	cm	deg
	1	3486.96 (PK)	5.92	-66.21	-60.29	-13.00	-47.29	100	0
*	2	5144.93 (PK)	8.95	-65.05	-56.10	-13.00	-43.10	100	0


CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3450.72 (PK)	5.85	-65.73	-59.88	-13.00	-46.88	100	0
* 2	5185.51 (PK)	9.04	-65.61	-56.57	-13.00	-43.57	100	0


MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3450.72 (PK)	5.85	-67.17	-61.32	-13.00	-48.32	100	0
* 2	5157.97 (PK)	8.98	-66.46	-57.48	-13.00	-44.48	100	0


CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3486.96 (PK)	5.92	-67.28	-61.36	-13.00	-48.36	100	0
* 2	5107.25 (PK)	8.86	-65.81	-56.95	-13.00	-43.95	100	0

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table	
							cm	deg
1	3478.26 (PK)	5.90	-66.82	-60.92	-13.00	-47.92	100	0
* 2	5185.51 (PK)	9.04	-67.06	-58.02	-13.00	-45.02	100	0



BUREAU
VERITAS

Test Report No.: RF150512N006-5

5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch, were founded in 2002 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Dongguan EMC/RF Lab:

Tel: +86-769-85935656

Fax: +86-769-85931080

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: RF150512N006-5

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---