



TEST REPORT

FCC ID: ZC8S321NETWORK

Applicant : Hemisphere GNSS Inc.

Address : 8515 E Anderson Dr, Scottsdale, AZ 85255, USA

Equipment under Test (EUT):

Name : GNSS Survey Receiver

Model : S321 Network , BRx6 Network

In Accordance with: FCC PART 15, SUBPART C: 2015 (Section 15.247)
ANSI C63.10:2013

Report No : T1851403 16

Date of Test : September 22- November 16, 2015

Date of Issue : November 16, 2015

Test Result : PASS

Test Result: **PASS**

In the configuration tested, the EUT complied with the standards specified above

Authorized Signature

(Mark Zhu)

General Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Alpha Product Testing Co., Ltd. Or test done by Shenzhen Alpha Product Testing Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Alpha Product Testing Co., Ltd. Approvals in writing.

TABLE OF CONTENT

| Description | Page |
|---|-----------|
| 1 General Information----- | 5 |
| 1.1 Description of Device (EUT)----- | 5 |
| 1.2 Description of Test Facility----- | 6 |
| 2 EMC Equipment List ----- | 6 |
| 3 Test Procedure ----- | 7 |
| 4 Summary of Measurement ----- | 8 |
| 4.1 Summary of test result ----- | 8 |
| 4.2 Test connection----- | 8 |
| 4.3 Assistant equipment used for test----- | 8 |
| 4.4 Test mode ----- | 9 |
| 4.5 Channel list ----- | 9 |
| 4.6 Test Conditions----- | 9 |
| 4.7 Measurement Uncertainty (95% confidence levels, k=2)----- | 10 |
| 5 Spurious Emission ----- | 11 |
| 5.1 Radiation Emission ----- | 11 |
| 5.1.1 Radiation Emission Limits(15.209) ----- | 11 |
| 5.1.2 Test Setup----- | 11 |
| 5.1.3 Test Procedure----- | 13 |
| 5.1.4 Test Equipment Setting For emission test Result----- | 13 |
| 5.1.5 Test Condition----- | 14 |
| 5.1.6 Test Result ----- | 14 |
| 6 POWER LINE CONDUCTED EMISSION ----- | 29 |
| 6.1 Conducted Emission Limits(15.207) ----- | 29 |
| 6.2 Test Setup----- | 29 |
| 6.3 Test Procedure----- | 30 |
| 6.4 Test Results----- | 30 |
| 7 Conducted Maximum Output Power ----- | 31 |
| 7.1 Test limit ----- | 31 |
| 7.2 Test Procedure----- | 31 |
| 7.3 Test Setup----- | 31 |
| 7.4 Test Results----- | 31 |
| 8 PEAK POWER SPECTRAL DENSITY ----- | 33 |
| 8.1 Test limit ----- | 33 |
| 8.2 Method of measurement ----- | 33 |
| 8.3 Test Setup----- | 33 |
| 8.4 Test Results----- | 34 |
| 9 Bandwidth ----- | 41 |
| 9.1 Test limit ----- | 41 |
| 9.2 Method of measurement ----- | 41 |
| 9.3 Test Setup----- | 41 |
| 9.4 Test Results----- | 41 |
| 10 Band Edge Check ----- | 49 |
| 10.1 Test limit ----- | 49 |
| 10.2 Test Procedure----- | 49 |
| 10.3 Test Setup----- | 49 |

| | | |
|-----------|-------------------------------------|-----------|
| 10.4 | Test Result ----- | 49 |
| 11 | Antenna Requirement ----- | 62 |
| 11.1 | Standard Requirement----- | 62 |
| 11.2 | Antenna Connected Construction----- | 62 |
| 11.3 | Result----- | 62 |
| 12 | Test setup photo----- | 63 |

TEST REPORT VERIFICATION

Applicant : Hemisphere GNSS Inc.
Manufacturer : Hemisphere GNSS Inc.
EUT Description : GNSS Survey Receiver

(A) Model No. : S321 Network , BRx6 Network
(B) Trademark : N/A
(C) Ratings Supply : DC 10.8V from internal battery or external battery
(D) Test Voltage : DC 10.8V from internal battery

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C 2014, ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the Part 15C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:


Eric Huang
Test Engineer

.....

.....

Approved by (name + signature).....:

Simple Guan
Project Manager

.....

.....

Date of issue.....

November 16, 2015

1 General Information

1.1 Description of Device (EUT)

Trade Name : N/A

EUT : GNSS Survey Receiver

Model No. : S321 Network , BRx6 Network

DIFF : Only differ in model number.

Antenna Type : Integrated Antenna, Maximum Gain is 3.92 dBi

Operation : IEEE 802.11b/g: 2412MHz-2462MHz
Frequency : IEEE 802.11n HT20: 2412MHz-2462MHz
IEEE 802.11n HT40: 2422MHz-2452MHz
IEEE 802.11b/g: 11Channels

Channel number : IEEE 802.11n HT20: 11 Channels
IEEE 802.11n HT40: 7 Channels
IEEE 802.11b: DSSS (CCK,DQPSK,DBPSK)

Modulation type : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11n :OFDM (64QAM, 16QAM, QPSK, BPSK)

Power Supply : DC 10.8V from internal battery or external battery

Adapter : PSAA30R-150

Applicant : Hemisphere GNSS Inc.

Address : 8515 E Anderson Dr, Scottsdale, AZ 85255, USA

Manufacturer : Hemisphere GNSS Inc.

Address : 8515 E Anderson Dr, Scottsdale, AZ 85255, USA

1.2 Description of Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building B, East Area of Nanchang Second, Industrial Zone, Gushu 2nd Road,
Bao'an, Shenzhen, China

August 11, 2014 File on Federal Communication Commission
Registration Number: 203110

July 18, 2014 Certificated by IC
Registration Number: 12135A

2 EMC Equipment List

| Equipment | Manufacture | Model No. | Serial No. | Last cal. | Cal Interval |
|------------------------|--------------|-------------------------|-------------------|------------|--------------|
| 3m Semi-Anechoic | ETS-LINDGREN | N/A | SEL0017 | 2015.01.19 | 1Year |
| Spectrum analyzer | Agilent | E4407B | MY46185649 | 2015.01.19 | 1Year |
| Receiver | R&S | ESCI | 1166.5950K03-1011 | 2015.01.19 | 1Year |
| Receiver | R&S | ESCI | 101202 | 2015.01.19 | 1Year |
| Bilog Antenna | Schwarzbeck | VULB 9168 | VULB9168-438 | 2015.01.21 | 1Year |
| Horn Antenna | EMCO | 3115 | 640201028-06 | 2015.01.21 | 1Year |
| Active Loop Antenna | Beijing Daze | ZN30900A | SEL0097 | 2015.01.21 | 1Year |
| Cable | Resenberger | N/A | No.1 | 2015.01.19 | 1Year |
| Cable | SCHWARZBECK | N/A | No.2 | 2015.01.19 | 1Year |
| Cable | SCHWARZBECK | N/A | No.3 | 2015.01.19 | 1Year |
| Pre-amplifier | Schwarzbeck | BBV9743 | 9743-019 | 2015.01.19 | 1Year |
| Pre-amplifier | R&S | AFS33-18002650-30-8P-44 | SEL0080 | 2015.01.19 | 1Year |
| Base station | Agilent | E5515C | GB44300243 | 2015.01.19 | 1 Year |
| Temperature controller | Terchy | MHQ | 120 | 2015.01.19 | 1Year |

| | | | | | |
|------------------|---------------|----------|------------|------------|--------|
| Power divider | Anritsu | K240C | 020346 | 2015.01.19 | 1 Year |
| Signal Generator | HP | 83732B | VS3449051 | 2015.01.19 | 1 Year |
| Power Meter | Anritsu | ML2487A | 6K00001491 | 2015.01.19 | 1 Year |
| Power sensor | Anritsu | ML2491A | 32516 | 2015.01.19 | 1 Year |
| L.I.S.N.#1 | Schwarzbeck | NSLK8126 | 8126466 | 2016.01.19 | 1 Year |
| L.I.S.N.#2 | ROHDE&SCHWARZ | ENV216 | 101043 | 2016.01.19 | 1 Year |

3 Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The test procedure used was ANSI Standard ANSI C63.10:2013 using a 50 u H LISN. Both Lines were observed. The bandwidth of the receiver was 10 kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25°C with a humidity of 58%.

RADIATION INTERFERENCE: The test procedure used was ANSI Standard ANSI C63.10:2013 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3MHz above 1 GHz. The ambient temperature of the EUT was 25°C with a humidity of 58%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS

33.20 dBuV + 10.36 dB + 0.9 dB = 44.46 dBuV/m @ 3m

ANSI STANDARD ANSI C63.10: 2013 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard ANSI C63.10:2013 with the EUT 40 cm from the vertical ground wall.


4 Summary of Measurement

4.1 Summary of test result

| Test Item | Test Requirement | Standards Paragraph | Result |
|---------------------|------------------|-----------------------|------------|
| Spurious Emission | FCC PART 15:2014 | Section 15.247&15.209 | Compliance |
| Conduction Emission | FCC PART 15:2014 | Section 15.207 | Compliance |
| Bandwidth Test | FCC PART 15:2014 | Section 15.247 | Compliance |
| Peak Power | FCC PART 15:2014 | Section 15.247 | Compliance |
| Power Density | FCC PART 15:2014 | Section 15.247 | Compliance |
| Band Edge | FCC PART 15:2014 | Section 15.247 | Compliance |
| Antenna Requirement | FCC PART 15:2014 | Section 15.203 | Compliance |

Note: The EUT has been tested as an independent unit, and continual transmitting in maximum power (The adapter be used during Test)

4.2 Test connection



4.3 Assistant equipment used for test

| | | |
|--------------|---|----------------------------|
| Description | : | Adapter |
| Manufacturer | : | NIL |
| Model No. | : | PSAA30R-150 |
| Input | : | AC 100-240V, 50-60Hz, 0.8A |
| Output | : | DC 15V, 2A |

4.4 Test mode

| Duty cycle :100% Keeping TX | | | |
|---|-------------------------------|-------------|--------------------|
| Mode | data rate (Mbps)(see Note) | Channel | Frequency (MHz) |
| IEEE 802.11b | 1 | Low :CH1 | 2412 |
| | 1 | Middle: CH6 | 2437 |
| | 1 | High: CH11 | 2462 |
| IEEE 802.11g | 6 | Low :CH1 | 2412 |
| | 6 | Middle: CH6 | 2437 |
| | 6 | High: CH11 | 2462 |
| IEEE 802.11 n/HT20 with 2.4G | 6.5 | Low :CH1 | 2412 |
| | 6.5 | Middle: CH6 | 2437 |
| | 6.5 | High: CH11 | 2462 |
| IEEE 802.11 n/HT40 with 2.4G | 13.5 | Low :CH3 | 2422 |
| | 13.5 | Middle:CH6 | 2437 |
| | 13.5 | High:CH9 | 2452 |
| Note: According exploratory test, EUT will have maximum output power in those data rate. so those data rate were used for all test. | | | |

4.5 Channel list

| For IEEE 802.11b/g and IEEE 802.11n/HT20 with 2.4G | | | | | |
|--|--------------------|---------|--------------------|---------|--------------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| CH1 | 2412 | CH5 | 2432 | CH9 | 2452 |
| CH2 | 2417 | CH6 | 2437 | CH10 | 2457 |
| CH3 | 2422 | CH7 | 2442 | CH11 | 2462 |
| CH4 | 2427 | CH8 | 2447 | | |

| For IEEE 802.11n/HT40 with 2.4G | | | | | |
|---------------------------------|--------------------|---------|--------------------|---------|--------------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| CH1 | / | CH5 | 2432 | CH9 | 2452 |
| CH2 | / | CH6 | 2437 | / | / |
| CH3 | 2422 | CH7 | 2442 | / | / |
| CH4 | 2427 | CH8 | 2447 | / | / |

4.6 Test Conditions

| | |
|-------------------|-----------|
| Temperature range | 21-25°C |
| Humidity range | 40-75% |
| Pressure range | 86-106kPa |

4.7 Measurement Uncertainty (95% confidence levels, k=2)

| Item | MU | Remark |
|--|--------------------|-------------|
| Uncertainty for Power point Conducted Emissions Test | 2.42dB | |
| Uncertainty for Radiation Emission test in 3m chamber (below 30MHz) | 2.13 dB | Polarize: V |
| | 2.57dB | Polarize: H |
| Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz) | 3.54dB | Polarize: V |
| | 4.1dB | Polarize: H |
| Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz) | 2.08dB | Polarize: H |
| | 2.56dB | Polarize: V |
| Uncertainty for radio frequency | 1×10^{-9} | |
| Uncertainty for conducted RF Power | 0.65dB | |
| Uncertainty for temperature | 0.2°C | |
| Uncertainty for humidity | 1% | |
| Uncertainty for DC and low frequency voltages | 0.06% | |

5 Spurious Emission

5.1 Radiation Emission

5.1.1 Radiation Emission Limits(15.209)

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |


Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

NOTE:


- a) The tighter limit applies at the band edges.
- b) $\text{Emission Level(dB uV/m)} = 20 \log \text{Emission Level(uv/m)}$

5.1.2 Test Setup


See the next page



Below 30 MHz Test Setup



Above 30 MHz Test Setup



Above 1 GHz Test Setup

5.1.3 Test Procedure

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation
- The Test antenna shall vary between 1m and 4m, both Horizontal and Vertical antennas are set of make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Quasi Peak Detector mode premeasured
- If Peak value comply with QP limit below 1GHz.The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.
- For the actual test configuration, please see the test setup photo.

5.1.4 Test Equipment Setting For emission test Result

| | | |
|--------------|------------|------------|
| 9KHz~150KHz | RBW 200Hz | VBW1KHz |
| 150KHz~30MHz | RBW 9KHz | VBW 30KHz |
| 30MHz~1GHz | RBW 120KHz | VBW 300KHz |
| Above 1GHz | RBW 1MHz | VBW 3MHz |

5.1.5 Test Condition

Continual transmitting in maximum power.

5.1.6 Test Result


We have scanned the 9 kHz from 25 GHz to the EUT.

Detailed information please see the following page.

From 9 kHz to 30MHz: Conclusion: PASS


Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

H:



Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

V:



Condition : FCC PART 15 B 3m POL: VERTICAL
 EUT : S321 GNSS Smart Antenna
 Model No : 750-0181-0
 Test Mode : Wifi mode
 Power : DC 5V From PC AC 120V/60Hz
 Test Engineer :
 Remark :
 Temp : 24.2°C
 Hum : 54%

| Item | Freq MHz | Read Level dBuV | Antenna Factor dB | Preamp Factor dB | Cable Loss dB | Level dBuV | Limit dBuV | Margin dBuV | Remark |
|------|-------------|-----------------------|-------------------------|------------------------|---------------------|---------------|---------------|----------------|--------|
| 1 | 32.41 | 44.23 | 13.28 | 30.90 | 0.11 | 26.72 | 40.00 | -13.28 | Peak |
| 2 | 39.58 | 44.47 | 14.07 | 30.84 | 0.17 | 27.87 | 40.00 | -12.13 | Peak |
| 3 | 135.03 | 38.25 | 13.08 | 29.41 | 0.46 | 22.38 | 43.50 | -21.12 | Peak |
| 4 | 175.04 | 47.52 | 12.58 | 29.07 | 0.74 | 31.77 | 43.50 | -11.73 | Peak |
| 5 | 261.98 | 54.05 | 11.83 | 28.17 | 0.65 | 38.36 | 46.00 | -7.64 | Peak |
| 6 | 314.38 | 50.43 | 13.19 | 27.92 | 0.55 | 36.25 | 46.00 | -9.75 | Peak |

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

From 1G-25GHz

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

IEEE 802.11b

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1103 | V | 44.52 | --- | -11.24 | 33.28 | --- | 74 | 54 | 40.72 | Peak |
| 4824 | V | 36.9 | --- | 0.64 | 37.54 | --- | 74 | 54 | 36.46 | Peak |
| N/A | | | | | | | | | | |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1103 | H | 44.04 | --- | -11.24 | 32.8 | --- | 74 | 54 | 41.2 | Peak |
| 4824 | H | 36.63 | --- | 0.64 | 37.27 | --- | 74 | 54 | 36.73 | Peak |
| N/A | | | | | | | | | | |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1103 | V | 43.49 | --- | -11.24 | 32.25 | --- | 74 | 54 | 41.75 | Peak |
| 4874 | V | 39.23 | --- | 0.76 | 39.99 | --- | 74 | 54 | 34.01 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1103 | H | 43.65 | --- | -11.24 | 32.41 | --- | 74 | 54 | 41.59 | Peak |
| 4874 | H | 40.23 | --- | 0.76 | 40.99 | --- | 74 | 54 | 33.01 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1103 | V | 43.44 | --- | -11.24 | 32.2 | --- | 74 | 54 | 41.8 | Peak |
| 4924 | V | 34.86 | --- | 0.87 | 35.73 | --- | 74 | 54 | 38.27 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1103 | H | 43.85 | --- | -11.24 | 32.61 | --- | 74 | 54 | 41.39 | Peak |
| 4924 | H | 33.7 | --- | 0.87 | 34.57 | --- | 74 | 54 | 39.43 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11 g:

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|-------------|--------------|---------------------|-------------------|-------------------|---------------|-------------|---------------------|-------------------|-------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1145 | V | 44.32 | --- | -11.24 | 33.08 | --- | 74 | 54 | 40.92 | Peak |
| 2586 | V | 46.39 | --- | -7.13 | 39.26 | --- | 74 | 54 | 34.74 | Peak |
| 3062 | V | 44.45 | --- | -5.74 | 38.71 | --- | 74 | 54 | 35.29 | Peak |
| 4824 | V | 44.05 | --- | 0.64 | 44.69 | --- | 74 | 54 | 29.31 | Peak |
| N/A | | | | | | | | | | |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|-------------|--------------|---------------------|-------------------|-------------------|---------------|-------------|---------------------|-------------------|-------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1294 | H | 43.66 | --- | -10.96 | 32.7 | --- | 74 | 54 | 41.3 | Peak |
| 2038 | H | 43.85 | --- | -8.58 | 35.27 | --- | 74 | 54 | 38.73 | Peak |
| 3483 | H | 42.75 | --- | -4.95 | 37.8 | --- | 74 | 54 | 36.2 | Peak |
| 4824 | H | 41.55 | --- | 0.64 | 42.19 | --- | 74 | 54 | 31.81 | Peak |
| N/A | | | | | | | | | | |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1374 | V | 43.85 | --- | -10.43 | 33.42 | --- | 74 | 54 | 40.58 | Peak |
| 2589 | V | 44.44 | --- | -7.13 | 37.31 | --- | 74 | 54 | 36.69 | Peak |
| 3365 | V | 43.82 | --- | -5.18 | 38.64 | --- | 74 | 54 | 35.36 | Peak |
| 4874 | V | 43.04 | --- | 0.76 | 43.8 | --- | 74 | 54 | 30.2 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1321 | H | 43.85 | --- | -10.84 | 33.01 | --- | 74 | 54 | 40.99 | Peak |
| 2314 | H | 44.55 | --- | -7.46 | 37.09 | --- | 74 | 54 | 36.91 | Peak |
| 3577 | H | 42.84 | --- | -4.76 | 38.08 | --- | 74 | 54 | 35.92 | Peak |
| 4874 | H | 40.55 | --- | 0.76 | 41.31 | --- | 74 | 54 | 32.69 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1302 | V | 43.85 | --- | -10.84 | 33.01 | --- | 74 | 54 | 40.99 | Peak |
| 2982 | V | 44.39 | --- | -5.86 | 38.53 | --- | 74 | 54 | 35.47 | Peak |
| 3831 | V | 43.45 | --- | -3.96 | 39.49 | --- | 74 | 54 | 34.51 | Peak |
| 4924 | V | 41.85 | --- | 0.87 | 42.72 | --- | 74 | 54 | 31.28 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1446 | H | 44.03 | --- | -10.29 | 33.74 | --- | 74 | 54 | 40.26 | Peak |
| 2198 | H | 42.85 | --- | -8.24 | 34.61 | --- | 74 | 54 | 39.39 | Peak |
| 3905 | H | 43.95 | --- | -3.68 | 40.27 | --- | 74 | 54 | 33.73 | Peak |
| 4924 | H | 41.43 | --- | 0.87 | 42.3 | --- | 74 | 54 | 31.7 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11n/HT20 with 2.4G

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1492 | V | 44.03 | --- | -10.27 | 33.76 | --- | 74 | 54 | 40.24 | Peak |
| 2671 | V | 43.62 | --- | -6.94 | 36.68 | --- | 74 | 54 | 37.32 | Peak |
| 3948 | V | 43.81 | --- | -3.68 | 40.13 | --- | 74 | 54 | 33.87 | Peak |
| 4824 | V | 42.56 | --- | 0.64 | 43.2 | --- | 74 | 54 | 30.8 | Peak |
| N/A | | | | | | | | | | |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1451 | H | 44.06 | --- | -10.27 | 33.79 | --- | 74 | 54 | 40.21 | Peak |
| 2839 | H | 44.33 | --- | -6.17 | 38.16 | --- | 74 | 54 | 35.84 | Peak |
| 3607 | H | 43.9 | --- | -4.52 | 39.38 | --- | 74 | 54 | 34.62 | Peak |
| 4824 | H | 42.82 | --- | 0.64 | 43.46 | --- | 74 | 54 | 30.54 | Peak |
| N/A | | | | | | | | | | |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1262 | V | 43.75 | --- | -10.96 | 32.79 | --- | 74 | 54 | 41.21 | Peak |
| 2013 | V | 44.19 | --- | -8.58 | 35.61 | --- | 74 | 54 | 38.39 | Peak |
| 3798 | V | 43.43 | --- | -4.07 | 39.36 | --- | 74 | 54 | 34.64 | Peak |
| 4874 | V | 42.55 | --- | 0.76 | 43.31 | --- | 74 | 54 | 30.69 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1511 | H | 43.65 | --- | -10.14 | 33.51 | --- | 74 | 54 | 40.49 | Peak |
| 2353 | H | 43.81 | --- | -7.59 | 36.22 | --- | 74 | 54 | 37.78 | Peak |
| 3266 | H | 44.08 | --- | -5.39 | 38.69 | --- | 74 | 54 | 35.31 | Peak |
| 4874 | H | 42.82 | --- | 0.76 | 43.58 | --- | 74 | 54 | 30.42 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1477 | V | 45.08 | --- | -10.27 | 34.81 | --- | 74 | 54 | 39.19 | Peak |
| 2703 | V | 43.96 | --- | -6.43 | 37.53 | --- | 74 | 54 | 36.47 | Peak |
| 3561 | V | 43.85 | --- | -4.76 | 39.09 | --- | 74 | 54 | 34.91 | Peak |
| 4924 | V | 42.68 | --- | 0.87 | 43.55 | --- | 74 | 54 | 30.45 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1503 | H | 43.63 | --- | -10.14 | 33.49 | --- | 74 | 54 | 40.51 | Peak |
| 3588 | H | 43.93 | --- | -4.96 | 38.97 | --- | 74 | 54 | 35.03 | Peak |
| 4153 | H | 43.74 | --- | -2.48 | 41.26 | --- | 74 | 54 | 32.74 | Peak |
| 4924 | H | 41.79 | --- | 0.87 | 42.66 | --- | 74 | 54 | 31.34 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11n/HT40 with 2.4G

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1551 | V | 44.09 | --- | -10.07 | 34.02 | --- | 74 | 54 | 39.98 | Peak |
| 2695 | V | 43.96 | --- | -6.94 | 37.02 | --- | 74 | 54 | 36.98 | Peak |
| 3463 | V | 43.25 | --- | -4.95 | 38.3 | --- | 74 | 54 | 35.7 | Peak |
| 4844 | V | 41.84 | --- | 0.64 | 42.48 | --- | 74 | 54 | 31.52 | Peak |
| N/A | | | | | | | | | | |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Low | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1542 | H | 43.86 | --- | -10.14 | 33.72 | --- | 74 | 54 | 40.28 | Peak |
| 2358 | H | 43.72 | --- | -7.59 | 36.13 | --- | 74 | 54 | 37.87 | Peak |
| 3096 | H | 44.13 | --- | -5.74 | 38.39 | --- | 74 | 54 | 35.61 | Peak |
| 4844 | H | 42.53 | --- | 0.64 | 43.17 | --- | 74 | 54 | 30.83 | Peak |
| N/A | | | | | | | | | | |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1628 | V | 44.42 | --- | -9.84 | 34.58 | --- | 74 | 54 | 39.42 | Peak |
| 2593 | V | 43.84 | --- | -7.13 | 36.71 | --- | 74 | 54 | 37.29 | Peak |
| 3301 | V | 43.98 | --- | -5.31 | 38.67 | --- | 74 | 54 | 35.33 | Peak |
| 4874 | V | 42.83 | --- | 0.76 | 43.59 | --- | 74 | 54 | 30.41 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX Mid | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1564 | H | 44.05 | --- | -10.07 | 33.98 | --- | 74 | 54 | 40.02 | Peak |
| 2248 | H | 44.39 | --- | -8.13 | 36.26 | --- | 74 | 54 | 37.74 | Peak |
| 3159 | H | 43.35 | --- | -5.52 | 37.83 | --- | 74 | 54 | 36.17 | Peak |
| 4874 | H | 42.6 | --- | 0.76 | 43.36 | --- | 74 | 54 | 30.64 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1645 | V | 44.48 | --- | -9.84 | 34.64 | --- | 74 | 54 | 39.36 | Peak |
| 2590 | V | 44.01 | --- | -7.13 | 36.88 | --- | 74 | 54 | 37.12 | Peak |
| 3851 | V | 43.43 | --- | -3.84 | 39.59 | --- | 74 | 54 | 34.41 | Peak |
| 4904 | V | 41.78 | --- | 0.87 | 42.65 | --- | 74 | 54 | 31.35 | Peak |

| | | | |
|--------------------|----------------------|--------------------------|-----------------------|
| EUT | GNSS Survey Receiver | Model Name | S321 Network |
| Temperature | 26°C | Relative Humidity | 56% |
| Pressure | 960hPa | Test voltage | DC 10.8V From battery |
| Test Mode | TX High | | |

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1792 | H | 44.15 | --- | -9.27 | 34.88 | --- | 74 | 54 | 39.12 | Peak |
| 2804 | H | 44.33 | --- | -6.17 | 38.16 | --- | 74 | 54 | 35.84 | Peak |
| 3743 | H | 44.69 | --- | -4.24 | 40.45 | --- | 74 | 54 | 33.55 | Peak |
| 4904 | H | 43.12 | --- | 0.87 | 43.99 | --- | 74 | 54 | 30.01 | Peak |

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

6 POWER LINE CONDUCTED EMISSION

6.1 Conducted Emission Limits(15.207)


| Frequency MHz | Limits dB(μ V) | |
|------------------|---------------------|---------------|
| | Quasi-peak Level | Average Level |
| 0.15 -0.50 | 66 -56* | 56 - 46* |
| 0.50 -5.00 | 56 | 46 |
| 5.00 -30.00 | 60 | 50 |

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3. The limit decreases in line with the logarithm of the frequency in the rang of 0.15 to 0.50 MHz.

6.2 Test Setup



6.3 Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCI) is set at 9 kHz.

6.4 Test Results

Not apply to battery operated product.

7 Conducted Maximum Output Power

7.1 Test limit

Please refer section RSS-247 & 15.247.

7.2 Test Procedure

Details see the KDB558074 Meas Guidance V03


7.2.1 Place the EUT on the table and set it in transmitting mode.

7.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

Details see the KDB 558074 DTS Meas Guidance V03

7.3 Test Setup



7.4 Test Results

PASS

Detailed information please see the following page.

| EUT: GNSS Survey Receiver | | M/N: S321 Network | | |
|------------------------------|-----------------|-----------------------|-----------------------|-------------|
| Test date: 2015-11-10 | | Test site: RF site | Tested by: Eric Huang | |
| Mode | Frequency (MHz) | PK Output power (dBm) | Limit (dBm) | Margin (dB) |
| IEEE 802.11 b | CH1: 2412 | 17.35 | 30 | 12.65 |
| | CH6: 2437 | 17.28 | 30 | 12.72 |
| | CH11: 2462 | 17.16 | 30 | 12.84 |
| IEEE 802.11 g | CH1: 2412 | 16.76 | 30 | 13.24 |
| | CH6: 2437 | 16.84 | 30 | 13.16 |
| | CH11: 2462 | 16.75 | 30 | 13.25 |
| IEEE 802.11 n/HT20 with 2.4G | CH1: 2412 | 16.12 | 30 | 13.88 |
| | CH6: 2437 | 16.33 | 30 | 13.67 |
| | CH11: 2462 | 16.29 | 30 | 13.71 |
| IEEE 802.11 n/HT40 with 2.4G | CH1: 2422 | 15.16 | 30 | 14.84 |
| | CH4: 2437 | 15.39 | 30 | 14.61 |
| | CH7: 2452 | 15.68 | 30 | 14.32 |
| Conclusion: PASS | | | | |

8 PEAK POWER SPECTRAL DENSITY

8.1 Test limit

8.1.1 Please refer section RSS-247 & 15.247.

8.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

8.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

8.2 Method of measurement

Details see the KDB558074 DTS Meas Guidance V03

8.2.1 Place the EUT on the table and set it in transmitting mode.


8.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

8.2.3 Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, span=5-30%EBW, detail see the test plot.

8.2.4 Record the max reading.

8.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

8.3 Test Setup



8.4 Test Results

PASS.

Detailed information please see the following page.

| EUT: GNSS Survey Receiver M/N: S321 Network | | | | |
|---|-----------------|----------------------|-------------|-----------------------|
| Test date: 2015-11-10 | | Test site: RF site | | Tested by: Eric Huang |
| Mode | Frequency (MHz) | PK Output power(dBm) | Limit (dBm) | Result |
| IEEE 802.11 b | CH1: 2412 | -6.553 | 8 | PASS |
| | CH6: 2437 | -9.165 | 8 | PASS |
| | CH11: 2462 | -9.618 | 8 | PASS |
| IEEE 802.11 g | CH1: 2412 | -16.047 | 8 | PASS |
| | CH6: 2437 | -16.331 | 8 | PASS |
| | CH11: 2462 | -17.238 | 8 | PASS |
| IEEE 802.11 n/HT20 with 2.4G | CH1: 2412 | -16.537 | 8 | PASS |
| | CH6: 2437 | -16.572 | 8 | PASS |
| | CH11: 2462 | -16.315 | 8 | PASS |
| IEEE 802.11 n/HT40 with 2.4G | CH1: 2422 | -19.963 | 8 | PASS |
| | CH4: 2437 | -19.926 | 8 | PASS |
| | CH7: 2452 | -20.301 | 8 | PASS |
| Conclusion: PASS | | | | |


IEEE 802.11b :
CH Low:




CH Mid:




CH High:

IEEE 802.11g :
CH Low


CH Mid:




CH High:




IEEE 802.11n HT20:
CH Low:



CH Mid:




CH High:



IEEE 802.11n HT40:


CH Low:



CH Mid:



CH High:



9 Bandwidth

9.1 Test limit

Please refer section RSS-247 & 15.247


For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

9.2 Method of measurement

Details see the KDB558074 D01 Meas Guidance

- a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set $RBW = 1-5 \% EBW$, $VBW \geq 3RBW$, Sweep time set auto, detail see the test plot.

9.3 Test Setup




9.4 Test Results

PASS.


Detailed information please see the following page.

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Limit (MHz) | Result |
|--------------------|-----------------|---------------------|------------------------------|-------------|--------|
| IEEE 802.11b: | | | | | |
| Low | 2412 | 9.574 | 15.037 | 0.5 | PASS |
| Mid | 2437 | 9.138 | 15.053 | 0.5 | PASS |
| High | 2462 | 10.05 | 15.030 | 0.5 | PASS |
| IEEE 802.11g | | | | | |
| Low | 2412 | 16.38 | 16.475 | 0.5 | PASS |
| Mid | 2437 | 16.40 | 16.496 | 0.5 | PASS |
| High | 2462 | 16.38 | 16.487 | 0.5 | PASS |
| IEEE 802.11n/HT20: | | | | | |
| Low | 2412 | 17.62 | 17.698 | 0.5 | PASS |
| Mid | 2437 | 17.62 | 17.695 | 0.5 | PASS |
| High | 2462 | 17.61 | 17.701 | 0.5 | PASS |
| IEEE 802.11n/HT40: | | | | | |
| Low | 2422 | 35.85 | 36.001 | 0.5 | PASS |
| Mid | 2437 | 35.78 | 36.026 | 0.5 | PASS |
| High | 2452 | 35.72 | 36.019 | 0.5 | PASS |


IEEE 802.11b:
CH Low:



CH Mid:




CH High:




IEEE 802.11g:


CH Low:




CH Mid:




CH High:




IEEE 802.11n HT20:
CH Low:



CH Mid:




CH High:




IEEE 802.11n/HT40:


CH Low:



CH Mid:



CH High:



10 Band Edge Check

10.1 Test limit

Please refer section RSS-247 & 15.247.

10.2 Test Procedure

12.2.1 Put the EUT on a 1.5 m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

12.2.2 Check the spurious emissions out of band.

12.2.3 RBW 1MHz, VBW 3MHz ,peak detector for peak value, RBW=1MHz ,VBW=3MHz, RMS detector for AV value.

10.3 Test Setup

Same as 5.2.2.

10.4 Test Result

PASS.

Detailed information please see the following page.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-----------------|-----------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx Low | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 42.16 | 27.62 | 3.92 | 34.97 | 38.73 | 74 | 35.27 | PK |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 42.29 | 27.62 | 3.92 | 34.97 | 38.86 | 74 | 35.14 | PK |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Note:

1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK

2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS

3, Result = Read level + Antenna factor + cable loss-Amp factor

4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-----------------|-----------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx High | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 42.29 | 27.89 | 4 | 34.97 | 39.21 | 74 | 34.79 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 43.77 | 27.89 | 4 | 34.97 | 40.69 | 74 | 33.31 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Note:

- 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-----------------|-----------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx Low | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 48.76 | 27.62 | 3.92 | 34.97 | 45.33 | 74 | 28.67 | PK |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 49.13 | 27.62 | 3.92 | 34.97 | 45.7 | 74 | 28.3 | PK |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Note:

1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK

2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS

3, Result = Read level + Antenna factor + cable loss-Amp factor

4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-----------------|-----------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx High | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 45.36 | 27.89 | 4 | 34.97 | 42.28 | 74 | 31.72 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 46.18 | 27.89 | 4 | 34.97 | 43.1 | 74 | 30.9 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Note:

- 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-------------------|-----------------------|----------------|-------------|-----------|--|--|--|--|--|--|
| EUT: GNSS Survey Receiver | | | | M/N: S321 Network | | | | | | | | | | |
| Power: DC 10.8V From battery | | | | | | | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | | | | | | | |
| Test mode: Tx Low | | | | | | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark | | | | | | |
| 2390 | 43.29 | 27.62 | 3.92 | 34.97 | 39.86 | 74 | 34.14 | PK | | | | | | |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | | | | | | |
| 2390 | 45.17 | 27.62 | 3.92 | 34.97 | 41.74 | 74 | 32.26 | PK | | | | | | |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

Note:

- 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-----------------|-----------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx High | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 46.12 | 27.89 | 4 | 34.97 | 43.04 | 74 | 30.96 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 46.74 | 27.89 | 4 | 34.97 | 43.66 | 74 | 30.34 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Note:

1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK

2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS

3, Result = Read level + Antenna factor + cable loss-Amp factor

4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-------------------|-----------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | M/N: S321 Network | | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx Low | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 43.14 | 27.62 | 3.92 | 34.97 | 39.71 | 74 | 34.29 | PK |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 44.06 | 27.62 | 3.92 | 34.97 | 40.63 | 74 | 33.37 | PK |
| 2390 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Note:

1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK

2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS

3, Result = Read level + Antenna factor + cable loss-Amp factor


4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

| Band Edge Test result | | | | | | | | |
|------------------------------|---------------------|-----------------------|-----------------------|-----------------|-----------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V From battery | | | | | | | | |
| Test date: 2015-06-06 | | | Test site: 3m Chamber | | Tested by: Eric Huang | | | |
| Test mode: Tx High | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 45.78 | 27.89 | 4 | 34.97 | 42.7 | 74 | 31.3 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 46.12 | 27.89 | 4 | 34.97 | 43.04 | 74 | 30.96 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |


Note:

- 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Conducted Method:
802.11b




802.11g



802.11n HT20



802.11n HT40



11 Antenna Requirement

11.1 Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

11.2 Antenna Connected Construction


The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

11.3 Result

It complies with the standard requirement.

12 Test setup photo

Photographs-Radiated Emission Test Setup in Chamber



-----END OF THE REPORT-----