



TEST REPORT

FCC ID: ZC8S321NETWORK

Applicant : Hemisphere GNSS Inc.
Address : 8515 E Anderson Dr, Scottsdale, AZ 85255, USA

Equipment under Test (EUT):

Name : GNSS Survey Receiver
Model : S321 Network, BRx6 Network

Standards : FCC PART 15, SUBPART C: 2014 (Section 15.247)
ANSI C63.10: 2013

Report No : T1851403 17
Date of Test : September 22- November 16, 2015
Date of Issue : November 16, 2015

Test Result : PASS

In the configuration tested, the EUT complied with the standards specified above
Authorized Signature

(Mark Zhu)
Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Alpha Product Testing Co., Ltd. Or test done by Shenzhen Alpha Product Testing Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Alpha Product Testing Co., Ltd. Approvals in writing.

Contents

| | |
|---|-----------|
| 1. General Information..... | 5 |
| 1.1. Description of Device (EUT) | 5 |
| 1.2. Accessories of device (EUT) | 6 |
| 1.3. Test Lab information | 6 |
| 2. Summary of test | 7 |
| 2.1. Summary of test result | 7 |
| 2.2. Assistant equipment used for test..... | 7 |
| 2.3. Block Diagram | 7 |
| 2.4. Test mode | 8 |
| 2.5. Test Conditions..... | 8 |
| 2.6. Measurement Uncertainty (95% confidence levels, k=2) | 9 |
| 2.7. Test Equipment..... | 10 |
| 3. Maximum Peak Output power | 11 |
| 3.1. Limit..... | 11 |
| 3.2. Test Procedure | 11 |
| 3.3. Test Setup | 11 |
| 3.4. Test Result..... | 11 |
| 4. Bandwidth | 12 |
| 4.1. Limit..... | 12 |
| 4.2. Test Procedure | 12 |
| 4.3. Test Result..... | 12 |
| 5. Carrier Frequency Separation..... | 18 |
| 5.1. Limit..... | 18 |
| 5.2. Test Procedure | 18 |
| 5.3. Test Result..... | 18 |
| 6. Number Of Hopping Channel | 21 |
| 6.1. Limit..... | 21 |
| 6.2. Test Procedure | 21 |
| 6.3. Test Result..... | 21 |
| 7. Dwell Time..... | 24 |
| 7.1. Test limit | 24 |
| 7.2. Test Procedure..... | 24 |
| 7.3. Test Results | 24 |
| 8. Radiated emissions..... | 31 |
| 8.1. Limit..... | 31 |
| 8.2. Block Diagram of Test setup | 32 |
| 8.3. Test Procedure | 33 |
| 8.4. Test Result..... | 33 |
| 9. Band Edge Compliance | 45 |
| 9.1. Block Diagram of Test Setup | 45 |
| 9.2. Limit..... | 45 |
| 9.3. Test Procedure | 45 |
| 9.4. Test Result..... | 45 |

| | |
|---|-----------|
| 10. Power Line Conducted Emissions | 64 |
| 10.1. Block Diagram of Test Setup | 64 |
| 10.2. Limit..... | 64 |
| 10.3. Test Procedure | 64 |
| 10.4. Test Result..... | 65 |
| 11. Antenna Requirements..... | 66 |
| 11.1. Limit..... | 66 |
| 11.2. Result..... | 66 |
| 12. Test setup photo | 67 |

TEST REPORT VERIFICATION

Applicant : Hemisphere GNSS Inc.
Manufacturer : Hemisphere GNSS Inc.
EUT Description : GNSS Survey Receiver
(A) Model No. : S321 Network , BRx6 Network
(B) Trademark : N/A
(C) Ratings Supply : DC 10.8V from internal battery or external battery
(D) Test Voltage : DC 10.8V from internal battery

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C 2014, ANSI C63.4-2014

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C and RSS-247 limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Eric Huang
Test Engineer

.....
Eric Huang
.....

Approved by (name + signature).....: Simple Guan
Project Manager

.....
Simple Guan
.....

Date of issue.....: November 16, 2015

1. General Information

1.1. Description of Device (EUT)

| | | |
|---------------------|---|--|
| EUT | : | GNSS Survey Receiver |
| Model No. | : | S321 Network , BRx6 Network |
| DIFF | | Only differ in model number. |
| Trade mark | : | N/A |
| Power supply | : | DC 10.8V from internal battery or external battery |
| Adapter | : | Manufacturer: NIL Model No.: PSAA30R-150 |
| Radio Technology | : | BT2.1+EDR |
| Operation frequency | : | 2402-2480MHz |
| Modulation | : | GFSK, $\pi/4$ DQPSK, 8-DPSK |
| Antenna Type | : | Integrated Antenna, max gain 3.92 dBi. |
| Applicant | : | Hemisphere GNSS Inc. |
| Address | : | 8515 E Anderson Dr, Scottsdale, AZ 85255, USA |
| Manufacturer | : | Hemisphere GNSS Inc. |
| Address | : | 8515 E Anderson Dr, Scottsdale, AZ 85255, USA |

1.2. Accessories of device (EUT)

Description : Adapter
Manufacturer : NIL
Model No. : PSAA30R-150
Input : AC 100-240V, 50-60Hz, 0.8A
Output : DC 15V, 2A

1.3. Test Lab information

Shenzhen Alpha Product Testing Co., Ltd
Building B, East Area of Nanchang Second, Industrial Zone, Gushu 2nd Road,
Bao'an, Shenzhen, China

August 11, 2014 File on Federal Communication Commission
Registration Number: 203110

July 18, 2014 Certificated by IC
Registration Number: 12135A

2. Summary of test

2.1. Summary of test result


| Description of Test Item | Standard | Results |
|--------------------------------|---|---------|
| Maximum Peak Output Power | FCC Part 15: 15.247(b)(1) ANSI C63.4 :2009 | PASS |
| Bandwidth | FCC Part 15: 15.215 ANSI C63.4 :2009 | PASS |
| Carrier Frequency Separation | FCC Part 15: 15.247(a)(1) ANSI C63.4 :2009 | PASS |
| Number Of Hopping Channel | FCC Part 15: 15.247(a)(1)(iii) ANSI C63.4 :2009 | PASS |
| Dwell Time | FCC Part 15: 15.247(a)(1)(iii) ANSI C63.4 :2009 | PASS |
| Radiated Emission | FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.4 :2009 | PASS |
| Band Edge Compliance | FCC Part 15: 15.247(d) ANSI C63.4 :2009 | PASS |
| Power Line Conducted Emissions | FCC Part 15: 15.207 ANSI C63.4 :2009 | PASS |
| Antenna requirement | FCC Part 15: 15.203 | PASS |
| Note: Test with engineer mode. | | |

2.2. Assistant equipment used for test


| | | |
|--------------------------|---|----------|
| Description | : | Notebook |
| Manufacturer | : | ACER |
| Model No. | : | ZQT |
| Remark: FCC DOC approved | | |

2.3. Block Diagram

1, For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was be set into BT test mode by engineer mode before test.



2, For Power Line Conducted Emissions Test: EUT was connected to notebook by 1.5m USB line



2.4. Test mode

The engineer mode was used to control EUT work in continuous TX mode, and select test channel, wireless mode.

| Tested mode, channel, and data rate information | | |
|---|--------------|-----------------|
| Mode | Channel | Frequency (MHz) |
| GFSK | Low :CH1 | 2402 |
| | Middle: CH40 | 2441 |
| | High: CH79 | 2480 |

| Tested mode, channel, and data rate information | | |
|---|--------------|-----------------|
| Mode | Channel | Frequency (MHz) |
| $\pi/4$ DQPSK | Low :CH1 | 2402 |
| | Middle: CH40 | 2441 |
| | High: CH79 | 2480 |

| Tested mode, channel, and data rate information | | |
|---|--------------|-----------------|
| Mode | Channel | Frequency (MHz) |
| 8- DPSK | Low :CH1 | 2402 |
| | Middle: CH40 | 2441 |
| | High: CH79 | 2480 |

2.5. Test Conditions

| | |
|-------------------|-----------|
| Temperature range | 21-25°C |
| Humidity range | 40-75% |
| Pressure range | 86-106kPa |

2.6. Measurement Uncertainty (95% confidence levels, k=2)

| Item | MU | Remark |
|--|--------------------|-------------|
| Uncertainty for Power point Conducted Emissions Test | 2.42dB | |
| Uncertainty for Radiation Emission test in 3m chamber (below 30MHz) | 2.13 dB | Polarize: V |
| | 2.57dB | Polarize: H |
| Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz) | 3.54dB | Polarize: V |
| | 4.1dB | Polarize: H |
| Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz) | 2.08dB | Polarize: H |
| | 2.56dB | Polarize: V |
| Uncertainty for radio frequency | 1×10^{-9} | |
| Uncertainty for conducted RF Power | 0.65dB | |
| Uncertainty for temperature | 0.2°C | |
| Uncertainty for humidity | 1% | |
| Uncertainty for DC and low frequency voltages | 0.06% | |

2.7. Test Equipment

| Equipment | Manufacture | Model No. | Serial No. | Cal. Due day | Cal Interval |
|---------------------|---------------|--------------|-------------------|--------------|--------------|
| 3m Semi-Anechoic | ETS-LINDGREN | N/A | SEL0017 | 2016.01.19 | 1 Year |
| Spectrum analyzer | Agilent | E4407B | MY49510055 | 2016.01.19 | 1 Year |
| Receiver | R&S | ESCI | 101165 | 2016.01.19 | 1 Year |
| Bilog Antenna | SCHWARZBECK | VULB 9168 | 9168-438 | 2017.01.21 | 2 Year |
| Horn Antenna | SCHWARZBECK | BBHA 9120 D | BBHA 9120 D(1201) | 2017.01.21 | 2 Year |
| Horn Antenna | SCHWARZBECK | BBHA 9170 | BBHA 9170 D(1432) | 2017.01.21 | 2 Year |
| Active Loop Antenna | Beijing Daze | ZN30900A | SEL0097 | 2016.01.19 | 1 Year |
| Cable | Resenberger | SUCOFLEX 104 | MY6562/4 | 2016.01.19 | 1 Year |
| Cable | Resenberger | SUCOFLEX 104 | 309972/4 | 2016.01.19 | 1 Year |
| Cable | Resenberger | SUCOFLEX 104 | 329112/4 | 2016.01.19 | 1 Year |
| L.I.S.N.#1 | Schwarzbeck | NSLK8126 | 8126466 | 2016.01.19 | 1 Year |
| L.I.S.N.#2 | ROHDE&SCHWARZ | ENV216 | 101043 | 2016.01.19 | 1 Year |
| Power Meter | Anritsu | ML2487A | 6K00001491 | 2016.01.19 | 1 Year |
| Power sensor | Anritsu | ML2491A | 32516 | 2016.01.19 | 1 Year |
| Pre-amplifier | SCHWARZBECK | BBV9743 | 9743-019 | 2016.01.19 | 1 Year |
| Pre-amplifier | Quietek | AP-180C | CHM-0602012 | 2016.01.19 | 1 Year |

3. Maximum Peak Output power


3.1. Limit

Please refer section 15.247.

3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

| EUT: GNSS Survey Receiver | | | M/N: S321 Network | | |
|---------------------------|------------|-----------------------|----------------------|------------------|-------------|
| Test date: 2015-11-11 | | Test site: RF site | | Tested by: Peter | |
| Mode | Freq (MHz) | PK Output Power (dBm) | PK Output Power (mW) | Limit (dBm) | Margin (dB) |
| GFSK | 2402 | 4.56 | 2.858 | 21 | 16.440 |
| | 2441 | 5.14 | 3.266 | 21 | 15.860 |
| | 2480 | 6.35 | 4.315 | 21 | 14.650 |
| $\pi/4$ DQPSK, | 2402 | 1.23 | 1.327 | 21 | 19.770 |
| | 2441 | 2.36 | 1.722 | 21 | 18.640 |
| | 2480 | 3.97 | 2.495 | 21 | 17.030 |
| 8- DPSK | 2402 | 1.12 | 1.294 | 21 | 19.880 |
| | 2441 | 2.46 | 1.762 | 21 | 18.540 |
| | 2480 | 4.03 | 2.529 | 21 | 16.970 |
| Conclusion: PASS | | | | | |

4. Bandwidth

4.1. Limit

Please refer section 15.247.

4.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via antenna. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

| EUT: GNSS Survey Receiver | | M/N: S321 Network | | |
|---------------------------|------------|----------------------|---------------------|------------|
| Test date: 2015-11-11 | | Test site: RF site | Tested by: Peter | |
| Mode | Freq (MHz) | 20dB Bandwidth (KHz) | 99% Bandwidth (kHz) | Conclusion |
| GFSK | 2402 | 874.3 | 833.49 | PASS |
| | 2441 | 887.4 | 830.98 | PASS |
| | 2480 | 872.4 | 825.09 | PASS |
| $\pi/4$ DQPSK | 2402 | 1221 | 11571 | PASS |
| | 2441 | 1221 | 11566 | PASS |
| | 2480 | 1210 | 11549 | PASS |
| 8- DPSK | 2402 | 1207 | 11460 | PASS |
| | 2441 | 1209 | 11400 | PASS |
| | 2480 | 1207 | 11443 | PASS |



GFSK:








$\pi/4$ DQPSK:





8- DPSK:





5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


5.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via antenna. The carrier frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW.

5.3. Test Result

| EUT: GNSS Survey Receiver | | M/N: S321 Network | | |
|---------------------------|--------------------------|----------------------|-----------------------------------|------------------|
| Test date: 2015-11-11 | | Test site: RF site | | Tested by: Peter |
| Mode/Channel | Channel separation (KHz) | 20dB Bandwidth (KHz) | Limit (KHz) 2/3 20dB bandwidth | Conclusion |
| GFSK | 1002 | 887.400 | 591.600 | PASS |
| $\pi/4$ DQPSK | 1005 | 1221.000 | 814.000 | PASS |
| 8- DPSK | 1002 | 1209.000 | 806.000 | PASS |

GFSK



$\pi/4$ DQPSK



8- DPSK



6. Number of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via antenna. The number of hopping channel was measured by spectrum analyzer with 300 kHz RBW and 1MHz VBW.


6.3. Test Result

| EUT: GNSS Survey Receiver | | M/N: S321 Network | |
|---------------------------|---------------------------|--------------------|------------------|
| Test date: 2015-11-11 | | Test site: RF site | Tested by: Peter |
| Mode | Number of hopping channel | Limit | Conclusion |
| GFSK | 79 | >15 | PASS |
| $\pi/4$ DQPSK | 79 | >15 | PASS |
| 8- DPSK | 79 | >15 | PASS |


GFSK



$\pi/4$ DQPSK



8- DPSK



7. Dwell Time

7.1. Test limit

Please refer section 15.247.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured was complete.

7.3. Test Results


PASS.

Detailed information please see the following page.


| EUT: GNSS Survey Receiver | | M/N: S321 Network | | | | |
|--|-------------|--------------------|---------------------|------------------|-----------|------------|
| Test date: 2015-11-11 | | Test site: RF site | | Tested by: Peter | | |
| Mode | Data Packet | Frequency (MHz) | Pulse Duration (ms) | Dwell Time (s) | Limit (s) | Conclusion |
| GFSK | DH1 | 2441 | 0.368 | 0.236 | <0.4 | PASS |
| | DH3 | 2441 | 1.668 | 0.356 | <0.4 | PASS |
| | DH5 | 2441 | 2.873 | 0.368 | <0.4 | PASS |
| $\pi/4$ DQPSK | DH1 | 2441 | 0.3976 | 0.254 | <0.4 | PASS |
| | DH3 | 2441 | 1.668 | 0.356 | <0.4 | PASS |
| | DH5 | 2441 | 2.898 | 0.371 | <0.4 | PASS |
| 8- DPSK | DH1 | 2441 | 0.3968 | 0.254 | <0.4 | PASS |
| | DH3 | 2441 | 1.668 | 0.356 | <0.4 | PASS |
| | DH5 | 2441 | 2.897 | 0.371 | <0.4 | PASS |
| Note: A period time = 0.4 (s) * 79 = 31.6(s) DH1 time slot = Pulse Duration * (1600/(1*79)) * A period time DH3 time slot = Pulse Duration * (1600/(3*79)) * A period time DH5 time slot = Pulse Duration * (1600/(5*79)) * A period time | | | | | | |

GFSK


DH1:




DH3:




DH5




$\pi/4$ DQPSK
DH1





DH3




DH5



8- DPSK:





8. Radiated emissions

8.1. Limit

All the emissions appearing within FCC PART 15 restricted frequency bands shall not exceed the limits shown in FCC PART 15, all the other emissions shall be at least 20 dB below the fundamental emissions, or comply with FCC PART 15 limits.

FCC PART 15 Restricted frequency band


| MHz | MHz | MHz | GHz |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - 156.52525 | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.7 - 156.9 | 2690 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 162.0125 - 167.17 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 167.72 - 173.2 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 240 - 285 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 322 - 335.4 | 3600 - 4400 | (²) |

FCC PART 15 Limit


| FREQUENCY MHz | DISTANCE Meters | FIELD STRENGTHS LIMIT | |
|------------------|--------------------|---|----------|
| | | μV/m | dB(μV)/m |
| 0.009-0.490 | 300 | 2400/F(KHz) | / |
| 0.490-1.705 | 30 | 24000/F(KHz) | / |
| 1.705-30 | 30 | 30 | 29.5 |
| 30 ~ 88 | 3 | 100 | 40.0 |
| 88 ~ 216 | 3 | 150 | 43.5 |
| 216 ~ 960 | 3 | 200 | 46.0 |
| 960 ~ 1000 | 3 | 500 | 54.0 |
| Above 1000 | 3 | 74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average) | |

8.2. Block Diagram of Test setup

8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1GHz testing, and 150 cm for above 1GHz testing.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produce highest emissions
- (4) Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4 2014 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.


8.4. Test Result

We have scanned the 10th harmonic from 9 kHz to the EUT.
Detailed information please see the following page.


From 9 kHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS



Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz was listed in this report.

| 1GHz—25GHz Radiated emission Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-------------------|------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | | |
| Power: DC 10.8V from battery | | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | | Tested by: Peter | | | |
| Test mode: GFSK Tx CH1 2402MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4804 | 40.94 | 33.95 | 10.18 | 34.26 | 50.81 | 74 | 23.19 | PK |
| 2 | 4804 | 31.56 | 33.95 | 10.18 | 34.26 | 41.43 | 54 | 12.57 | AV |
| 3 | 7206 | / | | | | | | | |
| 4 | 9608 | / | | | | | | | |
| 5 | 12010 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4804 | 41.83 | 33.95 | 10.18 | 34.26 | 51.7 | 74 | 22.3 | PK |
| 2 | 4804 | 30.77 | 33.95 | 10.18 | 34.26 | 40.64 | 54 | 13.36 | AV |
| 3 | 7206 | / | | | | | | | |
| 4 | 9608 | / | | | | | | | |
| 5 | 12010 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto. | | | | | | | | | |
| Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto. | | | | | | | | | |
| Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

| 1GHz—25GHz Radiated emissison Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-------------------|-----------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | | |
| Power: DC 10.8V from battery | | | | | | | | | |
| Test date: 2015-11-11 Test site: 3m Chamber Tested by: Peter | | | | | | | | | |
| Test mode: GFSK Tx CH40 2441MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4882 | 41.59 | 33.93 | 10.2 | 34.29 | 51.43 | 74 | 22.57 | PK |
| 2 | 4882 | 31.39 | 33.93 | 10.2 | 34.29 | 41.23 | 54 | 12.77 | AV |
| 3 | 7323 | / | | | | | | | |
| 4 | 9764 | / | | | | | | | |
| 5 | 12205 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4882 | 41.42 | 33.93 | 10.2 | 34.29 | 51.26 | 74 | 22.74 | PK |
| 2 | 4882 | 30.97 | 33.93 | 10.2 | 34.29 | 40.81 | 54 | 13.19 | AV |
| 3 | 7323 | / | | | | | | | |
| 4 | 9764 | / | | | | | | | |
| 5 | 12205 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

| 1GHz—25GHz Radiated emissison Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-------------------|------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | | |
| Power: DC 10.8V from battery | | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | | Tested by: Peter | | | |
| Test mode: GFSK Tx CH79 2480MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4960 | 41.87 | 33.98 | 10.22 | 34.25 | 51.82 | 74 | 22.18 | PK |
| 2 | 4960 | 31.09 | 33.98 | 10.22 | 34.25 | 41.04 | 54 | 12.96 | AV |
| 3 | 7440 | / | | | | | | | |
| 4 | 9920 | / | | | | | | | |
| 5 | 12400 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4960 | 41.81 | 33.98 | 10.22 | 34.25 | 51.76 | 74 | 22.24 | PK |
| 2 | 4960 | 31.07 | 33.98 | 10.22 | 34.25 | 41.02 | 54 | 12.98 | AV |
| 3 | 7440 | / | | | | | | | |
| 4 | 9920 | / | | | | | | | |
| 5 | 12400 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

| 1GHz—25GHz Radiated emissison Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-------------------|------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | | |
| Power: DC 10.8V from battery | | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | | Tested by: Peter | | | |
| Test mode: $\pi/4$ DQPSK Tx CH40 2441MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4882 | 41.6 | 33.93 | 10.2 | 34.29 | 51.44 | 74 | 22.56 | PK |
| 2 | 4882 | 31.18 | 33.93 | 10.2 | 34.29 | 41.02 | 54 | 12.98 | AV |
| 3 | 7323 | / | | | | | | | |
| 4 | 9764 | / | | | | | | | |
| 5 | 12205 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4882 | 41.6 | 33.93 | 10.2 | 34.29 | 51.44 | 74 | 22.56 | PK |
| 2 | 4882 | 30.97 | 33.93 | 10.2 | 34.29 | 40.81 | 54 | 13.19 | AV |
| 3 | 7323 | / | | | | | | | |
| 4 | 9764 | / | | | | | | | |
| 5 | 12205 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

| 1GHz—25GHz Radiated emissison Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-----------------|------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | M/N: S321 Network | | | | | | |
| Power: DC 10.8V from battery | | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | | Tested by: Peter | | | |
| Test mode: $\pi/4$ DQPSK Tx CH79 2480MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4960 | 41.5 | 33.98 | 10.22 | 34.25 | 51.45 | 74 | 22.55 | PK |
| 2 | 4960 | 31.35 | 33.98 | 10.22 | 34.25 | 41.3 | 54 | 12.7 | AV |
| 3 | 7440 | / | | | | | | | |
| 4 | 9920 | / | | | | | | | |
| 5 | 12400 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4960 | 41.88 | 33.98 | 10.22 | 34.25 | 51.83 | 74 | 22.17 | PK |
| 2 | 4960 | 31.45 | 33.98 | 10.22 | 34.25 | 41.4 | 54 | 12.6 | AV |
| 3 | 7440 | / | | | | | | | |
| 4 | 9920 | / | | | | | | | |
| 5 | 12400 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |


| 1GHz—25GHz Radiated emissison Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-----------------|------------------|----------------|-------------|--------|
| EUT: Bluetooth earphone | | | | | M/N: MDS-800X | | | | |
| Power: DC 5.0V From notebook | | | | | | | | | |
| Test date: 2015-01-07 | | | Test site: 3m Chamber | | | Tested by: Peter | | | |
| Test mode: 8- DQPSK Tx CH1 2402MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4804 | 41.49 | 33.95 | 10.18 | 34.26 | 51.36 | 74 | 22.64 | PK |
| 2 | 4804 | 30.88 | 33.95 | 10.18 | 34.26 | 40.75 | 54 | 13.25 | AV |
| 3 | 7206 | / | | | | | | | |
| 4 | 9608 | / | | | | | | | |
| 5 | 12010 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4804 | 41.17 | 33.95 | 10.18 | 34.26 | 51.04 | 74 | 22.96 | PK |
| 2 | 4804 | 30.54 | 33.95 | 10.18 | 34.26 | 40.41 | 54 | 13.59 | AV |
| 3 | 7206 | / | | | | | | | |
| 4 | 9608 | / | | | | | | | |
| 5 | 12010 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto. Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto. Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

| 1GHz—25GHz Radiated emissison Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-----------------|------------------|----------------|-------------|--------|
| EUT: Bluetooth earphone | | | M/N: MDS-800X | | | | | | |
| Power: DC 5.0V From notebook | | | | | | | | | |
| Test date: 2015-01-07 | | | Test site: 3m Chamber | | | Tested by: Peter | | | |
| Test mode: 8- DQPSK Tx CH40 2441MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4882 | 41.3 | 33.93 | 10.2 | 34.29 | 51.14 | 74 | 22.86 | PK |
| 2 | 4882 | 30.97 | 33.93 | 10.2 | 34.29 | 40.81 | 54 | 13.19 | AV |
| 3 | 7323 | / | | | | | | | |
| 4 | 9764 | / | | | | | | | |
| 5 | 12205 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4882 | 41.48 | 33.93 | 10.2 | 34.29 | 51.32 | 74 | 22.68 | PK |
| 2 | 4882 | 31.09 | 33.93 | 10.2 | 34.29 | 40.93 | 54 | 13.07 | AV |
| 3 | 7323 | / | | | | | | | |
| 4 | 9764 | / | | | | | | | |
| 5 | 12205 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

| 1GHz—25GHz Radiated emission Test result | | | | | | | | | |
|---|------------|---------------------|-----------------------|-----------------|-----------------|-----------------|----------------|-------------|--------|
| EUT: Bluetooth earphone | | | M/N: MDS-800X | | | | | | |
| Power: DC 5.0V From notebook | | | | | | | | | |
| Test date: 2015-01-07 Test site: 3m Chamber Tested by: Peter | | | | | | | | | |
| Test mode: 8- DQPSK Tx CH79 2480MHz | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | |
| No | Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 1 | 4960 | 41.28 | 33.98 | 10.22 | 34.25 | 51.23 | 74 | 22.77 | PK |
| 2 | 4960 | 32.5 | 33.98 | 10.22 | 34.25 | 42.45 | 54 | 11.55 | AV |
| 3 | 7440 | / | | | | | | | |
| 4 | 9920 | / | | | | | | | |
| 5 | 12400 | / | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | |
| 1 | 4960 | 41.6 | 33.98 | 10.22 | 34.25 | 51.55 | 74 | 22.45 | PK |
| 2 | 4960 | 30.97 | 33.98 | 10.22 | 34.25 | 40.92 | 54 | 13.08 | AV |
| 3 | 7440 | / | | | | | | | |
| 4 | 9920 | / | | | | | | | |
| 5 | 12400 | / | | | | | | | |
| Note: | | | | | | | | | |
| 1, Measuring frequency from 1GHz to 25GHz | | | | | | | | | |
| 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | | |

9. Band Edge Compliance

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in FCC PART 15, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with FCC PART 15 limits.

9.3. Test Procedure

All restriction band and non- restriction band have been tested , only worse case is reported.

9.4. Test Result

PASS. (See below detailed test data)

GFSK (CH Low)

| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------------|-----------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx CH Low 2402MHz | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 42.48 | 27.62 | 3.92 | 34.97 | 39.05 | 74 | 34.95 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| 2400 | 41.81 | 27.62 | 3.94 | 34.97 | 38.4 | 74 | 35.6 | PK |
| 2400 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 41.97 | 27.62 | 3.92 | 34.97 | 38.54 | 74 | 35.46 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| 2400 | 42.18 | 27.62 | 3.94 | 34.97 | 38.77 | 74 | 35.23 | PK |
| 2400 | -- | 27.62 | 3.94 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------------|-----------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx CH High 2480MHz | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 41.81 | 27.89 | 4 | 34.97 | 38.73 | 74 | 35.27 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 42.01 | 27.89 | 4 | 34.97 | 38.93 | 74 | 35.07 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------------|-----------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 40.82 | 27.62 | 3.92 | 34.97 | 37.39 | 74 | 36.61 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 41.77 | 27.62 | 3.92 | 34.97 | 38.34 | 74 | 35.66 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------------|-----------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 41.29 | 27.89 | 4 | 34.97 | 38.21 | 74 | 35.79 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 41.51 | 27.89 | 4 | 34.97 | 38.43 | 74 | 35.57 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | | | | | |
|--|---------------------------|-----------------------------|-----------------------|-----------------------|--------------------|-------------------|----------------|-----------|--|--|--|--|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | | | | | |
| Power: DC 10.8V from battery | | | | | | | | | | | | |
| Test date: 2015-11-11 Test site: 3m Chamber Tested by: Peter | | | | | | | | | | | | |
| Test mode: Tx CH Low 2402MHz | | | | | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark | | | | |
| 2390 | 41.59 | 27.62 | 3.92 | 34.97 | 38.16 | 74 | 35.84 | PK | | | | |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | | | | | |
| 2390 | 41.91 | 27.62 | 3.92 | 34.97 | 38.48 | 74 | 35.52 | PK | | | | |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

Note:

- Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK
- Result = Read level + Antenna factor + cable loss-Amp factor
- All the other emissions not reported were too low to read and deemed to comply with FCC limit.

$\pi/4$ DQPSK (CH High)

| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------------|-----------------|-------------------|----------------|-------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx CH High 2480MHz | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 41.03 | 27.89 | 4 | 34.97 | 37.95 | 74 | 36.05 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 41.44 | 27.89 | 4 | 34.97 | 38.36 | 74 | 35.64 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------|------------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | Test site: 3m Chamber | | Tested by: Peter | | | | |
| Test mode: | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 41.59 | 27.62 | 3.92 | 34.97 | 38.16 | 74 | 35.84 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 41.55 | 27.62 | 3.92 | 34.97 | 38.12 | 74 | 35.88 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | |
|---|---------------------------|-----------------------------|-----------------------|-----------------------|--------------------|-------------------|----------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 Test site: 3m Chamber Tested by: Peter | | | | | | | | |
| Test mode: Tx CH Low 2402MHz | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 41.77 | 27.62 | 3.92 | 34.97 | 38.34 | 74 | 35.66 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 41.98 | 27.62 | 3.92 | 34.97 | 38.55 | 74 | 35.45 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |


| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------|-----------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 Test site: 3m Chamber Tested by: Peter | | | | | | | | |
| Test mode: Tx CH High 2480MHz | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 40.82 | 27.89 | 4 | 34.97 | 37.74 | 74 | 36.26 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 42.17 | 27.89 | 4 | 34.97 | 39.09 | 74 | 34.91 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

8- DPSK (Hopping Low)


| Band Edge Test result | | | | | | | | |
|---|---------------------|-----------------------|-----------------------|-----------------|-------------------|----------------|-------------|-----------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2390 | 41.49 | 27.62 | 3.92 | 34.97 | 38.06 | 74 | 35.94 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2390 | 42.02 | 27.62 | 3.92 | 34.97 | 38.59 | 74 | 35.41 | PK |
| 2390 | -- | 27.62 | 3.92 | 34.97 | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |

| Band Edge Test result | | | | | | | | |
|---|---------------------------|-----------------------------|-----------------------|-----------------------|--------------------|-------------------|----------------|--------|
| EUT: GNSS Survey Receiver | | | | | M/N: S321 Network | | | |
| Power: DC 10.8V from battery | | | | | | | | |
| Test date: 2015-11-11 | | | Test site: 3m Chamber | | Tested by: Peter | | | |
| Test mode: Tx | | | | | | | | |
| Antenna polarity: Vertical | | | | | | | | |
| Freq (MHz) | Read Level (dBuV/m) | Antenna Factor (dB/m) | Cable loss (dB) | Amp Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
| 2483.5 | 40.91 | 27.89 | 4 | 34.97 | 37.83 | 74 | 36.17 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Antenna Polarity: Horizontal | | | | | | | | |
| 2483.5 | 41.62 | 27.89 | 4 | 34.97 | 38.54 | 74 | 35.46 | PK |
| 2483.5 | | -- | -- | -- | -- | 54 | -- | AV |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Note: | | | | | | | | |
| 1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK | | | | | | | | |
| 3, Result = Read level + Antenna factor + cable loss-Amp factor | | | | | | | | |
| 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit. | | | | | | | | |


Conducted Method
GFSK
CH Low:




CH High:



Hopping
Low:




High:




$\pi/4$ DQPSK

CH Low:




CH High:




Hopping


Low:




High:




8- DPSK:
CH Low:




CH High:



Hopping
Low:




High:



10. Power Line Conducted Emissions

10.1. Block Diagram of Test Setup



10.2. Limit

| Frequency | Maximum RF Line Voltage | |
|-----------------|----------------------------------|-------------------------------|
| | Quasi-Peak Level dB(μ V) | Average Level dB(μ V) |
| 150kHz ~ 500kHz | 66 ~ 56* | 56 ~ 46* |
| 500kHz ~ 5MHz | 56 | 46 |
| 5MHz ~ 30MHz | 60 | 50 |

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4 2014 on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10 kHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

10.4. Test Result

Not apply to battery operated product.

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC PART 15, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC PART 15, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are PCB Antenna for Bluetooth, the maximum peak gain of the transmit antenna is only 3.92 dBi .

12. Test setup photo

Photographs-Radiated Emission Test Setup in Chamber



-----END OF THE REPORT-----