TEST REPORT
No. I19Z60845-EMC03

Samsung Electronics Co Ltd

Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

Model Name: SM-T295C

FCC ID: ZCASMT295C

with

Hardware Version: REV0.4

Software Version: T295CZCU0ASEA

Issued Date: 2019-06-13

TESTING
NVLAP LAB CODE 600118-0

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I19Z60845-EMC03	Rev.0	1st edition	2019-06-13

CONTENTS

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

1.3. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-04-15
Testing End Date: 2019-05-10

1.5. Signature

Li Yan
(Prepared this test report)

Zhang Ying
(Reviewed this test report)

Liu Baodian
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name:	Samsung Electronics Co Ltd
Address:	19 Chapin Rd.,Building D Pine Brook, NJ 07058
City:	/
Postal Code:	/
Country:	/
Contact:	Jenni Chun
Email:	/
Telephone:	/

2.2. Manufacturer Information

Company Name:	Jiaxing Yongrui Electron Technology Co., Ltd.
Address:	NO.777 Yazhong Road, Daqiao Town, Nanhu District, Jiaxing City ,Zhejiang
City:	/
Postal Code:	/
Country:	/
Contact:	/
Email:	/
Telephone:	/

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN
Model Name	SM-T295C
FCC ID	ZCASMT295C
Extreme vol. Limits	3.6VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT2	/	/	/

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Battery	/	/
AE3	Charger	/	/
AE4	Charger	/	/
AE5	USB Cable	/	/

AE1
Model	SWD-WT-N8
Manufacturer	Sunwoda Electronic Co., Ltd.
Capacitance	4980mAh
Nominal voltage	3.82 V

AE2
Model	SCUD-WT-N8
Manufacturer	SCUD(Fujian) Electronic Co., Ltd.
Capacitance	4980mAh
Nominal voltage	3.82 V

AE3
Model	EP-TA50JWS
Manufacturer	RFTECH ELECTRONICS (HuiZhou) Co.,Ltd.
Length of cable	/

AE4
Model	EP-TA50JWE /
Manufacturer	RFTECH ELECTRONICS (HuiZhou) Co.,Ltd. /
Length of cable	/ /

AE5
  Model   GH39-02004A
  Manufacturer   RFTECH ELECTRONICS (HuiZhou) Co.,Ltd.
  Length of cable   /

Note: The USB cables are shielded.

3.4. <u>EUT set-ups</u>

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT2+ AE1/AE2+ AE3 +AE5	Charger + Camera
Set.2	EUT2+ AE1/AE2 + AE5	USB mode+MP3+GNSS
Set.3	EUT2+ AE1/AE2+ AE4 +AE5	Charger

Note: SM-T295C is a variant model based on SM-T295, According to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01; all results are cited from the initial model. The report number for initial model is I19Z60464-EMC03.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17 meters×10 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	**<** ± 4 dB, 3m/10m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Semi-anechoic chamber SAC-2 (10 meters×6.7meters×6.1meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	**<** ± 4 dB, 3m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz－1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail
	BR	Re-use test data from basic model report.

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	A.1	BR	**CTTL(BDA)**
2	Conducted Emission	15.107(a)	A.2	BR	**CTTL(BDA)**

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESU26	100376	R&S	2019-11-27	1 year
2	Test Receiver	ESCI	100766	R&S	2020-03-20	1 year
3	Universal Radio Communication Tester	CMW500	127406	R&S	2020-01-19	1 year
4	LISN	ESH3-Z5	825562/028	R&S	2019-08-22	1 year
5	EMI Antenna	VULB9163	9163-482	Schwarzbeck	2019-09-21	1 year
6	EMI Antenna	3117	00139065	ETS-Lindgren	2019-10-15	1 year
7	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
8	Keyboard	KU-1601	2048361	Lenovo	N/A	N/A
9	Mouse	EMS-537A	8021S3MC	Lenovo	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission
Reference
FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 3 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.
The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. During the charging mode the camera is keeping on taking photos. During the USB mode The EUT is keeping on playing MP3 and the GNSS application is started up. The model of the PC is Lenovo M4000e-17, and the serial number of the PC is M706RMW2. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.
Note：I/O information：Printer – USB, Mouse – PS/2, Keyboard – USB.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit (µV/m)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

Result = P_{Mea} + A_{Rpl} = P_{Mea} + G_A + G_{PL}

Where

G_A: Antenna factor of receive antenna

G_{PL}: Path Loss

P_{Mea}: Measurement result on receiver.

Measurement uncertainty (worst case): 30MHz-1GHz：5.40dB, 1GHz-18GHz：4.32dB, *k*=2.

Measurement results for Set.1:

Charging Mode+ Camera /Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17090.000	39.13	-25.5	41.3	23.3	54.0	14.9	V
17088.000	39.10	-25.5	41.3	23.3	54.0	14.9	V
17089.500	39.09	-25.5	41.3	23.2	54.0	14.9	V
17109.000	39.08	-25.5	41.3	23.2	54.0	14.9	V
17059.000	39.08	-25.5	41.4	23.2	54.0	14.9	H
17094.500	39.06	-25.5	41.3	23.2	54.0	14.9	H

Charging Mode+ Camera /Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17023.500	51.8	-25.6	41.4	35.97	74.0	22.2	V
17085.000	51.6	-25.5	41.3	35.75	74.0	22.4	H
17072.000	51.4	-25.5	41.3	35.54	74.0	22.6	H
16781.000	51.3	-26.2	41.5	36.06	74.0	22.7	H
17113.000	51.3	-25.5	41.3	35.45	74.0	22.7	H
17087.500	51.3	-25.5	41.3	35.46	74.0	22.7	V

Measurement results for Set.2:

USB Mode +MP3+GNSS /Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17053.500	39.16	-25.5	41.4	23.3	-25.5	41.4	H
17095.500	39.12	-25.5	41.3	23.3	-25.5	41.3	V
17105.500	39.12	-25.5	41.3	23.3	-25.5	41.3	V
17094.000	39.12	-25.5	41.3	23.3	-25.5	41.3	V
17085.000	39.10	-25.5	41.3	23.3	-25.5	41.3	V
17087.500	39.08	-25.5	41.3	23.2	-25.5	41.3	H

USB Mode +MP3+GNSS /Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
3585.500	59.9	-34.2	33.5	60.57	74.0	14.1	H
3587.500	56.5	-34.2	33.5	57.17	74.0	17.5	H
3596.000	55.0	-34.1	33.5	55.64	74.0	19.0	H
3590.500	54.9	-34.2	33.5	55.61	74.0	19.1	V
3591.000	54.9	-34.2	33.5	55.58	74.0	19.1	H
3597.000	54.8	-34.1	33.5	55.45	74.0	19.2	H

Measurement results for Set.3:

Charging Mode /Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17093.000	39.14	-25.5	41.3	23.3	54.0	14.9	H
17090.500	39.09	-25.5	41.3	23.2	54.0	14.9	V
17051.500	39.05	-25.5	41.4	23.2	54.0	14.9	H
17093.500	39.05	-25.5	41.3	23.2	54.0	15.0	V
17088.500	39.03	-25.5	41.3	23.2	54.0	15.0	H
17110.000	39.00	-25.5	41.3	23.2	54.0	15.0	V

Charging Mode /Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17037.000	52.3	-25.6	41.4	36.52	74.0	21.7	V
16972.500	51.3	-25.6	41.4	35.56	74.0	22.7	V
17118.000	51.3	-25.5	41.3	35.46	74.0	22.7	V
17509.000	51.3	-25.4	41.2	35.49	74.0	22.7	V
17109.000	51.3	-25.5	41.3	35.41	74.0	22.7	H
16718.500	51.3	-26.1	41.4	35.93	74.0	22.7	V

Charging Mode + Camera, Set.1

15B RE 30MHz-1GHz

Figure A.1 Radiated Emission from 30MHz to 1GHz

Final Result 1

| Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
41.446000	27.6	100.0	V	27.0	0.1	12.4	40.0
64.435000	28.3	100.0	V	293.0	-2.4	11.7	40.0
81.992000	23.3	125.0	H	187.0	-5.6	16.7	40.0
103.72000	22.7	119.0	V	302.0	-1.0	20.8	43.5
133.30500	18.6	110.0	V	190.0	-4.5	24.9	43.5
169.29200	17.9	100.0	V	-31.0	-4.0	25.6	43.5

15B RE - 1GHz-3GHz

Figure A.2 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz

Figure A.3 Radiated Emission from 3GHz to 18GHz

USB Mode +MP3+GNSS, Set.2

15B RE 30MHz-1GHz

Figure A.4 Radiated Emission from 30MHz to 1GHz

Note: the spike（520MHz）is occurred by Printer

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
36.014000	26.3	100.0	V	145.0	-0.8	13.7	40.0
72.098000	23.2	119.0	V	90.0	-4.7	16.8	40.0
135.53600	27.7	125.0	H	69.0	-4.7	15.8	43.5
289.28100	28.3	100.0	H	0.0	-0.1	17.7	46.0
506.07600	41.7	100.0	V	-24.0	5.9	4.3	46.0
520.14100	41.4	100.0	V	-28.0	6.1	4.6	46.0

15B RE - 1GHz-3GHz

Figure A.5 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz

Figure A.6 Radiated Emission from 3GHz to 18GHz

Charging Mode, Set.3

15B RE 30MHz-1GHz

Figure A.7 Radiated Emission from 30MHz to 1GHz

Final Result 1

| Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
41.252000	27.0	100.0	V	113.0	0.1	13.0	40.0
61.234000	31.8	100.0	V	266.0	-1.3	8.2	40.0
93.050000	23.4	111.0	V	283.0	-2.2	20.1	43.5
102.55600	22.3	100.0	V	200.0	-0.9	21.2	43.5
128.16400	17.8	125.0	V	-15.0	-3.9	25.7	43.5
206.54000	18.2	100.0	V	7.0	-2.2	25.3	43.5

15B RE - 1GHz-3GHz

Figure A.8 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz

Figure A.9 Radiated Emission from 3GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. During the charging mode the camera is keeping on taking photos. During the USB mode the EUT is keeping on playing MP3 and the GNSS application is started up. The model of the PC is Lenovo M4000e-17, and the serial number of the PC is M706RMW2. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note：I/O information：Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

A.2.4 Test Condition in charging mode

Voltage（V）	Frequency（Hz）
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: U= 3.10 dB, k=2.

Charging Mode + Camera, Set.1

Figure A.10 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.442500	47.3	10000.0	9.000	GND	N	10.3	9.7	57.0
0.537000	52.5	10000.0	9.000	GND	L1	10.3	3.5	56.0
0.825000	47.0	10000.0	9.000	GND	L1	10.4	9.0	56.0
1.873500	50.9	10000.0	9.000	GND	L1	10.4	5.1	56.0
2.625000	49.0	10000.0	9.000	GND	L1	10.5	7.0	56.0
4.483500	51.3	10000.0	9.000	GND	L1	10.5	4.7	56.0

Final Result 2

| Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.438000	44.8	10000.0	9.000	GND	L1	10.3	2.3	47.1
0.537000	42.9	10000.0	9.000	GND	L1	10.3	3.1	46.0
0.820500	42.5	10000.0	9.000	GND	L1	10.4	3.5	46.0
1.662000	40.8	10000.0	9.000	GND	L1	10.4	5.2	46.0
2.319000	42.6	10000.0	9.000	GND	L1	10.4	3.4	46.0
4.600500	41.8	10000.0	9.000	GND	L1	10.5	4.2	46.0

.USB Mode +MP3+GNSS, Set.2

Figure A.11 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	54.7	10000.0	9.000	GND	L1	10.2	11.3	66.0
0.366000	42.4	10000.0	9.000	GND	L1	10.3	16.2	58.6
1.545000	36.0	10000.0	9.000	GND	N	10.4	20.0	56.0
12.525000	42.0	10000.0	9.000	GND	N	10.9	18.0	60.0
17.704500	41.4	10000.0	9.000	GND	L1	11.3	18.6	60.0
20.391000	38.9	10000.0	9.000	GND	N	11.3	21.1	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	33.6	10000.0	9.000	GND	L1	10.2	22.5	56.0
0.199500	38.3	10000.0	9.000	GND	N	10.3	15.3	53.6
0.339000	33.2	10000.0	9.000	GND	N	10.3	16.0	49.2
0.609000	28.3	10000.0	9.000	GND	N	10.4	17.7	46.0
0.897000	27.6	10000.0	9.000	GND	N	10.4	18.4	46.0
17.587500	33.8	10000.0	9.000	GND	L1	11.3	16.2	50.0

Charging Mode, Set.3

Figure A.12 Conducted Emission

Final Result 1

Frequency	QuasiPeak	Meas. Time	Bandwidth	PE	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	(ms)	(kHz)			(dB)	(dB)	(dBµV)
0.550500	46.6	10000.0	9.000	GND	L1	10.3	9.4	56.0
0.942000	42.9	10000.0	9.000	GND	L1	10.4	13.1	56.0
1.617000	44.0	10000.0	9.000	GND	L1	10.4	12.0	56.0
2.152500	46.7	10000.0	9.000	GND	L1	10.4	9.3	56.0
4.929000	45.6	10000.0	9.000	GND	L1	10.5	10.5	56.0
20.422500	36.3	10000.0	9.000	GND	L1	11.4	23.7	60.0

Final Result 2

Frequency	Average	Meas. Time	Bandwidth	PE	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	(ms)	(kHz)			(dB)	(dB)	(dBµV)
0.541500	36.3	10000.0	9.000	GND	L1	10.3	9.7	46.0
1.666500	34.8	10000.0	9.000	GND	L1	10.4	11.2	46.0
1.716000	37.7	10000.0	9.000	GND	L1	10.4	8.3	46.0
2.647500	36.1	10000.0	9.000	GND	L1	10.5	9.9	46.0
4.924500	37.0	10000.0	9.000	GND	L1	10.5	9.0	46.0
20.044500	24.2	10000.0	9.000	GND	L1	11.4	25.8	50.0

ANNEX B: Persons involved in this testing

Test Item	Tester
Radiated Emission	Zhao Wenhui
Conducted Emission	Li Zongliang

END OF REPORT