





# TEST REPORT No. I19Z70269-WMD02

for

Samsung Electronics. Co., Ltd.

Mobole phone

Model Name: SM-A015F/DS,SM-A015F

FCC ID: ZCASMA015F

with

Hardware Version: REV.1.0

Software Version: A015F.001(A015FXXE0ASI1)

Issued Date: 2019-11-04

#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504 Email: <a href="mailto:cttl">cttl</a> terminals@caict.ac.cn, website: www.caict.ac.cn





# **REPORT HISTORY**

Report Number Revision		Description	Issue Date	
I19Z70269-WMD02	Rev.0	1 <sup>st</sup> edition	2019-11-04	

Note: the latest revision of the test report supersedes all previous version.





# **CONTENTS**

1.	TEST LABORATORY	4
1.1.	INTRODUCTION & ACCREDITATION	4
1.2.	TESTING LOCATION	4
1.3.	TESTING ENVIRONMENT	5
1.4.	PROJECT DATA	5
1.5.	SIGNATURE	5
2.	CLIENT INFORMATION	6
2.1.	APPLICANT INFORMATION	6
2.2.	MANUFACTURER INFORMATION	6
3.	EQUIPMENT UNDERTEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1.	ABOUT EUT	7
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
4.	REFERENCE DOCUMENTS	8
4.1.	REFERENCE DOCUMENTS FOR TESTING	8
5.	LABORATORY ENVIRONMENT	9
6.	SUMMARY OF TEST RESULT	0
6.1.	SUMMARY OF TEST RESULTS	0
7.	TEST EQUIPMENT UTILIZED	1
AN	NEX A: MEASUREMENT RESULTS1	2
A	.1 OUTPUT POWER	2
A	.2 EMISSION LIMIT	6
A	.3 FREQUENCY STABILITY20	0
	.4 OCCUPIED BANDWIDTH2	
A	.5 EMISSION BANDWIDTH	5
A	.6 BAND EDGE COMPLIANCE	7
A	.7 CONDUCTED SPURIOUS EMISSION	9
AN	NEX B: ACCREDITATION CERTIFICATE	3





# 1. Test Laboratory

## 1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

#### 1.2. Testing Location

Location 1: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China 100191

Location 2: CTTL (Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China 100191

Location 3: CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology

Development Area, Beijing, P. R. China 100176





# 1.3. <u>Testing Environment</u>

Normal Temperature:  $15-35^{\circ}$ C Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-09-15
Testing End Date: 2019-11-01

1.5. Signature

東原

Dong Yuan

(Prepared this test report)

周宇

Zhou Yu

(Reviewed this test report)

赵慧能

Zhao Hui Lin

Deputy Director of the laboratory (Approved this test report)





# 2. Client Information

# 2.1. Applicant Information

Company Name: Samsung Electronics. Co., Ltd.

R5, A Tower 22 Floor A-1,(Maetan dong)

Address / Post: 129, Samsung-ro, Yeongtong-gu, Suwon-Si, Gyeonggi-do 16677,

Korea

Contact: JP KIM

Email: jp426.kim@samsung.com

Telephone: +82-10-4376-0326

# 2.2. Manufacturer Information

Company Name: HUAQIN TELECOM HONG KONG LIMITED

Address /Post: FLAT/RM 510 5/F LINCOLN CENTER,20 YIP FUNG STREET

FANLING NT,HONG KONG

Contact: Dongling Li

Email: lidongling@huaqin.com

Telephone: +86 13632958367





# 3. Equipment UnderTest (EUT) and Ancillary Equipment (AE)

## 3.1. About EUT

Description Mobole phone

Model Name SM-A015F/DS,SM-A015F

FCC ID ZCASMA015F Antenna Embedded

Output power 20.50dBm maximum ERP measured for WCDMA Band V

Extreme vol. Limits 3.6VDC to 4.2VDC (nominal: 3.85VDC)

Extreme temp. Tolerance -10°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

## 3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	<b>HW Version</b>	SW Version	Date of receipt
LITO20	359471100062751/	REV.1.0	A015F.001	2019-09-15
UT02a	359471100062759	REV. 1.0	(A015FXXE0ASI1)	2019-09-15
UT19a	359471100096130/	REV.1.0	A015F.001	2019-09-26
UTTBA	359471100096138	KEV. 1.0	(A015FXXE0ASI1)	2019-09-20

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

# 3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Battery

AE1

Model Secondary Li-ion Battery

Manufacturer Ningde Amperex Technology Limited

Capacitance 2920mAh/3000mAh

AE2

Model Secondary Li-ion Battery

Manufacturer SCUD(Fujian) Electronics Co., Ltd.

Capacitance 2920mAh/3000mAh

<sup>\*</sup>AE ID: is used to identify the test sample in the lab internally.





# 4. Reference Documents

# 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-18
		Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
ANSI/TIA-102.CAAA	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT	2016
-E	METHODS	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	





# 5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	<1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters × 6.7 meters × 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	<±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz





# 6. SUMMARY OF TEST RESULT

# 6.1. Summary of test results

## **WCDMA Band V**

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	Р
2	Emission Limit	2.1051/22.917	Р
3	Frequency Stability	2.1055	Р
4	Occupied Bandwidth	2.1049	Р
5	Emission Bandwidth	22.917	Р
6	Band Edge Compliance	22.917	Р
7	Conducted Spurious Emission	22.917 P	

#### Terms used in Verdict column

Р	Pass. The EUT complies with the essential requirements in the standard.		
NP	Not Performed. The test was not performed by CTTL.		
NA	Not Applicable. The test was not applicable.		
BR	Re-use test data from basic model report.		
F	Fail. The EUT does not comply with the essential requirements in the		
	standard.		





# 7. Test Equipment Utilized

NO.	Description	Туре	Series Number	Manufacture	Cal Due Date	Calibration Interval
1	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2019-11-20	1 year
2	EMI Antenna	3117	00058889	ETS-Lindgren	2020-01-12	3 years
3	EMI Antenna	3117	00119024	ETS-Lindgren	2020-02-25	3 years
4	Universal Radio Communication Tester	CMU200	108646	R&S	2020-01-03	1 year
5	Spectrum Analyzer	FSU26	200030	R&S	2020-06-03	1 year
6	EMI Antenna	9117	167	Schwarzbeck	2020-05-27	1 year
7	Signal Generator	N5183A	MY49060052	Agilent	2020-06-24	1 year
8	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
9	Test Receiver	E4440A	MY48250642	Agilent	2020-03-18	1 year
10	Universal Radio Communication Tester	CMW500	143008	R&S	2019-11-26	1 year
11	Power Amplifier	5S1G4	0341863	AR	/	





# **ANNEX A: MEASUREMENT RESULTS**

## **A.1 OUTPUT POWER**

#### A.1.1 Summary

During the process of testing, the EUT was controlled via communication tester to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

#### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V; 1712.4MHz, 1732.4MHz and 1752.6MHz for WCDMA Band IV (bottom, middle and top of operational frequency range).

# WCDMA Band V Measurement result-QPSK

	CH	Frequency (MHz)	output power (dBm)
WCDMA	4132	826.4	23.61
(Band V)	4183	836.6	23.51
	4233	846.6	23.57





#### A.1.3 Radiated

#### A.1.3.1 Description


This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with rms detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test and the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The





test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the Amplifier and the Substitution Antenna.

The cable loss (P<sub>cl</sub>), the Substitution Antenna Gain (G<sub>a</sub>) and the Amplifier Gain (P<sub>Ag</sub>) should be recorded after test.

The measurement results are obtained as described below:

Power (EIRP) =  $P_{Mea} - P_{Ag} - P_{cl} - G_a$ 

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.





## **WCDMA Band V-ERP**

#### Limits

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

#### **Measurement result-QPSK**

Frequency	P <sub>Mea</sub>	P <sub>cl</sub>	P <sub>Ag</sub>	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
826.40	-21.89	2.25	45.76	0.93	2.15	20.40	38.45	18.05	Н
836.60	-21.57	2.26	45.66	0.82	2.15	20.50	38.45	17.95	Н
846.60	-22.24	2.26	45.56	0.81	2.15	19.72	38.45	18.73	Н

Frequency: 836.60MHz

 $Peak \; ERP \; (dBm) = P_{Mea}(-21.57dBm) - P_{cl}(2.26dB) - P_{Ag}(-45.66dB) - G_a \; (-0.82dB) - 2.15dB = 20.50dBm$ 

Note: Expanded measurement uncertainty is U = 2.84 dB, k = 2.





## A.2 EMISSION LIMIT


#### A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917, Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band V.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power  $(P_{Mea})$  is applied to the input of the





substitution antenna and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P<sub>pl</sub>) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G<sub>a</sub>) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (Ppl) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

Power (EIRP) =  $P_{Mea} - P_{pl} - G_a$ 

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP 2.15dBi.

#### A.2.2 Measurement Limit

Part 22.917 specifies that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

#### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.





## A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
	Low	30MHz-10GHz	Pass
WCDMA Band V	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass

## A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
	0.03~1	100kHz	300kHz	10
	1-2	1 MHz	3 MHz	2
WCDMA Band V	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3





## WCDMA BAND V Mode Channel 4132/826.4MHz

Frequency	P <sub>Mea</sub>	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1655.01	-60.53	3.57	5.22	2.15	-61.03	-13.00	48.03	Н
2481.00	-53.02	4.60	6.04	2.15	-53.73	-13.00	40.73	Н
3286.02	-54.97	5.28	7.69	2.15	-54.71	-13.00	41.71	V
4128.02	-56.02	6.04	9.03	2.15	-55.18	-13.00	42.18	Н
4936.01	-54.68	6.71	9.84	2.15	-53.70	-13.00	40.70	Н
5759.01	-53.98	7.25	10.55	2.15	-52.83	-13.00	39.83	V

## WCDMA BAND V Mode Channel 4183/836.6MHz

Frequency	P <sub>Mea</sub>	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1672.01	-59.97	3.58	5.19	2.15	-60.51	-13.00	47.51	Н
2490.00	-53.56	4.61	6.07	2.15	-54.25	-13.00	41.25	V
3350.02	-54.91	5.32	7.84	2.15	-54.54	-13.00	41.54	Н
4181.02	-53.81	6.16	9.08	2.15	-53.04	-13.00	40.04	V
5028.01	-55.79	6.57	9.94	2.15	-54.57	-13.00	41.57	Н
5858.01	-53.65	7.26	10.53	2.15	-52.53	-13.00	39.53	Н

# WCDMA BAND V Mode Channel 4233/846.6MHz

Frequency	P <sub>Mea</sub>	Path	Antenna	Correction	Peak ERP	Limit	Margin	Delerization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1713.01	-60.36	3.61	5.12	2.15	-61.00	-13.00	48.00	Н
2543.00	-52.78	4.66	6.18	2.15	-53.41	-13.00	40.41	Н
3386.02	-55.18	5.35	7.93	2.15	-54.75	-13.00	41.75	V
4232.02	-55.37	6.26	9.13	2.15	-54.65	-13.00	41.65	Н
5098.01	-55.53	6.77	10.04	2.15	-54.41	-13.00	41.41	Н
5953.01	-53.37	7.47	10.51	2.15	-52.48	-13.00	39.48	Н

Note: Expanded measurement uncertainty is U = 5.16 dB, k = 2.





## A.3 FREQUENCY STABILITY

#### A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -10℃.
- 3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II, WCDMA Band IV and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10℃ increments from -10℃ to +50℃. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10℃ increments from -10℃ to +50℃. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.2VDC, with a nominal voltage of 3.85VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.





# A.3.2 Measurement results

# **WCDMA Band V**

# Frequency Error vs Voltage-QPSK

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.6	-7.54	0.0090
3.85	4.03	0.0048
4.2	3.20	0.0038

# Frequency Error vs Temperature-QPSK

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-10	2.98	0.0036
0	-2.75	0.0033
10	-4.06	0.0049
20	2.35	0.0028
30	2.75	0.0033
40	-1.63	0.0019
50	-2.24	0.0027





## A.4 OCCUPIED BANDWIDTH

#### A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.






# WCDMA Band V (99% BW)-QPSK

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
826.4	4118.59
836.6	4134.62
846.6	4118.59

# WCDMA Band V Channel 4132-Occupied Bandwidth (99% BW)




Date: 18.SEP.2019 20:40:17






# Channel 4183-Occupied Bandwidth (99% BW)



Date: 18.SEP.2019 20:41:29

# Channel 4233-Occupied Bandwidth (99% BW)



Date: 18.SEP.2019 20:42:41





# **A.5 EMISSION BANDWIDTH**


#### A.5.1Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

## WCDMA Band V-QPSK

Frequency (MHz)	Emission Bandwidth (kHz)
826.40	4679.49
836.60	4679.49
846.60	4679.49

# WCDMA Band V Channel 4132-Emission Bandwidth




Date: 18.SEP.2019 20:44:55






## **Channel 4183-Emission Bandwidth**



Date: 18.SEP.2019 20:46:07

#### **Channel 4233-Emission Bandwidth**



Date: 18.SEP.2019 20:47:19





#### A.6 BAND EDGE COMPLIANCE


#### A.6.1 Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log (P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.






A.6.2 Measurement result WCDMA Band V-QPSK LOW BAND EDGE BLOCK-A (WCDMA Band  $\,\mathrm{V}$  )-Channel 4132



Date: 18.SEP.2019 20:48:43

# HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233



Date: 18.SEP.2019 20:49:02





## **A.7 CONDUCTED SPURIOUS EMISSION**

#### A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz).

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60





#### A. 7.2 Measurement Limit

Part 22.917 specifies that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.






#### A.7.3 Measurement result

#### **WCDMA Band V**

#### Channel 4132: 30MHz -8.49GHz


Spurious emission limit -13dBm.



Date: 18.SEP.2019 20:50:23

## Channel 4183: 30MHz -8.49GHz

Spurious emission limit -13dBm.




Date: 18.SEP.2019 20:50:39





# Channel 4233: 30MHz -8.49GHz

Spurious emission limit -13dBm.



Date: 18.SEP.2019 20:50:56





# **ANNEX B: Accreditation Certificate**

United States Department of Commerce National Institute of Standards and Technology



# Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

#### **Telecommunication Technology Labs, CAICT**

Beijing China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

#### **Electromagnetic Compatibility & Telecommunications**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2019-09-26 through 2020-09-30

Effective Dates

OF COMPLETE OF ANGEL

For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*