

FCC EVALUATION REPORT FOR CERTIFICATION

Applicant: JSYTEC Co., Ltd.

#621 Venture Complex II, Daegu Techno Park,

Hosan-Dong, Dalseo-Gu, Daegu, Korea

Attn: Mr. Sung-Ki Lee / Assistant Research Engineer

Date of Issue: December 20, 2011

Order Number: GETEC-C1-11-294

Test Report Number: GETEC-E3-11-133

Test Site: GUMI COLLEGE EMC CENTER

FCC Registration Number: (100749, 443957)

FCC ID. : ZCUA384-G

Applicant : JSYTEC Co., Ltd.

Rule Part(s)	: FCC Part 15 Subpart C-Intentional Radiator § 15.247
Test method	: Public Notice DA 00-705 (Guidance on measurement for Frequency hopping spread spectrum system)
Equipment Class	: Part 15 Spread Spectrum Transmitter (DSS)
EUT Type	: Car Multimedia System
Type of Authority	: Certification
Model Name	: A384-G, S-81ACRD, S-84SNTA, S-85ELTR, S-86OPTM, V-81ACRD V-81SONA, V-82ELAN, V-81OPTM
Trade Name	: INGENIX, JSYTEC

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the vest of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,


Seung-Chul Lee, Associate Engineer
GUMI COLLEGE EMC CENTER

Reviewed by,


Jae-Hoon Jeong, Senior Engineer
GUMI COLLEGE EMC CENTER



CONTENTS

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
3. PRODUCT INFORMATION	6
3.1 DESCRIPTION OF EUT.....	6
3.2 SUPPORT EQUIPMENT / CABLES USED	7
3.3 MODIFICATION ITEM(S)	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
5. ANTENNA REQUIREMENT - §15.203	8
5.1 DESCRIPTION OF ANTENNA.....	8
5.2 CONDUCTED EMISSION	9
5.3 RADIATED EMISSION.....	10
6. NUMBER OF HOPPING FREQUENCY USED	11
6.1 OPERATING ENVIRONMENT	11
6.2 TEST SET-UP (LAYOUT)	11
6.3 LIMIT	11
6.4 TEST EQUIPMENT USED.....	11
6.5 TEST RESULT	11
7. DWELL TIME ON EACH CHANNEL.....	13
7.1 OPERATING ENVIRONMENT	13
7.2 TEST SET-UP (LAYOUT)	13
7.3 LIMIT	13
7.4 TEST EQUIPMENT USED.....	13
7.5 TEST RESULT	13
8. CHANNEL BANDWIDTH	15
8.1 OPERATING ENVIRONMENT.....	15
8.2 TEST SET-UP (LAYOUT)	15
8.3 LIMIT	15
8.4 TEST EQUIPMENT USED.....	15
8.5 TEST RESULT	15
9. LIMIT OF HOPPING CHANNEL SEPARATION	18
9.1 OPERATING ENVIRONMENT	18
9.2 TEST SET-UP (LAYOUT)	18
9.3 LIMIT	18
9.4 TEST EQUIPMENT USED.....	18
9.5 TEST RESULT	18
10. MAXIMUM PEAK OUTPUT POWER	21
10.1 OPERATING ENVIRONMENT	21
10.2 TEST SET-UP (LAYOUT)	21
10.3 LIMIT	21
10.4 TEST EQUIPMENT USED.....	21
11.5 TEST RESULT	21



11. BAND EDGES MEASUREMENT	22
11.1 OPERATING ENVIRONMENT	22
11.2 TEST SET-UP (LAYOUT)	22
11.3 LIMIT	22
11.4 TEST EQUIPMENT USED	22
11.5 TEST RESULT	22
12. RADIATED EMISSION	25
12.1 OPERATING ENVIRONMENT	25
12.2 TEST SET-UP	25
12.3 MEASUREMENT UNCERTAINTY	25
12.4 LIMIT	25
12.5 TEST EQUIPMENT USED	26
12.6 RADIATED EMISSION TEST DATA	26
 APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – LABELLING	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – SCHEMATIC DIAGRAM	
APPENDIX E – TEST SETUP PHOTOGRAPH	
APPENDIX F – EXTERNAL PHOTOGRAPH	
APPENDIX G – INTERNAL PHOTOGRAPH	
APPENDIX H – USER’S MANUAL	
APPENDIX I – OPERATIONAL DESCRIPTION	
APPENDIX J – ANTENNA SPECIFICATION	
APPENDIX K – PART LIST	
APPENDIX L – MAXIMUM PERMISSIBLE EXPOSURE	



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: JSYSTEC Co., Ltd.

**Applicant address: #621 Venture Complex II, Daegu Techno Park, Hosan-Dong,
Dalseo-Gu, Daegu, Korea**

Manufacturer: JSYSTEC Co., Ltd.

**Manufacturer address: #621 Venture Complex II, Daegu Techno Park, Hosan-Dong,
Dalseo-Gu, Daegu, Korea**

Contact person: Mr. Sung-Ki Lee / Assistant Research Engineer

Telephone number: +82-53-722-3123 Fax number: +82-53-815-5862

- **FCC ID.** ZCUA384-G
- **Equipment Class** Spread Spectrum Transmitter (DSS)
- **EUT Type** Car Multimedia System
- **Model Name** A384-G, S-81ACRD, S-84SNTA, S-85ELTR, S-86OPTM, V-81ACRD
V-81SONA, V-82ELAN, V-81OPTM
"These model names are given in accordance with user interface change (Icon design and background) that are not effect on EMC performance. All the electrical and mechanical characteristics are the same as basic model except model name designation."
- **Rule Part(s)** FCC Part 15, Subpart C-Intentional Radiator § 15.247
- **Test Method** Public Notice DA 00-705
(Guidance on measurement for frequency hopping spread spectrum systems)
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003)
- **Dates of Test** December 9 ~ 14, 2011
- **Place of Test** **GUMI COLLEGE EMC CENTER** (FCC Registration No.: 100749, 443957)
407, Bugok-Dong, Gumi-si, Gyeongsangbuk-Do, Korea
- **Test Report Number** GETEC-E3-11-133
- **Dates of Issue** December 20, 2011

EUT Type: Car Multimedia System

FCC ID.: ZCUA384-G



2. Introduction


The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **JSYSTEC Co., Ltd.**

Car Multimedia System (Model name: A384-G, S-81ACRD, S-84SNTA, S-85ELTR, S-86OPTM, V-81ACRD, V-81SONA, V-82ELAN, V-81OPTM)

These measurement tests were conducted at **GUMI COLLEGE EMC CENTER.**

The site address is 407, Bugok-Dong, Gumi-si, Gyeongsangbuk-Do, Korea

This test site is one of the highest point of Gumi 1 college at about 200 kilometers away from Seoul city and 40 kilometers away from Daejeon city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 on October 19, 1992



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongsangbuk-Do, Korea
Tel: +82-54-440-1195~8
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **JSYSTEC Co., Ltd.**

Car Multimedia System (Model name: A384-G, S-81ACRD, S-84SNTA, S-85ELTR, S-86OPTM, V-81ACRD, V-81SONA, V-82ELAN, V-81OPTM) FCC ID.: ZCUA384-G

Navigation portion of this equipment will be applied the "Verification (Class A digital device)" procedure.
(Report Number: GETEC-E3-11-134)

-. General	Rated voltage: DC 12 V Maximum current consumption: 1 000 mA Processor speed: 800 MHz NAND flash memory: 128 MB
-. Monitor	Screen size: 8 inch diagonal Aspect ratio: 16 × 9 Pixels per square inch: 14 066 Backlight: LED
-. Audio	Maximum power output: 4.0 V Pre-amp output: 5 band Equalizer: 62 / 100 Hz, 396 Hz, 1 kHz, 2.51 kHz, 15 / 16 kHz Equalizer adjustment: +/- 15 dB
-. Bluetooth	Version: 2.0 Output power: 0 dBm
-. RF Frequency	Bluetooth - Band(2.4 GHz ~ 2.483 5 GHz), Carrier Frequency(2 402 MHz ~ 2 480 MHz)
-. External Connector	MULTI BOX(USB, SD, AV-IN, AUX), IPOD, ATSC-M/H, GPS, MIC, SPEAKER, AV-OUT (CVBS, L, R), AUDIO-OUT (L, R), IR-Receiver, Rear camera, DVD-controller, DVD (CVBS, L, R)
-. GPS Receive Frequency	1 575.42 MHz (L1)



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
None.	-	-	S/N: - FCC ID.: -

See “Appendix E – Test Setup Photographs” for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
None	-	-	S/N: - FCC ID.: -

3.2.3 Used Cable(s)

Cable Name	Condition	Description
DC power cable	Connected to the EUT	0.10 m unshielded

3.3 Modification Item(s)

-. None



4. Description of tests

4.1 Test Condition


The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency:
DC 12 V (The EUT power is fed from car battery. So, the conducted emission test was skipped.)
- Test Mode(s): Bluetooth RF transmitting mode

-. Executed "Bluetest 3 (Copyright by CSR)" to control the EUT continuously transmit RF signal

Test Software Version	BlueTest3		
Frequency	2 402 MHz	2 441 MHz	2 480 MHz
Power [Ext/Int]	255/61	255/61	255/61



5. Antenna Requirement - §15.203

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the applicant can be used with the device. The use of permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

5.1 Description of Antenna

The **JSYTEC Co., Ltd. Car Multimedia System** comply with the requirement of §15.203 with a multilayer chip antenna permanently attached to the transmitter.



5.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



5.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m \times 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site.




6. NUMBER OF HOPPING FREQUENCY USED

6.1 Operating Environment

Temperature : 22.0 °C
Relative Humidity : 40.0 % R.H.

6.2 Test Set-up (Layout)



6.3 Limit

At least 15 channels frequencies, and should be equally spaced

6.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP30	Rohde & Schwarz	Spectrum Analyzer	101431	04. 17. 2012


6.5 Test Result

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(a)(1)(iii)
- Modulation : GFSK
- Operating Condition : Bluetooth RF transmitting mode
- Power Source : DC 12 V (Car battery)

Modulation	Total channel No.	Hopping channel No.	Limit	Result
GFSK	79	79	> 15	Complies



Number of Hopping frequency used Plot on Configuration GFSK






7. DWELL TIME ON EACH CHANNEL

7.1 Operating Environment

Temperature : 22.0 °C
Relative Humidity : 40.0 % R.H.

7.2 Test Set-up (Layout)



7.3 Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP30	Rohde & Schwarz	Spectrum Analyzer	101431	04. 17. 2012

7.5 Test Result

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(a)(1)(iii)
- Modulation : GFSK
- Operating Condition : Bluetooth RF transmitting mode
- Power Source : DC 12 V (Car battery)



Spectrum Parameter

- Attenuation : Auto
- Span frequency : zero
- Resolution band width : 100 kHz
- Video band with : 100 kHz
- Sweep time : 5 s

Mode	Number of transmission in a 31.6 (79 Hopping * 0.4)	Length of transmission time (ms)	Measured (ms)	Limit (ms)	Result
GFSK	10 (times / 5 s) * 6.32 = 63.2	2.94	185.808	400	Complies



Dwell time on each time used Plot on Configuration GFSK






8. CHANNEL BANDWIDTH

8.1 Operating environment

Temperature : 22.0 °C
Relative Humidity : 40.0 % R.H.

8.2 Test Set-up (Layout)



8.3 Limit

For frequency hopping system operating in the 2 400 MHz ~ 2 483.5 MHz, If the 20 dB bandwidth of hopping channel is greater than 25 kHz, two-thirds 20 dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

8.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP30	Rohde & Schwarz	Spectrum Analyzer	101431	04. 17. 2012

8.5 Test result

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(a)(1)(iii)
- Modulation : GFSK
- Operating Condition : Bluetooth RF transmitting mode
- Power Source : DC 12 V (Car battery)


Spectrum Parameter

- Attenuation : Auto
- Span frequency : zero
- Resolution band width : 100 kHz
- Video band with : 100 kHz
- Sweep time : 2.5 ms


Channel	Channel frequency (MHz)	20 dB bandwidth (MHz)	Result
0	2 402	1.120	Complies
39	2 441	1.115	Complies
78	2 480	1.125	Complies



Channel bandwidth used Plot on Configuration GFSK/0 CH (2 402 MHz)




Channel bandwidth used Plot on Configuration GFSK/39 CH (2 441 MHz)





Channel bandwidth used Plot on Configuration GFSK/78 CH (2 480 MHz)






9. LIMIT OF HOPPING CHANNEL SEPARATION

9.1 Operating Environment

Temperature : 22.0 °C
Relative Humidity : 40.0 % R.H.

9.2 Test Set-up (Layout)



9.3 Limit

For frequency hopping system operating in the 2 400 MHz ~ 2 483.5 MHz, If the 20 dB bandwidth of hopping channel is greater than 25 kHz, two-thirds 20 dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

9.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP30	Rohde & Schwarz	Spectrum Analyzer	101431	04. 17. 2012

9.5 Test Result

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(a)(1)
- Modulation : GFSK
- Operating Condition : Bluetooth RF transmitting mode
- Power Source : DC 12 V (Car battery)


Spectrum Parameter

- Attenuation : Auto
- Span frequency : 2 MHz
- Resolution band width : 100 kHz
- Video band with : 100 kHz
- Sweep time : 2.5 ms


Channel	Channel frequency (MHz)	Adjacent channel Separation (MHz)	Limit (MHz) [2/3 of 20 dB bandwidth]	Result
0	2 402	1	> 0.746	Complies
39	2 441	1	> 0.743	Complies
78	2 480	1	> 0.745	Complies



Channel separation used Plot on Configuration GFSK/0 CH (2 402 MHz)




Channel separation used Plot on Configuration GFSK/39 CH (2 441 MHz)





Channel separation used Plot on Configuration GFSK/78 CH (2 480 MHz)






10. MAXIMUM PEAK OUTPUT POWER

10.1 Operating Environment

Temperature : 22.0 °C
Relative Humidity : 40.0 % R.H.

10.2 Test Set-up (Layout)



10.3 Limit

The maximum peak output power measurement is 125 mW

10.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - NRVD	Rohde & Schwarz	Power meter	837794/048	12.06.2012
■ - NRV-Z32	Rohde & Schwarz	Power sensor	100062	10.19.2012

11.5 Test Result

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(b)
- Modulation : GFSK
- Operating Condition : Bluetooth RF transmitting mode
- Power Source : DC 12 V (Car battery)

Channel	Channel Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Limit (mW)	Result
0	2 402	- 2.89	0.514	125	Complies
39	2 441	- 2.19	0.603	125	Complies
78	2 480	- 1.09	0.778	125	Complies




11. BAND EDGES MEASUREMENT

11.1 Operating Environment

Temperature : 22.0 °C
Relative Humidity : 40.0 % R.H.

11.2 Test Set-up (Layout)



11.3 Limit

Below -20 dB of the highest emission level of operating band (in 100 kHz resolution band width)

11.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP30	Rohde & Schwarz	Spectrum Analyzer	101431	04. 17. 2012

11.5 Test Result

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(b)
- Modulation : GFSK
- Operating Condition : Bluetooth RF transmitting mode
- Power Source : DC 12 V (Car battery)



The spectrum plots are attached on the following 8 images, D1 line indicates the highest level, D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement in part 15.247(d)



Spectrum Parameter

- Attenuation : Auto
- Resolution bandwidth : 100 kHz
- Video bandwidth : 100 kHz



Band edge used Plot on Configuration GFSK







12. RADIATED EMISSION

12.1 Operating Environment

Temperature : 24.0 °C
Relative Humidity : 43.0 % R.H.

12.2 Test Set-up

The formal radiated emission was measured at 3 m distance anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

12.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items (Anechoic chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.09 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 3.78 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.85 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 4.11 dB	Confidence level of approximately 95 % ($k = 2$)

12.4 Limit

20 dB in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2 400/F (kHz)	300
0.490 ~ 1.705	2 400/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



12.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	12. 05. 2012
■ - HFH2-Z2	Rohde & Schwarz	Loop Antenna	100041	12. 15. 2011
■ - VULB9160	Schwarzbeck	Broadband test antenna	3193	03. 15. 2012
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - BBHA9120D	Schwarzbeck	Horn antenna	207	12. 22. 2011
■ - 3160-09	ETS LINDGREN	Horn antenna	LM3423	04. 06. 2012
■ - AFS44-00101800-25-10P-44	MITEQ	Preamplifier	1258942	11. 12. 2012
■ - AFS44-00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2012

12.6 Radiated emission test data

- Test Date : December 13, 2011
- Reference Standard : Part 15 Subpart C, Sec. 15.247(d)
- Modulation / Channel : GFSK (0 CH / 39 CH / 78 CH)
- Operating Condition : RF transmitting mode
- Measuring Distance : 3 m
- Power Source : DC 12 V (Car battery)
- Note : This equipment is used in a fixed location.
- Measurement


Frequency range	9 kHz ~ 90 kHz, 110 kHz ~ 150 kHz	90 kHz ~ 110 kHz	150 kHz ~ 490 kHz	490 kHz ~ 30 MHz	30 MHz ~ 1 GHz	Above 1 GHz
Detector type	Peak / Average	Quasi peak	Peak / Average	Quasi peak	Quasi peak	Peak / Average
IF bandwidth	200 Hz	200 Hz	9 kHz	9 kHz	120 kHz	1 MHz



Result of radiated emission (9 kHz to 30 MHz)

No emission found between lowest internal used/generated frequencies to 30 MHz

Worst case result of radiated emission (30 MHz to 1 000 MHz): GFSK




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
31.040000	32.9	1000.0	120.000	100.0	V	339.0	12.5	7.1	40.0
62.463750	26.7	1000.0	120.000	100.0	V	305.0	12.3	13.3	40.0
93.117500	26.9	1000.0	120.000	130.0	V	-24.0	9.6	16.6	43.5
156.161250	22.5	1000.0	120.000	100.0	V	247.0	14.1	21.0	43.5
187.402500	32.4	1000.0	120.000	100.0	V	32.0	12.1	11.1	43.5
312.371250	38.2	1000.0	120.000	100.0	H	140.0	15.5	7.8	46.0
366.771250	28.5	1000.0	120.000	100.0	H	155.0	16.9	17.5	46.0
792.037500	45.6	1000.0	120.000	121.0	H	192.0	26.4	0.4	46.0



Worst case result of radiated emission (1 GHz to 25 GHz): GFSK

Frequency (MHz)	Measurement Level					Limit (dBμ V/m)		Margin (dB)		Positioning System			
	Reading Value (dBμ V/m)		AF	AMP / CL	Test Result (dBμ V/m)					Pol.	Height	Angle	
	Peak	Average	(dB/m)	(dB)	Peak	Average	Peak	Average	(H/V)	(cm)	(°)		
	Peak	Average	(dB/m)	(dB)	Peak	Average	Peak	Average	(H/V)	(cm)	(°)		
All frequencies	<<	<<	-	-	<<	<<	74.00	54.00	<<	<<	-	-	-



*Comment : AMP/CL_ Cable loss value + AMP gain value
AF : Antenna factor value
Pol. : H(Horizontal), V(Vertical)

Result of radiated emission (Band Edge)

0 CH (Restrict band: 2310 MHz ~ 2390 MHz)

Frequency (MHz)	Measurement Level					Limit (dBμ V/m)		Margin (dB)		Positioning System			
	Reading Value (dBμ V)		AF	AMP / CL	Test Result (dBμ V/m)					Pol.	Height	Angle	
	Peak	Average	(dB/m)	(dB)	Peak	Average	Peak	Average	(H/V)	(cm)	(°)		
2385.97	51.19	37.39	26.95	-36.94	41.20	27.40	74.00	54.00	32.80	26.60	V	200	254

79 CH (Restrict band: 2483.5 MHz ~ 2500 MHz)

Frequency (MHz)	Measurement Level						Limit (dBμ V/m)		Margin (dB)		Positioning System		
	Reading Value (dBμ V)		AF	AMP / CL	Test Result (dBμ V/m)						Pol.	Height	Angle
	Peak	Average	(dB/m)	(dB)	Peak	Average	(H/V)	(cm)	(°)				
	2483.50	65.97	51.37	27.21	-36.78	56.40	41.80	74.00	54.00	17.60	12.20	V	150

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBμV/m) = 20 log Emission level (μV/m).


Corrected reading: Antenna factor + Cable loss + Preamplifier gain + Read value = Test result



Result of radiated emission (1 GHz to 10th harmonics)

(GFSK, 0 CH / 2 402 MHz)


Frequency (MHz)	Measurement Level						Limit (dBμ V/m)		Margin (dB)		Positioning System		
	Reading Value (dBμ V/m)		AF	AMP / CL	Test Result (dBμ V/m)						Pol.	Height	Angle
	Peak	Average	(dB/m)	(dB)	Peak	Average	Peak	Average	Peak	Average	(H/V)	(cm)	(°)
4803.81	61.73	41.73	31.20	-32.83	60.10	40.10	74.00	54.00	13.90	13.90	H	115	161



*Comment : AMP/CL_Cable loss value + AMP gain value
AF : Antenna factor value
Pol. : H(Horizontal), V(Vertical)

(GFSK, 39 CH / 2 441 MHz)

Frequency (MHz)	Measurement Level					Limit (dBμ V/m)		Margin (dB)		Positioning System			
	Reading Value (dBμ V/m)		AF	AMP / CL	Test Result (dBμ V/m)					Pol. (H/V)	Height (cm)	Angle (°)	
	Peak	Average	(dB/m)	(dB)	Peak	Average	Peak	Average					
4881.93	63.83	50.53	31.34	-32.77	62.40	49.10	74.00	54.00	11.60	4.90	H	116	163




*Comment : AMP/CL_Cable loss value + AMP gain value
AF : Antenna factor value
Pol. : H(Horizontal), V(Vertical)



(GFSK, 78 CH / 2 480 MHz)

Frequency (MHz)	Measurement Level						Limit (dBμ V/m)		Margin (dB)		Positioning System		
	Reading Value (dBμ V/m)		AF	AMP / CL	Test Result (dBμ V/m)						Pol.	Height	Angle
	Peak	Average	(dB/m)	(dB)	Peak	Average	Peak	Average	Peak	Average	(H/V)	(cm)	(°)
4959.71	62.14	52.54	31.47	-32.71	60.90	51.30	74.00	54.00	13.10	2.70	H	146	167
9920.83	37.47	23.37	39.28	-21.95	54.80	40.70	74.00	54.00	19.20	13.30	H	100	151



*Comment : AMP/CL_ Cable loss value + AMP gain value
AF : Antenna factor value
Pol. : H(Horizontal), V(Vertical)

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBμV/m) = 20 log Emission level (μV/m).

Corrected Reading: Reading value + AF (Antenna Factor) +AMP/CL (Cable Loss + Preamp factor) = Test result

- The end -