FCC Test Report

Report No.: AGC02Y120701F2

FCC ID	:	ZDB-BRK3800BC
PRODUCT DESIGNATION	:	Bluetooth Keyboard
BRAND NAME	:	N/A
MODEL NAME	:	BRK3800BC ITIP-4000, BRK8800
CLIENT	:	Tianyu Technology Co., Ltd
DATE OF ISSUE	:	July 26, 2012
STANDARD(S)	:	FCC Part 15 Rules
REPORT VERSION	:	V1.0

*A*ttestation of *G*lobal *C*ompliance (Shenzhen) Co., Ltd.

VERIFICATION OF COMPLIANCE

Applicant	Tianyu Technology Co., Ltd
	No 5, 3rd Beian Road, Huangjiang Town, Dongguan City, China
Manufacturer	Tianyu Technology Co., Ltd
	No 5, 3rd Beian Road, Huangjiang Town, Dongguan City, China
Product Designation	Bluetooth Keyboard
Brand Name	N/A
Test Model	BRK3800BC ITIP-4000
Series Model	BRK8800
Model Difference	All models are the same except for appearance (color and size).
FCC ID	**ZDB-BRK3800BC**
Report Number	AGC02Y120701F2
Date of Test	July 23, 2012 to July 25, 2012

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Tested By: _____

Leo Lee   July 26, 2012

Reviewed By: _____

Forrest Lei   July 26, 2012

Approved By: _____

Solger Zhang   July 26, 2012

TABLE OF CONTENTS

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **Bluetooth Keyboard** designed as a "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following:

Operation Frequency	2.402 GHz to 2.480GHz
Max. Output Power	2.67dBm for GFSK modulation
Bluetooth Version	V3.0
Modulation	GFSK, π /4-DQPSK, 8DPSK
Number of channels	79
Antenna Designation	Integrated Antenna
Antenna Gain	0.8dBi
Hardware Version	N/A
Software Version	N/A
Power Supply	DC3.7V by Built-in Li-ion Battery

1.2 TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

1.3 RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3 MHz. In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection (e.g. single of multisport (packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

1.4 EXAMPLE OF A HOPPING SEQUENCE IN DATA MODE

Example of a 79 hopping sequence in data mode:
40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06
01,51,03,55,05,04

1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:
1 LAP/UAP of the master of the connection
2 Internal master clock
The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is
an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of
the 48BD_ADDRESS
The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and
Is never turned off. For synchronization with other units only offset are used. It has no relation to the time
Of the day. Its resolution is at least half the RX/TX slot length of 312.5us.The clock has a cycle of about
One day(23h30).In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence
the entire.
LAP(24 bits),4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values
different mathematical procedures(permutations, additions, XOR-operations)are performed to generate te
Sequence. This will be done at the beginning of every new transmission.
Regarding short transmissions the Bluetooth system has the following behavior:
The first connection between the two devices is established, a hopping sequence was generated. For
Transmitting the wanted data the complete hopping sequence was not used. The connection ended.
The second connection will be established. A new hopping sequence is generated. Due to the fact the
Bluetooth clock has a different value, because the period between the two transmission is longer(and it
Cannot be shorter)than the minimum resolution of the clock(312.5us).The hopping sequence will always
Differ from the first one.

1.6 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: ZDB-BRK3800BC**, filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.7 TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.8 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.
- Uncertainty of Conducted Emission, Uc = ±2.75dB
- Uncertainty of Radiated Emission, Uc = ±3.2dB

1.9 TEST FACILITY

All measurement facilities used to collect the measurement data are located at
Attestation of Global Compliance (Shenzhen) Co., Ltd.
2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China
The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.
FCC register No.: 259865

1.10 SPECIAL ACCESSORIES
Refer to section 2.2.

1.11 EQUIPMENT MODIFICATIONS
Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 CONFIGURATION OF TESTED SYSTEM
Configure 1 (Normal Hopping mode)

```
┌──────────────┐
│              │
│     EUT      │
│              │
└──────────────┘
```

Configure 2 (Control continuous TX through PC)

```
┌──────────────┐   ┌──────────────┐
│              │   │              │
│     EUT      │───│     PC       │
│              │   │              │
└──────────────┘   └──────────────┘
```

Note: All the accessories have been used during the test.

2.2 EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bluetooth Keyboard	N/A	BRK3800BC ITIP-4000	EUT
2	PC	DELL	INSPIRON	A.E

3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Peak Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.207	Conduction Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant
§15.247	Frequency Separation	Compliant

***Note: BT is active when charging.** The USB port only used for charging and can't be used to transfer data with PC.*

4. DESCRIPTION OF TEST MODES

The EUT has been operated in three modulations: GFSK, π /4-DQPSK, 8-DPSK independently.
The following operating modes were applied for the related test items. All 3axis have been tested.

No.	TEST MODES
1	Low Channel(TX)
2	Middle Channel(TX)
3	High Channel(TX)
4	Normal Hopping

***Note:** All the test modes were tested, and the battery is full filled, only the result of the worst case was recorded in the report.

5. PEAK OUTPUT POWER

5.1 MEASUREMENT PROCEDURE

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Set Span = approximately 5 times the 20 dB bandwidth, centered on a hoping channel
   RBW > the 20 dB bandwidth of the emission being measured
   VBW $\geq$ RBW; Sweep = auto; Detector function = peak.
5. Set SPA Trace 1 Max hold, then View.

5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

5.3 MEASUREMENT EQUIPMENT USED

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	07/18/2012	07/17/2013

5.4 LIMITS AND MEASUREMENT RESULT

PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MODULATION			
Frequency (GHz)	Result (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	2.67	30	Pass
2.441	2.61	30	Pass
2.480	2.56	30	Pass

PEAK OUTPUT POWER MEASUREMENT RESULT FOR Π /4-DQPSK, 8DPSK MODULATION				
Frequency (GHz)	Test Result 2 Mbps (dBm)	Test Result 3 Mbps (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	1.33	1.21	30	Pass
2.441	1.27	1.16	30	Pass
2.480	1.22	1.11	30	Pass

6. 20 dB BANDWIDTH

6.1 MEASUREMENT PROCEDURE
1. The EUT was placed on a table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel
   RBW $\geq$ 1% of the 20 dB bandwidth, VBW $\geq$ RBW; Sweep = auto; Detector function = peak
5. Set SPA Trace 1 Max hold, then View.

6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)
The same as described in Section 5.2

6.3 MEASUREMENT EQUIPMENT USED
The same as described in Section 5.3

6.4 LIMITS AND MEASUREMENT RESULTS

THE MEASUREMENT RESULT WITH THE WORST CASE OF 3MBPS FOR 8-DPSK MODULATION		
Applicable Limits	Measurement Result	
	Test Data (MHz)	Criteria
--	Low Channel	1.092	PASS
	Middle Channel	1.107	PASS
	High Channel	1.111	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL

7. CONDUCTED SPURIOUS EMISSION
7.1 MEASUREMENT PROCEDURE
1. The EUT was placed on a table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
   RBW = 100 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak.
5. Set SPA Trace 1 Max hold, then View.

7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)
The same as described in section 5.2

7.3 MEASUREMENT EQUIPMENT USED
The same as described in section 5.3

7.4 LIMITS AND MEASUREMENT RESULT

<table>
<tr><th colspan="3">LIMITS AND MEASUREMENT RESULT</th></tr>
<tr><th rowspan="2">Applicable Limits</th><th colspan="2">Measurement Result</th></tr>
<tr><th>Test Data</th><th>Criteria</th></tr>
<tr><td rowspan="2">In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.

In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))</td><td>At least -20dBc than the limit Specified on the BOTTOM Channel</td><td>PASS</td></tr>
<tr><td>At least -20dBc than the limit Specified on the TOP Channel</td><td>PASS</td></tr>
</table>

TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE
OF 1 MBPS FOR GFSK MODULATION IN LOW CHANNEL

8. RADIATED EMISSION
8.1 MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.

3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.

4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.

6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.

7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.

9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.'

Spectrum Parameter	Setting
Start Frequency	1GHz
Stop Frequency	26.5GHz
RB/VB(Emission in restricted band)	1MHz/1MHz for Peak, 1MHz/10Hz for Average
RB/VB(Emission in non-restricted band)	1MHz/1MHz for Peak

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.2 TEST SETUP

RADIATED EMISSION TEST SETUP BELOW 30MHz

RADIATED EMISSION TEST SETUP 30MHz-1000MHz

RADIATED EMISSION TEST SETUP ABOVE 1000MHz

8.3 TEST EQUIMENT LIST

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	07/18/2012	07/17/2013
Amplifier	EM	EM30180	0607030	07/18/2012	07/17/2013
Horn Antenna	EM	EM-AH-10180	N/A	07/18/2012	07/17/2013
EMI Test Receiver	Rohde & Schwarz	ESCI	N/A	07/18/2012	07/17/2013
Amplifier	EM	EM30180	N/A	07/18/2012	07/17/2013
Biological Antenna	A.H. Systems Inc.	SAS-521-4	N/A	07/18/2012	07/17/2013
Loop Antenna	Daze	ZN30900N	SEL0097	07/18/2012	07/17/2013
Isolation Transformer	LETEAC	LTBK	--	07/18/2012	07/17/2013

8.4 TEST RESULT

The worst case is Normal Hopping Mode.

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

Site:	site #1		Polarization:	*Horizontal*	Temperature: 26
Limit:	FCC Class B 3M Radiation		Power:		Humidity: 60 %
EUT:	Bluetooth Keyboard		Distance: 3m		
M/N:	BRK3800BC ITIP-4000				
Mode:	Normal Hopping				
Note:					

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		59.1000	25.34	3.63	28.97	40.00	-11.03	peak			
2		143.1667	10.11	12.76	22.87	43.50	-20.63	peak			
3		303.2167	16.66	17.21	33.87	46.00	-12.13	peak			
4		439.0167	13.54	21.43	34.97	46.00	-11.03	peak			
5	*	642.7167	14.49	24.61	39.10	46.00	-6.90	peak			
6		856.1167	7.14	29.54	36.68	46.00	-9.32	peak			

Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Keyboard

M/N: BRK3800BC ITIP-4000

Mode: Normal Hopping

Note:

Polarization: *Vertical*

Power:

Distance: 3m

Temperature: 26

Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		84.9666	17.28	13.89	31.17	40.00	-8.83	peak			
2		183.5833	21.50	10.66	32.16	43.50	-11.34	peak			
3		287.0500	13.45	17.13	30.58	46.00	-15.42	peak			
4		430.9333	13.76	21.01	34.77	46.00	-11.23	peak			
5	*	649.1833	15.54	24.32	39.86	46.00	-6.14	peak			
6		839.9500	5.22	31.34	36.56	46.00	-9.44	peak			

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics)

Site: site #1	Polarization: *Horizontal*	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Keyboard	Distance: 3m	
M/N: BRK3800BC ITIP-4000		
Mode: Normal Hopping		
Note:		

No.	Mk.	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	X	2402.000	66.29	10.32	76.61	74.00	2.61	peak			
2	*	2480.000	66.26	10.41	76.67	74.00	2.67	peak			
3		2960.000	32.68	11.54	44.22	74.00	-29.78	peak			
4		4793.333	39.59	7.66	47.25	74.00	-26.75	peak			

Site: site #1

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

EUT: Bluetooth Keyboard

M/N: BRK3800BC ITIP-4000

Mode: Normal Hopping

Note:

Polarization: *Vertical*

Power:

Distance: 3m

Temperature: 26

Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	X	2402.000	65.57	10.32	75.89	74.00	1.89	peak			
2	*	2480.000	65.67	10.41	76.08	74.00	2.08	peak			
3		2906.667	32.44	11.41	43.85	74.00	-30.15	peak			
4		4820.000	41.91	7.73	49.64	74.00	-24.36	peak			

Note: 5~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain, Over=Measurement-Limit.

9. BAND EDGES EMISSION
9.1 MEASUREMENT PROCEDURE
1, Set the EUT Work on the top, the bottom operation frequency individually.

2. Set SPA Start or Stop Frequency = Operation Frequency, RBW>=1%span, VBW>=RBW

3. The band edges was measured and recorded.

9.2 TEST SET-UP
The same as described in section 8.2

9.3 TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL (3Mbps)

Site: site #1	Polarization: *Horizontal*	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Keyboard	Distance: 3m	
M/N: BRK3800BC ITIP-4000		
Mode: Low Channel-TX(3Mbps)		
Note:		

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2392.250	23.66	10.31	33.97	74.00	-40.03	peak			
2		2400.000	22.96	10.32	33.28	74.00	-40.72	peak			
3	*	2402.000	66.52	10.32	76.84	74.00	2.84	peak			

Site:	site #1	Polarization:	*Vertical*	Temperature:	26
Limit:	FCC Class B 3M Radiation above 1GHZ(PK)	Power:		Humidity:	60 %
EUT:	Bluetooth Keyboard	Distance:	3m		
M/N:	BRK3800BC ITIP-4000				
Mode:	Low Channel-TX(3Mbps)				
Note:					

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2389.500	22.78	10.31	33.09	74.00	-40.91	peak			
2		2400.000	25.23	10.32	35.55	74.00	-38.45	peak			
3	*	2402.000	65.84	10.32	76.16	74.00	2.16	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (3Mbps)

Site: site #1

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

EUT: Bluetooth Keyboard

M/N: BRK3800BC ITIP-4000

Mode: High Channel-TX(3Mbps)

Note:

Polarization: *Horizontal*

Power:

Distance: 3m

Temperature: 26

Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	66.03	10.41	76.44	74.00	2.44	peak			
2		2483.500	21.57	10.41	31.98	74.00	-42.02	peak			
3		2487.643	24.73	10.42	35.15	74.00	-38.85	peak			

Site:	site #1	Polarization:	*Vertical*	Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Keyboard Distance: 3m

M/N: BRK3800BC ITIP-4000

Mode: High Channel-TX(3Mbps)

Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	66.83	10.41	77.24	74.00	3.24	peak			
2		2483.500	23.15	10.41	33.56	74.00	-40.44	peak			
3		2491.897	24.73	10.42	35.15	74.00	-38.85	peak			

10. NUMBER OF HOPPING FREQUENCY

10.1 MEASUREMENT PROCEDURE
1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
4. Set the Spectrum Analyzer as RBW>=1%span, VBW>=RBW.

10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2
Conducted Method.

10.3 MEASUREMENT EQUIPMENT USED
The same as described in section 5.3

10.4 LIMITS AND MEASUREMENT RESULT

TOTAL NO. OF HOPPING CHANNEL	LIMIT (NO. OF CH)	MEASUREMENT (NO. OF CH)	RESULT
	>=15	79	PASS

TEST PLOT FOR NO. OF TOTAL CHANNELS

11. TIME OF OCCUPANCY (DWELL TIME)

11.1 MEASUREMENT PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
3. Set Span = zero span, centered on a hoping channel.
4. Set the spectrum analyzer as RBW=1MHz, VBW>=RBW, Span = 0 Hz.

11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2
Conducted Method

11.3 MEASUREMENT EQUIPMENT USED

The same as described in section 5.3

11.4 LIMITS AND MEASUREMENT RESULT

Bluetooth 3Mbps Test Result

Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
Low	2.863	31.6	305.39	400
Middle	2.863	31.6	305.39	400
High	2.883	31.6	307.52	400

Low Channel Time
2.863*(1600/6)/79*31.6=305.39ms
Middle Channel Time
2.863*(1600/6)/79*31.6=305.39ms
High Channel Time
2.883*(1600/6)/79*31.6=307.52ms

TEST PLOT OF LOW CHANNEL

TEST PLOT OF MIDDLE CHANNEL

TEST PLOT OF HIGH CHANNEL

12. FREQUENCY SEPARATION
12.1 MEASUREMENT PROCEDURE

1. Place the EUT on the table and set it in transmitting mode
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
3. Set Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span Video (or Average) Bandwidth (VBW) $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold

12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)
Same as described in section 5.2

12.3 MEASUREMENT EQUIPMENT USED

The same as described in section 5.3

12.4 LIMITS AND MEASUREMENT RESULT

BLUETOOTH 1MBPS TEST RESULT

CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT
	KHz	KHz	
CH00-CH01	1000	>=25 KHz or 2/3 20 dB BW	Pass

TEST PLOT FOR FREQUENCY SEPARATION (1Mbps)

13. CONDUCTED EMISSION

13.1 LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**Note: 1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

13.2 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST

13.3 PROCEDURE OF LINE CONDUCTED EMISSION TEST

1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2) Support equipment, if needed, was placed as per ANSI C63.4.
3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4) The EUT received DC 5V charging power by adapter which received 120V/60Hz power through a LISN.
5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
7) During the above scans, the emissions were maximized by cable manipulation.
8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition(s) was reported on the Summary Data page.

13.4 TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION – L

Site: Conduction

Limit: FCC Class B Conduction(QP)

EUT: Bluetooth Keyboard

M/N: BRK3800BC ITIP-4000

Mode: Normal Hopping

Note:

Phase: **L1**

Power:

Temperature: 26

Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2300	40.73		27.83	10.25	50.98		38.08	62.45	52.45	-11.47	-14.37	P	
2	0.4540	35.93		23.62	10.37	46.30		33.99	56.80	46.80	-10.50	-12.81	P	
3	0.5580	35.00		20.95	10.35	45.35		31.30	56.00	46.00	-10.65	-14.70	P	
4	0.9418	33.72		18.94	10.39	44.11		29.33	56.00	46.00	-11.89	-16.67	P	
5	2.5499	33.62		24.34	10.44	44.06		34.78	56.00	46.00	-11.94	-11.22	P	
6	17.5217	36.83		23.14	10.12	46.95		33.26	60.00	50.00	-13.05	-16.74	P	

LINE CONDUCTED EMISSION – N

Site: Conduction
Limit: FCC Class B Conduction(QP)
EUT: Bluetooth Keyboard
M/N: BRK3800BC ITIP-4000
Mode: Normal Hopping
Note:

Phase: **N**
Power:

Temperature: 26
Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2580	38.14		26.42	10.27	48.41		36.69	61.49	51.49	-13.08	-14.80	P	
2	0.4500	36.32		26.22	10.37	46.69		36.59	56.87	46.87	-10.18	-10.28	P	
3	1.0180	35.67		24.59	10.37	46.04		34.96	56.00	46.00	-9.96	-11.04	P	
4	1.3099	35.98		22.95	10.38	46.36		33.33	56.00	46.00	-9.64	-12.67	P	
5	2.0619	35.98		22.62	10.25	46.23		32.87	56.00	46.00	-9.77	-13.13	P	
6	16.7179	38.75		26.59	10.12	48.87		36.71	60.00	50.00	-11.13	-13.29	P	

APPENDIX I
PHOTOGRAPHS OF THE EUT
TOP VIEW OF EUT


BOTTOM VIEW OF EUT

LEFT VIEW OF EUT


RIGHT VIEW OF EUT

FRONT VIEW OF EUT

BACK VIEW OF EUT

OPEN VIEW OF EUT

INTERNAL VIEW-1 OF EUT

INTERNAL VIEW-2 OF EUT

INTERNAL VIEW-3 OF EUT

Bluetooth
Antenna

INTERNAL VIEW-4 OF EUT

APPENDIX II
PHOTOGRAPHS OF THE TEST SETUP
CONDUCTED EMISSION

RADIATED EMISSION

----END OF REPORT----