

FCC PART 15.247

TEST REPORT

For

ShenZhen Foscam Intelligent Technology Co., Ltd.

5/F, Block 1, Vision Business Park, Nanshan District, Shenzhen, PRC

FCC ID: ZDEFOSBABYP1

Report Type: Original Report	Product Type: Wireless HD Baby Monitor
Test Engineer: David Lee	David Lee
Report Number: RSZ141127004-00	
Report Date: 2014-12-08	
Reviewed By: RF Engineer	Jimmy Xiao
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION-	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	9
APPLICABLE STANDARD	9
RESULT	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA	27

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	37
FCC §15.247(e) - POWER SPECTRAL DENSITY	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
PRODUCT SIMILARITY DECLARATION LETTER	50

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *ShenZhen Foscam Intelligent Technology Co., Ltd.*'s product, model number: *FosBaby P1* (FCC ID: *ZDEFOSBABYP1*) or the "EUT" in this report was a *Wireless HD Baby Monitor*, which was measured approximately: 8.3 cm (L) x 6.5 cm (W) x 12.8 cm (H), rated with input voltage: DC 5.0 V from adapter.

Adapter information:

Model: FEF0500200A1WU

Input: AC 100-240V, 50/60 Hz, 0.3A

Output: DC 5.0V, 2.0 A

Note: The product, series models FosBaby P1S, FosBaby P2, FosBaby P2S, FosBaby P3, FosBaby P3S, FosBaby P4, FosBaby P4S, FosBaby P5, FosBaby P5S, FosBaby P6 and FosBaby P6S are electrically identical with the model FosBaby P1, that was selected for fully testing, They are only named different due to marketing purpose and identical schematics, the detailed information can be referred to the attached declaration letter that stated and guaranteed by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: 1411231 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2014-11-27.*

Objective

This report is prepared on behalf of *ShenZhen Foscam Intelligent Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration-

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

EUT was tested with Channel 1, 6 and 13.

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 4 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

EUT Exercise Software

Test software: MT7610 USB V1.0.4.0.

802.11b: Rate 1 MHz, Power level: 10

802.11g: Rate 6 MHz, Power level: 0B

802.11n-HT20: Rate MCS0, Power level: 0B

802.11n-HT40: Rate MCS0, Power level: 0B

Equipment Modifications


No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	Remark
BULL	Socket	GN-415K	5503290068073	/

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Un-detachable AC Power Cable	1.0	Mains	Socket
Un-shielding Detachable USB Cable	1.4	EUT	adapter

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b)(1), §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2437	2	1.58	18.82	76.21	20	0.024	1

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one IPEX antenna connector arrangement for Wi-Fi which the gain was 2.0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements may be receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 V_{AC}/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2014-06-03	2015-06-03
Rohde & Schwarz	LISN	EAH2-Z5	892107/021	2014-06-09	2015-06-09
Rohde & Schwarz	Transient limiter	ESH3Z2	DE25985	2014-05-14	2015-05-14
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the worst margin reading as below:

9.6 dB at 24.001970 MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$


In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	17 °C
Relative Humidity:	53 %
ATM Pressure:	101.0 kPa

The testing was performed by David Lee on 2014-12-04.


EUT operation mode: Transmitting

AC 120V/60 Hz, Line**EMI Auto Test L**

Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave.)
0.242501	36.4	19.3	62.0	25.6	QP
0.242501	24.5	19.3	52.0	27.5	Ave.
0.301470	35.3	19.2	60.2	24.9	QP
0.301470	26.1	19.2	50.2	24.1	Ave.
0.577390	34.1	19.3	56.0	21.9	QP
0.577390	25.7	19.3	46.0	20.3	Ave.
0.620730	38.5	19.3	56.0	17.5	QP
0.620730	30.1	19.3	46.0	15.9	Ave.
0.664130	28.1	19.3	56.0	27.9	QP
0.664130	17.0	19.3	46.0	29.0	Ave.
24.001970	42.8	20.0	60.0	17.2	QP
24.001970	40.4	20.0	50.0	9.6	Ave.

AC 120V/60 Hz, Neutral

EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave.)
0.534050	36.1	19.2	56.0	19.9	QP
0.534050	25.5	19.2	46.0	20.5	Ave.
0.577330	40.0	19.2	56.0	16.0	QP
0.577330	30.3	19.2	46.0	15.7	Ave.
0.616610	44.4	19.2	56.0	11.6	QP
0.616610	35.1	19.2	46.0	10.9	Ave.
0.857130	34.4	19.3	56.0	21.6	QP
0.857130	23.7	19.3	46.0	22.3	Ave.
0.920110	35.2	19.3	56.0	20.8	QP
0.920110	25.1	19.3	46.0	20.9	Ave.
1.034490	33.9	19.4	56.0	22.1	QP
1.034490	24.4	19.4	46.0	21.6	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, and it will not be taken into consideration for the test data recorded in the report

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to an AC 120V/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2014-05-06	2015-05-06
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2014-09-25	2015-09-25
Sunol Sciences	Broadband Antenna	JB3	A111513	2014-06-18	2017-06-17
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2014-04-03	2015-04-03
Sunol Sciences	Horn Antenna	DRH-118	A052304	2014-12-01	2015-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2014-11-12	2015-11-12
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2014-08-03	2015-08-03
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the worst margin reading as below:

0.89 dB at 164.7 MHz in the Vertical polarization for 802.11b mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	43 %
ATM Pressure:	101.0 kPa

The testing was performed by David Lee on 2014-12-05.

EUT operation mode: Transmitting

30 MHz-25 GHz:**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
164.7	56.22	QP	67	1.9	V	-15.30	40.92	43.50	2.58
2412.0	87.56	PK	3	2.0	H	6.13	93.69	/	/
2412.0	80.50	Ave.	3	2.0	H	6.13	86.63	/	/
2412.0	94.97	PK	272	2.1	V	6.13	101.1	/	/
2412.0	90.84	Ave.	272	2.1	V	6.13	96.97	/	/
2359.0	42.75	PK	198	1.2	H	5.48	48.23	74	25.77
2359.0	26.05	Ave.	198	1.2	H	5.48	31.53	54	22.47
2378.7	39.90	PK	109	2.2	H	5.48	45.38	74	28.62
2378.7	26.59	Ave.	109	2.2	H	5.48	32.07	54	21.93
2495.7	44.49	PK	355	1.7	V	7.21	51.70	74	22.30
2495.7	41.24	Ave.	355	1.7	V	7.21	48.45	54	5.55
4824.0	46.45	PK	45	1.9	H	12.44	58.89	74	15.11
4824.0	40.44	Ave.	45	1.9	H	12.44	52.88	54	1.12
7236.0	37.50	PK	233	1.9	V	17.06	54.56	74	19.44
7236.0	20.02	Ave.	233	1.9	V	17.06	37.08	54	16.92
9648.0	36.24	PK	184	1.4	V	19.28	55.52	74	18.48
9648.0	19.88	Ave.	184	1.4	V	19.28	39.16	54	14.84
Middle Channel (2437 MHz)									
164.7	56.02	QP	124	1.7	V	-15.30	40.72	43.50	2.78
2437.0	86.53	PK	246	1.4	H	6.13	92.66	/	/
2437.0	79.91	Ave.	246	1.4	H	6.13	86.04	/	/
2437.0	96.35	PK	329	2.1	V	6.13	102.48	/	/
2437.0	90.05	Ave.	329	2.1	V	6.13	96.18	/	/
2344.5	42.21	PK	48	2.4	H	5.48	47.69	74	26.31
2344.5	25.91	Ave.	48	2.4	H	5.48	31.39	54	22.61
2372.8	39.17	PK	63	1.7	H	5.48	44.65	74	29.35
2372.8	25.41	Ave.	63	1.7	H	5.48	30.89	54	23.11
2487.4	43.95	PK	330	1.2	V	7.21	51.16	74	22.84
2487.4	43.45	Ave.	330	1.2	V	7.21	50.66	54	3.34
4874.0	47.49	PK	167	1.1	V	12.4	59.89	74	14.11
4874.0	40.32	Ave.	167	1.1	V	12.4	52.72	54	1.28
7311.0	35.90	PK	142	2.1	H	16.62	52.52	74	21.48
7311.0	20.60	Ave.	142	2.1	H	16.62	37.22	54	16.78
9748.0	35.56	PK	195	1.5	H	19.4	54.96	74	19.04
9748.0	20.54	Ave.	195	1.5	H	19.4	39.94	54	14.06

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2472 MHz)									
164.7	57.91	QP	82	1.8	V	-15.30	42.61	43.50	0.89
2472.0	87.25	PK	23	2.0	H	7.21	94.46	/	/
2472.0	81.69	Ave.	23	2.0	H	7.21	88.9	/	/
2472.0	96.30	PK	238	1.1	V	7.21	103.51	/	/
2472.0	89.92	Ave.	238	1.1	V	7.21	97.13	/	/
2342.5	41.68	PK	285	2.0	H	5.48	47.16	74	26.84
2342.5	25.15	Ave.	285	2.0	H	5.48	30.63	54	23.37
2384.6	40.21	PK	292	2.0	H	5.48	45.69	74	28.31
2384.6	27.67	Ave.	292	2.0	H	5.48	33.15	54	20.85
2483.5	44.78	PK	229	2.1	H	7.21	51.99	74	22.01
2483.5	41.11	Ave.	229	2.1	H	7.21	48.32	54	5.68
2494.7	43.03	PK	159	1.6	V	7.21	50.24	74	23.76
2494.7	41.65	Ave.	159	1.6	V	7.21	48.86	54	5.14
4944.0	48.58	PK	310	2.0	V	12.46	61.04	74	12.96
4944.0	40.39	Ave.	310	2.0	V	12.46	52.85	54	1.15
7416.0	36.76	PK	174	1.4	H	15.91	52.67	74	21.33
7416.0	20.26	Ave.	174	1.4	H	15.91	36.17	54	17.83
9888.0	36.51	PK	37	1.1	H	19.39	55.90	74	18.10
9888.0	19.96	Ave.	37	1.1	H	19.39	39.35	54	14.65

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
164.7	57.54	QP	11	1.8	V	-15.30	42.24	43.50	1.26
2412.0	87.87	PK	175	2.1	H	6.13	94.00	/	/
2412.0	79.83	Ave.	175	2.1	H	6.13	85.96	/	/
2412.0	95.10	PK	161	1.8	V	6.13	101.23	/	/
2412.0	91.20	Ave.	161	1.8	V	6.13	97.33	/	/
2344.8	41.49	PK	125	1.7	H	5.48	46.97	74	27.03
2344.8	27.95	Ave.	125	1.7	H	5.48	33.43	54	20.57
2386.0	40.72	PK	207	1.8	H	5.48	46.20	74	27.80
2386.0	26.72	Ave.	207	1.8	H	5.48	32.20	54	21.80
2496.0	44.22	PK	197	1.4	V	7.21	51.43	74	22.57
2496.0	43.74	Ave.	197	1.4	V	7.21	50.95	54	3.05
4824.0	46.65	PK	160	2.5	V	12.44	59.09	74	14.91
4824.0	40.53	Ave.	160	2.5	V	12.44	52.97	54	1.03
7236.0	37.43	PK	60	1.5	V	17.06	54.49	74	19.51
7236.0	19.91	Ave.	60	1.5	V	17.06	36.97	54	17.03
9648.0	34.85	PK	161	1.8	H	19.28	54.13	74	19.87
9648.0	20.39	Ave.	161	1.8	H	19.28	39.67	54	14.33
Middle Channel (2437 MHz)									
164.7	56.38	QP	348	1.8	V	-15.30	41.08	43.50	2.42
2437.0	86.65	PK	296	1.2	H	6.13	92.78	/	/
2437.0	80.13	Ave.	296	1.2	H	6.13	86.26	/	/
2437.0	95.66	PK	102	2.5	V	6.13	101.79	/	/
2437.0	91.17	Ave.	102	2.5	V	6.13	97.30	/	/
2349.4	41.08	PK	137	2.2	H	5.48	46.56	74	27.44
2349.4	26.39	Ave.	137	2.2	H	5.48	31.87	54	22.13
2386.9	38.27	PK	313	2.3	H	5.48	43.75	74	30.25
2386.9	23.62	Ave.	313	2.3	H	5.48	29.10	54	24.90
2492.7	42.50	PK	27	2.1	V	7.21	49.71	74	24.29
2492.7	41.48	Ave.	27	2.1	V	7.21	48.69	54	5.31
4874.0	46.49	PK	43	1.8	H	12.4	58.89	74	15.11
4874.0	40.48	Ave.	43	1.8	H	12.4	52.88	54	1.12
7311.0	36.75	PK	52	2.4	V	16.62	53.37	74	20.63
7311.0	21.58	Ave.	52	2.4	V	16.62	38.20	54	15.80
9748.0	35.15	PK	322	1.0	H	19.4	54.55	74	19.45
9748.0	21.22	Ave.	322	1.0	H	19.4	40.62	54	13.38

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2472 MHz)									
164.7	56.88	QP	41	2.3	V	-15.30	41.58	43.50	1.92
2472.0	87.12	PK	100	1.9	H	7.21	94.33	/	/
2472.0	80.18	Ave.	100	1.9	H	7.21	87.39	/	/
2472.0	95.14	PK	232	1.7	V	7.21	102.35	/	/
2472.0	91.50	Ave.	232	1.7	V	7.21	98.71	/	/
2354.6	40.89	PK	287	1.5	H	5.48	46.37	74	27.63
2354.6	25.75	Ave.	287	1.5	H	5.48	31.23	54	22.77
2381.6	38.11	PK	36	1.7	H	5.48	43.59	74	30.41
2381.6	26.23	Ave.	36	1.7	H	5.48	31.71	54	22.29
2483.5	47.78	PK	72	1.1	H	7.21	54.99	74	19.01
2483.5	43.26	Ave.	72	1.1	H	7.21	50.47	54	3.53
2496.8	45.80	PK	176	2.1	V	7.21	53.01	74	20.99
2496.8	41.73	Ave.	176	2.1	V	7.21	48.94	54	5.06
4944.0	47.86	PK	61	1.4	V	12.46	60.32	74	13.68
4944.0	40.38	Ave.	61	1.4	V	12.46	52.84	54	1.16
7416.0	37.72	PK	236	1.2	V	15.91	53.63	74	20.37
7416.0	20.92	Ave.	236	1.2	V	15.91	36.83	54	17.17
9888.0	35.09	PK	122	1.6	H	19.39	54.48	74	19.52
9888.0	19.98	Ave.	122	1.6	H	19.39	39.37	54	14.63

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
164.7	56.15	QP	229	2.5	V	-15.30	40.85	43.50	2.65
2412.0	87.77	PK	252	1.8	H	6.13	93.9	/	/
2412.0	80.03	Ave.	252	1.8	H	6.13	86.16	/	/
2412.0	95.62	PK	36	1.0	V	6.13	101.75	/	/
2412.0	90.20	Ave.	36	1.0	V	6.13	96.33	/	/
2369.6	40.70	PK	208	1.9	H	5.48	46.18	74	27.82
2369.6	27.83	Ave.	208	1.9	H	5.48	33.31	54	20.69
2383.9	40.23	PK	238	2.2	H	5.48	45.71	74	28.29
2383.9	25.61	Ave.	238	2.2	H	5.48	31.09	54	22.91
2493.5	42.86	PK	181	1.6	V	7.21	50.07	74	23.93
2493.5	42.49	Ave.	181	1.6	V	7.21	49.70	54	4.30
4824.0	48.41	PK	195	2.4	V	12.44	60.85	74	13.15
4824.0	40.50	Ave.	195	2.4	V	12.44	52.94	54	1.06
7236.0	35.98	PK	214	1.5	H	17.06	53.04	74	20.96
7236.0	21.63	Ave.	214	1.5	H	17.06	38.69	54	15.31
9648.0	35.40	PK	54	2.4	V	19.28	54.68	74	19.32
9648.0	21.56	Ave.	54	2.4	V	19.28	40.84	54	13.16
Middle Channel (2437 MHz)									
164.7	56.55	QP	312	1.3	V	-15.30	41.25	43.50	2.25
2437.0	86.61	PK	27	1.6	H	6.13	92.74	/	/
2437.0	81.79	Ave.	27	1.6	H	6.13	87.92	/	/
2437.0	95.40	PK	55	1.1	V	6.13	101.53	/	/
2437.0	90.44	Ave.	55	1.1	V	6.13	96.57	/	/
2351.3	39.82	PK	173	1.9	H	5.48	45.30	74	28.70
2351.3	26.18	Ave.	173	1.9	H	5.48	31.66	54	22.34
2376.2	37.83	PK	33	1.4	H	5.48	43.31	74	30.69
2376.2	23.93	Ave.	33	1.4	H	5.48	29.41	54	24.59
2493.8	46.95	PK	322	1.5	V	7.21	54.16	74	19.84
2493.8	38.81	Ave.	322	1.5	V	7.21	46.02	54	7.98
4874.0	47.92	PK	125	1.4	V	12.4	60.32	74	13.68
4874.0	40.51	Ave.	125	1.4	V	12.4	52.91	54	1.09
7311.0	37.55	PK	128	1.1	V	16.62	54.17	74	19.83
7311.0	21.66	Ave.	128	1.1	V	16.62	38.28	54	15.72
9748.0	36.66	PK	230	2.2	V	19.4	56.06	74	17.94
9748.0	20.63	Ave.	230	2.2	V	19.4	40.03	54	13.97

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2472 MHz)									
164.7	56.97	QP	354	1.5	V	-15.30	41.67	43.50	1.83
2472.0	86.58	PK	92	1.3	H	7.21	93.79	/	/
2472.0	79.92	Ave.	92	1.3	H	7.21	87.13	/	/
2472.0	96.74	PK	153	2.0	V	7.21	103.95	/	/
2472.0	91.19	Ave.	153	2.0	V	7.21	98.40	/	/
2350.2	40.28	PK	5	2.1	H	5.48	45.76	74	28.24
2350.2	26.28	Ave.	5	2.1	H	5.48	31.76	54	22.24
2380.4	41.16	PK	178	1.6	H	5.48	46.64	74	27.36
2380.4	24.39	Ave.	178	1.6	H	5.48	29.87	54	24.13
2483.5	46.34	PK	331	2.2	H	7.21	53.55	74	20.45
2483.5	42.87	Ave.	331	2.2	H	7.21	50.08	54	3.92
2498.3	43.23	PK	347	1.2	V	7.21	50.44	74	23.56
2498.3	41.47	Ave.	347	1.2	V	7.21	48.68	54	5.32
4944.0	46.43	PK	141	1.9	V	12.46	58.89	74	15.11
4944.0	40.35	Ave.	141	1.9	V	12.46	52.81	54	1.19
7416.0	36.74	PK	54	1.3	V	15.91	52.65	74	21.35
7416.0	21.37	Ave.	54	1.3	V	15.91	37.28	54	16.72
9888.0	36.27	PK	341	2.0	H	19.39	55.66	74	18.34
9888.0	21.30	Ave.	341	2.0	H	19.39	40.69	54	13.31

802.11n-HT40 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2422 MHz)									
164.7	56.16	QP	322	1.3	V	-15.30	40.86	43.50	2.64
2422.0	86.81	PK	4	1.7	H	6.13	92.94	/	/
2422.0	80.27	Ave.	4	1.7	H	6.13	86.40	/	/
2422.0	95.51	PK	24	2.3	V	6.13	101.64	/	/
2422.0	90.00	Ave.	24	2.3	V	6.13	96.13	/	/
2343.5	41.73	PK	264	2.2	H	5.48	47.21	74	26.79
2343.5	27.11	Ave.	264	2.2	H	5.48	32.59	54	21.41
2374.7	41.83	PK	43	2.1	H	5.48	47.31	74	26.69
2374.7	24.75	Ave.	43	2.1	H	5.48	30.23	54	23.77
2487.7	42.53	PK	184	1.6	V	7.21	49.74	74	24.26
2487.7	41.36	Ave.	184	1.6	V	7.21	48.57	54	5.43
4844.0	46.63	PK	284	2.4	H	12.4	59.03	74	14.97
4844.0	40.29	Ave.	284	2.4	H	12.4	52.69	54	1.31
7266.0	37.72	PK	150	1.1	V	16.62	54.34	74	19.66
7266.0	20.91	Ave.	150	1.1	V	16.62	37.53	54	16.47
9688.0	36.70	PK	211	1.7	H	19.29	55.99	74	18.01
9688.0	20.33	Ave.	211	1.7	H	19.29	39.62	54	14.38
Middle Channel (2437 MHz)									
164.7	56.78	QP	247	2.3	V	-15.30	41.48	43.50	2.02
2437.0	87.01	PK	14	1.7	H	6.13	93.14	/	/
2437.0	81.45	Ave.	14	1.7	H	6.13	87.58	/	/
2437.0	96.50	PK	17	1.4	V	6.13	102.63	/	/
2437.0	89.82	Ave.	17	1.4	V	6.13	95.95	/	/
2350.0	44.47	PK	121	2.5	H	5.48	49.95	74	24.05
2350.0	28.69	Ave.	121	2.5	H	5.48	34.17	54	19.83
2383.9	40.49	PK	122	2.0	H	5.48	45.97	74	28.03
2383.9	25.25	Ave.	122	2.0	H	5.48	30.73	54	23.27
2496.0	46.82	PK	22	2.1	V	7.21	54.03	74	19.97
2496.0	39.73	Ave.	22	2.1	V	7.21	46.94	54	7.06
4874.0	48.59	PK	99	1.3	H	12.4	60.99	74	13.01
4874.0	40.44	Ave.	99	1.3	H	12.4	52.84	54	1.16
7311.0	36.93	PK	30	1.8	H	16.62	53.55	74	20.45
7311.0	20.64	Ave.	30	1.8	H	16.62	37.26	54	16.74
9748.0	36.31	PK	118	1.9	H	19.4	55.71	74	18.29
9748.0	20.52	Ave.	118	1.9	H	19.4	39.92	54	14.08

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
164.7	56.21	QP	326	1.3	V	-15.30	40.91	43.50	2.59
2462.0	87.72	PK	150	1.4	H	6.13	93.85	/	/
2462.0	80.27	Ave.	150	1.4	H	6.13	86.4	/	/
2462.0	95.33	PK	71	1.1	V	6.13	101.46	/	/
2462.0	90.50	Ave.	71	1.1	V	6.13	96.63	/	/
2347.1	40.28	PK	268	2.1	H	5.48	45.76	74	28.24
2347.1	24.85	Ave.	268	2.1	H	5.48	30.33	54	23.67
2385.2	38.20	PK	52	2.1	H	5.48	43.68	74	30.32
2385.2	24.10	Ave.	52	2.1	H	5.48	29.58	54	24.42
2483.5	43.48	PK	119	2.0	H	7.21	50.69	74	23.31
2483.5	41.45	Ave.	119	2.0	H	7.21	48.66	54	5.34
2489.9	43.82	PK	56	1.8	V	7.21	51.03	74	22.97
2489.9	39.68	Ave.	56	1.8	V	7.21	46.89	54	7.11
4924.0	48.25	PK	233	2.0	V	12.46	60.71	74	13.29
4924.0	40.40	Ave.	233	2.0	V	12.46	52.86	54	1.14
7386.0	36.92	PK	147	2.0	H	15.91	52.83	74	21.17
7386.0	20.04	Ave.	147	2.0	H	15.91	35.95	54	18.05
9848.0	34.78	PK	114	2.0	H	19.29	54.07	74	19.93
9848.0	21.22	Ave.	114	2.0	H	19.29	40.51	54	13.49

Note:

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor


Margin = Limit- Corr. Amplitude

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-05-31	2015-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by David Lee on 2014-12-02.


Test Result: Pass.

Please refer to the following tables and plots.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	10.16	≥ 500
Middle	2437	10.16	≥ 500
High	2472	10.16	≥ 500
802.11g mode			
Low	2412	16.41	≥ 500
Middle	2437	16.41	≥ 500
High	2472	16.41	≥ 500
802.11n-HT20 mode			
Low	2412	17.13	≥ 500
Middle	2437	17.13	≥ 500
High	2472	17.13	≥ 500
802.11n-HT40 mode			
Low	2422	35.31	≥ 500
Middle	2437	35.31	≥ 500
High	2462	35.31	≥ 500


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n-HT20 Low Channel




802.11n-HT20 Middle Channel



802.11n-HT20 High Channel



802.11n-HT40 Low Channel



Delta 1 [T1] -2.56 dB

Ref Lvl 23.5 dBm

35.31062124 MHz

RBW 100 kHz

VBW 300 kHz

SWT 12.5 ms

RF Att 30 dB

Unit dBm

3.5 dB Offset

Delta 2 [T1] -5.36 dBm

2.44441483 GHz

35.31062124 MHz

Center 2.462 GHz

5 MHz/

Span 50 MHz

Date: 2.DEC.2014 23:36:53


FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Power Meter	N1912A	MY50000448	2014-11-03	2015-11-03
HP	Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	55 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by David Lee from 2014-12-03.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	12.73	10.36	30
Middle	2437	13.95	11.37	30
High	2472	13.76	10.89	30
802.11g				
Low	2412	18.12	10.75	30
Middle	2437	18.79	11.60	30
High	2472	18.44	11.49	30
802.11n-HT20				
Low	2412	17.78	10.83	30
Middle	2437	18.82	11.34	30
High	2472	18.69	11.24	30
802.11n-HT40				
Low	2422	17.98	10.68	30
Middle	2437	18.54	11.45	30
High	2462	18.31	11.60	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-05-31	2015-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	19 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by David Lee on 2014-12-03.


Test Result: *Compliance*

Please refer to the following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side




802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side



802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY**Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB558074 D01 DTS Meas Guidance v03r02 sub-clause 10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-05-31	2015-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	19 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by David Lee on 2014-12-03.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-13.44	≤ 8
Middle	2437	-14.53	≤ 8
High	2472	-14.41	≤ 8
802.11g mode			
Low	2412	-17.98	≤ 8
Middle	2437	-15.80	≤ 8
High	2472	-16.54	≤ 8
802.11n-HT20 mode			
Low	2412	-16.89	≤ 8
Middle	2437	-16.06	≤ 8
High	2472	-16.58	≤ 8
802.11n-HT40 mode			
Low	2422	-20.41	≤ 8
Middle	2437	-16.40	≤ 8
High	2462	-16.22	≤ 8


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n-HT20 Low Channel




Power Spectral Density, 802.11n-HT20 Middle Channel




Power Spectral Density, 802.11n-HT20 High Channel




Power Spectral Density, 802.11n-HT40 Low Channel



Power Spectral Density, 802.11n-HT40 Middle Channel



Power Spectral Density, 802.11n-HT40 High Channel



PRODUCT SIMILARITY DECLARATION LETTER

FOSCAM

Shenzhen Foscam Intelligent Technology Co., Ltd.
5/F, Block 1, Vision Business Park, Nanshan District, Shenzhen, PRC
Tel: 86-0755-26720367-8306

2014-12-2

Product Similarity Declaration

To Whom It May Concern,

We, Foscam Intelligent Technology Co., Ltd., hereby declare that we have a product named as Wireless IP Camera (Model number: FosBaby P1) was tested by BACL, meanwhile, for our marketing purpose, we would like to list a series models FosBaby P1S, FosBaby P2, FosBaby P2S, FosBaby P3, FosBaby P3S, FosBaby P4, FosBaby P4S, FosBaby P5, FosBaby P5S, FosBaby P6, FosBaby P6S. on reports and certificate, all the models are identical schematics, except for the differences as below:

The model number is different.

No other changes are made to them.

We confirm that all information above is true, and we'll be responsible for all the consequences. Please contact me if you have any question.

Signature:

Tank Fang

Engineer Manager

Tank Fang 12/2, 2014

***** END OF REPORT *****