FCC ID: ZDYGF1X

WLAN (Portable device)

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to KDB 447498 (2)(a)(i)

Frequency Range		Center	
Low Frequency (MHz)	High Frequency(MHz)	frequency (MHz)	60/f SAR Limitation (mw)
2412	2462	2437	25

Maximum measured transmitter power: 802.11b

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
10.89	1.0	15.45

Maximum measured transmitter power: 802.11g

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
9.32	1.0	10.76

Maximum measured transmitter power: 802.11n HT20

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
9.49	1.0	11.19

Maximum measured transmitter power: 802.11n HT40

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
8.95	1.0	9.89

Threshold at which no SAR required is 25 mw.

Maximum Tx power is 15.45mw EIRP.

Conclusion: No SAR is required.

hong shenly

Sincerely,

Zheng Zhong

E-mail: : zhongzheng@leader-intl.com

Phone: : +86-755-6166 2702 Fax: : +86-755-6161 3490

Address : 4 Floor, Dongjiang Environmental Building, Central

Langshan Road, Hi-Tech Park, Nanshan District, ShenZhen,

China