



# FCC RADIO TEST REPORT

## FCC ID: ZFN-A072G

**Product :** Mobile Internet Device

**Trade Name :** HKC, Pioneer, ODYS, MEDIACOM, EXPER, ZEKI, Xelio, Proscan, KLU, exper, Teach pad, artes, Advance, plaisio, XENO, Smart Touch, GHIA

**Model Name :** A072G

Serial Model: Refer to page7

**Report No. :** NTEK-2013NT0929322F

### Prepared for

HuiKe Electronics(shenzhen)Co.,Ltd.  
Building 1,2,3,Huike Industrial Park,Minying Industrial  
Zone,ShuiTian,ShiYan,Bao'an,Shenzhen, China

### Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street  
Bao'an District, Shenzhen P.R. China  
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599  
Website:www.ntek.org.cn

**TEST RESULT CERTIFICATION****Applicant's name** ..... : HuiKe Electronics(shenzhen)Co.,Ltd.Address ..... : Building 1,2,3,Huik Industrial Park,Minying Industrial  
Zone,ShuiTian,ShiYan,Bao'an,Shenzhen, China**Manufacture's Name** ..... : HuiKe Electronics(shenzhen)Co.,Ltd.Address ..... : Building 1,2,3,Huik Industrial Park,Minying Industrial  
Zone,ShuiTian,ShiYan,Bao'an,Shenzhen,China**Product description**

Product name ..... : Mobile Internet Device

Model and/or type reference : A072G

Serial Model ..... : Refer to page7

**Standards** ..... : FCC Part15.247

Test procedure ..... ANSI C63.4-2003

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.


**Date of Test** ..... :

Date (s) of performance of tests ..... : 29 Sep. 2013 ~16 Oct. 2013

Date of Issue ..... : 16 Oct. 2013


Test Result ..... : **Pass**

Testing Engineer :




(Polo Cha)

Technical Manager :



(Brown Lu)

Authorized Signatory :



(Bovey Yang)

## Table of Contents

	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
<b>2 . GENERAL INFORMATION</b>	<b>7</b>
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
<b>3 . EMC EMISSION TEST</b>	<b>13</b>
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	23
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	24
<b>4 . POWER SPECTRAL DENSITY TEST</b>	<b>38</b>
4.1 APPLIED PROCEDURES / LIMIT	38
4.1.1 TEST PROCEDURE	38
4.1.2 DEVIATION FROM STANDARD	38
4.1.3 TEST SETUP	38
4.1.4 EUT OPERATION CONDITIONS	38
4.1.5 TEST RESULTS	39
<b>5 . BANDWIDTH TEST</b>	<b>47</b>
5.1 APPLIED PROCEDURES / LIMIT	47
5.1.1 TEST PROCEDURE	47

<b>Table of Contents</b>	<b>Page</b>
5.1.2 EUT OPERATION CONDITIONS	47
5.1.3 TEST RESULTS	48
<b>6 . PEAK OUTPUT POWER TEST</b>	<b>56</b>
6.1 APPLIED PROCEDURES / LIMIT	56
6.1.1 TEST PROCEDURE	56
6.1.2 DEVIATION FROM STANDARD	56
6.1.3 TEST SETUP	56
6.1.4 EUT OPERATION CONDITIONS	56
6.1.5 TEST RESULTS	57
<b>7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>58</b>
7.1 DEVIATION FROM STANDARD	58
7.2 TEST SETUP	58
7.3 EUT OPERATION CONDITIONS	58
7.4 TEST RESULTS	59
<b>8 . ANTENNA REQUIREMENT</b>	<b>64</b>
8.1 STANDARD REQUIREMENT	64
8.2 EUT ANTENNA	64
<b>9 . EUT TEST PHOTO</b>	<b>65</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

## 1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Mobile Internet Device	
Trade Name	HKC, Pioneer, ODYS, MEDIACOM, EXPER, ZEKI, Xelio, Proscan, KLU, exper, Teach pad, artes, Advance, plaisio, XENO, Smart Touch, GHIA	
Model Name	A072G	
Serial Model	A072D, R071A, P07CR, R1, A79, A072D-BK, TBT-7R1-K, M-MP710GO, H7S, H7G, H7D, TBDG773B, Pedi plus, Opos, A072A, A072B, A072C, A072E, A072F, A072T, R072B, R072C, MV072B, MV072C, MV072D, M072A, AXXXXX (where X would be any arabian numeral or letters or blank or symbols)	
Model Difference	All the model are the same circuit and RF module, except the model name.	
Product Description	The EUT is a Mobile Internet Device	
	Operation Frequency:	802.11b/g/n(20MHz):2412~2462 MHz 802.11n(40MHz):2422~2452 MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20/40MHz):150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20MHz:11CH 802.11n40MHz:7CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	802.11b: 17.86 dBm (Max.) 802.11g: 14.78dBm (Max.) 802.11n(20M) : 13.85 dBm (Max.) 802.11n (40M): 13.74 dBm (Max.)
	Antenna Gain (dBi)	0.15 dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	

Channel List	Please refer to the Note 2.
Ratings	DC5V, 2A
Adapter	Model: JY-05200 AC Power Input: 100-240V~, 50/60Hz, 0.3A Output: 5.0V---, 2A
Battery	DC 3.7V
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	FPCB Antenna	N/A	0.15	Wifi Antenna



## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n CH1/ CH6/ CH11
Mode 4	802.11n CH3/ CH6/ CH9
Mode 5	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n CH1/ CH6/ CH11
Mode 4	802.11n CH3/ CH6/ CH9

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

### Conducted Emission Test



### Radiated Spurious Emission Test



## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Mobile Internet Device	HKC, Pioneer, ODYS, MEDIACOM, EXPER, ZEKI, Xelio, Proscan, KLU, exper, Teach pad, artes, Advance, plaisio, XENO, Smart Touch, GHIA	A072G	N/A	EUT
E-2	Adapter	N/A	JY-05200	N/A	
E-3	Earphone	N/A	2688	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	80cm	
C-2	NO	NO	80cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2013.07.06	2014.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2013.06.07	2014.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2013.07.06	2014.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2013.06.07	2014.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2013.06.07	2014.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2013.07.06	2014.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2013.07.06	2014.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2012.12.22	2013.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2013.06.08	2014.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2013.07.06	2014.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2013.07.06	2014.07.05	1 year

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2013.06.06	2014.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2013.06.07	2014.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2013.06.07	2014.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2013.06.08	2014.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2013.06.08	2014.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



**Note: 1.**Support units were connected to second LISN .

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


### 3.1.6 TEST RESULTS

EUT :	Mobile Internet Device	Model Name. :	A072G
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC120V/60Hz	Test Mode :	Mode 1

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2020	29.60	10.68	40.28	63.52	-23.24	QP
0.2020	17.19	10.68	27.87	53.52	-25.65	AVG
1.1019	26.37	10.52	36.89	56.00	-19.11	QP
1.1220	13.49	10.52	24.01	46.00	-21.99	AVG
1.5580	27.70	10.52	38.22	56.00	-17.78	QP
1.5940	14.16	10.52	24.68	46.00	-21.32	AVG
3.8420	9.91	10.60	20.51	46.00	-25.49	AVG
4.0060	22.00	10.60	32.60	56.00	-23.40	QP
4.9099	21.18	10.64	31.82	56.00	-24.18	QP
4.9739	7.61	10.64	18.25	46.00	-27.75	AVG
10.6779	18.58	10.85	29.43	60.00	-30.57	QP
11.6379	7.18	10.87	18.05	50.00	-31.95	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Mobile Internet Device	Model Name. :	A072G
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC120V/60Hz	Test Mode :	Mode 1


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Detector Type
0.1940	34.07	10.76	44.83	63.86	-19.03	QP
0.1940	18.60	10.76	29.36	53.86	-24.50	AVG
0.2460	29.18	10.80	39.98	61.89	-21.91	QP
0.2460	14.18	10.80	24.98	51.89	-26.91	AVG
0.6660	25.30	10.54	35.84	56.00	-20.16	QP
0.6660	7.61	10.54	18.15	46.00	-27.85	AVG
1.5380	29.85	10.52	40.37	56.00	-15.63	QP
1.5380	16.30	10.52	26.82	46.00	-19.18	AVG
5.8059	23.26	10.68	33.94	60.00	-26.06	QP
5.8059	8.06	10.68	18.74	50.00	-31.26	AVG
12.6779	23.49	10.88	34.37	60.00	-25.63	QP
12.6779	9.03	10.88	19.91	50.00	-30.09	AVG

**Remark:**

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.







### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

**3.2.2 TEST PROCEDURE**

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**Note:**


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

**3.2.3 DEVIATION FROM TEST STANDARD**


No deviation

### 3.2.4 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	Mobile Internet Device	Model Name. :	A072G
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

### 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	57.5938	23.11	5.67	28.78	40.00	-11.22	QP
V	183.8439	30.10	9.77	39.87	43.50	-3.63	QP
V	360.4476	14.89	16.46	31.35	46.00	-14.65	QP
V	468.8761	18.06	19.69	37.75	46.00	-8.25	QP
V	836.2441	13.81	27.35	41.16	46.00	-4.84	QP
V	938.8325	12.40	29.56	41.96	46.00	-4.04	QP
H	82.0705	17.99	8.11	26.10	40.00	-13.90	QP
H	148.9625	22.13	11.79	33.92	43.50	-9.58	QP
H	182.5592	28.48	9.87	38.35	43.50	-5.15	QP
H	360.4476	24.16	16.46	40.62	46.00	-5.38	QP
H	468.8761	23.80	19.69	43.49	46.00	-2.51	QP
H	938.8325	11.77	29.56	41.33	46.00	-4.67	QP

#### Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

### 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

#### Radiated Spurious Emission

EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX		

1GHz~25GHz:

#### 802.11b

##### Normal Voltage

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412							
V	4824.0000	57.21	10.44	67.65	74.00	-6.35	peak
V	4824.0000	36.40	10.44	47.84	54.00	-7.16	AVG
V	7236.0000	52.71	12.39	65.10	74.00	-8.90	peak
V	7236.0000	30.88	12.39	33.27	54.00	-10.73	AVG
H	4824.0000	56.38	10.44	66.82	74.00	-7.18	peak
H	4824.0000	32.95	10.44	43.39	54.00	-10.61	AVG
operation frequency:2437							
V	4874.5000	54.27	10.40	64.67	74.00	-9.33	peak
V	4874.5000	32.83	10.40	43.23	54.00	-10.77	AVG
V	7311.5000	40.37	12.75	53.12	74.00	-20.88	peak
H	4874.0000	57.05	10.40	67.45	74.00	-6.55	peak
H	4874.2500	30.98	10.40	41.38	54.00	-12.62	AVG
H	7311.5000	37.69	12.75	50.44	74.00	-23.56	peak
operation frequency:2462							
V	4924.2500	55.17	10.39	65.56	74.00	-8.44	peak
V	4924.2500	32.96	10.39	43.35	54.00	-10.65	AVG
V	7386.6750	38.79	12.68	51.47	74.00	-22.53	peak
H	4924.1500	53.15	10.39	63.54	74.00	-11.46	peak
H	4924.1500	35.22	10.39	45.61	54.00	-8.39	AVG
H	7386.2750	37.16	12.68	49.84	74.00	-24.16	peak

#### Remark:

Absolute Level= Reading Level+ Factor, Margin= Absolute Level - Limit

Note: Scan with 802.11b, 802.11g,802.11n),the worst case is 802.11b.





**Radiated band edge:**



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b							
2390	58.75	-13.06	45.69	74	-28.31	peak	Vertical
2390	58.69	-13.06	45.63	74	-28.37	peak	Horizontal
2483.5	59.37	-12.78	46.59	74	-27.41	peak	Vertical
2483.5	58.66	-12.78	45.88	74	-28.12	peak	Horizontal
802.11g							
2390	58.93	-13.06	45.87	74	-28.13	peak	Vertical
2390	55.64	-13.06	42.58	74	-31.42	peak	Horizontal
2483.5	60.72	-12.78	47.94	74	-26.06	peak	Vertical
2483.5	60.82	-12.78	48.04	74	-25.96	peak	Horizontal
802.11n20							
2390	60.78	-13.06	47.72	74	-26.28	peak	Vertical
2390	60.46	-13.06	47.4	74	-26.6	peak	Horizontal
2483.5	58.55	-12.78	45.77	74	-28.23	peak	Vertical
2483.5	59.42	-12.78	46.64	74	-27.36	peak	Horizontal
802.11n40							
2390	60.43	-13.06	47.37	74	-26.63	peak	Vertical
2390	60.86	-13.06	47.8	74	-26.2	peak	Horizontal
2483.5	58.52	-12.78	45.74	74	-28.26	peak	Vertical
2483.5	58.63	-12.78	45.85	74	-28.15	peak	Horizontal

NOTE: The result(PK) less than AV limite,No need shown AV result.



### Conducted Spurious Emissions at Antenna Port: 802.11b Low Channel





## 802.11b Middle Channel





### 802.11b High Channel





## 802.11g Low Channel





## 802.11g Middle Channel



## 802.11g High Channel





## 802.11n-HT20 Low Channel









## 802.11n-HT20 Middle Channel





## 802.11n-HT20 High Channel





## 802.11n-HT40 Low Channel



## 802.11n-HT40 Middle Channel



## 802.11n-HT40 High Channel



## 4. POWER SPECTRAL DENSITY TEST

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


#### 4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW  $\geq 3$  kHz.
4. Set the VBW  $\geq 3 \times$  RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP




#### 4.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.1.5 TEST RESULTS

EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-16.02	8	PASS
2437 MHz	-15.91	8	PASS
2462 MHz	-16.32	8	PASS










EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-16.36	8	PASS
2437 MHz	-16.35	8	PASS
2462 MHz	-16.54	8	PASS







EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-16.22	8	PASS
2437 MHz	-16.31	8	PASS
2462 MHz	-16.38	8	PASS






EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-16.39	8	PASS
2437 MHz	-16.47	8	PASS
2452 MHz	-16.41	8	PASS



### TX CH06



### TX CH09



## 5. BANDWIDTH TEST


### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.




#### 5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 5.1.3 TEST RESULTS


EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.104	500	Pass
Middle	2437	10.082	500	Pass
High	2462	10.088	500	Pass






### TX CH 06




### TX CH 11




EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.576	500	Pass
Middle	2437	16.577	500	Pass
High	2462	16.594	500	Pass


### TX CH 01



### TX CH 06




### TX CH 11





EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.830	500	Pass
Middle	2437	17.780	500	Pass
High	2462	17.830	500	Pass

### TX CH 01








EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	36.402	500	Pass
Middle	2437	36.417	500	Pass
High	2452	36.409	500	Pass

### TX CH 03





## 6. PEAK OUTPUT POWER TEST

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



### 6.1.5 TEST RESULTS

EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	TX b/g/n(20M, 40M) Mode /CH01, CH06, CH11		

#### TX 802.11b Mode

Test Channe	Frequency	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(MHz)	(dBm)	(dBm)	(dBm)
CH01	2412	17.58	14.67	30
CH06	2437	17.64	14.83	30
CH11	2462	17.86	14.59	30

#### TX 802.11g Mode

CH01	2412	14.69	11.62	30
CH06	2437	14.78	11.51	30
CH11	2462	14.65	11.55	30

#### TX 802.11n-HT20 Mode

CH01	2412	13.59	10.46	30
CH06	2437	13.85	10.83	30
CH11	2462	13.43	10.66	30

#### TX 802.11n-HT40 Mode

CH03	2422	13.74	10.35	30
CH06	2437	13.36	10.28	30
CH09	2452	13.42	10.47	30

## 7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

### APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


### TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 7.1 DEVIATION FROM STANDARD

No deviation.

### 7.2 TEST SETUP



### 7.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 7.4 TEST RESULTS


EUT :	Mobile Internet Device	Model Name :	A072G
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
802.11b			
Left-band	38.02	20	Pass
Right-band	57.22	20	Pass
802.11g			
Left-band	30.96	20	Pass
Right-band	47.70	20	Pass
802.11n20			
Left-band	31.38	20	Pass
Right-band	48.12	20	Pass
802.11n40			
Left-band	31.19	20	Pass
Right-band	42.55	20	Pass


## 802.11b: Band Edge, Left Side




## 802.11b: Band Edge, Right Side




## 802.11g: Band Edge, Left Side




## 802.11g: Band Edge, Right Side




## 802.11n-HT20: Band Edge, Left Side




## 802.11n-HT20: Band Edge, Right Side



## 802.11n-HT40: Band Edge, Left Side



## 802.11n-HT40: Band Edge, Right Side



## **8. ANTENNA REQUIREMENT**

### **8.1 STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



### **8.2 EUT ANTENNA**

The EUT antenna is FPCB antenna. It comply with the standard requirement.



## 9. EUT TEST PHOTO

### Radiated Measurement Photos



### Conducted Measurement Photos

