

CENTRE OF TESTING SERVICE INTERNATIONAL

OPERATE ACCORDING TO ISO/IEC 17025

FCC ID TEST REPORT

TEST REPORT NUMBER: CGZ3150210-00185-EF



CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

CENTRE OF TESTING SERVICE





	TEST REPORT For FCC ID
	47 CFR PART 15 OCT, 2014
Report Reference No	CGZ3150210-00185-EF
Date of issue	13 February 2015
Testing Laboratory Name	CENTRE OF TESTING SERVICE CO., LTD.
Address	A101,No.65,Zhuji Highway,Tianhe District,Guangzhou, China
Testing location/ procedure	Full application of Harmonised standards ■
	Partial application of Harmonised standards \square
	Other standard testing method \square
Applicant's name	G-BLUE Technology Limited
Address	8/F, Cnt Comm Blog 302 Queen's RD Central, Hong Kong
Test specification	
Standard	47 CFR PART 15 OCT, 2014
Test Report Form No	CTSEMC-1.0
TRF Originator	CENTRE OF TESTING SERVICE CO., LTD.
Master TRF	Dated 2009-01
CENTRE OF TESTING SERVICE	CO., LTD. All rights reserved.
CENTRE OF TESTING SERVICE material. CENTRE OF TESTING for damages resulting from the re context.	ed in whole or in part for non-commercial purposes as long as the ECO., LTD is acknowledged as copyright owner and source of the SERVICE CO., LTD takes no responsibility for and will not assume liability ader's interpretation of the reproduced material due to its placement and
Test item description	: Sport Bluetooth Headset
Trade Mark	Gblue
Manufacturer	Shenzhen Gblue Technology Co., Ltd.
Model/Type reference	S90
Ratings	Battery 3.7V, DC 5V for Charging
Operating Frequency	2402.0MHz ~2480.0MHz
Result	Positive

Compiled by:

Supervised by:

Approved by:

Kate zhang / Fileadministrators

Duke yang / Technique principal

Vincent yao / Manager

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





FCCID-TEST REPORT

Type / Model	S90
EUT	Sport Bluetooth Headset
Applicant	G-BLUE Technology Limited
Address	8/F, Cnt Comm Blog 302 Queen's RD Central, Hong Kong
Telephone	1
Fax	
Contact	
Manufacturer	Shenzhen Gblue Technology Co., Ltd.
Address	2nd Floor, Fukang Commercial Plaza, Yousong Road, Longhua Avenue, Longhua New District, Shenzhen, China
Telephone	1
Fax	
Contact	
Factory	Shenzhen Gblue Technology Co., Ltd.
Address	2nd Floor, Fukang Commercial Plaza, Yousong Road, Longhua Avenue, Longhua New District, Shenzhen, China
Telephone	1
Fax	1
Contact	

Test Result according to the standards on page 1: PASSED

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn



TABLE OF CONTENTS

<u>Description</u>	Page
1.TEST STANDARDS	5
2.SUMMARY	5
2.1 GENERAL REMARKS	5
2.2 FINAL ASSESSMENT	5
3.EQUIPMENT UNDER TEST	5
3.1 Power supply system utilised	5
3.2 SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)	5
3.3 EUT OPERATION MODE	5
3.4 EUT CONFIGURATION	6
4.TEST ENVIRONMENT	7
4.1 Address of the test laboratory	
4.2 Test facility	
4.3 Environmental conditions	
4.4 DEFINITIONS OF SYMBOLS USED IN THIS TEST REPORT	
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY	
4.6 MEASUREMENT UNCERTAINTY	8
5.SUMMARY OF STANDARDS AND RESULTS	8
5.1.DESCRIPTION OF STANDARDS AND RESULTS	8
6.POWER LINE CONDUCTED EMISSION TEST	9
6.1.Test Equipment	9
6.2. BLOCK DIAGRAM OF TEST SETUP	
6.3. Power Line Conducted Emission Test Limits	
6.4.Test Procedure	
6.5. Power Line Conducted Emission Test Results	9
7.RADIATED DISTURBANCE (ELECTRIC FIELD)	12
7.1.Test Equipment	
7.2.BLOCK DIAGRAM OF TEST SETUP	
7.3.RADIATED EMISSION LIMIT:	
7.4.Test Procedure	
7.5.RADIATED EMISSION TEST RESULTS	14
8.BAND EDGE COMPLIANCE TEST	24
8.1. TEST EQUIPMENT	
8.2. TEST PROCEDURE	
8.3. TEST RESULTS Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Con	
copyright of this report is owned by Centre of resting Service and may not be reproduced other than in full except with the written approval of the issuing Con	ipariy.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

CENTRE OF TESTING SERVICE





9.DEVIATION TO TEST SPECIFICATIONS29

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

CENTRE OF TESTING SERVICE





1.TEST STANDARDS

The tests were performed according to following standards:

- 47 CFR PART 15 OCT, 2014
- ANSI C63.4-2009

2.SUMMARY

2.1 GENERAL REMARKS

Date of receipt of test sample	06 February 2015
Testing commenced on	11~13 February 2015
Testing concluded on	09 February 2015

2.2 FINAL ASSESSMENT

The FCC requirements pertaining to the technical standards and tested operation modes are

fulfilled.

□ - **not** fulfilled.

The equipment under test

fulfils the FCC requirements cited on page 1.

□ - **does not** fulfil the FCC requirements cited on page 1.

3.EQUIPMENT UNDER TEST

3.1 Power supply system utilised

Power supply voltage : ■ 3.7V by Battery

■ AC 120/60Hz for Charging by NoteBooK

3.2 Short description of the Equipment under Test (EUT)

Number of tested samples: 1

Serial number: Prototype

3.3 EUT operation mode

The equipment under test was operated during the measurement under the following conditions:

□ - Standby

☐ TX- Y position

☐ TX- Zposition

■ TX- X position

Charging

Operation mode 1:TX-X Position Low (2402MHz), TX-X Position Middle (2440MHz),

TX-X Position High (2480MHz)

Operation mode 2:Charging

Note:Operation mode 1 TX -X position of EUT is the radiated test worst case; so only these test results be recorded in the test report.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





3.4 EUT configuration

3.4.1. Description of configuration (EUT)

Description		Sport Bluetooth Headset
Model Number	:	S90
Operation frequency	:	2402~ 2480 MHz ISM Band
Radio Technology	:	V4.0
Modulation Technology	:	GFSK, π/4-DQPSK,8DPSK modulation
Antenna	:	Ceramic antenna, met requirement of FCC 15.203

3.4.2. Tested Supporting System Details

3.4.2.1. Notebook

M/N	:	F83VF
S/N		N/A
Manufacturer		AUSU
Power Cord		1
FCC ID	:	ID

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 6 of 29

CENTRE OF TESTING SERVICE





4.TEST ENVIRONMENT

4.1 Address of the test laboratory

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

4.2 Test facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L3394

CENTRE OF TESTING SERVICE CO., LTD has been assessed and proved to be in compliance with CNAS-CL01: 2006 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

IC-Registration No.: 8374A

The 3m Alternate Test Site of CENTRE OF TESTING SERVICE CO., LTD has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 8374A on June 6, 2011.

FCC-Registration No.: 971995

CENTRE OF TESTING SERVICE CO., LTD, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration No.791995, July 13,2012.

4.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 ° C
Humidity:	25~75 %
Atmospheric pressure:	86~106 kPa

4.4 Definitions of symbols used in this test report

- - The black square indicates that the listed condition, standard or equipment is applicable for this report.
- □ The empty square indicates that the listed condition, standard or equipment is **not** applicable for this report.

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the CTS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 7 of 29







4.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	±1.22dB	(1)
Power disturbance	30MHz~300MHz	±1.38dB	(1)
	30MHz~300MHz	±3.14dB	(1)
Radiation emission (3m)	300MHz~1000MHz	±3.18dB	(1)
	1GHz~26.5GHz	±3.54dB	(1)

^{(1).} This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5. Summary of standards and results

5.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Results	
Conducted Emission Test	FCC Part 15 : 15.207 ANSI C63.4-2009	PASSED	
Radiated Emission Test	FCC Part 15 C: 15.249 FCC Part 15 : 109 ANSI C63.4-2009	PASSED	
Band Edge Compliance Test	FCC Part 15 C: 15.249 ANSI C63.4-2009	PASSED	
N/A is an abbreviation for Not Applicable.			

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service






6. Power Line Conducted Emission Test

6.1.Test Equipment

Conduc	Conducted Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	EMI Test Receiver	ROHDE & SCHWARZ	ESHS10	842884/012	2014/11	
2	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/025	2014/11	
3	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/026	2014/11	
4	Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100301	2014/11	
5	EMI Test Software	ROHDE & SCHWARZ	ESK1	N/A	2014/11	

6.2. Block Diagram of Test Setup



(EUT: Sport Bluetooth Headset)

6.3. Power Line Conducted Emission Test Limits

Standard:RSS-Gen:7.2.4,FCC Part 15: 15.207,ANSI C63.4-2009

		Maximum RF Line Voltage	
Frequency		Quasi-Peak Level	Average Level
		dB(μV)	dB(μV)
150kHz	~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz	~ 5MHz	56	46
5MHz	~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

6.4.Test Procedure

The Notebook connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). This provides a 50 ohm coupling impedance for the EUT. Please refer the block diagram of the test setup and photographs. The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#1). Power on the PC and let it work normally, we use a keyboard test soft ware, let EUT working in test mode, then test it. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC Part 15C on Conducted Emission Test.

6.5. Power Line Conducted Emission Test Results PASSED.

The frequency range from 150KHz~30MHz is investigated. Please see the following pages.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 9 of 29

^{2.} The lower limit shall apply at the transition frequencies.








Test point:	L	Result:	■ - passed
Frequency range:	0.15MHz~30MHz		□ - not passed

EUT	Sport Bluetooth Headset
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test Date:	11~13 February 2015
Operator	Duke
MODEL NO	S90



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.1620	9.78	15.83	25.61	65.36	-39.75	QP
2	0.1620	9.78	-0.79	8.99	55.36	-46.37	AVG
3	0.5420	9.84	12.77	22.61	56.00	-33.39	QP
4	0.5420	9.84	-1.26	8.58	46.00	-37.42	AVG
5	1.4300	9.84	2.11	11.95	56.00	-44.05	QP
6	1.4300	9.84	-3.87	5.97	46.00	-40.03	AVG
7	1.9820	9.86	1.00	10.86	56.00	-45.14	QP
8	1.9820	9.86	-3.95	5.91	46.00	-40.09	AVG
9	16.2660	9.96	5.20	15.16	60.00	-44.84	QP
10	16.2660	9.96	-3.25	6.71	50.00	-43.29	AVG
11	27.8500	10.08	12.60	22.68	60.00	-37.32	QP
12	27.8500	10.08	8.46	18.54	50.00	-31.46	AVG
Remark:	Remark: Other frequency mini margin all >6 dB of Limit						

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service







Test point:	N	Result:	passed
Frequency range:	0.15MHz~30MHz		□ - not passed



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.1620	9.78	16.15	25.93	65.36	-39.43	QP
2	0.1620	9.78	-0.54	9.24	55.36	-46.12	AVG
3	0.5420	9.84	12.44	22.28	56.00	-33.72	QP
4	0.5420	9.84	-1.39	8.45	46.00	-37.55	AVG
5	1.7020	9.85	2.83	12.68	56.00	-43.32	QP
6	1.7020	9.85	-3.75	6.10	46.00	-39.90	AVG
7	4.3180	9.91	-0.34	9.57	56.00	-46.43	QP
8	4.3180	9.91	-5.06	4.85	46.00	-41.15	AVG
9	17.8860	9.98	9.58	19.56	60.00	-40.44	QP
10	17.8860	9.98	4.42	14.40	50.00	-35.60	AVG
11	26.3540	10.07	15.33	25.40	60.00	-34.60	QP
12	26.3540	10.07	10.46	20.53	50.00	-29.47	AVG
Remark:	Remark: Other frequency mini margin all >6 dB of Limit						

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service






7. Radiated disturbance (electric field)

7.1.Test Equipment

Radia	Radiated disturbance (electric field)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2014/11	
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2014/03	
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2014/03	
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2014/03	
5	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03	
6	Loop Antenna	A.R.A	PLA-1030/B	1030	2014/11	

7.2.Block Diagram of Test Setup

7.2.1 Block Diagram of connection between EUT and simulators



(EUT: Sport Bluetooth Headset)

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn





7.2.2 Anechoic Chamber Setup Diagram



7.3. Radiated Emission Limit:

Standard: FCC 15.249, FCC 15.209.

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (µV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

FRE	FREQUENCY		DISTANCE	FIELD STREN	GTHS LIMIT
	MHz		Meters	μV/m	dB(μV)/m
0.009	~	0.490	300	2400/F(kHz)	
0.490	~	1.705	30	24000/F(kHz)	
1.705	~	30	30	30	
30	~	88	3	100	40.0
88	~	216	3	150	43.5
216	~	960	3	200	46.0
960	~	1000	3	500	54.0
Above 1000		000	3	Other:74.0 dB(μV)/m (Peak)	
At	Above 1000		3	54.0 dB(μV)/n	n (Average)

Remark:

- (1) Emission level $dB\mu V = 20 \log Emission level \mu V/m$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

CENTRE OF TESTING SERVICE





7.4.Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2009on radiated emission Test.

The frequency range from 30MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 120kHz RBW below 1GHz and a Peak and Average detector with 2MHz RBW above 1GHz,

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 300kHz VBW below 1GHz and a Peak detector with1MHz VBW above 1GHz, A average detector with 10Hz VBW above 1GHz

Pretest x, y, z position of EUT, final, select the worst case x position test and record the test results in the report.

The test modes (TX Mode) is tested in Anechoic Chamber and all the scanning waveforms are reported on section 7.5

7.5. Radiated Emission Test Results

PASSED.

The frequency range from 9KHz~30MHz,30MHz to 230MHz, 230MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 14 of 29







Test Mode:	TX –X Position Mode	Result:	■ - passed
Frequency range:	9KHz~30MHz		☐ - not passed

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
Rem	ark: The test re	sult readi	ng value is to I	ow, margin a	II > 10dB of t	he limit.	

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 15 of 29








Channel:	TX –X Position	Result:	■ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	30MHz-1GHz		

EUT	Sport Bluetooth Headset
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	11~13 February 2015
Operator	Duke
MODEL NO	S90



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.						
1	159.3186	-24.82	54.08	29.26	43.50	-14.24	QP						
2	184.7495	-19.87	52.13	32.26	43.50	-11.24	QP						
3	260.5010	-18.58	53.87	35.29	46.00	-10.71	QP						
4	268.0762	-17.92	54.81	36.89	46.00	-9.11	QP						
5	288.0962	-13.50	52.34	38.84	46.00	-7.16	QP						
6	296.2124	-12.44	54.26	41.82	46.00	-4.18	QP						
Remark	Other frequen	icy mini ma	rgin all >6 dB o	Remark: Other frequency mini margin all >6 dB of Limit									

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China


Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

CENTRE OF TESTING SERVICE







No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	347.6954	-23.24	50.17	26.93	46.00	-19.07	QP			
2	478.1563	-19.03	48.89	29.86	46.00	-16.14	QP			
3	626.8537	-15.76	47.22	31.46	46.00	-14.54	QP			
4	636.6733	-16.00	47.73	31.73	46.00	-14.27	QP			
5	751.7034	-14.56	47.36	32.80	46.00	-13.20	QP			
6	887.7756	-11.87	45.97	34.10	46.00	-11.90	QP			
Remark:	Remark: Other frequency mini margin all >6 dB of Limit									

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn







Channel:	TX –X Position Low CH	Result: ■ - passed	
Test point:	Horizontal	□ - not passe	d
Frequency range:	1GHz-26.5GHz		-

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2402.00	-5.48	94.35	88.87	114.00	-25.13	Peak
2	2402.00	-5.48	91.37	85.89	94.00	-8.11	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	1903.808	-9.79	46.10	36.31	74.00	-37.69	peak			
2	1903.808	-9.79	31.13	21.34	54.00	-32.66	AVG			
3	4328.657	2.10	46.12	48.22	74.00	-25.78	peak			
4	4328.657	2.10	31.19	33.29	54.00	-20.71	AVG			
5	6753.507	8.72	44.95	53.67	74.00	-20.33	peak			
6	6753.507	8.72	30.02	38.74	54.00	-15.26	AVG			
Remark:	Remark: Other frequency mini margin all >6 dB of Limit									

Channel:	TX –X Position Middle CH	Result:	■ - passed
Test point:	Horizontal		□ - not passed
Frequency range:	1GHz-26.5GHz		•

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2440.00	-5.13	93.78	88.65	114.00	-25.35	Peak
2	2440.00	-5.13	90.47	85.34	94.00	-8.66	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	1705.411	-10.95	44.76	33.81	74.00	-40.19	peak			
2	1705.411	-10.95	30.19	19.24	54.00	-34.76	AVG			
3	3645.291	0.19	46.13	46.32	74.00	-27.68	peak			
4	3645.291	0.19	31.10	31.29	54.00	-22.71	AVG			
5	5849.699	6.42	44.19	50.61	74.00	-23.39	peak			
6	5849.699	6.42	28.86	35.28	54.00	-18.72	AVG			
Remark:	Remark: Other frequency mini margin all >6 dB of Limit									

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 18 of 29







Channel:	TX –X Position High CH	Result:	■ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2480.00	-4.76	93.19	88.43	114.00	-25.57	Peak
2	2480.00	-4.76	90.05	85.29	94.00	-8.71	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	1286.573	-13.15	49.72	36.57	74.00	-37.43	peak			
2	1286.573	-13.15	34.45	21.30	54.00	-32.70	AVG			
3	3997.996	1.32	48.44	49.76	74.00	-24.24	peak			
4	3997.996	1.32	33.26	34.58	54.00	-19.42	AVG			
5	5981.964	6.84	46.74	53.58	74.00	-20.42	peak			
6	5981.964	6.84	31.90	38.74	54.00	-15.26	AVG			
Remark	Remark: Other frequency mini margin all >6 dB of Limit									

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

Page 19 of 29









No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.0000	-24.45	59.58	35.13	40.00	-4.87	QP			
2	79.7796	-27.41	53.20	25.79	40.00	-14.21	QP			
3	119.8196	-24.17	52.98	28.81	43.50	-14.69	QΡ			
4	129.5591	-23.11	53.15	30.04	43.50	-13.46	QP			
5	199.8998	-18.65	56.54	37.89	43.50	-5.61	QP			
6	248.0561	-18.84	50.29	31.45	46.00	-14.55	QP			
Remark	Remark: Other frequency mini margin all >6 dB of Limit									

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Complaint line: +86-20-85533471


E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

CENTRE OF TESTING SERVICE







No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.		
1	344.8898	-23.19	49.61	26.42	46.00	-19.58	QP		
2	398.1964	-24.34	49.41	25.07	46.00	-20.93	QP		
3	480.9619	-18.73	48.55	29.82	46.00	-16.18	QP		
4	626.8537	-15.76	47.91	32.15	46.00	-13.85	QP		
5	762.9259	-13.96	46.89	32.93	46.00	-13.07	QP		
6	907.4148	-11.73	45.96	34.23	46.00	-11.77	QP		
Remark:	Remark: Other frequency mini margin all >6 dB of Limit								

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn







Channel:	TX –X Position Low CH	Result:	■ - passed
Test point:	Vertical		□ - not passed
Frequency range:	1GHz-26.5GHz		

	No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
	1	2402.00	-5.48	90.92	85.44	114.00	-28.56	Peak
ĺ	2	2402.00	-5.48	89.2	83.72	94.00	-10.28	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.		
1	1969.940	-9.41	46.31	36.90	74.00	-37.10	peak		
2	1969.940	-9.41	30.75	21.34	54.00	-32.66	AVG		
3	4218.437	1.84	45.91	47.75	74.00	-26.25	peak		
4	4218.437	1.84	30.84	32.68	54.00	-21.32	AVG		
5	6533.066	8.19	45.36	53.55	74.00	-20.45	peak		
6	6533.066	8.19	30.52	38.71	54.00	-15.29	AVG		
Remark:	Remark: Other frequency mini margin all >6 dB of Limit								

Channel:	TX –X Position Middle CH	Result:	■ - passed
Test point:	Vertical		□ - not passed
Frequency range:	1GHz-26.5GHz		

	No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
	1	2440.00	-5.13	90.38	85.25	114.00	-28.75	Peak
Γ	2	2440.00	-5.13	88.25	83.12	94.00	-10.88	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.		
1	1705.411	-10.95	45.87	34.92	74.00	-39.08	peak		
2	1705.411	-10.95	31.08	20.13	54.00	-33.87	AVG		
3	3336.673	-0.80	46.28	45.48	74.00	-28.52	peak		
4	3336.673	-0.80	31.54	30.74	54.00	-23.26	AVG		
5	5937.876	6.70	44.31	51.01	74.00	-22.99	peak		
6	5937.876	6.70	29.57	36.27	54.00	-17.73	AVG		
Remark	Remark: Other frequency mini margin all >6 dB of Limit								

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 22 of 29







Channel:	TX –X Position High CH	Result:	■ - passed
Test point:	Vertical		□ - not passed
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2480.00	-4.76	90.11	85.35	114.00	-28.65	Peak
2	2480.00	-4.76	87.84	83.08	94.00	-10.92	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.		
1	1462.926	-12.32	47.13	34.81	74.00	-39.19	peak		
2	1462.926	-12.32	32.45	20.13	54.00	-33.87	AVG		
3	3799.599	0.69	47.89	48.58	74.00	-25.42	peak		
4	3799.599	0.69	32.96	33.65	54.00	-20.35	AVG		
5	6533.066	8.19	45.96	54.15	74.00	-19.85	peak		
6	6533.066	8.19	31.82	40.01	54.00	-13.99	AVG		
Remark	Remark: Other frequency mini margin all >6 dB of Limit								

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Report No.: CGZ3150210-00185-EF Page 23 of 29





8. Band Edge Compliance test

8.1. Test Equipment

Band Edge Compliance test								
Item Test Equipment Manufacturer Model No. Serial No. Last C								
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	10868	2014/11			
2	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2014/03			
3	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2014/03			

8.2. Test procedure

- 1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=1/on time(3KHz) / Sweep=AUTO

8.3. Test Results

PASSED.

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

Test Mode	Channel	Test Result Highest Emission (dBuv/m)				
	Marked Frequency	Horizontal Vertical				
		Peak	Average	Peak	Average	
Low Channel	2390MHz	35.30	20.26	32.54	19.86	
Low Charmer	2400MHz	70.41	65.52	68.11	64.15	
High Channel	2483.5MHz	59.70	47.68	56.01	44.23	
	2500MHz	30.26	20.10	29.74	19.49	

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service


Report No.: CGZ3150210-00185-EF Page 24 of 29





Band Edges (Low)





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.


A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China


Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn









Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China


Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406


Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn





Band Edges (High)





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China


Tel: +86-20-85543113 (32 lines)


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn









Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406

Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

CENTRE OF TESTING SERVICE





9. Deviation to test specifications

The following identical model(s):

UB-BTE90, S20, S20I, S90I, S50, S50I

Belong to the tested device:

Product description: **Sport Bluetooth Headset**Model name: **S90**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.