

FCC TEST REPORT

For

HIGH HOPE INTERNATIONAL GROUP JIANGSU
NATIVE PRODUCE IMP EXP CORP LTD

4 Channel RC Car

Model No.: 0059

Prepared For : HIGH HOPE INTERNATIONAL GROUP JIANGSU NATIVE
PRODUCE IMP EXP CORP LTD

Address : 91 BAI XIA ROAD, NANJING, CHINA

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan
District, Shenzhen, Guangdong, China

Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R0217060154W

Date of Test : Jun. 21~Jul. 04, 2017

Date of Report : Jul. 04, 2017

Contents

| | |
|---|----|
| 1. General Information..... | 4 |
| 1.1. Client Information..... | 4 |
| 1.2. Description of Device (EUT)..... | 4 |
| 1.3. Auxiliary Equipment Used During Test..... | 4 |
| 1.4. Description of Test Modes..... | 5 |
| 1.5. List of channels..... | 5 |
| 1.6. Description Of Test Setup..... | 6 |
| 1.7. Test Equipment List..... | 7 |
| 1.8. Measurement Uncertainty..... | 8 |
| 1.9. Description of Test Facility..... | 8 |
| 2. Summary of Test Results..... | 9 |
| 3. Conducted Emission Test..... | 10 |
| 3.1. Test Standard and Limit..... | 10 |
| 3.2. Test Setup..... | 10 |
| 3.3. Test Procedure..... | 10 |
| 3.4. Test Data..... | 10 |
| 4. Radiation Spurious Emission and Band Edge..... | 11 |
| 4.1. Test Standard and Limit..... | 11 |
| 4.2. Test Setup..... | 12 |
| 4.3. Test Procedure..... | 13 |
| 4.4. Test Data..... | 13 |
| 5. 20DB Occupy Bandwidth Test..... | 18 |
| 5.1. Test Standard and Limit..... | 18 |
| 5.2. Test Setup..... | 18 |
| 5.3. Test Procedure..... | 18 |
| 5.4. Test Data..... | 18 |
| 6. Antenna Requirement..... | 21 |
| 6.1. Test Standard and Requirement..... | 21 |
| 6.2. Antenna Connected Construction..... | 21 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH..... | 22 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH..... | 23 |
| APPENDIX III -- INTERNAL PHOTOGRAPH..... | 27 |

TEST REPORT

Applicant : HIGH HOPE INTERNATIONAL GROUP JIANGSU NATIVE PRODUCE IMP
EXP CORP LTD
Manufacturer : HIGH HOPE INTERNATIONAL GROUP JIANGSU NATIVE PRODUCE IMP
EXP CORP LTD
Product Name : 4 Channel RC Car
Model No. : 0059
Trade Mark : U.S.ARMY
Rating(s) : DC 3.0V by "AA" Battery*2

Test Standard(s) : FCC Part15 Subpart C 2016, Section 15.227

Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : Jun. 21~Jul. 04, 2017

Prepared by :



Winkey Wang

(Tested Engineer / Winkey Wang)

Reviewer :

Dolly mo

(Project Manager / Dolly Mo)

Approved & Authorized Signer :

Tom Chen

(Manager / Tom Chen)

1. General Information

1.1. Client Information

| | | |
|--------------|---|---|
| Applicant | : | HIGH HOPE INTERNATIONAL GROUP JIANGSU NATIVE PRODUCE IMP EXP CORP LTD |
| Address | : | 91 BAI XIA ROAD, NANJING, CHINA |
| Manufacturer | : | HIGH HOPE INTERNATIONAL GROUP JIANGSU NATIVE PRODUCE IMP EXP CORP LTD |
| Address | : | 91 BAI XIA ROAD, NANJING, CHINA |

1.2. Description of Device (EUT)

| | | | |
|---|---|---------------------------|-------------------|
| Product Name | : | 4 Channel RC Car | |
| Model No. | : | 0059 | |
| Trade Mark | : | U.S.ARMY | |
| Test Power Supply | : | DC 3.0V by "AA" Battery*2 | |
| Product Description | : | Operation Frequency: | 27.145MHz |
| | | Number of Channel: | 1 Channels |
| | | Modulation Type: | ASK |
| | | Antenna Type: | Integral antenna. |
| | | Antenna Gain(Peak): | 4 dbi |
| Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. | | | |

1.3. Auxiliary Equipment Used During Test

| | |
|-----|--|
| N/A | |
|-----|--|

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-------------------------|
| Mode 1 | Continuous transmission |

| For Radiated Emission | |
|-----------------------|-------------------------|
| Final Test Mode | Description |
| Mode 1 | Continuous transmission |


Note: During the test, the EUT was keeping continuous transmission.

1.5. List of channels

| Channel | Freq. (MHz) |
|---------|----------------|
| 01 | 27.145 |

1.6. Description Of Test Setup

RE



1.7. Test Equipment List

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|---|----------------------------|----------------|---------------|---------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | Rohde & Schwarz | ENV216 | 100055 | May 27, 2017 | 1 Year |
| 2. | EMI Test Receiver | Rohde & Schwarz | ESCI | 100627 | May 27, 2017 | 1 Year |
| 3. | RF Switching Unit | Compliance Direction | RSU-M2 | 38303 | May 27, 2017 | 1 Year |
| 4. | Spectrum Analysis | Agilent | E4407B | US39390582 | May 27, 2017 | 1 Year |
| 5. | Preamplifier | SKET Electronic | BK1G18G30 D | KD17503 | May 27, 2017 | 1 Year |
| 6. | EMI Test Receiver | Rohde & Schwarz | ESPI | 101604 | May 27, 2017 | 1 Year |
| 7. | Double Ridged Horn Antenna | Instruments corporation | GTH-0118 | 351600 | May 31, 2017 | 1 Year |
| 8. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | VULB 9163-289 | May 31, 2017 | 1 Year |
| 9. | Loop Antenna | Schwarzbeck | HFH2-Z2 | 100047 | Apr. 03, 2017 | 1 Year |
| 10. | Pre-amplifier | SONOMA | 310N | 186860 | May 27, 2017 | 1 Year |
| 11. | EMI Test Software EZ-EMC | SHURPLE | N/A | N/A | N/A | N/A |
| 12. | Power Sensor | DAER | RPR3006W | 15I00041SN045 | May 27, 2017 | 1 Year |
| 13. | Power Sensor | DAER | RPR3006W | 15I00041SN046 | May 27, 2017 | 1 Year |
| 14. | MXA Spectrum Analysis | Agilent | N9020A | MY51170037 | May 27, 2017 | 1 Year |
| 15. | MXG RF Vector Signal Generator | Agilent | N5182A | MY48180656 | May 27, 2017 | 1 Year |
| 16. | Signal Generator | Agilent | E4421B | MY41000743 | May 27, 2017 | 1 Year |
| 17. | DC Power supply | IVYTECH | IV6003 | 1601D6030007 | May 26, 2017 | 1 Year |
| 18. | TEMP&HUMI PROGRAMMABLE CHAMBER | Sertep | ZJ-HWHS80 B | ZJ-17042804 | Mar. 03, 2017 | 1 Year |

1.8. Measurement Uncertainty

| | | |
|------------------------|---|--------------------------|
| Radiation Uncertainty | : | Ur = 4.1 dB (Horizontal) |
| | | Ur = 4.3 dB (Vertical) |
| | | |
| Conduction Uncertainty | : | Uc = 3.4dB |

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 06, 2016.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

2. Summary of Test Results

| Standard Section | Test Item | Result |
|---|-------------------------|--------|
| 15.203 | Antenna Requirement | PASS |
| 15.207 | Conducted Emission | N/A |
| 15.205/15.209/15.227 | Spurious Emission | PASS |
| 15.215(c) | 20dB Occupied Bandwidth | PASS |
| Remark: “N/A” is an abbreviation for Not Applicable. | | |


3. Conducted Emission Test

3.1. Test Standard and Limit

| Test Standard | FCC Part15 Section 15.207 | | |
|---------------|---------------------------|--------------------------------|---------------|
| Test Limit | Frequency | Maximum RF Line Voltage (dBuV) | |
| | | Quasi-peak Level | Average Level |
| | 150kHz~500kHz | 66 ~ 56 * | 56 ~ 46 * |
| | 500kHz~5MHz | 56 | 46 |
| | 5MHz~30MHz | 60 | 50 |

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

N/A

The EUT was power supplied by "AA" Battery*2 (DC 3.0V).

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

| | | | | | |
|--|---|-------------------------------------|-------------------|------------|-----------------------------|
| Test Standard | FCC Part15 C Section 15.209, 15.205 and 15.227(a) | | | | |
| Test Limit | Frequency (MHz) | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz~0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz~88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz~216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz~960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz~1000MHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1000MHz | 500 | 54.0 | Average | 3 |
| | | - | 74.0 | Peak | 3 |
| Remark: (1)The lower limit shall apply at the transition frequency. (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. | | | | | |

According to §15.227(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

$$\text{Emission Level (dBuV/m)} = 20 \log \text{Emission Level (uV/m)}$$

The field strength of emission limits have been calculated in below table:

| Fundamental Frequency (MHz) | Field Strength of Fundamental (dBuV/m)@3m |
|-----------------------------|---|
| 26.96~27.28 | 80.0 (AVG) |
| 26.96~27.28 | 100.0 (Peak) |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

Test Results (Fundamental 27.145MHz)

| Frequency | Antenna | Reading | Cable Loss | Ant Factor | Amplifier | Duty cycle Factor | Results | Limits | Det. |
|-----------|---------|----------|------------|------------|-----------|-------------------|----------|----------|------|
| (MHz) | Pol. | (dBuV/m) | (dB) | (dB) | (dB) | (dB) | (dBuV/m) | (dBuV/m) | Mode |
| 27.145 | H | 92.35 | 1.12 | -16.70 | 0.00 | -- | 76.77 | 100.00 | PK |
| 27.145 | H | 92.35 | 1.12 | -16.70 | 0.00 | -4.12 | 72.65 | 80.00 | AV |
| 27.145 | V | 94.42 | 1.12 | -16.70 | 0.00 | -- | 78.84 | 100.00 | PK |
| 27.145 | V | 94.42 | 1.12 | -16.70 | 0.00 | -4.12 | 74.72 | 80.00 | AV |

Remark :

1. Result = Reading + Cable Loss +Ant Factor –Amplifier + Duty cycle Factor

3. Duty Cycle Factor

Calculate Formula:

AV=PEAK +Duty Cycle Factor

Duty Cycle Factor=20log(Duty Cycle)

Duty Cycle= on time/ period

Test Data:


T on time=1.55ms*4+0.5ms*10=11.20ms

T period=18.0ms

Duty Cycle=62.22%

Duty Cycle Factor =20log(Duty Cycle)=-4.12

T on time slot



T period



Test Results (Harmonics Emissions)

| Frequency | Antenna | Reading | Cable Loss | Ant Factor | Amplifier | Duty cycle Factor | Results | Limits | Det |
|-----------|---------|----------|------------|------------|-----------|-------------------|----------|----------|------|
| (MHz) | Pol. | (dBuV/m) | (dB) | (dB) | (dB) | (dB) | (dBuV/m) | (dBuV/m) | Mode |
| 54.290 | H | 82.55 | 1.17 | 12.14 | 31.15 | -- | 64.71 | 100.00 | PK |
| 54.290 | H | 82.55 | 1.17 | 12.14 | 31.15 | -4.12 | 60.59 | 80.00 | AV |
| 54.290 | V | 84.37 | 1.17 | 12.14 | 31.15 | -- | 66.53 | 100.00 | PK |
| 54.290 | V | 84.37 | 1.17 | 12.14 | 31.15 | -4.12 | 62.41 | 80.00 | AV |
| 81.435 | H | 63.41 | 1.20 | 12.27 | 31.16 | -- | 45.72 | 100.00 | PK |
| 81.435 | H | 63.41 | 1.20 | 12.27 | 31.16 | -4.12 | 41.60 | 80.00 | AV |
| 81.435 | V | 65.28 | 1.20 | 12.27 | 31.16 | -- | 47.59 | 100.00 | PK |
| 81.435 | V | 65.28 | 1.20 | 12.27 | 31.16 | -4.12 | 43.47 | 80.00 | AV |
| 108.580 | H | * | | | | | | 100.00 | PK |
| 108.580 | H | * | | | | | | 80.00 | AV |
| 108.580 | V | * | | | | | | 100.00 | PK |
| 108.580 | V | * | | | | | | 80.00 | AV |

Remark :

1. Result = Reading + Cable Loss +Ant Factor –Amplifier + Duty cycle Factor
3. Duty Cycle Factor=-4.12
4. “*”, means this data is the too weak instrument of signal is unable to test.

Test Results (Radiated Emission)

| Frequency | Antenna | Reading | Cable Loss | Ant Factor | Amplifier | Results | Limits | Margin | Det. |
|-----------|---------|----------|------------|------------|-----------|----------|----------|--------|------|
| (MHz) | Pol. | (dBuV/m) | (dB) | (dB) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | Mode |
| 75.48 | H | 45.41 | 1.18 | 12.27 | 30.74 | 28.12 | 40.00 | -11.88 | QP |
| 135.25 | H | 47.48 | 1.24 | 12.25 | 30.48 | 30.49 | 43.50 | -13.01 | QP |
| 725.21 | H | 46.53 | 1.73 | 13.76 | 31.27 | 30.75 | 46.00 | -15.25 | QP |
| 75.48 | V | 47.35 | 1.18 | 12.27 | 30.74 | 30.06 | 40.00 | -9.94 | QP |
| 135.25 | V | 46.21 | 1.24 | 12.25 | 30.48 | 29.22 | 43.50 | -14.28 | QP |
| 725.21 | V | 49.16 | 1.73 | 13.76 | 31.27 | 33.38 | 46.00 | -12.62 | QP |

Remark:


1. Results = Reading + Cable Loss +Ant Factor –Amplifier

5. 20DB Occupy Bandwidth Test

5.1. Test Standard and Limit

| | |
|---------------|---|
| Test Standard | FCC Part15 C Section 15.215 |
| Test Limit | <p>15.215(c), Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.</p> <p>Operation within the band: 26. 96 – 27.28 MHz</p> |

5.2. Test Setup




5.3. Test Procedure

1. Place the EUT on the table and set it in the continuously transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
 RBW = 30kHz, VBW \geq 3*RBW =100kHz,
 Span= 3MHz
 Detector= Peak
 Trace mode= Max hold.
 Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

5.4. Test Data

| | | | | | |
|--------------|---|----------------|-------------|---|-------------------------|
| Test Item | : | 20dB Bandwidth | Test Mode | : | Continuous transmission |
| Test Voltage | : | DC 3V | Temperature | : | 24℃ |
| Test Result | : | PASS | Humidity | : | 55%RH |

| Freq. (MHz) | Bandwidth (kHz) |
|----------------|-----------------|
| 27.145 | 158.3 |



20 dB BW

6. Antenna Requirement

6.1. Test Standard and Requirement

| | |
|---------------|--|
| Test Standard | FCC Part15 Section 15.203 |
| Requirement | <p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.</p> <p>Antenna requirement must meet at least one of the following:</p> <ol style="list-style-type: none"> 1) Antenna must be permanently attached to device. 2) The antenna must use a unique type of connector to attach to the device. 3) Device must be professionally installed. The installer shall be responsible for ensuring that the correct antenna is employed by the device. |



6.2. Antenna Connected Construction

The RF antenna is a Integral antenna which permanently attached, and the best case gain of the antenna is 4 dBi. It complies with the standard requirement.





APPENDIX I -- TEST SETUP PHOTOGRAPH


Photo of Radiation Emission Test



APPENDIX II -- EXTERNAL PHOTOGRAPH









APPENDIX III -- INTERNAL PHOTOGRAPH

