

## FCC Test Report

**Report No.:** RF120531C10N

**FCC ID:** ZHV-DTAEA

**Test Model:** DTAEA

**Received Date:** May 09, 2012

**Test Date:** Mar. 17 ~ Apr. 11, 2016

**Issued Date:** Apr. 18, 2016

**Applicant:** Riverbed Technology Inc.

**Address:** 680 Folsom Street San Francisco, California USA 94107

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b>	<b>4</b>
<b>1 Certificate of Conformity</b>	<b>5</b>
<b>2 Summary of Test Results</b>	<b>6</b>
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
<b>3 General Information</b>	<b>7</b>
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	9
3.3 Duty Cycle of Test Signal	11
3.4 Description of Support Units	12
3.4.1 Configuration of System under Test	12
3.5 General Description of Applied Standards	12
<b>4 Test Types and Results</b>	<b>14</b>
4.1 Radiated Emission and Bandedge Measurement	14
4.1.1 Limits of Radiated Emission and Bandedge Measurement	14
4.1.2 Test Instruments	15
4.1.3 Test Procedures	16
4.1.4 Deviation from Test Standard	16
4.1.5 Test Set Up	17
4.1.6 EUT Operating Conditions	17
4.1.7 Test Results	18
4.2 Conducted Emission Measurement	32
4.2.1 Limits of Conducted Emission Measurement	32
4.2.2 Test Instruments	32
4.2.3 Test Procedures	33
4.2.4 Deviation from Test Standard	33
4.2.5 Test Setup	33
4.2.6 EUT Operating Conditions	33
4.2.7 Test Results	34
4.3 6dB Bandwidth Measurement	38
4.3.1 Limits of 6dB Bandwidth Measurement	38
4.3.2 Test Setup	38
4.3.3 Test Instruments	38
4.3.4 Test Procedure	38
4.3.5 Deviation from Test Standard	38
4.3.6 EUT Operating Conditions	38
4.3.7 Test Result	39
4.4 Conducted Output Power Measurement	41
4.4.1 Limits of Conducted Output Power Measurement	41
4.4.2 Test Setup	41
4.4.3 Test Instruments	41
4.4.4 Test Procedures	41
4.4.5 Deviation from Test Standard	41
4.4.6 EUT Operating Conditions	41
4.4.7 Test Results	42
4.5 Power Spectral Density Measurement	43
4.5.1 Limits of Power Spectral Density Measurement	43
4.5.2 Test Setup	43
4.5.3 Test Instruments	43
4.5.4 Test Procedure	43
4.5.5 Deviation from Test Standard	43
4.5.6 EUT Operating Condition	43

4.5.7 Test Results .....	44
4.6 Conducted Out of Band Emission Measurement.....	47
4.6.1 Limits of Conducted Out of Band Emission Measurement .....	47
4.6.2 Test Setup.....	47
4.6.3 Test Instruments .....	47
4.6.4 Test Procedure .....	47
4.6.5 Deviation from Test Standard .....	47
4.6.6 EUT Operating Condition .....	47
4.6.7 Test Results .....	47
<b>5 Pictures of Test Arrangements.....</b>	<b>56</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>57</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
RF120531C10N	Original release.	Apr. 18, 2016

## 1 Certificate of Conformity

**Product:** Wireless-N 300Mbps+300Mbps Ceiling Mount Dual Band Concurrent AP

**Brand:** riverbed

**Test Model:** DTAEA

**Sample Status:** Engineering sample

**Applicant:** Riverbed Technology Inc.

**Test Date:** Mar. 17 ~ Apr. 11, 2016

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Sunttee Liu , **Date:** Apr. 18, 2016  
Sunttee Liu / Specialist

**Approved by :** Ken Liu , **Date:** Apr. 18, 2016  
Ken Liu / Senior Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -11.15 dB at 3.37109 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2350.00 & 2377.00 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is I-PEX not a standard connector.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.34 dB
	200MHz ~ 1000MHz	3.35 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	Wireless-N 300Mbps+300Mbps Ceiling Mount Dual Band Concurrent AP
Brand	<b>riverbed</b>
Test Model	DTAEA
Sample Status	Engineering sample
Power Supply Rating	12Vdc (adapter) 48Vdc (POE)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 300Mbps
Operating Frequency	2412~2462MHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7
Output Power	721.132mW
Antenna Type	PIFA antenna with 2dBi gain
Antenna Connector	IPEX
Accessory Device	Adapter
Data Cable Supplied	NA

#### Note:

- The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Modulation Mode	TX Function
802.11b	2TX
802.11g	2TX
802.11n (HT20)	2TX
802.11n (HT40)	2TX

- The EUT uses following adapter and POE. POE is provided as support unit only.

Adapter	
Brand	Powertron
Model	PA1024-2HUB
Input Power	100-240Vac, 50-60Hz, 0.6A
Output Power	12Vdc, 2.0A, 24.0W
Power Line	1.5m non-shielded cable with one core

POE	
Model	PD-6083G300
Input Power	100-250Vac, 50/60Hz, 0.5A
Output Power	48Vdc, 0.35A

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		



### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
A	√	√	√	√	Power from adapter
B	-	√	√	-	Power from POE

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement  
 RE<1G: Radiated Emission below 1GHz  
 PLC: Power Line Conducted Emission  
 APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.
2. "-" means no effect.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Date Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Date Rate (Mbps)
A, B	802.11g	1 to 11	6	OFDM	BPSK	6.0

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Date Rate (Mbps)
A, B	802.11g	1 to 11	6	OFDM	BPSK	6.0

#### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Date Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

#### Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE $\geq$ 1G	19deg. C, 68%RH	120Vac, 60Hz	Jones Chang
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Chris Lin
PLC	23deg. C, 66%RH	120Vac, 60Hz	Ben Huang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Leo Tsai

### 3.3 Duty Cycle of Test Signal

802.11b: Duty cycle of test signal is  $\geq 98\%$ , duty factor is not required.


802.11g, 802.11n (HT20), 802.11n (HT40): Duty cycle of test signal is  $< 98\%$ , duty factor shall be considered.

802.11b: Duty cycle = 100%

802.11g: Duty cycle =  $2.019/2.075 = 0.973$ , Duty factor =  $10 * \log(1/0.973) = 0.12$

802.11n (HT20): Duty cycle =  $1.882/1.941 = 0.970$ , Duty factor =  $10 * \log(1/0.970) = 0.13$

802.11n (HT40): Duty cycle =  $0.922/0.967 = 0.953$ , Duty factor =  $10 * \log(1/0.953) = 0.21$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved	-
B.	POE	NA	PD-6083G300	NA	NA	Provided by Manufacturer


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items A~B acted as communication partners to transfer data.


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ45 , Cat5e	1	3	N	0	-
2.	RJ45 , Cat5e	1	3	N	0	-

#### 3.4.1 Configuration of System under Test

Test mode A



Test mode B



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v03r05**

**662911 D01 Multiple Transmitter Output v02r01**

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.

#### 4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Dec. 23, 2015	Dec. 22, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Sep. 02, 2015	Sep. 01, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-171	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna SCHWARZBECK	9120D	209	Jan. 20, 2016	Jan. 19, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Jan. 18, 2016	Jan. 17, 2017
Preamplifier Agilent	8447D	2944A10738	Oct. 18, 2015	Oct. 17, 2016
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (214378)	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 106	Cable-CH3-03 (309224+12738)	Aug. 22, 2015	Aug. 21, 2016
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA
High Speed Peak Power Meter	ML2495A	0824011	Jul. 09, 2015	Jul. 08, 2016
Power Sensor	MA2411B	0738171	Jul. 09, 2015	Jul. 08, 2016

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 3.  
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
4. The FCC Site Registration No. is 988962.  
5. The IC Site Registration No. is IC 7450F-3.

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


#### 4.1.4 Deviation from Test Standard

No deviation.




#### 4.1.5 Test Set Up

<Frequency Range 30MHz~1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared notebook to act as communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.7 Test Results

Above 1GHz Worst-case Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2325.00	63.5 PK	74.0	-10.5	2.11 H	19	31.00	32.50
2	2325.00	50.9 AV	54.0	-3.1	2.11 H	19	18.40	32.50
3	*2412.00	107.0 PK			1.39 H	53	74.10	32.90
4	*2412.00	103.8 AV			1.39 H	53	70.90	32.90
5	4824.00	48.1 PK	74.0	-25.9	1.90 H	134	42.20	5.90
6	4824.00	35.9 AV	54.0	-18.1	1.90 H	134	30.00	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2325.00	71.8 PK	74.0	-2.2	2.81 V	348	39.30	32.50
2	2325.00	52.5 AV	54.0	-1.5	2.81 V	348	20.00	32.50
3	*2412.00	111.6 PK			2.41 V	61	78.70	32.90
4	*2412.00	108.2 AV			2.41 V	61	75.30	32.90
5	2500.00	60.6 PK	74.0	-13.4	2.81 V	59	27.60	33.00
6	2500.00	51.6 AV	54.0	-2.4	2.81 V	59	18.60	33.00
7	4824.00	52.5 PK	74.0	-21.5	2.98 V	141	46.60	5.90
8	4824.00	47.3 AV	54.0	-6.7	2.98 V	141	41.40	5.90

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2350.00	60.1 PK	74.0	-13.9	2.12 H	338	27.50	32.60
2	2350.00	51.3 AV	54.0	-2.7	2.12 H	338	18.70	32.60
3	*2437.00	110.4 PK			1.67 H	49	77.50	32.90
4	*2437.00	106.9 AV			1.67 H	49	74.00	32.90
5	4874.00	48.4 PK	74.0	-25.6	1.86 H	120	42.40	6.00
6	4874.00	36.3 AV	54.0	-17.7	1.86 H	120	30.30	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2350.00	62.8 PK	74.0	-11.2	2.92 V	4	30.20	32.60
2	<b>2350.00</b>	<b>53.0 AV</b>	<b>54.0</b>	<b>-1.0</b>	<b>2.92 V</b>	<b>4</b>	<b>20.40</b>	<b>32.60</b>
3	*2437.00	112.3 PK			2.63 V	8	79.40	32.90
4	*2437.00	108.6 AV			2.63 V	8	75.70	32.90
5	4874.00	49.7 PK	74.0	-24.3	2.76 V	158	43.70	6.00
6	4874.00	37.3 AV	54.0	-16.7	2.76 V	158	31.30	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	59.7 PK	74.0	-14.3	1.81 H	329	26.90	32.80
2	2377.00	50.2 AV	54.0	-3.8	1.81 H	329	17.40	32.80
3	2387.00	60.3 PK	74.0	-13.7	1.50 H	87	27.50	32.80
4	2387.00	48.5 AV	54.0	-5.5	1.50 H	87	15.70	32.80
5	*2462.00	107.5 PK			1.48 H	101	74.60	32.90
6	*2462.00	104.1 AV			1.48 H	101	71.20	32.90
7	4924.00	48.0 PK	74.0	-26.0	1.92 H	343	42.00	6.00
8	4924.00	35.7 AV	54.0	-18.3	1.92 H	343	29.70	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	62.3 PK	74.0	-11.7	2.93 V	348	29.50	32.80
2	<b>2377.00</b>	<b>53.0 AV</b>	<b>54.0</b>	<b>-1.0</b>	<b>2.93 V</b>	<b>348</b>	<b>20.20</b>	<b>32.80</b>
3	*2462.00	110.2 PK			2.48 V	340	77.30	32.90
4	*2462.00	106.6 AV			2.48 V	340	73.70	32.90
5	2487.00	71.2 PK	74.0	-2.8	2.86 V	274	38.20	33.00
6	2487.00	51.5 AV	54.0	-2.5	2.86 V	274	18.50	33.00
7	4924.00	49.9 PK	74.0	-24.1	2.71 V	122	43.90	6.00
8	4924.00	37.3 AV	54.0	-16.7	2.71 V	122	31.30	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* " : Fundamental frequency.

## 802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.6 PK	74.0	-3.4	1.77 H	59	37.80	32.80
2	2390.00	52.8 AV	54.0	-1.2	1.77 H	59	20.00	32.80
3	*2412.00	108.9 PK			1.47 H	62	76.00	32.90
4	*2412.00	99.6 AV			1.47 H	62	66.70	32.90
5	4824.00	49.3 PK	74.0	-24.7	1.76 H	166	43.40	5.90
6	4824.00	36.4 AV	54.0	-17.6	1.76 H	166	30.50	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.4 PK	74.0	-2.6	2.62 V	347	38.60	32.80
2	2390.00	52.8 AV	54.0	-1.2	2.62 V	347	20.00	32.80
3	*2412.00	110.4 PK			2.41 V	62	77.50	32.90
4	*2412.00	100.4 AV			2.41 V	62	67.50	32.90
5	4824.00	48.9 PK	74.0	-25.1	2.01 V	130	43.00	5.90
6	4824.00	35.8 AV	54.0	-18.2	2.01 V	130	29.90	5.90

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2356.00	66.6 PK	74.0	-7.4	1.18 H	23	33.90	32.70
2	2356.00	52.1 AV	54.0	-1.9	1.18 H	23	19.40	32.70
3	*2437.00	117.5 PK			1.49 H	147	84.60	32.90
4	*2437.00	107.8 AV			1.49 H	147	74.90	32.90
5	2483.50	62.2 PK	74.0	-11.8	1.55 H	10	29.20	33.00
6	2483.50	49.6 AV	54.0	-4.4	1.55 H	10	16.60	33.00
7	4874.00	52.8 PK	74.0	-21.2	1.68 H	170	46.80	6.00
8	4874.00	38.3 AV	54.0	-15.7	1.68 H	170	32.30	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2350.00	70.4 PK	74.0	-3.6	1.58 V	341	37.80	32.60
2	2350.00	52.5 AV	54.0	-1.5	1.58 V	341	19.90	32.60
3	*2437.00	120.2 PK			2.68 V	4	87.30	32.90
4	*2437.00	110.7 AV			2.68 V	4	77.80	32.90
5	2483.50	68.1 PK	74.0	-5.9	2.68 V	300	35.10	33.00
6	2483.50	50.9 AV	54.0	-3.1	2.68 V	300	17.90	33.00
7	4874.00	53.5 PK	74.0	-20.5	2.23 V	187	47.50	6.00
8	4874.00	38.3 AV	54.0	-15.7	2.23 V	187	32.30	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.2 PK			1.44 H	278	76.30	32.90
2	*2462.00	99.6 AV			1.44 H	278	66.70	32.90
3	2483.50	70.5 PK	74.0	-3.5	2.03 H	15	37.50	33.00
4	2483.50	52.0 AV	54.0	-2.0	2.03 H	15	19.00	33.00
5	4924.00	51.6 PK	74.0	-22.4	2.01 H	32	45.60	6.00
6	4924.00	37.4 AV	54.0	-16.6	2.01 H	32	31.40	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.1 PK			2.50 V	69	77.20	32.90
2	*2462.00	101.0 AV			2.50 V	69	68.10	32.90
3	2483.50	71.5 PK	74.0	-2.5	2.61 V	0	38.50	33.00
4	2483.50	52.2 AV	54.0	-1.8	2.61 V	0	19.20	33.00
5	4924.00	48.9 PK	74.0	-25.1	2.00 V	304	42.90	6.00
6	4924.00	36.1 AV	54.0	-17.9	2.00 V	304	30.10	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.5 PK	74.0	-3.5	1.51 H	35	37.70	32.80
2	2390.00	51.5 AV	54.0	-2.5	1.51 H	35	18.70	32.80
3	*2412.00	107.2 PK			1.43 H	51	74.30	32.90
4	*2412.00	97.7 AV			1.43 H	51	64.80	32.90
5	4824.00	47.6 PK	74.0	-26.4	1.80 H	156	41.70	5.90
6	4824.00	34.6 AV	54.0	-19.4	1.80 H	156	28.70	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.9 PK	74.0	-4.1	2.35 V	33	37.10	32.80
2	2390.00	52.4 AV	54.0	-1.6	2.35 V	33	19.60	32.80
3	*2412.00	108.4 PK			2.42 V	62	75.50	32.90
4	*2412.00	99.2 AV			2.42 V	62	66.30	32.90
5	4824.00	48.6 PK	74.0	-25.4	1.89 V	200	42.70	5.90
6	4824.00	35.3 AV	54.0	-18.7	1.89 V	200	29.40	5.90

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.5 PK	74.0	-6.5	1.26 H	24	34.70	32.80
2	2390.00	50.9 AV	54.0	-3.1	1.26 H	24	18.10	32.80
3	*2437.00	116.8 PK			1.50 H	146	83.90	32.90
4	*2437.00	107.4 AV			1.50 H	146	74.50	32.90
5	2483.50	63.9 PK	74.0	-10.1	1.50 H	66	30.90	33.00
6	2483.50	49.6 AV	54.0	-4.4	1.50 H	66	16.60	33.00
7	4874.00	48.3 PK	74.0	-25.7	1.70 H	107	42.30	6.00
8	4874.00	35.9 AV	54.0	-18.1	1.70 H	107	29.90	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2345.00	70.0 PK	74.0	-4.0	2.39 V	317	37.40	32.60
2	2345.00	52.1 AV	54.0	-1.9	2.39 V	317	19.50	32.60
3	*2437.00	118.3 PK			2.09 V	60	85.40	32.90
4	*2437.00	108.7 AV			2.09 V	60	75.80	32.90
5	2483.50	64.6 PK	74.0	-9.4	2.40 V	0	31.60	33.00
6	2483.50	50.3 AV	54.0	-3.7	2.40 V	0	17.30	33.00
7	4874.00	51.9 PK	74.0	-22.1	2.12 V	234	45.90	6.00
8	4874.00	39.0 AV	54.0	-15.0	2.12 V	234	33.00	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.0 PK			1.39 H	278	76.10	32.90
2	*2462.00	99.5 AV			1.39 H	278	66.60	32.90
3	2483.50	67.9 PK	74.0	-6.1	1.54 H	11	34.90	33.00
4	2483.50	51.7 AV	54.0	-2.3	1.54 H	11	18.70	33.00
5	4924.00	47.5 PK	74.0	-26.5	1.69 H	356	41.50	6.00
6	4924.00	34.8 AV	54.0	-19.2	1.69 H	356	28.80	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.8 PK			2.41 V	24	76.90	32.90
2	*2462.00	100.4 AV			2.41 V	24	67.50	32.90
3	2483.50	69.6 PK	74.0	-4.4	2.47 V	345	36.60	33.00
4	2483.50	52.8 AV	54.0	-1.2	2.47 V	345	19.80	33.00
5	4924.00	50.2 PK	74.0	-23.8	2.10 V	100	44.20	6.00
6	4924.00	37.0 AV	54.0	-17.0	2.10 V	100	31.00	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.4 PK	74.0	-9.6	1.55 H	56	31.60	32.80
2	2390.00	50.1 AV	54.0	-3.9	1.55 H	56	17.30	32.80
3	*2422.00	100.2 PK			1.52 H	53	67.30	32.90
4	*2422.00	91.5 AV			1.52 H	53	58.60	32.90
5	4844.00	47.1 PK	74.0	-26.9	1.00 H	145	41.30	5.80
6	4844.00	33.7 AV	54.0	-20.3	1.00 H	145	27.90	5.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.8 PK	74.0	-7.2	2.34 V	32	34.00	32.80
2	2390.00	52.4 AV	54.0	-1.6	2.34 V	32	19.60	32.80
3	*2422.00	101.7 PK			2.38 V	63	68.80	32.90
4	*2422.00	92.7 AV			2.38 V	63	59.80	32.90
5	4844.00	46.9 PK	74.0	-27.1	2.26 V	169	41.10	5.80
6	4844.00	34.3 AV	54.0	-19.7	2.26 V	169	28.50	5.80

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.0 PK	74.0	-9.0	1.34 H	23	32.20	32.80
2	2390.00	50.7 AV	54.0	-3.3	1.34 H	23	17.90	32.80
3	*2437.00	105.1 PK			1.49 H	276	72.20	32.90
4	*2437.00	95.6 AV			1.49 H	276	62.70	32.90
5	4874.00	47.6 PK	74.0	-26.4	1.76 H	143	41.60	6.00
6	4874.00	34.4 AV	54.0	-19.6	1.76 H	143	28.40	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.5 PK	74.0	-4.5	1.90 V	351	36.70	32.80
2	2390.00	52.3 AV	54.0	-1.7	1.90 V	351	19.50	32.80
3	*2437.00	106.0 PK			2.36 V	8	73.10	32.90
4	*2437.00	97.0 AV			2.36 V	8	64.10	32.90
5	4874.00	47.9 PK	74.0	-26.1	2.06 V	68	41.90	6.00
6	4874.00	35.1 AV	54.0	-18.9	2.06 V	68	29.10	6.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	100.8 PK			1.36 H	13	67.80	33.00
2	*2452.00	91.7 AV			1.36 H	13	58.70	33.00
3	2483.50	65.0 PK	74.0	-9.0	1.91 H	18	32.00	33.00
4	2483.50	49.6 AV	54.0	-4.4	1.91 H	18	16.60	33.00
5	4904.00	47.0 PK	74.0	-27.0	1.56 H	69	41.10	5.90
6	4904.00	33.9 AV	54.0	-20.1	1.56 H	69	28.00	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	101.5 PK			2.30 V	66	68.50	33.00
2	*2452.00	92.7 AV			2.30 V	66	59.70	33.00
3	2483.50	70.6 PK	74.0	-3.4	2.36 V	24	37.60	33.00
4	2483.50	52.3 AV	54.0	-1.7	2.36 V	24	19.30	33.00
5	4904.00	47.2 PK	74.0	-26.8	1.90 V	301	41.30	5.90
6	4904.00	34.1 AV	54.0	-19.9	1.90 V	301	28.20	5.90

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### Below 1GHz Worst-Case Data: 802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	90.17	36.5 QP	43.5	-7.0	1.99 H	130	28.30	8.20
2	179.61	34.4 QP	43.5	-9.1	1.50 H	250	21.80	12.60
3	255.44	35.3 QP	46.0	-10.7	1.00 H	90	22.10	13.20
4	374.04	31.9 QP	46.0	-14.1	1.99 H	250	15.00	16.90
5	675.40	33.2 QP	46.0	-12.8	1.24 H	128	10.40	22.80
6	902.89	35.8 QP	46.0	-10.2	1.00 H	266	9.00	26.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	37.5 QP	40.0	-2.5	1.24 V	163	25.70	11.80
2	88.23	38.2 QP	43.5	-5.3	1.00 V	89	29.70	8.50
3	148.50	33.6 QP	43.5	-9.9	1.00 V	302	19.50	14.10
4	224.33	32.3 QP	46.0	-13.7	1.00 V	132	20.30	12.00
5	274.88	27.9 QP	46.0	-18.1	1.24 V	217	13.90	14.00
6	374.04	34.5 QP	46.0	-11.5	1.00 V	211	17.60	16.90

### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	191.28	34.6 QP	43.5	-8.9	1.25 H	235	22.90	11.70
2	255.44	34.7 QP	46.0	-11.3	1.25 H	107	21.50	13.20
3	374.04	38.0 QP	46.0	-8.0	1.00 H	220	21.10	16.90
4	500.42	35.8 QP	46.0	-10.2	2.00 H	202	15.80	20.00
5	624.85	35.9 QP	46.0	-10.1	1.25 H	193	13.60	22.30
6	875.67	33.9 QP	46.0	-12.1	1.50 H	201	7.40	26.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	55.18	36.9 QP	40.0	-3.1	1.50 V	26	23.20	13.70
2	255.44	35.1 QP	46.0	-10.9	1.00 V	258	21.90	13.20
3	374.04	35.8 QP	46.0	-10.2	1.24 V	192	18.90	16.90
4	500.42	36.3 QP	46.0	-9.7	1.00 V	207	16.30	20.00
5	624.85	33.2 QP	46.0	-12.8	1.00 V	102	10.90	22.30
6	875.67	32.8 QP	46.0	-13.2	1.24 V	106	6.30	26.50

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

**Note:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 16, 2015	Nov. 15, 2016
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Dec. 26, 2015	Dec. 25, 2016
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2016	Feb. 25, 2017
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 24, 2015	Jul. 23, 2016
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

**Note:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.

3. The VCCI Site Registration No. is C-2040.



### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

### 4.2.4 Deviation from Test Standard

No deviation.

### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.2.6 EUT Operating Conditions

Same as 4.1.6.


#### 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.14	50.15	33.43	50.29	33.57	66.00	56.00	-15.71	-22.43
2	0.24375	0.21	40.47	27.88	40.68	28.09	61.97	51.97	-21.28	-23.87
3	0.53672	0.17	39.31	32.96	39.48	33.13	56.00	46.00	-16.52	-12.87
4	1.79688	0.23	29.37	21.67	29.60	21.90	56.00	46.00	-26.40	-24.10
5	3.45703	0.31	36.01	29.68	36.32	29.99	56.00	46.00	-19.68	-16.01
6	12.89453	0.66	33.40	27.45	34.06	28.11	60.00	50.00	-25.94	-21.89

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.23	50.35	34.08	50.58	34.31	66.00	56.00	-15.42	-21.69
2	0.25938	0.29	40.56	28.39	40.85	28.68	61.45	51.45	-20.60	-22.77
3	0.54453	0.26	40.08	34.26	40.34	34.52	56.00	46.00	-15.66	-11.48
4	2.41797	0.36	35.39	30.21	35.75	30.57	56.00	46.00	-20.25	-15.43
5	3.77344	0.44	36.66	31.45	37.10	31.89	56.00	46.00	-18.90	-14.11
6	12.91406	0.75	34.48	29.25	35.23	30.00	60.00	50.00	-24.77	-20.00

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18516	0.13	41.45	34.41	41.58	34.54	64.25	54.25	-22.68	-19.72
2	0.46641	0.14	33.65	32.38	33.79	32.52	56.58	46.58	-22.79	-14.06
3	0.65391	0.16	36.34	33.88	36.50	34.04	56.00	46.00	-19.50	-11.96
4	2.62109	0.26	33.73	32.87	33.99	33.13	56.00	46.00	-22.01	-12.87
<b>5</b>	<b>3.37109</b>	<b>0.30</b>	<b>36.12</b>	<b>34.55</b>	<b>36.42</b>	<b>34.85</b>	<b>56.00</b>	<b>46.00</b>	<b>-19.58</b>	<b>-11.15</b>
6	13.85938	0.84	27.79	27.21	28.63	28.05	60.00	50.00	-31.37	-21.95

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18516	0.14	40.73	33.95	40.87	34.09	64.25	54.25	-23.39	-20.17
2	0.65781	0.18	36.77	34.30	36.95	34.48	56.00	46.00	-19.05	-11.52
3	0.84531	0.19	33.80	28.92	33.99	29.11	56.00	46.00	-22.01	-16.89
4	2.62500	0.27	32.41	31.43	32.68	31.70	56.00	46.00	-23.32	-14.30
5	3.37500	0.31	32.57	30.73	32.88	31.04	56.00	46.00	-23.12	-14.96
6	14.35156	0.76	31.50	31.24	32.26	32.00	60.00	50.00	-27.74	-18.00

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

##### 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	10.13	10.14	0.5	Pass
6	2437	10.12	10.12	0.5	Pass
11	2462	10.12	10.11	0.5	Pass

##### 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.43	16.38	0.5	Pass
6	2437	16.36	16.36	0.5	Pass
11	2462	16.40	16.39	0.5	Pass

##### 802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	17.65	17.62	0.5	Pass
6	2437	17.55	16.72	0.5	Pass
11	2462	17.61	17.62	0.5	Pass


##### 802.11n (HT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.50	36.49	0.5	Pass
6	2437	36.42	36.40	0.5	Pass
9	2452	36.48	36.46	0.5	Pass


# Spectrum Plot of Worst Value

802.11b

802.11g




A D T




A D T

802.11n (HT20)

802.11n (HT40)



A D T



A D T



## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

Same as 4.3.6.

#### 4.4.7 Test Results

For Average Power

##### 802.11b

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.43	18.68	143.453	21.57	30	Pass
6	2437	19.26	18.63	157.279	21.97	30	Pass
11	2462	17.72	17.96	121.673	20.85	30	Pass

##### 802.11g

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	15.17	15.70	70.039	18.45	30	Pass
6	2437	26.01	25.08	<b>721.132</b>	28.58	30	Pass
11	2462	16.21	15.81	79.890	19.02	30	Pass

##### 802.11n (HT20)

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	13.56	14.08	48.285	16.84	30	Pass
6	2437	25.31	25.05	659.515	28.19	30	Pass
11	2462	16.16	15.90	80.210	19.04	30	Pass

##### 802.11n (HT40)


Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	9.61	10.16	19.516	12.90	30	Pass
6	2437	14.23	14.13	52.367	17.19	30	Pass
9	2452	10.58	10.01	21.452	13.31	30	Pass

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

#### For AVG. power (duty cycle $\geq 98\%$ )

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

#### For AVG. power (duty cycle $< 98\%$ )

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

Same as 4.3.6.

#### 4.5.7 Test Results

##### 802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass/Fail
0	1	2412	-10.92	3.01	-7.91	8	Pass
	6	2437	-9.99	3.01	-6.98	8	Pass
	11	2462	-11.26	3.01	-8.25	8	Pass
1	1	2412	-10.17	3.01	-7.16	8	Pass
	6	2437	-10.14	3.01	-7.13	8	Pass
	11	2462	-11.58	3.01	-8.57	8	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , therefore the limit no need to reduced.

##### 802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass/Fail
0	1	2412	-15.99	3.01	0.12	-12.86	8	Pass
	6	2437	-5.61	3.01	0.12	-2.48	8	Pass
	11	2462	-15.10	3.01	0.12	-11.97	8	Pass
1	1	2412	-14.60	3.01	0.12	-11.47	8	Pass
	6	2437	-5.16	3.01	0.12	-2.03	8	Pass
	11	2462	-15.07	3.01	0.12	-11.94	8	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , therefore the limit no need to reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (HT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass/Fail
0	1	2412	-18.10	3.01	0.13	-14.96	8	Pass
	6	2437	-6.33	3.01	0.13	-3.19	8	Pass
	11	2462	-15.61	3.01	0.13	-12.47	8	Pass
1	1	2412	-17.61	3.01	0.13	-14.47	8	Pass
	6	2437	-6.78	3.01	0.13	-3.64	8	Pass
	11	2462	-15.29	3.01	0.13	-12.15	8	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = 2dBi + 10log(2) = 5.01dBi < 6dBi, therefore the limit no need to reduced.
- Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (HT40)

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass/Fail
0	3	2422	-24.95	3.01	0.21	-21.73	8	Pass
	6	2437	-20.29	3.01	0.21	-17.07	8	Pass
	9	2452	-24.00	3.01	0.21	-20.78	8	Pass
1	3	2422	-24.20	3.01	0.21	-20.98	8	Pass
	6	2437	-20.05	3.01	0.21	-16.83	8	Pass
	9	2452	-24.80	3.01	0.21	-21.58	8	Pass


Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = 2dBi + 10log(2) = 5.01dBi < 6dBi, therefore the limit no need to reduced.
- Refer to section 3.3 for duty cycle spectrum plot.


# Spectrum Plot of Worst Value

802.11b

802.11g




A D T




A D T

802.11n (HT20)

802.11n (HT40)



A D T




A D T

## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = average.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition

Same as 4.3.6.


### 4.6.7 Test Results

The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

## 802.11b\_Chain 0

## CH 1




A D T




A D T

## CH 6




A D T




A D T

## CH 11




A D T




A D T

## CH 1 Band edge



A D T

## CH 11 Band edge




A D T




## 802.11b\_Chain 1

## CH 1




A D T




A D T

## CH 6




A D T




A D T

## CH 11




A D T




A D T

## CH 1 Band edge



A D T


## CH 11 Band edge




A D T

## 802.11g\_Chain 0


## CH 1



## CH 6




## CH 11




## CH 1 Band edge

## CH 11 Band edge




## 802.11g\_Chain 1


## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




# 802.11n (HT20)\_Chain 0


## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




## 802.11n (HT20)\_Chain 1


## CH 1




## CH 6




## CH 11



## CH 1 Band edge





## CH 11 Band edge





## 802.11n (HT40)\_Chain 0



## CH 3




## CH 6




## CH 9



## CH 3 Band edge





## CH 9 Band edge





## 802.11n (HT40)\_Chain 1



## CH 3





## CH 6




## CH 9



## CH 3 Band edge



## CH 9 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).



## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---