## FCC ID:ZHW-8044147

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \*  $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

## Bluetooth:

Transmit Frequency	Mode	Measured Power	Tune-up power	Max tune-up	Result	1g SAR
(GHz)		(dBm)	(dBm)	power(dBm)	calculation	
2.402	GFSK	3.60	4±1	5	0.9802	3
2.441		4.15	4±1	5	0.9881	3
2.48		4.36	4±1	5	0.9960	3
2.402	π/4-DQPSK	4.20	4±1	5	0.9802	3
2.441		4.72	4±1	5	0.9881	3
2.48		4.88	4±1	5	0.9960	3
2.402	8DPSK	4.13	4±1	5	0.9802	3
2.441		4.61	4±1	5	0.9881	3
2.48		4.80	4±1	5	0.9960	3

Conclusion:

For the max result :  $0.9960 \le 3.0$  for 1g SAR, No SAR is required.

Jason chen

Signature: Date: 2016-4-18

NAME AND TITLE (Please print or type): Jason Chen /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.