Report No.: 14A110606R-FR

FCC ID : ZJM-UMWWS IC ID : 2225A-UMWWS

# CFR 47 FCC Part 15.231

# Industry Canada RSS-210 TEST REPORT

Product: water sensor

Trade Name: N/A

Model Number: UM-WWS

FCC ID: ZJM-UMWWS

IC ID: 2225A-UMWWS

Prepared for

# **Condoplex Monitoring Systems Inc**

7-75 Horner Ave Etobicoke ON Canada M8Z 4X5

Prepared by

#### Interocean EMC Technology Corp.

No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City, Taiwan 244, R.O.C.

TEL.: +886 2 2600 6861 FAX.: +886 2 2600 6859

#### Remark:

The test report consists of <u>33</u> pages in total. It shall not be reproduced except in full, without the written approval of IETC. This document may be altered or revised by IETC only, and shall be noted in the revision section of the document.

The test result in the report is only subjected to the test sample.

Page 1 of 33

IC ID: 2225A-UMWWS Page 2 of 33

# **Statement of Compliance**

Applicant:	Condoplex Monitoring Sys	stems Inc
Manufacturer:	Nutek Corporation	
Product:	water sensor	
Model No.:	UM-WWS	
Tested Power Supply:	DC 9V	
Date of Final Test:	Nov. 20, 2014	
Revision of Report:	Rev. 01	
Configuration of Measu	rements and Standards U	sed:
FCC Rules and Regulation Industry Canada RSS-Ge Industry Canada RSS-210	n Issue 3	
_	report relate only to the ite not be reproduced expect i	m tested. n full, without the written approval of IETC
Report Issued:	2014/11/25	
Project Engineer:	311 chang	Approved: Lin

Elli Chang

Jerry Liu

Report No.: 14A110606R-FR FCC ID: ZJM-UMWWS IC ID: 2225A-UMWWS

Page 3 of 33

# **Table of Contents**

1	Sı	ummary of Measurement	4
2	Ge	eneral Information	5
	2.1	Description of Equipment Under Test	5
	2.2	Details of Tested Peripheral Equipment	6
	2.3	Test Facility	7
3	Te	est Specifications	8
	3.1	Test Standard	8
	3.2	Test Step of EUT	8
	3.3	Test Equipment	9
4	Ra	diated Emission Test	10
	4.1	Limits	10
	4.2	Calculation of Average Factor	11
	4.3	Configuration of Measurement	17
	4.4	Test Procedure	17
	4.5	Test Result	17
5	Em	nission Bandwidth	21
	5.1	Limits	21
	5.2	Test Result	21
6	999	% Occupied Bandwidth	23
	6.1	Limits	23
	6.2	Test Result	23
7	Ph	otographs of Test	25
	7.1	Radiated Emission Measurement	25
8	Ph	otographs of FUT	27

Report No.: 14A110606R-FR

FCC ID: ZJM-UMWWS

IC ID: 2225A-UMWWS Page 4 of 33

# 1 Summary of Measurement

Report Clause	lest Parameter	Reference	Results	
4	Timing Requirement	§FCC15.231(a)	RSS-210 A1.1.1	Pass
4	Radiated Emission	§FCC15.231(b), 15.209	RSS-210 A1.1.2	Pass
5	Emission Bandwidth	§FCC15.231(c)		Pass
6	99% Occupied Bandwidth		RSS-210 A1.1.3	Pass

FCC ID: ZJM-UMWWS

IC ID: 2225A-UMWWS Page 5 of 33

#### 2 **General Information**

Report No.: 14A110606R-FR

# **Description of Equipment Under Test**

**Product** : water sensor

**Model Number** : UM-WWS

**Applicant** : Condoplex Monitoring Systems Inc

7-75 Horner Ave Etobicoke ON Canada M8Z 4X5

Manufacturer : Nutek Corporation

No.167, Lane 235, Bauchiau Rd., Shindian City,

Taipei Country 23145, Taiwan

: DC 9V **Power Supply** 

Operating Frequency : 433.92MHz

Type of Modulation : ASK

**Antenna Description** : This device uses Helix antenna.

The antenna is integral to the device, thereby meeting the

requirement of FCC 15.203.

**Date of Test** : Nov. 07 ~ 20, 2014

Additional Description: 1) The Model Number "UM-WWS" is representative selected in

the test and included in this report.

2) For more detail specification about EUT, please refer to the

user's manual.

IC ID: 2225A-UMWWS Page 6 of 33

# 2.2 Details of Tested Peripheral Equipment

N/A

IC ID: 2225A-UMWWS Page 7 of 33

#### 2.3 Test Facility

Site Description : ⊠ OATS 1

Name of Firm : Interocean EMC Technology Corp.

Company web : http://www.ietc.com.tw

**Location**: No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,

Taiwan 244, R.O.C.

Site Filing : ● Federal Communication Commissions – USA

Registration No.: 96399 (OATS 1, 2, 3 & Chamber 3)

Designation No.: TW1020

Industry Canada (IC)

OUR FILE: 46405-4437

Registration No. (OATS 1): Site# 4437A-1 Registration No. (OATS 3): Site# 4437A-3 Registration No. (Chamber 3): Site# 4437A-5 Registration No. (OATS 5): Site# 4437A-6

Voluntary Control Council for Interference by Information

Technology Equipment (VCCI) – Japan

Member No.: 1349

Registration No. (Conducted Room): C-1094 Registration No. (Conducted Room): T-1562 Registration No. (OATS 1): R-1040; G-274

Registration No. (OATS 2): R-1041

Site Accreditation

Bureau of Standards and Metrology and Inspection (BSMI) –

Taiwan, R.O.C.

Accreditation No.:

SL2-IN-E-0026 for CNS13438 / CISPR 22 SL2-IN-E-0026 for CNS14757-2 / IEC 62040-2 SL2-R1-E-0026 for CNS13439 / CISPR 13 SL2-R2-E-0026 for CNS13439 / CISPR 13 SL2-A1-E-0026 for CNS13783-1 / CISPR 14-1

SL2-L1-E-0026 for CNS 14115 / CISPR 15

Taiwan Accreditation Foundation (TAF)

Accreditation No.: 1113

Vehicle Safety Certification Center (VSCC)

Approval No.: TW16-11-0

TüV NORD

Certificate No: TNTW0801R-04

Nemko

Authorisation No: AeLA 011 Authorisation No: ELA 181

IC ID: 2225A-UMWWS Page 8 of 33

# 3 Test Specifications

# 3.1 Test Standard

The EUT was performed according to FCC Part 15 Subpart C Section 15.231 and Industry Canada RSS-210 procedure and setup followed by ANSI C63.4, 2003 requirements.

# 3.2 Test Step of EUT

- 3.2.1 Setup the fixture to EUT for power supplying.
- 3.2.2 Turn on the power of all equipment.
- 3.2.3 Let the EUT continuous transmission. Executed the test.

FCC ID: ZJM-UMWWS
IC ID: 2225A-UMWWS
Page 9 of 33

IC ID · ZZZSA-OWWWWS

# 3.3 Test Equipment

Report No.: 14A110606R-FR

Instrument	Manufacturer	Model	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSP40	100478	2015/06/02
Preamplifier	Agilent	8449B	3008A01434	2015/05/07
Preamplifier	Agilent	83050A	3950A00225	2015/09/08
Horn Antenna	Schwarzbeck	BBHA 9120	9120D-583	2015/05/13
Horn Antenna	Schwarzbeck	BBHA 9170	213	2015/07/24
Cable	HARBOUR	27478LL142	CBL22	2015/01/01
EMI Test Receiver	Rohde & Schwarz	ESVS10	826148/011	2015/10/29
Biconical Antenna	Schwarzbeck	BBA 9106	VHA 9103-2418	2015/01/18
Log Antenna	Schwarzbeck	UHALP 9108 A	0738	2015/01/18
Pre-Amplifier	Agilent	8447D	2944A09703	2015/04/29
RF Cable	EMCI	EMC8D-NM-NM-25000	140105	2015/02/16
RF Cable	Mini-Circuits	CBL-3FL-NMNM	CBL56	2015/08/29
RF Cable	Insulated Wire	CBL59	CBL59	2015/01/22

Note: The above equipments are within the valid calibration period.

Page 10 of 33

# 4 Radiated Emission Test

#### 4.1 Limits

According to FCC 15.231(b) and RSS-210 Annex 1 requirement:

In addition to the provisions of §15.205, the field strength of emissions from intentional radiator operated under this section shall not exceed the following:

#### **Fundamental and harmonics emission limits**

Frequency	Field Strength	of Fundamental	Field Strength	of Harmonics
(MHz)	( μ V/m@3m) (dB μ V/m@3m)		( $\mu$ V/m @3m)	(dB $\mu$ V/m@3m)
433.92	10996	80.8	1099.6	60.8

#### **General Radiated Emission Limit**

Spurious Emission tested through until 10<sup>th</sup> harmonic. Radiated emissions, which fall in the restricted bands, as defined in §15.205 (a), comply with the radiated emission limits specified in §15.209 (a) and defined in RSS-Gen Table 3, comply with the radiated emission limits specified in RSS-Gen 7.2.5.

.

Frequency	15.209 Limits					
(MHz)	( μ V/m@3m)	(dB $\mu$ V/m @3m)				
30-88	100	40				
88-216	150	43.5				
216-960	200	46				
Above 960	500	54				

#### Remark:

- 1. The table above tighter limit applies at the band edges.
- 2. The measurement distance in meters, which that between form closest point of EUT to instrument antenna.

IC ID: 2225A-UMWWS Page 11 of 33

# 4.2 Calculation of Average Factor

The output field strengths of specification in accordance with the rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector. The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.

Averaging factor in dB =20 log (duty cycle)

The duration of one cycle = 105.84ms

The duty cycle is simply the on-time divided by 100ms

Duty Cycle = (0.8ms\*40+0.4\*38) = 47.2 ms / 100ms


Therefore, the averaging factor is found by  $20 \log 0.472 = -6.52 dB$ 

Please see the diagrams below.

Report No.: 14A110606R-FR FCC ID: ZJM-UMWWS IC ID: 2225A-UMWWS

IC ID: 2225A-UMWWS Page 12 of 33


# **Duty Cycle**




Report No.: 14A110606R-FR
FCC ID: ZJM-UMWWS
IC.ID: 2225A-LIMWWS

IC ID: 2225A-UMWWS Page 13 of 33


# **Time Slot**



Time Slot 1



Time Slot 2




Time Slot 3

Report No.: 14A110606R-FR FCC ID: ZJM-UMWWS IC: ID: 2225A-LIMWWS

IC ID: 2225A-UMWWS Page 16 of 33

The EUT was complied with the requirement of FCC 15.231 (a)(1) and RSS-210 Annex 1, which employed a switch that will automatically deactivate the transmitter within less than 5 seconds of being released.



FCC ID : ZJM-UMWWS
IC ID : 2225A-UMWWS
Page 17 of 33

# 4.3 Configuration of Measurement

Report No.: 14A110606R-FR

Measurement Frequency under 1GHz

RF Cable

A m

Test table & Turntable


RF Cable

Fre-Amplifier

Fre-Amplifier

Ground Plane

Measurement Frequency above 1GHz



#### 4.4 Test Procedure

Radiated emission measurements frequency range were performed from 30MHz to 5GHz. Spectrum Analyzer Resolution Bandwidth set to 100kHz or greater for frequencies from 30MHz to 1GHz, and set 1MHz Resolution Bandwidth for frequencies above 1GHz.

The EUT is place on non-conductive turntable for the test. If peripheral devices apply to the EUT, the peripheral devices will be connected to EUT and whole system. During the emission test, the signal is maximized through rotation and all cables were present worst-case emissions. The height of antenna and polarization is constantly changed for exploring maximum signal reading. The height of antenna can be up form reference ground to 4 meter and down to 1 meter.

#### 4.5 Test Result

#### PASS.

The final test emission data is shown as following tables.

IC ID: 2225A-UMWWS Page 18 of 33

# **Radiated Emission Below 1GHz**

Frequency	Antenna	Reading	Preamp	Correction Factor	Corrected Level	Limits	Margin	Det
(MHz)	Polarization	(dBuV)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	Mode
112.400	Н	41.54	29.84	13.33	25.03	43.52	-18.49	PK
160.560	Н	40.67	30.21	17.38	27.84	43.52	-15.68	PK
204.780	Н	35.78	29.94	19.80	25.64	43.52	-17.88	PK
288.420	Н	35.60	29.47	23.32	29.45	46.02	-16.57	PK
340.130	Н	39.53	29.40	18.49	28.62	46.02	-17.40	PK
450.790	Н	37.77	30.61	21.74	28.90	46.02	-17.12	PK
71.200	V	45.26	30.71	7.64	22.19	40.00	-17.81	PK
114.600	V	43.19	29.92	14.50	27.77	43.52	-15.75	PK
211.800	V	36.10	29.77	20.00	26.33	43.52	-17.19	PK
289.630	V	36.73	29.46	22.36	29.63	46.02	-16.39	PK
324.000	V	40.09	29.38	17.90	28.61	46.02	-17.41	PK
410.200	V	38.65	29.87	20.79	29.57	46.02	-16.45	PK

Remark : Corrected Level = Reading + Correction Factor - Preamp

Correction Factor = Antenna Factor + Cable Loss

Report No.: 14A110606R-FR FCC ID: ZJM-UMWWS IC ID: 2225A-UMWWS

Page 19 of 33

# **Fundamental and Harmonics Emissions**

Fundamental and Harmonics Emissions									
Freq.	Antenna	Reading	Preamp	Correction			Limits	Margin	Det
•			-	Factor	Factor	Level		_	
(MHz)	Polarization	,	(dB)	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
433.92	Н	59.86	0.00	21.30		81.16	100.8	-19.64	PK
433.92	Н	59.86	0.00	21.30	-6.52	74.64	80.8	-6.16	AV
867.84	Н	46.95	30.10	29.36		46.21	80.8	-34.59	PK
867.84	Н	46.95	30.10	29.36	-6.52	39.69	60.8	-21.11	AV
1301.76	Н	52.88	27.36	28.11		53.63	74.0	-20.37	PK
1301.76	Н	52.88	27.36	28.11	-6.52	47.11	54.0	-6.89	AV
1735.68	Н	49.90	27.67	29.31		51.54	80.8	-29.26	PK
1735.68	Н	49.90	27.67	29.31	-6.52	45.02	60.8	-15.78	AV
2169.60	Н	40.40	27.80	30.57		43.17	80.8	-37.63	PK
2169.60	Н	40.40	27.80	30.57	-6.52	36.65	60.8	-24.15	AV
2603.52	Н	41.90	27.83	32.14		46.21	80.8	-34.59	PK
2603.52	Н	41.90	27.83	32.14	-6.52	39.69	60.8	-21.11	AV
3037.44	Н	47.00	27.97	33.36		52.39	80.8	-28.41	PK
3037.44	Н	47.00	27.97	33.36	-6.52	45.87	60.8	-14.93	AV
3471.36	Н	46.57	27.79	33.68		52.46	80.8	-28.34	PK
3471.36	Н	46.57	27.79	33.68	-6.52	45.94	60.8	-14.86	AV
3905.28	Н	36.36	27.86	35.88		44.38	74.0	-29.62	PK
3905.28	Н	36.36	27.86	35.88	-6.52	37.86	54.0	-16.14	AV
4339.20	Н	35.40	27.61	36.53		44.32	74.0	-29.68	PK
4339.20	Н	35.40	27.61	36.53	-6.52	37.80	54.0	-16.20	AV
433.92	V	50.21	0.00	21.06		71.27	100.8	-29.53	PK
433.92	V	50.21	0.00	21.06	-6.52	64.75	80.8	-16.05	AV
867.84	V	40.72	30.10	28.94		39.56	80.8	-41.24	PK
867.84	V	40.72	30.10	28.94	-6.52	33.04	60.8	-27.76	AV
1301.76	V	45.54	27.36	28.11		46.29	74.0	-27.71	PK
1301.76	V	45.54	27.36	28.11	-6.52	39.77	54.0	-14.23	AV
1735.68	V	49.02	27.67	29.31		50.66	80.8	-30.14	PK
1735.68	V	49.02	27.67	29.31	-6.52	44.14	60.8	-16.66	AV
2169.60	V	37.88	27.80	30.57		40.65	80.8	-40.15	PK
2169.60	V	37.88	27.80	30.57	-6.52	34.13	60.8	-26.67	AV
2603.52	V	42.26	27.83	32.14		46.57	80.8	-34.23	PK
2603.52	V	42.26	27.83	32.14	-6.52	40.05	60.8	-20.75	AV
<u> </u>	ļ				<u> </u>		ļ		

IC ID: 2225A-UMWWS Page 20 of 33

3037.44	V	49.04	27.97	33.36		54.43	80.8	-26.37	PK
3037.44	V	49.04	27.97	33.36	-6.52	47.91	60.8	-12.89	AV
3471.36	V	50.00	27.79	33.68		55.89	80.8	-24.91	PK
3471.36	V	50.00	27.79	33.68	-6.52	49.37	60.8	-11.43	AV
3905.28	V	38.15	27.86	35.88		46.17	74.0	-27.83	PK
3905.28	V	38.15	27.86	35.88	-6.52	39.65	54.0	-14.35	AV
4339.20	V	35.80	27.61	36.53		44.72	74.0	-29.28	PK
4339.20	V	35.80	27.61	36.53	-6.52	38.20	54.0	-15.80	AV

Remark: 1. Corrected Level = Reading + Correction Factor – Preamp

- 2. Correction Factor = Antenna Factor + Cable Loss
- 3. " \* " Mark indicated Background Noise Level
- 4. The signal bandwidth was measured and less then 100KHz RBW so PDCF factor is not required to correct the fundamental signal peak result.

IC ID: 2225A-UMWWS Page 21 of 33

# 5 Emission Bandwidth

# 5.1 Limits

According to FCC 15.231(c) requirement:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating between 70 MHz to 900 MHz. Those devices operating above 900 MHz, the emission spurious shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

B.W (20dBc) Limit = 0.25% \* f(MHz) = 0.25% \* 433.92MHz = 1084.8kHz

#### 5.2 Test Result


#### PASS.

The final test data is shown as following.

FCC ID: ZJM-UMWWS
IC ID: 2225A-LIMWWS
Page 22 of 3

IC ID : 2225A-UMWWS Page 22 of 33

Channel Frequency (MHz)	Measured 20dB Bandwidth (kHz)	Limit (kHz)	Result
433.92	60	1084.8	PASS



Report No.: 14A110606R-FR

FCC ID: ZJM-UMWWS

IC ID: 2225A-UMWWS Page 23 of 33

# 6 99% Occupied Bandwidth

#### 6.1 Limits

Report No.: 14A110606R-FR

According to RSS-210 Annex 1 requirement:

The 99% bandwidth shall be no wider than 0.25% of the centre frequency for devices operating between 70 MHz and 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the centre frequency.

99% OBW Limit = 0.25% \* f(MHz) = 0.25% \* 433.92MHz = 1084.8kHz

# 6.2 Test Result


# PASS.

The final test data is shown as following.

FCC ID: ZJM-UMWWS

IC ID: 2225A-UMWWS Page 24 of 33

Channel Frequency (MHz)	Measured 99% Bandwidth (kHz)	Limit (kHz)	Result
433.92	84	1084.8	PASS



Report No.: 14A110606R-FR