

# FCC SAR Test Report

Product Name : GPS Controller(GPS Receiver)

Model No. : S Series-A

Applicant : BAP Precision Ltd.

Address : 6F., No.1-5, Ln. 1224, Zhongzheng Rd., Taoyuan City,  
Taoyuan County 330, Taiwan (R.O.C.)

Date of Receipt : 2015/03/03

Issued Date : 2015/05/20

Report No. : 1530073R-SAUSP02V00

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

# Test Report

Issued Date: 2015/05/20

Report No.: 1530073R-SAUSP02V00



Product Name : GPS Controller(GPS Receiver)  
Applicant : BAP Precision Ltd.  
Address : 6F., No.1-5, Ln. 1224, Zhongzheng Rd., Taoyuan City,  
Taoyuan County 330, Taiwan (R.O.C.)  
Manufacturer : Logwell Technology Co, Ltd.  
Model No. : S Series-A  
Trade Name : BAP  
FCC ID : ZK7SSERIES-A  
Applicable Standard : FCC Oet65 Supplement C June 2001  
47CFR § 2.1093  
Measurement : KDB 447498 D01 v05r02  
procedures : KDB 248227 D01 v02  
KDB 941225 D01 v03  
KDB 648474 D04 v01r01  
KDB 865664 D01 v01r03  
Test Result : Max. SAR Measurement (1g)  
**0.62** W/kg  
Application Type : Certification

Documented By :

*Anny Chou*

( Senior Adm. Specialist / Anny Chou )

Tested By :

*wenLee*

( Senior Engineer / Wen Lee )

Approved By :

*Vincent Lin*

( Director / Vincent Lin )

## TABLE OF CONTENTS

Description	Page
<b>1. General Information.....</b>	<b>4</b>
1.1 EUT Description .....	4
1.2 Antenna List.....	4
1.3 Test Environment .....	5
<b>2. SAR Measurement System .....</b>	<b>6</b>
2.1 DASY5 System Description .....	6
2.1.1 Applications .....	7
2.1.2 Area Scans.....	7
2.1.3 Zoom Scan (Cube Scan Averaging).....	7
2.1.4 Uncertainty of Inter-/Extrapolation and Averaging .....	7
2.2 DASY5 E-Field Probe .....	8
2.2.1 Isotropic E-Field Probe Specification .....	8
2.3 Boundary Detection Unit and Probe Mounting Device .....	9
2.4 DATA Acquisition Electronics (DAE) and Measurement Server .....	9
2.5 Robot.....	10
2.6 Light Beam Unit.....	10
2.7 Device Holder .....	11
2.8 SAM Twin Phantom .....	11
<b>3. Tissue Simulating Liquid .....</b>	<b>12</b>
3.1 The composition of the tissue simulating liquid .....	12
3.2 Tissue Calibration Result .....	12
3.3 Tissue Dielectric Parameters for Head and Body Phantoms .....	14
<b>4. SAR Measurement Procedure .....</b>	<b>15</b>
4.1 SAR System Check.....	15
4.1.1 Dipoles .....	15
4.1.2 System Check Result .....	16
4.2 SAR Measurement Procedure.....	17
<b>5. SAR Exposure Limits .....</b>	<b>18</b>
<b>6. Test Equipment List.....</b>	<b>19</b>
<b>7. Measurement Uncertainty .....</b>	<b>20</b>
<b>8. Conducted Power Measurement (Including tolerance allowed for production unit) .....</b>	<b>21</b>
<b>9. Test Results.....</b>	<b>24</b>
9.1 SAR Test Results Summary .....	24
9.2 Simultaneous Transmission .....	30
<b>10. SAR measurement variability .....</b>	<b>31</b>
Appendix.....	32
Appendix A. SAR System Check Data	
Appendix B. SAR measurement Data	
Appendix C. Test Setup Photographs & EUT Photographs	
Appendix D. Probe Calibration Data	
Appendix E. Dipole Calibration Data	

## 1. General Information

### 1.1 EUT Description

Product Name	GPS Controller(GPS Receiver)
Trade Name	BAP
Model No.	S Series-A
FCC ID(WLAN)	ZK7SSERIES-A
Contain FCC ID (WWAN)	ZK7MSERIES
TX Frequency	GSM 850/WCDMA Band V : 824 ~ 849MHz PCS 1900/WCDMA Band II : 1850 ~ 1910MHz WCDMA Band IV : 1710 ~ 1755MHz 802.11b/g/n-20BW : 2412 ~2462MHz
RX Frequency	GSM 850/WCDMA Band V : 869 ~ 894MHz PCS 1900/WCDMA Band II : 1930 ~ 1990MHz WCDMA Band IV : 2110 ~ 2155MHz 802.11b/g/n-20BW : 2412 ~2462MHz
Type of Modulation	WWAN : GMSK/8PSK/QPSK WLAN :DSSS/OFDM/BPSK/QPSK/16QAM/64QAM
Antenna Type	Linear Polarization
Device Category	Portable
RF Exposure Environment	Uncontrolled
Max. Output Power (Conducted)	GSM 850 :32.94dBm; GSM 1900 : 28.95dBm WCDMA Band II :23.54dBm; WCDMA Band IV : 32.69dBm WCDMA Band V : 23.08dBm 802.11b/g/n: 12.35 dBm
Power Adapter	MFR: TOUCH, M/N: SP9715-A Input: 100-240V ~ 0.6A, 50-60Hz Output: 5V==2A Cable Out: Non-Shielded, 1.8m

Note : (1) Per FCC KDB 447498 D01.The output power of BT is less than 10mW, so SAR not required.

(2) WWAN & WLAN can't work simultaneously, thus simultaneous mode is no need.

### 1.2 Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	cirocomm	86X	1.75 dBi for WLAN 0.88 dBi for WWAN

### 1.3 Test Environment

Ambient conditions in the laboratory:

Test Date: Mar. 10, 2015

Items	Required	Actual
Temperature (°C)	18-25	20.7 ± 2
Humidity (%RH)	30-70	51

Test Date: Mar. 11, 2015

Items	Required	Actual
Temperature (°C)	18-25	21.3 ± 2
Humidity (%RH)	30-70	55

Test Date: Mar. 12, 2015

Items	Required	Actual
Temperature (°C)	18-25	20.3 ± 2
Humidity (%RH)	30-70	53

Test Date: Apr. 15, 2015

Items	Required	Actual
Temperature (°C)	18-25	22.0 ± 2
Humidity (%RH)	30-70	49

Site Description:


Accredited by TAF  
Accredited Number: 3023  
Effective through: December 12, 2017

Site Name: Quietek Corporation

Site Address: No.5-22, Ruishukeng, Linkou Dist.,  
New Taipei City 24451,  
Taiwan, R.O.C.  
TEL: 886-2-8601-3788 / FAX: 886-2-8601-3789  
E-Mail: [service@quietek.com](mailto:service@quietek.com)

## 2. SAR Measurement System

### 2.1 DASY5 System Description



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

### **2.1.1 Applications**

Predefined procedures and evaluations for automated compliance testing with all worldwide standards, e.g., IEEE 1528, OET 65, IEC 62209-1, IEC 62209-2, EN 50360, EN 50383 and others.

### **2.1.2 Area Scans**

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm<sup>2</sup> step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2003, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan).

### **2.1.3 Zoom Scan (Cube Scan Averaging)**

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. A density of 1000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x7 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 30mm in the Z axis.

### **2.1.4 Uncertainty of Inter-/Extrapolation and Averaging**

In order to evaluate the uncertainty of the interpolation, extrapolation and averaged SAR calculation algorithms of the Postprocessor, DASY5 allows the generation of measurement grids which are artificially predefined by analytically based test functions. Therefore, the grids of area scans and zoom scans can be filled with uncertainty test data, according to the SAR benchmark functions of IEEE 1528. The three analytical functions shown in equations as below are used to describe the possible range of the expected SAR distributions for the tested handsets. The field gradients are covered by the spatially flat

distribution f1, the spatially steep distribution f3 and f2 accounts for H-field cancellation on the phantom/tissue surface.

$$f_1(x, y, z) = Ae^{-\frac{z}{2a}} \cos^2 \left( \frac{\pi}{2} \frac{\sqrt{x'^2 + y'^2}}{5a} \right)$$

$$f_2(x, y, z) = Ae^{-\frac{z}{a}} \frac{a^2}{a^2 + x'^2} \left( 3 - e^{-\frac{2z}{a}} \right) \cos^2 \left( \frac{\pi}{2} \frac{y'}{3a} \right)$$


$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \left( e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

## 2.2 DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO 17025. The calibration data are in Appendix D.

### 2.2.1 Isotropic E-Field Probe Specification

Model	Ex3DV4	
Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)	
Directivity	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.	



## 2.3 Boundary Detection Unit and Probe Mounting Device

The DASY probes use a precise connector and an additional holder for the probe, consisting of a plastic tube and a flexible silicon ring to center the probe. The connector at the DAE is flexibly mounted and held in the default position with magnets and springs. Two switching systems in the connector mount detect frontal and lateral probe collisions and trigger the necessary software response.



## 2.4 DATA Acquisition Electronics (DAE) and Measurement Server

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit.

Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE4 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chipdisk and 128MB RAM. The necessary circuits for communication with the DAE electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.



## 2.5 Robot

The DASY5 system uses the high precision robots TX90 XL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY5 system, the CS8C robot controller version from Stäubli is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller



## 2.6 Light Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



## 2.7 Device Holder

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon_r = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



## 2.8 SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

### 3. Tissue Simulating Liquid

#### 3.1 The composition of the tissue simulating liquid

INGREDIENT (% Weight)	835MHz Body	1800MHz Body	1900MHz Body	2450MHz Body
<b>Water</b>	52.4	52.64	40.5	73.2
<b>Salt</b>	1.40	0.36	0.50	0.04
<b>Sugar</b>	45.0	0.00	58.0	0
<b>HEC</b>	1.00	0.00	0.50	0
<b>Preventol</b>	0.20	0.00	0.50	0
<b>DGBE</b>	0.00	47	0.00	26.76

#### 3.2 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using APREL Dielectric Probe Kit and Agilent E5071C Vector Network Analyzer.

Body Tissue Simulate Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		$\epsilon_r$	$\sigma$ [s/m]	
835 MHz	Reference result ± 5% window	55.2 52.44 to 57.96	0.99 0.9405 to 1.0395	N/A
	10-Mar-15	56.41	0.98	19.8
824.2 MHz	Low channel	56.63	0.96	19.8
836.4 MHz	Mid channel	56.36	0.98	19.8
848.8 MHz	High channel	56.18	0.99	19.8

Body Tissue Simulate Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		$\epsilon_r$	$\sigma$ [s/m]	
1800 MHz	Reference result ± 5% window	53.5 50.64 to 55.97	1.52 1.444 to 1.596	N/A
	12-Mar-15	53.02	1.56	19.2
1712.4 MHz	Low channel	53.51	1.47	19.2
1732.6 MHz	Mid channel	53.39	1.49	19.2
1752.6 MHz	High channel	53.28	1.51	19.2

Body Tissue Simulate Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		$\epsilon_r$	$\sigma$ [s/m]	
1900 MHz	Reference result ± 5% window	53.3 50.635 to 55.965	1.52 1.444 to 1.596	N/A
	11-Mar-15	54.32	1.51	20.1
1850.2 MHz	Low channel	55.02	1.47	20.1
1880 MHz	Mid channel	54.59	1.49	20.1
1909.8 MHz	High channel	54.16	1.52	20.1

Body Tissue Simulate Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		$\epsilon_r$	$\sigma$ [s/m]	
2450 MHz	Reference result ± 5% window	52.7 50.065 to 55.335	1.95 1.8525 to 2.0475	N/A
	15-Apr-15	53.42	1.96	20.9
2412 MHz	Low channel	53.89	1.92	20.9
2437 MHz	Mid channel	53.67	1.95	20.9
2462 MHz	High channel	53.35	1.98	20.9

### 3.3 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.


Target Frequency	Head		Body	
(MHz)	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

## 4. SAR Measurement Procedure

### 4.1 SAR System Check

#### 4.1.1 Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
900MHz	152.0	83.4	3.6
1800MHz	74.0	41.7	3.6
1900MHz	68.0	39.5	3.6
2450MHz	53.5	30.4	3.6

#### 4.1.2 System Check Result

##### System Performance Check at 835MHz, 1800MHz, 1900MHz and 2450MHz

##### Dipole Kit: ASL-D-835

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
835 MHz	Reference result ± 10% window	9.80 8.82 to 10.78	6.40 5.76 to 7.04	N/A
	10-Mar-15	9.20	6.00	19.8

##### Dipole Kit: ASL-D-1800

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
1800 MHz	Reference result ± 10% window	38.20 34.38 to 42.02	20.20 18.18 to 22.22	N/A
	12-Mar-15	35.84	18.72	19.2

##### Dipole Kit: ASL-D-1900

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
1900 MHz	Reference result ± 10% window	40.80 36.72 to 44.88	21.60 19.44 to 23.76	N/A
	11-Mar-15	38.20	19.56	20.1

##### Dipole Kit: D2450V2

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
2450 MHz	Reference result ± 10% window	53.2 47.88 to 58.52	24.36 21.92 to 26.80	N/A
	15-Apr-15	48.4	22.2	20.9

Note: (1) The power level is used 250mW  
 (2) All SAR values are normalized to 1W forward power.  
 (3) The reference result is from Appendix E.



## 4.2 SAR Measurement Procedure

The Dasy5 calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

$\sigma$ : represents the simulated tissue conductivity

$\rho$ : represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm<sup>2</sup>) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm<sup>3</sup>).

## 5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 “Uncontrolled Environments” limits. These limits apply to a location which is deemed as “Uncontrolled Environment” which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

**Limits for General Population/Uncontrolled Exposure (W/kg)**

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	<b>1.60 W/kg</b>
Spatial Average SAR (whole body)	<b>0.08 W/kg</b>
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	<b>4.00 W/kg</b>

## 6. Test Equipment List

Instrument	Manufacturer	Model No.	Serial No.	Last Calibration	Next Calibration
Stäubli Robot TX60L	Stäubli	TX60L	F09/5BL1A1/A06	2009/05/18	only once
Controller	Speag	CS8c	N/A	2009/05/18	only once
Reference Dipole 835Mhz	Apriel	ALS-D-835	QTK-315	2014/05/16	2016/05/15
Reference Dipole 1800MHz	Apriel	ALS-D-1800	317	2014/05/19	2016/05/18
Reference Dipole 1900MHz	Apriel	ALS-D1900	318	2014/05/19	2016/05/18
Reference Dipole 2450MHz	Apriel	D2450V2	930	2014/11/19	2016/11/18
SAM Twin Phantom	Speag	QD000 P40 CA	Tp 1515	N/A	N/A
Device Holder	Speag	N/A	N/A	N/A	N/A
Data Acquisition Electronic	Speag	DAE4	1425	2014/11/13	2015/11/12
E-Field Probe	Speag	EX3DV4	3979	2014/11/21	2015/11/20
SAR Software	Speag	DASY52	V52.8 (8)	N/A	N/A
Apriel Dipole Spaccer	Apriel	ALS-DS-U	QTK-295	N/A	N/A
Power Amplifier	Mini-Circuit	ZHL-42	D051404-20	N/A	N/A
Directional Coupler	Agilent	778D-012	50550	N/A	N/A
Universal Radio Communication Tester	R&S	CMU200	104846	2014/06/05	2015/06/04
Vector Network	Agilent	E5071C	MY46108013	2015/03/30	2016/03/28
Signal Generator	Anritsu	MG3694A	041902	2014/08/06	2015/08/05
Power Meter	Anritsu	ML2495A	143004	2014/09/05	2015/09/04
Wide Bandwidth Sensor	Anritsu	MA2411B	1339194	2014/09/12	2015/09/11

## 7. Measurement Uncertainty

<b>DASY5 Uncertainty</b>								
Measurement uncertainty for 300 MHz to 3 GHz averaged over 1 gram / 10 gram.								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) V <sub>eff</sub>
<b>Measurement System</b>								
Probe Calibration	±6.0%	N	1	1	1	±6.0%	±6.0%	∞
Axial Isotropy	±4.7%	R	$\sqrt{3}$	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	$\sqrt{3}$	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	$\sqrt{3}$	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Readout Electronics	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response Time	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	$\sqrt{3}$	1	1	±1.5%	±1.5%	∞
RF Ambient Noise	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
RF Ambient Reflections	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	$\sqrt{3}$	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Max. SAR Eval.	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
<b>Test Sample Related</b>								
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9%	±2.9%	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	±4.0%	R	$\sqrt{3}$	1	1	±2.3%	±2.3%	∞
Liquid Conductivity (target)	±5.0%	R	$\sqrt{3}$	0.64	0.43	±1.8%	±1.2%	∞
Liquid Conductivity (meas.)	±2.5%	N	1	0.64	0.43	±1.6%	±1.1%	∞
Liquid Permittivity (target)	±5.0%	R	$\sqrt{3}$	0.6	0.49	±1.7%	±1.4%	∞
Liquid Permittivity (meas.)	±2.5%	N	1	0.6	0.49	±1.5%	±1.2%	∞
<b>Combined Std. Uncertainty</b>						±11%	±10.8%	387
<b>Expanded STD Uncertainty</b>						±22%	±21.5%	

## 8. Conducted Power Measurement (Including tolerance allowed for production unit)

### 8.1 Output power Measurement- GSM

Mode	Band	Channel	GMSK(CS1)				8PSK(MCS5)			
			Target (+Tolerance)	GPRS 1Slot (dBm)	Target (+Tolerance)	GPRS 2Slot (dBm)	Target (+Tolerance)	EGPRS 1Slot (dBm)	Target (+Tolerance)	EGPRS 2Slot (dBm)
average power	850	128	33.5	32.59	30.5	29.18	27	26.43	24	23.34
		189	33.5	32.94	30.5	29.19	27	26.44	24	23.32
		251	33.5	32.89	30.5	28.92	27	26.48	24	23.38
	1900	512	31	28.95	26	25.37	26.5	24.61	22	21.56
		661	31	28.71	26	25.01	26.5	24.2	22	21.18
		810	31	28.56	26	24.98	26.5	24.23	22	21.04
Source-base time average power	850	128	24.47	23.56	24.48	23.16	17.97	17.4	17.98	17.32
		189	24.47	23.91	24.48	23.17	17.97	17.41	17.98	17.3
		251	24.47	23.86	24.48	22.9	17.97	17.45	17.98	17.36
	1900	512	21.97	19.92	19.98	19.35	17.47	15.58	15.98	15.54
		661	21.97	19.68	19.98	18.99	17.47	15.17	15.98	15.16
		810	21.97	19.53	19.98	18.96	17.47	15.2	15.98	15.02

## 8.2 Output power Measurement - WCDMA

Band	Channel	Target (+Tolerance)	Voice /RMC	HSDPA				HSUPA				
				Set1	Set2	Set3	Set4	Set1	Set2	Set3	Set4	Set5
				Output Power(dBm)								
II	9262	23.5	22.76	23.21	22.92	21.93	22.25	22.24	21.2	21.9	21.32	22.44
II	9400	23.5	23.12	23.41	22.61	21.82	21.67	22.09	20.33	21.12	20.99	22.91
II	9538	23.5	22.88	23.54	22.75	22.28	22.26	22.55	21.23	21.8	20.84	22.63
IV	1312	24.0	23.43	23.12	20.92	20.47	21.46	23.38	22.02	22.73	22.42	23.27
IV	1413	24.0	23.69	22.52	21.19	21.17	21.37	22.83	21.51	22.42	22.16	23.46
IV	1513	24.0	23.68	22.75	21.41	21.03	21.09	23.35	21.87	22.01	21.82	23.04
V	4132	23.5	22.77	22.4	21.68	20.67	21.07	21.79	20.81	20.92	20.78	21.93
V	4183	23.5	22.95	22.4	21.81	20.91	20.77	21.41	20.36	20.43	20.43	21.55
V	4233	23.5	23.08	22.47	21.85	20.98	20.85	21.19	20.52	20.6	20.6	20.92
$\beta_c$				2	12	15	15	11	6	15	2	15
$\beta_d$				15	15	8	4	15	15	9	15	15
$\Delta ACK, \Delta NACK, \Delta CQI$				8	8	8	8	8	8	8	8	8
AGV				--	--	--	--	20	12	15	17	21
MPR				0	0	0.5	0.5	0	2	1	2	0

### 8.3 Output power Measurement - WIFI

Test Mode	Channel No.	Frequency (MHz)	Target (+Tolerance)	Average Power (dBm)
802.11b	01	2412	12.5	12.35
	06	2437	12.5	11.13
	11	2462	12.5	10.51
802.11g	01	2412	12.5	11.36
	06	2437	12.5	10.75
	11	2462	12.5	10.17
802.11n(20M)	01	2412	11	9.72
	06	2437	11	9.01
	11	2462	11	8.91

## 9. Test Results

### 9.1 SAR Test Results Summary

SAR MEASUREMENT								
Ambient Temperature (°C) : 20.7 ±2					Relative Humidity (%): 51			
Liquid Temperature (°C) : 19.8 ±2					Depth of Liquid (cm):>15			
Test Mode: GSM 850 (GPRS 1UP)								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Front	Fixed	189	836.4	32.94	33.50	0.412	0.469	1.6
Back	Fixed	189	836.4	32.94	33.50	0.422	0.480	1.6
Test Mode: GSM 850 (GPRS 2UP)								
Back	Fixed	128	824.2	29.18	30.5	0.428	0.580	1.6
Back	Fixed	189	836.4	29.19	30.5	0.431	0.583	1.6
Back	Fixed	251	848.8	28.92	30.5	0.407	0.586	1.6
Test Mode: GSM 850 (EGPRS 2UP)								
Back	Fixed	189	836.4	23.32	24	0.101	0.118	1.6
Note : Test distance between the phantom is 10mm .								



SAR MEASUREMENT								
Ambient Temperature (°C) : 21.3 ±2					Relative Humidity (%): 55			
Liquid Temperature (°C) : 20.1 ±2					Depth of Liquid (cm):>15			
Test Mode: PCS 1900 (GPRS 1UP)								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Front	Fixed	661	1880	28.71	31	0.110	0.186	1.6
Back	Fixed	661	1880	28.71	31	0.081	0.137	1.6
Test Mode: PCS 1900 (GPRS 2UP)								
Front	Fixed	512	1850.2	25.37	26	0.164	0.190	1.6
Front	Fixed	661	1880	25.01	26	0.115	0.144	1.6
Front	Fixed	810	1909.8	24.98	26	0.106	0.134	1.6
Test Mode: PCS 1900 (EGPRS 2UP)								
Front	Fixed	512	1850.2	21.18	22	0.062	0.075	1.6
Note : Test distance between the phantom is 10mm .								

SAR MEASUREMENT								
Ambient Temperature (°C) : 21.3 ±2					Relative Humidity (%): 55			
Liquid Temperature (°C) : 20.1 ±2					Depth of Liquid (cm):>15			
Test Mode: WCDMA RMC Band 2								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Front	Fixed	9262	1852.4	22.76	23.5	0.224	0.266	1.6
Front	Fixed	9400	1880	23.12	23.5	0.252	0.275	1.6
Front	Fixed	9538	1907.6	22.88	23.5	0.326	0.376	1.6
Back	Fixed	9400	1880	23.12	23.5	0.195	0.213	1.6
Test Mode: WCDMA HSDPA Band 2								
Front	Fixed	9400	1880	23.41	23.5	0.226	0.231	1.6
Test Mode: WCDMA HSUPA Band 2								
Front	Fixed	9400	1880	22.91	23.5	0.266	0.305	1.6
Note : Test distance between the phantom is 10mm .								

SAR MEASUREMENT								
Ambient Temperature (°C) : 20.3 ±2					Relative Humidity (%): 53			
Liquid Temperature (°C) : 19.2 ±2					Depth of Liquid (cm):>15			
Test Mode: WCDMA RMC Band 4								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Front	Fixed	1312	1712.4	23.43	24.0	0.187	0.213	1.6
Front	Fixed	1413	1732.6	23.69	24.0	0.185	0.199	1.6
Front	Fixed	1513	1752.6	23.68	24.0	0.245	0.264	1.6
Back	Fixed	1413	1732.6	23.69	24.0	0.105	0.113	1.6
Test Mode: WCDMA HSDPA Band 4								
Front	Fixed	1413	1732.6	22.52	24.0	0.184	0.259	1.6
Test Mode: WCDMA HSUPA Band 4								
Front	Fixed	1413	1732.6	23.46	24.0	0.182	0.206	1.6
Note : Test distance between the phantom is 10mm .								

SAR MEASUREMENT								
Ambient Temperature (°C) : 20.7 ±2					Relative Humidity (%): 51			
Liquid Temperature (°C) : 19.8 ±2					Depth of Liquid (cm):>15			
Test Mode: WCDMA RMC Band 5								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Front	Fixed	4183	836.6	23.69	23.5	0.440	0.421	1.6
Back	Fixed	4132	826.4	23.43	23.5	0.408	0.415	1.6
Back	Fixed	4183	836.6	23.69	23.5	0.479	0.458	1.6
Back	Fixed	4233	846.6	23.68	23.5	0.381	0.366	1.6
Test Mode: WCDMA HSDPA Band 5								
Back	Fixed	4183	836.6	22.40	23.5	0.398	0.513	1.6
Test Mode: WCDMA HSUPA Band 5								
Back	Fixed	4183	836.6	21.55	23.5	0.398	0.624	1.6
Note : Test distance between the phantom is 10mm .								

SAR MEASUREMENT								
Ambient Temperature (°C) : 22.0 ±2					Relative Humidity (%): 49			
Liquid Temperature (°C) : 20.9 ±2					Depth of Liquid (cm):>15			
Test Mode: 802.11b - 2450 MHz								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Front	Fixed	6	2437	11.13	12.5	0.045	0.062	1.6
Back	Fixed	1	2412	12.35	12.5	0.125	0.129	1.6
Back	Fixed	6	2437	11.13	12.5	0.167	0.229	1.6
Back	Fixed	11	2462	10.51	12.5	0.135	0.213	1.6
Note : (1)Test distance between the phantom is 10mm .								
(2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required								

## 9.2 Simultaneous Transmission

According the KDB 447498 D01 Section 4.3.2, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion

$$(max. power of channel, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f(GHz)}/7.5]$$

Frequency	Max. power (dBm)	Test separation distance ,(mm)	Estimated BT SAR (W/Kg)
2480	-14.81	100	0.00

When the sum of SAR is larger than the limit, The ratio is determined by  $(SAR1 + SAR2)^{1.5/R_i}$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion . The estimation result as below :

**For DTS Band :**

WLAN SAR (W/Kg)	Estimated BT SAR (W/Kg)	Simultaneous Transmission (W/Kg)	Antenna pair in mm	Peak location separation ratio
0.229	0.00	0.229	N/A	N/A

The sum of value is less than 1.6W/Kg, thus simultaneous SAR testing is no need.

## 10. SAR measurement variability

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

Frequency		SAR 1g (W/kg)						
Channel	MHz	Original	First Repeated		Second Repeated		Third Repeated	
			Value	Ratio	Value	Ratio	Value	Ratio
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

## **Appendix**

**Appendix A. SAR System Check Data**

**Appendix B. SAR measurement Data**

**Appendix C. Test Setup Photographs & EUT Photographs**

**Appendix D. Probe Calibration Data**

**Appendix E. Dipole Calibration Data**



## Appendix A. SAR System Check Data

Test Laboratory: QuieTek

Date/Time: 2015/3/10

### SystemPerformanceCheck-835MHz\_Body

**DUT: Dipole 835 MHz; Type: ALS-D-835**

Communication System: UID 10000, CW; Frequency: 835 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.98 \text{ S/m}$ ;  $\epsilon_r = 56.41$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient Temperature ( $^{\circ}\text{C}$ ) : 20.7, Liquid Temperature ( $^{\circ}\text{C}$ ) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/835MHz\_Body/Area Scan (7x9x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.49 W/kg

### Configuration/835MHz\_Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:


Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 52.12 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.48 W/kg

**SAR(1 g) = 2.3 W/kg; SAR(10 g) = 1.5 W/kg**

Maximum value of SAR (measured) = 2.70 W/kg.



Test Laboratory: QuieTek

Date/Time: 2015/3/12

### System Performance Check\_1800MHz-Body

**DUT: Dipole 1800 MHz; Type: ALS-D-1800**

Communication System: UID 10000, CW; Frequency: 1800 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.56$  S/m;  $\epsilon_r = 53.02$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.64, 7.64, 7.64); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/1800MHz\_Body/Area Scan (7x7x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 11.3 W/kg

### Configuration/1800MHz\_Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 79.38 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 16.3 W/kg

**SAR(1 g) = 8.96 W/kg; SAR(10 g) = 4.68 W/kg**

Maximum value of SAR (measured) = 11.2 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/11

### System Performance Check\_1900MHz-Body

**DUT: Dipole 1900 MHz; Type: ALS-D-1900**

Communication System: UID 10000, CW; Frequency: 1900 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.51$  S/m;  $\epsilon_r = 54.32$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/1900MHz\_Body/Area Scan (8x7x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 10.0 W/kg

### Configuration/1900MHz\_Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 88.83 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 18.0 W/kg

**SAR(1 g) = 9.55 W/kg; SAR(10 g) = 4.88 W/kg**

Maximum value of SAR (measured) = 11.7 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/4/15

### System Performance Check\_2450MHz-Body

**DUT: Dipole 2450 MHz; Type: D2450V2**

Communication System: UID 10000, CW; Frequency: 2450 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.96$  S/m;  $\epsilon_r = 53.42$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 22.0, Liquid Temperature (°C) : 20.9

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/2450MHz\_Body/Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 15.8 W/kg

### Configuration/2450MHz\_Body/Zoom Scan (7x7x7) (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 89.41 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 25.3 W/kg

**SAR(1 g) = 12.1 W/kg; SAR(10 g) = 5.55 W/kg**

Maximum value of SAR (measured) = 17.2 W/kg



## Appendix B. SAR measurement Data

Test Laboratory: QuieTek

Date/Time: 2015/3/10

### GSM 850 GPRS 1UP\_Front 10mm-189

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC GSM\_850MHz; Frequency: 836.4 MHz;

Communication System PAR: 9.191 dB

Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.36$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.455 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.09 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.529 W/kg

**SAR(1 g) = 0.412 W/kg; SAR(10 g) = 0.314 W/kg**

Maximum value of SAR (measured) = 0.451 W/kg





Test Laboratory: QuieTek

Date/Time: 2015/3/10

**GSM 850 GPRS 1UP\_Back 10mm-189**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC GSM\_850MHz; Frequency: 836.4 MHz;

Communication System PAR: 9.191 dB

Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.36$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.466 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm  
Reference Value = 21.97 V/m; Power Drift = -0.12 dB  
Peak SAR (extrapolated) = 0.562 W/kg  
**SAR(1 g) = 0.422 W/kg; SAR(10 g) = 0.310 W/kg**  
Maximum value of SAR (measured) = 0.472 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/10

**GSM 850 GPRS 2UP\_Back 10mm-128**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC GSM\_850MHz\_GPRS&EGPRS-2 Slot; Frequency: 824.2 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 824.2$  MHz;  $\sigma = 0.96$  S/m;  $\epsilon_r = 56.63$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.471 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.10 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.567 W/kg

**SAR(1 g) = 0.428 W/kg; SAR(10 g) = 0.315 W/kg**

Maximum value of SAR (measured) = 0.478 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/10

**GSM 850 GPRS 2UP\_Back 10mm-189**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC GSM\_850MHz\_GPRS&EGPRS-2 Slot; Frequency: 836.4 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.36$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.479 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.09 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.570 W/kg

**SAR(1 g) = 0.431 W/kg; SAR(10 g) = 0.317 W/kg**

Maximum value of SAR (measured) = 0.481 W/kg





Test Laboratory: QuieTek

Date/Time: 2015/3/10

**GSM 850 GPRS 2UP\_Back 10mm-251**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC GSM\_850MHz\_GPRS&EGPRS-2 Slot; Frequency: 848.8 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 848.8$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 56.18$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.453 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.54 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.536 W/kg

**SAR(1 g) = 0.407 W/kg; SAR(10 g) = 0.299 W/kg**

Maximum value of SAR (measured) = 0.453 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/10

### GSM 850 EGPRS 2UP\_Back 10mm-189

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC GSM\_850MHz\_GPRS&EGPRS-2 Slot; Frequency: 836.4 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.36$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.108 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.55 V/m; Power Drift = 0.09 dB


Peak SAR (extrapolated) = 0.132 W/kg

**SAR(1 g) = 0.101 W/kg; SAR(10 g) = 0.074 W/kg**

Maximum value of SAR (measured) = 0.113 W/kg



**GSM 850 EUT Back (GPRS 2UP 10mm) Z-Axis plot**  
**Channel: 189**



Test Laboratory: QuiteTek

Date/Time: 2015/3/11

**PCS 1900 GPRS 1UP\_Front 10mm-661**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC PCS\_1900MHz; Frequency: 1880 MHz;

Communication System PAR: 9.191 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.123 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.251 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.171 W/kg

**SAR(1 g) = 0.110 W/kg; SAR(10 g) = 0.070 W/kg**

Maximum value of SAR (measured) = 0.129 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/11

### PCS 1900 GPRS 1UP\_Back 10mm-661

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC PCS\_1900MHz; Frequency: 1880 MHz;

Communication System PAR: 9.191 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0905 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.950 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.128 W/kg

**SAR(1 g) = 0.081 W/kg; SAR(10 g) = 0.050 W/kg**

Maximum value of SAR (measured) = 0.0954 W/kg





Test Laboratory: QuieTek

Date/Time: 2015/3/11

**PCS 1900 GPRS 2UP\_Front 10mm-512**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC PCS\_1900MHz\_GPRS&EGPRS-2 Slot; Frequency: 1850.2 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.47$  S/m;  $\epsilon_r = 55.02$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.187 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.185 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.249 W/kg

**SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.105 W/kg**

Maximum value of SAR (measured) = 0.191 W/kg



Test Laboratory: QuiteTek

Date/Time: 2015/3/11

**PCS 1900 GPRS 2UP\_Front 10mm-661**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC PCS\_1900MHz\_GPRS&EGPRS-2 Slot; Frequency: 1880 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.133 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.459 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.181 W/kg

**SAR(1 g) = 0.115 W/kg; SAR(10 g) = 0.074 W/kg**

Maximum value of SAR (measured) = 0.135 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/11

**PCS 1900 GPRS 2UP\_Front 10mm-810**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC PCS\_1900MHz\_GPRS&EGPRS-2 Slot; Frequency: 1909.8 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 1909.8$  MHz;  $\sigma = 1.52$  S/m;  $\epsilon_r = 54.16$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.122 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.149 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.165 W/kg

**SAR(1 g) = 0.106 W/kg; SAR(10 g) = 0.067 W/kg**

Maximum value of SAR (measured) = 0.124 W/kg





Test Laboratory: QuiteTek

Date/Time: 2015/3/11

**PCS 1900 EGPRS 2UP\_Front 10mm-512**

**DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC PCS\_1900MHz\_GPRS&EGPRS-2 Slot; Frequency: 1850.2 MHz;

Communication System PAR: 6.128 dB

Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.47$  S/m;  $\epsilon_r = 55.02$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.0722 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.064 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 0.0990 W/kg

**SAR(1 g) = 0.062 W/kg; SAR(10 g) = 0.040 W/kg**

Maximum value of SAR (measured) = 0.079 W/kg



**PCS 1900 EUT Front (GPRS 2UP 10mm) Z-Axis plot**  
**Channel: 512**



Test Laboratory: QuiteTek

Date/Time: 2015/3/11

# **WCDMA RMC BAND2\_Front 10mm-9262**

## **DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC WCDMA\_Band-2; Frequency: 1852.4 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.47$  S/m;  $\epsilon_r = 54.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.259 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.264 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.347 W/kg

**SAR(1 g) = 0.224 W/kg; SAR(10 g) = 0.144 W/kg**

Maximum value of SAR (measured) = 0.260 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/11

### WCDMA RMC BAND2\_Front 10mm-9400

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-2; Frequency: 1880 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.292 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.011 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.387 W/kg

**SAR(1 g) = 0.252 W/kg; SAR(10 g) = 0.162 W/kg**

Maximum value of SAR (measured) = 0.290 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/11

### WCDMA RMC BAND2\_Front 10mm-9538

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-2; Frequency: 1907.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.51$  S/m;  $\epsilon_r = 54.21$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.383 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.162 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.508 W/kg

**SAR(1 g) = 0.326 W/kg; SAR(10 g) = 0.209 W/kg**

Maximum value of SAR (measured) = 0.379 W/kg





Test Laboratory: Quietek

Date/Time: 2015/3/11

### WCDMA RMC BAND2\_Back 10mm-9400

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-2; Frequency: 1880 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.234 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.697 V/m; Power Drift = -0.09 dB  
Peak SAR (extrapolated) = 0.307 W/kg  
**SAR(1 g) = 0.195 W/kg; SAR(10 g) = 0.122 W/kg**  
Maximum value of SAR (measured) = 0.230 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/11

### WCDMA HSDPA BAND2\_Front 10mm-9400

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-2; Frequency: 1880 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.254 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.493 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.349 W/kg

**SAR(1 g) = 0.226 W/kg; SAR(10 g) = 0.145 W/kg**

Maximum value of SAR (measured) = 0.262 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/11

### WCDMA HSUPA BAND2\_Front 10mm-9400

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-2; Frequency: 1880 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 54.59$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 21.3, Liquid Temperature (°C) : 20.1


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.51, 7.51, 7.51); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)


**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.309 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm  
Reference Value = 7.302 V/m; Power Drift = -0.14 dB  
Peak SAR (extrapolated) = 0.415 W/kg  
**SAR(1 g) = 0.266 W/kg; SAR(10 g) = 0.170 W/kg**  
Maximum value of SAR (measured) = 0.313 W/kg





**WCDMA RMC Band 2 EUT Front (10mm) Z-Axis plot**  
**Channel: 9538**



Test Laboratory: QuieTek

Date/Time: 2015/3/12

# **WCDMA RMC BAND4\_Front 10mm-1312**

## **DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC WCDMA\_Band 4; Frequency: 1712.4 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1712.4$  MHz;  $\sigma = 1.47$  S/m;  $\epsilon_r = 53.51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.77, 7.77, 7.77); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.217 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.311 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.277 W/kg

**SAR(1 g) = 0.187 W/kg; SAR(10 g) = 0.124 W/kg**

Maximum value of SAR (measured) = 0.216 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/12

# **WCDMA RMC BAND4\_Front 10mm-1413**

## **DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC WCDMA\_Band 4; Frequency: 1732.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 53.39$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.77, 7.77, 7.77); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.209 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.051 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.269 W/kg

**SAR(1 g) = 0.185 W/kg; SAR(10 g) = 0.120 W/kg**

Maximum value of SAR (measured) = 0.210 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/12

# **WCDMA RMC BAND4\_Front 10mm-1513**

## **DUT: GPS Controller(GPS Receiver); Type: S Series-A**

Communication System: UID 0, FCC WCDMA\_Band 4; Frequency: 1752.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1752.6$  MHz;  $\sigma = 1.51$  S/m;  $\epsilon_r = 53.28$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.77, 7.77, 7.77); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.283 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.659 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.365 W/kg

**SAR(1 g) = 0.245 W/kg; SAR(10 g) = 0.161 W/kg**

Maximum value of SAR (measured) = 0.284 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/3/12

### WCDMA RMC BAND4\_Back 10mm-1413

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band 4; Frequency: 1732.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 53.39$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.77, 7.77, 7.77); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.126 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.546 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.172 W/kg

**SAR(1 g) = 0.105 W/kg; SAR(10 g) = 0.064 W/kg**

Maximum value of SAR (measured) = 0.127 W/kg





Test Laboratory: QuiteTek

Date/Time: 2015/3/12

### WCDMA HSDPA BAND4\_Front 10mm-1413

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band 4; Frequency: 1732.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 53.39$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.77, 7.77, 7.77); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.212 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.059 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.279 W/kg

**SAR(1 g) = 0.184 W/kg; SAR(10 g) = 0.124 W/kg**

Maximum value of SAR (measured) = 0.219 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/12

### WCDMA HSUPA BAND4\_Front 10mm-1413

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band 4; Frequency: 1732.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 53.39$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.3, Liquid Temperature (°C) : 19.2

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.77, 7.77, 7.77); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with left table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.216 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.241 V/m; Power Drift = -0.13 dB


Peak SAR (extrapolated) = 0.281 W/kg

**SAR(1 g) = 0.182 W/kg; SAR(10 g) = 0.124 W/kg**

Maximum value of SAR (measured) = 0.220 W/kg



**WCDMA RMC Band 4 EUT Front (10mm) Z-Axis plot**  
**Channel: 1513**





Test Laboratory: Quietek

Date/Time: 2015/3/10

### WCDMA RMC BAND5\_Front 10mm-4183

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-5; Frequency: 836.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.494 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.70 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.564 W/kg

**SAR(1 g) = 0.440 W/kg; SAR(10 g) = 0.330 W/kg**

Maximum value of SAR (measured) = 0.485 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/10

### WCDMA RMC BAND5\_Back 10mm-4132

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-5; Frequency: 826.4 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.96$  S/m;  $\epsilon_r = 56.57$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.450 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.04 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.535 W/kg

**SAR(1 g) = 0.408 W/kg; SAR(10 g) = 0.301 W/kg**

Maximum value of SAR (measured) = 0.455 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/10

### WCDMA RMC BAND5\_Back 10mm-4183

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-5; Frequency: 836.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.538 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.41 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.631 W/kg

**SAR(1 g) = 0.479 W/kg; SAR(10 g) = 0.352 W/kg**

Maximum value of SAR (measured) = 0.534 W/kg



Test Laboratory: Quietek

Date/Time: 2015/3/10

### WCDMA RMC BAND5\_Back 10mm-4233

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-5; Frequency: 846.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 846.6$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 56.24$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.420 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:  
dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.81 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.505 W/kg

**SAR(1 g) = 0.381 W/kg; SAR(10 g) = 0.279 W/kg**

Maximum value of SAR (measured) = 0.428 W/kg



Test Laboratory: QuiteTek

Date/Time: 2015/3/10

### WCDMA HSDPA BAND5\_Back 10mm-4183

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-5; Frequency: 836.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.450 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.85 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.523 W/kg

**SAR(1 g) = 0.398 W/kg; SAR(10 g) = 0.293 W/kg**

Maximum value of SAR (measured) = 0.445 W/kg





Test Laboratory: Quietek

Date/Time: 2015/3/10

### WCDMA HSUPA BAND5\_Back 10mm-4183

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, FCC WCDMA\_Band-5; Frequency: 836.6 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 56.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 20.7, Liquid Temperature (°C) : 19.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(9.68, 9.68, 9.68); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.435 W/kg

**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.42 V/m; Power Drift = -0.17 dB


Peak SAR (extrapolated) = 0.527 W/kg

**SAR(1 g) = 0.398 W/kg; SAR(10 g) = 0.293 W/kg**

Maximum value of SAR (measured) = 0.444 W/kg



# **WCDMA RMC Band 5 EUT Back (10mm) Z-Axis plot** **Channel: 4183**



Test Laboratory: QuieTek

Date/Time: 2015/4/15

### 802.11b\_6-Front 10mm

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.95$  S/m;  $\epsilon_r = 53.67$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 22.0, Liquid Temperature (°C) : 20.9

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (10x13x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.0575 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.499 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.0870 W/kg

**SAR(1 g) = 0.045 W/kg; SAR(10 g) = 0.024 W/kg**

Maximum value of SAR (measured) = 0.0579 W/kg





Test Laboratory: QuieTek

Date/Time: 2015/4/15

### 802.11b\_1-Back 10mm

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, WLAN 2.4G; Frequency: 2412 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.92$  S/m;  $\epsilon_r = 53.89$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 22.0, Liquid Temperature (°C) : 20.9

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (10x14x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.144 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.091 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.228 W/kg

**SAR(1 g) = 0.125 W/kg; SAR(10 g) = 0.065 W/kg**

Maximum value of SAR (measured) = 0.158 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/4/15

### 802.11b\_6-Back 10mm

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.95$  S/m;  $\epsilon_r = 53.67$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 22.0, Liquid Temperature (°C) : 20.9

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (16x14x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.197 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.007 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.303 W/kg

**SAR(1 g) = 0.167 W/kg; SAR(10 g) = 0.088 W/kg**

Maximum value of SAR (measured) = 0.207 W/kg



Test Laboratory: QuieTek

Date/Time: 2015/4/15

### 802.11b\_11-Back 10mm

#### DUT: GPS Controller(GPS Receiver); Type: S Series-A

Communication System: UID 0, WLAN 2.4G; Frequency: 2462 MHz;

Communication System PAR: 0 dB

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.98$  S/m;  $\epsilon_r = 53.35$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature (°C) : 22.0, Liquid Temperature (°C) : 20.9

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 2014/11/21;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM with right table; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/Body/Area Scan (10x14x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.170 W/kg


**Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.770 V/m; Power Drift = 0.08 dB


Peak SAR (extrapolated) = 0.247 W/kg

**SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.071 W/kg**

Maximum value of SAR (measured) = 0.171 W/kg



**802.11b EUT Back (10mm) Z-Axis plot**  
**Channel: 6**



## **Appendix D. Probe Calibration Data**

**Object: EX3DV4- SN: 3979**





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **Quietek-TW (Auden)**

Certificate No: **EX3-3979\_Nov14**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3979**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **November 21, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	03-Apr-14 (No. 217-01911)	Apr-15
Power sensor E4412A	MY41498087	03-Apr-14 (No. 217-01911)	Apr-15
Reference 3 dB Attenuator	SN: S5054 (3c)	03-Apr-14 (No. 217-01915)	Apr-15
Reference 20 dB Attenuator	SN: S5277 (20x)	03-Apr-14 (No. 217-01919)	Apr-15
Reference 30 dB Attenuator	SN: S5129 (30b)	03-Apr-14 (No. 217-01920)	Apr-15
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-14)	In house check: Oct-15

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: November 24, 2014			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).



# Probe EX3DV4

## SN:3979

Manufactured:	November 5, 2013
Calibrated:	November 21, 2014

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	0.48	0.50	0.48	$\pm 10.1 \%$
DCP (mV) <sup>B</sup>	99.8	99.9	100.5	

### Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc <sup>E</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	193.1	$\pm 3.8 \%$
		Y	0.0	0.0	1.0		190.4	
		Z	0.0	0.0	1.0		184.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

### Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unct. (k=2)
750	41.9	0.89	9.94	9.94	9.94	0.64	0.70	± 12.0 %
835	41.5	0.90	9.50	9.50	9.50	0.27	1.16	± 12.0 %
900	41.5	0.97	9.29	9.29	9.29	0.26	1.19	± 12.0 %
1450	40.5	1.20	8.36	8.36	8.36	0.80	0.58	± 12.0 %
1640	40.3	1.29	8.08	8.08	8.08	0.68	0.78	± 12.0 %
1750	40.1	1.37	8.02	8.02	8.02	0.71	0.73	± 12.0 %
1810	40.0	1.40	7.81	7.81	7.81	0.67	0.74	± 12.0 %
1900	40.0	1.40	7.76	7.76	7.76	0.56	0.83	± 12.0 %
2000	40.0	1.40	7.78	7.78	7.78	0.62	0.76	± 12.0 %
2300	39.5	1.67	7.38	7.38	7.38	0.44	0.87	± 12.0 %
2450	39.2	1.80	7.09	7.09	7.09	0.43	0.88	± 12.0 %
2600	39.0	1.96	6.90	6.90	6.90	0.42	0.97	± 12.0 %
3500	37.9	2.91	7.19	7.19	7.19	0.77	0.66	± 13.1 %
5200	36.0	4.66	4.88	4.88	4.88	0.35	1.80	± 13.1 %
5300	35.9	4.76	4.69	4.69	4.69	0.35	1.80	± 13.1 %
5500	35.6	4.96	4.57	4.57	4.57	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.45	4.45	4.45	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.40	4.40	4.40	0.40	1.80	± 13.1 %

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

### Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unct. (k=2)
750	55.5	0.96	9.79	9.79	9.79	0.44	0.85	± 12.0 %
835	55.2	0.97	9.68	9.68	9.68	0.66	0.69	± 12.0 %
900	55.0	1.05	9.43	9.43	9.43	0.35	0.99	± 12.0 %
1450	54.0	1.30	8.11	8.11	8.11	0.74	0.62	± 12.0 %
1640	53.8	1.40	8.25	8.25	8.25	0.60	0.71	± 12.0 %
1750	53.4	1.49	7.77	7.77	7.77	0.65	0.69	± 12.0 %
1810	53.3	1.52	7.64	7.64	7.64	0.52	0.77	± 12.0 %
1900	53.3	1.52	7.51	7.51	7.51	0.63	0.70	± 12.0 %
2000	53.3	1.52	7.61	7.61	7.61	0.45	0.79	± 12.0 %
2300	52.9	1.81	7.30	7.30	7.30	0.67	0.64	± 12.0 %
2450	52.7	1.95	7.08	7.08	7.08	0.80	0.61	± 12.0 %
2600	52.5	2.16	6.81	6.81	6.81	0.80	0.50	± 12.0 %
3500	51.3	3.31	6.40	6.40	6.40	0.57	0.85	± 13.1 %
5200	49.0	5.30	4.60	4.60	4.60	0.40	1.90	± 13.1 %
5300	48.9	5.42	4.42	4.42	4.42	0.40	1.90	± 13.1 %
5500	48.6	5.65	4.04	4.04	4.04	0.45	1.90	± 13.1 %
5600	48.5	5.77	4.01	4.01	4.01	0.45	1.90	± 13.1 %
5800	48.2	6.00	4.18	4.18	4.18	0.50	1.90	± 13.1 %


<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

## Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$

f=600 MHz, TEM



f=1800 MHz, R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )



## Dynamic Range f(SAR<sub>head</sub>)


(TEM cell , f<sub>eval</sub>= 1900 MHz)



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)





## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979****Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-46.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

## **Appendix E. Dipole Calibration**

**Validation Dipole 835 MHz**

**M/N: ALS-D-835**

**S/N: QTK-315**



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client Quietek-TW (Auden)

Certificate No: ALS-D-835-QTK-315\_May14

## CALIBRATION CERTIFICATE

Object ALS-D-835 - SN: QTK-315

Calibration procedure(s) QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: May 16, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	30-Apr-14 (No. DAE4-601_Apr14)	Apr-15
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: Name Claudio Leubler Function Laboratory Technician

Signature

Approved by: Katja Pokovic Technical Manager

Issued: May 20, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.2 $\pm$ 6 %	0.94 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

## SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.32 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	<b>8.92 W/kg <math>\pm</math> 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.49 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	<b>5.78 W/kg <math>\pm</math> 16.5 % (k=2)</b>

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	56.6 $\pm$ 6 %	1.02 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

## SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.45 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	<b>9.49 W/kg <math>\pm</math> 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.60 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	<b>6.23 W/kg <math>\pm</math> 16.5 % (k=2)</b>



## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	$48.6 \Omega + 1.4 j\Omega$
Return Loss	- 34.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	$44.6 \Omega + 1.0 j\Omega$
Return Loss	- 24.7 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	0.985 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	APREL
Manufactured on	Unknown



## DASY5 Validation Report for Head TSL

Date: 16.05.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: ALS-D-835; Serial: ALS-D-835 - SN: QTK-315**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.94$  S/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.22, 6.22, 6.22); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2014
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm 2/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.23 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 3.50 W/kg

**SAR(1 g) = 2.32 W/kg; SAR(10 g) = 1.49 W/kg**

Maximum value of SAR (measured) = 2.72 W/kg



## Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 15.05.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: ALS-D-835; Serial: ALS-D-835 - SN: QTK-315**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 1.02$  S/m;  $\epsilon_r = 56.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.09, 6.09, 6.09); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2014
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.71 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.64 W/kg

**SAR(1 g) = 2.45 W/kg; SAR(10 g) = 1.6 W/kg**

Maximum value of SAR (measured) = 2.86 W/kg





Impedance Measurement Plot for Body TSL

