QUICK START GUIDE SCHNELLINSTALLATIONSANLEITUNG **GUIDE D'INSTALLATION RAPIDE GUIDA RAPIDA DI INSTALLAZIONE GUÍA DE INSTALACIÓN RÁPIDA** GUIA DE INSTALAÇÃO RÁPIDA SNELLE INSTALLATIE GIDS 簡単スタートガイド ИНСТРУКЦИЯ ПО БЫСТРОМУ ЗАПУСКУ 快速使用指南 عيرسلا ليغشتاا لعلد

لماكل مدختسمها لكيلد

Полное руководство пользователя 完全用户指南 Manuale di istruzioni integrale Benutzerleitfaden Vollversion Guia de utilização completo Guide complet d'utilisation Guía completa del usuario Uitgebreide handleiding 完全ユーザーガイド Full user guide










BeeWi

SMART PLUG BBP200



	(0)	-		<u> </u>		(8)			- "/	
	LOCAL ACCESS MODE MODE ACCES LOCAL IOKALER ZIGREFSMODIS	MODALITÀ ACCESSO LOCALE MODO ACCESO LOCAL MODO DE ACESSO LOCAL LOKALE TOEGANGSMODUS	MECTHBIЙ PEWMM ローカルアクセスモード 本地権式 IsZlizje III Elado III Incela	:) (2		9	+	
•	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 g 5.2 oz	148 8
1	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4 °	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4"	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4"	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4°	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4°	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4"	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4°	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4°	124 x 76 x 36.5 mm 4.9 x 2.9 x 1.4"	124 x 76 x
4	16 A	16 A	16 A	100-240V	100-240V	16 A	100-240V	16 A	16 A	16 A	00-240V
<u>(-)</u>	Program 1 ming & energy saving	Program 1 mation & économie d'énergie	Program 1 mieren & Energie sparen	Programm 1 azione e risparmio energetico	Ahorro de 1 programa ción y energía	Programa 1 ção e economia de energia	Program 1 mering & energiebe sparing	Програм 1 мируем ый и энергос	プログラム 1 & エネル ギー節約	要報 乗車	e Gelecia
	±0.5°C ±0.9°F.	±0.5°C	±0.9°E.	±0.5°C	±0.5°C	±0.5°C ±0.9°F.	±0.5°C	±0.5°C ±0.9°F.	±0.5°C ±0.9°F.	±0.5°C ±0.9°F.	±0.5°C
0	On/off	Marche/ Arrêt	An/aus	Accension e/spegnim ento	Encendido /apagado	On/Off	Aan/uit	кл/Выкл	42//47	*/#	iqêşk
*	Detection O over 100°, up to 5m/16ft	Detection M a 100°, jusqu'à 5m/16ft	Detektion A über 100°, bis 5 m/16	Rilevazion Accension e a 100°, e/spegnim fino a 5 m/16 ft	Detección E precisa / 100°, hasta 5 m/16 pies	Deteção acima de 100°, até 5 m/16 ft	Detectie over 100°, tot 5m/16ft	Определевки/выки ние сверх 100°, до 5 м/16 футов	100°C以 上の検出 、5mまで	商品 超过100° 米/16英 万	500 000
••	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%	%9:0	0.5%	0.5%
\$	30 m	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m 98 ft	30 m
v	Bluetooth Smart 4.0	Bluetooth Smart 4.0	Bluetooth Smart 4.0	Smart 4.0	Smart 4.0	Bluetooth Smart 4.0	Smart 4.0	Smart 4.0	Bluetooth Smart 4.0	Bluetooth Smart 4.0	Bluetooth
* &	1 % "				1	1	1		1	144	1.00









H(U)







