



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Micron Electronics LLC.

11001 Yamato Road, Suite 400, Boca Raton, Florida 33431 United States

FCC ID: ZKQ-MBLTA

Report Type: Original Report	Product Type: Tracker
Test Engineer: Stone Zhang <i>Stone Zhang</i>	
Report Number: RSHA190910003-00B	
Report Date: 2019-09-26	
Reviewed By:	Oscar Ye <i>Oscar Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	61
APPLICABLE STANDARD	61
TEST PROCEDURE	61
TEST DATA	62
FCC §15.247(d) – BAND EDGE.....	65
APPLICABLE STANDARD	65
TEST PROCEDURE	65
TEST DATA	65
FCC §15.247(e) - POWER SPECTRAL DENSITY	71
APPLICABLE STANDARD	71
TEST PROCEDURE	71
TEST DATA	71

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Micron Electronics LLC.
Tested Model:	Bolt Mini 2A
Product Type:	Tracker
Dimension:	77.8mm (L)*44mm (W)*22mm(H)
Power Supply:	DC 6V from 4cell "AA" alkaline battery

**All measurement and test data in this report was gathered from production sample serial number: 20190910003.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2019-09-10)*

Objective

This report is prepared on behalf of *Micron Electronics LLC.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section FCC Title 47, 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JAB and Part 15.231 DSC submissions with FCC ID: ZKQ-MBLTA.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11;

For 802.11n-HT40 mode, EUT was tested with Channel 3, 6 and 9;

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
18	2438	38	2478
19	2440	39	2480

Equipment Modifications


No modification was made to the EUT tested.

EUT Exercise Software


RF test software: Maui META 3G ver 8.1520.0.0

Pre-scan with all the data rates, and the worst case was performed as below:


Mode	Data Rate	Power Level
802.11b	1 Mbps	16
802.11g	6 Mbps	9
802.11n-HT20	MCS0	9
802.11n-HT40	MCS0	9
BLE	1 Mbps	15

Duty Cycle:**802.11b Mode Middle Channel**


802.11g Mode Middle Channel




802.11n-HT20 Mode Middle Channel



802.11n-HT40 Mode Middle Channel



BLE Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100.00	/	/	0.00
802.11g	100.00	/	/	0.00
802.11n-HT20	100.00	/	/	0.00
802.11n-HT40	100.00	/	/	0.00
BLE	71.93	0.451	2.22	1.43

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263

External I/O Cable


Cable Description	Shielding Type	Length (m)	From Port	To
USB Cable	Un-shielding	0.5	Notebook	EUT

Block Diagram of Test Setup

For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note)
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note: The equipment is power supply by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-30	2019-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-08-27	2020-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2019-01-11	2022-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-12-12	2019-12-11
A.H.Systems, inc	Preamplifier	2641-1	491	2019-02-20	2020-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-30	2019-11-29
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Agilent	Power Meter	N1912A	MY5000492	2018-11-18	2019-11-17
Agilent	Power Sensor	N1921A	MY54210024	2018-11-18	2019-11-17
Micron	RF Cable	Micron C01	C01	Each Time	/

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1310 & §2.1091 –RF EXPOSURE

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Measurement Result

Mode	Frequency Range (MHz)	Antenna Gain		Target Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	0.50	1.12	14.50	28.18	20	0.0063	1.0
802.11g		0.50	1.12	12.00	15.85	20	0.0035	1.0
802.11n-HT20		0.50	1.12	12.00	15.85	20	0.0035	1.0
802.11n-HT40	2422~2452	0.50	1.12	12.00	15.85	20	0.0035	1.0
BLE	2402~2480	0.20	1.05	5.00	3.16	20	0.0007	1.0
LTE Band 2	1850~1910	0.50	1.12	24.00	251.19	20	0.0561	1.23
LTE Band 4	1710~1755	0.50	1.12	24.00	251.19	20	0.0561	1.14
LTE Band 12	699~716	-0.30	0.93	24.45	278.61	20	0.0517	0.47
LTE Band 13	777~787	0.00	1.00	24.00	251.19	20	0.0500	0.52

Note:

- 1). The target output power was declared by the manufacturer.
- 2) The LTE module FCC ID: RI7ME910C1NA.
- 3) WiFi ,BLE and LTE can transmit simultaneously; the worst condition was as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0063/1.00 + 0.0007/1.00 + 0.0517/0.47 = 0.0063 + 0.0007 + 0.11 = 0.1170 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



Antenna Connector Construction

The EUT has a FPC antenna for Wi-Fi & BLE, which the Wi-Fi antenna gain is 0.5 dBi and BLE antenna gain is 0.2 dBi fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**

Temperature:	24.1-24.8 °C
Relative Humidity:	48-50 %
ATM Pressure:	101.0-101.2kPa


The testing was performed by Stone Zhang from 2019-09-12 to 2019-09-17.

Test Result: Compliant.

EUT operation mode: Transmitting

Spurious Emission Test:**30MHz-1GHz:**

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11b mode in Z-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
31.54	18.61	100.0	V	155.0	-5.0	40.00	21.39
70.57	5.16	100.0	V	0.0	-17.3	40.00	34.84
126.46	10.51	150.0	H	149.0	-11.4	43.50	32.99
241.93	9.61	200.0	H	170.0	-12.1	46.00	36.39
287.18	10.67	200.0	V	190.0	-10.9	46.00	35.33
709.42	18.85	100.0	H	304.0	-3.0	46.00	27.15

1GHz-18GHz:**802.11b Mode:**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1591.60	---	25.81	250.0	V	153.0	-9.6	54.00	28.19
1591.60	36.71	---	250.0	V	153.0	-9.6	74.00	37.29
4223.20	---	42.22	150.0	V	82.0	-1.5	54.00	11.78
4223.20	51.93	---	150.0	V	82.0	-1.5	74.00	22.07
4824.00	---	36.05	150.0	H	30.0	-0.5	54.00	17.95
4824.00	44.48	---	150.0	H	30.0	-0.5	74.00	29.52
6732.40	---	37.04	200.0	V	117.0	4.8	54.00	16.96
6732.40	48.54	---	200.0	V	117.0	4.8	74.00	25.46
8847.20	---	40.03	250.0	V	231.0	7.3	54.00	13.97
8847.20	50.68	---	250.0	V	231.0	7.3	74.00	23.32
17605.60	---	46.25	150.0	H	295.0	14.1	54.00	7.75
17605.60	57.12	---	150.0	H	295.0	14.1	74.00	16.88

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.60	---	27.87	200.0	V	190.0	-9.6	54.00	26.13
1591.60	37.69	---	200.0	V	190.0	-9.6	74.00	36.31
4223.20	---	43.66	150.0	V	91.0	-1.5	54.00	10.34
4223.20	52.35	---	150.0	V	91.0	-1.5	74.00	21.65
5511.80	---	35.37	150.0	V	304.0	1.4	54.00	18.63
5511.80	45.23	---	150.0	V	304.0	1.4	74.00	28.77
7861.20	---	39.86	250.0	H	332.0	6.8	54.00	14.14
7861.20	50.42	---	250.0	H	332.0	6.8	74.00	23.58
12284.60	---	43.27	100.0	V	359.0	10.2	54.00	10.73
12284.60	53.52	---	100.0	V	359.0	10.2	74.00	20.48
17561.40	---	46.93	200.0	V	260.0	14.2	54.00	7.07
17561.40	57.51	---	200.0	V	260.0	14.2	74.00	16.49

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1578.00	---	25.29	100.0	V	188.0	-9.7	54.00	28.71
1578.00	35.14	---	100.0	V	188.0	-9.7	74.00	38.86
4223.20	---	44.37	150.0	V	99.0	-1.5	54.00	9.63
4223.20	53.00	---	150.0	V	99.0	-1.5	74.00	21.00
6144.20	---	36.54	100.0	V	7.0	2.9	54.00	17.46
6144.20	46.88	---	100.0	V	7.0	2.9	74.00	27.12
10367.00	---	41.11	150.0	H	149.0	8.8	54.00	12.89
10367.00	52.33	---	150.0	H	149.0	8.8	74.00	21.67
14443.60	---	44.59	250.0	V	258.0	12.7	54.00	9.41
14443.60	55.26	---	250.0	V	258.0	12.7	74.00	18.74
17561.40	---	46.42	150.0	H	249.0	14.2	54.00	7.58
17561.40	57.12	---	150.0	H	249.0	14.2	74.00	16.88

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1554.20	36.16	---	100.0	V	275.0	-9.7	74.00	37.84
1554.20	---	24.68	100.0	V	275.0	-9.7	54.00	29.32
4223.20	50.14	---	150.0	V	86.0	-1.5	74.00	23.86
4223.20	---	41.33	150.0	V	86.0	-1.5	54.00	12.67
5131.00	45.27	---	200.0	V	263.0	0.2	74.00	28.73
5131.00	---	33.59	200.0	V	263.0	0.2	54.00	20.41
6980.60	---	38.06	150.0	H	238.0	5.3	54.00	15.94
6980.60	49.53	---	150.0	H	238.0	5.3	74.00	24.47
11730.40	---	41.85	250.0	V	133.0	9.9	54.00	12.15
11730.40	53.13	---	250.0	V	133.0	9.9	74.00	20.87
17945.60	---	46.46	100.0	V	228.0	13.6	54.00	7.54
17945.60	57.78	---	100.0	V	228.0	13.6	74.00	16.22

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1880.60	---	25.29	250.0	V	324.0	-8.6	54.00	28.71
1880.60	36.05	---	250.0	V	324.0	-8.6	74.00	37.95
3499.00	---	31.72	200.0	H	5.0	-3.5	54.00	22.28
3499.00	43.15	---	200.0	H	5.0	-3.5	74.00	30.85
4223.20	---	35.68	150.0	V	109.0	-1.5	54.00	18.32
4223.20	44.85	---	150.0	V	109.0	-1.5	74.00	29.15
5545.80	---	34.87	250.0	H	59.0	1.5	54.00	19.13
5545.80	46.21	---	250.0	H	59.0	1.5	74.00	27.79
7980.20	---	39.77	150.0	H	132.0	7.0	54.00	14.23
7980.20	50.34	---	150.0	H	132.0	7.0	74.00	23.66
17683.80	---	45.49	100.0	V	201.0	14.0	54.00	8.51
17683.80	56.65	---	100.0	V	201.0	14.0	74.00	17.35

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1268.60	---	22.98	200.0	V	289.0	-11.2	54.00	31.02
1268.60	34.56	---	200.0	V	289.0	-11.2	74.00	39.44
3325.60	---	30.76	150.0	V	344.0	-3.8	54.00	23.24
3325.60	41.75	---	150.0	V	344.0	-3.8	74.00	32.25
4831.80	---	33.10	200.0	V	205.0	-0.5	54.00	20.90
4831.80	43.54	---	200.0	V	205.0	-0.5	74.00	30.46
6555.60	---	37.90	100.0	V	196.0	4.5	54.00	16.10
6555.60	49.18	---	100.0	V	196.0	4.5	74.00	24.82
10900.80	---	41.71	250.0	V	276.0	9.6	54.00	12.29
10900.80	52.45	---	250.0	V	276.0	9.6	74.00	21.55
17649.80	---	47.10	100.0	V	344.0	14.0	54.00	6.90
17649.80	56.57	---	100.0	V	344.0	14.0	74.00	17.43

802.11n-HT20 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel : 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1523.60	35.23	---	100.0	H	329.0	-9.9	74.00	38.77
1523.60	---	25.49	100.0	H	329.0	-9.9	54.00	28.51
4223.20	54.39	---	100.0	V	79.0	-1.5	74.00	19.61
4223.20	---	44.86	100.0	V	79.0	-1.5	54.00	9.14
6028.60	46.61	---	250.0	V	316.0	2.4	74.00	27.39
6028.60	---	36.39	250.0	V	316.0	2.4	54.00	17.61
7997.20	49.85	---	150.0	H	220.0	7.1	74.00	24.15
7997.20	---	40.53	150.0	H	220.0	7.1	54.00	13.47
11281.60	53.76	---	200.0	H	346.0	9.8	74.00	20.24
11281.60	---	42.56	200.0	H	346.0	9.8	54.00	11.44
17524.00	---	46.64	250.0	V	308.0	14.2	54.00	7.36
17524.00	57.49	---	250.0	V	308.0	14.2	74.00	16.51

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1595.00	---	25.76	250.0	V	270.0	-9.6	54.00	28.24
1595.00	37.05	---	250.0	V	270.0	-9.6	74.00	36.95
3070.60	---	31.11	200.0	V	252.0	-4.3	54.00	22.89
3070.60	41.84	---	200.0	V	252.0	-4.3	74.00	32.16
4223.20	---	43.54	200.0	V	85.0	-1.5	54.00	10.46
4223.20	54.29	---	200.0	V	85.0	-1.5	74.00	19.71
7252.60	---	38.19	200.0	H	126.0	5.7	54.00	15.81
7252.60	48.85	---	200.0	H	126.0	5.7	74.00	25.15
10761.40	---	41.44	150.0	V	228.0	9.4	54.00	12.56
10761.40	52.10	---	150.0	V	228.0	9.4	74.00	21.90
17541.00	---	46.44	200.0	V	110.0	14.2	54.00	7.56
17541.00	57.12	---	200.0	V	110.0	14.2	74.00	16.88

High Channel : 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.60	---	25.75	150.0	V	252.0	-9.6	54.00	28.25
1591.60	36.24	---	150.0	V	252.0	-9.6	74.00	37.76
3070.60	---	31.12	250.0	V	269.0	-4.3	54.00	22.88
3070.60	41.25	---	250.0	V	269.0	-4.3	74.00	32.75
4223.20	---	42.73	150.0	V	99.0	-1.5	54.00	11.27
4223.20	54.78	---	150.0	V	99.0	-1.5	74.00	19.22
5525.40	---	35.30	100.0	H	127.0	1.5	54.00	18.70
5525.40	45.60	---	100.0	H	127.0	1.5	74.00	28.40
8847.20	---	40.49	250.0	H	359.0	7.3	54.00	13.51
8847.20	50.84	---	250.0	H	359.0	7.3	74.00	23.16
13797.60	---	44.34	200.0	V	323.0	12.3	54.00	9.66
13797.60	55.55	---	200.0	V	323.0	12.3	74.00	18.45

802.11n-HT40 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel : 2422MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1612.00	---	26.93	150.0	V	236.0	-9.6	54.00	27.07
1612.00	38.78	---	150.0	V	236.0	-9.6	74.00	35.22
4223.20	---	40.71	200.0	V	97.0	-1.5	54.00	13.29
4223.20	53.01	---	200.0	V	97.0	-1.5	74.00	20.99
5382.60	---	32.98	200.0	V	81.0	1.0	54.00	21.02
5382.60	44.18	---	200.0	V	81.0	1.0	74.00	29.82
7466.80	---	38.02	150.0	V	268.0	6.1	54.00	15.98
7466.80	48.71	---	150.0	V	268.0	6.1	74.00	25.29
10989.20	---	40.40	150.0	H	26.0	9.7	54.00	13.60
10989.20	52.56	---	150.0	H	26.0	9.7	74.00	21.44
17602.20	---	46.51	150.0	V	327.0	14.1	54.00	7.49
17602.20	57.10	---	150.0	V	327.0	14.1	74.00	16.90

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1595.00	---	25.13	200.0	V	97.0	-9.6	54.00	28.87
1595.00	34.64	---	200.0	V	97.0	-9.6	74.00	39.36
4223.20	---	41.99	150.0	V	87.0	-1.5	54.00	12.01
4223.20	54.39	---	150.0	V	87.0	-1.5	74.00	19.61
5518.60	---	34.50	200.0	V	163.0	1.4	54.00	19.50
5518.60	44.88	---	200.0	V	163.0	1.4	74.00	29.12
6967.00	---	37.67	150.0	V	147.0	5.3	54.00	16.33
6967.00	48.32	---	150.0	V	147.0	5.3	74.00	25.68
11359.80	---	41.30	200.0	H	253.0	9.8	54.00	12.70
11359.80	53.25	---	200.0	H	253.0	9.8	74.00	20.75
17462.80	---	46.64	150.0	V	247.0	14.1	54.00	7.36
17462.80	56.75	---	150.0	V	247.0	14.1	74.00	17.25

High Channel : 2452MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1574.60	---	24.58	200.0	V	285.0	-9.7	54.00	29.42
1574.60	35.14	---	200.0	V	285.0	-9.7	74.00	38.86
4223.20	---	41.81	150.0	V	83.0	-1.5	54.00	12.19
4223.20	53.90	---	150.0	V	83.0	-1.5	74.00	20.10
5661.40	---	34.27	200.0	V	334.0	1.7	54.00	19.73
5661.40	45.23	---	200.0	V	334.0	1.7	74.00	28.77
7946.20	---	39.41	150.0	H	359.0	7.0	54.00	14.59
7946.20	50.39	---	150.0	H	359.0	7.0	74.00	23.61
10768.20	---	41.26	150.0	H	9.0	9.4	54.00	12.74
10768.20	52.53	---	150.0	H	9.0	9.4	74.00	21.47
17653.20	---	46.03	150.0	V	0.0	14.0	54.00	7.97
17653.20	56.12	---	150.0	V	0.0	14.0	74.00	17.88

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11b mode in Z-axis of orientation** was recorded

Horizontal

Date: 17.SEP.2019 08:31:13

Vertical

Date: 17.SEP.2019 08:45:43

Fundamental Test & Restricted Bands Emissions Test:

Note:

Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

802.11b Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	35.91	200.0	H	35.0	2.8	54.00	18.09
2390.000000	46.05	---	200.0	H	35.0	2.8	74.00	27.50
High Channel: 2462MHz								
2483.500000	---	36.57	150.0	H	345.0	3.0	54.00	17.43
2483.500000	45.78	---	150.0	H	345.0	3.0	74.00	28.22

802.11g Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	34.92	150.0	V	122.0	2.8	54.00	19.08
2390.000000	46.70	---	150.0	V	122.0	2.8	74.00	27.30
High Channel: 2462MHz								
2483.500000	---	36.15	200.0	V	128.0	3.0	54.00	17.85
2483.500000	47.03	---	200.0	V	128.0	3.0	74.00	26.97

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	35.74	200.0	V	64.0	2.8	54.00	18.26
2390.000000	46.94	---	200.0	V	64.0	2.8	74.00	27.06
High Channel: 2462MHz								
2483.500000	---	36.14	150.0	H	44.0	3.0	54.00	17.86
2483.500000	48.37	---	150.0	H	44.0	3.0	74.00	25.63

802.11n-HT40 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2422MHz								
2390.000000	---	35.69	200.0	V	198.0	2.8	54.00	18.31
2390.000000	46.50	---	200.0	V	198.0	2.8	74.00	27.50
High Channel: 2452MHz								
2483.500000	---	37.35	200.0	H	281.0	3.0	54.00	16.65
2483.500000	48.55	---	200.0	H	281.0	3.0	74.00	25.45

For BLE Mode:**Spurious Emission Test:****30MHz-1GHz**

(The worst case low channel of operation in the Z axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Height (cm)	Polar (H/V)				
30.90	18.16	100.0	H	283.0	-4.5	40.00	21.84
71.35	4.71	200.0	H	18.0	-17.3	40.00	35.29
134.71	9.77	200.0	H	24.0	-11.8	43.50	33.73
326.57	11.55	200.0	V	59.0	-9.9	46.00	34.45
510.38	15.32	200.0	H	236.0	-6.0	46.00	30.68
779.87	19.12	200.0	H	128.0	-2.0	46.00	26.88

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1799.00	---	28.68	200.0	H	53.0	-8.9	54.00	25.32
1799.00	38.80	---	200.0	H	53.0	-8.9	74.00	35.20
3390.20	---	31.07	150.0	V	295.0	-3.7	54.00	22.93
3390.20	40.64	---	150.0	V	295.0	-3.7	74.00	33.36
4804.00	---	41.34	200.0	V	86.0	-0.6	54.00	12.66
4804.00	50.98	---	200.0	V	86.0	-0.6	74.00	23.02
7206.00	---	44.94	150.0	V	284.0	5.7	54.00	9.06
7206.00	52.17	---	150.0	V	284.0	5.7	74.00	21.83
11013.00	---	41.43	150.0	H	258.0	9.8	54.00	12.57
11013.00	50.77	---	150.0	H	258.0	9.8	74.00	23.23
17959.20	---	46.65	150.0	H	275.0	13.5	54.00	7.35
17959.20	55.95	---	150.0	H	275.0	13.5	74.00	18.05

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1829.60	---	28.05	200.0	V	122.0	-8.8	54.00	25.95
1829.60	36.81	---	200.0	V	122.0	-8.8	74.00	37.19
3254.20	---	31.52	150.0	V	154.0	-4.0	54.00	22.48
3254.20	41.66	---	150.0	V	154.0	-4.0	74.00	32.34
4880.00	---	42.31	150.0	V	260.0	-0.4	54.00	11.69
4880.00	49.86	---	150.0	V	260.0	-0.4	74.00	24.14
7320.00	---	42.97	200.0	H	112.0	5.8	54.00	11.03
7320.00	51.33	---	200.0	H	112.0	5.8	74.00	22.67
12199.60	---	46.79	200.0	H	63.0	10.2	54.00	7.21
12199.60	55.20	---	200.0	H	63.0	10.2	74.00	18.80
17592.00	---	46.37	150.0	V	2.0	14.1	54.00	7.63
17592.00	56.35	---	150.0	V	2.0	14.1	74.00	17.65

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1856.80	---	27.81	150.0	H	259.0	-8.7	54.00	26.19
1856.80	36.36	---	150.0	H	259.0	-8.7	74.00	37.64
3448.00	---	31.07	200.0	V	353.0	-3.6	54.00	22.93
3448.00	41.78	---	200.0	V	353.0	-3.6	74.00	32.22
4960.00	---	38.15	200.0	H	223.0	-0.3	54.00	15.85
4960.00	48.20	---	200.0	H	223.0	-0.3	74.00	25.80
7440.00	---	44.91	200.0	H	240.0	6.0	54.00	9.09
7440.00	53.20	---	200.0	H	240.0	6.0	74.00	20.80
12400.20	---	46.03	200.0	H	191.0	10.3	54.00	7.97
12400.20	54.58	---	200.0	H	191.0	10.3	74.00	19.42
17513.80	---	46.39	200.0	H	305.0	14.3	54.00	7.61
17513.80	56.58	---	200.0	H	305.0	14.3	74.00	17.42

18GHz-25GHz


(The worst case low channel of operation in the Z axis of orientation was recorded)

Horizontal



Date: 17.SEP.2019 00:14:50

Vertical



Date: 17.SEP.2019 08:15:40

Fundamental Test & Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	---	45.59	200.0	H	215.0	2.8	54.00	8.41
2390.00	49.96	---	200.0	H	215.0	2.8	74.00	24.04
High Channel: 2480MHz								
2483.50	---	42.60	150.0	V	118.0	3.0	54.00	11.40
2483.50	48.83	---	150.0	V	118.0	3.0	74.00	25.17

Spurious Emission Test:**For Co-location mode****30MHz-1GHz:**


(The worst case LTE Band 12 (3M BW) High Channel , middle channel of 802.11b mode ,Sub-G mode and BLE low channel transmitting simultaneously in X-axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
31.41	20.78	100.0	V	81.0	-4.9	40.00	19.22
142.20	36.28	200.0	H	129.0	-12.0	43.50	7.22
161.45	18.36	100.0	V	50.0	-12.8	43.50	25.14
249.81	23.10	150.0	H	284.0	-12.1	46.00	22.90
799.99	35.55	100.0	H	92.0	-1.7	46.00	10.45
870.96	35.87	100.0	H	127.0	-0.6	46.00	10.13

1GHz-18GHz:

(The worst case LTE Band 12 (3M BW) High Channel , high channel of 802.11b mode ,Sub-G mode and BLE low channel transmitting simultaneously in X-axis of orientation was recorded)




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1768.40	---	33.05	150.0	H	0.0	-9.0	54.00	20.95
1768.40	47.32	---	150.0	H	0.0	-9.0	74.00	26.68
3441.20	---	31.08	150.0	V	359.0	-3.6	54.00	22.92
3441.20	41.70	---	150.0	V	359.0	-3.6	74.00	32.30
4821.60	---	39.54	150.0	V	63.0	-0.5	54.00	14.46
4821.60	47.63	---	150.0	V	63.0	-0.5	74.00	26.37
4961.00	---	35.99	200.0	V	169.0	-0.3	54.00	18.01
4961.00	48.99	---	200.0	V	169.0	-0.3	74.00	25.01
7439.60	52.55	---	200.0	V	14.0	6.0	74.00	21.45
7439.60	---	45.75	200.0	V	14.0	6.0	54.00	8.25
12400.20	---	46.77	150.0	H	341.0	10.3	54.00	7.23
12400.20	54.95	---	150.0	H	341.0	10.3	74.00	19.05

18GHz-25GHz:


(The worst case LTE Band 12 (3M BW) High Channel , high channel of 802.11b mode ,Sub-G mode and BLE low channel transmitting simultaneously in X-axis of orientation was recorded)

Horizontal





Date: 17.SEP.2019 09:46:13

Vertical



Date: 17.SEP.2019 09:15:52

Conducted Spurious Emissions at Antenna Port**802.11b Mode Low Channel****802.11b Mode Middle Channel**

Marker 1 [T1]
 Ref Lvl -48.02 dBm
 20 dBm 4.88388778 GHz
 RBW 100 kHz RF Att 20 dB
 VBW 300 kHz
 SWT 6.4 s Unit dBm

10.5 dB Offset
 ▼1 [T1] -48.02 dBm
 4.88388778 GHz

D1 1.63 dBm
 1MAX
 D2 -18.37 dBm
 1MA

Start 30 MHz 2.497 GHz/ Stop 25 GHz

Date: 17.SEP.2019 09:52:26

Marker 1 [T1]
 Ref Lvl -61.44 dBm
 10 dBm 6.58525050 GHz
 RBW 100 kHz RF Att 10 dB
 VSW 300 kHz
 SWT 6.4 s Unit dBm


10.5 dB Offset
 ▼1 [T1] -61.44 dBm
 6.58525050 GHz

D1 -7.56 dBm
 1MAX
 D2 -27.56 dBm
 1


Start 30 MHz 2.497 GHz/ Stop 25 GHz

Date: 17.SEP.2019 10:04:35


802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	23.1°C-24.5°C
Relative Humidity:	48 %-50 %
ATM Pressure:	101.0kPa-102.0kPa


The testing was performed by Stone Zhang from 2019-09-16 to 2019-09-21.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	9.138	≥ 0.5
Middle	2437	9.138	≥ 0.5
High	2462	9.138	≥ 0.5
802.11g Mode			
Low	2412	16.433	≥ 0.5
Middle	2437	16.433	≥ 0.5
High	2462	16.513	≥ 0.5
802.11n-HT20 Mode			
Low	2412	17.715	≥ 0.5
Middle	2437	17.715	≥ 0.5
High	2462	17.635	≥ 0.5
802.11n-HT40 Mode			
Low	2422	36.313	≥ 0.5
Middle	2437	36.343	≥ 0.5
High	2452	36.313	≥ 0.5
BLE Mode			
Low	2402	0.782	≥ 0.5
Middle	2440	0.739	≥ 0.5
High	2480	0.782	≥ 0.5


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW \geq DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

Temperature:	24.1℃
Relative Humidity:	50 %
ATM Pressure:	101.2kPa


The testing was performed by Stone Zhang on 2019-09-16.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b Mode				
Low	2412	14.13	30	Pass
Middle	2437	14.16	30	Pass
High	2462	13.98	30	Pass
802.11g Mode				
Low	2412	11.65	30	Pass
Middle	2437	11.58	30	Pass
High	2462	11.52	30	Pass
802.11n-HT20 Mode				
Low	2412	11.68	30	Pass
Middle	2437	11.57	30	Pass
High	2462	11.47	30	Pass
802.11n-HT40 Mode				
Low	2422	11.88	30	Pass
Middle	2437	11.57	30	Pass
High	2452	11.83	30	Pass
BLE Mode				
Low	2402	4.56	30	Pass
Middle	2440	4.31	30	Pass
High	2480	4.05	30	Pass


BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	22.1 °C-24.1 °C
Relative Humidity:	49 %-50 %
ATM Pressure:	101.2kPa-102.1kPa

The testing was performed by Stone Zhang from 2019-09-16 to 2019-09-17.


Test Result: Compliant.

EUT operation mode: Transmitting


802.11b Mode Left Side




802.11b Mode Right Side



802.11g Mode Left Side



802.11g Mode Right Side



Marker 1 [T1]
 -47.06 dBm
 RBW 100 kHz RF Att 10 dB
 10 dBm 2.39887776 GHz SWT 17.5 ms Unit dBm

10.5 dB Offset
 -47.06 dBm
 2.39887776 GHz

D1 -7.61 dBm
 1MAX
 D2 -27.61 dBm
 1MAX

Center 2.4 GHz 7 MHz/ Span 70 MHz


Date: 17.SEP.2019 10:20:39

Ref Lvl 10 dBm RBW 100 kHz RF Att 10 dB
 10 dBm 2.48420140 GHz SWT 17.5 ms Unit dBm


Marker 1 [T1] -54.72 dBm
 10.5 dB Offset
 -D1 -8.02 dBm
 1MAX
 -D2 -28.02 dBm
 1
 Center 2.4835 GHz 7 MHz/
 Span 70 MHz

Date: 17.SEP.2019 10:19:25


802.11n-HT40 Mode Left Side




802.11n-HT40 Mode Right Side



BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq [3 \times \text{RBW}]$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	22.1 °C-24.1 °C
Relative Humidity:	49 %-50 %
ATM Pressure:	101.2kPa-102.1kPa


The testing was performed by Stone Zhang from 2019-09-16 to 2019-09-17.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-10.17	≤8
Middle	2437	-11.37	≤8
High	2462	-12.15	≤8
802.11g mode			
Low	2412	-22.27	≤8
Middle	2437	-21.29	≤8
High	2462	-21.12	≤8
802.11n-HT20 mode			
Low	2412	-19.43	≤8
Middle	2437	-21.41	≤8
High	2462	-20.48	≤8
802.11n-HT40 mode			
Low	2422	-22.87	≤8
Middle	2437	-23.78	≤8
High	2452	-23.53	≤8
BLE mode			
Low	2402	-10.12	≤8
Middle	2440	-7.67	≤8
High	2480	-10.73	≤8


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



***** END OF REPORT *****