TEST REPORT

REPORT NUMBER: B19W50651-WLAN_Rev2

ON

Type of Equipment:	Tracker
Model Name:	PT200LSV
Manufacturer:	Micron Electronics LLC.

ACCORDING TO

FCC Part 15, Subpart C, 2019:
15.205 Restricted bands of operation,
15.209 Radiated emission limits; general requirements,
15.247 Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz
ANSI C63.10-2013:American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Chongqing Academy of Information and Communications Technology

Month date, year
Jan, 14, 2020

Signature



Zhang Yan
Director

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of Chongqing Academy of Information and Communications Technology.

Revision Version

Report Number	Revision	Date	Memo
B19W50651-WLAN	V0.0	2019-12-27	--
B19W50651-WLAN	V1.0	2020-01-08	--
B19W50651-WLAN	V2.0	2020-01-14	--

Address：No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777

FCC ID:	ZKQ-PT200LSV
Report Date:	2020-01-14
Test Firm Name:	Chongqing Academy of Information and Communications Technology
FCC Registration Number:	CN1239

Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC Parts 15, subpart C. The sample tested was found to comply with the requirements defined in the applied rules.

CONTENTS

1 General Information

1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC Parts 15, subpart C and ANSI C63.10-2013 and FCC KDB 558074.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.

The following deviation from, additions to, or exclusions from the test specifications have been made. See Annex B.

Chongqing Academy of Information and Communications Technology authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of Chongqing Academy of Information and Communications Technology. Mr. Zhang Yan.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Chongqing Institute of Telecommunications accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

1.2 Testers

Name:	Li Xu
Position:	Engineer
Department:	Department of RF test
Date:	2019-12-10 to 2020-01-07
Signature:	

Editor of this test report:

Name:	Chen Wen
Position:	Engineer
Department:	Department of RF test
Date:	2020-01-14
Signature:	

Technical responsibility for area of testing:

Name:	Zhang Yan
Position:	Manager
Department:	Director of the laboratory
Date:	2020-01-14
Signature:	

1.3 Testing Laboratory information

1.3.1 Location

Name:	Chongqing Academy of Information and Communications Technology
Address:	Building B, Technology Innovation Center, No.8, Yuma Road, Chayuan New Area, Nan'an District, Chongqing, People's Republic of China, 401336
Tel:	+86-23-88069965
Fax:	+86-23-88608777
Email:	liqiao@caict.ac.cn

1.3.2 Test location, where different from section 1.3.1

Name:	------
Street:	------
City:	------
Country:	------
Telephone:	------
Fax:	------
Postcode:	------

1.4 Details of applicant or manufacturer

1.4.1 Applicant

Name:	Micron Electronics LLC.
Address:	1001 Yamato Road,Suite 400,Boca Raton,Florida,United States 33431
Country:	USA
Telephone:	+18885383489
Fax:	+18885501805
Contact:	Ping Cheng
Email:	pcheng@micron-electronics.com

1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name:	--
Address:	--
Country:	--
Telephone:	--
Fax:	--
Contact:	--
Email:	--

2 Test Item

2.1 General Information

Manufacturer:	Micron Electronics LLC.
Type of Equipment:	Tracker
Model Name:	PT200LSV
Production Status:	Product
Hardware Version:	A506_V1_PCB
Software Version:	--
Normal Voltages	3.80 V
High Voltages	4.20 V
Low Voltages	3.40 V
Receipt date of test item:	2019-12-10

2.2 Outline of Equipment under Test

The PT200LSV, referred to as “EUT” hereafter, is a a multi-Band wireless modem operating on the LTE/Wi-Fi/Bluetooth networks. The table below shows the supported bands for the EUT.

Technology	Freq.(MHz)	Note
2.4G WLAN	2400-2483.5	--

2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	Modules	Micron Electronics LLC.	AT Plus 4E	--	None
B	Modules	Micron Electronics LLC.	AT Plus 4E	--	None
C	Adapter	--	--	--	--
D	Battery	--	--	--	--

2.5 Other Information

--

3 Summary of Test Results

A brief summary of the tests carried out is shown as following.

FCC Rules	Name of Test	Result
15.247(b)	Maximum Peak Output Power	Pass
15.247(e)	Peak Power Spectral Density	Pass
15.247(a)	6dB Occupied Bandwidth	Pass
15.247(d)	Band Edges Compliance	Pass
15.247 (d)	Transmitter Spurious Emission-Conducted	Pass
15.247, 15.205, 15.209	Transmitter Spurious Emission-Radiated	Pass
ANSI C63.10 voltage mains test	Power line Conducted Emissions	Pass
Note:--		

4 Test Equipments and Ancillaries Used For Tests

The test equipments and ancillaries used are as follows.

No.	Equipment	Model	SN	Manufacture	Cal. Due Date
1	EMI Test Receiver	ESU26	100367	R&S	2020-03-01
2	Trilog super broad band test antenna	VULB 9163	9163-544	R&S	2020-11-23
3	Double-Ridged Horn Antenna	HF907	100357	R&S	2021-06-22
4	Fully-Anechoic Chamber	11.8m×6.5 m×6.3m	--	ETS	2020-10-22
5	Universal Radio Communication Tester	SP8315	SP8315-1249	StarPoint	2020-03-01
6	Signal Generator	SMU200A	104517	R&S	2020-03-01
7	Spectrum analyzer	FSQ 26	201137/026	R&S	2020-03-01
8	spectrum analyzer	N9020A	MY50200376	Agilent	2020-03-01
9	DC Power Supply	N6705B	MY50000919	Agilent	2020-12-04
10	Climate chamber	SH-241	92010759	ESPEC	2020-03-01

5 Test Results

5.1 Maximum Peak Output Power

Specifications:	FCC Part 15.247(b)
DUT Serial Number:	353081090308407
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	Pass

Limit Level Construction:

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz: 1 watt.

2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Measurement Uncertainty:

Measurement Uncertainty	±1.0dB

Test Method1:

1. The output power of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Enable EUT transmitter maximum power continuously.
3. Set RBW ≥ OBW, Set the appropriate VBW
4. Set sPan=zero
5. Sweep time=auto couple
6. Detector : Peak.
7. Trace mode: Max Hold

Test Method2:

1. The output power of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Enable EUT transmitter maximum power continuously.
3. Set RBW =1MHz , VBW=3MHz
4. Detector=peak
5. Sweep time=auto couple
6. Trace mode: Max Hold

Note: The test image shows only the worst-case results.

Measurement Results:

802.11b/g mode

Mode	Data Rate(Mbps)	Teat Result(dBm)			Conclusion
		Ch1	Ch6	Ch11	
802.11b	1	14.14	15.83	15.06	Pass
	2	14.01	15.57	15.10	Pass
	5.5	13.88	15.42	14.87	Pass
	11	13.95	15.39	14.89	Pass
802.11g	6	16.53	17.67	17.16	Pass
	9	16.93	17.83	16.75	Pass
	12	16.24	17.03	16.76	Pass
	18	16.35	16.81	16.52	Pass
	24	16.68	16.84	16.77	Pass
	36	16.35	16.93	16.65	Pass
	48	16.21	17.36	16.33	Pass
	54	16.20	16.92	16.90	Pass

802.11n mode

Mode	Data Rate(Mbps)	Teat Result(dBm)			Conclusion
		Ch1	Ch6	Ch11	
802.11n (20MHz)	MCS0	16.24	17.14	16.68	Pass
	MCS1	15.61	17.14	16.79	Pass
	MCS2	15.78	17.10	16.44	Pass
	MCS3	16.01	16.95	16.50	Pass
	MCS4	15.94	16.99	16.48	Pass
	MCS5	16.53	17.08	16.80	Pass
	MCS6	16.39	16.63	16.31	Pass
	MCS7	16.07	17.52	16.57	Pass
802.11n (40MHz)	MCS0	17.61	17.81	17.63	Pass
	MCS1	17.29	17.32	17.30	Pass
	MCS2	17.25	17.35	17.20	Pass
	MCS3	17.69	17.64	17.58	Pass
	MCS4	17.35	17.68	17.50	Pass
	MCS5	17.51	17.72	17.50	Pass
	MCS6	17.45	17.65	17.39	Pass
	MCS7	17.45	17.56	17.43	Pass

Conclusion: PASS

Test figure as below:



Fig.1 Peak Conducted Output Power CH6, 11b, Rate1



Fig.2 Conducted Output Power CH6, 11g, Rate9



Fig.3 Conducted Output Power CH6, 11n, Rate MCS7



Fig.4 Conducted Output Power CH6, 11n(40M), Rate MCS0

5.2 Peak Power Spectral Density

Specifications:	FCC CFR Part 15.247(e)
DUT Serial Number:	--
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	--

Limit Level Construction:

Standard	Limit
FCC CFR Part 15.247(e)	< 8dBm/3 KHz

Measurement Uncertainty:

Measurement Uncertainty	±0.82dBm/KHz

Test procedure:

The measurement is according to ANSI C63.10 clause 11.10.

1. The output power of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Enable EUT transmitter maximum power continuously.
3. Set analyzer center frequency to DTS channel center frequency.
4. Set the span to 1.5 times the DTS bandwidth.
5. Set the RBW to 3 kHz ≤ RBW ≤ 100 kHz.
6. Set the VBW ≥ [3 × RBW].
7. Detector = peak.
8. Sweep time = auto couple.
9. Trace mode = max hold.
10. Allow trace to fully stabilize.
11. Use the peak marker function to determine the maximum amplitude level within the RBW.
12. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Note: --

Test Results:

802.11b/g/n mode

Mode	Power Spectral Density(dBm/3kHz)			Conclusion
	Ch1	Ch6	Ch11	
802.11b	-12.68	-10.77	-11.81	Pass
802.11g	-18.84	-17.42	-18.18	Pass
802.11n(20MHz)	-18.72	-18.40	-18.44	Pass
802.11n(40MHz)	-21.99	-21.95	-20.90	Pass

Conclusion: PASS

Test figure as below:



Fig.5 Power spectral density: CH1,11b



Fig.6 Power spectral density: CH1,11g



Fig.7 Power spectral density: CH1,11n



Fig.8 Power spectral density: CH1,11n(40M)



Fig.9 Power spectral density: CH6,11b



Fig.10 Fig.66 Power spectral density: CH6,11g



Fig.11 Power spectral density: CH6,11n



Fig.12 Power spectral density: CH6,11n(40M)



Fig.13 Power spectral density: CH11,11b



Fig.14 Power spectral density: CH11,11g



Fig.15 Power spectral density: CH11,11n



Fig.16 Power spectral density: CH11,11n(40M)

5.3 6dB Occupied Bandwidth

Specifications:	FCC 47 CFR Part 15.247(a)
DUT Serial Number:	--
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	--

Limit Level Construction:

Standard	Limit(KHz)
FCC 47 CFR Part 15.247(a)	≥500

Measurement Uncertainty:

Measurement Uncertainty	±1.1KHz

Test Procedure

The measurement is according to ANSI C63.10 clause 11.8.

1. The output power of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Enable EUT transmitter maximum power continuously.
3. Set RBW = 100 kHz.
4. Set the VBW ≥ [3 × RBW].
5. Detector = peak.
6. Trace mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize.
9. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: --

Test Result:

802.11b/g/n mode

Mode	Occupied 6dB Bandwidth(MHz)			Conclusion
	Ch1	Ch6	Ch11	
802.11b	9.695	9.936	9.455	Pass
802.11g	8.093	8.093	8.093	Pass
802.11n(20MHz)	8.814	8.734	6.811	Pass
802.11n(40MHz)	17.949	17.789	17.788	Pass

Conclusion: PASS

Test figure as below:



Fig.17 6dB Bandwidth: Ch1,11b



Fig.18 6dB Bandwidth: Ch1,11g



Fig.19 6dB Bandwidth: Ch1,11n



Fig.20 6dB Bandwidth: Ch1,11n(40M)



Fig.21 6dB Bandwidth: Ch6,11b



Fig.22 6dB Bandwidth: Ch6,11g



Fig.23 6dB Bandwidth: Ch6,11n



Fig.24 6dB Bandwidth: Ch6,11n(40M)



Fig.25 6dB Bandwidth: Ch11,11b



Fig.26 6dB Bandwidth: Ch11,11g



Fig.27 6dB Bandwidth: Ch11,11n



Fig.28 6dB Bandwidth: Ch11,11n(40M)

5.4 Band Edges Compliance

Specifications:	FCC 47 CFR Part 15.247(d)
DUT Serial Number:	--
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	--

Limit Level Construction:

Standard	**Limited(**dBuV/m**)**	
FCC 47 CFR Part 15.247(d)	Peak	74
	Average	54

Measurement Uncertainty:

Frequency Range	**Uncertainty**
1 GHz to 6 GHz	4.68

Test Procedure

The measurement is according to ANSI C63.10 clause11.13.

1. Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
2. Reference level offset: Corrected for gains and losses of test antenna factor, preamp gain and cable loss, so as to indicate field strength, in units of dBμV/m at 3 m, directly on the instrument display. Alternatively, the reference level offset may be set to zero and calculations shall be provided showing the conversion of raw measured data to thefield strength in dBμV/m at 3 m.
3. Reference level: As required to keep the signal from exceeding the maximum spectrum analyzer input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2..
4. Attenuation: Auto (at least 10 dB preferred).
5. Sweep time: Coupled.
6. Resolution bandwidth: Above 1 GHz: 1 MHz
7. Video bandwidth: VBW for Peak, Quasi-peak, or Average Detector Function: 3×RBW
8. Detector (unless specified otherwise): Peak and average above 1 GHz
9. Trace: Max hold for final measurement; a combination of two traces, clear-write and max hold, is recommended for maximizing the emission.

Note: --

Test Result:

802.11b/g mode

mode	Channel	Test Results(dBuV/m)			Conclusion
802.11b	1	Peak	2400.000MHz	49.453	Pass
		Average	2400.000MHz	40.026	
		Fig.29			
	11	Peak	2483.500MHz	48.328	Pass
		Average	2483.500MHz	37.930	
		Fig.30			
802.11g	1	Peak	2400.000MHz	69.391	Pass
		Average	2400.000MHz	45.819	
		Fig.31			
	11	Peak	2483.500MHz	63.459	Pass
		Average	2483.500MHz	42.060	
		Fig.32			

802.11n mode

mode	Channel	Test Results(dBuV/m)			Conclusion
802.11n (20MHz)	1	Peak	2400.000MHz	68.274	Pass
		Average	2400.000MHz	45.274	
		Fig.33			
	11	Peak	2483.500MHz	64.440	Pass
		Average	2483.500MHz	43.192	
		Fig.34			
802.11n (40MHz)	3	Peak	2400.000MHz	53.680	Pass
		Average	2400.000MHz	34.256	
		Fig.35			
	11	Peak	2486.294MHz	68.042	Pass
		Average	2483.356MHz	43.774	
		Fig.36			

Conclusion: PASS

Test figure as below:



Fig.29 Frequency Band Edge: Ch1,11b



Fig.30 Frequency Band Edge: Ch11,11b

BAND EDGERE 1GHz-3GHz 2380-2450



Fig.31 Frequency Band Edge: Ch1,11g

BAND EDGERE 1GHz-3GHz 2483.5-2500



Fig.32 Frequency Band Edge: Ch11,11g



Fig.33 Frequency Band Edge: Ch1,11n(20M)



Fig.34 Frequency Band Edge: Ch11,11n(20M)

Address: No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777



Fig.35 Frequency Band Edge: Ch3,11n(40M)

Fig.36 Frequency Band Edge: Ch11,11n(40M)

5.5 Transmitter Spurious Emission-Conducted

Specifications:	FCC 47 CFR Part15.247 (d)
DUT Serial Number:	--
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	--

Limit

Standard	Limit
FCC 47 CFR Part15.247 (d)	20dB below peak output power in 100KHz bandwidth

Measurement Uncertainty:

Frequency Range	Uncertainty
30MHz ≤ f ≤ 26GHz	±2.7

Test Procedure

This measurement is according to ANSI C63.10 clause 11.11.

1. The output power of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Enable EUT transmitter maximum power continuously.

Reference level measurement

3. Set instrument center frequency to DTS channel center frequency.
4. Set the span to ≥ 1.5 times the DTS bandwidth.
5. Set the RBW = 100 kHz.
6. Set the VBW ≥ [3 × RBW].
7. Detector = peak.
8. Sweep time = auto couple.
9. Trace mode = max hold.
10. Allow trace to fully stabilize.
11. Use the peak marker function to determine the maximum PSD level.

Emission level measurement

12. Set the center frequency and span to encompass frequency range to be measured.
13. Set the RBW = 100 kHz.
14. Set the VBW ≥ [3 × RBW].
15. Detector = peak.
16. Sweep time = auto couple.
17. Trace mode = max hold.
18. Allow trace to fully stabilize.
19. Use the peak marker function to determine the maximum amplitude level.

Test Result:

802.11b/g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412GHz	Fig.37	Pass
		30MHz~26GHz	Fig.38	Pass
	6	2.437GHz	Fig.39	Pass
		30MHz~26GHz	Fig.40	Pass
	11	2.462GHz	Fig.41	Pass
		30MHz~26GHz	Fig.42	Pass
802.11g	1	2.412GHz	Fig.43	Pass
		30MHz~26GHz	Fig.44	Pass
	6	2.437GHz	Fig.45	Pass
		30MHz~26GHz	Fig.46	Pass
	11	2.462GHz	Fig.47	Pass
		30MHz~26GHz	Fig.48	Pass

802.11n mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (20MHz)	1	2.412GHz	Fig.49	Pass
		30MHz~26GHz	Fig.50	Pass
	6	2.437GHz	Fig.51	Pass
		30MHz~26GHz	Fig.52	Pass
	11	2.462GHz	Fig.53	Pass
		30MHz~26GHz	Fig.54	Pass
802.11n (40MHz)	1	2.422GHz	Fig.55	Pass
		30MHz~26GHz	Fig.56	Pass
	6	2.442GHz	Fig.57	Pass
		30MHz~26GHz	Fig.58	Pass
	11	2.462GHz	Fig.59	Pass
		30MHz~26GHz	Fig.60	Pass

Conclusion: PASS

Test figure as below:



Fig.37 Conducted spurious emission: Ch1,11b,2412MHz



Fig.38 Conducted spurious emission: Ch1,11b,30MHz~26GHz



Fig.39 Conducted spurious emission: Ch6,11b,2437MHz



Fig.40 Conducted spurious emission: Ch6,11b,30MHz~26GHz



Fig.41 Conducted spurious emission: Ch11,11b,2462MHz



Fig.42 Conducted spurious emission: Ch11,11b,30MHz~26GHz



Fig.43 Conducted spurious emission: Ch1,11g,2412MHz



Fig.44 Conducted spurious emission: Ch1,11g,30MHz~26GHz



Fig.45 Conducted spurious emission: Ch6,11g,2437MHz



Fig.46 Conducted spurious emission: Ch6,11g,30MHz~26GHz



Fig.47 Conducted spurious emission: Ch11,11g,2462MHz



Fig.48 Conducted spurious emission: Ch11,11g,30MHz~26GHz



Fig.49 Conducted spurious emission: Ch1,11n,2412MHz



Fig.50 Conducted spurious emission: Ch1,11n,30MHz~26GHz



Fig.51 Conducted spurious emission: Ch6,11n,2437MHz



Fig.52 Conducted spurious emission: Ch6,11n,30MHz~26GHz



Fig.53 Conducted spurious emission: Ch11,11n,2462MHz



Fig.54 Conducted spurious emission: Ch11,11n,30MHz~26GHz



Fig.55 Conducted spurious emission: Ch1,11n(40M),2422MHz



Fig.56 Conducted spurious emission: Ch1,11n(40M),30MHz~26GHz



Fig.57 Conducted spurious emission: Ch6,11n(40M),2442MHz



Fig.58 Conducted spurious emission: Ch6,11n(40M),30MHz~26GHz



Fig.59 Conducted spurious emission: Ch11,11n(40M),2462MHz



Fig.60 Conducted spurious emission: Ch11,11n(40M),30MHz~26GHz

5.6 Transmitter Spurious Emission-Radiated

Specifications:	FCC 47 CFR Part 15.247, 15.205, 15.209
DUT Serial Number:	--
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	--

Limit

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see 15.205(c)).

Measurement Uncertainty:

Frequency Range	Uncertainty
30MHz ≤ f ≤ 2GHz	±1.13
2GHz ≤ f ≤3.6GHz	±1.16
3.6GHz ≤ f ≤8GHz	±2.45
8GHz ≤ f ≤12.75GHz	±2.99

Limit in restricted band:

Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)
30~88	100	40
88~216	150	43.5
216~960	200	46
Above 960	500	54

Test Procedure

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a non-conducting platform, the top of which is 80 cm above the reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, but it may be larger or smaller to accommodate various sized EUTs.

For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also ANSI C63.10-2013 section 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time (s)
30~1000	100KHz/300KHz	5
1000~4000	1MHz/1MHz	15
4000~18000	1MHz/1MHz	40
18000~26500	1MHz/1MHz	20

Test Result:

A “reference path loss” is established and ARpi is the attenuation of “reference path loss”, and including the gain of receive antenna , the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

ARpi= Cable loss + Antenna Gain-Preamplifier gain

Result=PMea + ARpi

Channel	Frequency Range	Test Results	Conclusion
Ch1	30MH-1GHz	Fig.61	Pass
	1GHz-3GHz	Fig.62	Pass
	3GHz-18GHz	Fig.63	Pass

Channel	Frequency Range	Test Results	Conclusion
Ch6	30MH-1GHz	Fig.64	Pass
	1GHz-3GHz	Fig.65	Pass

	3GHz-18GHz	Fig.66	Pass

Channel	Frequency Range	Test Results	Conclusion
Ch11	30MH-1GHz	Fig.67	Pass
	1GHz-3GHz	Fig.68	Pass
	3GHz-18GHz	Fig.69	Pass
All channels	18GHz-26GHz	Fig.70	Pass

Note: all the test data shown was peak detected.

Conclusion: PASS

Test graphs as below:



Fig.61 Radiated emission: Ch1, 30MHz-1GHz



Fig.62 Radiated emission: Ch1, 1GHz-3GHz



Fig.63 Radiated emission: Ch1, 3GHz-18GHz



Fig.64 Radiated emission:Ch6, 30MHz-1GHz



Fig.65 Radiated emission: Ch6, 1GHz-3GHz



Fig.66 Radiated emission: Ch6, 3GHz-18GHz



Fig.67 Radiated emission: Ch11, 30MHz-1GHz



Fig.68 Radiated emission: Ch11, 1GHz-3GHz



Fig.69 Radiated emission: Ch11, 3GHz-18GHz



Fig.70 Radiated emission: 18 GHz - 26 GHz

Test photo

See the Pic1- Pic 2 in document" PT200LSV _Wifi_BT_Test Setup Photos".

5.7 Power line Conducted Emissions

Specifications:	ANSI C63.10 voltage mains test
DUT Serial Number:	353081090308282
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa
Test Results:	--

Limit

The EUT meets the requirement of having a peak to average ratio of less than 13dB.

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Measurement Uncertainty:

Frequency Range	Uncertainty
150 kHz to 30 MHz	1.83

Limits of the conducted disturbance at the AC mains ports:

Frequency range	Limit(Quasi-peak)	Limit(Average)
0.15 MHz to 0.5 MHz	66 dBμV – 56 dBμV	56 dBμV – 46 dBμV
>0.5 MHz to 5MHz	56 dBμV	46 dBμV
>5 MHz to 30 MHz	60 dBμV	50 dBμV
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Setup

The EUT was placed in a shielding room. The WLAN TESTER was used to set the TX channel and power level. The ac adapter output is connected to Receiver through an AMN (Artificial Mains Network).



Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

The measurement is made according to Public notice FCC Public Notice KDB 558074, March 2000, and ANSI C63.10-2013.

Test Result:
Line L&N

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.551512	41.5	1000.0	9.000	On	L1	9.7	14.5	56.0
16.346194	39.4	1000.0	9.000	On	L1	9.9	20.6	60.0
16.464756	40.1	1000.0	9.000	On	L1	9.9	19.9	60.0
16.588694	40.5	1000.0	9.000	On	L1	9.9	19.5	60.0
16.789675	38.9	1000.0	9.000	On	L1	9.9	21.1	60.0
16.797106	38.7	1000.0	9.000	On	L1	9.9	21.3	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.558706	34.0	1000.0	9.000	On	L1	9.7	12.0	46.0
15.883188	29.1	1000.0	9.000	On	L1	9.9	20.9	50.0
16.314194	29.5	1000.0	9.000	On	L1	9.9	20.5	50.0
16.321056	29.3	1000.0	9.000	On	L1	9.9	20.7	50.0
16.757106	28.9	1000.0	9.000	On	L1	9.9	21.1	50.0
24.001881	42.5	1000.0	9.000	On	L1	9.9	7.5	50.0

Conclusion: PASS



Line L& N

Test photo

See the Pic3 in document" PT200LSV _Wifi_BT_Test Setup Photos".

Annex A EUT Photos

See the document" PT200LSV -External Photos".
See the document" PT200LSV -Internal Photos".

ANNEX B Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

End Of Report