

Radio Frequency Exposure

Graupner GmbH & Co. KG

FCC ID: ZKZ-33508

Product Description: Receiver GR-16 HoTT

Model No.: GR-16

Prepared for: Graupner GmbH & Co. KG

Henriettenstr. 94-96 D-73230 Kirchheim Teck, Germany

Prepared by: Shenzhen Laker Testing Technology Co., Ltd

15C , Block 1, Sunshine Huayi Building, Nanhai West Road,

Nanshan, Shenzhen, China

Tel: 86-755-27617110

Fax: 86-755-27617110

Report No.: LK11ER-00102E

Issue Date: May 26, 2011

Test Date: May 05~20, 2011

Test by:

Reviewed By:



Owen Li



Edmund Zou

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See FCC part 15.247(i) and §1.1307(b)(1) of this chapter.

EUT Specification

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT | Receiver GR-16 HoTT |
| Type of Modulation: | FHSS |
| Frequency Band: | 2404 MHz ~ 2474 MHz |
| Number of Channels: | 70 |
| Channel Bandwidth: | 1 MHz |
| Device category | <input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure ($S = 5mW/cm^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S = 1mW/cm^2$) |
| Antenna diversity | <input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity |
| Max. output power | 13.95dBm (24.83mW) |
| Antenna gain (Max) | 1.5 dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |
| Note: 1. The maximum output power is <u>13.95dBm (24.83mW)) at 2439MHz (with 1.5 numeric antenna gain.)</u> 2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser. | |

TEST RESULT

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field Strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Equation 1

Where d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW / cm²

Maximum Permissible Exposure

EUT Output Power=24.83mW

Numeric antenna gain=1.5

Substituting the MPE safe distance using $d=20$ cm into **Equation 1** :

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power Density in mW / cm²

$$\text{The power density } S = 0.000199 \times 24.83 \times 1.5 = 0.0074 \text{ mW / cm}^2$$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW / cm² even if the calculation indicates that the power density would be larger.)

Evaluation result : **PASS**