



# FCC RF Test Report

**APPLICANT** : Bullitt Group  
**EQUIPMENT** : Smart Phone  
**BRAND NAME** : LAND ROVER  
**MODEL NAME** : Explore  
**FCC ID** : ZL5AP01  
**STANDARD** : 27(M)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on May 11, 2018 and completely tested on May 18, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



---

Approved by: James Huang / Manager

***Sporton International (Kunshan) Inc.***

***No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China***



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test .....	5
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	6
1.7 Testing Location .....	7
1.8 Applicable Standards .....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Test Mode .....	8
2.2 Connection Diagram of Test System .....	9
2.3 Support Unit used in test configuration and system .....	9
2.4 Measurement Results Explanation Example .....	9
2.5 Frequency List of Low/Middle/High Channels .....	10
<b>3 CONDUCTED TEST ITEMS .....</b>	<b>11</b>
3.1 Measuring Instruments .....	11
3.2 Test Setup .....	11
3.3 Test Result of Conducted Test .....	11
3.4 Conducted Output Power and ERP/EIRP .....	12
3.5 Peak-to-Average Ratio .....	13
3.6 Occupied Bandwidth .....	14
3.7 Conducted Band Edge .....	15
3.8 Conducted Spurious Emission .....	16
3.9 Frequency Stability .....	17
<b>4 RADIATED TEST ITEMS .....</b>	<b>18</b>
4.1 Measuring Instruments .....	18
4.2 Test Setup .....	18
4.3 Test Result of Radiated Test .....	18
4.4 Radiated Spurious Emission .....	19
<b>5 LIST OF MEASURING EQUIPMENT .....</b>	<b>20</b>
<b>6 UNCERTAINTY OF EVALUATION .....</b>	<b>21</b>
<b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>	
<b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>	
<b>APPENDIX C. TEST SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG7N1019-02B	Rev. 01	Initial issue of report	Jun. 19, 2018

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 7)	EIRP < 2Watt	PASS	-
3.5	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7)	§27.53(m)(4)	PASS	-
3.8	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7)	< 55+10log <sub>10</sub> (P[Watts])	PASS	-
3.9	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7)	< 55+10log <sub>10</sub> (P[Watts])	PASS	Under limit 24.92 dB at 5051.000 MHz



# 1 General Description

## 1.1 Applicant

**Bullitt Group**

One Valpy, Valpy Street, Reading, Berkshire, England RG1 1AR

## 1.2 Manufacturer

**Bullitt Group**

One Valpy, Valpy Street, Reading, Berkshire, England RG1 1AR

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	LAND ROVER
Model Name	Explore
FCC ID	ZL5AP01
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/ Bluetooth v4.1 LE/Bluetooth v4.2 LE
IMEI Code	Conducted: 353930090005217/353930090010217 Radiation: 353930090005126/353930090010126
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to perform all tests.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz
Rx Frequency	LTE Band 7 : 2622.5MHz ~ 2687.5 MHz
Bandwidth	LTE Band 7 : 5MHz/ 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 7 : 23.70 dBm
Antenna Gain	LTE Band 7 : -0.20 dBi
Type of Modulation	QPSK / 16QAM

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 7		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2502.5 ~ 2567.5	4M51G7D	-	0.2234	4M51W7D	-	0.1841
10	2505.0 ~ 2565.0	9M09G7D	0.0021	0.2228	9M05W7D	-	0.1849
15	2507.5 ~ 2562.5	13M6G7D	-	0.2223	13M5W7D	-	0.1849
20	2510.0 ~ 2560.0	18M4G7D	-	0.2239	18M5W7D	-	0.1871

## 1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	TH01-KS	03CH04-KS	630927

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 27(M)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	7	-	-				v	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	7	-	-	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	7	-	-	v	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	7	-	-	v	v	v	v	v	v	v	v			v	v	v
Frequency Stability	7	-	-		v			v					v		v	
E.I.R.P	7	-	-	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	7	Worst Case													v	
Note	1. The mark “v” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															



## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 5.5 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.5 \text{ (dB)} \end{aligned}$$



## 2.5 Frequency List of Low/Middle/High Channels

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5


### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.

### 3.4 Conducted Output Power and EIRP

#### 3.4.1 Description of the Conducted Output Power Measurement and EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 7.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

## 3.5 Peak-to-Average Ratio

### 3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

## 3.6 Occupied Bandwidth

### 3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.  
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log (P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW  $\geq 1\%$  EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. Offset has included the duty factor for LTE Band 38. Duty factor  $= 10 \log (1/x)$ , where x is the measured duty cycle
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from  $43 + 10 \log (P)$  dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10 \log (P)] \text{ (dB)}$$

$$= [30 + 10 \log (P)] \text{ (dBm)} - [43 + 10 \log (P)] \text{ (dB)} = -13 \text{ dBm.}$$

10. For LTE Band 7, 38, the other 40 dB, and 55 dB have additionally applied same calculation above.

## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For Band 7:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $55 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Offset has included the duty factor for LTE Band 38. Duty factor =  $10 \log (1/x)$ , where x is the measured duty cycle.
9. Taking the record of maximum spurious emission.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from  $43 + 10 \log (P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10 \log (P)]$  (dB)  
 $= [30 + 10 \log (P)]$  (dBm) -  $[43 + 10 \log (P)]$  (dB)  
 $= -13$  dBm.
12. For Band 7  
The limit line is derived from  $55 + 10 \log (P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [55 + 10 \log (P)]$  (dB)  
 $= [30 + 10 \log (P)]$  (dBm) -  $[55 + 10 \log (P)]$  (dB)  
 $= -25$  dBm.



### 3.9 Frequency Stability

#### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.

## 4.4 Radiated Spurious Emission

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For Band 7

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $55 + 10 \log (P)$  dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

13. For Band 7:

The limit line is derived from  $55 + 10\log(P)$ dB below the transmitter power P(Watts)



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	May 15, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Radio communication analyzer	Anritsu	MT8820C	6201300652	2G/3G/LTE_ full band	Aug. 08, 2017	May 15, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 12, 2017	May 15, 2018	Oct. 11, 2018	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44GHz	Oct. 10, 2017	May 18, 2018	Oct. 09, 2018	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Jan. 29, 2018	May 18, 2018	Jan. 28, 2019	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Dec. 16, 2017	May 18, 2018	Dec. 15, 2018	Radiation (03CH04-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	May 18, 2018	Feb. 06, 2019	Radiation (03CH04-KS)
Amplifier	Burgeon	BPA-530	102219	0.01MHz ~3000MHz	Dec. 16, 2017	May 18, 2018	Dec. 15, 2018	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 OP	2025788	1Ghz-18Ghz	Apr. 17, 2018	May 18, 2018	Apr. 16, 2019	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35 -HG	2014749	18~40GHz	Feb. 08, 2018	May 18, 2018	Feb. 07, 2019	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Dec. 16, 2017	May 18, 2018	Dec. 15, 2018	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 18, 2018	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 18, 2018	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 18, 2018	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.3dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.8dB
---	-------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.70	23.66	23.62
20	1	49		23.64	23.60	23.56
20	1	99		23.66	23.63	23.60
20	50	0		22.76	22.76	22.74
20	50	24		22.74	22.71	22.66
20	50	50		22.70	22.64	22.56
20	100	0		22.71	22.69	22.64
20	1	0	16-QAM	22.84	22.92	22.86
20	1	49		22.87	22.86	22.83
20	1	99		22.90	22.88	22.87
20	50	0		21.71	21.73	21.72
20	50	24		21.72	21.69	21.66
20	50	50		21.67	21.62	21.55
20	100	0		21.68	21.66	21.63
15	1	0	QPSK	23.65	23.63	23.58
15	1	37		23.67	23.62	23.59
15	1	74		23.65	23.63	23.60
15	36	0		22.71	22.70	22.66
15	36	20		22.72	22.69	22.64
15	36	39		22.69	22.67	22.59
15	75	0		22.71	22.68	22.64
15	1	0	16-QAM	22.83	22.85	22.82
15	1	37		22.86	22.81	22.81
15	1	74		22.87	22.84	22.83
15	36	0		21.68	21.70	21.66
15	36	20		21.70	21.69	21.63
15	36	39		21.68	21.65	21.59
15	75	0		21.69	21.67	21.63



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.61	23.59	23.54
10	1	25		23.65	23.61	23.58
10	1	49		23.68	23.65	23.61
10	25	0		22.65	22.67	22.61
10	25	12		22.70	22.66	22.60
10	25	25		22.70	22.62	22.56
10	50	0		22.69	22.68	22.61
10	1	0	16-QAM	22.77	22.78	22.77
10	1	25		22.83	22.80	22.82
10	1	49		22.87	22.84	22.86
10	25	0		21.62	21.66	21.61
10	25	12		21.69	21.66	21.61
10	25	25		21.68	21.61	21.54
10	50	0		21.67	21.67	21.60
5	1	0	QPSK	23.62	23.59	23.54
5	1	12		23.69	23.65	23.62
5	1	24		23.64	23.59	23.57
5	12	0		22.64	22.62	22.59
5	12	7		22.70	22.64	22.62
5	12	13		22.69	22.65	22.60
5	25	0		22.67	22.65	22.61
5	1	0	16-QAM	22.78	22.79	22.75
5	1	12		22.85	22.83	22.80
5	1	24		22.82	22.81	22.76
5	12	0		21.62	21.62	21.61
5	12	7		21.69	21.66	21.63
5	12	13		21.69	21.65	21.59
5	25	0		21.66	21.64	21.60

**EIRP**

LTE Band 7 (GT - LC = -0.20 dBi) QPSK			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency	2502.5	2535	2567.5
(MHz)			
Conducted Power (dBm)	23.69	23.65	23.62
Conducted Power (Watts)	0.2339	0.2317	0.2301
EIRP(dBm)	23.49	23.45	23.42
EIRP(Watts)	0.2234	0.2213	0.2198

LTE Band 7 (GT - LC = -0.20 dBi) QPSK									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
(MHz)									
Conducted Power (dBm)	23.68	23.65	23.61	23.67	23.62	23.59	23.70	23.66	23.62
Conducted Power (Watts)	0.2333	0.2317	0.2296	0.2328	0.2301	0.2286	0.2344	0.2323	0.2301
EIRP(dBm)	23.48	23.45	23.41	23.47	23.42	23.39	23.50	23.46	23.42
EIRP(Watts)	0.2228	0.2213	0.2193	0.2223	0.2198	0.2183	0.2239	0.2218	0.2198





LTE Band 7 (GT - LC = -0.20 dBi) 16QAM			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency	2502.5	2535	2567.5
(MHz)			
Conducted Power (dBm)	22.85	22.83	22.80
Conducted Power (Watts)	0.1928	0.1919	0.1905
EIRP(dBm)	22.65	22.63	22.60
EIRP(Watts)	0.1841	0.1832	0.1820

LTE Band 7 (GT - LC = -0.20 dBi) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
(MHz)									
Conducted Power (dBm)	22.87	22.84	22.86	22.87	22.84	22.83	22.84	22.92	22.86
Conducted Power (Watts)	0.1936	0.1923	0.1932	0.1936	0.1923	0.1919	0.1923	0.1959	0.1932
EIRP(dBm)	22.67	22.64	22.66	22.67	22.64	22.63	22.64	22.72	22.66
EIRP(Watts)	0.1849	0.1837	0.1845	0.1849	0.1837	0.1832	0.1837	0.1871	0.1845



## LTE Band 7


### Peak-to-Average Ratio

Mode	LTE Band 7 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.64	5.1	4.87	6.09	<b>PASS</b>
Middle CH	4.38	4.96	5.36	5.91	
Highest CH	5.25	5.16	5.39	6.12	




## LTE Band 7 / 20MHz / QPSK


## Lowest Channel / 1RB




## Lowest Channel / Full RB




## Middle Channel / 1RB




## Middle Channel / Full RB



## Highest Channel / 1RB




## Highest Channel / Full RB






## LTE Band 7 / 20MHz / 16QAM

## Lowest Channel / 1RB




Date: 15 MAY 2018 20:51:52

## Lowest Channel / Full RB




Date: 15 MAY 2018 20:52:05

## Middle Channel / 1RB




Date: 15 MAY 2018 20:53:02

## Middle Channel / Full RB



Date: 15 MAY 2018 20:52:48

## Highest Channel / 1RB



Date: 15 MAY 2018 20:53:33

## Highest Channel / Full RB



Date: 15 MAY 2018 20:53:44


**26dB Bandwidth**

Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.925	4.915	9.63	9.97	14.296	14.655	20.42	20.22
Middle CH	-	-	-	-	5.065	4.875	9.93	9.85	14.266	14.326	20.539	20.22
Highest CH	-	-	-	-	4.935	4.985	9.75	9.83	14.565	14.146	20.34	20.14




## LTE Band 7

## Lowest Channel / 5MHz / QPSK




Date: 15 MAY 2018 18:48:35

## Lowest Channel / 5MHz / 16QAM




Date: 15 MAY 2018 18:48:56

## Middle Channel / 5MHz / QPSK




Date: 15 MAY 2018 18:57:54

## Middle Channel / 5MHz / 16QAM




Date: 15 MAY 2018 18:57:33

## Highest Channel / 5MHz / QPSK



Date: 15 MAY 2018 18:58:15

## Highest Channel / 5MHz / 16QAM




Date: 15 MAY 2018 18:58:37




## LTE Band 7


## Lowest Channel / 10MHz / QPSK




## Lowest Channel / 10MHz / 16QAM




## Middle Channel / 10MHz / QPSK




## Middle Channel / 10MHz / 16QAM



## Highest Channel / 10MHz / QPSK




## Highest Channel / 10MHz / 16QAM






## LTE Band 7

## Lowest Channel / 15MHz / QPSK




Date: 15 MAY 2018 19:48:23

## Lowest Channel / 15MHz / 16QAM




Date: 15 MAY 2018 19:48:44

## Middle Channel / 15MHz / QPSK




Date: 15 MAY 2018 19:57:42

## Middle Channel / 15MHz / 16QAM




Date: 15 MAY 2018 19:57:21

## Highest Channel / 15MHz / QPSK



Date: 15 MAY 2018 19:58:04

## Highest Channel / 15MHz / 16QAM




Date: 15 MAY 2018 19:58:25






## LTE Band 7

## Lowest Channel / 20MHz / QPSK




Date: 15 MAY 2018 20:05:10

## Lowest Channel / 20MHz / 16QAM




Date: 15 MAY 2018 20:05:32

## Middle Channel / 20MHz / QPSK




Date: 15 MAY 2018 20:14:29

## Middle Channel / 20MHz / 16QAM




Date: 15 MAY 2018 20:14:08

## Highest Channel / 20MHz / QPSK



Date: 15 MAY 2018 20:14:51

## Highest Channel / 20MHz / 16QAM



Date: 15 MAY 2018 20:15:12


**Occupied Bandwidth**

Mode	LTE Band 7 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.51	4.51	9.09	9.01	13.55	13.52	18.42	18.42
Middle CH	-	-	-	-	4.51	4.5	9.07	9.01	13.43	13.46	18.34	18.38
Highest CH	-	-	-	-	4.48	4.48	9.07	9.05	13.46	13.43	18.42	18.46




## LTE Band 7

## Lowest Channel / 5MHz / QPSK




Date: 15 MAY 2018 18:48:24

## Lowest Channel / 5MHz / 16QAM




Date: 15 MAY 2018 18:48:46

## Middle Channel / 5MHz / QPSK




Date: 15 MAY 2018 18:57:44

## Middle Channel / 5MHz / 16QAM




Date: 15 MAY 2018 18:57:22

## Highest Channel / 5MHz / QPSK



Date: 15 MAY 2018 18:58:05

## Highest Channel / 5MHz / 16QAM




Date: 15 MAY 2018 18:58:26




## LTE Band 7


## Lowest Channel / 10MHz / QPSK




## Lowest Channel / 10MHz / 16QAM




## Middle Channel / 10MHz / QPSK




## Middle Channel / 10MHz / 16QAM



## Highest Channel / 10MHz / QPSK




## Highest Channel / 10MHz / 16QAM






## LTE Band 7

## Lowest Channel / 15MHz / QPSK




Date: 15 MAY 2018 19:48:13

## Lowest Channel / 15MHz / 16QAM




Date: 15 MAY 2018 19:48:34

## Middle Channel / 15MHz / QPSK




Date: 15 MAY 2018 19:57:32

## Middle Channel / 15MHz / 16QAM




Date: 15 MAY 2018 19:57:10

## Highest Channel / 15MHz / QPSK



Date: 15 MAY 2018 19:57:53

## Highest Channel / 15MHz / 16QAM




Date: 15 MAY 2018 19:58:14




## LTE Band 7

## Lowest Channel / 20MHz / QPSK




Date: 15 MAY 2018 20:05:00

## Lowest Channel / 20MHz / 16QAM




Date: 15 MAY 2018 20:05:21

## Middle Channel / 20MHz / QPSK




Date: 15 MAY 2018 20:14:19

## Middle Channel / 20MHz / 16QAM




Date: 15 MAY 2018 20:15:57

## Highest Channel / 20MHz / QPSK



Date: 15 MAY 2018 20:14:40

## Highest Channel / 20MHz / 16QAM




Date: 15 MAY 2018 20:15:01




## Conducted Band Edge

### LTE Band 7 / 5MHz / QPSK


#### Lowest Band Edge / 1 RB




#### Highest Band Edge / 1 RB



#### Lowest Band Edge / Full RB




#### Highest Band Edge / Full RB






## LTE Band 7 / 5MHz / 16QAM


## Lowest Band Edge / 1 RB



## Highest Band Edge / 1 RB



## Lowest Band Edge / Full RB



## Highest Band Edge / Full RB

