LTE Band 12

Peak-to-Average Ratio


Mode					
Mod.	QPSK 16QAM				Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.88	4.99	5.42	6	
Middle CH	4.29	4.87	4.93	6	PASS
Highest CH	4.03	4.78	5.22	5.83	


Report No.: FG552956B

Report Template No.: BU5-FGLTE Version 1.3

SPORTON INTERNATIONAL INC. Page Number : A12-1 of 31

TEL: 886-3-327-3456 FAX: 886-3-328-4978





26dB Bandwidth

Mode		LTE Band 12 : 26dB BW(MHz)										
BW	1.41	ИНz	31/	lHz	5N	lHz	10	ИHz	15N	ИHz	201	ИHz
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.29	1.3	3.05	2.97	5.05	5.06	10.01	10.09	-	-	-	-
Middle CH	1.28	1.3	3.04	3.05	5	5.05	9.93	9.99	-	-	-	-
Highest CH	1.28	1.3	3.05	3.06	5.07	5.08	10.03	9.99	-	-	-	-


Report No.: FG552956B

SPORTON INTERNATIONAL INC. Page Number : A12-4 of 31

TEL: 886-3-327-3456


FAX: 886-3-328-4978

Report Template No.: BU5-FGLTE Version 1.3




Page Number : A12-5 of 31

Report Template No.: BU5-FGLTE Version 1.3




Page Number : A12-6 of 31

Report Template No.: BU5-FGLTE Version 1.3



Page Number : A12-7 of 31

Report Template No.: BU5-FGLTE Version 1.3



Page Number : A12-8 of 31

Report Template No.: BU5-FGLTE Version 1.3

Occupied Bandwidth

Mode	LTE Band 12 : 99%OBW(MHz)											
BW	1.41	MHz	3N	lHz	5N	lHz	101	ИHz	15N	ИНz	201	ИHz
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.73	2.73	4.5	4.51	9.09	9.03	-	-	-	-
Middle CH	1.09	1.09	2.72	2.73	4.5	4.5	9.01	9.01	-	-	-	-
Highest CH	1.09	1.1	2.73	2.74	4.51	4.51	9.01	9.03	-	-	-	-

Report No.: FG552956B

SPORTON INTERNATIONAL INC. Page Number : A12-9 of 31

TEL: 886-3-327-3456


FAX: 886-3-328-4978

Report Template No.: BU5-FGLTE Version 1.3




Page Number : A12-10 of 31

Report No.: FG552956B




Page Number : A12-11 of 31

Report No.: FG552956B



Page Number : A12-12 of 31

Report No.: FG552956B




TEL: 886-3-327-3456

Conducted Band Edge

Report No.: FG552956B


SPORTON INTERNATIONAL INC. Page Number: A12-14 of 31

FAX: 886-3-328-4978 Report Template No.: BU5-FGLTE Version 1.3




Page Number : A12-15 of 31

Report No.: FG552956B




TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-16 of 31

Report No.: FG552956B




Page Number : A12-17 of 31


Report Template No.: BU5-FGLTE Version 1.3



TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-18 of 31


Report Template No.: BU5-FGLTE Version 1.3






Page Number : A12-20 of 31

Report Template No.: BU5-FGLTE Version 1.3



TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-21 of 31

Report No.: FG552956B



TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-22 of 31

Report Template No.: BU5-FGLTE Version 1.3

Conducted Spurious Emission

Report No.: FG552956B

SPORTON INTERNATIONAL INC. Page Number: A12-23 of 31

TEL: 886-3-327-3456


FAX: 886-3-328-4978

Report Template No.: BU5-FGLTE Version 1.3



TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-24 of 31

Report Template No.: BU5-FGLTE Version 1.3




TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-25 of 31

Report Template No.: BU5-FGLTE Version 1.3



Page Number : A12-26 of 31

Report Template No.: BU5-FGLTE Version 1.3





TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-28 of 31

Report No.: FG552956B



TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A12-29 of 31

Report Template No.: BU5-FGLTE Version 1.3

Frequency Stability

Test Conditions		LTE Band 12 (QPSK) / Middle Channel	Limit	
_		BW 10MHz	Note 2.	
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result	
50	Normal Voltage	0.0082		
40	Normal Voltage	0.0011		
30	Normal Voltage	0.0076		
20(Ref.)	Normal Voltage	0.0000		
10	Normal Voltage	0.0082		
0	Normal Voltage	0.0007		
-10	Normal Voltage	0.0006	PASS	
-20	Normal Voltage	0.0079		
-30	Normal Voltage	0.0073		
20	Maximum Voltage	0.0014		
20	Normal Voltage	0.0000		
20	Battery End Point	0.0086		

Report No.: FG552956B

Note:

- 1. Normal Voltage = 3.9V. ; Battery End Point (BEP) = 3.4 V. ; Maximum Voltage =4.35 V
- 2. Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

SPORTON INTERNATIONAL INC. Page Number : A12-30 of 31

TEL: 886-3-327-3456

FAX: 886-3-328-4978

Report Template No.: BU5-FGLTE Version 1.3

Test Conditions		LTE Band 12 (QPSK) / Middle Channel	Limit
Tamananatana	Valtana	BW 5MHz	Within Band
Temperature (°C)	Voltage (Volt)	Frequency Offset (∆f) (Hz)	Result
50	Normal Voltage	5.8	
40	Normal Voltage	0.8	
30	Normal Voltage	5.4	
20(Ref.)	Normal Voltage	0	
10	Normal Voltage	5.8	
0	Normal Voltage	0.5	
-10	Normal Voltage	-0.4	PASS
-20	Normal Voltage	5.6	
-30	Normal Voltage	5.2	
20	Maximum Voltage	1	
20	Normal Voltage	0	
20	Battery End Point	6.1	

Report No.: FG552956B

Report Template No.: BU5-FGLTE Version 1.3

 $|MAX(\Delta f)|$ 6.1= Hz

Frequency Stability	Frequency (MHz)	Limit Line	Result
$f_L - MAX(\Delta f) $	699.099994	≥ 698 MHz	DACC
f _H + MAX(∆f)	715.896006	≦ 716 MHz	PASS

SPORTON INTERNATIONAL INC. Page Number: A12-31 of 31

TEL : 886-3-327-3456 FAX : 886-3-328-4978