

TEST REPORT

For

**Electronics Technology (Dongguan) Company Limited**

No.161, Xin Min Road, Tong Luo Wei Industrial Zone,  
Jin Xia, Chang An Town, Dong Guan, Guang Dong, China

**FCC ID: ZL9M72T2**

|  |                             |
|--|-----------------------------|
| <b>Report Type:</b><br>Original Report   | <b>Product Type:</b><br>MID |
| <b>Test Engineer:</b> Jimmy Xiao <i>Jimmy Xiao</i>   |                             |
| <b>Report Number:</b> RSZ110518001-00B   |                             |
| <b>Report Date:</b> 2011-08-29   |                             |
| <b>Reviewed By:</b> EMC Engineer<br>Merry Zhao <i>Merry Zhao</i>   |                             |
| <b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F, the 3rd Phase of WanLi Industrial Building,<br>ShiHua Road, FuTian Free Trade Zone<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                             |

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

## **TABLE OF CONTENTS**

|  |           |
|--|-----------|
| <b>GENERAL INFORMATION.....</b>  | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....               | 4         |
| OBJECTIVE .....  | 4         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                     | 4         |
| TEST METHODOLOGY .....   | 4         |
| TEST FACILITY .....  | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                  | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                | 6         |
| EUT EXERCISE SOFTWARE .....  | 6         |
| EQUIPMENT MODIFICATIONS .....  | 6         |
| EXTERNAL I/O CABLE.....  | 6         |
| CONFIGURATION OF TEST SETUP .....                                      | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                      | 7         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                   | <b>8</b>  |
| <b>FCC §15.247 (i) &amp; §2.1093 - RF EXPOSURE INFORMATION .....</b>   | <b>9</b>  |
| APPLICABLE STANDARD .....  | 9         |
| TEST RESULT .....  | 9         |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                          | <b>10</b> |
| APPLICABLE STANDARD .....  | 10        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                   | 10        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>             | <b>11</b> |
| APPLICABLE STANDARD .....  | 11        |
| MEASUREMENT UNCERTAINTY .....  | 11        |
| EUT SETUP.....   | 11        |
| EMI TEST RECEIVER SETUP.....   | 12        |
| TEST PROCEDURE .....   | 12        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 12        |
| TEST RESULTS SUMMARY .....   | 12        |
| TEST DATA .....  | 12        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b> | <b>15</b> |
| APPLICABLE STANDARD .....  | 15        |
| MEASUREMENT UNCERTAINTY .....  | 15        |
| EUT SETUP.....   | 15        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                      | 16        |
| TEST PROCEDURE .....   | 16        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                         | 16        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 17        |
| TEST RESULTS SUMMARY .....   | 17        |
| TEST DATA .....  | 17        |
| <b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>               | <b>25</b> |
| APPLICABLE STANDARD .....  | 25        |
| TEST PROCEDURE .....   | 25        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 25        |
| TEST DATA .....  | 25        |

|   |           |
|---|-----------|
| <b>FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER .....</b>           | <b>30</b> |
| APPLICABLE STANDARD .....   | 30        |
| TEST PROCEDURE .....  | 30        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 30        |
| TEST DATA .....   | 30        |
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b> | <b>38</b> |
| APPLICABLE STANDARD .....   | 38        |
| TEST PROCEDURE .....  | 38        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 38        |
| TEST DATA .....   | 38        |
| <b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>                  | <b>42</b> |
| APPLICABLE STANDARD .....   | 42        |
| TEST PROCEDURE .....  | 42        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 42        |
| TEST DATA .....   | 42        |
| <b>PRODUCT SIMILARITY DECLARATION LETTER.....</b>                     | <b>47</b> |

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *ELECTRONICS TECHNOLOGY (DONG GUAN) COMPANY LIMITED*'s product, model number: *M72T2 (FCC ID: ZL9M72T2)* ("EUT") in this report is a *MID*, which was measured approximately: 19.75 cm (L) x 14.2 cm (W) x 0.85 cm (H), rated input voltage: DC 5V adapter or 3.7V battery.

Adapter information:

Model: ZDA050150US

Input: AC 100-240V, 50/60Hz, 0.35 A

Output: DC 5.0 V, 1500 mA

*Note: The series product, model M72T2, M72C2 and M72J2 are electrically identical, they are just different in model names and appearance due to marketing purposes, and we select M72T2 for fully testing, which was explained in the attached declaration letter.*

*\* All measurement and test data in this report was gathered from production sample serial number: 1105093 (Assigned by applicant). The EUT was received on 2011-05-18.*

### Objective

This report is prepared on behalf of *ELECTRONICS TECHNOLOGY (DONG GUAN) COMPANY LIMITED* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15 Class B submission with FCC ID: ZL9M72T2

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is  $\pm 0.96$  dB, the uncertainty of any radiation on emissions measurement is  $\pm 4.0$  dB

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b and 802.11g mode, 11 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 7       | 2442            |
| 2       | 2417            | 8       | 2447            |
| 3       | 2422            | 9       | 2452            |
| 4       | 2427            | 10      | 2457            |
| 5       | 2432            | 11      | 2462            |
| 6       | 2437            | /       | /               |

EUT was tested with Channel 1, 6 and 11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### EUT Exercise Software

The test was performed under QualDiag.exe which was provided by the manufacturer:

802.11b: TX Power level 16, data rate: 1 Mbps.

802.11g: TX Power level 10, data rate: 6 Mbps.


### Equipment Modifications

No modification was made to the EUT tested.


### External I/O Cable

| Cable Description                                | Length (m) | From Port | To  |
|--|------------|-----------|-----|
| Unshielded Detachable DC Power Cable with a Core | 1.8        | Adapter   | EUT |

## Configuration of Test Setup



## Block Diagram of Test Setup



## SUMMARY OF TEST RESULTS

| FCC Rules                       | Description of Test                      | Result      |
|---------------------------------|--|-------------|
| §15.247 (i), §2.1093            | RF Exposure Information                  | Compliance* |
| §15.203                         | Antenna Requirement                      | Compliance  |
| §15.207 (a)                     | AC Line Conducted Emissions              | Compliance  |
| §15.247(d)                      | Spurious Emissions at Antenna Port       | Compliance  |
| §15.205, §15.209,<br>§15.247(d) | Spurious Emissions                       | Compliance  |
| §15.247 (a)(2)                  | 6 dB Emission Bandwidth                  | Compliance  |
| §15.247(b)(3)                   | Maximum Peak Output Power                | Compliance  |
| §15.247(d)                      | 100 kHz Bandwidth of Frequency Band Edge | Compliance  |
| §15.247(e)                      | Power Spectral Density                   | Compliance  |

Note: \* Please refer to the SAR report RSZ110518001-20



---

## **FCC §15.247 (i) & §2.1093 - RF EXPOSURE INFORMATION**

---

### **Applicable Standard**

According to FCC §15.247 (i) & §2.1093

### **Test Result**

Compliance\*: Please refer to the SAR report RSZ110518001-20

---

## FCC §15.203 - ANTENNA REQUIREMENT

---

### Applicable Standard

According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Antenna Connector Construction

The EUT used internal fixed antennas, which complied with 15.203, the maximum gain is 0 dBi, please refer to the internal photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard


FCC §15.207

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is  $\pm 2.4$  dB ( $k=2$ , 95% level of confidence).

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source,

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| <b><i>Frequency Range</i></b> | <b><i>IF B/W</i></b> |
|-------------------------------|----------------------|
| 150 kHz – 30 MHz              | 9 kHz                |

## Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

| <b>Manufacturer</b> | <b>Description</b> | <b>Model</b> | <b>Serial Number</b> | <b>Calibration Date</b> | <b>Calibration Due Date</b> |
|---------------------|--------------------|--------------|----------------------|-------------------------|-----------------------------|
| Rohde & Schwarz     | EMI Test Receiver  | ESCS30       | 830245               | 2011-03-03              | 2012-03-02                  |
| Rohde & Schwarz     | L.I.S.N.           | ESH2-Z5      | 892107/021           | 2011-03-09              | 2012-03-08                  |

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**13.48 dB at 1.655 MHz** in the **Line** conducted mode

## Test Data


### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 ° C    |
| <b>Relative Humidity:</b> | 56 %      |
| <b>ATM Pressure:</b>      | 100.0 kPa |


*The testing was performed by Jimmy Xiao on 2011-07-06.*

*Test Mode: Transmitting*

120 V, 60 Hz, Line:



| Conducted Emissions<br>FCC Part 15.207 |                         |                        |              |             |                       |
|--|-------------------------|------------------------|--------------|-------------|-----------------------|
| Frequency (MHz)                        | Corrected Result (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/QP/Ave.) |
| 1.655                                  | 32.52                   | 10.13                  | 46.00        | 13.48       | Ave.                  |
| 0.885                                  | 32.20                   | 10.11                  | 46.00        | 13.80       | Ave.                  |
| 0.310                                  | 36.93                   | 10.10                  | 51.43        | 14.50       | Ave.                  |
| 0.895                                  | 38.35                   | 10.11                  | 56.00        | 17.65       | QP                    |
| 1.655                                  | 38.25                   | 10.13                  | 56.00        | 17.75       | QP                    |
| 0.310                                  | 41.88                   | 10.10                  | 61.43        | 19.55       | QP                    |
| 0.400                                  | 29.13                   | 10.10                  | 48.86        | 19.73       | Ave.                  |
| 0.400                                  | 37.60                   | 10.10                  | 58.86        | 21.26       | QP                    |
| 3.590                                  | 23.97                   | 10.17                  | 46.00        | 22.03       | Ave.                  |
| 0.185                                  | 42.57                   | 10.10                  | 65.00        | 22.43       | QP                    |
| 3.560                                  | 28.30                   | 10.17                  | 56.00        | 27.70       | QP                    |
| 0.185                                  | 25.93                   | 10.10                  | 55.00        | 29.07       | Ave.                  |

**120V, 60 Hz, Neutral:**

| Conducted Emissions<br>FCC Part 15.207 |                               |                              |                 |                |                           |
|--|-------------------------------|------------------------------|-----------------|----------------|---------------------------|
| Frequency<br>(MHz)                     | Corrected<br>Result<br>(dBμV) | Correction<br>Factor<br>(dB) | Limit<br>(dBμV) | Margin<br>(dB) | Detector<br>(PK /QP/Ave.) |
| 0.885                                  | 30.25                         | 10.11                        | 46.00           | 15.75          | Ave.                      |
| 1.790                                  | 30.00                         | 10.13                        | 46.00           | 16.00          | Ave.                      |
| 0.300                                  | 32.51                         | 10.10                        | 51.71           | 19.20          | Ave.                      |
| 2.495                                  | 26.45                         | 10.14                        | 46.00           | 19.55          | Ave.                      |
| 0.885                                  | 35.58                         | 10.11                        | 56.00           | 20.42          | QP                        |
| 1.790                                  | 34.09                         | 10.13                        | 56.00           | 21.91          | QP                        |
| 0.300                                  | 38.06                         | 10.10                        | 61.71           | 23.65          | QP                        |
| 0.285                                  | 37.29                         | 10.10                        | 62.14           | 24.85          | QP                        |
| 1.325                                  | 31.00                         | 10.12                        | 56.00           | 25.00          | QP                        |
| 1.325                                  | 20.86                         | 10.12                        | 46.00           | 25.14          | Ave.                      |
| 0.285                                  | 26.48                         | 10.10                        | 52.14           | 25.66          | Ave.                      |
| 2.510                                  | 29.31                         | 10.14                        | 56.00           | 26.69          | QP                        |

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 4.0$  dB(k=2, 95% level of confidence) .

### EUT Setup

#### Below 1GHz:



#### Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source,

### EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| <i><b>Frequency Range</b></i> | <i><b>RBW</b></i> | <i><b>Video B/W</b></i> | <i><b>Detector</b></i> |
|-------------------------------|-------------------|-------------------------|------------------------|
| 30 MHz – 1000 MHz             | 100 kHz           | 300 kHz                 | QP                     |
| 1000 MHz – 25 GHz             | 1 MHz             | 3 MHz                   | PK                     |
| 1000 MHz – 25 GHz             | 1 MHz             | 10 Hz                   | Ave.                   |

### Test Procedure

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$



## Test Equipment List and Details

| Manufacturer    | Description       | Model    | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|----------|---------------|------------------|----------------------|
| HP              | Amplifier         | HP8447D  | 2944A09795    | 2010-08-02       | 2011-08-01           |
| Rohde & Schwarz | EMI Test Receiver | ESCI     | 100035        | 2010-11-11       | 2011-11-10           |
| Sunol Sciences  | Broadband Antenna | JB1      | A040904-1     | 2011-07-05       | 2012-07-04           |
| Mini-circuits   | Amplifier         | ZVA-213+ | T-E27H        | 2011-03-08       | 2012-03-07           |
| Sunol Sciences  | Horn Antenna      | DRH-118  | A052604       | 2011-05-05       | 2012-05-04           |
| HP              | Spectrum Analyzer | 8593A    | 51475684      | 2011-07-08       | 2012-07-07           |
| Rohde & Schwarz | Spectrum Analyzer | FSEM30   | 849720/019    | 2011-07-08       | 2012-07-07           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

**6.68 dB at 4824.00 MHz in the Horizontal polarization (802.11b mode)**

## Test Data


### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 ° C    |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Jimmy Xiao on 2011-07-13.*

Test Mode: Transmitting

**1) Below 1 GHz (worse case):**



| Frequency (MHz) | Corrected Amplitude (dBμV/m) | Ant. Height (cm) | Ant. Polarity (H/V) | Turntable Position (degree) | Correction Factor (dB) | Limit (dBμV/m) | Margin (dB) |
|-----------------|------------------------------|------------------|---------------------|-----------------------------|------------------------|----------------|-------------|
| 274.914500      | 34.8                         | 100.0            | H                   | 84.0                        | -12.9                  | 46.0           | 11.2        |
| 392.722750      | 33.0                         | 100.0            | H                   | 317.0                       | -10.1                  | 46.0           | 13.0        |
| 117.815750      | 26.9                         | 284.0            | H                   | 273.0                       | -12.6                  | 43.5           | 16.6        |
| 215.998750      | 25.9                         | 157.0            | H                   | 124.0                       | -14.1                  | 43.5           | 17.6        |
| 30.425081       | 20.0                         | 124.0            | V                   | 58.0                        | -5.7                   | 40.0           | 20.0        |
| 176.786250      | 23.2                         | 173.0            | H                   | 111.0                       | -15.2                  | 43.5           | 20.3        |

**2) Above 1 GHz:**

802.11b Mode:

| Indicated                 |                           | Detector<br>(PK/Ave.) | Table<br>Angle<br>Degree | Test Antenna  |                | Correction Factor        |                       |                      | FCC Part 15.247/15.209    |                   |                |          |
|---------------------------|---------------------------|-----------------------|--------------------------|---------------|----------------|--------------------------|-----------------------|----------------------|---------------------------|-------------------|----------------|----------|
| Frequency<br>(MHz)        | S.A.<br>Reading<br>(dBμV) |                       |                          | Height<br>(m) | Polar<br>(H/V) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Pre-<br>Amp.<br>(dB) | Cord.<br>Amp.<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Comment  |
| Low Channel (2412 MHz)    |                           |                       |                          |               |                |                          |                       |                      |                           |                   |                |          |
| 4824.00                   | 33.47                     | Ave.                  | 220                      | 1.3           | H              | 36.3                     | 4.3                   | 26.75                | 47.32                     | 54                | 6.68           | harmonic |
| 4824.00                   | 31.26                     | Ave.                  | 180                      | 1.5           | V              | 33.6                     | 4.3                   | 26.75                | 42.41                     | 54                | 11.59          | harmonic |
| 4824.00                   | 48.22                     | PK                    | 220                      | 1.3           | H              | 36.3                     | 4.3                   | 26.75                | 62.07                     | 74                | 11.93          | harmonic |
| 4824.00                   | 44.01                     | PK                    | 180                      | 1.5           | V              | 33.6                     | 4.3                   | 26.75                | 55.16                     | 74                | 18.84          | harmonic |
| 1350.14                   | 30.25                     | Ave.                  | 330                      | 1.8           | H              | 25.6                     | 2.14                  | 26.56                | 31.43                     | 54                | 22.57          | spurious |
| 1350.14                   | 29.87                     | Ave.                  | 170                      | 1.1           | V              | 25.6                     | 2.14                  | 26.56                | 31.05                     | 54                | 22.95          | spurious |
| 1350.14                   | 44.56                     | PK                    | 330                      | 1.8           | H              | 25.6                     | 2.14                  | 26.56                | 45.74                     | 74                | 28.26          | spurious |
| 1350.14                   | 40.54                     | PK                    | 170                      | 1.1           | V              | 25.6                     | 2.14                  | 26.56                | 41.72                     | 74                | 32.28          | spurious |
| Middle Channel (2437 MHz) |                           |                       |                          |               |                |                          |                       |                      |                           |                   |                |          |
| 4874.00                   | 32.79                     | Ave.                  | 320                      | 1.5           | H              | 36.3                     | 4.32                  | 26.75                | 46.66                     | 54                | 7.34           | harmonic |
| 4874.00                   | 31.05                     | Ave.                  | 170                      | 1.9           | V              | 33.6                     | 4.32                  | 26.75                | 42.22                     | 54                | 11.78          | harmonic |
| 4874.00                   | 47.65                     | PK                    | 320                      | 1.5           | H              | 36.3                     | 4.32                  | 26.75                | 61.52                     | 74                | 12.48          | harmonic |
| 4874.00                   | 43.26                     | PK                    | 170                      | 1.9           | V              | 33.6                     | 4.32                  | 26.75                | 54.43                     | 74                | 19.57          | harmonic |
| 1350.14                   | 32.47                     | Ave.                  | 160                      | 1.2           | H              | 25.6                     | 2.14                  | 26.56                | 33.65                     | 54                | 20.35          | spurious |
| 1350.14                   | 30.14                     | Ave.                  | 330                      | 2.1           | V              | 25.6                     | 2.14                  | 26.56                | 31.32                     | 54                | 22.68          | spurious |
| 1350.14                   | 44.26                     | PK                    | 160                      | 1.2           | H              | 25.6                     | 2.14                  | 26.56                | 45.44                     | 74                | 28.56          | spurious |
| 1350.14                   | 41.26                     | PK                    | 330                      | 2.1           | V              | 25.6                     | 2.14                  | 26.56                | 42.44                     | 74                | 31.56          | spurious |
| High Channel (2462 MHz)   |                           |                       |                          |               |                |                          |                       |                      |                           |                   |                |          |
| 4924.00                   | 32.05                     | Ave.                  | 160                      | 1.3           | H              | 36.3                     | 4.4                   | 26.75                | 46.0                      | 54                | 8.0            | harmonic |
| 4924.00                   | 31.75                     | Ave.                  | 180                      | 1.2           | V              | 33.6                     | 4.4                   | 26.75                | 43.0                      | 54                | 11.0           | harmonic |
| 4924.00                   | 47.41                     | PK                    | 160                      | 1.3           | H              | 36.3                     | 4.4                   | 26.75                | 61.36                     | 74                | 12.64          | harmonic |
| 1350.14                   | 33.26                     | Ave.                  | 210                      | 1.9           | H              | 25.6                     | 2.14                  | 26.56                | 34.44                     | 54                | 19.56          | spurious |
| 4924.00                   | 42.38                     | PK                    | 180                      | 1.2           | V              | 33.6                     | 4.4                   | 26.75                | 53.63                     | 74                | 20.37          | harmonic |
| 1350.14                   | 29.89                     | Ave.                  | 250                      | 1.7           | V              | 25.6                     | 2.14                  | 26.56                | 31.07                     | 54                | 22.93          | spurious |
| 1350.14                   | 46.38                     | PK                    | 210                      | 1.9           | H              | 25.6                     | 2.14                  | 26.56                | 47.56                     | 74                | 26.44          | spurious |
| 1350.14                   | 40.72                     | PK                    | 250                      | 1.7           | V              | 25.6                     | 2.14                  | 26.56                | 41.9                      | 74                | 32.1           | spurious |

**Radiated spurious emission in restricted band**

| Freq.<br>(MHz) | S.A.<br>Reading<br>(dBμV) | Detector<br>(PK /Ave.) | Direction<br>Degree | Test Antenna  |                |                  | Cable<br>Loss<br>(dB) | Pre-<br>Amp.<br>(dB) | Cord.<br>Amp.<br>(dBμV/m) | FCC Part 15.247/205/209 |                |
|----------------|---------------------------|------------------------|---------------------|---------------|----------------|------------------|-----------------------|----------------------|---------------------------|-------------------------|----------------|
|                |                           |                        |                     | Height<br>(m) | Polar<br>(H/V) | Factor<br>(dB/m) |                       |                      |                           | Limit<br>(dBμV/m)       | Margin<br>(dB) |
| 2495.2         | 31.89                     | Ave.                   | 200                 | 1.7           | H              | 30.6             | 3.14                  | 26.88                | 38.75                     | 54                      | 15.25          |
| 2495.2         | 30.47                     | Ave.                   | 190                 | 1.3           | V              | 30.6             | 3.14                  | 26.88                | 37.33                     | 54                      | 16.67          |
| 2323.6         | 30.29                     | Ave.                   | 260                 | 1.5           | V              | 30.5             | 2.98                  | 26.85                | 36.92                     | 54                      | 17.08          |
| 2323.6         | 28.45                     | Ave.                   | 190                 | 2.2           | H              | 30.5             | 2.98                  | 26.85                | 35.08                     | 54                      | 18.92          |
| 2495.2         | 42.68                     | PK                     | 200                 | 1.7           | H              | 30.6             | 3.14                  | 26.88                | 49.54                     | 74                      | 24.46          |
| 2323.6         | 41.26                     | PK                     | 260                 | 1.5           | V              | 30.5             | 2.98                  | 26.85                | 47.89                     | 74                      | 26.11          |
| 2495.2         | 39.87                     | PK                     | 190                 | 1.3           | V              | 30.6             | 3.14                  | 26.88                | 46.73                     | 74                      | 27.27          |
| 2323.6         | 39.56                     | PK                     | 190                 | 2.2           | H              | 30.5             | 2.98                  | 26.85                | 46.19                     | 74                      | 27.81          |

802.11g Mode:


| Indicated                 |                           | Detector<br>(PK/Ave) | Table<br>Angle<br>Degree | Test Antenna  |                | Correction Factor        |                       |                      | FCC Part 15.247/15.209    |                   |                |          |
|---------------------------|---------------------------|----------------------|--------------------------|---------------|----------------|--------------------------|-----------------------|----------------------|---------------------------|-------------------|----------------|----------|
| Frequency<br>(MHz)        | S.A.<br>Reading<br>(dBμV) |                      |                          | Height<br>(m) | Polar<br>(H/V) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Pre-<br>Amp.<br>(dB) | Cord.<br>Amp.<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Comment  |
| Low Channel (2412 MHz)    |                           |                      |                          |               |                |                          |                       |                      |                           |                   |                |          |
| 4824.00                   | 30.45                     | Ave.                 | 170                      | 1.1           | H              | 36.3                     | 4.3                   | 26.75                | 44.3                      | 54                | 9.70           | harmonic |
| 4824.00                   | 28.46                     | Ave.                 | 140                      | 1.7           | V              | 33.6                     | 4.3                   | 26.75                | 39.61                     | 54                | 14.39          | harmonic |
| 4824.00                   | 42.22                     | PK                   | 170                      | 1.1           | H              | 36.3                     | 4.3                   | 26.75                | 56.07                     | 74                | 17.93          | harmonic |
| 1350.14                   | 34.26                     | Ave.                 | 210                      | 2.1           | H              | 25.6                     | 2.14                  | 26.56                | 35.44                     | 54                | 18.56          | spurious |
| 1350.14                   | 30.28                     | Ave.                 | 230                      | 1.4           | V              | 25.6                     | 2.14                  | 26.56                | 31.46                     | 54                | 22.54          | spurious |
| 4824.00                   | 37.43                     | PK                   | 140                      | 1.7           | V              | 33.6                     | 4.3                   | 26.75                | 48.58                     | 74                | 25.42          | harmonic |
| 1350.14                   | 46.46                     | PK                   | 210                      | 2.1           | H              | 25.6                     | 2.14                  | 26.56                | 47.64                     | 74                | 26.36          | spurious |
| 1350.14                   | 41.01                     | PK                   | 230                      | 1.4           | V              | 25.6                     | 2.14                  | 26.56                | 42.19                     | 74                | 31.81          | spurious |
| Middle Channel (2437 MHz) |                           |                      |                          |               |                |                          |                       |                      |                           |                   |                |          |
| 4874.00                   | 31.14                     | Ave.                 | 180                      | 1.5           | H              | 36.3                     | 4.32                  | 26.75                | 45.01                     | 54                | 8.99           | harmonic |
| 4874.00                   | 29.68                     | Ave.                 | 140                      | 2.1           | V              | 33.6                     | 4.32                  | 26.75                | 40.85                     | 54                | 13.15          | harmonic |
| 4874.00                   | 43.25                     | PK                   | 180                      | 1.5           | H              | 36.3                     | 4.32                  | 26.75                | 57.12                     | 74                | 16.88          | harmonic |
| 1350.14                   | 35.14                     | Ave.                 | 230                      | 1.1           | H              | 25.6                     | 2.14                  | 26.56                | 36.32                     | 54                | 17.68          | spurious |
| 1350.14                   | 29.79                     | Ave.                 | 150                      | 2.1           | V              | 25.6                     | 2.14                  | 26.56                | 30.97                     | 54                | 23.03          | spurious |
| 4874.00                   | 38.43                     | PK                   | 140                      | 2.1           | V              | 33.6                     | 4.32                  | 26.75                | 49.6                      | 74                | 24.4           | harmonic |
| 1350.14                   | 45.68                     | PK                   | 230                      | 1.1           | H              | 25.6                     | 2.14                  | 26.56                | 46.86                     | 74                | 27.14          | spurious |
| 1350.14                   | 40.78                     | PK                   | 150                      | 2.1           | V              | 25.6                     | 2.14                  | 26.56                | 41.96                     | 74                | 32.04          | spurious |
| High Channel (2462 MHz)   |                           |                      |                          |               |                |                          |                       |                      |                           |                   |                |          |
| 4924.00                   | 31.01                     | Ave.                 | 110                      | 1.2           | H              | 36.3                     | 4.4                   | 26.75                | 44.96                     | 54                | 9.04           | harmonic |
| 4924.00                   | 28.14                     | Ave.                 | 260                      | 2.1           | V              | 33.6                     | 4.4                   | 26.75                | 39.39                     | 54                | 14.61          | harmonic |
| 4924.00                   | 42.68                     | PK                   | 110                      | 1.2           | H              | 36.3                     | 4.4                   | 26.75                | 56.63                     | 74                | 17.37          | harmonic |
| 1350.14                   | 33.78                     | Ave.                 | 310                      | 1.4           | H              | 25.6                     | 2.14                  | 26.56                | 34.96                     | 54                | 19.04          | spurious |
| 1350.14                   | 30.75                     | Ave.                 | 280                      | 1.6           | V              | 25.6                     | 2.14                  | 26.56                | 31.93                     | 54                | 22.07          | spurious |
| 4924.00                   | 38.08                     | PK                   | 260                      | 2.1           | V              | 33.6                     | 4.4                   | 26.75                | 49.33                     | 74                | 24.67          | harmonic |
| 1350.14                   | 46.37                     | PK                   | 310                      | 1.4           | H              | 25.6                     | 2.14                  | 26.56                | 47.55                     | 74                | 26.45          | spurious |
| 1350.14                   | 41.26                     | PK                   | 280                      | 1.6           | V              | 25.6                     | 2.14                  | 26.56                | 42.44                     | 74                | 31.56          | spurious |

Radiated spurious emission in restricted band


| Freq.<br>(MHz) | S.A.<br>Reading<br>(dBμV) | Detector<br>PK/Ave | Direction<br>Degree | Test Antenna  |                |                  | Cable<br>Loss<br>(dB) | Pre-<br>Amp.<br>(dB) | Cord.<br>Amp.<br>(dBμV/m) | FCC Part 15.247/205/209 |                |
|----------------|---------------------------|--------------------|---------------------|---------------|----------------|------------------|-----------------------|----------------------|---------------------------|-------------------------|----------------|
|                |                           |                    |                     | Height<br>(m) | Polar<br>(H/V) | Factor<br>(dB/m) |                       |                      |                           | Limit<br>(dBμV/m)       | Margin<br>(dB) |
| 2498.2         | 33.42                     | Ave.               | 180                 | 1.9           | V              | 30.6             | 3.14                  | 26.88                | 40.28                     | 54                      | 13.72          |
| 2498.2         | 32.15                     | Ave.               | 330                 | 2.1           | H              | 30.6             | 3.14                  | 26.88                | 39.01                     | 54                      | 14.99          |
| 2327.4         | 29.25                     | Ave.               | 210                 | 1.6           | H              | 30.5             | 2.98                  | 26.85                | 35.88                     | 54                      | 18.12          |
| 2327.4         | 28.75                     | Ave.               | 310                 | 1.1           | V              | 30.5             | 2.98                  | 26.85                | 35.38                     | 54                      | 18.62          |
| 2498.2         | 43.26                     | PK                 | 330                 | 2.1           | H              | 30.6             | 3.14                  | 26.88                | 50.12                     | 74                      | 23.88          |
| 2498.2         | 42.75                     | PK                 | 180                 | 1.9           | V              | 30.6             | 3.14                  | 26.88                | 49.61                     | 74                      | 24.39          |
| 2327.4         | 41.21                     | PK                 | 210                 | 1.6           | H              | 30.5             | 2.98                  | 26.85                | 47.84                     | 74                      | 26.16          |
| 2327.4         | 39.28                     | PK                 | 310                 | 1.1           | V              | 30.5             | 2.98                  | 26.85                | 45.91                     | 74                      | 28.09          |

**Antenna Port Conducted Spurious Emissions:**


| Channel  | Frequency (MHz) | Data Rate (Mbps) | Delta Value (dBc) | Limit (dBc) | Result |
|----------|-----------------|------------------|-------------------|-------------|--------|
| 801.11 b |                 |                  |                   |             |        |
| Low      | 1581.2          | 1                | 51.35             | 20          | Pass   |
| Middle   | 1581.2          | 1                | 50.30             | 20          | pass   |
| High     | 1581.2          | 1                | 47.49             | 20          | pass   |
| 801.11 g |                 |                  |                   |             |        |
| Low      | 3182.5          | 6                | 50.80             | 20          | Pass   |
| Middle   | 1581.2          | 6                | 49.46             | 20          | pass   |
| High     | 1631.3          | 6                | 50.21             | 20          | pass   |

**802.11b Low Channel**


## 802.11b Middle Channel




## 802.11b High Channel




## 802.11g Low Channel



## 802.11g Middle Channel



# 802.11g High Channel






## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Equipment List and Details

| Manufacturer    | Description       | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|-------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI  | 100035        | 2010-11-11       | 2011-11-10           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

|                    |          |
|--------------------|----------|
| Temperature:       | 25 °C    |
| Relative Humidity: | 56%      |
| ATM Pressure:      | 100.0kPa |


*The testing was performed by Jimmy Xiao on 2011-06-28.*

**Test Result:** Pass.

Please refer to the following tables and plots.


| Channel  | Frequency (MHz) | Data Rate (Mbps) | 6 dB Bandwidth (MHz) | Limit (kHz) | Result |
|----------|-----------------|------------------|----------------------|-------------|--------|
| 802.11 b |                 |                  |                      |             |        |
| Low      | 2412            | 1                | 12.80                | 500         | Pass   |
| Middle   | 2437            | 1                | 12.88                | 500         | Pass   |
| High     | 2462            | 1                | 12.88                | 500         | Pass   |
| 802.11 g |                 |                  |                      |             |        |
| Low      | 2412            | 6                | 16.64                | 500         | Pass   |
| Middle   | 2437            | 6                | 16.64                | 500         | Pass   |
| High     | 2462            | 6                | 16.64                | 500         | Pass   |

## 802.11b Low Channel




Date: 28.JUN.2011 23:32:33

### 802.11b Middle Channel




Date: 28.JUN.2011 23:54:45

### 802.11b High Channel




Date: 28.JUN.2011 23:58:42

### 802.11g Low Channel




Date: 28.JUN.2011 23:05:51

### 802.11g Middle Channel



Date: 28.JUN.2011 23:03:12

# 802.11g High Channel



Date: 28.JUN.2011 22:07:49


## FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



### Test Equipment List and Details

| Manufacturer    | Description       | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|-------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI  | 100035        | 2010-11-11       | 2011-11-10           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25 ° C    |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 100.0 kPa |

The testing was performed by Jimmy Xiao from 2011-06-20 to 2011-06-28.


Test Mode: Transmitting

| Channel | Frequency (MHz) | Data Rate (Mbps) | Conducted Output Power (dBm) | Limit (dBm) | Result |
|---------|-----------------|------------------|------------------------------|-------------|--------|
| 802.11b |                 |                  |                              |             |        |
| Low     | 2412            | 1                | 13.22                        | 30          | pass   |
| Middle  | 2437            | 1                | 13.87                        | 30          | pass   |
| High    | 2462            | 1                | 14.01                        | 30          | pass   |
| 802.11g |                 |                  |                              |             |        |
| Low     | 2412            | 6                | 11.66                        | 30          | pass   |
| Middle  | 2437            | 6                | 12.30                        | 30          | pass   |
| High    | 2462            | 6                | 11.34                        | 30          | pass   |


### 802.11b 99% Occupied Bandwidth, Low Channel



Date: 20.JUN.2011 22:30:41

**802.11b RF Output Power, Low Channel**


Date: 20.JUN.2011 22:33:47

**802.11b 99% Occupied Bandwidth, Middle Channel**

Date: 20.JUN.2011 22:35:15




### 802.11b RF Output Power, Middle Channel




Date: 20.JUN.2011 22:45:07

### 802.11b 99% Occupied Bandwidth, High Channel




Date: 20.JUN.2011 22:46:32

### 802.11b RF Output Power, High Channel




Date: 20.JUN.2011 22:47:20

### 802.11g 99% Occupied Bandwidth, Low Channel




Date: 28.JUN.2011 23:12:09

### 802.11g RF Output Power, Low Channel




Date: 28.JUN.2011 23:12:51

### 802.11g 99% Occupied Bandwidth, Middle Channel




Date: 28.JUN.2011 22:59:22

## 802.11g RF Output Power, Middle Channel




Date: 28.JUN.2011 23:00:16

## 802.11g 99% Occupied Bandwidth, High Channel



Date: 28.JUN.2011 21:56:35

# 802.11g RF Output Power, High Channel



Date: 28.JUN.2011 22:00:32

## FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

| Manufacturer    | Description       | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|-------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI  | 100035        | 2010-11-11       | 2011-11-10           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 ° C    |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Jimmy Xiao on 2011-06-28*

**Test Result:** *Compliance*

Please refer to following plots.

Ref 15 dBm \*Att 30 dB

- \*RBW 100 kHz
- \*VBW 300 kHz
- \*SWT 10 ms

Marker 1 [T1 ] 1.56 dBm  
2.411240000 GHz

Marker 2 [T1 ] 1.56 dBm  
2.396960000 GHz


1 PK MAXH

3DB AC

Center 2.399 GHz 6 MHz/ Span 60 MHz


Date: 28.JUN.2011 23:28:50

### 802.11b: Band Edge, Right Side



Date: 28.JUN.2011 23:59:45


### 802.11g: Band Edge, Left Side



Date: 28.JUN.2011 23:10:46



802.11g: Band Edge, Right Side



Date: 28.JUN.2011 23:24:44

## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to 1.5MHz span mode. And then, set RBW and VBW of spectrum analyzer to proper value. (DTS)
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

| Manufacturer    | Description       | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI   | 100035        | 2010-11-11       | 2011-11-10           |
| Rohde & Schwarz | Spectrum Analyzer | FSEM30 | 849720/019    | 2011-07-08       | 2012-07-07           |

\* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 ° C    |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 100.0 kPa |


*The testing was performed by Jimmy Xiao on 2011-06-18 and 2011-08-23.*

*Test Mode: Transmitting*

**Test Result:** Pass


| Channel  | Frequency (MHz) | Data Rate (Mbps) | Peak Power Spectral Density (dBm) | Limit (dBm) | Result |
|----------|-----------------|------------------|-----------------------------------|-------------|--------|
| 802.11 b |                 |                  |                                   |             |        |
| Low      | 2412            | 1                | -12.56                            | 8           | pass   |
| Middle   | 2437            | 1                | -11.52                            | 8           | pass   |
| High     | 2462            | 1                | -14.01                            | 8           | pass   |
| 802.11 g |                 |                  |                                   |             |        |
| Low      | 2412            | 6                | -16.19                            | 8           | pass   |
| Middle   | 2437            | 6                | -16.39                            | 8           | pass   |
| High     | 2462            | 6                | -17.21                            | 8           | pass   |

### Power Spectral Density, 802.11b Low Channel




Date: 28.JUN.2011 23:42:16

### Power Spectral Density, 802.11b Middle Channel




Date: 28.JUN.2011 23:52:07


### Power Spectral Density, 802.11b High Channel



Date: 20.JUN.2011 23:14:24


**Power Spectral Density, 802.11g Low Channel**

Date: 28.JUN.2011 23:22:59

**Power Spectral Density, 802.11g Middle Channel**

Date: 23.AUG.2011 00:08:18

# Power Spectral Density, 802.11g High Channel



Date: 28.JUN.2011 22:22:20

## **PRODUCT SIMILARITY DECLARATION LETTER**

### **ELECTRONICS TECHNOLOGY (DONG GUAN) COMPANY LIMITED**

No.161, Xin Min Road, Tong Luo Wei Industrial Zone, Jin Xia, Chang An Town, Dong  
Guan City, Guang Dong Province, China  
Tel: 0755-86335557 Fax: 0755-86335566  
Date: 2011-07-01

### **Product Similarity Declaration**

To Whom It May Concern,

We, ELECTRONICS TECHNOLOGY (DONG GUAN) COMPANY LIMITED hereby  
declare that our MID, Model Number: M72C2, M72J2 are electrically identical with the  
M72T2 that was certified by BACL. They are just different in appearance and model  
names, due to marketing purposes.

Please contact me if you have any question.

Signature:

Xiaona liu  
Quality Manager



**\*\*\*\*\* END OF REPORT \*\*\*\*\***