



# FCC PART 15.247 TEST REPORT

For

# Power Idea Technology (Shenzhen) Co., Ltd.

4th Floor, A Section, Languang Science&technology Xinxi RD, Hi-Tech Industrial Park North, Nanshan, ShenZhen, China

FCC ID: ZLE-RG850

Report Type: **Product Type:** LTE SMARTPHONE Original Report **Report Number:** RSZ180710006-00C **Report Date:** 2018-09-20 Rocky Kang Rocky Kang Reviewed By: RF Engineer **Prepared By:** Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

**Note**: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*".

# **TABLE OF CONTENTS**

GENERAL INFORMATION	
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
DUTY CYCLE	
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	15
Applicable Standard	
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	
EUT Setup	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	27
APPLICABLE STANDARD	
EUT SETUP	27
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	28
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY TEST DATA	26 اور
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH&99% OCCUPIED BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	
APPLICABLE STANDARD	

TEST PROCEDURE	
Test Data	59
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	61
APPLICABLE STANDARD	61
TEST PROCEDURE	61
Test Data	61
FCC §15.247(e) - POWER SPECTRAL DENSITY	67
APPLICABLE STANDARD	67
TEST PROCEDURE	67
Test Data	67

#### **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The *Power Idea Technology (Shenzhen) Co., Ltd.*'s product, model number: *RG850* (*FCC ID: ZLE-RG850*) or the "EUT" in this report was a *LTE SMARTPHONE*, which was measured approximately: 16.2 cm (L) \* 7.9 cm (W) \*1.1 cm (H), rated with input voltage: DC 3.83 V battery or DC 5V from adapter.

Report No.: RSZ180710006-00C

White Adapter Information: Model: HKC0115020-2B

Input: AC 100-240V, 50/60Hz, 0.5 A

Output: DC 5V, 2A

Black Adapter Information: Model: HKC0115021-2D

Input: AC 100-240V, 50/60Hz, 0.5 A

Output: DC 5V, 2A

\*All measurement and test data in this report was gathered from production sample serial number: 180710006 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-07-10.

#### **Objective**

This report is prepared on behalf of *Power Idea Technology (Shenzhen) Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

#### Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS and Part 22H&24E&27 PCE submissions with FCC ID: ZLE-RG850.

#### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 DTS Meas Guidance v04.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 76

#### **Measurement Uncertainty**

Parameter		Uncertainty	
Occupied Channel Bandwidth		±5%	
RF Output Power	with Power meter	±0.5dB	
RF conducted test with spectrum		±1.5dB	
AC Power Lines Conducted Emissions		±1.95dB	
Emissions,	Below 1GHz	±4.75dB	
Radiated	Above 1GHz	±4.88dB	
Temperature		±3°C	
Humidity		±6%	
Supply	voltages	±0.4%	

Report No.: RSZ180710006-00C

#### **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15.247 Page 5 of 76

# **SYSTEM TEST CONFIGURATION**

#### **Description of Test Configuration**

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

Report No.: RSZ180710006-00C

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6and 11

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	/	/
4	2437	/	/
5	2442	/	/

EUT was tested with Channel 1, 4 and 7.

FCC Part 15.247 Page 6 of 76

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Report No.: RSZ180710006-00C

EUT was tested with Channel 0, 19 and 39.

### **Equipment Modifications**

No modification was made to the EUT tested.

#### **EUT Exercise Software**

BLE & Wi-Fi test in the engineer mode.

"QRCT.exe" software was made to the EUT tested.

The device was tested with the worst case was performed as below:

Mode	Data vota	Power level		
Mode	Data rate	Low channel	Middle channel	High channel
802.11b	1 Mbps	13	13	13
802.11g	6 Mbps	11	11	12
802.11n-HT20	MCS0	11	11	11
802.11n-HT40	MCS0	12	12	9
BLE	/	Default	Default	Default


Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.

FCC Part 15.247 Page 7 of 76

**Duty cycle** 


#### 802.11b mode

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 16:29:50

### 802.11g mode




Date: 1.AUG.2018 16:27:19

FCC Part 15.247 Page 8 of 76


#### 802.11n-HT20 Mode

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 16:23:55

#### 802.11n-HT40 Mode




Date: 1.AUG.2018 16:26:02

FCC Part 15.247 Page 9 of 76

# **BLE Mode**

Report No.: RSZ180710006-00C



Date: 21.SEP.2018 17:21:23

Mode	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	99	-	-	10Hz	-
802.11g	88	1378	0.73	1kHz	0.56
802.11n-HT20	88	1294	0.77	1kHz	0.56
802.11n-HT40	77	649	1.54	3kHz	1.14
BLE	68	423	2.36	3kHz	1.67

# **Support Equipment List and Details**

Manufacturer	Manufacturer Description		Serial Number
/	/	/	/


#### **External I/O Cable**

Cable Description	Length (m)	From Port	То
Un-shielding Detachable USB Cable	1.0	EUT	Adapter
Un-shielding Detachable Earphone Cable	1.2	EUT	Earphone

FCC Part 15.247 Page 10 of 76

# **Block Diagram of Test Setup**

For conducted emission



FCC Part 15.247 Page 11 of 76

# SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: RSZ180710006-00C

FCC Part 15.247 Page 12 of 76

# TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date	
Conducted Emissions Test						
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-08-04	2019-08-04	
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2017-12-21	2018-12-21	
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-05-12	2018-11-21	
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR	
N/A	Conducted Emission Cable	N/A	UF A210B-1- 0720-504504	2018-05-12	2018-11-12	
	Radia	ated Emission T	est			
A.H.System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17	
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23	
COM-POWER	Pre-amplifier	PA-122	181919	2018-05-22	2018-11-22	
Sonoma instrument	Amplifier	310N	186238	2018-05-12	2018-11-12	
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21	
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-02-01	2018-08-01	
Ducommun technologies	RF Cable	UFA147A- 2362-100100	MFR64639 231029-003	2018-02-01	2018-08-01	
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-21	
Ducommun technologies	RF Cable	RG-214	1	2018-05-21	2018-11-19	
Ducommun technologies	RF Cable	RG-214	2	2018-05-22	2018-11-22	
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28	
Heatsink Required	Amplifier	QLW- 18405536-J0	15964001002	2018-02-01	2018-08-01	
Sinoscite	Notch Filter	BSF2402- 2480MN- 0898-001	N/A	2018-02-01	2018-08-01	
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR	

Report No.: RSZ180710006-00C

FCC Part 15.247 Page 13 of 76

Report No.: RSZ180710006-00C

FCC Part 15.247 Page 14 of 76

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

#### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RSZ180710006-00C

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

#### **Measurement Result**

#### For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	5.5	3.55	5	1.12	3.0	Yes

Result: No SAR test is required

#### For WIFI:

WIFI please refer to the report number: RSZ180710006-20A.

FCC Part 15.247 Page 15 of 76

## FCC §15.203 - ANTENNA REQUIREMENT

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: RSZ180710006-00C

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is -2.8 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

FCC Part 15.247 Page 16 of 76

# FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

#### **Applicable Standard**

FCC§15.207

#### **EUT Setup**



Report No.: RSZ180710006-00C

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

#### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W		
150 kHz – 30 MHz	9 kHz		

#### **Test Procedure**

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.247 Page 17 of 76

#### **Corrected Factor & Margin Calculation**

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RSZ180710006-00C

Margin = Limit – Corrected Amplitude

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Nancy Wang on 2018-08-22.


EUT operation mode: Transmitting

FCC Part 15.247 Page 18 of 76

**BLE Mode:** 

### White Adapter

#### AC 120V/60 Hz, Line




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.628430	43.1	19.7	56.0	12.9	QP
0.679890	40.6	19.7	56.0	15.4	QP
15.825810	44.0	20.2	60.0	16.0	QP
17.185230	45.2	20.2	60.0	14.8	QP
17.810770	44.5	20.2	60.0	15.5	QP
24.226470	43.9	20.4	60.0	16.1	QP
0.628430	29.4	19.7	46.0	16.6	Ave.
0.679890	26.4	19.7	46.0	19.6	Ave.
15.825810	35.5	20.2	50.0	14.5	Ave.
17.185230	35.9	20.2	50.0	14.1	Ave.
17.810770	35.2	20.2	50.0	14.8	Ave.
24.226470	32.8	20.4	50.0	17.2	Ave.

FCC Part 15.247 Page 19 of 76

# AC 120V/60 Hz, Neutral




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.201500	44.3	19.7	63.5	19.2	QP
1.975970	38.4	19.9	56.0	17.6	QP
2.141570	38.9	19.9	56.0	17.1	QP
2.429790	37.7	19.9	56.0	18.3	QP
2.670370	38.6	19.9	56.0	17.4	QP
3.370670	37.0	19.9	56.0	19.0	QP
0.201500	34.5	19.7	53.5	19.0	Ave.
1.975970	26.2	19.9	46.0	19.8	Ave.
2.141570	27.3	19.9	46.0	18.7	Ave.
2.429790	28.5	19.9	46.0	17.5	Ave.
2.670370	28.7	19.9	46.0	17.3	Ave.
3.370670	28.6	19.9	46.0	17.4	Ave.

FCC Part 15.247 Page 20 of 76

# **Black Adapter**

### AC 120V/60 Hz, Line




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.460070	40.6	19.8	56.0	15.4	QP
2.792090	36.7	19.9	56.0	19.3	QP
3.963170	37.3	20.0	56.0	18.7	QP
4.009550	36.8	20.0	56.0	19.2	QP
11.585890	40.6	20.2	60.0	19.4	QP
11.861810	40.1	20.2	60.0	19.9	QP
1.460070	28.6	19.8	46.0	17.4	Ave.
2.792090	26.5	19.9	46.0	19.5	Ave.
3.963170	27.1	20.0	46.0	18.9	Ave.
4.009550	26.7	20.0	46.0	19.3	Ave.
11.585890	31.6	20.2	50.0	18.4	Ave.
11.861810	30.4	20.2	50.0	19.6	Ave.

FCC Part 15.247 Page 21 of 76

# AC 120V/60 Hz, Neutral



Report No.: RSZ180710006-00C


Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.198500	40.4	19.7	63.7	23.3	QP
0.262500	38.9	19.7	61.4	22.5	QP
1.042190	38.9	19.8	56.0	17.1	QP
1.215550	37.0	19.7	56.0	19.0	QP
2.606730	34.9	19.9	56.0	21.1	QP
2.626490	35.7	19.9	56.0	20.3	QP
0.198500	26.9	19.7	53.7	26.8	Ave.
0.262500	30.1	19.7	51.4	21.3	Ave.
1.042190	30.0	19.8	46.0	16.0	Ave.
1.215550	28.4	19.7	46.0	17.6	Ave.
2.606730	28.9	19.9	46.0	17.1	Ave.
2.626490	28.8	19.9	46.0	17.2	Ave.

FCC Part 15.247 Page 22 of 76

Wi-Fi Mode:

### White adapter

### AC 120 V/60 Hz, Line:




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.675830	42.4	19.7	56.0	13.6	QP
15.953330	44.3	20.2	60.0	15.7	QP
16.415090	44.7	20.2	60.0	15.3	QP
18.025750	44.8	20.2	60.0	15.2	QP
22.735150	44.4	20.3	60.0	15.6	QP
24.396030	44.8	20.4	60.0	15.2	QP
0.675830	29.8	19.7	46.0	16.2	Ave.
15.953330	35.9	20.2	50.0	14.1	Ave.
16.415090	36.2	20.2	50.0	13.8	Ave.
18.025750	36.0	20.2	50.0	14.0	Ave.
22.735150	34.0	20.3	50.0	16.0	Ave.
24.396030	34.5	20.4	50.0	15.5	Ave.

FCC Part 15.247 Page 23 of 76

# **AC 120V/ 60 Hz, Neutral:**




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.857450	39.3	19.9	56.0	16.7	QP
1.980210	38.1	19.9	56.0	17.9	QP
2.184790	38.1	19.9	56.0	17.9	QP
2.693830	38.5	19.9	56.0	17.5	QP
24.317710	44.4	20.4	60.0	15.6	QP
24.395990	44.3	20.4	60.0	15.7	QP
1.857450	26.5	19.9	46.0	19.5	Ave.
1.980210	26.9	19.9	46.0	19.1	Ave.
2.184790	27.4	19.9	46.0	18.6	Ave.
2.693830	29.2	19.9	46.0	16.8	Ave.
24.317710	34.1	20.4	50.0	15.9	Ave.
24.395990	34.4	20.4	50.0	15.6	Ave.

FCC Part 15.247 Page 24 of 76

# Black adapter

# AC 120 V/60 Hz, Line:




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.325110	37.2	19.8	59.6	22.4	QP
0.411850	41.8	19.7	57.6	15.8	QP
1.050310	38.6	19.8	56.0	17.4	QP
1.373390	38.0	19.8	56.0	18.0	QP
11.478670	40.2	20.2	60.0	19.8	QP
11.703070	39.6	20.2	60.0	20.4	QP
0.325110	27.3	19.8	49.6	22.3	Ave.
0.411850	34.1	19.7	47.6	13.5	Ave.
1.050310	28.7	19.8	46.0	17.3	Ave.
1.373390	22.2	19.8	46.0	23.8	Ave.
11.478670	31.2	20.2	50.0	18.8	Ave.
11.703070	30.3	20.2	50.0	19.7	Ave.

FCC Part 15.247 Page 25 of 76

#### **AC 120V/60 Hz, Neutral:**



Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.281500	44.6	19.7	60.8	16.2	QP
0.869130	37.9	19.7	56.0	18.1	QP
1.054010	41.4	19.8	56.0	14.6	QP
1.172450	40.4	19.7	56.0	15.6	QP
1.306590	39.1	19.8	56.0	16.9	QP
1.393030	38.0	19.8	56.0	18.0	QP
0.281500	31.1	19.7	50.8	19.7	Ave.
0.869130	30.5	19.7	46.0	15.5	Ave.
1.054010	35.7	19.8	46.0	10.3	Ave.
1.172450	33.9	19.7	46.0	12.1	Ave.
1.306590	31.7	19.8	46.0	14.3	Ave.
1.393030	31.5	19.8	46.0	14.5	Ave.

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
  3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 26 of 76


# FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

#### **Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

#### **EUT Setup**

#### **Below 1 GHz:**



Report No.: RSZ180710006-00C

#### Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

FCC Part 15.247 Page 27 of 76

#### **EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Report No.: RSZ180710006-00C

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz Note 1	/	Average
	1MHz	>1/T Note 2	/	Average

Note 1: when duty cycle is no less than 98% Note 2: when duty cycle is less than 98%

#### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C</u>, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

FCC Part 15.247 Page 28 of 76

### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

Report No.: RSZ180710006-00C

The testing was performed by Nancy Wang on 2018-07-26.


EUT operation mode: Transmitting

FCC Part 15.247 Page 29 of 76

**BLE Mode:** 

### White adapter

### 30 MHz~1 GHz:




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
33.492750	16.28	133.0	V	188.0	-6.8	40.00	23.72
42.596250	19.40	100.0	V	163.0	-12.5	40.00	20.60
42.946875	16.67	116.0	V	79.0	-12.7	40.00	23.33
237.503250	25.00	128.0	Н	90.0	-10.6	46.00	21.00
828.374875	22.33	100.0	Н	207.0	-0.1	46.00	23.67
946.123250	24.19	112.0	V	89.0	1.9	46.00	21.81

FCC Part 15.247 Page 30 of 76

# Black adapter

### 30 MHz~1 GHz:



Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.560682	16.83	320.0	V	149.0	-5.0	40.00	23.17
170.586375	24.71	165.0	Н	233.0	-11.6	43.50	18.79
181.310000	26.30	124.0	Н	226.0	-12.2	43.50	17.20
681.181000	20.72	152.0	V	97.0	-2.3	46.00	25.28
834.494750	23.83	109.0	V	292.0	0.1	46.00	22.17
934.922250	24.58	102.0	Н	184.0	1.5	46.00	21.42

FCC Part 15.247 Page 31 of 76

# 1 **GHz-25 GHz(BLE)**:

F	Re	Receiver		Rx An	tenna	Corrected	Corrected	T **4	M		
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)		Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)		
	Low Channel (2402 MHz)										
2402.00	61.51	PK	168	1.6	Н	33.00	94.51	/	/		
2402.00	55.42	Ave.	168	1.6	Н	33.00	88.42	/	/		
2402.00	65.64	PK	73	1.3	V	33.00	98.64	/	/		
2402.00	59.33	Ave.	73	1.3	V	33.00	92.33	/	/		
2372.56	27.52	PK	357	1.1	V	33.00	60.52	74	13.48		
2372.56	14.11	Ave.	357	1.1	V	33.00	47.11	54	6.89		
2488.51	27.14	PK	39	1.0	V	33.20	60.34	74	13.66		
2488.51	13.67	Ave.	39	1.0	V	33.20	46.87	54	7.13		
4804.00	47.25	PK	88	2.1	V	7.88	55.13	74	18.87		
4804.00	33.24	Ave.	88	2.1	V	7.88	41.12	54	12.88		
	_	<u> </u>	Middle C	hannel	(2440 N	/IHz)	1				
2440.00	61.32	PK	188	1.3	Н	33.10	94.42	/	/		
2440.00	55.18	Ave.	188	1.3	Н	33.10	88.28	/	/		
2440.00	65.87	PK	241	1.4	V	33.10	98.97	/	/		
2440.00	60.23	Ave.	241	1.4	V	33.10	93.33	/	/		
4880.00	47.38	PK	251	1.8	V	9.21	56.59	74	17.41		
4880.00	32.39	Ave.	251	1.8	V	9.21	41.60	54	12.40		
			High Ch	annel (2	2480 M	Hz)	l .				
2480.00	59.34	PK	318	1.0	Н	33.20	92.54	/	/		
2480.00	53.14	Ave.	318	1.0	Н	33.20	86.34	/	/		
2480.00	63.21	PK	343	1.8	V	33.20	96.41	/	/		
2480.00	58.52	Ave.	343	1.8	V	33.20	91.72	/	/		
2324.51	27.62	PK	323	1.7	V	32.97	60.59	74	13.41		
2324.51	14.51	Ave.	323	1.7	V	32.97	47.48	54	6.52		
2486.72	28.32	PK	187	1.1	V	33.20	61.52	74	12.48		
2486.72	14.83	Ave.	187	1.1	V	33.20	48.03	54	5.97		
4960.00	47.29	PK	149	2.0	V	9.07	56.36	74	17.64		
4960.00	31.54	Ave.	149	2.0	V	9.07	40.61	54	13.39		


Report No.: RSZ180710006-00C

FCC Part 15.247 Page 32 of 76

#### Wi-Fi Mode:

### White adapter

#### 30 MHz~1 GHz:




Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.055524	17.34	326.0	Н	26.0	-4.7	40.00	22.66
86.231500	17.24	220.0	Н	92.0	-16.1	40.00	22.76
86.701250	18.46	400.0	Н	92.0	-16.1	40.00	21.54
690.387000	20.58	261.0	V	317.0	-1.9	46.00	25.42
835.085375	22.68	180.0	V	264.0	0.1	46.00	23.32
957.118750	24.89	112.0	V	212.0	2.3	46.00	21.11

FCC Part 15.247 Page 33 of 76

# Black adapter

### 30 MHz~1 GHz:



Report No.: RSZ180710006-00C

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.284656	17.13	308.0	V	279.0	-4.9	40.00	22.87
162.225125	16.74	281.0	Н	264.0	-11.2	43.50	26.76
180.925625	20.38	139.0	Н	210.0	-12.2	43.50	23.12
670.819750	21.21	116.0	V	357.0	-2.4	46.00	24.79
770.186375	22.65	106.0	V	121.0	-1.0	46.00	23.35
945.912875	24.07	400.0	Н	217.0	1.9	46.00	21.93

FCC Part 15.247 Page 34 of 76

# 1 GHz-25 GHz(WIFI):

### 802.11b Mode:

-	Re	eceiver	T 4 1 1	Rx Ar	tenna	Corrected	Corrected	T,	3.6
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)		Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	67.96	PK	226	2.3	Н	33.92	101.88	/	/
2412.00	62.46	Ave.	226	2.3	Н	33.92	96.38	/	/
2412.00	61.48	PK	135	2.3	V	33.92	95.40	/	/
2412.00	55.40	Ave.	135	2.3	V	33.92	89.32	/	/
2366.59	29.18	PK	352	1.2	Н	33.92	63.10	74	10.90
2366.59	14.23	Ave.	352	1.2	Н	33.92	48.15	54	5.85
2485.55	27.18	PK	181	1.1	Н	34.08	61.26	74	12.74
2485.55	13.40	Ave.	181	1.1	Н	34.08	47.48	54	6.52
4824.00	43.44	PK	302	1.8	Н	5.84	49.28	74	24.72
4824.00	28.42	Ave.	302	1.8	Н	5.84	34.26	54	19.74
			Middle C	Channel	(2437N	IHz)			
2437.00	71.23	PK	8	1.3	Н	33.92	105.15	/	/
2437.00	65.33	Ave.	8	1.3	Н	33.92	99.25	/	/
2437.00	66.52	PK	73	2.2	V	33.92	100.44	/	/
2437.00	60.49	Ave.	73	2.2	V	33.92	94.41	/	/
4874.00	43.36	PK	244	2.3	Н	6.21	49.57	74	24.43
4874.00	28.77	Ave.	244	2.3	Н	6.21	34.98	54	19.02
			High Ch	annel (	2462 M	Hz)			
2462.00	69.44	PK	45	2.0	Н	34.08	103.52	/	/
2462.00	63.54	Ave.	45	2.0	Н	34.08	97.62	/	/
2462.00	63.64	PK	285	2.2	V	34.08	97.72	/	/
2462.00	58.08	Ave.	285	2.2	V	34.08	92.16	/	/
2357.29	28.26	PK	256	1.9	Н	33.92	62.18	74	11.82
2357.29	13.97	Ave.	256	1.9	Н	33.92	47.89	54	6.11
2487.27	27.64	PK	82	1.7	Н	34.08	61.72	74	12.28
2487.27	13.56	Ave.	82	1.7	Н	34.08	47.64	54	6.36
4924.00	42.68	PK	21	1.9	Н	6.21	48.89	74	25.11
4924.00	27.84	Ave.	21	1.9	Н	6.21	34.05	54	19.95

Report No.: RSZ180710006-00C

FCC Part 15.247 Page 35 of 76

# 802.11g Mode:

Б	Re	eceiver	T (1)	Rx Ar	tenna	Corrected	Corrected	T,	N/ :
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)		Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	69.26	PK	21	1.6	Н	33.92	103.18	/	/
2412.00	51.37	Ave.	21	1.6	Н	33.92	85.29	/	/
2412.00	65.48	PK	28	2.3	V	33.92	99.40	/	/
2412.00	47.97	Ave.	28	2.3	V	33.92	81.89	/	/
2389.52	27.53	PK	130	1.3	Н	33.92	61.45	74	12.55
2389.52	13.66	Ave.	130	1.3	Н	33.92	47.58	54	6.42
2484.03	27.00	PK	266	1.7	Н	34.08	61.08	74	12.92
2484.03	13.54	Ave.	266	1.7	Н	34.08	47.62	54	6.38
4824.00	41.84	PK	250	1.2	Н	5.84	47.68	74	26.32
4824.00	27.07	Ave.	250	1.2	Н	5.84	32.91	54	21.09
			Middle C	Channel	(2437N	IHz)			
2437.00	69.77	PK	188	1.2	Н	33.92	103.69	/	/
2437.00	51.96	Ave.	188	1.2	Н	33.92	85.88	/	/
2437.00	66.31	PK	164	2.3	V	33.92	100.23	/	/
2437.00	49.56	Ave.	164	2.3	V	33.92	83.48	/	/
4874.00	42.27	PK	193	2.2	Н	6.21	48.48	74	25.52
4874.00	27.81	Ave.	193	2.2	Н	6.21	34.02	54	19.98
			High Ch	annel (	2462 M	Hz)			
2462.00	72.64	PK	235	2.4	Н	34.08	106.72	/	/
2462.00	54.83	Ave.	235	2.4	Н	34.08	88.91	/	/
2462.00	63.74	PK	200	1.6	V	34.08	97.82	/	/
2462.00	46.57	Ave.	200	1.6	V	34.08	80.65	/	/
2382.46	28.29	PK	93	1.7	Н	33.92	62.21	74	11.79
2382.46	14.13	Ave.	93	1.7	Н	33.92	48.05	54	5.95
2493.04	27.15	PK	331	2.4	Н	34.08	61.23	74	12.77
2493.04	13.56	Ave.	331	2.4	Н	34.08	47.64	54	6.36
4924.00	41.09	PK	344	1.2	Н	6.21	47.30	74	26.70
4924.00	26.74	Ave.	344	1.2	Н	6.21	32.95	54	21.05

Report No.: RSZ180710006-00C

FCC Part 15.247 Page 36 of 76

# 802.11n-HT20 Mode:

Т	Re	eceiver	T 4 11	Rx Ar	itenna	Corrected	Corrected	T,	34 .
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	annel (2	2412 M	Hz)			
2412.00	69.68	PK	44	1.9	Н	33.92	103.60	/	/
2412.00	51.96	Ave.	44	1.9	Н	33.92	85.88	/	/
2412.00	64.77	PK	170	1.5	V	33.92	98.69	/	/
2412.00	47.77	Ave.	170	1.5	V	33.92	81.69	/	/
2369.80	27.89	PK	42	1.5	Н	33.92	61.81	74	12.19
2369.80	13.66	Ave.	42	1.5	Н	33.92	47.58	54	6.42
2484.02	26.65	PK	187	1.2	Н	34.08	60.73	74	13.27
2484.02	13.38	Ave.	187	1.2	Н	34.08	47.46	54	6.54
4824.00	42.15	PK	123	1.9	Н	5.84	47.99	74	26.01
4824.00	27.27	Ave.	123	1.9	Н	5.84	33.11	54	20.89
			Middle C	Channel	(2437N	(Hz)			
2437.00	70.06	PK	40	2.2	Н	33.92	103.98	/	/
2437.00	52.97	Ave.	40	2.2	Н	33.92	86.89	/	/
2437.00	66.40	PK	324	1.6	V	33.92	100.32	/	/
2437.00	49.18	Ave.	324	1.6	V	33.92	83.10	/	/
4874.00	41.72	PK	105	1.2	Н	6.21	47.93	74	26.07
4874.00	27.60	Ave.	105	1.2	Н	6.21	33.81	54	20.19
			High Ch	annel (	2462 M	Hz)			
2462.00	69.65	PK	246	2.1	Н	34.08	103.73	/	/
2462.00	50.69	Ave.	246	2.1	Н	34.08	84.77	/	/
2462.00	61.71	PK	303	1.7	V	34.08	95.79	/	/
2462.00	43.92	Ave.	303	1.7	V	34.08	78.00	/	/
2346.23	27.41	PK	5	1.9	Н	33.83	61.24	92	30.76
2346.23	13.38	Ave.	5	1.9	Н	33.83	47.21	60	12.79
2486.18	27.55	PK	38	1.4	V	34.08	61.63	92	30.37
2486.18	13.51	Ave.	38	1.4	V	34.08	47.59	60	12.41
4924.00	42.05	PK	285	1.7	Н	6.21	48.26	74	25.74
4924.00	27.30	Ave.	285	1.7	Н	6.21	33.51	54	20.49

Report No.: RSZ180710006-00C

FCC Part 15.247 Page 37 of 76

#### 802.11n-HT40 Mode:

<b>T</b>	Re	eceiver	T	Rx An	itenna	Corrected	Corrected	T ''4	M
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	annel (2	2422 M	Hz)			
2422.00	65.77	PK	357	1.4	Н	33.92	99.69	/	/
2422.00	53.75	Ave.	357	1.4	Н	33.92	87.67	/	/
2422.00	60.62	PK	35	1.7	V	33.92	94.54	/	/
2422.00	47.84	Ave.	35	1.7	V	33.92	81.76	/	/
2390.00	31.43	PK	354	2.4	Н	33.92	65.35	92	26.65
2390.00	16.34	Ave.	354	2.4	Н	33.92	50.26	60	9.74
2488.56	26.85	PK	100	2.3	V	34.08	60.93	92	31.07
2488.56	13.45	Ave.	100	2.3	V	34.08	47.53	60	12.47
4844.00	42.84	PK	340	1.3	Н	5.84	48.68	74	25.32
4844.00	28.58	Ave.	340	1.3	Н	5.84	34.42	54	19.58
		T	Middle C	Channel	(2437N	(IHz)			
2437.00	67.37	PK	281	2.4	Н	33.92	101.29	/	/
2437.00	55.53	Ave.	281	2.4	Н	33.92	89.45	/	/
2437.00	62.80	PK	116	2.2	V	33.92	96.72	/	/
2437.00	46.30	Ave.	116	2.2	V	33.92	80.22	/	/
4874.00	42.22	PK	112	1.9	Н	5.34	47.56	74	26.44
4874.00	28.81	Ave.	112	1.9	Н	5.34	34.15	54	19.85
			High Ch	nannel (2	2452 M	Hz)			
2452.00	63.17	PK	126	1.3	Н	34.08	97.25	/	/
2452.00	50.98	Ave.	126	1.3	Н	34.08	85.06	/	/
2452.00	59.10	PK	321	1.7	V	34.08	93.18	/	/
2452.00	45.93	Ave.	321	1.7	V	34.08	80.01	/	/
2348.80	26.66	PK	95	1.3	Н	33.83	60.49	74	13.51
2348.80	13.28	Ave.	95	1.3	Н	33.83	47.11	54	6.89
2498.12	26.81	PK	265	2.5	Н	34.08	60.89	74	13.11
2498.12	13.40	Ave.	265	2.5	Н	34.08	47.48	54	6.52
4904.00	43.76	PK	311	1.3	Н	6.21	49.97	74	24.03
4904.00	28.94	Ave.	311	1.3	Н	6.21	35.15	54	18.85

Report No.: RSZ180710006-00C

Corrected Factor = Antenna factor (RX) + Cable Loss - Amplifier Factor Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.


FCC Part 15.247 Page 38 of 76

# Pre-scan with 802.11n-HT40 Mode, High channel Horizontal




FCC Part 15.247 Page 39 of 76

#### Vertical




Date: 26.JUL.2018 13:17:12




FCC Part 15.247 Page 40 of 76

#### Pre-scan for Average Horizontal




Date: 26.JUL.2018 13:14:06




FCC Part 15.247 Page 41 of 76

#### Vertical



Date: 26.JUL.2018 13:19:29



FCC Part 15.247 Page 42 of 76

# FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH&99% OCCUPIED BANDWIDTH


Report No.: RSZ180710006-00C

#### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Nancy Wang on 2018-08-01 and 2018-08-07.

Test Result: Pass.

Please refer to the following table and plots.

FCC Part 15.247 Page 43 of 76


Channel	Frequency (MHz)	6dB bandwidth (MHz)	99% OBW (MHz)	Limit (kHz)			
	802.11b mode						
Low	2412	9.62	14.36	≥500			
Middle	2437	9.13	13.91	≥500			
High	2462	9.62	14.49	≥500			
		802.11g mode					
Low	2412	15.87	17.63	≥500			
Middle	2437	15.77	17.18	≥500			
High	2462	15.87	17.76	≥500			
	802.11n-HT20 mode						
Low	2412	15.82	17.63	≥500			
Middle	2437	15.77	17.12	≥500			
High	2462	15.87	17.56	≥500			
	802.11n-HT40 mode						
Low	2422	36.25	37.44	≥500			
Middle	2437	32.69	35.90	≥500			
High	2452	23.85	35.77	≥500			

Channel	Frequency (MHz)	6 dB Emission Bandwidth(MHz)	Limit (kHz)
Low	2402	0.676	≥500
Middle	2440	0.667	≥500
High	2480	0.679	≥500

FCC Part 15.247 Page 44 of 76


#### 6dB Bandwidth, 802.11b Low Channel

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 11:58:52


#### 6dB Bandwidth, 802.11b Middle Channel



Date: 1.AUG.2018 11:57:39


FCC Part 15.247 Page 45 of 76

# 6dB Bandwidth, 802.11b High Channel



Date: 1.AUG.2018 11:55:05


# 6dB Bandwidth, 802.11g Low Channel



Date: 1.AUG.2018 13:13:10


FCC Part 15.247 Page 46 of 76

# 6dB Bandwidth, 802.11g Middle Channel



Date: 1.AUG.2018 13:14:44

# 6dB Bandwidth, 802.11g High Channel




Date: 1.AUG.2018 13:19:01

FCC Part 15.247 Page 47 of 76


#### 6dB Bandwidth, 802.11n-HT20 Low Channel

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 13:35:15


#### 6dB Bandwidth, 802.11n-HT20 Middle Channel



Date: 1.AUG.2018 13:34:17


FCC Part 15.247 Page 48 of 76

#### 6dB Bandwidth, 802.11n-HT20 High Channel




Date: 1.AUG.2018 13:32:52


#### 6dB Bandwidth, 802.11n-HT40 Low Channel



Date: 1.AUG.2018 11:19:58


FCC Part 15.247 Page 49 of 76






Date: 1.AUG.2018 11:17:16

#### 6dB Bandwidth, 802.11n-HT40 High Channel




Date: 1.AUG.2018 10:50:11

FCC Part 15.247 Page 50 of 76



Date: 1.AUG.2018 11:47:40

# 99% Occupied Bandwidth, 802.11b Middle Channel




Date: 1.AUG.2018 11:49:14

FCC Part 15.247 Page 51 of 76


#### 99% Occupied Bandwidth, 802.11b High Channel

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 11:50:05

# 99% Occupied Bandwidth, 802.11g Low Channel




Date: 1.AUG.2018 13:24:57

FCC Part 15.247 Page 52 of 76


#### 99% Occupied Bandwidth, 802.11g Middle Channel

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 13:24:17

# 99% Occupied Bandwidth, 802.11g High Channel




Date: 1.AUG.2018 13:23:29

FCC Part 15.247 Page 53 of 76


# 99% Occupied Bandwidth, 802.11n-HT20 Low Channel

Report No.: RSZ180710006-00C



Date: 1.AUG.2018 13:27:25


#### 99% Occupied Bandwidth, 802.11n-HT20 Middle Channel



Date: 1.AUG.2018 13:28:22


FCC Part 15.247 Page 54 of 76

# 99% Occupied Bandwidth, 802.11n-HT20 High Channel



Date: 1.AUG.2018 13:29:21


#### 99% Occupied Bandwidth, 802.11n-HT40 Low Channel



Date: 1.AUG.2018 11:31:20


FCC Part 15.247 Page 55 of 76

#### 99% Occupied Bandwidth, 802.11n-HT40 Middle Channe



Date: 1.AUG.2018 11:33:03


#### 99% Occupied Bandwidth, 802.11n-HT40 High Channel



Date: 1.AUG.2018 11:34:41


FCC Part 15.247 Page 56 of 76






Date: 7.AUG.2018 13:29:55


#### **BLE Middle Channel**



Date: 7.AUG.2018 13:32:37

FCC Part 15.247 Page 57 of 76





Date: 7.AUG.2018 22:18:48

FCC Part 15.247 Page 58 of 76

# FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


#### **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: RSZ180710006-00C

#### **Test Procedure**

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Nancy Wang on 2018-08-07.

EUT operation mode: Transmitting

FCC Part 15.247 Page 59 of 76

# Wi-Fi mode

Report No.: RSZ180710006-00C

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)			
		802.11b					
Low	2412	12.14	7.39	30			
Middle	2437	11.49	9.29	30			
High	2462	11.60	8.02	30			
	802.11g						
Low	2412	14.53	7.66	30			
Middle	2437	14.83	8.98	30			
High	2462	14.82	8.98	30			
		802.11n HT20					
Low	2412	14.56	7.86	30			
Middle	2437	15.01	9.00	30			
High	2462	14.99	8.20	30			
	802.11n HT40						
Low	2422	15.31	8.94	30			
Middle	2437	15.15	8.46	30			
High	2452	14.92	7.55	30			

# **BLE** mode

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	5.39	30	Pass
Middle	2440	5.44	30	Pass
High	2480	2.19	30	Pass

FCC Part 15.247 Page 60 of 76

# FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: RSZ180710006-00C

#### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Nancy Wang on 2018-08-01 and 2018-08-07.


EUT operation mode: Transmitting

Test Result: Compliance

Please refer to the following plots.


FCC Part 15.247 Page 61 of 76

802.11b: Band Edge, Left Side



Date: 1.AUG.2018 16:32:17


802.11b: Band Edge, Right Side



Date: 1.AUG.2018 16:33:36


FCC Part 15.247 Page 62 of 76

# 802.11g: Band Edge, Left Side



Date: 1.AUG.2018 16:37:49


#### 802.11g: Band Edge, Right Side



Date: 1.AUG.2018 16:36:06


FCC Part 15.247 Page 63 of 76

# 802.11n-HT20: Band Edge, Left Side



Date: 1.AUG.2018 16:38:51


#### 802.11n-HT20: Band Edge, Right Side



Date: 1.AUG.2018 16:40:36

FCC Part 15.247 Page 64 of 76

#### 802.11n-HT40: Band Edge, Left Side



Date: 1.AUG.2018 16:42:55


#### 802.11n-HT40: Band Edge, Right Side



Date: 1.AUG.2018 16:42:06


FCC Part 15.247 Page 65 of 76

**BLE: Band Edge, Left Side** 



Date: 7.AUG.2018 13:38:13

BLE: Band Edge, Right Side



Date: 7.AUG.2018 13:39:19

FCC Part 15.247 Page 66 of 76

# FCC §15.247(e) - POWER SPECTRAL DENSITY

#### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: RSZ180710006-00C

#### **Test Procedure**

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW to:  $3kHz \le RBW \le 100 \text{ kHz}$ .
- 3. Set the VBW  $> 3 \times RBW$ .
- 4. Set the span to 1.5 times the DTS bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Nancy Wang on 2018-08-01 and 2018-08-07.

EUT operation mode: Transmitting


**Test Result:** Pass

FCC Part 15.247 Page 67 of 76

	<b>D</b>	PSD	Limit					
Channel	Frequency (MHz)	(dBm/3kHz)	(dBm/3kHz)					
	802.11b mode							
Low	2412	-22.07	≤8					
Middle	2437	-20.54	≤8					
High	2462	-24.51	≤8					
	802.11g	mode						
Low	2412	-22.37	≤8					
Middle	2437	-21.38	≤8					
High	2462	-23.88	≤8					
	802.11n-H	Γ20 mode						
Low	2412	-22.02	≤8					
Middle	2437	-21.66	≤8					
High	2462	-23.28	≤8					
	802.11n-H	Γ40 mode						
Low	2422	-25.27	≤8					
Middle	2437	-24.76	≤8					
High	2452	-20.74	≤8					
	BLE mode							
Low	2402	-9.00	≤8					
Middle	2440	-9.54	≤8					
High	2480	-13.54	≤8					


FCC Part 15.247 Page 68 of 76

# Power Spectral Density, 802.11b Low Channel



Date: 1.AUG.2018 15:43:28


# Power Spectral Density, 802.11b Middle Channel



Date: 1.AUG.2018 15:45:42


FCC Part 15.247 Page 69 of 76

# Power Spectral Density, 802.11b High Channel



Date: 1.AUG.2018 15:46:48


# Power Spectral Density, 802.11g Low Channel



Date: 1.AUG.2018 15:51:29


FCC Part 15.247 Page 70 of 76

#### Power Spectral Density, 802.11g Middle Channel



Date: 1.AUG.2018 15:50:16


# Power Spectral Density, 802.11g High Channel



Date: 1.AUG.2018 15:48:51


FCC Part 15.247 Page 71 of 76

# Power Spectral Density, 802.11n-HT20 Low Channel



Date: 1.AUG.2018 15:52:37


# Power Spectral Density, 802.11n-HT20 Middle Channel



Date: 1.AUG.2018 15:53:45


FCC Part 15.247 Page 72 of 76

# Power Spectral Density, 802.11n-HT20 High Channel



Date: 1.AUG.2018 15:54:47


# Power Spectral Density, 802.11n-HT40 Low Channel



Date: 1.AUG.2018 15:58:58


FCC Part 15.247 Page 73 of 76

#### Power Spectral Density, 802.11n-HT40 Middle Channel



Date: 1.AUG.2018 16:00:12

#### Power Spectral Density, 802.11n-HT40 High Channel




Date: 1.AUG.2018 16:18:08

FCC Part 15.247 Page 74 of 76


# Power Spectral Density, BLE Low Channel

Report No.: RSZ180710006-00C



Date: 7.AUG.2018 22:21:15

#### Power Spectral Density, BLE Middle Channel




Date: 7.AUG.2018 13:47:34

FCC Part 15.247 Page 75 of 76

# Power Spectral Density, BLE High Channel

Report No.: RSZ180710006-00C



Date: 7.AUG.2018 22:20:36

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15.247 Page 76 of 76