

FCC SAR Test Report

Report No. : SA180315C04
Applicant : FIBOCOM
Address : 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Product : LTE module
FCC ID : ZMOL850GL
Brand : Fibocom
Model No. : L850-GL
Standards : FCC 47 CFR PART 2 (2.1093), IEEE C95.1:1992, IEEE STD 1528:2013
KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 248227 D01 v02r02,
KDB 447498 D01 v06, KDB 616217 D04 v01r02, KDB 941225 D01 v03r01
KDB 941225 D05 v02r05, KDB 941225 D05A v01r02
Sample Received Date : Mar. 15, 2018
Date of Testing : Apr. 23, 2018 ~ May 06, 2018
Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.
Test Location : No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

Evonne Liu

Evonne Liu / Specialist

Approved By :

Eli Hsu

Eli Hsu / Senior Engineer



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	6
3.1 Definition of Specific Absorption Rate (SAR)	6
3.2 SPEAG DASY52 System	6
3.2.1 Robot.....	7
3.2.2 Probes.....	8
3.2.3 Data Acquisition Electronics (DAE)	9
3.2.4 Phantoms	9
3.2.5 Device Holder.....	10
3.2.6 System Validation Dipoles.....	10
3.2.7 Tissue Simulating Liquids.....	11
3.3 SAR System Verification	14
3.4 SAR Measurement Procedure	15
3.4.1 Area & Zoom Scan Procedure	15
3.4.2 Volume Scan Procedure.....	15
3.4.3 Power Drift Monitoring.....	16
3.4.4 Spatial Peak SAR Evaluation	16
3.4.5 SAR Averaged Methods	16
4. SAR Measurement Evaluation	17
4.1 EUT Configuration and Setting.....	17
4.2 EUT Testing Position	34
4.2.1 Body Exposure Conditions	34
4.2.2 SAR Test Exclusion Evaluations	36
4.3 Tissue Verification	38
4.4 System Validation.....	39
4.5 System Verification.....	40
4.6 Maximum Output Power.....	41
4.6.1 Maximum Target Conducted Power	41
Laptop.....	41
Tablet.....	41
Laptop.....	43
Tablet.....	46
4.6.2 Measured Conducted Power Result.....	48
Laptop.....	48
Tablet.....	59
4.7 SAR Testing Results	82
4.7.1 SAR Test Reduction Considerations	82
4.7.2 SAR Results for Body Exposure Condition	87
Laptop PC Mode.....	87
Tablet PC Mode	91
4.7.3 SAR Measurement Variability.....	100
5. Calibration of Test Equipment.....	205
6. Measurement Uncertainty.....	206
7. Information on the Testing Laboratories.....	208
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate for Probe and Dipole	
Appendix D. Photographs of EUT and Setup	

Release Control Record

Report No.	Reason for Change	Date Issued
SA180315C04	Initial release	May 25, 2018

FCC SAR Test Report

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest SAR-1g Body (W/kg)	
		Laptop PC	Tablet PC
PCB	WCDMA II	0.46	1.16
	WCDMA IV	0.60	0.96
	WCDMA V	0.74	0.45
	LTE 2	0.42	1.18
	LTE 4	0.60	1.19
	LTE 5	0.88	0.63
	LTE 7	0.62	1.14
	LTE 12	0.93	0.77
	LTE 13	1.01	0.69
	LTE 17	0.85	0.73
	LTE 26	0.90	0.63
	LTE 30	0.81	0.85
	LTE 38	0.76	1.17
	LTE 41	0.62	1.06
	LTE 66	0.58	0.95
DTS	2.4G WLAN	1.16	1.03
NII	5.3G WLAN	1.10	0.97
	5.6G WLAN	1.16	0.93
	5.8G WLAN	1.11	0.92
DSS	Bluetooth	0.03	0.37
Highest Simultaneous Transmission SAR		Body	
		1.58	1.56

Note:

- The SAR criteria (**Head & Body: SAR-1g 1.6 W/kg, and Extremity: SAR-10g 4.0 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

FCC SAR Test Report

2. Description of Equipment Under Test

EUT Type	LTE module
IC	ZMOL850GL
Brand Name	Fibocom
Model Name	L850-GL
EUT Configurations	EUT 1 : CPU 1 + eMMc 1 + LCD 1 + Camera 1 EUT 2 : CPU 2 + eMMc 2 + LCD 2 + Camera 2 EUT 3 : CPU 3 + eMMc 3 + LCD 3 + Camera 3
Tx Frequency Bands (Unit: MHz)	WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV : 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 ~ 1909.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) LTE Band 4 : 1710.7 ~ 1754.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) LTE Band 5 : 824.7 ~ 848.3 (BW: 1.4M, 3M, 5M, 10M) LTE Band 7 : 2502.5 ~ 2567.5 (BW: 5M, 10M, 15M, 20M) LTE Band 12 : 699.7 ~ 715.3 (BW: 1.4M, 3M, 5M, 10M) LTE Band 13 : 779.5 ~ 784.5 (BW: 5M, 10M) LTE Band 17 : 706.5 ~ 713.5 (BW: 5M, 10M) LTE Band 26 : 814.7 ~ 848.3 (BW: 1.4M, 3M, 5M, 10M, 15M) LTE Band 30 : 2307.5 ~ 2312.5 (BW: 5M, 10M) LTE Band 38 : 2572.5 ~ 2617.5 (BW: 5M, 10M, 15M, 20M) LTE Band 41 : 2498.5 ~ 2687.5 (BW: 5M, 10M, 15M, 20M) LTE Band 66 : 1710.7 ~ 1779.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5720, 5745 ~ 5825 Bluetooth : 2402 ~ 2480
Uplink Modulations	WCDMA : QPSK LTE : QPSK, 16QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 4.6.1 of this report
Antenna Type	PIFA Antenna (Peak Antenna Gain : 1.6 dBi for 2.4GHz, 2.35 dBi for 5GHz)
EUT Stage	Identical Prototype

Note:

1. The EUT was installed in Notebook PC (Brand: ASUS, Model: TP401C, J401C, R406C).
2. It is co-located with a WLAN module under FCC ID: MSQ8265NG in the host.
3. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

List of Accessory:

Battery	Brand Name	Dyna
	Model Name	C211N1714
	Power Rating	7.7Vdc, 39WH
	Type	Li-ion

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY52 System

DASY52 system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY52 software defined. The DASY52 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




Fig-3.1 SPEAG DASY52 System Setup

3.2.1 Robot

The DASY52 system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version of CS8c from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)





Fig-3.2 SPEAG DASY52 System


FCC SAR Test Report

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.


Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	


Model	ET3DV6	
Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 2.3 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.4 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 16 mm) Tip diameter: 6.8 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.7 mm	


FCC SAR Test Report

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	


3.2.4 Phantoms


Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	


FCC SAR Test Report

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528 and IEC 62209-1. For the body tissue simulating liquids, the dielectric properties are defined in RSS-102 Annex D and IEC 62209-2. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

FCC SAR Test Report

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

FCC SAR Test Report

The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.




Fig-3.3 System Verification Setup

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Considerations Related to Proximity Sensor>

The device supports WWAN, WLAN, and Bluetooth capabilities. It is designed with a proximity sensor which can trigger/not trigger power reduction for WCDMA and LTE on Rear Face and Top Side of EUT for SAR compliance. Others RF capability (WLAN and Bluetooth) have no power reduction. The power levels for all wireless technologies and the power reduction please refer to section 4.6 of this report.

Proximity Sensor Triggering Distances (KDB 616217 D04 §6.2)

The proximity sensor triggering distance was determined per KDB 616217 for rear face and applicable edge. Summary for power verification per distance was tabulated in the below table.


Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	20	21	22	23	24	25	26	27	28	29	30
WCDMA II	11.4	11.5	11.6	11.6	11.6	11.7	23.5	23.1	23.5	23.5	23.1
WCDMA IV	13.4	13.5	13.2	13.1	13.1	13.2	23.2	23.4	23.0	23.3	23.3
WCDMA V	18.6	18.4	18.9	18.6	18.9	18.5	23.4	22.9	23.3	23.1	23.3
LTE 2	11.4	11.6	11.4	11.3	11.3	11.5	22.5	22.9	22.9	22.6	22.6
LTE 4	13.6	13.4	13.5	13.4	13.7	13.6	22.8	22.6	22.8	22.4	22.7
LTE 5	13.6	13.9	13.5	13.4	13.4	13.8	22.6	22.6	22.2	22.5	22.3
LTE 7	11.7	11.4	11.9	11.8	11.6	11.6	22.4	22.3	22.2	22.1	22.3
LTE 12	19.2	18.9	19.0	19.0	19.2	18.8	22.8	22.6	22.9	22.7	22.5
LTE 13	19.0	18.9	18.8	19.2	19.2	18.7	22.4	22.4	22.7	22.5	22.8
LTE 17	18.9	19.1	19.3	19.2	19.3	19.3	22.7	22.3	22.5	22.8	22.3
LTE 26	19.1	19.5	19.6	19.2	19.4	19.6	22.9	22.4	22.8	22.8	22.8
LTE 30	12.8	12.6	12.5	12.7	12.5	12.9	22.3	22.1	22.0	22.5	22.4
LTE 38	15.3	15.3	15.1	15.6	15.5	15.6	22.1	22.2	22.6	22.3	22.6
LTE 41	13.9	13.7	13.8	13.8	13.8	13.8	22.3	22.1	22.2	22.5	22.3
LTE 66	14.1	14.3	14.1	14.4	14.1	14.0	22.5	22.6	22.4	22.4	22.3

Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	19	20	21	22	23	24	25	26	27	28	29
WCDMA II	11.5	11.7	11.5	11.4	11.7	11.6	23.3	23.3	23.0	23.5	23.4
WCDMA IV	13.1	13.6	13.3	13.5	13.3	13.1	23.0	22.9	23.2	23.3	23.2
WCDMA V	18.9	18.8	18.5	18.5	18.8	18.9	23.0	23.2	23.3	23.0	23.3
LTE 2	11.6	11.4	11.7	11.7	11.6	11.7	22.5	22.8	23.0	22.6	23.0
LTE 4	13.4	13.4	13.5	13.5	13.5	13.9	22.3	22.8	22.4	22.8	22.6
LTE 5	13.8	13.6	13.8	13.7	13.7	13.6	22.6	22.6	22.2	22.4	22.4
LTE 7	11.5	11.9	11.5	11.8	11.8	11.9	22.6	22.4	22.2	22.1	22.2
LTE 12	19.0	18.8	18.8	19.3	19.3	19.1	22.8	22.9	22.9	22.8	22.6
LTE 13	19.2	19.1	18.7	18.9	18.9	19.2	22.9	22.8	22.8	22.7	22.7
LTE 17	19.4	18.9	19.4	19.2	19.1	19.2	22.3	22.6	22.5	22.6	22.7
LTE 26	19.6	19.1	19.6	19.4	19.6	19.6	22.8	22.8	22.9	22.8	22.8
LTE 30	12.7	12.7	12.5	12.6	12.5	12.6	22.4	22.0	22.4	22.1	22.4
LTE 38	15.3	15.5	15.6	15.6	15.2	15.5	22.2	22.4	22.5	22.2	22.6
LTE 41	13.9	14.1	13.8	14.0	14.0	14.1	22.3	22.0	22.5	22.5	22.1
LTE 66	14.0	14.3	14.3	14.0	14.4	14.3	22.3	22.7	22.5	22.6	22.7

FCC SAR Test Report

Proximity Sensor Tilt Angle Influences (KDB 616217 D04 §6.4)

The proximity sensor tilt angle influence was determined per KDB 616217 for applicable edge. Summary for proximity sensor tilt angle influence is shown in below.



Orientation	Separation Distance (mm)	Tilt Angle										
		-45°	-40°	-30°	-20°	-10°	0°	10°	20°	30°	40°	45°
Top Edge	24	On	On	On	On	On	On	On	On	On	On	On

Summary for Proximity Sensor Triggering Test

According to the procedures noticed in KDB 616217 D04, the proximity sensor triggering distance is 25 mm for EUT Rear Face, and 24 mm for Top Side. The separation distance of 24 mm determined by the smallest triggering distance on Top Side is used to access the tilt angle influence and the sensor does not release during ± 45 degree. Therefore, the smallest separation distance for tilt angle influence is 24 mm for the Top Side. The conservation triggering distances based on the separation distance for the sensor trigger / not triggered as EUT with power reduction at 0 mm, and EUT without power reduction at 20 mm for EUT Rear Face, and 20 mm for Top Side were used to test SAR.

The power reduction is depends on the proximity sensor input. For a steady SAR test, the power reduction was enabled or disabled manually by engineering software during SAR testing.

FCC SAR Test Report

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to WCDMA for Setup and Testing>

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices”, for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices”, for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

FCC SAR Test Report

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{HS}^{(1)(2)}$	CM ⁽³⁾ (dB)	MPR ⁽³⁾ (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	12/15 ⁽⁴⁾	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Release 6 HSPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{HS}^{(1)}$	β_{ec}	$\beta_{ed}^{(4)(5)}$	β_{ed} (SF)	β_{ed} (Codes)	CM ⁽²⁾ (dB)	MPR ⁽²⁾⁽⁶⁾ (dB)	AG ⁽⁵⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{HS} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPCCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

DC-HSDPA SAR Guidance

The 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 5 HSDPA, SAR is required for Rel. 8 DC-HSDPA. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

FCC SAR Test Report

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
12	V	V	V	V		
13			V	V		
17			V	V		
26	V	V	V	V	V	
30			V	V		
38			V	V	V	V
41			V	V	V	V
66	V	V	V	V	V	V

FCC SAR Test Report

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2


Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

FCC SAR Test Report

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 • Ts	2192 • Ts	2560 • Ts	7680 • Ts	2192 • Ts	2560 • Ts
1	19760 • Ts			20480 • Ts		
2	21952 • Ts			23040 • Ts		
3	24144 • Ts			25600 • Ts		
4	26336 • Ts	4384 • Ts	5120 • Ts	7680 • Ts	4384 • Ts	5120 • Ts
5	6592 • Ts			20480 • Ts		
6	19760 • Ts			23040 • Ts		
7	21952 • Ts			12800 • Ts		
8	24144 • Ts			-	-	-
9	13168 • Ts			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

FCC SAR Test Report

LTE Downlink Carrier Aggregation (CA) Setup Configurations

LTE Carrier Aggregation (CA) was defined in 3GPP release 10 and higher. The LTE device in CA mode has one Primary Component Carrier (PCC) and one or more Secondary Component Carriers (SCC). PCC acts as the anchor carrier and can optionally cross-schedule data transmission on SCC. The RRC connection is only handled by one cell, the PCC for downlink and uplink communications. After making a data connection to the PCC, the LTE device adds the SCC on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. The combinations of downlink carrier aggregation supported by this device are listed in below.

LTE CA Configurations and Bandwidth Combination Sets defined for Intra-Band Contiguous CA

Downlink CA Configuration	Component carriers in order of increasing carrier frequency				Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
	Channel bandwidths for carrier-1 [MHz]	Channel bandwidths for carrier-2 [MHz]	Channel bandwidths for carrier-3 [MHz]	Channel bandwidths for carrier-4 [MHz]		
CA_2C	5	20			40	0
	10	15, 20				
	15	10, 15, 20				
	20	5, 10, 15, 20				
CA_7B	15	5			20	0
CA_7C	15	15			40	0
	20	20				
	10	20			40	1
	15	15, 20				
	20	10, 15, 20				
	15	10, 15			40	2
	20	15, 20				

FCC SAR Test Report

Downlink CA Configuration	Component carriers in order of increasing carrier frequency				Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
	Channel bandwidths for carrier-1 [MHz]	Channel bandwidths for carrier-2 [MHz]	Channel bandwidths for carrier-3 [MHz]	Channel bandwidths for carrier-4 [MHz]		
CA_41C	10	20			40	0
	15	15, 20				
	20	10, 15, 20				
	5, 10	20			40	1
	15	15, 20				
	20	5, 10, 15, 20				
	10	15, 20			40	2
	15	10, 15, 20				
	20	10, 15, 20				
	10	20			40	3
	20	20				
CA_66D	5	20	20		60	0
	20	5	20			
	20	20	5			
	10	20	15			
	15	20	10			
	10, 15, 20	15, 20	20			
	15, 20	10	20			
	15	15, 20	15			
	20	15, 20	10, 15			
	20	10	15			

FCC SAR Test Report

LTE CA Configurations and Bandwidth Combination Sets defined for Intra-Band Non-Contiguous CA

Downlink CA Configuration	Component Carriers in order of Increasing Carrier Frequency				Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
	Channel Bandwidths for Carrier-1 [MHz]	Channel Bandwidths for Carrier-2 [MHz]	Channel Bandwidths for Carrier-3 [MHz]	Channel Bandwidths for Carrier-4 [MHz]		
CA_2A-2A	5, 10, 15, 20	5, 10, 15, 20			40	0
CA_4A-4A	5, 10, 15, 20	5, 10, 15, 20			40	0
	5, 10	5, 10			20	1
CA_7A-7A	5	15			40	0
	10	10, 15				
	15	15, 20				
	20	20				
	5, 10, 15, 20	5, 10, 15, 20			40	1
	5, 10, 15, 20	5, 10			30	2
	10, 15, 20	10, 15, 20			40	3
CA_41A-41A	10, 15, 20	10, 15, 20			40	0
	5, 10, 15, 20	5, 10, 15, 20			40	1

LTE CA Configurations and Bandwidth Combination Sets defined for Inter-Band CA (Two Bands)

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_2A-4A	2	1.4, 3, 5, 10, 15, 20	40	0
	4	5, 10, 15, 20		
	2	5, 10	20	1
	4	5, 10		
	2	5, 10, 15, 20	40	2
	4	5, 10, 15, 20		
CA_2A-5A	2	5, 10, 15, 20	30	0
	5	5, 10		
	2	5, 10	20	1
	5	5, 10		
CA_2A-2A-5A	2	Refer to CA_2A-2A (BCS0)	50	0
	5	5, 10		
CA_2C-5A	2	Refer to CA_2C (BCS0)	50	0
	5	5, 10		

FCC SAR Test Report

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_2A-12A	2	5, 10, 15, 20	30	0
	12	5, 10		
	2	5, 10, 15, 20	30	1
	12	3, 5, 10		
	2	5, 10	20	2
	12	5, 10		
CA_2A-13A	2	5, 10, 15, 20	30	0
	13	10		
	2	5, 10	20	1
	13	10		
CA_2A-2A-13A	2	Refer to CA_2A-2A (BCS0)	50	0
	13	10		
CA_2A-17A	2	5, 10	20	0
	17	5, 10		
CA_2A-29A	2	5, 10	20	0
	29	3, 5, 10		
	2	5, 10	20	1
	29	5, 10		
	2	5, 10, 15, 20	30	2
	29	5, 10		
CA_2A-30A	2	5, 10, 15, 20	30	0
	30	5, 10		

FCC SAR Test Report

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_2A-66A	2	1.4, 3, 5, 10, 15, 20	40	0
	66	5, 10, 15, 20		
	2	5, 10	20	1
	66	5, 10		
	2	5, 10, 15, 20	40	2
	66	5, 10, 15, 20		
CA_2A-66B	2	5, 10, 15, 20	40	0
	66	Refer to CA_66B (BCS0)		
CA_2A-66C	2	5, 10, 15, 20	60	0
	66	Refer to CA_66C (BCS0)		
CA_2A-66A-66A	2	5, 10, 15, 20	60	0
	66	Refer to CA_66A-66A (BCS0)		
CA_4A-5A	4	5, 10	20	0
	5	5, 10		
	4	5, 10, 15, 20	30	1
	5	5, 10		
CA_4A-4A-5A	4	Refer to CA_4A-4A (BCS0)	50	0
	5	5, 10		
CA_4A-12A	4	1.4, 3, 5, 10	20	0
	12	5, 10		
	4	1.4, 3, 5, 10, 15, 20	30	1
	12	5, 10		
	4	5, 10, 15, 20	30	2
	12	3, 5, 10		
	4	5, 10	20	3
	12	5, 10		
	4	5, 10, 15, 20	30	4
	12	5, 10		
	4	5, 10, 15	20	5
	12	5		

FCC SAR Test Report

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_4A-13A	4	5, 10, 15, 20	30	0
	13	10		
	4	5, 10	20	1
	13	10		
CA_4A-4A-13A	4	Refer to CA_4A-4A (BCS0)	50	0
	13	10		
CA_4A-17A	4	5, 10	20	0
	17	5, 10		
CA_4A-29A	4	5, 10	20	0
	29	3, 5, 10		
	4	5, 10	20	1
	29	5, 10		
	4	5, 10, 15, 20	30	2
	29	5, 10		
CA_4A-30A	4	5, 10, 15, 20	30	0
	30	5, 10		
CA_5A-7A	5	1.4, 3, 5, 10	30	0
	7	10, 15, 20		
	5	5, 10	30	1
	7	10, 15, 20		
CA_5A-30A	5	5, 10	20	0
	30	5, 10		
CA_5A-66A	5	5, 10	30	0
	66	5, 10, 15, 20		
CA_5A-66A-66A	5	5, 10	50	0
	66	Refer to CA_66A-66A (BCS0)		
CA_5A-66B	5	5, 10	30	0
	66	Refer to CA_66B (BCS0)		
CA_5A-66C	5	5, 10	50	0
	66	Refer to CA_66C (BCS0)		

FCC SAR Test Report

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_12A-30A	12	5, 10	20	0
	30	5, 10		
CA_13A-66A	13	5, 10	30	0
	66	5, 10, 15, 20		
CA_13A-66A-66A	13	5, 10	50	0
	66	Refer to CA_66A-66A (BCS0)		
CA_13A-66B	13	5, 10	30	0
	66	Refer to CA_66B (BCS0)		
CA_13A-66C	13	5, 10	50	0
	66	Refer to CA_66C (BCS0)		
CA_29A-30A	29	5, 10	20	0
	30	5, 10		

LTE CA Configurations and Bandwidth Combination Sets defined for Inter-Band CA (Three Bands)

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_2A-4A-5A	2	5, 10, 15,20	50	0
	4	5, 10, 15,20		
	5	5, 10		
CA_2A-4A-13A	2	5, 10, 15, 20	50	0
	4	5, 10, 15, 20		
	13	10		
CA_2C-5A-30A	2	Refer to CA_2C (BCS0)	60	0
	5	5, 10		
	30	5, 10		
CA_2A-5A-66A	2	5, 10, 15, 20	50	0
	5	5, 10		
	66	5, 10, 15, 20		
CA_2A-12A-30A	2	5, 10, 15, 20	40	0
	12	5, 10		
	30	5, 10		

FCC SAR Test Report

Downlink CA Configuration	LTE Bands	Channel Bandwidths for Carrier [MHz]	Maximum Aggregated Bandwidth [MHz]	Bandwidth Combination Set
CA_2A-13A-66A	2	5, 10, 15, 20	50	0
	13	5, 10		
	66	5, 10, 15, 20		
CA_2A-29A-30A	2	5, 10, 15, 20	40	0
	29	5, 10		
	30	5, 10		
CA_4A-5A-30A	4	5, 10, 15, 20	40	0
	5	5, 10		
	30	5, 10		
CA_4A-12A-30A	4	5, 10, 15, 20	40	0
	12	5, 10		
	30	5, 10		
CA_4A-29A-30A	4	5, 10, 15, 20	40	0
	29	5, 10		
	30	5, 10		

This device does not support full CA (Carrier Aggregation) features on 3GPP release 12. Its capability for LTE CA is for LTE band 41 only and supported configuration is shown in above. For network enhancement features, it does not support Wi-Fi Offloading, Enhanced SC-FDMA, Uplink MIMO, CoMP, HetNet, Relay, SON, Cross-Carrier Scheduling, eICIC, Enhanced Downlink MIMO, MBMS, M2M/D2D. All other uplink communications are identical to the LTE Release 8 specifications.

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

<Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

4.2 EUT Testing Position

4.2.1 Body Exposure Conditions

For laptop PC with antennas built-in on display screen, according to RSS-102 Supplementary procedures (SPR-001), IC requires SAR measurements to be performed with the side/edge of the display screen containing the built-in antenna pointing towards the flat phantom, unless the side/edge of the laptop computer containing the built-in antenna was already tested against the flat phantom to account for the user requirements (e.g. antenna in the laptop base). The separation distance shall not exceed 25 mm between the device and the flat phantom to show compliance for bystanders. Additional configurations regarding SAR testing for laptop computer are not required if the separation distance of 25 mm for bystanders represents the worst-case configuration.

The bystander SAR measurement procedure is as following.

1. If the integrated antenna is located in the back side of the display screen, the back side shall be facing towards the flat phantom at a distance not exceeding 25 mm.
2. If the integrated antenna is installed along the edge of the display screen, the edge shall be facing towards the flat phantom at a distance not exceeding 25 mm.
3. If the integrated antenna is installed at the corner of the display, both edges, as well as back side shall be tested to ensure that the worst-case configuration is captured.

For laptop PC, according to KDB 616217 D04, SAR evaluation is required for the bottom surface of the keyboard. This EUT was tested in the base of EUT directly against the flat phantom. The required minimum test separation distance for incorporating transmitters and antennas into laptop computer display is determined with the display screen opened at an angle of 90° to the keyboard compartment.




Fig-4.1 Illustration for Laptop Setup

FCC SAR Test Report

For full-size tablet, according to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.




Fig-4.2 Illustration for Tablet Setup

FCC SAR Test Report

4.2.2 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(MHz)}}{150} \right) \right]_{(mW)}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(mW)}$$

<For WWAN>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?
WCDMA II	23.5	224	5	61.88	Yes	2.2	61.88	Yes	228.5	1894 mW	No	2.2	61.88	Yes	193	1539 mW	No
WCDMA IV	23.5	224	5	59.31	Yes	2.2	59.31	Yes	228.5	1898 mW	No	2.2	59.31	Yes	193	1543 mW	No
WCDMA V	23.5	224	5	41.22	Yes	2.2	41.22	Yes	228.5	1170 mW	No	2.2	41.22	Yes	193	970 mW	No
LTE 2	23.5	224	5	61.91	Yes	2.2	61.91	Yes	228.5	1894 mW	No	2.2	61.91	Yes	193	1539 mW	No
LTE 4	23	200	5	52.99	Yes	2.2	52.99	Yes	228.5	1898 mW	No	2.2	52.99	Yes	193	1543 mW	No
LTE 5	23	200	5	36.86	Yes	2.2	36.86	Yes	228.5	1173 mW	No	2.2	36.86	Yes	193	972 mW	No
LTE 7	23	200	5	64.12	Yes	2.2	64.12	Yes	228.5	1879 mW	No	2.2	64.12	Yes	193	1524 mW	No
LTE 12	23	200	5	33.85	Yes	2.2	33.85	Yes	228.5	1029 mW	No	2.2	33.85	Yes	193	860 mW	No
LTE 13	23	200	5	35.49	Yes	2.2	35.49	Yes	228.5	1106 mW	No	2.2	35.49	Yes	193	919 mW	No
LTE 17	23	200	5	33.85	Yes	2.2	33.85	Yes	228.5	1029 mW	No	2.2	33.85	Yes	193	860 mW	No
LTE 26	23	200	5	36.86	Yes	2.2	36.86	Yes	228.5	1173 mW	No	2.2	36.86	Yes	193	972 mW	No
LTE 30	23	200	5	60.86	Yes	2.2	60.86	Yes	228.5	1884 mW	No	2.2	60.86	Yes	193	1529 mW	No
LTE 38	23	200	5	64.75	Yes	2.2	64.75	Yes	228.5	1878 mW	No	2.2	64.75	Yes	193	1523 mW	No
LTE 41	23	200	5	65.6	Yes	2.2	65.6	Yes	228.5	1876 mW	No	2.2	65.6	Yes	193	1521 mW	No
LTE 66	23	200	5	53.37	Yes	2.2	53.37	Yes	228.5	1897 mW	No	2.2	53.37	Yes	193	1542 mW	No

FCC SAR Test Report

<For WLAN Ant-0>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?
WLAN 2.4G	17	50	5	15.69	Yes	315	2746 mW	No	5.45	14.4	Yes	20	3.92	Yes	173	1326 mW	No
WLAN 5.2G	8.5	7	5	3.2	Yes	315	2716 mW	No	5.45	2.94	No	20	0.80	No	173	1296 mW	No
WLAN 5.3G	8.5	7	5	3.23	Yes	315	2715 mW	No	5.45	2.96	No	20	0.81	No	173	1295 mW	No
WLAN 5.6G	6	4	5	1.91	No	315	2713 mW	No	5.45	1.76	No	20	0.48	No	173	1293 mW	No
WLAN 5.8G	6	4	5	1.93	No	315	2712 mW	No	5.45	1.77	No	20	0.48	No	173	1292 mW	No

<For WLAN Ant-1>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?
WLAN 2.4G	13.5	22	5	6.9	Yes	71	306 mW	No	223	1826 mW	No	213	1726 mW	No	2	6.9	Yes
WLAN 5.2G	7.5	6	5	2.75	No	71	276 mW	No	223	1796 mW	No	213	1696 mW	No	2	2.75	No
WLAN 5.3G	7.5	6	5	2.77	No	71	275 mW	No	223	1795 mW	No	213	1695 mW	No	2	2.77	No
WLAN 5.6G	7.5	6	5	2.87	No	71	273 mW	No	223	1793 mW	No	213	1693 mW	No	2	2.87	No
WLAN 5.8G	8	6	5	2.9	No	71	272 mW	No	223	1792 mW	No	213	1692 mW	No	2	2.9	No
BT	13	20	5	6.3	Yes	71	305 mW	No	223	1825 mW	Yes	213	1725 mW	No	2	6.3	Yes

<For WLAN Ant-0 + Ant-1>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?
WLAN 2.4G	17	50	5	15.69	Yes	71	306 mW	No	5.45	14.4	Yes	20	3.92	Yes	2	15.69	Yes
WLAN 5.2G	11.5	14	5	6.41	Yes	71	276 mW	No	5.45	5.88	Yes	20	1.60	No	2	6.41	Yes
WLAN 5.3G	11.5	14	5	6.46	Yes	71	275 mW	No	5.45	5.92	Yes	20	1.61	No	2	6.46	Yes
WLAN 5.6G	11.5	14	5	6.7	Yes	71	273 mW	No	5.45	6.14	Yes	20	1.67	No	2	6.7	Yes
WLAN 5.8G	12	16	5	7.72	Yes	71	272 mW	No	5.45	7.09	Yes	20	1.93	No	2	7.72	Yes

FCC SAR Test Report

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Apr. 24, 2018	Body	750	23.3	0.969	53.811	0.96	55.5	0.94	-3.04
Apr. 24, 2018	Body	835	23.2	1.007	54.216	0.97	55.2	3.81	-1.78
Apr. 24, 2018	Body	835	23.3	0.972	56.099	0.97	55.2	0.21	1.63
Apr. 23, 2018	Body	1750	23.6	1.441	51.719	1.49	53.4	-3.29	-3.15
Apr. 24, 2018	Body	1750	23.3	1.456	52.165	1.49	53.4	-2.28	-2.31
Apr. 23, 2018	Body	1900	23.6	1.555	51.48	1.52	53.3	2.30	-3.41
Apr. 24, 2018	Body	1900	23.3	1.584	51.781	1.52	53.3	4.21	-2.85
Apr. 23, 2018	Body	2300	23.5	1.836	51.736	1.81	52.9	1.44	-2.20
Apr. 25, 2018	Body	2300	23.4	1.875	52.498	1.81	52.9	3.59	-0.76
May. 06, 2018	Body	2300	23.4	1.872	52.242	1.81	52.9	3.43	-1.24
Apr. 23, 2018	Body	2450	23.5	1.997	51.382	1.95	52.7	2.41	-2.50
Apr. 25, 2018	Body	2450	23.3	2.047	52.052	1.95	52.7	4.97	-1.23
Apr. 26, 2018	Body	2450	23.5	2.032	52.19	1.95	52.7	4.21	-0.97
May. 04, 2018	Body	2450	23.3	2.022	51.416	1.95	52.7	3.69	-2.44
Apr. 23, 2018	Body	2600	23.5	2.169	50.963	2.16	52.5	0.42	-2.93
Apr. 25, 2018	Body	2600	23.3	2.238	51.648	2.16	52.5	3.61	-1.62
May. 03, 2018	Body	5250	23.4	5.262	49.557	5.36	48.9	-1.83	1.34
Apr. 25, 2018	Body	5600	23.3	5.755	48.281	5.77	48.5	-0.26	-0.45
Apr. 26, 2018	Body	5600	23.5	5.957	46.623	5.77	48.5	3.24	-3.87
May. 03, 2018	Body	5600	23.4	5.713	49.047	5.77	48.5	-0.99	1.13
Apr. 25, 2018	Body	5800	23.3	6.006	48.412	6	48.2	0.10	0.44
Apr. 26, 2018	Body	5800	23.5	6.246	46.271	6	48.2	4.10	-4.00
May. 03, 2018	Body	5800	23.4	5.991	48.749	6	48.2	-0.15	1.14

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

FCC SAR Test Report

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Apr. 24, 2018	3820	Body	750	0.969	53.811	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 24, 2018	3971	Body	835	1.007	54.216	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 24, 2018	3820	Body	835	0.972	56.099	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 23, 2018	3971	Body	1750	1.441	51.719	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 24, 2018	3820	Body	1750	1.456	52.165	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 23, 2018	3971	Body	1900	1.555	51.48	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 24, 2018	3820	Body	1900	1.584	51.781	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 23, 2018	3971	Body	2300	1.836	51.736	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 25, 2018	3820	Body	2300	1.875	52.498	Pass	Pass	Pass	N/A	N/A	N/A
May. 06, 2018	3971	Body	2300	1.872	52.242	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 23, 2018	3971	Body	2450	1.997	51.382	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 25, 2018	3820	Body	2450	2.047	52.052	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 26, 2018	3820	Body	2450	2.032	52.19	Pass	Pass	Pass	OFDM	N/A	Pass
May. 04, 2018	3820	Body	2450	2.022	51.416	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 23, 2018	3971	Body	2600	2.169	50.963	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 25, 2018	3820	Body	2600	2.238	51.648	Pass	Pass	Pass	N/A	N/A	N/A
May. 03, 2018	3820	Body	5250	5.262	49.557	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 25, 2018	3820	Body	5600	5.755	48.281	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 26, 2018	3650	Body	5600	5.957	46.623	Pass	Pass	Pass	OFDM	N/A	Pass
May. 03, 2018	3820	Body	5600	5.713	49.047	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 25, 2018	3820	Body	5800	6.006	48.412	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 26, 2018	3650	Body	5800	6.246	46.271	Pass	Pass	Pass	OFDM	N/A	Pass
May. 03, 2018	3820	Body	5800	5.991	48.749	Pass	Pass	Pass	OFDM	N/A	Pass

FCC SAR Test Report

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Apr. 24, 2018	Body	750	8.72	2.19	8.76	0.46	1013	3820	917
Apr. 24, 2018	Body	835	9.61	2.48	9.92	3.23	4d121	3971	1431
Apr. 24, 2018	Body	835	9.61	2.23	8.92	-7.18	4d121	3820	917
Apr. 23, 2018	Body	1750	36.20	8.86	35.44	-2.10	1055	3971	1431
Apr. 24, 2018	Body	1750	36.20	9.26	37.04	2.32	1055	3820	917
Apr. 23, 2018	Body	1900	40.20	9.75	39.00	-2.99	5d036	3971	1431
Apr. 24, 2018	Body	1900	40.20	10.4	41.60	3.48	5d036	3820	917
Apr. 23, 2018	Body	2300	47.30	11	44.00	-6.98	1004	3971	1431
Apr. 25, 2018	Body	2300	47.30	12.2	48.80	3.17	1004	3820	917
May. 06, 2018	Body	2300	47.30	11.2	44.80	-5.29	1004	3971	1431
Apr. 23, 2018	Body	2450	49.70	12	48.00	-3.42	737	3971	1431
Apr. 25, 2018	Body	2450	49.70	13.1	52.40	5.43	737	3820	917
Apr. 26, 2018	Body	2450	49.70	12.6	50.40	1.41	737	3820	917
May. 04, 2018	Body	2450	49.70	12.5	50.00	0.60	737	3820	917
Apr. 23, 2018	Body	2600	54.30	14.20	56.80	4.60	1020	3971	1431
Apr. 25, 2018	Body	2600	54.30	14	56.00	3.13	1020	3820	917
May. 03, 2018	Body	5250	76.50	7.47	74.70	-2.35	1019	3820	917
Apr. 25, 2018	Body	5600	79.70	7.81	78.10	-2.01	1019	3820	917
Apr. 26, 2018	Body	5600	79.70	7.84	78.40	-1.63	1019	3650	861
May. 03, 2018	Body	5600	79.70	7.5	75.00	-5.90	1019	3820	917
Apr. 25, 2018	Body	5800	76.90	7.25	72.50	-5.72	1019	3820	917
Apr. 26, 2018	Body	5800	76.90	7.9	79.00	2.73	1019	3650	861
May. 03, 2018	Body	5800	76.90	7.56	75.60	-1.69	1019	3820	917

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

FCC SAR Test Report

4.6 Maximum Output Power

4.6.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Laptop

Mode	WCDMA Band II	WCDMA Band IV	WCDMA Band V
RMC 12.2K	12.0	14.0	19.0
HSDPA / HSUPA / DC-HSDPA	12.0	14.0	19.0

Mode	LTE 2	LTE 4	LTE 5	LTE 7
Maximum Target Power	12.0	14.0	19.5	12.0

Mode	LTE 12	LTE 13	LTE 17	LTE 26
Maximum Target Power	19.5	19.5	19.5	20.0

Mode	LTE 30	LTE 38	LTE 41	LTE 66
Maximum Target Power	13.0	16.0	14.5	14.5

Tablet

Mode	WCDMA Band II (without Power Reduction)	WCDMA Band II (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	23.5	12.0	11.5
HSDPA / HSUPA / DC-HSDPA	23.5	12.0	11.5

Mode	WCDMA Band IV (without Power Reduction)	WCDMA Band IV (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	23.5	14.0	9.5
HSDPA / HSUPA / DC-HSDPA	23.5	14.0	9.5

Mode	WCDMA Band V (without Power Reduction)	WCDMA Band V (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	23.5	19.0	4.5
HSDPA / HSUPA / DC-HSDPA	23.5	19.0	4.5

Mode	LTE 2 (without Power Reduction)	LTE 2 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.5	12.0	11.5

Mode	LTE 4 (without Power Reduction)	LTE 4 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	14.0	9.0

FCC SAR Test Report

Mode	LTE 5 (without Power Reduction)	LTE 5 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	19.5	3.5

Mode	LTE 7 (without Power Reduction)	LTE 7 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	12.0	11.0

Mode	LTE 12 (without Power Reduction)	LTE 12 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	19.5	3.5

Mode	LTE 13 (without Power Reduction)	LTE 13 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	19.5	3.5

Mode	LTE 17 (without Power Reduction)	LTE 17 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	19.5	3.5

Mode	LTE 26 (without Power Reduction)	LTE 26 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	20.0	3.0

Mode	LTE 30 (without Power Reduction)	LTE 30 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	13.0	10.0

Mode	LTE 38 (without Power Reduction)	LTE 38 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	16.0	7.0

Mode	LTE 41 (without Power Reduction)	LTE 41 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	14.5	8.5

Mode	LTE 66 (without Power Reduction)	LTE 66 (with Power Reduction)	Power Reduction (dB)
Maximum Target Power	23.0	14.5	8.5

FCC SAR Test Report

Laptop

Mode	Tx Antenna	2.4G WLAN
802.11b	Ant-0	CH1:11:17.0 CH12:13.0 CH13:7.0
	Ant-1	CH1:11:16.0 CH12:14.0 CH13:7.0
802.11g	Ant-0	CH1:15.0 CH6:17.0 CH11:15.0 CH12:11.0 CH13:-4.0
	Ant-1	CH1:16.0 Ch6:17.0 Ch11:16.0 CH12:12.0 CH13:-4.0
802.11n HT20	Ant-0	CH1:15.0 CH6:17.0 CH11:15.0 CH12:11.0 CH13:-4.0
	Ant-1	CH1:16.0 Ch6:17.0 Ch11:16.0 CH12:12.0 CH13:-4.0
	Ant-0+Ant-1	CH1:14.0 CH6:17.0 CH11:14.0 CH12:7.0 CH13:-8.0
802.11n HT40	Ant-0	Ch3:12.0 Ch6:15.5 Ch9:14.0
	Ant-1	Ch3:15.0 Ch6:15.5 Ch9:14.0
	Ant-0+Ant-1	CH3:11.0 CH6:12.5 CH9:12.0

FCC SAR Test Report

Mode	Tx Antenna	5.2G WLAN
802.11a	Ant-0	Ch36:17.0 Ch40-48:19.0
	Ant-1	12.5
802.11n HT20	Ant-0	Ch36:17.0 Ch40-48:19.0
	Ant-1	12.5
	Ant-0+Ant-1	Ch36:15.0 Ch40-44:18.0 Ch48:17.0
802.11n HT40	Ant-0	CH38:16.0 CH46:19.0
	Ant-1	12.5
	Ant-0+Ant-1	CH38:11.0 CH46:18.0
802.11ac VHT80	Ant-0	12.0
	Ant-1	12.0
	Ant-0+Ant-1	9.0

Mode	Tx Antenna	5.3G WLAN
802.11a	Ant-0	Ch52-60:19.0 Ch64:16.0
	Ant-1	12.5
802.11n HT20	Ant-0	Ch52-60:19.0 Ch64:16.0
	Ant-1	12.5
	Ant-0+Ant-1	Ch52-60:18.0 Ch64:12.0
802.11n HT40	Ant-0	CH54:19.0 CH62:12.0
	Ant-1	12.5
	Ant-0+Ant-1	CH54:18.0 CH62:10.0
802.11ac VHT80	Ant-0	10.0
	Ant-1	11.0
	Ant-0+Ant-1	8.0

FCC SAR Test Report

Mode	Tx Antenna	5.6G WLAN
802.11a	Ant-0	Ch100:17.0 Ch116-132:19.0 Ch140:16.0 Ch144:18.0
	Ant-1	12.0
802.11n HT20	Ant-0	Ch100:17.0 Ch116-132:19.0 Ch140:16.0 Ch144:18.0
	Ant-1	12.0
	Ant-0+Ant-1	Ch100:15.0 Ch116-132:18.0 Ch140:14.0 Ch144:17.0
802.11n HT40	Ant-0	CH102:17.0 CH110-126:19.0 CH134:18.0 CH42:19.0
	Ant-1	12.0
	Ant-0+Ant-1	CH102:12.0 CH110:17.0 CH118-126:18.0 CH134:16.0 CH142:18.0
802.11ac VHT80	Ant-0	Ch106:12.0 Ch122-138:18.0
	Ant-1	12.0
	Ant-0+Ant-1	Ch106:10.0 Ch122:16.0 Ch138:17.0

Mode	Tx Antenna	5.8G WLAN
802.11a	Ant-0	19.0
	Ant-1	12.0
802.11n HT20	Ant-0	19.0
	Ant-1	12.0
	Ant-0+Ant-1	16.0
802.11n HT40	Ant-0	19.0
	Ant-1	12.0
	Ant-0+Ant-1	16.0
802.11ac VHT80	Ant-0	17.0
	Ant-1	12.0
	Ant-0+Ant-1	15.5

Mode	2.4G Bluetooth
Bluetooth DH	13.0
Bluetooth LE	12.0

FCC SAR Test Report

Tablet

Mode	Tx Antenna	2.4G WLAN
802.11b	Ant-0	CH1:11:17.0 CH12:13.0 CH13:7.0
	Ant-1	CH1:12:13.5 CH13:7.0
802.11g	Ant-0	CH1:15.0 CH6:17.0 CH11:15.0 CH12:11.0 CH13:-4.0
	Ant-1	CH1:11:13.5 CH12:12.0 CH13:-4.0
802.11n HT20	Ant-0	CH1:15.0 CH6:17.0 CH11:15.0 CH12:11.0 CH13:-4.0
	Ant-1	CH1:11:13.5 CH12:12.0 CH13:-4.0
	Ant-0+Ant-1	CH1:14.0 CH6:17.0 CH11:14.0 CH12:7.0 CH13:-6.5
802.11n HT40	Ant-0	17.0
	Ant-1	13.5
	Ant-0+Ant-1	CH3:11.0 CH6:14.0 CH9:12.0

Mode	Tx Antenna	5.2G WLAN
802.11a	Ant-0	8.5
	Ant-1	7.5
802.11n HT20	Ant-0	8.5
	Ant-1	7.5
	Ant-0+Ant-1	11.5
802.11n HT40	Ant-0	8.5
	Ant-1	7.5
	Ant-0+Ant-1	11.5
802.11ac VHT80	Ant-0	8.5
	Ant-1	7.5
	Ant-0+Ant-1	11.5

FCC SAR Test Report

Mode	Tx Antenna	5.3G WLAN
802.11a	Ant-0	8.5
	Ant-1	7.5
802.11n HT20	Ant-0	8.5
	Ant-1	7.5
	Ant-0+Ant-1	11.5
802.11n HT40	Ant-0	8.5
	Ant-1	7.5
	Ant-0+Ant-1	11.5
802.11ac VHT80	Ant-0	8.5
	Ant-1	7.5
	Ant-0+Ant-1	11.5

Mode	Tx Antenna	5.6G WLAN
802.11a	Ant-0	6.0
	Ant-1	7.5
802.11n HT20	Ant-0	6.0
	Ant-1	7.5
	Ant-0+Ant-1	11.5
802.11n HT40	Ant-0	6.0
	Ant-1	7.5
	Ant-0+Ant-1	11.5
802.11ac VHT80	Ant-0	6.0
	Ant-1	7.5
	Ant-0+Ant-1	11.5

Mode	Tx Antenna	5.8G WLAN
802.11a	Ant-0	6.0
	Ant-1	8.0
802.11n HT20	Ant-0	6.0
	Ant-1	8.0
	Ant-0+Ant-1	12.0
802.11n HT40	Ant-0	6.0
	Ant-1	8.0
	Ant-0+Ant-1	12.0
802.11ac VHT80	Ant-0	6.0
	Ant-1	8.0
	Ant-0+Ant-1	12.0

Mode	2.4G Bluetooth
Bluetooth DH	13.0
Bluetooth LE	12.0

FCC SAR Test Report

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Laptop

Band	WCDMA Band II			WCDMA Band IV			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6	
RMC 12.2K	11.87	11.83	11.90	13.51	13.54	13.62	18.78	18.93	18.84	-
HSDPA Subtest-1	11.83	11.79	11.84	13.48	13.51	13.59	18.63	18.78	18.69	0
HSDPA Subtest-2	11.82	11.78	11.83	13.46	13.49	13.57	18.61	18.76	18.67	0
HSDPA Subtest-3	11.83	11.79	11.84	13.45	13.48	13.56	18.65	18.80	18.71	0
HSDPA Subtest-4	11.86	11.82	11.87	13.44	13.47	13.55	18.67	18.82	18.73	0
DC-HSDPA Subtest-1	11.78	11.74	11.79	13.40	13.43	13.51	18.60	18.75	18.66	0
DC-HSDPA Subtest-2	11.79	11.75	11.81	13.38	13.41	13.49	18.56	18.71	18.62	0
DC-HSDPA Subtest-3	11.78	11.74	11.82	13.37	13.40	13.48	18.61	18.76	18.68	0
DC-HSDPA Subtest-4	11.80	11.77	11.85	13.36	13.39	13.47	18.64	18.80	18.71	0
HSUPA Subtest-1	11.88	11.84	11.87	13.45	13.48	13.56	18.57	18.72	18.63	0
HSUPA Subtest-2	11.89	11.85	11.88	13.43	13.46	13.54	18.61	18.76	18.67	0
HSUPA Subtest-3	11.79	11.75	11.80	13.40	13.43	13.51	18.56	18.71	18.62	0
HSUPA Subtest-4	11.70	11.66	11.71	13.42	13.45	13.53	18.60	18.75	18.66	0
HSUPA Subtest-5	11.80	11.76	11.81	13.41	13.44	13.52	18.58	18.73	18.64	0

FCC SAR Test Report

LTE Band 2															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100				Channel		18675	18900	19125	
		Frequency (MHz)		1860	1880	1900				Frequency (MHz)		1857.5	1880	1902.5	
20M	QPSK	1	0	11.82	11.62	11.54	0	15M	QPSK	1	0	11.81	11.61	11.54	0
		1	50	11.80	11.60	11.52	0			1	37	11.75	11.52	11.52	0
		1	99	11.66	11.46	11.38	0			1	74	11.62	11.36	11.37	0
		50	0	11.85	11.65	11.57	0			36	0	11.77	11.64	11.52	0
		50	25	11.75	11.55	11.47	0			36	19	11.65	11.52	11.43	0
		50	50	11.65	11.45	11.37	0			36	39	11.57	11.43	11.27	0
		100	0	11.84	11.64	11.56	0			75	0	11.76	11.55	11.49	0
	16QAM	1	0	11.76	11.55	11.51	0		16QAM	1	0	11.73	11.48	11.43	0
		1	50	11.70	11.52	11.42	0			1	37	11.77	11.43	11.41	0
		1	99	11.56	11.38	11.29	0			1	74	11.59	11.40	11.26	0
		50	0	11.81	11.58	11.52	0			36	0	11.70	11.56	11.45	0
		50	25	11.75	11.47	11.47	0			36	19	11.66	11.47	11.36	0
		50	50	11.64	11.38	11.28	0			36	39	11.50	11.32	11.31	0
		100	0	11.83	11.58	11.47	0			75	0	11.81	11.51	11.37	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18650	18900	19150				Channel		18625	18900	19175	
		Frequency (MHz)		1855	1880	1905				Frequency (MHz)		1852.5	1880	1907.5	
10M	QPSK	1	0	11.72	11.39	11.46	0	5M	QPSK	1	0	11.78	11.58	11.28	0
		1	24	11.60	11.36	11.34	0			1	12	11.71	11.54	11.34	0
		1	49	11.59	11.42	11.33	0			1	24	11.54	11.30	11.08	0
		25	0	11.71	11.50	11.39	0			12	0	11.82	11.62	11.40	0
		25	12	11.71	11.44	11.34	0			12	6	11.70	11.35	11.25	0
		25	25	11.51	11.31	11.33	0			12	13	11.61	11.31	10.98	0
		50	0	11.64	11.58	11.47	0			25	0	11.71	11.44	11.32	0
	16QAM	1	0	11.67	11.56	11.31	0		16QAM	1	0	11.61	11.55	11.33	0
		1	24	11.60	11.47	11.40	0			1	12	11.65	11.45	11.34	0
		1	49	11.53	11.32	11.26	0			1	24	11.56	11.23	11.31	0
		25	0	11.56	11.36	11.32	0			12	0	11.71	11.50	11.42	0
		25	12	11.57	11.48	11.21	0			12	6	11.62	11.46	11.22	0
		25	25	11.50	11.35	11.27	0			12	13	11.57	11.32	11.19	0
		50	0	11.62	11.54	11.45	0			25	0	11.72	11.35	11.49	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18615	18900	19185				Channel		18607	18900	19193	
		Frequency (MHz)		1851.5	1880	1908.5				Frequency (MHz)		1850.7	1880	1909.3	
3M	QPSK	1	0	11.69	11.41	11.38	0	1.4M	QPSK	1	0	11.63	11.58	11.49	0
		1	7	11.70	11.56	11.43	0			1	2	11.72	11.56	11.38	0
		1	14	11.52	11.34	11.18	0			1	5	11.42	11.39	11.35	0
		8	0	11.71	11.62	11.54	0			3	0	11.68	11.60	11.49	0
		8	3	11.53	11.35	11.30	0			3	1	11.57	11.39	11.24	0
		8	7	11.41	11.20	11.19	0			3	3	11.62	11.36	11.29	0
		15	0	11.80	11.49	11.51	0			6	0	11.77	11.54	11.41	0
	16QAM	1	0	11.55	11.42	11.34	0		16QAM	1	0	11.59	11.52	11.33	0
		1	7	11.66	11.45	11.44	0			1	2	11.63	11.35	11.48	0
		1	14	11.44	11.20	11.21	0			1	5	11.41	11.26	11.17	0
		8	0	11.55	11.41	11.28	0			3	0	11.71	11.44	11.24	0
		8	3	11.63	11.42	11.38	0			3	1	11.56	11.45	11.35	0
		8	7	11.51	11.24	11.21	0			3	3	11.43	11.12	11.17	0
		15	0	11.61	11.47	11.44	0			6	0	11.70	11.55	11.40	0

FCC SAR Test Report

LTE Band 4															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20050	20175	20300				Channel		20025	20175	20325	
		Frequency (MHz)		1720.0	1732.5	1745.0				Frequency (MHz)		1717.5	1732.5	1747.5	
20M	QPSK	1	0	13.92	13.84	13.99	0	15M	QPSK	1	0	13.92	13.82	13.89	0
		1	50	13.91	13.77	13.94	0			1	37	13.81	13.74	13.88	0
		1	99	13.78	13.64	13.81	0			1	74	13.69	13.54	13.71	0
		50	0	13.97	13.83	13.98	0			36	0	13.95	13.79	13.94	0
		50	25	13.89	13.75	13.92	0			36	19	13.85	13.73	13.90	0
		50	50	13.79	13.65	13.82	0			36	39	13.75	13.57	13.76	0
	16QAM	100	0	13.90	13.76	13.93	0			75	0	13.80	13.66	13.85	0
		1	0	13.89	13.77	13.98	0		16QAM	1	0	13.82	13.66	13.89	0
		1	50	13.86	13.76	13.85	0			1	37	13.77	13.65	13.86	0
		1	99	13.77	13.59	13.71	0			1	74	13.68	13.61	13.79	0
		50	0	13.90	13.73	13.88	0			36	0	13.93	13.71	13.86	0
		50	25	13.86	13.69	13.89	0			36	19	13.76	13.63	13.81	0
10M	QPSK	50	50	13.69	13.59	13.74	0	5M	16QAM	36	39	13.65	13.49	13.68	0
		100	0	13.87	13.67	13.89	0			75	0	13.79	13.61	13.84	0
	16QAM	1	0	13.72	13.72	13.85	0		QPSK	1	0	13.77	13.70	13.83	0
		1	24	13.71	13.58	13.71	0			1	12	13.72	13.75	13.66	0
		1	49	13.56	13.45	13.66	0			1	24	13.67	13.48	13.71	0
		25	0	13.84	13.65	13.90	0			12	0	13.80	13.73	13.82	0
	16QAM	25	12	13.67	13.67	13.73	0		16QAM	12	6	13.79	13.75	13.71	0
		25	25	13.75	13.45	13.60	0			12	13	13.64	13.53	13.58	0
		50	0	13.80	13.60	13.82	0			25	0	13.80	13.56	13.75	0
		1	0	13.75	13.65	13.77	0		16QAM	1	0	13.80	13.63	13.90	0
		1	24	13.81	13.61	13.71	0			1	12	13.82	13.61	13.89	0
		1	49	13.66	13.33	13.68	0			1	24	13.48	13.36	13.68	0
3M	QPSK	25	0	13.68	13.60	13.84	0	1.4M	QPSK	12	0	13.73	13.73	13.91	0
		25	12	13.77	13.48	13.75	0			12	6	13.78	13.56	13.80	0
		25	25	13.64	13.47	13.64	0			12	13	13.59	13.44	13.65	0
		50	0	13.68	13.58	13.74	0			25	0	13.75	13.60	13.81	0
	16QAM	1	0	13.77	13.73	13.87	0		16QAM	1	0	13.80	13.60	13.90	0
		1	7	13.82	13.70	13.81	0			1	2	13.71	13.58	13.92	0
		1	14	13.57	13.58	13.74	0			1	5	13.61	13.58	13.76	0
		8	0	13.87	13.74	13.95	0			3	0	13.85	13.65	13.88	0
		8	3	13.79	13.58	13.81	0			3	1	13.79	13.73	13.81	0
		8	7	13.60	13.57	13.67	0			3	3	13.71	13.58	13.75	0
3M	QPSK	15	0	13.76	13.55	13.75	0		16QAM	6	0	13.73	13.52	13.69	0
		1	0	13.78	13.73	13.85	0			1	0	13.78	13.67	13.78	0
		1	7	13.67	13.54	13.72	0			1	2	13.75	13.58	13.90	0
		1	14	13.65	13.48	13.56	0			1	5	13.56	13.56	13.65	0
		8	0	13.78	13.71	13.86	0			3	0	13.89	13.67	13.77	0
		8	3	13.78	13.52	13.74	0			3	1	13.69	13.47	13.71	0
	16QAM	8	7	13.60	13.46	13.62	0			3	3	13.57	13.41	13.54	0
		15	0	13.73	13.49	13.71	0			6	0	13.69	13.53	13.74	0

FCC SAR Test Report

LTE Band 5															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600				Channel		20425	20525	20625	
		Frequency (MHz)		829.0	836.5	844.0				Frequency (MHz)		826.5	836.5	846.5	
10M	QPSK	1	0	19.32	19.28	19.20	0	5M	QPSK	1	0	19.10	19.12	19.02	0
		1	24	19.17	19.13	19.05	0			1	12	19.00	18.98	18.84	0
		1	49	19.13	19.09	19.01	0			1	24	19.00	18.91	18.84	0
		25	0	19.21	19.17	19.09	0			12	0	19.03	18.99	18.90	0
		25	12	19.10	19.06	18.98	0			12	6	19.04	18.92	18.85	0
		25	25	19.09	19.05	18.97	0			12	13	18.92	18.97	18.80	0
		50	0	19.09	19.05	18.97	0			25	0	19.03	18.91	18.73	0
	16QAM	1	0	19.29	19.25	19.13	0		16QAM	1	0	19.08	19.26	19.13	0
		1	24	19.07	19.12	19.01	0			1	12	19.00	18.98	18.76	0
		1	49	19.13	19.07	18.99	0			1	24	18.91	18.95	18.77	0
		25	0	19.14	19.16	19.09	0			12	0	19.00	18.98	19.01	0
		25	12	19.10	18.98	18.93	0			12	6	18.96	18.85	18.72	0
25		25	19.08	19.02	18.91	0	12	13		18.91	18.99	18.75	0		
50	0	19.08	19.02	18.96	0	25	0	19.08	18.87	18.71	0				
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20415	20525	20635				Channel		20407	20525	20643	
		Frequency (MHz)		825.5	836.5	847.5				Frequency (MHz)		824.7	836.5	848.3	
3M	QPSK	1	0	19.21	19.06	19.06	0	1.4M	QPSK	1	0	19.27	19.23	19.13	0
		1	7	19.03	18.96	18.86	0			1	2	18.95	18.99	19.00	0
		1	14	18.93	18.86	18.81	0			1	5	18.96	18.87	18.89	0
		8	0	19.13	19.13	19.00	0			3	0	19.14	19.11	19.04	0
		8	3	18.98	18.96	18.90	0			3	1	18.88	18.92	18.90	0
		8	7	18.93	18.97	18.83	0			3	3	18.91	18.89	18.83	0
	16QAM	15	0	18.97	18.87	18.81	0		16QAM	6	0	18.92	18.85	18.89	0
		1	0	19.03	18.94	19.06	0			1	0	19.13	19.24	18.97	0
		1	7	18.99	19.04	19.00	0			1	2	19.05	18.97	18.97	0
		1	14	19.08	18.89	18.76	0			1	5	19.10	19.06	18.90	0
		8	0	18.93	18.97	18.97	0			3	0	19.14	18.92	18.83	0
		8	3	18.96	18.86	18.81	0			3	1	18.96	18.86	18.88	0
8	7	18.78	18.90	18.79	0	3	3	18.93	18.98	18.77	0				
15	0	18.82	18.91	18.76	0	6	0	18.98	18.89	18.81	0				

FCC SAR Test Report

LTE Band 7															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency (MHz)		2510.0	2535.0	2560.0				Frequency (MHz)		2507.5	2535.0	2562.5	
20M	QPSK	1	0	11.90	11.92	11.99	0	15M	QPSK	1	0	11.89	11.85	11.97	0
		1	50	11.74	11.76	11.83	0			1	37	11.72	11.69	11.75	0
		1	99	11.89	11.91	11.98	0			1	74	11.81	11.91	11.93	0
		50	0	11.89	11.91	11.98	0			36	0	11.84	11.81	11.93	0
		50	25	11.87	11.89	11.96	0			36	19	11.80	11.79	11.93	0
		50	50	11.86	11.88	11.95	0			36	39	11.76	11.78	11.91	0
		100	0	11.88	11.90	11.97	0			75	0	11.80	11.84	11.96	0
	16QAM	1	0	11.85	11.86	11.95	0		16QAM	1	0	11.87	11.76	11.89	0
		1	50	11.67	11.74	11.80	0			1	37	11.64	11.71	11.77	0
		1	99	11.88	11.87	11.93	0			1	74	11.79	11.80	11.86	0
		50	0	11.79	11.86	11.96	0			36	0	11.76	11.83	11.81	0
		50	25	11.84	11.81	11.95	0			36	19	11.77	11.80	11.92	0
		50	50	11.84	11.85	11.92	0			36	39	11.77	11.77	11.91	0
10M	QPSK	1	0	11.81	11.84	11.93	0	5M	QPSK	1	0	11.86	11.79	11.75	0
		1	24	11.58	11.60	11.75	0			1	12	11.59	11.63	11.53	0
		1	49	11.72	11.75	11.84	0			1	24	11.77	11.72	11.77	0
		25	0	11.83	11.77	11.93	0			12	0	11.73	11.83	11.65	0
		25	12	11.71	11.72	11.88	0			12	6	11.74	11.73	11.78	0
		25	25	11.81	11.85	11.82	0			12	13	11.72	11.84	11.79	0
	16QAM	50	0	11.78	11.82	11.84	0			25	0	11.75	11.78	11.78	0
		1	0	11.80	11.80	11.81	0		16QAM	1	0	11.77	11.74	11.88	0
		1	24	11.52	11.59	11.72	0			1	12	11.60	11.68	11.72	0
		1	49	11.82	11.74	11.81	0			1	24	11.78	11.79	11.82	0
		25	0	11.64	11.59	11.74	0			12	0	11.77	11.74	11.88	0
		25	12	11.66	11.71	11.71	0			12	6	11.70	11.68	11.65	0
5M	QPSK	25	25	11.78	11.77	11.64	0		16QAM	12	13	11.79	11.56	11.75	0
		50	0	11.67	11.80	11.82	0			25	0	11.69	11.68	11.82	0
	16QAM	1	0	11.81	11.84	11.93	0		QPSK	1	0	11.86	11.79	11.75	0
		1	24	11.58	11.60	11.75	0			1	12	11.59	11.63	11.53	0
		1	49	11.72	11.75	11.84	0			1	24	11.77	11.72	11.77	0
		25	0	11.83	11.77	11.93	0			12	0	11.73	11.83	11.65	0
		25	12	11.71	11.72	11.88	0			12	6	11.74	11.73	11.78	0
		25	25	11.81	11.85	11.82	0			12	13	11.72	11.84	11.79	0
	16QAM	50	0	11.78	11.82	11.84	0			25	0	11.75	11.78	11.78	0
		1	0	11.80	11.80	11.81	0		16QAM	1	0	11.77	11.74	11.88	0
		1	24	11.52	11.59	11.72	0			1	12	11.60	11.68	11.72	0
		1	49	11.82	11.74	11.81	0			1	24	11.78	11.79	11.82	0
		25	0	11.64	11.59	11.74	0			12	0	11.77	11.74	11.88	0
		25	12	11.66	11.71	11.71	0			12	6	11.70	11.68	11.65	0

FCC SAR Test Report

LTE Band 12															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23060	23095	23130				Channel		23035	23095	23155	
		Frequency (MHz)		704.0	707.5	711.0				Frequency (MHz)		701.5	707.5	713.5	
10M	QPSK	1	0	19.33	19.29	19.30	0	5M	QPSK	1	0	19.18	19.11	19.09	0
		1	24	19.35	19.31	19.32	0			1	12	19.25	19.07	19.03	0
		1	49	19.30	19.26	19.27	0			1	24	19.09	19.11	19.14	0
		25	0	19.29	19.25	19.26	0			12	0	19.15	19.12	19.04	0
		25	12	19.34	19.30	19.31	0			12	6	19.20	19.15	19.16	0
		25	25	19.26	19.22	19.23	0			12	13	19.13	19.07	19.02	0
	16QAM	50	0	19.28	19.24	19.25	0			25	0	19.17	19.06	19.03	0
		1	0	19.33	19.25	19.25	0		16QAM	1	0	19.24	19.15	19.22	0
		1	24	19.25	19.27	19.27	0			1	12	19.17	19.11	19.12	0
		1	49	19.25	19.25	19.19	0			1	24	19.01	19.05	19.18	0
		25	0	19.26	19.25	19.25	0			12	0	19.04	19.07	19.13	0
		25	12	19.30	19.24	19.30	0			12	6	19.19	18.99	19.15	0
3M	QPSK	25	25	19.16	19.12	19.13	0			12	13	19.08	19.00	19.02	0
		50	0	19.22	19.21	19.20	0			25	0	19.09	19.05	19.16	0
	16QAM	1	0	19.14	19.21	19.19	0		QPSK	1	0	19.26	19.15	19.19	0
		1	7	19.10	19.08	19.20	0			1	2	19.32	19.08	19.16	0
		1	14	19.17	19.04	19.10	0			1	5	19.18	19.09	19.14	0
		8	0	19.20	19.17	19.12	0			3	0	19.15	19.09	19.11	0
		8	3	19.19	19.15	19.17	0			3	1	19.25	19.22	19.31	0
		8	7	19.20	19.20	19.08	0			3	3	19.20	19.16	19.09	0
	16QAM	15	0	19.13	19.22	19.12	0			6	0	19.22	19.09	19.10	0
		1	0	19.05	19.18	19.07	0	1.4M	16QAM	1	0	19.17	19.15	19.22	0
		1	7	19.19	19.18	19.15	0			1	2	19.17	19.04	19.10	0
		1	14	19.29	19.14	19.10	0			1	5	19.06	19.10	19.10	0
		8	0	19.09	19.06	19.08	0			3	0	19.18	19.05	19.07	0
		8	3	19.24	19.14	19.18	0			3	1	19.15	19.13	19.03	0
		8	7	18.99	19.06	19.11	0			3	3	19.11	18.97	19.13	0
10M	QPSK	15	0	18.98	19.06	19.15	0			6	0	19.08	19.00	19.03	0
		1	0		19.13		0	5M	QPSK	1	0	18.94	19.00	18.96	0
		1	24		19.01		0			1	12	18.83	18.89	18.85	0
		1	49		19.22		0			1	24	18.98	19.04	19.00	0
		25	0		19.18		0			12	0	19.02	19.08	19.04	0
		25	12		19.04		0			12	6	18.81	18.87	18.83	0
	16QAM	25	25		19.11		0			12	13	18.96	19.02	18.98	0
		50	0		19.19		0			25	0	18.99	19.05	19.01	0
		1	0		19.07		0		16QAM	1	0	18.85	18.91	18.87	0
		1	24		18.91		0			1	12	18.83	18.89	18.85	0
		1	49		19.22		0			1	24	18.92	18.98	18.94	0
		25	0		19.14		0			12	0	18.96	19.02	18.98	0
10M	QPSK	25	12		18.96		0			12	6	18.80	18.86	18.82	0
		25	25		19.08		0			12	13	18.80	18.86	18.82	0
		50	0		19.14		0			25	0	18.97	19.03	18.99	0
	16QAM	1	0				0	5M	QPSK	1	0	18.94	19.00	18.96	0
		1	24				0			1	12	18.83	18.89	18.85	0
		1	49				0			1	24	18.98	19.04	19.00	0
		25	0				0			12	0	19.02	19.08	19.04	0
		25	12				0			12	6	18.81	18.87	18.83	0
		25	25				0			12	13	18.96	19.02	18.98	0
10M	QPSK	50	0				0			25	0	18.99	19.05	19.01	0
		1	0				0		16QAM	1	0	18.85	18.91	18.87	0
		1	24				0			1	12	18.83	18.89	18.85	0
		1	49				0			1	24	18.92	18.98	18.94	0
		25	0				0			12	0	18.96	19.02	18.98	0
		25	12				0			12	6	18.80	18.86	18.82	0
	16QAM	25	25				0			12	13	18.80	18.86	18.82	0
		50	0				0			25	0	18.97	19.03	18.99	0

FCC SAR Test Report

LTE Band 17															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23780	23790	23800				Channel		23755	23790	23825	
		Frequency (MHz)		709.0	710.0	711.0				Frequency (MHz)		706.5	710.0	713.5	
10M	QPSK	1	0	19.36	19.34	19.43	0	5M	QPSK	1	0	19.17	19.23	19.21	0
		1	24	19.26	19.24	19.33	0			1	12	19.12	19.23	19.08	0
		1	49	19.42	19.40	19.49	0			1	24	19.37	19.24	19.21	0
		25	0	19.33	19.31	19.40	0			12	0	19.18	19.19	19.11	0
		25	12	19.29	19.27	19.36	0			12	6	19.11	19.16	19.15	0
		25	25	19.30	19.28	19.37	0			12	13	19.16	19.07	19.11	0
		50	0	19.32	19.30	19.39	0			25	0	19.19	19.14	19.23	0
	16QAM	1	0	19.33	19.25	19.40	0		16QAM	1	0	19.10	19.12	19.32	0
		1	24	19.18	19.14	19.31	0			1	12	19.15	19.07	19.14	0
		1	49	19.41	19.33	19.49	0			1	24	19.24	19.22	19.31	0
		25	0	19.25	19.29	19.33	0			12	0	19.24	19.22	19.19	0
		25	12	19.20	19.20	19.32	0			12	6	19.05	19.14	19.18	0
		25	25	19.26	19.18	19.35	0			12	13	19.26	19.14	19.08	0
		50	0	19.24	19.30	19.34	0			25	0	19.23	19.16	19.30	0

FCC SAR Test Report

LTE Band 26															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26765	26865	26965				Channel		26740	26865	26990	
		Frequency (MHz)		821.5	831.5	841.5				Frequency (MHz)		819.0	831.5	844.0	
15M	QPSK	1	0	19.21	19.30	19.36	0	10M	QPSK	1	0	19.12	19.20	19.18	0
		1	37	19.66	19.57	19.63	0			1	24	19.57	19.43	19.40	0
		1	74	19.49	19.40	19.46	0			1	49	19.39	19.35	19.35	0
		36	0	19.54	19.45	19.51	0			25	0	19.40	19.40	19.40	0
		36	19	19.51	19.42	19.48	0			25	12	19.39	19.23	19.30	0
		36	39	19.46	19.37	19.43	0			25	25	19.29	19.21	19.39	0
		75	0	19.56	19.47	19.53	0			50	0	19.43	19.35	19.46	0
	16QAM	1	0	19.19	19.20	19.34	0		16QAM	1	0	19.12	19.22	19.22	0
		1	37	19.57	19.52	19.60	0			1	24	19.47	19.51	19.43	0
		1	74	19.46	19.37	19.45	0			1	49	19.37	19.16	19.36	0
		36	0	19.54	19.36	19.45	0			25	0	19.32	19.30	19.43	0
		36	19	19.41	19.32	19.43	0			25	12	19.35	19.39	19.27	0
		36	39	19.38	19.28	19.33	0			25	25	19.35	19.29	19.25	0
		75	0	19.48	19.43	19.45	0			50	0	19.48	19.29	19.41	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26715	26865	27015				Channel		26705	26865	27025	
		Frequency (MHz)		816.5	831.5	846.5				Frequency (MHz)		815.5	831.5	847.5	
5M	QPSK	1	0	19.00	19.23	19.16	0	3M	QPSK	1	0	19.00	19.22	19.12	0
		1	12	19.42	19.53	19.52	0			1	7	19.54	19.51	19.58	0
		1	24	19.39	19.33	19.35	0			1	14	19.41	19.22	19.34	0
		12	0	19.48	19.34	19.31	0			8	0	19.34	19.28	19.37	0
		12	6	19.33	19.35	19.16	0			8	3	19.45	19.24	19.39	0
		12	13	19.33	19.29	19.30	0			8	7	19.36	19.23	19.33	0
		25	0	19.51	19.37	19.35	0			15	0	19.42	19.46	19.30	0
	16QAM	1	0	19.07	19.10	19.27	0		16QAM	1	0	18.97	19.13	19.13	0
		1	12	19.46	19.43	19.50	0			1	7	19.49	19.40	19.40	0
		1	24	19.34	19.23	19.26	0			1	14	19.35	19.26	19.20	0
		12	0	19.42	19.33	19.38	0			8	0	19.36	19.22	19.30	0
		12	6	19.26	19.22	19.36	0			8	3	19.39	19.27	19.36	0
		12	13	19.19	19.15	19.23	0			8	7	19.37	19.20	19.17	0
		25	0	19.33	19.22	19.32	0			15	0	19.34	19.34	19.30	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)								
		Channel		26697	26865	27033									
		Frequency (MHz)		814.7	831.5	848.3									
1.4M	QPSK	1	0	19.10	19.18	19.26	0								
		1	2	19.53	19.37	19.47	0								
		1	5	19.31	19.27	19.24	0								
		3	0	19.49	19.28	19.37	0								
		3	1	19.39	19.35	19.38	0								
		3	3	19.35	19.26	19.38	0								
		6	0	19.40	19.35	19.47	0								
	16QAM	1	0	18.94	19.10	19.09	0								
		1	2	19.47	19.52	19.53	0								
		1	5	19.37	19.14	19.34	0								
		3	0	19.30	19.19	19.33	0								
		3	1	19.33	19.30	19.27	0								
		3	3	19.27	19.18	19.22	0								
		6	0	19.47	19.29	19.42	0								

FCC SAR Test Report

LTE Band 30																	
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)		
		Channel								27710		Channel		27685		27710	27735
		Frequency (MHz)								2310.0		Frequency (MHz)		2307.5		2310.0	2312.5
10M	QPSK	1	0		12.99		0	5M	QPSK	1	0	12.95	12.93	12.94	0		
		1	24		12.89		0			1	12	12.83	12.69	12.82	0		
		1	49		12.84		0			1	24	12.84	12.77	12.83	0		
		25	0		12.88		0			12	0	12.06	12.75	12.27	0		
		25	12		12.91		0			12	6	12.11	12.87	12.21	0		
		25	25		12.93		0			12	13	12.03	12.78	12.32	0		
		50	0		12.96		0			25	0	12.05	12.83	12.39	0		
	16QAM	1	0		12.94		0		16QAM	1	0	11.78	12.75	12.40	0		
		1	24		12.86		0			1	12	12.34	12.80	12.30	0		
		1	49		12.77		0			1	24	12.10	12.72	12.25	0		
		25	0		12.79		0			12	0	11.08	12.69	11.27	0		
		25	12		12.83		0			12	6	11.03	12.74	11.28	0		
		25	25		12.89		0			12	13	11.15	12.81	11.18	0		
		50	0		12.86		0			25	0	11.01	12.76	11.25	0		

LTE Band 38															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency (MHz)		2580.0	2595.0	2610.0				Frequency (MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	15.11	15.23	15.50	0	15M	QPSK	1	0	15.06	15.18	15.48	0
		1	50	15.16	15.28	15.55	0			1	37	15.08	15.25	15.45	0
		1	99	15.68	15.67	15.69	0			1	74	15.19	15.40	15.60	0
		50	0	15.09	15.21	15.48	0			36	0	15.00	15.21	15.43	0
		50	25	15.15	15.27	15.54	0			36	19	15.13	15.23	15.46	0
		50	50	15.19	15.31	15.58	0			36	39	15.15	15.26	15.49	0
		100	0	15.20	15.32	15.59	0			75	0	15.11	15.27	15.58	0
	16QAM	1	0	15.11	15.15	15.43	0		16QAM	1	0	14.93	15.18	15.38	0
		1	50	15.08	15.27	15.49	0			1	37	15.14	15.12	15.42	0
		1	99	15.19	15.38	15.58	0			1	74	15.14	15.30	15.56	0
		50	0	14.99	15.19	15.47	0			36	0	15.02	15.12	15.37	0
		50	25	15.06	15.23	15.48	0			36	19	15.03	15.20	15.41	0
		50	50	15.15	15.24	15.57	0			36	39	15.13	15.13	15.45	0
		100	0	15.17	15.31	15.55	0			75	0	15.08	15.23	15.51	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37800	38000	38200				Channel		37775	38000	38225	
		Frequency (MHz)		2575.0	2595.0	2615.0				Frequency (MHz)		2572.5	2595.0	2617.5	
10M	QPSK	1	0	14.90	15.21	15.41	0	5M	QPSK	1	0	15.02	15.17	15.34	0
		1	24	15.08	15.16	15.35	0			1	12	14.96	15.12	15.28	0
		1	49	15.22	15.26	15.53	0			1	24	15.07	15.38	15.64	0
		25	0	14.97	15.03	15.37	0			12	0	15.02	15.06	15.21	0
		25	12	15.06	15.22	15.45	0			12	6	15.09	15.27	15.32	0
		25	25	14.99	15.14	15.40	0			12	13	15.10	15.17	15.43	0
		50	0	15.02	15.18	15.55	0			25	0	15.14	15.26	15.45	0
	16QAM	1	0	14.91	15.13	15.29	0		16QAM	1	0	14.87	15.13	15.38	0
		1	24	15.01	15.16	15.35	0			1	12	14.97	15.03	15.26	0
		1	49	15.08	15.24	15.53	0			1	24	15.17	15.22	15.55	0
		25	0	14.95	15.04	15.28	0			12	0	15.00	15.02	15.36	0
		25	12	15.03	15.05	15.32	0			12	6	14.95	14.94	15.38	0
		25	25	15.04	15.21	15.51	0			12	13	15.14	15.22	15.42	0
		50	0	15.00	15.09	15.41	0			25	0	15.08	15.19	15.42	0

FCC SAR Test Report

LTE Band 41																			
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)
		Channel		39790	40185	40620	41055	41490				Channel		39765	40173	40620	41068	41515	
		Frequency (MHz)		2510	2549.5	2593.0	2636.5	2680.0				Frequency (MHz)		2507.5	2548.3	2593.0	2637.8	2682.5	
20M	QPSK	1	0	14.24	14.20	14.12	14.26	14.07	0	15M	QPSK	1	0	14.18	14.13	14.10	14.17	14.01	0
		1	50	14.23	14.19	14.11	14.25	14.06	0			1	37	14.13	14.12	14.08	14.17	13.98	0
		1	99	14.17	14.13	14.05	14.19	14.00	0			1	74	14.10	14.10	13.99	14.12	13.91	0
		50	0	14.21	14.17	14.09	14.23	14.04	0			36	0	14.19	14.12	13.99	14.22	14.03	0
		50	25	14.18	14.14	14.06	14.20	14.01	0			36	19	14.12	14.08	14.06	14.20	13.98	0
		50	50	14.20	14.16	14.08	14.22	14.03	0			36	39	14.19	14.11	14.08	14.19	14.02	0
	16QAM	100	0	14.19	14.15	14.07	14.21	14.02	0			75	0	14.18	14.05	14.02	14.11	13.99	0
		1	0	14.23	14.12	14.02	14.19	14.00	0		16QAM	1	0	14.19	14.18	14.10	14.16	14.00	0
		1	50	14.16	14.17	14.01	14.23	13.97	0			1	37	14.19	14.13	14.11	14.25	13.97	0
		1	99	14.09	14.07	13.95	14.18	13.92	0			1	74	14.14	14.10	14.03	14.18	13.96	0
		50	0	14.17	14.09	14.08	14.20	13.97	0			36	0	14.20	14.13	14.01	14.19	13.99	0
		50	25	14.14	14.13	14.02	14.14	13.98	0			36	19	14.13	14.11	14.00	14.13	13.98	0
50	50	14.14	14.10	14.07	14.22	14.03	0	36	39			14.15	14.07	14.05	14.12	14.01	0		
100	0	14.14	14.14	14.06	14.13	13.92	0	75	0			14.17	14.10	14.00	14.18	13.92	0		
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)
		Channel		39740	40160	40620	41080	41540				Channel		39715	40148	40620	41093	41565	
		Frequency (MHz)		2505	2547.0	2593.0	2639.0	2685.0				Frequency (MHz)		2502.5	2545.8	2593.0	2640.3	2687.5	
10M	QPSK	1	0	14.05	14.10	14.05	14.13	13.99	0	5M	QPSK	1	0	14.19	14.13	14.09	14.13	13.97	0
		1	24	14.14	14.16	14.05	14.19	13.99	0			1	12	14.15	14.09	14.05	14.15	13.91	0
		1	49	14.08	13.96	13.95	14.06	13.99	0			1	24	14.04	13.96	13.95	14.13	13.98	0
		25	0	14.13	14.01	13.99	14.09	13.95	0			12	0	14.08	14.14	14.00	14.17	13.92	0
		25	12	14.07	13.97	13.92	14.14	13.82	0			12	6	14.02	14.08	14.04	14.11	13.94	0
		25	25	14.06	14.02	13.92	14.08	13.93	0			12	13	14.17	14.02	13.98	14.12	14.02	0
	16QAM	50	0	14.14	14.03	13.98	14.09	13.83	0			25	0	14.11	13.99	14.02	14.20	13.98	0
		1	0	14.07	14.14	14.06	14.17	13.94	0		16QAM	1	0	14.10	14.13	14.03	14.14	13.96	0
		1	24	14.13	14.08	13.96	14.16	14.01	0			1	12	14.17	14.15	13.96	14.25	13.96	0
		1	49	14.08	14.05	13.87	14.09	13.93	0			1	24	14.04	14.03	13.95	14.07	13.91	0
		25	0	14.17	14.07	14.04	14.08	14.00	0			12	0	14.16	14.06	13.99	14.14	14.00	0
		25	12	14.08	13.99	13.94	14.09	13.87	0			12	6	14.07	14.07	13.96	14.08	13.98	0
25	25	14.09	13.99	13.93	14.11	13.89	0	12	13			14.15	14.09	14.00	14.02	14.02	0		
50	0	14.19	14.05	13.94	14.18	13.83	0	25	0			14.10	14.04	13.98	14.19	13.93	0		

FCC SAR Test Report

LTE Band 66															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		132072	132322	132572				Channel		132047	132322	132597	
		Frequency (MHz)		1720.0	1745.0	1770.0				Frequency (MHz)		1717.5	1745.0	1772.5	
20M	QPSK	1	0	14.40	14.47	14.25	0	15M	QPSK	1	0	14.37	14.42	14.15	0
		1	50	14.08	14.15	13.93	0			1	37	14.05	14.08	13.83	0
		1	99	14.05	14.12	13.90	0			1	74	14.02	14.09	13.84	0
		50	0	14.30	14.37	14.15	0			36	0	14.26	14.29	14.07	0
		50	25	14.19	14.26	14.04	0			36	19	14.19	14.23	14.01	0
		50	50	14.17	14.24	14.02	0			36	39	14.14	14.14	13.97	0
	16QAM	100	0	14.31	14.38	14.16	0			75	0	14.29	14.34	14.06	0
		1	0	14.40	14.39	14.23	0		16QAM	1	0	14.34	14.32	14.11	0
		1	50	14.08	14.15	13.89	0			1	37	14.00	14.13	13.90	0
		1	99	14.02	14.08	13.80	0			1	74	13.92	14.01	13.82	0
		50	0	14.27	14.33	14.07	0			36	0	14.25	14.32	14.08	0
		50	25	14.13	14.16	13.94	0			36	19	14.07	14.13	13.94	0
10M	QPSK	50	50	14.10	14.19	14.02	0	5M	16QAM	36	39	14.11	14.05	13.92	0
		100	0	14.30	14.33	14.16	0			75	0	14.26	14.29	13.97	0
	16QAM	1	0	14.29	14.26	14.02	0		QPSK	1	0	14.28	14.41	14.16	0
		1	24	13.83	13.92	13.87	0			1	12	14.00	13.96	13.78	0
		1	49	13.75	14.01	13.86	0			1	24	13.85	13.91	13.75	0
		25	0	14.10	14.18	13.98	0			12	0	14.16	14.24	13.91	0
3M	QPSK	25	12	14.05	14.12	13.82	0		16QAM	12	6	14.06	14.11	13.68	0
		25	25	13.97	14.01	13.80	0			12	13	14.00	14.17	13.86	0
		50	0	14.19	14.28	14.06	0			25	0	14.17	14.29	14.14	0
	16QAM	1	0	14.27	14.31	14.18	0		QPSK	1	0	14.15	14.31	14.06	0
		1	7	13.94	13.99	13.74	0			1	12	13.99	13.87	13.62	0
		1	14	13.74	13.99	13.88	0			1	24	13.87	13.87	13.63	0
1.4M	QPSK	8	0	14.17	14.27	14.03	0		16QAM	12	0	14.17	14.09	14.03	0
		8	3	14.01	14.23	13.90	0			12	6	13.97	14.15	13.88	0
		8	7	14.04	14.06	13.75	0			12	13	13.90	14.00	13.79	0
		15	0	14.10	14.21	14.08	0			25	0	14.08	14.07	13.88	0
	16QAM	1	0	14.27	14.31	14.18	0		QPSK	3	0	14.12	14.25	14.07	0
		1	7	13.94	13.99	13.74	0			3	1	14.18	14.12	13.91	0
		1	14	13.74	13.99	13.88	0			3	3	14.08	14.08	13.89	0
		8	0	14.17	14.27	14.03	0			6	0	14.14	14.24	14.06	0
		8	3	14.01	14.23	13.90	0		16QAM	1	0	14.19	14.39	14.04	0
		8	7	14.04	14.06	13.75	0			1	2	13.96	13.95	13.80	0
		15	0	14.10	14.21	14.08	0			1	5	13.92	14.02	13.63	0
3M	QPSK	1	0	14.32	14.26	14.08	0			3	0	14.05	14.18	14.04	0
		1	7	13.93	14.02	13.81	0			3	1	14.00	14.10	13.98	0
		1	14	13.98	14.06	13.76	0			3	3	14.02	14.03	13.78	0
		8	0	14.18	14.18	14.03	0			6	0	14.15	14.15	14.02	0
		8	3	14.05	14.09	13.97	0								
		8	7	14.08	14.04	13.93	0								
1.4M	QPSK	15	0	14.18	14.25	14.12	0								
		1	0	14.27	14.31	14.18	0								
		1	7	13.94	13.99	13.74	0								
		1	14	13.74	13.99	13.88	0								
		8	0	14.17	14.27	14.03	0								
		8	3	14.01	14.23	13.90	0								
3M	QPSK	8	7	14.04	14.06	13.75	0								
		15	0	14.10	14.21	14.08	0								
	16QAM	1	0	14.27	14.31	14.18	0								
		1	7	13.94	13.99	13.74	0								
		1	14	13.74	13.99	13.88	0								
		8	0	14.17	14.27	14.03	0								

FCC SAR Test Report

Tablet

Band	WCDMA Band II			WCDMA Band IV			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6	
EUT without Power Reduction (P-Sensor NOT Triggered)										
RMC 12.2K	23.40	23.47	23.50	23.21	23.32	23.48	23.44	23.49	23.38	-
HSDPA Subtest-1	23.46	23.44	23.47	23.14	23.26	23.45	23.39	23.43	23.43	0
HSDPA Subtest-2	22.42	22.51	22.47	22.19	22.29	22.51	22.42	22.97	22.40	0
HSDPA Subtest-3	21.98	22.03	21.97	21.69	21.84	22.00	21.94	22.49	21.89	0.5
HSDPA Subtest-4	21.75	21.79	21.73	21.46	21.57	21.75	21.66	22.25	21.67	0.5
DC-HSDPA Subtest-1	23.44	23.41	23.46	23.11	23.23	23.42	23.34	23.38	23.38	0
DC-HSDPA Subtest-2	22.41	22.50	22.46	22.14	22.24	22.46	22.39	22.94	22.38	0
DC-HSDPA Subtest-3	21.96	22.02	21.95	21.65	21.80	21.97	21.89	22.44	21.87	0.5
DC-HSDPA Subtest-4	21.71	21.83	21.79	21.43	21.55	21.73	21.60	22.20	21.65	0.5
HSUPA Subtest-1	22.50	22.55	22.48	22.24	22.27	22.49	22.54	22.93	22.44	0
HSUPA Subtest-2	20.20	20.25	20.21	19.96	20.09	20.24	20.29	20.76	20.25	2
HSUPA Subtest-3	20.97	21.02	20.89	20.70	20.77	21.00	21.05	21.50	20.96	1
HSUPA Subtest-4	20.49	20.53	20.46	20.24	20.30	20.53	20.58	21.12	20.54	2
HSUPA Subtest-5	22.50	22.50	22.60	22.20	22.30	22.50	22.50	23.10	22.50	0
EUT with Power Reduction (P-Sensor Triggered)										
RMC 12.2K	11.87	11.83	11.90	13.51	13.54	13.62	18.78	18.93	18.84	-
HSDPA Subtest-1	11.83	11.79	11.84	13.48	13.51	13.59	18.63	18.78	18.69	0
HSDPA Subtest-2	11.82	11.78	11.83	13.46	13.49	13.57	18.61	18.76	18.67	0
HSDPA Subtest-3	11.83	11.79	11.84	13.45	13.48	13.56	18.65	18.80	18.71	0
HSDPA Subtest-4	11.86	11.82	11.87	13.44	13.47	13.55	18.67	18.82	18.73	0
DC-HSDPA Subtest-1	11.78	11.74	11.79	13.40	13.43	13.51	18.60	18.75	18.66	0
DC-HSDPA Subtest-2	11.79	11.75	11.81	13.38	13.41	13.49	18.56	18.71	18.62	0
DC-HSDPA Subtest-3	11.78	11.74	11.82	13.37	13.40	13.48	18.61	18.76	18.68	0
DC-HSDPA Subtest-4	11.80	11.77	11.85	13.36	13.39	13.47	18.64	18.80	18.71	0
HSUPA Subtest-1	11.88	11.84	11.87	13.45	13.48	13.56	18.57	18.72	18.63	0
HSUPA Subtest-2	11.89	11.85	11.88	13.43	13.46	13.54	18.61	18.76	18.67	0
HSUPA Subtest-3	11.79	11.75	11.80	13.40	13.43	13.51	18.56	18.71	18.62	0
HSUPA Subtest-4	11.70	11.66	11.71	13.42	13.45	13.53	18.60	18.75	18.66	0
HSUPA Subtest-5	11.80	11.76	11.81	13.41	13.44	13.52	18.58	18.73	18.64	0

FCC SAR Test Report

LTE Band 2															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100				Channel		18675	18900	19125	
		Frequency (MHz)		1860	1880	1900				Frequency (MHz)		1857.5	1880	1902.5	
20M	QPSK	1	0	23.09	22.95	22.79	0	15M	QPSK	1	0	23.04	22.90	22.74	0
		1	50	22.76	22.93	22.70	0			1	37	22.71	22.88	22.65	0
		1	99	22.86	22.79	22.73	0			1	74	22.81	22.74	22.68	0
		50	0	21.91	21.90	21.81	1			36	0	21.86	21.85	21.76	1
		50	25	21.75	21.84	21.65	1			36	19	21.70	21.79	21.60	1
		50	50	21.65	21.83	21.54	1			36	39	21.60	21.78	21.49	1
		100	0	21.95	21.90	21.94	1			75	0	21.90	21.85	21.89	1
	16QAM	1	0	22.22	22.16	21.96	1		16QAM	1	0	22.19	22.13	21.93	1
		1	50	21.91	22.14	21.87	1			1	37	21.88	22.11	21.84	1
		1	99	21.98	21.96	21.93	1			1	74	21.95	21.93	21.90	1
		50	0	20.91	20.93	20.56	2			36	0	20.88	20.90	20.53	2
		50	25	20.79	20.93	20.68	2			36	19	20.76	20.90	20.65	2
		50	50	20.66	20.89	20.81	2			36	39	20.63	20.86	20.78	2
		100	0	20.85	20.99	20.90	2			75	0	20.82	20.96	20.87	2
10M	QPSK	1	0	22.97	22.83	22.67	0	5M	QPSK	1	0	22.90	22.76	22.60	0
		1	24	22.64	22.81	22.58	0			1	12	22.57	22.74	22.51	0
		1	49	22.74	22.67	22.61	0			1	24	22.67	22.60	22.54	0
		25	0	21.79	21.78	21.69	1			12	0	21.72	21.71	21.62	1
		25	12	21.63	21.72	21.53	1			12	6	21.56	21.65	21.46	1
		25	25	21.53	21.71	21.42	1			12	13	21.46	21.64	21.35	1
		50	0	21.83	21.78	21.82	1			25	0	21.76	21.71	21.75	1
	16QAM	1	0	22.16	22.10	21.90	1		16QAM	1	0	22.14	22.08	21.88	1
		1	24	21.85	22.08	21.81	1			1	12	21.83	22.06	21.79	1
		1	49	21.92	21.90	21.87	1			1	24	21.90	21.88	21.85	1
		25	0	20.85	20.87	20.50	2			12	0	20.83	20.85	20.48	2
		25	12	20.73	20.87	20.62	2			12	6	20.71	20.85	20.60	2
		25	25	20.60	20.83	20.75	2			12	13	20.58	20.81	20.73	2
		50	0	20.79	20.93	20.84	2			25	0	20.77	20.91	20.82	2
3M	QPSK	1	0	22.84	22.70	22.54	0	1.4M	QPSK	1	0	22.80	22.66	22.50	0
		1	7	22.51	22.68	22.45	0			1	2	22.47	22.64	22.41	0
		1	14	22.61	22.54	22.48	0			1	5	22.57	22.50	22.44	0
		8	0	21.66	21.65	21.56	1			3	0	22.62	22.61	22.52	0
		8	3	21.50	21.59	21.40	1			3	1	22.46	22.55	22.36	0
		8	7	21.40	21.58	21.29	1			3	3	22.36	22.54	22.25	0
		15	0	21.70	21.65	21.69	1			6	0	21.66	21.61	21.65	1
	16QAM	1	0	22.06	22.00	21.80	1		16QAM	1	0	21.99	21.93	21.73	1
		1	7	21.75	21.98	21.71	1			1	2	21.68	21.91	21.64	1
		1	14	21.82	21.80	21.77	1			1	5	21.75	21.73	21.70	1
		8	0	20.75	20.77	20.40	2			3	0	21.68	21.70	21.33	1
		8	3	20.63	20.77	20.52	2			3	1	21.56	21.70	21.45	1
		8	7	20.50	20.73	20.65	2			3	3	21.43	21.66	21.58	1
		15	0	20.69	20.83	20.74	2			6	0	20.62	20.76	20.67	2

FCC SAR Test Report

LTE Band 2															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100				Channel		18675	18900	19125	
		Frequency (MHz)		1860	1880	1900				Frequency (MHz)		1857.5	1880	1902.5	
20M	QPSK	1	0	11.82	11.62	11.54	0	15M	QPSK	1	0	11.81	11.61	11.54	0
		1	50	11.80	11.60	11.52	0			1	37	11.75	11.52	11.52	0
		1	99	11.66	11.46	11.38	0			1	74	11.62	11.36	11.37	0
		50	0	11.85	11.65	11.57	0			36	0	11.77	11.64	11.52	0
		50	25	11.75	11.55	11.47	0			36	19	11.65	11.52	11.43	0
		50	50	11.65	11.45	11.37	0			36	39	11.57	11.43	11.27	0
		100	0	11.84	11.64	11.56	0			75	0	11.76	11.55	11.49	0
	16QAM	1	0	11.76	11.55	11.51	0		16QAM	1	0	11.73	11.48	11.43	0
		1	50	11.70	11.52	11.42	0			1	37	11.77	11.43	11.41	0
		1	99	11.56	11.38	11.29	0			1	74	11.59	11.40	11.26	0
		50	0	11.81	11.58	11.52	0			36	0	11.70	11.56	11.45	0
		50	25	11.75	11.47	11.47	0			36	19	11.66	11.47	11.36	0
		50	50	11.64	11.38	11.28	0			36	39	11.50	11.32	11.31	0
		100	0	11.83	11.58	11.47	0			75	0	11.81	11.51	11.37	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18650	18900	19150				Channel		18625	18900	19175	
		Frequency (MHz)		1855	1880	1905				Frequency (MHz)		1852.5	1880	1907.5	
10M	QPSK	1	0	11.72	11.39	11.46	0	5M	QPSK	1	0	11.78	11.58	11.28	0
		1	24	11.60	11.36	11.34	0			1	12	11.71	11.54	11.34	0
		1	49	11.59	11.42	11.33	0			1	24	11.54	11.30	11.08	0
		25	0	11.71	11.50	11.39	0			12	0	11.82	11.62	11.40	0
		25	12	11.71	11.44	11.34	0			12	6	11.70	11.35	11.25	0
		25	25	11.51	11.31	11.33	0			12	13	11.61	11.31	10.98	0
		50	0	11.64	11.58	11.47	0			25	0	11.71	11.44	11.32	0
	16QAM	1	0	11.67	11.56	11.31	0		16QAM	1	0	11.61	11.55	11.33	0
		1	24	11.60	11.47	11.40	0			1	12	11.65	11.45	11.34	0
		1	49	11.53	11.32	11.26	0			1	24	11.56	11.23	11.31	0
		25	0	11.56	11.36	11.32	0			12	0	11.71	11.50	11.42	0
		25	12	11.57	11.48	11.21	0			12	6	11.62	11.46	11.22	0
		25	25	11.50	11.35	11.27	0			12	13	11.57	11.32	11.19	0
		50	0	11.62	11.54	11.45	0			25	0	11.72	11.35	11.49	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18615	18900	19185				Channel		18607	18900	19193	
		Frequency (MHz)		1851.5	1880	1908.5				Frequency (MHz)		1850.7	1880	1909.3	
3M	QPSK	1	0	11.69	11.41	11.38	0	1.4M	QPSK	1	0	11.63	11.58	11.49	0
		1	7	11.70	11.56	11.43	0			1	2	11.72	11.56	11.38	0
		1	14	11.52	11.34	11.18	0			1	5	11.42	11.39	11.35	0
		8	0	11.71	11.62	11.54	0			3	0	11.68	11.60	11.49	0
		8	3	11.53	11.35	11.30	0			3	1	11.57	11.39	11.24	0
		8	7	11.41	11.20	11.19	0			3	3	11.62	11.36	11.29	0
		15	0	11.80	11.49	11.51	0			6	0	11.77	11.54	11.41	0
	16QAM	1	0	11.55	11.42	11.34	0		16QAM	1	0	11.59	11.52	11.33	0
		1	7	11.66	11.45	11.44	0			1	2	11.63	11.35	11.48	0
		1	14	11.44	11.20	11.21	0			1	5	11.41	11.26	11.17	0
		8	0	11.55	11.41	11.28	0			3	0	11.71	11.44	11.24	0
		8	3	11.63	11.42	11.38	0			3	1	11.56	11.45	11.35	0
		8	7	11.51	11.24	11.21	0			3	3	11.43	11.12	11.17	0
		15	0	11.61	11.47	11.44	0			6	0	11.70	11.55	11.40	0

FCC SAR Test Report

LTE Band 4															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20050	20175	20300				Channel		20025	20175	20325	
		Frequency (MHz)		1720.0	1732.5	1745.0				Frequency (MHz)		1717.5	1732.5	1747.5	
20M	QPSK	1	0	22.78	22.83	22.88	0	15M	QPSK	1	0	22.70	22.75	22.80	0
		1	50	22.70	22.54	22.60	0			1	37	22.62	22.46	22.52	0
		1	99	22.67	22.50	22.55	0			1	74	22.59	22.42	22.47	0
		50	0	21.82	21.75	21.90	1			36	0	21.74	21.67	21.82	1
		50	25	21.79	21.56	21.64	1			36	19	21.71	21.48	21.56	1
		50	50	21.67	21.50	21.80	1			36	39	21.59	21.42	21.72	1
		100	0	21.78	21.61	21.82	1			75	0	21.70	21.53	21.74	1
	16QAM	1	0	21.87	21.99	21.78	1		16QAM	1	0	21.85	21.97	21.76	1
		1	50	21.90	21.74	21.84	1			1	37	21.88	21.72	21.82	1
		1	99	21.87	21.71	21.84	1			1	74	21.85	21.69	21.82	1
		50	0	20.90	20.76	20.61	2			36	0	20.88	20.74	20.59	2
		50	25	20.81	20.58	20.70	2			36	19	20.79	20.56	20.68	2
		50	50	20.71	20.51	20.84	2			36	39	20.69	20.49	20.82	2
		100	0	20.83	20.63	20.77	2			75	0	20.81	20.61	20.75	2
10M	QPSK	1	0	22.65	22.70	22.75	0	5M	QPSK	1	0	22.58	22.63	22.68	0
		1	24	22.57	22.41	22.47	0			1	12	22.50	22.34	22.40	0
		1	49	22.54	22.37	22.42	0			1	24	22.47	22.30	22.35	0
		25	0	21.69	21.62	21.77	1			12	0	21.62	21.55	21.70	1
		25	12	21.66	21.43	21.51	1			12	6	21.59	21.36	21.44	1
		25	25	21.54	21.37	21.67	1			12	13	21.47	21.30	21.60	1
		50	0	21.65	21.48	21.69	1			25	0	21.58	21.41	21.62	1
	16QAM	1	0	21.82	21.94	21.73	1		16QAM	1	0	21.80	21.92	21.71	1
		1	24	21.85	21.69	21.79	1			1	12	21.83	21.67	21.77	1
		1	49	21.82	21.66	21.79	1			1	24	21.80	21.64	21.77	1
		25	0	20.85	20.71	20.56	2			12	0	20.83	20.69	20.54	2
		25	12	20.76	20.53	20.65	2			12	6	20.74	20.51	20.63	2
		25	25	20.66	20.46	20.79	2			12	13	20.64	20.44	20.77	2
		50	0	20.78	20.58	20.72	2			25	0	20.76	20.56	20.70	2
3M	QPSK	1	0	22.52	22.57	22.62	0	1.4M	QPSK	1	0	22.48	22.53	22.58	0
		1	7	22.44	22.28	22.34	0			1	2	22.40	22.24	22.30	0
		1	14	22.41	22.24	22.29	0			1	5	22.37	22.20	22.25	0
		8	0	21.56	21.49	21.64	1			3	0	22.52	22.45	22.60	0
		8	3	21.53	21.30	21.38	1			3	1	22.49	22.26	22.34	0
		8	7	21.41	21.24	21.54	1			3	3	22.37	22.20	22.50	0
		15	0	21.52	21.35	21.56	1			6	0	21.48	21.31	21.52	1
	16QAM	1	0	21.72	21.84	21.63	1		16QAM	1	0	21.65	21.77	21.56	1
		1	7	21.75	21.59	21.69	1			1	2	21.68	21.52	21.62	1
		1	14	21.72	21.56	21.69	1			1	5	21.65	21.49	21.62	1
		8	0	20.75	20.61	20.46	2			3	0	21.68	21.54	21.39	1
		8	3	20.66	20.43	20.55	2			3	1	21.59	21.36	21.48	1
		8	7	20.56	20.36	20.69	2			3	3	21.49	21.29	21.62	1
		15	0	20.68	20.48	20.62	2			6	0	20.61	20.41	20.55	2

FCC SAR Test Report

LTE Band 4															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20050	20175	20300				Channel		20025	20175	20325	
		Frequency (MHz)		1720.0	1732.5	1745.0				Frequency (MHz)		1717.5	1732.5	1747.5	
20M	QPSK	1	0	13.92	13.84	13.99	0	15M	QPSK	1	0	13.92	13.82	13.89	0
		1	50	13.91	13.77	13.94	0			1	37	13.81	13.74	13.88	0
		1	99	13.78	13.64	13.81	0			1	74	13.69	13.54	13.71	0
		50	0	13.97	13.83	13.98	0			36	0	13.95	13.79	13.94	0
		50	25	13.89	13.75	13.92	0			36	19	13.85	13.73	13.90	0
		50	50	13.79	13.65	13.82	0			36	39	13.75	13.57	13.76	0
		100	0	13.90	13.76	13.93	0			75	0	13.80	13.66	13.85	0
	16QAM	1	0	13.89	13.77	13.98	0		16QAM	1	0	13.82	13.66	13.89	0
		1	50	13.86	13.76	13.85	0			1	37	13.77	13.65	13.86	0
		1	99	13.77	13.59	13.71	0			1	74	13.68	13.61	13.79	0
		50	0	13.90	13.73	13.88	0			36	0	13.93	13.71	13.86	0
		50	25	13.86	13.69	13.89	0			36	19	13.76	13.63	13.81	0
		50	50	13.69	13.59	13.74	0			36	39	13.65	13.49	13.68	0
		100	0	13.87	13.67	13.89	0			75	0	13.79	13.61	13.84	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20000	20175	20350				Channel		19975	20175	20375	
		Frequency (MHz)		1715.0	1732.5	1750.0				Frequency (MHz)		1712.5	1732.5	1752.5	
10M	QPSK	1	0	13.72	13.72	13.85	0	5M	QPSK	1	0	13.77	13.70	13.83	0
		1	24	13.71	13.58	13.71	0			1	12	13.72	13.75	13.66	0
		1	49	13.56	13.45	13.66	0			1	24	13.67	13.48	13.71	0
		25	0	13.84	13.65	13.90	0			12	0	13.80	13.73	13.82	0
		25	12	13.67	13.67	13.73	0			12	6	13.79	13.75	13.71	0
		25	25	13.75	13.45	13.60	0			12	13	13.64	13.53	13.58	0
		50	0	13.80	13.60	13.82	0			25	0	13.80	13.56	13.75	0
	16QAM	1	0	13.75	13.65	13.77	0		16QAM	1	0	13.80	13.63	13.90	0
		1	24	13.81	13.61	13.71	0			1	12	13.82	13.61	13.89	0
		1	49	13.66	13.33	13.68	0			1	24	13.48	13.36	13.68	0
		25	0	13.68	13.60	13.84	0			12	0	13.73	13.73	13.91	0
		25	12	13.77	13.48	13.75	0			12	6	13.78	13.56	13.80	0
		25	25	13.64	13.47	13.64	0			12	13	13.59	13.44	13.65	0
		50	0	13.68	13.58	13.74	0			25	0	13.75	13.60	13.81	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		19965	20175	20385				Channel		19957	20175	20393	
		Frequency (MHz)		1711.5	1732.5	1753.5				Frequency (MHz)		1710.7	1732.5	1754.3	
3M	QPSK	1	0	13.77	13.73	13.87	0	1.4M	QPSK	1	0	13.80	13.60	13.90	0
		1	7	13.82	13.70	13.81	0			1	2	13.71	13.58	13.92	0
		1	14	13.57	13.58	13.74	0			1	5	13.61	13.58	13.76	0
		8	0	13.87	13.74	13.95	0			3	0	13.85	13.65	13.88	0
		8	3	13.79	13.58	13.81	0			3	1	13.79	13.73	13.81	0
		8	7	13.60	13.57	13.67	0			3	3	13.71	13.58	13.75	0
		15	0	13.76	13.55	13.75	0			6	0	13.73	13.52	13.69	0
	16QAM	1	0	13.78	13.73	13.85	0		16QAM	1	0	13.78	13.67	13.78	0
		1	7	13.67	13.54	13.72	0			1	2	13.75	13.58	13.90	0
		1	14	13.65	13.48	13.56	0			1	5	13.56	13.56	13.65	0
		8	0	13.78	13.71	13.86	0			3	0	13.89	13.67	13.77	0
		8	3	13.78	13.52	13.74	0			3	1	13.69	13.47	13.71	0
		8	7	13.60	13.46	13.62	0			3	3	13.57	13.41	13.54	0
		15	0	13.73	13.49	13.71	0			6	0	13.69	13.53	13.74	0

FCC SAR Test Report

LTE Band 5															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600				Channel		20425	20525	20625	
		Frequency (MHz)		829.0	836.5	844.0				Frequency (MHz)		826.5	836.5	846.5	
10M	QPSK	1	0	22.73	22.72	22.71	0	5M	QPSK	1	0	22.66	22.48	21.64	0
		1	24	22.61	22.55	22.53	0			1	12	22.54	22.65	22.46	0
		1	49	22.59	22.69	22.34	0			1	24	22.52	22.62	22.27	0
		25	0	21.78	21.74	21.75	1			12	0	21.71	21.67	21.68	1
		25	12	21.69	21.70	21.56	1			12	6	21.62	21.63	21.49	1
		25	25	21.67	21.67	21.47	1			12	13	21.60	21.60	21.40	1
		50	0	21.75	21.73	21.56	1			25	0	21.68	21.66	21.49	1
	16QAM	1	0	21.96	21.83	21.91	1		16QAM	1	0	21.91	21.78	21.86	1
		1	24	21.85	21.82	21.79	1			1	12	21.80	21.77	21.74	1
		1	49	21.87	21.83	21.65	1			1	24	21.82	21.78	21.60	1
		25	0	20.73	20.79	20.77	2			12	0	20.68	20.74	20.72	2
		25	12	20.70	20.85	20.56	2			12	6	20.65	20.80	20.51	2
		25	25	20.71	20.82	20.52	2			12	13	20.66	20.77	20.47	2
		50	0	20.75	20.88	20.59	2			25	0	20.70	20.83	20.54	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20415	20525	20635				Channel		20407	20525	20643	
		Frequency (MHz)		825.5	836.5	847.5				Frequency (MHz)		824.7	836.5	848.3	
3M	QPSK	1	0	22.62	22.44	21.60	0	1.4M	QPSK	1	0	22.58	22.40	21.56	0
		1	7	22.50	22.61	22.42	0			1	2	22.46	22.57	22.38	0
		1	14	22.48	22.58	22.23	0			1	5	22.44	22.54	22.19	0
		8	0	21.67	21.63	21.64	1			3	0	22.63	22.59	22.60	0
		8	3	21.58	21.59	21.45	1			3	1	22.54	22.55	22.41	0
		8	7	21.56	21.56	21.36	1			3	3	22.52	22.52	22.32	0
		15	0	21.64	21.62	21.45	1			6	0	21.60	21.58	21.41	1
	16QAM	1	0	21.83	21.70	21.78	1		16QAM	1	0	21.76	21.63	21.71	1
		1	7	21.72	21.69	21.66	1			1	2	21.65	21.62	21.59	1
		1	14	21.74	21.70	21.52	1			1	5	21.67	21.63	21.45	1
		8	0	20.60	20.66	20.64	2			3	0	21.53	21.59	21.57	1
		8	3	20.57	20.72	20.43	2			3	1	21.50	21.65	21.36	1
		8	7	20.58	20.69	20.39	2			3	3	21.51	21.62	21.32	1
		15	0	20.62	20.75	20.46	2			6	0	20.55	20.68	20.39	2

FCC SAR Test Report

LTE Band 5															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600				Channel		20425	20525	20625	
		Frequency (MHz)		829.0	836.5	844.0				Frequency (MHz)		826.5	836.5	846.5	
10M	QPSK	1	0	19.32	19.28	19.20	0	5M	QPSK	1	0	19.10	19.12	19.02	0
		1	24	19.17	19.13	19.05	0			1	12	19.00	18.98	18.84	0
		1	49	19.13	19.09	19.01	0			1	24	19.00	18.91	18.84	0
		25	0	19.21	19.17	19.09	0			12	0	19.03	18.99	18.90	0
		25	12	19.10	19.06	18.98	0			12	6	19.04	18.92	18.85	0
		25	25	19.09	19.05	18.97	0			12	13	18.92	18.97	18.80	0
		50	0	19.09	19.05	18.97	0			25	0	19.03	18.91	18.73	0
	16QAM	1	0	19.29	19.25	19.13	0		16QAM	1	0	19.08	19.26	19.13	0
		1	24	19.07	19.12	19.01	0			1	12	19.00	18.98	18.76	0
		1	49	19.13	19.07	18.99	0			1	24	18.91	18.95	18.77	0
		25	0	19.14	19.16	19.09	0			12	0	19.00	18.98	19.01	0
		25	12	19.10	18.98	18.93	0			12	6	18.96	18.85	18.72	0
		25	25	19.08	19.02	18.91	0			12	13	18.91	18.99	18.75	0
		50	0	19.08	19.02	18.96	0			25	0	19.08	18.87	18.71	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20415	20525	20635				Channel		20407	20525	20643	
		Frequency (MHz)		825.5	836.5	847.5				Frequency (MHz)		824.7	836.5	848.3	
3M	QPSK	1	0	19.21	19.06	19.06	0	1.4M	QPSK	1	0	19.27	19.23	19.13	0
		1	7	19.03	18.96	18.86	0			1	2	18.95	18.99	19.00	0
		1	14	18.93	18.86	18.81	0			1	5	18.96	18.87	18.89	0
		8	0	19.13	19.13	19.00	0			3	0	19.14	19.11	19.04	0
		8	3	18.98	18.96	18.90	0			3	1	18.88	18.92	18.90	0
		8	7	18.93	18.97	18.83	0			3	3	18.91	18.89	18.83	0
		15	0	18.97	18.87	18.81	0			6	0	18.92	18.85	18.89	0
	16QAM	1	0	19.03	18.94	19.06	0		16QAM	1	0	19.13	19.24	18.97	0
		1	7	18.99	19.04	19.00	0			1	2	19.05	18.97	18.97	0
		1	14	19.08	18.89	18.76	0			1	5	19.10	19.06	18.90	0
		8	0	18.93	18.97	18.97	0			3	0	19.14	18.92	18.83	0
		8	3	18.96	18.86	18.81	0			3	1	18.96	18.86	18.88	0
		8	7	18.78	18.90	18.79	0			3	3	18.93	18.98	18.77	0
		15	0	18.82	18.91	18.76	0			6	0	18.98	18.89	18.81	0

FCC SAR Test Report

LTE Band 7															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency (MHz)		2510.0	2535.0	2560.0				Frequency (MHz)		2507.5	2535.0	2562.5	
20M	QPSK	1	0	22.46	22.56	22.68	0	15M	QPSK	1	0	22.38	22.48	22.60	0
		1	50	22.30	22.45	22.55	0			1	37	22.22	22.37	22.47	0
		1	99	22.31	22.40	22.44	0			1	74	22.23	22.32	22.36	0
		50	0	21.39	21.46	21.53	1			36	0	21.31	21.38	21.45	1
		50	25	21.42	21.61	21.64	1			36	19	21.34	21.53	21.56	1
		50	50	21.48	21.69	21.70	1			36	39	21.40	21.61	21.62	1
		100	0	21.54	21.70	21.77	1			75	0	21.46	21.62	21.69	1
	16QAM	1	0	21.50	21.94	21.66	1		16QAM	1	0	21.48	21.92	21.64	1
		1	50	21.57	21.83	21.73	1			1	37	21.55	21.81	21.71	1
		1	99	21.68	21.66	21.70	1			1	74	21.66	21.64	21.68	1
		50	0	20.41	20.74	20.56	2			36	0	20.39	20.72	20.54	2
		50	25	20.43	20.68	20.65	2			36	19	20.41	20.66	20.63	2
		50	50	20.47	20.52	20.72	2			36	39	20.45	20.50	20.70	2
		100	0	20.54	20.71	20.77	2			75	0	20.52	20.69	20.75	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20800	21100	21400				Channel		20775	21100	21425	
		Frequency (MHz)		2505.0	2535.0	2565.0				Frequency (MHz)		2502.5	2535.0	2567.5	
10M	QPSK	1	0	22.31	22.41	22.53	0	5M	QPSK	1	0	22.28	22.38	22.50	0
		1	24	22.15	22.30	22.40	0			1	12	22.12	22.27	22.37	0
		1	49	22.16	22.25	22.29	0			1	24	22.13	22.22	22.26	0
		25	0	21.24	21.31	21.38	1			12	0	21.21	21.28	21.35	1
		25	12	21.27	21.46	21.49	1			12	6	21.24	21.43	21.46	1
		25	25	21.33	21.54	21.55	1			12	13	21.30	21.51	21.52	1
		50	0	21.39	21.55	21.62	1			25	0	21.36	21.52	21.59	1
	16QAM	1	0	21.46	21.90	21.62	1		16QAM	1	0	21.39	21.83	21.55	1
		1	24	21.53	21.79	21.69	1			1	12	21.46	21.72	21.62	1
		1	49	21.64	21.62	21.66	1			1	24	21.57	21.55	21.59	1
		25	0	20.37	20.70	20.52	2			12	0	20.30	20.63	20.45	2
		25	12	20.39	20.64	20.61	2			12	6	20.32	20.57	20.54	2
		25	25	20.43	20.48	20.68	2			12	13	20.36	20.41	20.61	2
		50	0	20.50	20.67	20.73	2			25	0	20.43	20.60	20.66	2

FCC SAR Test Report

LTE Band 7															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency (MHz)		2510.0	2535.0	2560.0				Frequency (MHz)		2507.5	2535.0	2562.5	
20M	QPSK	1	0	11.90	11.92	11.99	0	15M	QPSK	1	0	11.89	11.85	11.97	0
		1	50	11.74	11.76	11.83	0			1	37	11.72	11.69	11.75	0
		1	99	11.89	11.91	11.98	0			1	74	11.81	11.91	11.93	0
		50	0	11.89	11.91	11.98	0			36	0	11.84	11.81	11.93	0
		50	25	11.87	11.89	11.96	0			36	19	11.80	11.79	11.93	0
		50	50	11.86	11.88	11.95	0			36	39	11.76	11.78	11.91	0
		100	0	11.88	11.90	11.97	0			75	0	11.80	11.84	11.96	0
	16QAM	1	0	11.85	11.86	11.95	0		16QAM	1	0	11.87	11.76	11.89	0
		1	50	11.67	11.74	11.80	0			1	37	11.64	11.71	11.77	0
		1	99	11.88	11.87	11.93	0			1	74	11.79	11.80	11.86	0
		50	0	11.79	11.86	11.96	0			36	0	11.76	11.83	11.81	0
		50	25	11.84	11.81	11.95	0			36	19	11.77	11.80	11.92	0
		50	50	11.84	11.85	11.92	0			36	39	11.77	11.77	11.91	0
		100	0	11.85	11.81	11.89	0			75	0	11.77	11.75	11.85	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20800	21100	21400				Channel		20775	21100	21425	
		Frequency (MHz)		2505.0	2535.0	2565.0				Frequency (MHz)		2502.5	2535.0	2567.5	
10M	QPSK	1	0	11.81	11.84	11.93	0	5M	QPSK	1	0	11.86	11.79	11.75	0
		1	24	11.58	11.60	11.75	0			1	12	11.59	11.63	11.53	0
		1	49	11.72	11.75	11.84	0			1	24	11.77	11.72	11.77	0
		25	0	11.83	11.77	11.93	0			12	0	11.73	11.83	11.65	0
		25	12	11.71	11.72	11.88	0			12	6	11.74	11.73	11.78	0
		25	25	11.81	11.85	11.82	0			12	13	11.72	11.84	11.79	0
		50	0	11.78	11.82	11.84	0			25	0	11.75	11.78	11.78	0
	16QAM	1	0	11.80	11.80	11.81	0		16QAM	1	0	11.77	11.74	11.88	0
		1	24	11.52	11.59	11.72	0			1	12	11.60	11.68	11.72	0
		1	49	11.82	11.74	11.81	0			1	24	11.78	11.79	11.82	0
		25	0	11.64	11.59	11.74	0			12	0	11.77	11.74	11.88	0
		25	12	11.66	11.71	11.71	0			12	6	11.70	11.68	11.65	0
		25	25	11.78	11.77	11.64	0			12	13	11.79	11.56	11.75	0
		50	0	11.67	11.80	11.82	0			25	0	11.69	11.68	11.82	0

FCC SAR Test Report

LTE Band 12															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23060	23095	23130				Channel		23035	23095	23155	
		Frequency (MHz)		704.0	707.5	711.0				Frequency (MHz)		701.5	707.5	713.5	
10M	QPSK	1	0	22.96	22.83	22.89	0	5M	QPSK	1	0	22.91	22.78	22.84	0
		1	24	22.64	22.72	22.53	0			1	12	22.59	22.67	22.48	0
		1	49	22.72	22.59	22.68	0			1	24	22.67	22.54	22.63	0
		25	0	21.95	21.88	21.88	1			12	0	21.90	21.83	21.83	1
		25	12	21.94	21.79	21.61	1			12	6	21.89	21.74	21.56	1
		25	25	21.85	21.62	21.63	1			12	13	21.80	21.57	21.58	1
		50	0	21.94	21.72	21.78	1			25	0	21.89	21.67	21.73	1
	16QAM	1	0	21.97	21.83	21.86	1		16QAM	1	0	21.90	21.76	21.79	1
		1	24	21.89	21.74	21.96	1			1	12	21.82	21.67	21.89	1
		1	49	21.88	21.90	21.94	1			1	24	21.81	21.83	21.87	1
		25	0	20.93	20.82	20.67	2			12	0	20.86	20.75	20.60	2
		25	12	20.86	20.85	20.64	2			12	6	20.79	20.78	20.57	2
		25	25	20.95	20.70	20.90	2			12	13	20.88	20.63	20.83	2
		50	0	20.78	20.85	20.79	2			25	0	20.71	20.78	20.72	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23025	23095	23165				Channel		23017	23095	23173	
		Frequency (MHz)		700.5	707.5	714.5				Frequency (MHz)		699.7	707.5	715.3	
3M	QPSK	1	0	22.86	22.73	22.79	0	1.4M	QPSK	1	0	22.82	22.69	22.75	0
		1	7	22.54	22.62	22.43	0			1	2	22.50	22.58	22.39	0
		1	14	22.62	22.49	22.58	0			1	5	22.58	22.45	22.54	0
		8	0	21.85	21.78	21.78	1			3	0	22.81	22.74	22.74	0
		8	3	21.84	21.69	21.51	1			3	1	22.80	22.65	22.47	0
		8	7	21.75	21.52	21.53	1			3	3	22.71	22.48	22.49	0
		15	0	21.84	21.62	21.68	1			6	0	21.80	21.58	21.64	1
	16QAM	1	0	21.82	21.68	21.71	1		16QAM	1	0	21.75	21.61	21.64	1
		1	7	21.74	21.59	21.81	1			1	2	21.67	21.52	21.74	1
		1	14	21.73	21.75	21.79	1			1	5	21.66	21.68	21.72	1
		8	0	20.78	20.67	20.52	2			3	0	21.71	21.60	21.45	1
		8	3	20.71	20.70	20.49	2			3	1	21.64	21.63	21.42	1
		8	7	20.80	20.55	20.75	2			3	3	21.73	21.48	21.68	1
		15	0	20.63	20.70	20.64	2			6	0	20.56	20.63	20.57	2

FCC SAR Test Report

LTE Band 12															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23060	23095	23130				Channel		23035	23095	23155	
		Frequency (MHz)		704.0	707.5	711.0				Frequency (MHz)		701.5	707.5	713.5	
10M	QPSK	1	0	19.33	19.29	19.30	0	5M	QPSK	1	0	19.18	19.11	19.09	0
		1	24	19.35	19.31	19.32	0			1	12	19.25	19.07	19.03	0
		1	49	19.30	19.26	19.27	0			1	24	19.09	19.11	19.14	0
		25	0	19.29	19.25	19.26	0			12	0	19.15	19.12	19.04	0
		25	12	19.34	19.30	19.31	0			12	6	19.20	19.15	19.16	0
		25	25	19.26	19.22	19.23	0			12	13	19.13	19.07	19.02	0
		50	0	19.28	19.24	19.25	0			25	0	19.17	19.06	19.03	0
	16QAM	1	0	19.33	19.25	19.25	0		16QAM	1	0	19.24	19.15	19.22	0
		1	24	19.25	19.27	19.27	0			1	12	19.17	19.11	19.12	0
		1	49	19.25	19.25	19.19	0			1	24	19.01	19.05	19.18	0
		25	0	19.26	19.25	19.25	0			12	0	19.04	19.07	19.13	0
		25	12	19.30	19.24	19.30	0			12	6	19.19	18.99	19.15	0
		25	25	19.16	19.12	19.13	0			12	13	19.08	19.00	19.02	0
		50	0	19.22	19.21	19.20	0			25	0	19.09	19.05	19.16	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23025	23095	23165				Channel		23017	23095	23173	
		Frequency (MHz)		700.5	707.5	714.5				Frequency (MHz)		699.7	707.5	715.3	
3M	QPSK	1	0	19.14	19.21	19.19	0	1.4M	QPSK	1	0	19.26	19.15	19.19	0
		1	7	19.10	19.08	19.20	0			1	2	19.32	19.08	19.16	0
		1	14	19.17	19.04	19.10	0			1	5	19.18	19.09	19.14	0
		8	0	19.20	19.17	19.12	0			3	0	19.15	19.09	19.11	0
		8	3	19.19	19.15	19.17	0			3	1	19.25	19.22	19.31	0
		8	7	19.20	19.20	19.08	0			3	3	19.20	19.16	19.09	0
	16QAM	15	0	19.13	19.22	19.12	0		16QAM	6	0	19.22	19.09	19.10	0
		1	0	19.05	19.18	19.07	0			1	0	19.17	19.15	19.22	0
		1	7	19.19	19.18	19.15	0			1	2	19.17	19.04	19.10	0
		1	14	19.29	19.14	19.10	0			1	5	19.06	19.10	19.10	0
		8	0	19.09	19.06	19.08	0			3	0	19.18	19.05	19.07	0
		8	3	19.24	19.14	19.18	0			3	1	19.15	19.13	19.03	0
		8	7	18.99	19.06	19.11	0			3	3	19.11	18.97	19.13	0
		15	0	18.98	19.06	19.15	0			6	0	19.08	19.00	19.03	0

FCC SAR Test Report

LTE Band 13																
EUT without Power Reduction (P-Sensor NOT Triggered)																
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	
		Channel								23205	23230					23225
		Frequency (MHz)								779.5	782.0					784.5
10M	QPSK	1	0		22.67		0	5M	QPSK	1	0	22.87	22.91	22.89	0	
		1	24		22.55		0			1	12	22.73	22.87	22.90	0	
		1	49		22.93		0			1	24	22.88	22.74	22.85	0	
		25	0		21.74		1			12	0	21.98	21.79	21.90	1	
		25	12		21.50		1			12	6	21.68	21.84	21.92	1	
		25	25		21.69		1			12	13	21.89	21.91	21.86	1	
		50	0		21.61		1			25	0	21.95	21.84	21.96	1	
	16QAM	1	0		21.89		1		16QAM	1	0	21.90	21.92	21.94	1	
		1	24		21.79		1			1	12	21.71	21.83	21.77	1	
		1	49		21.75		1			1	24	21.99	21.79	21.86	1	
		25	0		20.80		2			12	0	20.86	20.91	20.84	2	
		25	12		20.58		2			12	6	20.79	20.78	20.94	2	
		25	25		20.76		2			12	13	21.00	20.80	20.85	2	
		50	0		20.65		2			25	0	20.81	20.83	20.84	2	

LTE Band 13															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel								Channel					
		Frequency (MHz)								Frequency (MHz)					
10M	QPSK	1	0		19.13		0	5M	QPSK	1	0	18.94	19.00	18.96	0
		1	24		19.01		0			1	12	18.83	18.89	18.85	0
		1	49		19.22		0			1	24	18.98	19.04	19.00	0
		25	0		19.18		0			12	0	19.02	19.08	19.04	0
		25	12		19.04		0			12	6	18.81	18.87	18.83	0
		25	25		19.11		0			12	13	18.96	19.02	18.98	0
		50	0		19.19		0			25	0	18.99	19.05	19.01	0
	16QAM	1	0		19.07		0		16QAM	1	0	18.85	18.91	18.87	0
		1	24		18.91		0			1	12	18.83	18.89	18.85	0
		1	49		19.22		0			1	24	18.92	18.98	18.94	0
		25	0		19.14		0			12	0	18.96	19.02	18.98	0
		25	12		18.96		0			12	6	18.80	18.86	18.82	0
		25	25		19.08		0			12	13	18.80	18.86	18.82	0
		50	0		19.14		0			25	0	18.97	19.03	18.99	0

FCC SAR Test Report

LTE Band 17															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23780	23790	23800				Channel		23755	23790	23825	
		Frequency (MHz)		709.0	710.0	711.0				Frequency (MHz)		706.5	710.0	713.5	
10M	QPSK	1	0	22.73	22.79	22.65	0	5M	QPSK	1	0	22.64	22.70	22.56	0
		1	24	22.56	22.50	22.47	0			1	12	22.47	22.41	22.38	0
		1	49	22.82	22.81	22.85	0			1	24	22.73	22.72	22.76	0
		25	0	21.65	21.62	21.57	1			12	0	21.56	21.53	21.48	1
		25	12	21.61	21.50	21.53	1			12	6	21.52	21.41	21.44	1
		25	25	21.75	21.65	21.79	1			12	13	21.66	21.56	21.70	1
		50	0	21.59	21.60	21.70	1			25	0	21.50	21.51	21.61	1
	16QAM	1	0	21.78	21.86	21.93	1		16QAM	1	0	21.75	21.83	21.90	1
		1	24	21.93	21.76	21.83	1			1	12	21.90	21.73	21.80	1
		1	49	21.71	21.76	21.83	1			1	24	21.68	21.73	21.80	1
		25	0	20.87	20.75	20.65	2			12	0	20.84	20.72	20.62	2
		25	12	20.70	20.56	20.61	2			12	6	20.67	20.53	20.58	2
		25	25	20.72	20.65	20.90	2			12	13	20.69	20.62	20.87	2
		50	0	20.68	20.68	20.80	2			25	0	20.65	20.65	20.77	2

LTE Band 17															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23780	23790	23800				Channel		23755	23790	23825	
		Frequency (MHz)		709.0	710.0	711.0				Frequency (MHz)		706.5	710.0	713.5	
10M	QPSK	1	0	19.36	19.34	19.43	0	5M	QPSK	1	0	19.17	19.23	19.21	0
		1	24	19.26	19.24	19.33	0			1	12	19.12	19.23	19.08	0
		1	49	19.42	19.40	19.49	0			1	24	19.37	19.24	19.21	0
		25	0	19.33	19.31	19.40	0			12	0	19.18	19.19	19.11	0
		25	12	19.29	19.27	19.36	0			12	6	19.11	19.16	19.15	0
		25	25	19.30	19.28	19.37	0			12	13	19.16	19.07	19.11	0
		50	0	19.32	19.30	19.39	0			25	0	19.19	19.14	19.23	0
	16QAM	1	0	19.33	19.25	19.40	0		16QAM	1	0	19.10	19.12	19.32	0
		1	24	19.18	19.14	19.31	0			1	12	19.15	19.07	19.14	0
		1	49	19.41	19.33	19.49	0			1	24	19.24	19.22	19.31	0
		25	0	19.25	19.29	19.33	0			12	0	19.24	19.22	19.19	0
		25	12	19.20	19.20	19.32	0			12	6	19.05	19.14	19.18	0
		25	25	19.26	19.18	19.35	0			12	13	19.26	19.14	19.08	0
		50	0	19.24	19.30	19.34	0			25	0	19.23	19.16	19.30	0

FCC SAR Test Report

LTE Band 26															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26765	26865	26965				Channel		26740	26865	26990	
		Frequency (MHz)		821.5	831.5	841.5				Frequency (MHz)		819.0	831.5	844.0	
15M	QPSK	1	0	22.48	22.55	22.67	0	10M	QPSK	1	0	22.44	22.51	22.63	0
		1	37	22.94	22.71	22.69	0			1	24	22.90	22.67	22.65	0
		1	74	22.72	22.65	22.33	0			1	49	22.68	22.61	22.29	0
		36	0	21.87	21.70	21.74	1			25	0	21.83	21.66	21.70	1
		36	19	21.98	21.76	21.84	1			25	12	21.94	21.72	21.80	1
		36	39	21.69	21.69	21.59	1			25	25	21.65	21.65	21.55	1
		75	0	21.95	21.81	21.82	1			50	0	21.91	21.77	21.78	1
	16QAM	1	0	21.81	21.98	22.00	1		16QAM	1	0	21.74	21.91	21.93	1
		1	37	21.83	21.74	21.71	1			1	24	21.76	21.67	21.64	1
		1	74	21.96	21.87	21.64	1			1	49	21.89	21.80	21.57	1
		36	0	20.88	20.70	20.87	2			25	0	20.81	20.63	20.80	2
		36	19	20.80	20.69	20.80	2			25	12	20.73	20.62	20.73	2
		36	39	20.77	20.75	20.57	2			25	25	20.70	20.68	20.50	2
		75	0	20.76	20.87	20.86	2			50	0	20.69	20.80	20.79	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26715	26865	27015				Channel		26705	26865	27025	
		Frequency (MHz)		816.5	831.5	846.5				Frequency (MHz)		815.5	831.5	847.5	
5M	QPSK	1	0	22.38	22.45	22.57	0	3M	QPSK	1	0	22.34	22.41	22.53	0
		1	12	22.84	22.61	22.59	0			1	7	22.80	22.57	22.55	0
		1	24	22.62	22.55	22.23	0			1	14	22.58	22.51	22.19	0
		12	0	21.77	21.60	21.64	1			8	0	21.73	21.56	21.60	1
		12	6	21.88	21.66	21.74	1			8	3	21.84	21.62	21.70	1
		12	13	21.59	21.59	21.49	1			8	7	21.55	21.55	21.45	1
		25	0	21.85	21.71	21.72	1			15	0	21.81	21.67	21.68	1
	16QAM	1	0	21.71	21.88	21.90	1		16QAM	1	0	21.63	21.80	21.82	1
		1	12	21.73	21.64	21.61	1			1	7	21.65	21.56	21.53	1
		1	24	21.86	21.77	21.54	1			1	14	21.78	21.69	21.46	1
		12	0	20.78	20.60	20.77	2			8	0	20.70	20.52	20.69	2
		12	6	20.70	20.59	20.70	2			8	3	20.62	20.51	20.62	2
		12	13	20.67	20.65	20.47	2			8	7	20.59	20.57	20.39	2
		25	0	20.66	20.77	20.76	2			15	0	20.58	20.69	20.68	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)								
		Channel		26697	26865	27033									
		Frequency (MHz)		814.7	831.5	848.3									
1.4M	QPSK	1	0	22.30	22.37	22.49	0								
		1	2	22.76	22.53	22.51	0								
		1	5	22.54	22.47	22.15	0								
		3	0	22.69	22.52	22.56	0								
		3	1	22.80	22.58	22.66	0								
		3	3	22.51	22.51	22.41	0								
		6	0	21.77	21.63	21.64	1								
	16QAM	1	0	21.56	21.73	21.75	1								
		1	2	21.58	21.49	21.46	1								
		1	5	21.71	21.62	21.39	1								
		3	0	21.63	21.45	21.62	1								
		3	1	21.55	21.44	21.55	1								
		3	3	21.52	21.50	21.32	1								
		6	0	20.51	20.62	20.61	2								

FCC SAR Test Report

LTE Band 26															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26765	26865	26965				Channel		26740	26865	26990	
		Frequency (MHz)		821.5	831.5	841.5				Frequency (MHz)		819.0	831.5	844.0	
15M	QPSK	1	0	19.21	19.30	19.36	0	10M	QPSK	1	0	19.12	19.20	19.18	0
		1	37	19.66	19.57	19.63	0			1	24	19.57	19.43	19.40	0
		1	74	19.49	19.40	19.46	0			1	49	19.39	19.35	19.35	0
		36	0	19.54	19.45	19.51	0			25	0	19.40	19.40	19.40	0
		36	19	19.51	19.42	19.48	0			25	12	19.39	19.23	19.30	0
		36	39	19.46	19.37	19.43	0			25	25	19.29	19.21	19.39	0
		75	0	19.56	19.47	19.53	0			50	0	19.43	19.35	19.46	0
	16QAM	1	0	19.19	19.20	19.34	0		16QAM	1	0	19.12	19.22	19.22	0
		1	37	19.57	19.52	19.60	0			1	24	19.47	19.51	19.43	0
		1	74	19.46	19.37	19.45	0			1	49	19.37	19.16	19.36	0
		36	0	19.54	19.36	19.45	0			25	0	19.32	19.30	19.43	0
		36	19	19.41	19.32	19.43	0			25	12	19.35	19.39	19.27	0
		36	39	19.38	19.28	19.33	0			25	25	19.35	19.29	19.25	0
		75	0	19.48	19.43	19.45	0			50	0	19.48	19.29	19.41	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26715	26865	27015				Channel		26705	26865	27025	
		Frequency (MHz)		816.5	831.5	846.5				Frequency (MHz)		815.5	831.5	847.5	
5M	QPSK	1	0	19.00	19.23	19.16	0	3M	QPSK	1	0	19.00	19.22	19.12	0
		1	12	19.42	19.53	19.52	0			1	7	19.54	19.51	19.58	0
		1	24	19.39	19.33	19.35	0			1	14	19.41	19.22	19.34	0
		12	0	19.48	19.34	19.31	0			8	0	19.34	19.28	19.37	0
		12	6	19.33	19.35	19.16	0			8	3	19.45	19.24	19.39	0
		12	13	19.33	19.29	19.30	0			8	7	19.36	19.23	19.33	0
		25	0	19.51	19.37	19.35	0			15	0	19.42	19.46	19.30	0
	16QAM	1	0	19.07	19.10	19.27	0		16QAM	1	0	18.97	19.13	19.13	0
		1	12	19.46	19.43	19.50	0			1	7	19.49	19.40	19.40	0
		1	24	19.34	19.23	19.26	0			1	14	19.35	19.26	19.20	0
		12	0	19.42	19.33	19.38	0			8	0	19.36	19.22	19.30	0
		12	6	19.26	19.22	19.36	0			8	3	19.39	19.27	19.36	0
		12	13	19.19	19.15	19.23	0			8	7	19.37	19.20	19.17	0
		25	0	19.33	19.22	19.32	0			15	0	19.34	19.34	19.30	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)								
		Channel		26697	26865	27033									
		Frequency (MHz)		814.7	831.5	848.3									
1.4M	QPSK	1	0	19.10	19.18	19.26	0								
		1	2	19.53	19.37	19.47	0								
		1	5	19.31	19.27	19.24	0								
		3	0	19.49	19.28	19.37	0								
		3	1	19.39	19.35	19.38	0								
		3	3	19.35	19.26	19.38	0								
		6	0	19.40	19.35	19.47	0								
	16QAM	1	0	18.94	19.10	19.09	0								
		1	2	19.47	19.52	19.53	0								
		1	5	19.37	19.14	19.34	0								
		3	0	19.30	19.19	19.33	0								
		3	1	19.33	19.30	19.27	0								
		3	3	19.27	19.18	19.22	0								
		6	0	19.47	19.29	19.42	0								

FCC SAR Test Report

LTE Band 30															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel			27710					Channel		27685	27710	27735	
		Frequency (MHz)			2310.0					Frequency (MHz)		2307.5	2310.0	2312.5	
10M	QPSK	1	0		22.55		0	5M	QPSK	1	0	22.49	22.25	22.43	0
		1	24		22.24		0			1	12	22.40	22.45	22.47	0
		1	49		22.51		0			1	24	22.54	22.51	22.43	0
		25	0		21.38		1			12	0	21.34	21.33	21.58	1
		25	12		21.50		1			12	6	21.39	21.48	21.52	1
		25	25		21.62		1			12	13	21.31	21.51	21.63	1
		50	0		21.69		1			25	0	21.33	21.50	21.70	1
	16QAM	1	0		21.84		1		16QAM	1	0	21.06	21.51	21.71	1
		1	24		21.71		1			1	12	21.62	21.90	21.61	1
		1	49		21.79		1			1	24	21.38	21.47	21.56	1
		25	0		20.40		2			12	0	20.36	20.34	20.58	2
		25	12		20.59		2			12	6	20.31	20.50	20.59	2
		25	25		20.67		2			12	13	20.43	20.55	20.49	2
		50	0		20.81		2			25	0	20.29	20.43	20.56	2

LTE Band 30															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel			27710					Channel		27685	27710	27735	
		Frequency (MHz)			2310.0					Frequency (MHz)		2307.5	2310.0	2312.5	
10M	QPSK	1	0		12.99		0	5M	QPSK	1	0	12.95	12.93	12.94	0
		1	24		12.89		0			1	12	12.83	12.69	12.82	0
		1	49		12.84		0			1	24	12.84	12.77	12.83	0
		25	0		12.88		0			12	0	12.06	12.75	12.27	0
		25	12		12.91		0			12	6	12.11	12.87	12.21	0
		25	25		12.93		0			12	13	12.03	12.78	12.32	0
		50	0		12.96		0			25	0	12.05	12.83	12.39	0
	16QAM	1	0		12.94		0		16QAM	1	0	11.78	12.75	12.40	0
		1	24		12.86		0			1	12	12.34	12.80	12.30	0
		1	49		12.77		0			1	24	12.10	12.72	12.25	0
		25	0		12.79		0			12	0	11.08	12.69	11.27	0
		25	12		12.83		0			12	6	11.03	12.74	11.28	0
		25	25		12.89		0			12	13	11.15	12.81	11.18	0
		50	0		12.86		0			25	0	11.01	12.76	11.25	0

FCC SAR Test Report

LTE Band 38															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency (MHz)		2580.0	2595.0	2610.0				Frequency (MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	22.40	22.54	22.56	0	15M	QPSK	1	0	22.35	22.49	22.51	0
		1	50	22.38	22.51	22.61	0			1	37	22.33	22.46	22.56	0
		1	99	22.49	22.62	22.68	0			1	74	22.44	22.57	22.63	0
		50	0	21.47	21.66	21.73	1			36	0	21.42	21.61	21.68	1
		50	25	21.44	21.60	21.66	1			36	19	21.39	21.55	21.61	1
		50	50	21.46	21.62	21.68	1			36	39	21.41	21.57	21.63	1
		100	0	21.37	21.59	21.62	1			75	0	21.32	21.54	21.57	1
	16QAM	1	0	21.61	21.84	21.90	1		16QAM	1	0	21.54	21.77	21.83	1
		1	50	21.60	21.79	21.84	1			1	37	21.53	21.72	21.77	1
		1	99	21.71	21.91	21.90	1			1	74	21.64	21.84	21.83	1
		50	0	20.57	20.78	20.85	2			36	0	20.50	20.71	20.78	2
		50	25	20.58	20.79	20.84	2			36	19	20.51	20.72	20.77	2
		50	50	20.61	20.83	20.86	2			36	39	20.54	20.76	20.79	2
		100	0	20.47	20.66	20.71	2			75	0	20.40	20.59	20.64	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37800	38000	38200				Channel		37775	38000	38225	
		Frequency (MHz)		2575.0	2595.0	2615.0				Frequency (MHz)		2572.5	2595.0	2617.5	
10M	QPSK	1	0	22.30	22.44	22.46	0	5M	QPSK	1	0	22.26	22.40	22.42	0
		1	24	22.28	22.41	22.51	0			1	12	22.24	22.37	22.47	0
		1	49	22.39	22.52	22.58	0			1	24	22.35	22.48	22.54	0
		25	0	21.37	21.56	21.63	1			12	0	21.33	21.52	21.59	1
		25	12	21.34	21.50	21.56	1			12	6	21.30	21.46	21.52	1
		25	25	21.36	21.52	21.58	1			12	13	21.32	21.48	21.54	1
		50	0	21.27	21.49	21.52	1			25	0	21.23	21.45	21.48	1
	16QAM	1	0	21.51	21.74	21.80	1		16QAM	1	0	21.43	21.66	21.72	1
		1	24	21.50	21.69	21.74	1			1	12	21.42	21.61	21.66	1
		1	49	21.61	21.81	21.80	1			1	24	21.53	21.73	21.72	1
		25	0	20.47	20.68	20.75	2			12	0	20.39	20.60	20.67	2
		25	12	20.48	20.69	20.74	2			12	6	20.40	20.61	20.66	2
		25	25	20.51	20.73	20.76	2			12	13	20.43	20.65	20.68	2
		50	0	20.37	20.56	20.61	2			25	0	20.29	20.48	20.53	2

FCC SAR Test Report

LTE Band 38															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency (MHz)		2580.0	2595.0	2610.0				Frequency (MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	15.11	15.23	15.50	0	15M	QPSK	1	0	15.06	15.18	15.48	0
		1	50	15.16	15.28	15.55	0			1	37	15.08	15.25	15.45	0
		1	99	15.68	15.67	15.69	0			1	74	15.19	15.40	15.60	0
		50	0	15.09	15.21	15.48	0			36	0	15.00	15.21	15.43	0
		50	25	15.15	15.27	15.54	0			36	19	15.13	15.23	15.46	0
		50	50	15.19	15.31	15.58	0			36	39	15.15	15.26	15.49	0
		100	0	15.20	15.32	15.59	0			75	0	15.11	15.27	15.58	0
	16QAM	1	0	15.11	15.15	15.43	0		16QAM	1	0	14.93	15.18	15.38	0
		1	50	15.08	15.27	15.49	0			1	37	15.14	15.12	15.42	0
		1	99	15.19	15.38	15.58	0			1	74	15.14	15.30	15.56	0
		50	0	14.99	15.19	15.47	0			36	0	15.02	15.12	15.37	0
		50	25	15.06	15.23	15.48	0			36	19	15.03	15.20	15.41	0
		50	50	15.15	15.24	15.57	0			36	39	15.13	15.13	15.45	0
		100	0	15.17	15.31	15.55	0			75	0	15.08	15.23	15.51	0
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37800	38000	38200				Channel		37775	38000	38225	
		Frequency (MHz)		2575.0	2595.0	2615.0				Frequency (MHz)		2572.5	2595.0	2617.5	
10M	QPSK	1	0	14.90	15.21	15.41	0	5M	QPSK	1	0	15.02	15.17	15.34	0
		1	24	15.08	15.16	15.35	0			1	12	14.96	15.12	15.28	0
		1	49	15.22	15.26	15.53	0			1	24	15.07	15.38	15.64	0
		25	0	14.97	15.03	15.37	0			12	0	15.02	15.06	15.21	0
		25	12	15.06	15.22	15.45	0			12	6	15.09	15.27	15.32	0
		25	25	14.99	15.14	15.40	0			12	13	15.10	15.17	15.43	0
		50	0	15.02	15.18	15.55	0			25	0	15.14	15.26	15.45	0
	16QAM	1	0	14.91	15.13	15.29	0		16QAM	1	0	14.87	15.13	15.38	0
		1	24	15.01	15.16	15.35	0			1	12	14.97	15.03	15.26	0
		1	49	15.08	15.24	15.53	0			1	24	15.17	15.22	15.55	0
		25	0	14.95	15.04	15.28	0			12	0	15.00	15.02	15.36	0
		25	12	15.03	15.05	15.32	0			12	6	14.95	14.94	15.38	0
		25	25	15.04	15.21	15.51	0			12	13	15.14	15.22	15.42	0
		50	0	15.00	15.09	15.41	0			25	0	15.08	15.19	15.42	0

FCC SAR Test Report

LTE Band 41																			
EUT without Power Reduction (P-Sensor NOT Triggered)																			
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)
		Channel		39750	40185	40620	41055	41490				Channel		39725	40173	40620	41068	41515	
		Frequency (MHz)		2506	2549.5	2593.0	2636.5	2680.0				Frequency (MHz)		2503.5	2548.3	2593.0	2637.8	2682.5	
20M	QPSK	1	0	22.24	22.23	22.32	22.56	22.55	0	15M	QPSK	1	0	22.22	22.21	22.30	22.53	22.54	0
		1	50	22.20	22.22	22.29	22.47	22.42	0			1	37	22.18	22.20	22.27	22.45	22.40	0
		1	99	22.15	22.18	22.31	22.51	22.27	0			1	74	22.13	22.16	22.29	22.49	22.25	0
		50	0	21.18	21.19	21.26	21.45	21.38	1			36	0	21.16	21.17	21.24	21.43	21.36	1
		50	25	21.25	21.21	21.28	21.52	21.45	1			36	19	21.23	21.19	21.26	21.50	21.43	1
		50	50	21.11	21.18	21.23	21.49	21.32	1			36	39	21.09	21.16	21.21	21.47	21.30	1
		100	0	21.30	21.28	21.27	21.54	21.43	1			75	0	21.28	21.26	21.25	21.52	21.41	1
	16QAM	1	0	21.15	21.28	21.31	21.48	21.49	1		16QAM	1	0	21.10	21.23	21.26	21.43	21.44	1
		1	50	21.24	21.27	21.34	21.54	21.37	1			1	37	21.19	21.22	21.29	21.49	21.32	1
		1	99	21.29	21.27	21.37	21.48	21.25	1			1	74	21.24	21.22	21.32	21.43	21.20	1
		50	0	20.33	20.28	20.38	20.53	20.55	2			36	0	20.28	20.23	20.33	20.48	20.50	2
		50	25	20.31	20.30	20.37	20.60	20.46	2			36	19	20.25	20.25	20.32	20.55	20.41	2
		50	50	20.34	20.27	20.42	20.56	20.42	2			36	39	20.29	20.22	20.37	20.51	20.37	2
		100	0	20.28	20.30	20.37	20.58	20.44	2			75	0	20.24	20.25	20.32	20.53	20.39	2
10M	QPSK	1	0	22.18	22.17	22.26	22.49	22.50	0	5M	QPSK	1	0	22.14	22.13	22.22	22.45	22.46	0
		1	24	22.14	22.16	22.23	22.41	22.36	0			1	12	22.10	22.12	22.19	22.37	22.32	0
		1	49	22.09	22.12	22.25	22.45	22.21	0			1	24	22.05	22.08	22.21	22.41	22.17	0
		25	0	21.12	21.13	21.20	21.39	21.32	1			12	0	21.08	21.09	21.16	21.35	21.28	1
		25	12	21.19	21.15	21.22	21.46	21.39	1			12	6	21.15	21.11	21.18	21.42	21.35	1
		25	25	21.05	21.12	21.17	21.43	21.26	1			12	13	21.01	21.08	21.13	21.39	21.22	1
		50	0	21.24	21.22	21.21	21.48	21.37	1			25	0	21.20	21.18	21.17	21.44	21.33	1
	16QAM	1	0	21.07	21.20	21.23	21.40	21.41	1		16QAM	1	0	20.99	21.12	21.15	21.32	21.33	1
		1	24	21.16	21.19	21.26	21.46	21.29	1			1	12	21.08	21.11	21.18	21.38	21.21	1
		1	49	21.21	21.19	21.29	21.40	21.17	1			1	24	21.13	21.11	21.21	21.32	21.09	1
		25	0	20.25	20.20	20.30	20.45	20.47	2			12	0	20.17	20.12	20.22	20.37	20.39	2
		25	12	20.21	20.22	20.29	20.52	20.38	2			12	6	20.13	20.14	20.21	20.44	20.30	2
		25	25	20.26	20.19	20.34	20.48	20.34	2			12	13	20.18	20.11	20.26	20.40	20.26	2
		50	0	20.18	20.22	20.29	20.50	20.36	2			25	0	20.14	20.14	20.21	20.42	20.28	2

LTE Band 41																			
EUT with Power Reduction (P-Sensor Triggered)																			
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)
		Channel		39750	40185	40620	41055	41490				Channel		39725	40173	40620	41068	41515	
		Frequency (MHz)		2506	2549.5	2593.0	2636.5	2680.0				Frequency (MHz)		2503.5	2548.3	2593.0	2637.8	2682.5	
20M	QPSK	1	0	14.09	14.20	14.12	14.26	14.07	0	15M	QPSK	1	0	14.12	14.13	14.10	14.17	14.01	0
		1	50	14.08	14.19	14.11	14.25	14.06	0			1	37	14.11	14.12	14.08	14.17	13.98	0
		1	99	14.05	14.13	14.05	14.19	14.00	0			1	74	14.09	14.10	13.99	14.12	13.91	0
		50	0	14.08	14.17	14.09	14.23	14.04	0			36	0	14.11	14.12	13.99	14.22	14.03	0
		50	25	14.06	14.14	14.06	14.20	14.01	0			36	19	14.07	14.08	14.06	14.20	13.98	0
		50	50	14.03	14.16	14.08	14.22	14.03	0			36	39	14.10	14.11	14.08	14.19	14.02	0
		100	0	14.06	14.15	14.07	14.21	14.02	0			75	0	14.04	14.05	14.02	14.11	13.99	0
	16QAM	1	0	14.10	14.12	14.02	14.19	14.00	0		16QAM	1	0	14.17	14.18	14.10	14.16	14.00	0
		1	50	14.15	14.17	14.01	14.23	13.97	0			1	37	14.12	14.13	14.11	14.25	13.97	0
		1	99	14.05	14.07	13.95	14.18	13.92	0			1	74	14.09	14.10	14.03	14.18	13.96	0
		50	0	14.07	14.09	14.08	14.20	13.97	0			36	0	14.12	14.13	14.01	14.19	13.99	0
		50	25	14.11	14.13	14.02	14.14	13.98	0			36	19	14.10	14.11	14.00	14.13	13.98	0
		50	50	14.08	14.10	14.07	14.22	14.03	0			36	39	14.06	14.07	14.05	14.12	14.01	0
		100	0	14.12	14.14	14.06	14.13	13.92	0			75	0	14.09	14.10	14.00	14.18	13.92	0
10M	QPSK	1	0	14.08	14.10	14.05	14.13	13.99	0	5M	QPSK	1	0	14.10	14.13	14.09	14.13	13.97	0
		1	24	14.14	14.16	14.05	14.19	13.99	0			1	12	14.06	14.09	14.05	14.15	13.91	0
		1	49	13.94	13.96	13.95	14.06	13.99	0			1	24	13.93	13.96	13.95	14.13	13.98	0
		25	0	13.99	14.01	13.99	14.09	13.95	0			12	0	14.11	14.14	14.00	14.17	13.92	0
		25	12	13.95	13.97	13.92	14.14	13.82	0			12	6	14.05	14.08	14.04	14.11	13.94	0
		25	25	14.00	14.02	13.92	14.08	13.93	0			12	13	13.99	14.02	13.98	14.12	14.02	0
		50	0	14.01	14.03	13.98	14.09	13.83	0			25	0	13.96	13.99	14.02	14.20	13.98	0
	16QAM	1	0	14.12	14.14	14.06	14.17	13.94	0		16QAM	1	0	14.10	14.13	14.03	14.14	13.96	0
		1	24	14.06	14.08	13.96	14.16	14.01	0			1	12	14.12	14.15	13.96	14.25	13.96	0
		1	49	14.03	14.05	13.87	14.09	13.93	0			1	24	14.00	14.03	13.95	14.07	13.91	0
		25	0	14.05	14.07	14.04	14.08	14.00	0			12	0	14.03	14.06	13.99	14.14	14.00	0
		25	12	13.97	13.99	13.94	14.09	13.87	0			12	6	14.04	14.07	13.96	14.08	13.98	0
		25	25	13.97	13.99	13.93	14.11	13.89	0			12	13	14.06	14.09	14.00	14.02	14.02	0
		50	0	14.03	14.05	13.94	14.18	13.83	0			25	0	14.01	14.04	13.98	14.19	13.93	0

FCC SAR Test Report

LTE Band 66															
EUT without Power Reduction (P-Sensor NOT Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		132072	132322	132572				Channel		132047	132322	132597	
		Frequency (MHz)		1720.0	1745.0	1770.0				Frequency (MHz)		1717.5	1745.0	1772.5	
20M	QPSK	1	0	22.77	22.89	22.86	0	15M	QPSK	1	0	22.70	22.82	22.79	0
		1	50	22.72	22.58	22.43	0			1	37	22.65	22.51	22.36	0
		1	99	22.54	22.63	22.68	0			1	74	22.47	22.56	22.61	0
		50	0	21.80	21.82	21.69	1			36	0	21.73	21.75	21.62	1
		50	25	21.75	21.57	21.53	1			36	19	21.68	21.50	21.46	1
		50	50	21.61	21.45	21.54	1			36	39	21.54	21.38	21.47	1
		100	0	21.81	21.90	21.79	1			75	0	21.74	21.83	21.72	1
	16QAM	1	0	21.97	21.94	21.89	1		16QAM	1	0	21.95	21.92	21.87	1
		1	50	21.75	21.87	21.74	1			1	37	21.73	21.85	21.72	1
		1	99	21.83	21.78	21.71	1			1	74	21.81	21.76	21.69	1
		50	0	20.76	20.46	20.61	2			36	0	20.74	20.44	20.59	2
		50	25	20.69	20.57	20.43	2			36	19	20.67	20.55	20.41	2
		50	50	20.54	20.75	20.48	2			36	39	20.52	20.73	20.46	2
		100	0	20.81	20.75	20.78	2			75	0	20.79	20.73	20.76	2
10M	QPSK	1	0	22.65	22.77	22.74	0	5M	QPSK	1	0	22.61	22.73	22.70	0
		1	24	22.60	22.46	22.31	0			1	12	22.56	22.42	22.27	0
		1	49	22.42	22.51	22.56	0			1	24	22.38	22.47	22.52	0
		25	0	21.68	21.70	21.57	1			12	0	21.64	21.66	21.53	1
		25	12	21.63	21.45	21.41	1			12	6	21.59	21.41	21.37	1
		25	25	21.49	21.33	21.42	1			12	13	21.45	21.29	21.38	1
		50	0	21.69	21.78	21.67	1			25	0	21.65	21.74	21.63	1
	16QAM	1	0	21.92	21.89	21.84	1		16QAM	1	0	21.84	21.81	21.76	1
		1	24	21.70	21.82	21.69	1			1	12	21.62	21.74	21.61	1
		1	49	21.78	21.73	21.66	1			1	24	21.70	21.65	21.58	1
		25	0	20.71	20.41	20.56	2			12	0	20.63	20.33	20.48	2
		25	12	20.64	20.52	20.38	2			12	6	20.56	20.44	20.30	2
		25	25	20.49	20.70	20.43	2			12	13	20.41	20.62	20.35	2
		50	0	20.76	20.70	20.73	2			25	0	20.68	20.62	20.65	2
3M	QPSK	1	0	22.54	22.66	22.63	0	1.4M	QPSK	1	0	22.50	22.62	22.59	0
		1	7	22.49	22.35	22.20	0			1	2	22.45	22.31	22.16	0
		1	14	22.31	22.40	22.45	0			1	5	22.27	22.36	22.41	0
		8	0	21.57	21.59	21.46	1			3	0	22.53	22.55	22.42	0
		8	3	21.52	21.34	21.30	1			3	1	22.48	22.30	22.26	0
		8	7	21.38	21.22	21.31	1			3	3	22.34	22.18	22.27	0
		15	0	21.58	21.67	21.56	1			6	0	21.54	21.63	21.52	1
	16QAM	1	0	21.82	21.79	21.74	1		16QAM	1	0	21.75	21.72	21.67	1
		1	7	21.60	21.72	21.59	1			1	2	21.53	21.65	21.52	1
		1	14	21.68	21.63	21.56	1			1	5	21.61	21.56	21.49	1
		8	0	20.61	20.31	20.46	2			3	0	21.54	21.24	21.39	1
		8	3	20.54	20.42	20.28	2			3	1	21.47	21.35	21.21	1
		8	7	20.39	20.60	20.33	2			3	3	21.32	21.53	21.26	1
		15	0	20.66	20.60	20.63	2			6	0	20.59	20.53	20.56	2

FCC SAR Test Report

LTE Band 66															
EUT with Power Reduction (P-Sensor Triggered)															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		132072	132322	132572				Channel		132047	132322	132597	
		Frequency (MHz)		1720.0	1745.0	1770.0				Frequency (MHz)		1717.5	1745.0	1772.5	
20M	QPSK	1	0	14.40	14.47	14.25	0	15M	QPSK	1	0	14.37	14.42	14.15	0
		1	50	14.08	14.15	13.93	0			1	37	14.05	14.08	13.83	0
		1	99	14.05	14.12	13.90	0			1	74	14.02	14.09	13.84	0
		50	0	14.30	14.37	14.15	0			36	0	14.26	14.29	14.07	0
		50	25	14.19	14.26	14.04	0			36	19	14.19	14.23	14.01	0
		50	50	14.17	14.24	14.02	0			36	39	14.14	14.14	13.97	0
		100	0	14.31	14.38	14.16	0			75	0	14.29	14.34	14.06	0
	16QAM	1	0	14.40	14.39	14.23	0		16QAM	1	0	14.34	14.32	14.11	0
		1	50	14.08	14.15	13.89	0			1	37	14.00	14.13	13.90	0
		1	99	14.02	14.08	13.80	0			1	74	13.92	14.01	13.82	0
		50	0	14.27	14.33	14.07	0			36	0	14.25	14.32	14.08	0
		50	25	14.13	14.16	13.94	0			36	19	14.07	14.13	13.94	0
		50	50	14.10	14.19	14.02	0			36	39	14.11	14.05	13.92	0
		100	0	14.30	14.33	14.16	0			75	0	14.26	14.29	13.97	0
10M	QPSK	1	0	14.30	14.30	14.13	0	5M	QPSK	1	0	14.28	14.41	14.16	0
		1	24	13.97	13.98	13.82	0			1	12	14.00	13.96	13.78	0
		1	49	13.99	14.08	13.75	0			1	24	13.85	13.91	13.75	0
		25	0	14.25	14.29	13.98	0			12	0	14.16	14.24	13.91	0
		25	12	14.05	14.08	13.99	0			12	6	14.06	14.11	13.68	0
		25	25	14.12	14.06	13.98	0			12	13	14.00	14.17	13.86	0
		50	0	14.16	14.27	14.08	0			25	0	14.17	14.29	14.14	0
	16QAM	1	0	14.29	14.26	14.02	0		16QAM	1	0	14.15	14.31	14.06	0
		1	24	13.83	13.92	13.87	0			1	12	13.99	13.87	13.62	0
		1	49	13.75	14.01	13.86	0			1	24	13.87	13.87	13.63	0
		25	0	14.10	14.18	13.98	0			12	0	14.17	14.09	14.03	0
		25	12	14.05	14.12	13.82	0			12	6	13.97	14.15	13.88	0
		25	25	13.97	14.01	13.80	0			12	13	13.90	14.00	13.79	0
		50	0	14.19	14.28	14.06	0			25	0	14.08	14.07	13.88	0
3M	QPSK	1	0	14.32	14.26	14.08	0	1.4M	QPSK	1	0	14.19	14.34	14.18	0
		1	7	13.93	14.02	13.81	0			1	2	13.97	14.04	13.73	0
		1	14	13.98	14.06	13.76	0			1	5	13.83	14.04	13.77	0
		8	0	14.18	14.18	14.03	0			3	0	14.12	14.25	14.07	0
		8	3	14.05	14.09	13.97	0			3	1	14.18	14.12	13.91	0
		8	7	14.08	14.04	13.93	0			3	3	14.08	14.08	13.89	0
		15	0	14.18	14.25	14.12	0			6	0	14.14	14.24	14.06	0
	16QAM	1	0	14.27	14.31	14.18	0		16QAM	1	0	14.19	14.39	14.04	0
		1	7	13.94	13.99	13.74	0			1	2	13.96	13.95	13.80	0
		1	14	13.74	13.99	13.88	0			1	5	13.92	14.02	13.63	0
		8	0	14.17	14.27	14.03	0			3	0	14.05	14.18	14.04	0
		8	3	14.01	14.23	13.90	0			3	1	14.00	14.10	13.98	0
		8	7	14.04	14.06	13.75	0			3	3	14.02	14.03	13.78	0
		15	0	14.10	14.21	14.08	0			6	0	14.15	14.15	14.02	0

FCC SAR Test Report

Laptop PC Mode

<WLAN 2.4G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11b	1	2412	16.05	15.48	-
	6	2437	16.82	15.76	-
	11	2462	16.49	15.63	-
	12	2467	12.98	13.90	-
	13	2472	6.85	6.94	-
802.11n (HT20)	1	2412	-	-	13.97
	6	2437	-	-	16.93
	11	2462	-	-	13.97
	12	2467	-	-	6.97
	13	2472	-	-	-8.02

<WLAN 5.3G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11n (HT40)	54	5270	18.86	12.38	17.95
	62	5310	11.96	12.16	9.96

<WLAN 5.6G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11n (HT40)	102	5510	16.93	-	11.97
	110	5550	18.97	-	16.96
	118	5590	18.92	-	17.82
	126	5630	18.82	-	17.95
	134	5670	17.95	-	15.88
	142	5710	18.88	-	17.93
802.11ac (VHT80)	106	5530	-	11.48	-
	122	5610	-	11.05	-
	138	5690	-	11.79	-

<WLAN 5.8G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11n (HT40)	151	5755	18.91	-	15.97
	159	5795	18.89	-	15.80
802.11ac (VHT80)	155	5775	-	11.58	-

<Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power
Bluetooth EDR	0	2402	12.7
	39	2441	12.82
	78	2480	12.65
Bluetooth LE	0	2402	11.53
	19	2440	11.73
	39	2480	11.75

FCC SAR Test Report

Tablet PC Mode

<WLAN 2.4G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11b	1	2412	16.89	13.37	-
	6	2437	16.96	13.49	-
	11	2462	16.92	13.47	-
	12	2467	12.98	13.42	-
	13	2472	6.85	6.94	-
802.11n (HT20)	1	2412	-	-	13.97
	6	2437	-	-	16.93
	11	2462	-	-	13.97
	12	2467	-	-	6.97
	13	2472	-	-	-6.54

<WLAN 5.3G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11ac (VHT80)	58	5290	8.43	7.47	11.39

<WLAN 5.6G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11ac (VHT80)	106	5530	5.92	7.34	11.45
	122	5610	5.95	7.42	11.40
	138	5690	5.96	7.47	11.47

<WLAN 5.8G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11ac (VHT80)	155	5775	5.97	7.95	11.73

<Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power
Bluetooth EDR	0	2402	12.7
	39	2441	12.82
	78	2480	12.65
Bluetooth LE	0	2402	11.53
	19	2440	11.73
	39	2480	11.75

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

(1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

(2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

(3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

(4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

FCC SAR Test Report

<Power Confirmation for SAR Test Exclusion for LTE Downlink CA>

According to KDB 941225 D05A, the uplink maximum output power below was measured with downlink CA active on the channel with highest measured maximum output power when downlink CA is inactive. The downlink SCC channel was paired with the uplink channel as normal operation. For intra-band contiguous CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing per section 5.4.1A of 3GPP TS36.521. For intra-band non-contiguous CA, the downlink channel spacing between the component carriers was set to maximum separation from PCC and remain fully within the downlink transmission band. For Inter-band CA, the SCC downlink channel was set to near the middle of its transmission band.

EUT without Power Reduction (P-Sensor NOT Triggered)

Power Measurements for Intra-Band Contiguous Downlink CA

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
7C	7	20M	21350	2560	1	0	3350	2680	7	20M	3152	2660.2	-	-	-	-	22.68	22.62
7B	7	15M	21375	2562.5	1	0	3375	2682.5	7	5M	3282	2673.2	-	-	-	-	22.60	22.47
41C	41	20M	41055	2636.5	1	0	41055	2636.5	41	20M	41253	2656.3	-	-	-	-	22.56	22.50
66D	66	20M	132072	1720	1	0	66536	2120	66	20M	66734	2139.8	66	20M	66932	2159.6	22.77	22.49

Power Measurements for Intra-Band Non-Contiguous Downlink CA

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
7A-7A	7	20M	21350	2560	1	0	3350	2680	7	20M	2850	2630	-	-	-	-	22.68	22.39
41A-41A	41	20M	41055	2636.5	1	0	41055	2636.5	41	20M	41490	2680	-	-	-	-	22.56	22.51

Power Measurements for Intra-Band Non-Contiguous Downlink CA(Two Band)

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
2C-5A	2	20M	18700	1860	1	0	700	1940	2	20M	898	1959.8	5	10M	2525	881.5	23.09	22.97
2A-17A	2	10M	18650	1855	1	0	650	1935	17	10M	5790	740	-	-	-	-	22.97	22.81
2A-66B	2	20M	18700	1860	1	0	700	1940	66	15M	66786	2145	66	5M	66879	2154.3	23.09	22.62
2A-66C	2	20M	18700	1860	1	0	700	1940	66	20M	66786	2145	66	20M	66984	2164.8	23.09	22.94
4A-17A	4	10M	20350	1750	1	0	2350	2150	17	10M	5790	740	-	-	-	-	22.75	22.57
5A-7A	5	10M	20450	829	1	0	2450	874	7	20M	3100	2565	-	-	-	-	22.73	22.70
5A-66B	5	10M	20450	829	1	0	2450	874	66	15M	66786	2145	66	5M	66879	2154.3	22.73	22.70
5A-66C	5	10M	20450	829	1	0	2450	874	66	20M	66786	2145	66	20M	66984	2164.8	22.73	22.69
13A-66B	13	10M	23230	782	1	49	5230	751	66	15M	66786	2145	66	5M	66879	2154.3	22.93	22.85
13A-66C	13	10M	23230	782	1	49	5230	751	66	20M	66786	2145	66	20M	66984	2164.8	22.93	22.92

FCC SAR Test Report

Power Measurements for Intra-Band Non-Contiguous Downlink CA(Three Band)

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
2A-4A-5A	2	20M	18700	1860	1	0	700	1940	4	20M	2175	2132.5	5	10M	2525	881.5	23.09	23.07
2A-4A-13A	2	20M	18700	1860	1	0	700	1940	4	20M	2175	2132.5	13	10M	5230	751	23.09	22.98
2A-5A-30A	2	20M	18700	1860	1	0	700	1940	5	10M	2525	881.5	30	10M	9820	2355	23.09	23.04
2A-5A-66A	2	20M	18700	1860	1	0	700	1940	5	10M	2525	881.5	66	20M	66786	2145	23.09	22.90
2A-12A-30A	2	20M	18700	1860	1	0	700	1940	12	10M	5095	737.5	30	10M	9820	2355	23.09	22.85
2A-13A-66A	2	20M	18700	1860	1	0	700	1940	13	10M	5230	751	66	20M	66786	2145	23.09	22.67
2A-29A-30A	2	20M	18700	1860	1	0	700	1940	29	10M	9715	722.5	30	10M	9820	2355	23.09	22.74
4A-5A-30A	4	20M	20300	1745	1	0	2300	2145	5	10M	2525	881.5	30	10M	9820	2355	22.88	22.42
4A-12A-30A	4	20M	20300	1745	1	0	2300	2145	12	10M	5095	737.5	30	10M	9820	2355	22.88	22.47
4A-29A-30A	4	20M	20300	1745	1	0	2300	2145	29	10M	9715	722.5	30	10M	9820	2355	22.88	22.55

EUT with Power Reduction (P-Sensor Triggered)

Power Measurements for Intra-Band Contiguous Downlink CA

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
7C	7	20M	21350	2560	1	0	3350	2680	7	20M	3152	2660.2	-	-	-	-	11.99	11.81
7B	7	15M	21375	2562.5	1	0	3375	2682.5	7	5M	3282	2673.2	-	-	-	-	11.97	11.92
41C	41	20M	41055	2636.5	1	0	41055	2636.5	41	20M	41253	2656.3	-	-	-	-	14.26	14.11
66D	66	20M	132072	1720	1	0	66536	2120	66	20M	66734	2139.8	66	20M	66932	2159.6	13.92	13.84

Power Measurements for Intra-Band Non-Contiguous Downlink CA

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
7A-7A	7	20M	21350	2560	1	0	3350	2680	7	20M	2850	2630	-	-	-	-	11.99	11.86
41A-41A	41	20M	41055	2636.5	1	0	41055	2636.5	41	20M	41490	2680	-	-	-	-	14.26	14.01

FCC SAR Test Report

Power Measurements for Intra-Band Non-Contiguous Downlink CA(Two Band)

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
2C-5A	2	20M	18700	1860	50	0	700	1940	2	20M	898	1959.8	5	10M	2525	881.5	11.85	11.76
2A-17A	2	10M	18650	1855	1	0	650	1935	17	10M	5790	740	-	-	-	-	11.72	11.64
2A-66B	2	20M	18700	1860	50	0	700	1940	66	15M	66786	2145	66	5M	66879	2154.3	11.85	11.52
2A-66C	2	20M	18700	1860	50	0	700	1940	66	20M	66786	2145	66	20M	66984	2164.8	11.85	11.83
4A-17A	4	10M	20350	1750	25	0	2350	2150	17	10M	5790	740	-	-	-	-	13.90	13.85
5A-7A	5	10M	20450	829	1	0	2450	874	7	20M	3100	2565	-	-	-	-	19.32	19.24
5A-66B	5	10M	20450	829	1	0	2450	874	66	15M	66786	2145	66	5M	66879	2154.3	19.32	19.19
5A-66C	5	10M	20450	829	1	0	2450	874	66	20M	66786	2145	66	20M	66984	2164.8	19.32	19.30
13A-66B	13	10M	23230	782	1	49	5230	751	66	15M	66786	2145	66	5M	66879	2154.3	19.22	19.02
13A-66C	13	10M	23230	782	1	49	5230	751	66	20M	66786	2145	66	20M	66984	2164.8	19.22	19.18

Power Measurements for Intra-Band Non-Contiguous Downlink CA(Three Band)

CA Combination	PCC								SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Ch	UL Freq. (MHz)	RB Size	RB Offset	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	LTE Band	BW (MHz)	DL Ch	DL Freq. (MHz)	Single Carrier Tx Power (dBm)	Tx Power with DL-CA Active (dBm)
2A-4A-5A	2	20M	18700	1860	50	0	700	1940	4	20M	2175	2132.5	5	10M	2525	881.5	11.85	11.72
2A-4A-13A	2	20M	18700	1860	50	0	700	1940	4	20M	2175	2132.5	13	10M	5230	751	11.85	11.77
2A-5A-30A	2	20M	18700	1860	50	0	700	1940	5	10M	2525	881.5	30	10M	9820	2355	11.85	11.75
2A-5A-66A	2	20M	18700	1860	50	0	700	1940	5	10M	2525	881.5	66	20M	66786	2145	11.85	11.80
2A-12A-30A	2	20M	18700	1860	50	0	700	1940	12	10M	5095	737.5	30	10M	9820	2355	11.85	11.77
2A-13A-66A	2	20M	18700	1860	50	0	700	1940	13	10M	5230	751	66	20M	66786	2145	11.85	11.75
2A-29A-30A	2	20M	18700	1860	50	0	700	1940	29	10M	9715	722.5	30	10M	9820	2355	11.85	11.76
4A-5A-30A	4	20M	20300	1745	1	0	2300	2145	5	10M	2525	881.5	30	10M	9820	2355	13.99	13.62
4A-12A-30A	4	20M	20300	1745	1	0	2300	2145	12	10M	5095	737.5	30	10M	9820	2355	13.99	13.82
4A-29A-30A	4	20M	20300	1745	1	0	2300	2145	29	10M	9715	722.5	30	10M	9820	2355	13.99	13.69

Summary for SAR Test Exclusion for LTE Downlink CA

Per power confirmation results in above, the uplink maximum output power with downlink CA active remains within the specified tune-up tolerance and not more than 0.25 dB higher than the maximum output power with downlink CA inactive. According to KDB 941225 D05A, the SAR test exclusion applies to LTE downlink CA operation.

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC SAR Test Report

4.7.2 SAR Results for Body Exposure Condition

Laptop PC Mode

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
01	WCDMA II	RMC 12.2K	Bottom	0	9538	1	12.0	11.90	1.02	0.07	0.448	0.46
	WCDMA II	RMC 12.2K	Bottom	0	9262	1	12.0	11.87	1.03	-0.02	0.418	0.43
	WCDMA II	RMC 12.2K	Bottom	0	9400	1	12.0	11.83	1.04	0.06	0.405	0.42
	WCDMA II	RMC 12.2K	Bottom	0	9538	2	12.0	11.90	1.02	0.14	0.409	0.42
	WCDMA II	RMC 12.2K	Bottom	0	9538	3	12.0	11.90	1.02	0.09	0.401	0.41
02	WCDMA IV	RMC 12.2K	Bottom	0	1513	1	14.0	13.62	1.09	0.03	0.456	0.50
	WCDMA IV	RMC 12.2K	Bottom	0	1312	1	14.0	13.51	1.12	0.1	0.538	0.60
	WCDMA IV	RMC 12.2K	Bottom	0	1413	1	14.0	13.54	1.11	-0.05	0.479	0.53
	WCDMA IV	RMC 12.2K	Bottom	0	1312	2	14.0	13.51	1.12	0.09	0.509	0.57
	WCDMA IV	RMC 12.2K	Bottom	0	1312	3	14.0	13.51	1.12	0.13	0.501	0.56
03	WCDMA V	RMC 12.2K	Bottom	0	4182	1	19.0	18.93	1.02	0.11	0.701	0.71
	WCDMA V	RMC 12.2K	Bottom	0	4132	1	19.0	18.78	1.05	0.07	0.693	0.73
	WCDMA V	RMC 12.2K	Bottom	0	4233	1	19.0	18.84	1.04	-0.13	0.718	0.74
	WCDMA V	RMC 12.2K	Bottom	0	4233	2	19.0	18.84	1.04	0.14	0.701	0.73
	WCDMA V	RMC 12.2K	Bottom	0	4233	3	19.0	18.84	1.04	0.09	0.698	0.72

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	RB#	RB Offset	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
04	LTE 2	QPSK20M	Bottom	0	18700	1	0	1	12.0	11.82	1.04	0.10	0.400	0.42
	LTE 2	QPSK20M	Bottom	0	18700	50	0	1	12.0	11.85	1.04	-0.05	0.219	0.23
	LTE 2	QPSK20M	Bottom	0	18900	1	0	1	12.0	11.62	1.09	0.01	0.365	0.40
	LTE 2	QPSK20M	Bottom	0	19100	1	0	1	12.0	11.54	1.11	0.08	0.364	0.40
	LTE 2	QPSK20M	Bottom	0	18700	1	0	2	12.0	11.82	1.04	0.03	0.395	0.41
	LTE 2	QPSK20M	Bottom	0	18700	1	0	3	12.0	11.82	1.04	0.01	0.361	0.38
05	LTE 4	QPSK20M	Bottom	0	20300	1	0	1	14.0	13.99	1.00	-0.03	0.501	0.50
	LTE 4	QPSK20M	Bottom	0	20300	50	0	1	14.0	13.98	1.00	0.09	0.491	0.49
	LTE 4	QPSK20M	Bottom	0	20050	1	0	1	14.0	13.92	1.02	0.04	0.592	0.60
	LTE 4	QPSK20M	Bottom	0	20175	1	0	1	14.0	13.84	1.04	0.01	0.561	0.58
	LTE 4	QPSK20M	Bottom	0	20050	1	0	2	14.0	13.92	1.02	0.06	0.563	0.57
	LTE 4	QPSK20M	Bottom	0	20050	1	0	3	14.0	13.92	1.02	0.13	0.555	0.57
06	LTE 5	QPSK10M	Bottom	0	20450	1	0	1	19.5	19.32	1.04	0.03	0.789	0.82
	LTE 5	QPSK10M	Bottom	0	20450	25	0	1	19.5	19.21	1.07	-0.07	0.724	0.77
	LTE 5	QPSK10M	Bottom	0	20525	1	0	1	19.5	19.28	1.05	0.04	0.840	0.88
	LTE 5	QPSK10M	Bottom	0	20600	1	0	1	19.5	19.20	1.07	0.09	0.817	0.88
	LTE 5	QPSK10M	Bottom	0	20450	50	0	1	19.5	19.09	1.10	-0.03	0.795	0.87
	LTE 5	QPSK10M	Bottom	0	20525	1	0	2	19.5	19.28	1.05	0.06	0.751	0.79
07	LTE 5	QPSK10M	Bottom	0	20525	1	0	3	19.5	19.28	1.05	0.01	0.749	0.79
	LTE 5	QPSK10M	Bottom	0	20525	1	0	1	19.5	19.28	1.05	0.04	0.82	0.86
	LTE 7	QPSK20M	Bottom	0	21350	1	0	1	12.0	11.99	1.00	0.08	0.620	0.62
	LTE 7	QPSK20M	Bottom	0	21350	50	0	1	12.0	11.98	1.00	-0.03	0.586	0.59
	LTE 7	QPSK20M	Bottom	0	20850	1	0	1	12.0	11.90	1.02	-0.12	0.546	0.56
	LTE 7	QPSK20M	Bottom	0	21100	1	0	1	12.0	11.92	1.02	-0.03	0.566	0.58
	LTE 7	QPSK20M	Bottom	0	21350	1	0	2	12.0	11.99	1.00	0.05	0.595	0.60
	LTE 7	QPSK20M	Bottom	0	21350	1	0	3	12.0	11.99	1.00	0.13	0.569	0.57

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	RB#	RB Offset	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
08	LTE 12	QPSK10M	Bottom	0	23060	1	24	1	19.5	19.35	1.04	0.08	0.881	0.91
	LTE 12	QPSK10M	Bottom	0	23060	25	12	1	19.5	19.34	1.04	0.04	0.867	0.90
	LTE 12	QPSK10M	Bottom	0	23095	1	24	1	19.5	19.31	1.04	-0.10	0.886	0.93
	LTE 12	QPSK10M	Bottom	0	23130	1	24	1	19.5	19.32	1.04	0.03	0.868	0.90
	LTE 12	QPSK10M	Bottom	0	23095	25	12	1	19.5	19.30	1.05	-0.04	0.861	0.90
	LTE 12	QPSK10M	Bottom	0	23130	25	12	1	19.5	19.31	1.04	0.05	0.858	0.90
	LTE 12	QPSK10M	Bottom	0	23060	50	0	1	19.5	19.28	1.05	0.07	0.836	0.88
	LTE 12	QPSK10M	Bottom	0	23095	1	24	2	19.5	19.31	1.04	0.09	0.759	0.79
09	LTE 12	QPSK10M	Bottom	0	23095	1	24	3	19.5	19.31	1.04	0.04	0.751	0.78
	LTE 12	QPSK10M	Bottom	0	23095	1	24	1	19.5	19.31	1.04	-0.05	0.878	0.92
	LTE 13	QPSK10M	Bottom	0	23230	1	49	1	19.5	19.22	1.07	0.08	0.925	0.99
	LTE 13	QPSK10M	Bottom	0	23230	25	0	1	19.5	19.18	1.08	-0.09	0.934	1.01
	LTE 13	QPSK10M	Bottom	0	23230	50	0	1	19.5	19.19	1.07	0.1	0.928	1.00
	LTE 13	QPSK10M	Bottom	0	23230	25	0	2	19.5	19.18	1.08	0.06	0.921	0.99
	LTE 13	QPSK10M	Bottom	0	23230	25	0	3	19.5	19.18	1.08	0.09	0.917	0.99
	LTE 13	QPSK10M	Bottom	0	23230	25	0	1	19.5	19.18	1.08	0.05	0.931	1.00
10	LTE 17	QPSK10M	Bottom	0	23800	1	49	1	19.5	19.49	1.00	-0.06	0.847	0.85
	LTE 17	QPSK10M	Bottom	0	23800	25	0	1	19.5	19.40	1.02	0.03	0.82	0.84
	LTE 17	QPSK10M	Bottom	0	23780	1	49	1	19.5	19.42	1.02	0.07	0.811	0.83
	LTE 17	QPSK10M	Bottom	0	23790	1	49	1	19.5	19.40	1.02	-0.02	0.806	0.82
	LTE 17	QPSK10M	Bottom	0	23780	25	0	1	19.5	19.33	1.04	0.03	0.808	0.84
	LTE 17	QPSK10M	Bottom	0	23790	25	0	1	19.5	19.31	1.04	0.1	0.805	0.84
	LTE 17	QPSK10M	Bottom	0	23800	50	0	1	19.5	19.39	1.03	0.08	0.813	0.83
	LTE 17	QPSK10M	Bottom	0	23800	1	49	2	19.5	19.49	1.00	0.09	0.791	0.79
	LTE 17	QPSK10M	Bottom	0	23800	1	49	3	19.5	19.49	1.00	0.01	0.785	0.79
	LTE 17	QPSK10M	Bottom	0	23800	1	49	1	19.5	19.49	1.00	-0.04	0.843	0.84
11	LTE 26	QPSK15M	Bottom	0	26765	1	37	1	20.0	19.66	1.08	0.1	0.788	0.85
	LTE 26	QPSK15M	Bottom	0	26765	36	0	1	20.0	19.54	1.11	0.07	0.779	0.87
	LTE 26	QPSK15M	Bottom	0	26865	1	37	1	20.0	19.57	1.10	-0.16	0.819	0.90
	LTE 26	QPSK15M	Bottom	0	26965	1	37	1	20.0	19.63	1.09	0.12	0.782	0.85
	LTE 26	QPSK15M	Bottom	0	26865	36	0	1	20.0	19.45	1.14	0.03	0.792	0.90
	LTE 26	QPSK15M	Bottom	0	26965	36	0	1	20.0	19.51	1.12	-0.1	0.789	0.88
	LTE 26	QPSK15M	Bottom	0	26865	1	37	2	20.0	19.57	1.10	0.09	0.717	0.79
	LTE 26	QPSK15M	Bottom	0	26865	1	37	3	20.0	19.57	1.10	0.13	0.709	0.78
12	LTE 26	QPSK15M	Bottom	0	26865	1	37	1	20.0	19.57	1.10	-0.16	0.813	0.90
	LTE 30	QPSK10M	Bottom	0	27710	1	0	1	13.0	12.99	1.00	-0.17	0.807	0.81
	LTE 30	QPSK10M	Bottom	0	27710	25	25	1	13.0	12.93	1.02	0.03	0.785	0.80
	LTE 30	QPSK10M	Bottom	0	27710	50	0	1	13.0	12.96	1.01	0.1	0.795	0.80
	LTE 30	QPSK10M	Bottom	0	27710	1	0	2	13.0	12.99	1.00	0.06	0.776	0.78
	LTE 30	QPSK10M	Bottom	0	27710	1	0	3	13.0	12.99	1.00	0.08	0.743	0.74
13	LTE 30	QPSK10M	Bottom	0	27710	1	0	1	13.0	12.99	1.00	0.06	0.801	0.80
	LTE 38	QPSK20M	Bottom	0	38150	1	99	1	16.0	15.69	1.07	-0.06	0.616	0.66
	LTE 38	QPSK20M	Bottom	0	38150	50	50	1	16.0	15.58	1.10	-0.03	0.601	0.66
	LTE 38	QPSK20M	Bottom	0	37850	1	99	1	16.0	15.68	1.08	0.17	0.705	0.76
	LTE 38	QPSK20M	Bottom	0	38000	1	99	1	16.0	15.67	1.08	0.02	0.671	0.72
	LTE 38	QPSK20M	Bottom	0	37850	1	99	2	16.0	15.68	1.08	0.05	0.661	0.71
	LTE 38	QPSK20M	Bottom	0	37850	1	99	3	16.0	15.68	1.08	0.13	0.651	0.70

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	RB#	RB Offset	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 41	QPSK20M	Bottom	0	41055	1	0	1	14.5	14.26	1.06	-0.03	0.465	0.49
	LTE 41	QPSK20M	Bottom	0	41055	50	0	1	14.5	14.23	1.06	0.05	0.432	0.46
	LTE 41	QPSK20M	Bottom	0	39750	1	0	1	14.5	14.09	1.10	0.08	0.518	0.57
14	LTE 41	QPSK20M	Bottom	0	40185	1	0	1	14.5	14.20	1.07	0.11	0.578	0.62
	LTE 41	QPSK20M	Bottom	0	40620	1	0	1	14.5	14.12	1.09	0.05	0.545	0.59
	LTE 41	QPSK20M	Bottom	0	41490	1	0	1	14.5	14.07	1.10	-0.03	0.376	0.42
	LTE 41	QPSK20M	Bottom	0	40185	1	0	2	14.5	14.20	1.07	0.05	0.541	0.58
	LTE 41	QPSK20M	Bottom	0	40185	1	0	3	14.5	14.20	1.07	0.13	0.532	0.57
	LTE 66	QPSK20M	Bottom	0	132322	1	0	1	14.5	14.47	1.01	-0.09	0.478	0.48
	LTE 66	QPSK20M	Bottom	0	132322	50	0	1	14.5	14.37	1.03	0.04	0.467	0.48
15	LTE 66	QPSK20M	Bottom	0	132072	1	0	1	14.5	14.40	1.02	0.08	0.564	0.58
	LTE 66	QPSK20M	Bottom	0	132572	1	0	1	14.5	14.25	1.06	0.1	0.437	0.46
	LTE 66	QPSK20M	Bottom	0	132072	1	0	2	14.5	14.40	1.02	0.06	0.513	0.52
	LTE 66	QPSK20M	Bottom	0	132072	1	0	3	14.5	14.40	1.02	-0.13	0.503	0.51

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	EUT Config.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
16	WLAN2.4G	802.11b	Bottom	0	6	1	Ant 0	17.0	16.82	1.04	0.06	1.11	1.16
	WLAN2.4G	802.11b	Bottom	0	6	1	Ant 1	16.0	15.76	1.06	-0.03	1.02	1.08
	WLAN2.4G	802.11n HT20	Bottom	0	6	1	Ant 0+1	17.0	16.93	1.02	-0.05	0.472	0.48
	WLAN2.4G	802.11b	Bottom	0	1	1	Ant 0	17.0	16.05	1.24	-0.09	0.902	1.12
	WLAN2.4G	802.11b	Bottom	0	11	1	Ant 0	17.0	16.49	1.12	0.02	1.02	1.15
	WLAN2.4G	802.11b	Bottom	0	12	1	Ant 0	13.0	12.98	1.00	0.04	0.335	0.34
	WLAN2.4G	802.11b	Bottom	0	13	1	Ant 0	7.0	6.85	1.04	-0.02	0.086	0.09
	WLAN2.4G	802.11b	Bottom	0	1	1	Ant 1	16.0	15.48	1.13	0.01	0.992	1.12
	WLAN2.4G	802.11b	Bottom	0	6	2	Ant 0	17.0	16.82	1.04	0.06	1.01	1.05
	WLAN2.4G	802.11b	Bottom	0	11	2	Ant 0	17.0	16.49	1.12	0.02	0.985	1.11
	WLAN2.4G	802.11b	Bottom	0	6	3	Ant 0	17.0	16.82	1.04	0.06	0.985	1.03
	WLAN2.4G	802.11b	Bottom	0	11	3	Ant 0	17.0	16.49	1.12	0.02	0.949	1.07
	WLAN2.4G	802.11b	Bottom	0	6	1	Ant 0	17.0	16.82	1.04	0.05	1.08	1.13

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	EUT Config.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WLAN5G	802.11n HT40	Bottom	0	54	1	Ant 0	19.0	18.86	1.03	0.04	0.338	0.35
	WLAN5G	802.11n HT40	Bottom	0	54	1	Ant 1	12.5	12.38	1.03	0.09	0.997	1.02
17	WLAN5G	802.11n HT40	Bottom	0	54	1	Ant 0+1	18.0	17.95	1.01	-0.03	1.09	1.10
	WLAN5G	802.11n HT40	Bottom	0	62	1	Ant 1	12.5	12.16	1.08	0.06	0.826	0.89
	WLAN5G	802.11n HT40	Bottom	0	62	1	Ant 0+1	10.0	9.96	1.01	-0.08	0.202	0.20
	WLAN5G	802.11n HT40	Bottom	0	54	2	Ant 0+1	18.0	17.95	1.01	0.03	0.959	0.97
	WLAN5G	802.11n HT40	Bottom	0	62	2	Ant 0+1	10.0	9.96	1.01	0.09	0.195	0.20
	WLAN5G	802.11n HT40	Bottom	0	54	3	Ant 0+1	18.0	17.95	1.01	0.1	0.943	0.95
	WLAN5G	802.11n HT40	Bottom	0	62	3	Ant 0+1	10.0	9.96	1.01	0.08	0.191	0.19
	WLAN5G	802.11n HT40	Bottom	0	54	1	Ant 0+1	18.0	17.95	1.01	0.02	1.05	1.06
	WLAN5G	802.11n HT40	Bottom	0	110	1	Ant 0	19.0	18.97	1.01	0.06	0.589	0.59
	WLAN5G	802.11ac VHT80	Bottom	0	138	1	Ant 1	12.0	11.79	1.05	-0.11	1.09	1.14
18	WLAN5G	802.11n HT40	Bottom	0	126	1	Ant 0+1	18.0	17.95	1.01	-0.07	1.15	1.16
	WLAN5G	802.11ac VHT80	Bottom	0	106	1	Ant 1	12.0	11.48	1.13	0.05	0.989	1.11
	WLAN5G	802.11n HT40	Bottom	0	102	1	Ant 0+1	12.0	11.97	1.01	-0.08	0.246	0.25
	WLAN5G	802.11n HT40	Bottom	0	110	1	Ant 0+1	17.0	16.96	1.01	0.02	0.764	0.77
	WLAN5G	802.11n HT40	Bottom	0	118	1	Ant 0+1	18.0	17.82	1.04	-0.11	0.953	0.99
	WLAN5G	802.11n HT40	Bottom	0	134	1	Ant 0+1	16.0	15.88	1.03	0.05	0.701	0.72
	WLAN5G	802.11n HT40	Bottom	0	142	1	Ant 0+1	18.0	17.93	1.02	-0.06	1.13	1.15
	WLAN5G	802.11n HT40	Bottom	0	126	2	Ant 0+1	18.0	17.95	1.01	0.09	1.08	1.09
	WLAN5G	802.11n HT40	Bottom	0	142	2	Ant 0+1	18.0	17.93	1.02	0.01	1.01	1.03
	WLAN5G	802.11n HT40	Bottom	0	126	3	Ant 0+1	18.0	17.95	1.01	0.08	1.03	1.04
	WLAN5G	802.11n HT40	Bottom	0	142	3	Ant 0+1	18.0	17.93	1.02	0.08	0.99	1.01
	WLAN5G	802.11n HT40	Bottom	0	126	1	Ant 0+1	18.0	17.95	1.01	0.02	1.11	1.12
	WLAN5G	802.11n HT40	Bottom	0	151	1	Ant 0	19.0	18.91	1.02	0.03	0.752	0.77
19	WLAN5G	802.11ac VHT80	Bottom	0	155	1	Ant 1	12.0	11.58	1.10	0.16	1.01	1.11
	WLAN5G	802.11n HT40	Bottom	0	151	1	Ant 0+1	16.0	15.97	1.01	-0.03	1.07	1.08
	WLAN5G	802.11n HT40	Bottom	0	159	1	Ant 0+1	16.0	15.80	1.05	-0.02	1.05	1.10
	WLAN5G	802.11ac VHT80	Bottom	0	155	2	Ant 1	12.0	11.58	1.10	0.09	0.959	1.06
	WLAN5G	802.11ac VHT80	Bottom	0	155	3	Ant 1	12.0	11.58	1.10	0.13	0.943	1.04
	WLAN5G	802.11n HT40	Bottom	0	151	1	Ant 0+1	16.0	15.97	1.01	0.11	1.03	1.04

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	EUT Config.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
20	BT	BR/EDR	Bottom	0	39	1	Ant 1	13.0	12.82	1.04	-0.10	0.025	0.03
	BT	BR/EDR	Bottom	0	0	1	Ant 1	13.0	12.70	1.07	-0.02	0.024	0.03
	BT	BR/EDR	Bottom	0	78	1	Ant 1	13.0	12.65	1.08	0.11	0.023	0.02
	BT	BR/EDR	Bottom	0	39	2	Ant 1	13.0	12.82	1.04	0.14	0.017	0.02
	BT	BR/EDR	Bottom	0	39	3	Ant 1	13.0	12.82	1.04	0.09	0.012	0.01

FCC SAR Test Report

Tablet PC Mode

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
21	WCDMA II	RMC 12.2K	Rear Face	20	9538	w/o	1	23.5	23.50	1.00	0.01	0.538	0.54
	WCDMA II	RMC 12.2K	Rear Face	0	9538	w/	1	12.0	11.90	1.02	-0.02	1.13	1.16
	WCDMA II	RMC 12.2K	Left Side	0	9538	w/o	1	23.5	23.50	1.00	-0.05	0.196	0.20
	WCDMA II	RMC 12.2K	Right Side	0	9538	w/o	1	23.5	23.50	1.00	0.00	0.001	0.00
	WCDMA II	RMC 12.2K	Top Side	20	9538	w/o	1	23.5	23.50	1.00	0.04	0.091	0.09
	WCDMA II	RMC 12.2K	Top Side	0	9538	w/	1	12.0	11.90	1.02	-0.13	0.114	0.12
	WCDMA II	RMC 12.2K	Bottom Side	0	9538	w/o	1	23.5	23.50	1.00	0.00	0.001	0.00
	WCDMA II	RMC 12.2K	Rear Face	0	9262	w/	1	12.0	11.87	1.03	0.05	0.993	1.02
	WCDMA II	RMC 12.2K	Rear Face	0	9400	w/	1	12.0	11.83	1.04	-0.01	1.058	1.10
	WCDMA II	RMC 12.2K	Rear Face	0	9538	w/	2	12.0	11.90	1.02	0.06	1.11	1.14
	WCDMA II	RMC 12.2K	Rear Face	0	9262	w/	2	12.0	11.87	1.03	0.05	1.03	1.06
	WCDMA II	RMC 12.2K	Rear Face	0	9400	w/	2	12.0	11.83	1.04	0.01	0.995	1.03
	WCDMA II	RMC 12.2K	Rear Face	0	9538	w/	3	12.0	11.90	1.02	0.09	1.08	1.11
	WCDMA II	RMC 12.2K	Rear Face	0	9262	w/	3	12.0	11.87	1.03	-0.10	0.991	1.02
	WCDMA II	RMC 12.2K	Rear Face	0	9400	w/	3	12.0	11.83	1.04	0.06	0.988	1.03
	WCDMA II	RMC 12.2K	Rear Face	0	9538	w/	1	12.0	11.90	1.02	-0.02	1.11	1.14
22	WCDMA IV	RMC 12.2K	Rear Face	20	1513	w/o	1	23.5	23.48	1.00	-0.03	0.323	0.32
	WCDMA IV	RMC 12.2K	Rear Face	0	1513	w/	1	14.0	13.62	1.09	0.01	0.839	0.92
	WCDMA IV	RMC 12.2K	Left Side	0	1513	w/o	1	23.5	23.48	1.00	0.13	0.126	0.13
	WCDMA IV	RMC 12.2K	Right Side	0	1513	w/o	1	23.5	23.48	1.00	0.00	0.001	0.00
	WCDMA IV	RMC 12.2K	Top Side	20	1513	w/o	1	23.5	23.48	1.00	0.05	0.069	0.07
	WCDMA IV	RMC 12.2K	Top Side	0	1513	w/	1	14.0	13.62	1.09	-0.05	0.087	0.09
	WCDMA IV	RMC 12.2K	Bottom Side	0	1513	w/o	1	23.5	23.48	1.00	0.00	0.001	0.00
	WCDMA IV	RMC 12.2K	Rear Face	0	1312	w/	1	14.0	13.51	1.12	-0.16	0.857	0.96
	WCDMA IV	RMC 12.2K	Rear Face	0	1413	w/	1	14.0	13.54	1.11	0.02	0.843	0.94
	WCDMA IV	RMC 12.2K	Rear Face	0	1312	w/	2	14.0	13.51	1.12	0.05	0.832	0.93
	WCDMA IV	RMC 12.2K	Rear Face	0	1413	w/	2	14.0	13.54	1.11	0.13	0.821	0.91
	WCDMA IV	RMC 12.2K	Rear Face	0	1513	w/	2	14.0	13.62	1.09	0.06	0.813	0.89
	WCDMA IV	RMC 12.2K	Rear Face	0	1312	w/	3	14.0	13.51	1.12	0.09	0.828	0.93
	WCDMA IV	RMC 12.2K	Rear Face	0	1413	w/	3	14.0	13.54	1.11	0.11	0.82	0.91
	WCDMA IV	RMC 12.2K	Rear Face	0	1513	w/	3	14.0	13.62	1.09	0.05	0.814	0.89
	WCDMA IV	RMC 12.2K	Rear Face	0	1312	w/	1	14.0	13.51	1.12	-0.16	0.855	0.96
23	WCDMA V	RMC 12.2K	Rear Face	20	4182	w/o	1	23.5	23.49	1.00	-0.01	0.164	0.16
	WCDMA V	RMC 12.2K	Rear Face	0	4182	w/	1	19.0	18.93	1.02	-0.01	0.423	0.43
	WCDMA V	RMC 12.2K	Left Side	0	4182	w/o	1	23.5	23.49	1.00	0.14	0.140	0.14
	WCDMA V	RMC 12.2K	Right Side	0	4182	w/o	1	23.5	23.49	1.00	0.00	0.001	0.00
	WCDMA V	RMC 12.2K	Top Side	20	4182	w/o	1	23.5	23.49	1.00	0.10	0.054	0.05
	WCDMA V	RMC 12.2K	Top Side	0	4182	w/	1	19.0	18.93	1.02	0.09	0.125	0.13
	WCDMA V	RMC 12.2K	Bottom Side	0	4182	w/o	1	23.5	23.49	1.00	0.00	0.001	0.00
	WCDMA V	RMC 12.2K	Rear Face	0	4132	w/	1	19.0	18.78	1.05	-0.05	0.422	0.44
	WCDMA V	RMC 12.2K	Rear Face	0	4233	w/	1	19.0	18.84	1.04	0.03	0.432	0.45
	WCDMA V	RMC 12.2K	Rear Face	0	4233	w/	2	19.0	18.84	1.04	0.13	0.421	0.44
	WCDMA V	RMC 12.2K	Rear Face	0	4233	w/	3	19.0	18.84	1.04	0.06	0.408	0.42

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 2	QPSK20M	Rear Face	20	18700	1	0	w/o	1	23.5	23.09	1.10	-0.06	0.354	0.39
	LTE 2	QPSK20M	Rear Face	0	18700	1	0	w/	1	12.0	11.82	1.04	-0.09	1.05	1.09
	LTE 2	QPSK20M	Left Side	0	18700	1	0	w/o	1	23.5	23.09	1.10	0.11	0.294	0.32
	LTE 2	QPSK20M	Right Side	0	18700	1	0	w/o	1	23.5	23.09	1.10	0.00	0.001	0.00
	LTE 2	QPSK20M	Top Side	20	18700	1	0	w/o	1	23.5	23.09	1.10	0.12	0.074	0.08
	LTE 2	QPSK20M	Top Side	0	18700	1	0	w/	1	12.0	11.82	1.04	0.03	0.133	0.14
	LTE 2	QPSK20M	Bottom Side	0	18700	1	0	w/o	1	23.5	23.09	1.10	0.00	0.001	0.00
	LTE 2	QPSK20M	Rear Face	20	18700	50	0	w/o	1	22.5	21.91	1.15	0.14	0.288	0.33
	LTE 2	QPSK20M	Rear Face	0	18700	50	0	w/	1	12.0	11.85	1.04	-0.05	1.04	1.08
	LTE 2	QPSK20M	Left Side	0	18700	50	0	w/o	1	22.5	21.91	1.15	0.13	0.241	0.28
	LTE 2	QPSK20M	Right Side	0	18700	50	0	w/o	1	22.5	21.91	1.15	0.00	0.001	0.00
	LTE 2	QPSK20M	Top Side	20	18700	50	0	w/o	1	22.5	21.91	1.15	0.15	0.063	0.07
	LTE 2	QPSK20M	Top Side	0	18700	50	0	w/	1	12.0	11.85	1.04	0.02	0.083	0.09
	LTE 2	QPSK20M	Bottom Side	0	18700	50	0	w/o	1	22.5	21.91	1.15	0.00	0.001	0.00
	LTE 2	QPSK20M	Rear Face	0	18900	1	0	w/	1	12.0	11.62	1.09	0.01	1.03	1.12
	LTE 2	QPSK20M	Rear Face	0	19100	1	0	w/	1	12.0	11.54	1.11	0.00	1.04	1.16
	LTE 2	QPSK20M	Rear Face	0	18900	50	0	w/	1	12.0	11.65	1.08	-0.08	1.06	1.15
24	LTE 2	QPSK20M	Rear Face	0	19100	50	0	w/	1	12.0	11.57	1.10	-0.05	1.07	1.18
	LTE 2	QPSK20M	Rear Face	0	18700	100	0	w/	1	12.0	11.84	1.04	0.01	1.02	1.06
	LTE 2	QPSK20M	Rear Face	0	19100	50	0	w/	2	12.0	11.57	1.10	0.09	1.06	1.17
	LTE 2	QPSK20M	Rear Face	0	18700	50	0	w/	2	12.0	11.85	1.04	0.04	0.983	1.02
	LTE 2	QPSK20M	Rear Face	0	18900	50	0	w/	2	12.0	11.65	1.08	0.14	0.959	1.04
	LTE 2	QPSK20M	Rear Face	0	19100	50	0	w/	3	12.0	11.57	1.10	0.08	1.03	1.14
	LTE 2	QPSK20M	Rear Face	0	18700	50	0	w/	3	12.0	11.85	1.04	0.05	0.955	0.99
	LTE 2	QPSK20M	Rear Face	0	18900	50	0	w/	3	12.0	11.65	1.08	0.01	0.943	1.02
	LTE 2	QPSK20M	Rear Face	0	19100	50	0	w/	1	12.0	11.57	1.10	-0.05	1.05	1.16
	LTE 4	QPSK20M	Rear Face	20	20300	1	0	w/o	1	23.0	22.88	1.03	0.06	0.398	0.41
	LTE 4	QPSK20M	Rear Face	0	20300	1	0	w/	1	14.0	13.99	1.00	-0.08	1.11	1.11
	LTE 4	QPSK20M	Left Side	0	20300	1	0	w/o	1	23.0	22.88	1.03	-0.09	0.16	0.16
	LTE 4	QPSK20M	Right Side	0	20300	1	0	w/o	1	23.0	22.88	1.03	0.00	0.001	0.00
	LTE 4	QPSK20M	Top Side	20	20300	1	0	w/o	1	23.0	22.88	1.03	0.03	0.088	0.09
	LTE 4	QPSK20M	Top Side	0	20300	1	0	w/	1	14.0	13.99	1.00	0.03	0.113	0.11
	LTE 4	QPSK20M	Bottom Side	0	20300	1	0	w/o	1	23.0	22.88	1.03	0.00	0.001	0.00
	LTE 4	QPSK20M	Rear Face	20	20300	50	0	w/o	1	22.0	21.90	1.02	-0.02	0.319	0.33
25	LTE 4	QPSK20M	Rear Face	0	20300	50	0	w/	1	14.0	13.98	1.00	-0.04	1.18	1.19
	LTE 4	QPSK20M	Left Side	0	20300	50	0	w/o	1	22.0	21.90	1.02	0.01	0.085	0.09
	LTE 4	QPSK20M	Right Side	0	20300	50	0	w/o	1	22.0	21.90	1.02	0.00	0.001	0.00
	LTE 4	QPSK20M	Top Side	20	20300	50	0	w/o	1	22.0	21.90	1.02	0.07	0.09	0.09
	LTE 4	QPSK20M	Top Side	0	20300	50	0	w/	1	14.0	13.98	1.00	-0.07	0.091	0.09
	LTE 4	QPSK20M	Bottom Side	0	20300	50	0	w/o	1	22.0	21.90	1.02	0.00	0.001	0.00
	LTE 4	QPSK20M	Rear Face	0	20050	1	0	w/	1	14.0	13.92	1.02	0.08	1.03	1.05
	LTE 4	QPSK20M	Rear Face	0	20175	1	0	w/	1	14.0	13.84	1.04	-0.08	1.06	1.10
	LTE 4	QPSK20M	Rear Face	0	20050	50	0	w/	1	14.0	13.97	1.01	0.12	0.99	1.00
	LTE 4	QPSK20M	Rear Face	0	20175	50	0	w/	1	14.0	13.83	1.04	0.03	1.02	1.06
	LTE 4	QPSK20M	Rear Face	0	20300	100	0	w/	1	14.0	13.93	1.02	-0.05	0.921	0.94
	LTE 4	QPSK20M	Rear Face	0	20300	50	0	w/	2	14.0	13.98	1.00	0.09	1.09	1.10
	LTE 4	QPSK20M	Rear Face	0	20050	50	0	w/	2	14.0	13.97	1.01	0.06	1.06	1.07
	LTE 4	QPSK20M	Rear Face	0	20175	50	0	w/	2	14.0	13.83	1.04	0.01	1.03	1.07
	LTE 4	QPSK20M	Rear Face	0	20300	50	0	w/	3	14.0	13.98	1.00	0.08	1.05	1.05
	LTE 4	QPSK20M	Rear Face	0	20050	50	0	w/	3	14.0	13.97	1.01	0.13	0.995	1.00
	LTE 4	QPSK20M	Rear Face	0	20175	50	0	w/	3	14.0	13.83	1.04	0.06	0.987	1.03
	LTE 4	QPSK20M	Rear Face	0	20300	50	0	w/	1	14.0	13.98	1.00	-0.04	1.13	1.14

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 5	QPSK10M	Rear Face	20	20450	1	0	w/o	1	23.0	22.73	1.06	0.00	0.145	0.15
	LTE 5	QPSK10M	Rear Face	0	20450	1	0	w/	1	19.5	19.32	1.04	-0.09	0.552	0.58
	LTE 5	QPSK10M	Left Side	0	20450	1	0	w/o	1	23.0	22.73	1.06	-0.02	0.096	0.10
	LTE 5	QPSK10M	Right Side	0	20450	1	0	w/o	1	23.0	22.73	1.06	0.00	0.001	0.00
	LTE 5	QPSK10M	Top Side	20	20450	1	0	w/o	1	23.0	22.73	1.06	0.00	0.046	0.05
	LTE 5	QPSK10M	Top Side	0	20450	1	0	w/	1	19.5	19.32	1.04	0.03	0.12	0.13
	LTE 5	QPSK10M	Bottom Side	0	20450	1	0	w/o	1	23.0	22.73	1.06	0.00	0.001	0.00
	LTE 5	QPSK10M	Rear Face	20	20450	25	0	w/o	1	22.0	21.78	1.05	-0.01	0.113	0.12
26	LTE 5	QPSK10M	Rear Face	0	20450	25	0	w/	1	19.5	19.21	1.07	0.03	0.589	0.63
	LTE 5	QPSK10M	Left Side	0	20450	25	0	w/o	1	22.0	21.78	1.05	0.02	0.069	0.07
	LTE 5	QPSK10M	Right Side	0	20450	25	0	w/o	1	22.0	21.78	1.05	0.00	0.001	0.00
	LTE 5	QPSK10M	Top Side	20	20450	25	0	w/o	1	22.0	21.78	1.05	-0.18	0.064	0.07
	LTE 5	QPSK10M	Top Side	0	20450	25	0	w/	1	19.5	19.21	1.07	0.00	0.116	0.12
	LTE 5	QPSK10M	Bottom Side	0	20450	25	0	w/o	1	22.0	21.78	1.05	0.00	0.001	0.00
	LTE 5	QPSK10M	Rear Face	0	20525	1	0	w/	1	19.5	19.17	1.08	0.01	0.538	0.58
	LTE 5	QPSK10M	Rear Face	0	20600	1	0	w/	1	19.5	19.09	1.10	0.08	0.541	0.59
	LTE 5	QPSK10M	Rear Face	0	20450	25	0	w/	2	19.5	19.21	1.07	0.06	0.544	0.58
	LTE 5	QPSK10M	Rear Face	0	20450	25	0	w/	3	19.5	19.21	1.07	0.13	0.532	0.57
	LTE 7	QPSK20M	Rear Face	20	21350	1	0	w/o	1	23.0	22.68	1.08	0.05	0.385	0.41
	LTE 7	QPSK20M	Rear Face	0	21350	1	0	w/	1	12.0	11.99	1.00	-0.13	0.780	0.78
	LTE 7	QPSK20M	Left Side	0	21350	1	0	w/o	1	23.0	22.68	1.08	-0.06	0.107	0.12
	LTE 7	QPSK20M	Right Side	0	21350	1	0	w/o	1	23.0	22.68	1.08	0.00	0.001	0.00
	LTE 7	QPSK20M	Top Side	20	21350	1	0	w/o	1	23.0	22.68	1.08	-0.06	0.166	0.18
	LTE 7	QPSK20M	Top Side	0	21350	1	0	w/	1	12.0	11.99	1.00	0.04	0.202	0.20
	LTE 7	QPSK20M	Bottom Side	0	21350	1	0	w/o	1	23.0	22.68	1.08	0.00	0.001	0.00
	LTE 7	QPSK20M	Rear Face	20	21350	50	50	w/o	1	22.0	21.70	1.07	0.06	0.274	0.29
	LTE 7	QPSK20M	Rear Face	0	21350	50	0	w/	1	12.0	11.98	1.00	-0.14	1.10	1.11
	LTE 7	QPSK20M	Left Side	0	21350	50	50	w/o	1	22.0	21.70	1.07	-0.18	0.604	0.65
	LTE 7	QPSK20M	Right Side	0	21350	50	50	w/o	1	22.0	21.70	1.07	0.00	0.001	0.00
	LTE 7	QPSK20M	Top Side	20	21350	50	50	w/o	1	22.0	21.70	1.07	0.04	0.107	0.11
	LTE 7	QPSK20M	Top Side	0	21350	50	0	w/	1	12.0	11.98	1.00	0.09	0.175	0.18
	LTE 7	QPSK20M	Bottom Side	0	21350	50	50	w/o	1	22.0	21.70	1.07	0.00	0.001	0.00
27	LTE 7	QPSK20M	Rear Face	0	20850	50	0	w/	1	12.0	11.89	1.03	-0.02	1.11	1.14
	LTE 7	QPSK20M	Rear Face	0	21100	50	0	w/	1	12.0	11.91	1.02	-0.02	0.98	1.00
	LTE 7	QPSK20M	Rear Face	0	21350	100	0	w/	1	12.0	11.97	1.01	0.03	0.895	0.90
	LTE 7	QPSK20M	Rear Face	0	20850	50	0	w/	2	12.0	11.89	1.03	0.06	1.03	1.06
	LTE 7	QPSK20M	Rear Face	0	21100	50	0	w/	2	12.0	11.91	1.02	0.13	0.982	1.00
	LTE 7	QPSK20M	Rear Face	0	21350	50	0	w/	2	12.0	11.98	1.00	0.08	0.942	0.95
	LTE 7	QPSK20M	Rear Face	0	20850	50	0	w/	3	12.0	11.89	1.03	0.09	1.01	1.04
	LTE 7	QPSK20M	Rear Face	0	21100	50	0	w/	3	12.0	11.91	1.02	0.05	0.995	1.02
	LTE 7	QPSK20M	Rear Face	0	21350	50	0	w/	3	12.0	11.98	1.00	0.01	0.943	0.95
	LTE 7	QPSK20M	Rear Face	0	20850	50	0	w/	1	12.0	11.89	1.03	-0.02	1.05	1.08

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
28	LTE 12	QPSK10M	Rear Face	20	23060	1	0	w/o	1	23.0	22.96	1.01	0.01	0.123	0.12
	LTE 12	QPSK10M	Rear Face	0	23060	1	24	w/	1	19.5	19.35	1.04	-0.06	0.745	0.77
	LTE 12	QPSK10M	Left Side	0	23060	1	0	w/o	1	23.0	22.96	1.01	-0.08	0.088	0.09
	LTE 12	QPSK10M	Right Side	0	23060	1	0	w/o	1	23.0	22.96	1.01	0.00	0.001	0.00
	LTE 12	QPSK10M	Top Side	20	23060	1	0	w/o	1	23.0	22.96	1.01	0.00	0.001	0.00
	LTE 12	QPSK10M	Top Side	0	23060	1	24	w/	1	19.5	19.35	1.04	-0.09	0.188	0.19
	LTE 12	QPSK10M	Bottom Side	0	23060	1	0	w/o	1	23.0	22.96	1.01	0.00	0.001	0.00
	LTE 12	QPSK10M	Rear Face	20	23060	25	0	w/o	1	22.0	21.95	1.01	0.02	0.087	0.09
	LTE 12	QPSK10M	Rear Face	0	23060	25	12	w/	1	19.5	19.34	1.04	0.03	0.652	0.68
	LTE 12	QPSK10M	Left Side	0	23060	25	0	w/o	1	22.0	21.95	1.01	-0.13	0.066	0.07
	LTE 12	QPSK10M	Right Side	0	23060	25	0	w/o	1	22.0	21.95	1.01	0.00	0.001	0.00
	LTE 12	QPSK10M	Top Side	20	23060	25	0	w/o	1	22.0	21.95	1.01	0.00	0.001	0.00
	LTE 12	QPSK10M	Top Side	0	23060	25	12	w/	1	19.5	19.34	1.04	-0.05	0.148	0.15
	LTE 12	QPSK10M	Bottom Side	0	23060	25	0	w/o	1	22.0	21.95	1.01	0.00	0.001	0.00
	LTE 12	QPSK10M	Rear Face	0	23095	1	24	w/	1	19.5	19.31	1.04	0.02	0.667	0.70
	LTE 12	QPSK10M	Rear Face	0	23130	1	24	w/	1	19.5	19.32	1.04	-0.11	0.648	0.68
	LTE 12	QPSK10M	Rear Face	0	23060	1	24	w/	2	19.5	19.35	1.04	0.06	0.712	0.74
	LTE 12	QPSK10M	Rear Face	0	23060	1	24	w/	3	19.5	19.35	1.04	0.13	0.711	0.74
	LTE 13	QPSK10M	Rear Face	20	23230	1	49	w/o	1	23.0	22.93	1.02	-0.01	0.153	0.16
	LTE 13	QPSK10M	Rear Face	0	23230	1	49	w/	1	19.5	19.22	1.07	0.01	0.617	0.66
	LTE 13	QPSK10M	Left Side	0	23230	1	49	w/o	1	23.0	22.93	1.02	0.08	0.075	0.08
	LTE 13	QPSK10M	Right Side	0	23230	1	49	w/o	1	23.0	22.93	1.02	0.00	0.001	0.00
	LTE 13	QPSK10M	Top Side	20	23230	1	49	w/o	1	23.0	22.93	1.02	0.00	0.001	0.00
	LTE 13	QPSK10M	Top Side	0	23230	1	49	w/	1	19.5	19.22	1.07	-0.03	0.187	0.20
	LTE 13	QPSK10M	Bottom Side	0	23230	1	49	w/o	1	23.0	22.93	1.02	0.00	0.001	0.00
	LTE 13	QPSK10M	Rear Face	20	23230	25	0	w/o	1	22.0	21.74	1.06	0.10	0.131	0.14
	LTE 13	QPSK10M	Rear Face	0	23230	25	0	w/	1	19.5	19.18	1.08	-0.02	0.640	0.69
	LTE 13	QPSK10M	Left Side	0	23230	25	0	w/o	1	22.0	21.74	1.06	0.06	0.058	0.06
	LTE 13	QPSK10M	Right Side	0	23230	25	0	w/o	1	22.0	21.74	1.06	0.00	0.001	0.00
	LTE 13	QPSK10M	Top Side	20	23230	25	0	w/o	1	22.0	21.74	1.06	0.00	0.001	0.00
	LTE 13	QPSK10M	Top Side	0	23230	25	0	w/	1	19.5	19.18	1.08	0.07	0.196	0.21
	LTE 13	QPSK10M	Bottom Side	0	23230	25	0	w/o	1	22.0	21.74	1.06	0.00	0.001	0.00
	LTE 13	QPSK10M	Rear Face	0	23230	25	0	w/	2	19.5	19.18	1.08	0.06	0.599	0.64
	LTE 13	QPSK10M	Rear Face	0	23230	25	0	w/	3	19.5	19.18	1.08	0.13	0.587	0.63

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 17	QPSK10M	Rear Face	20	23800	1	49	w/o	1	23.0	22.85	1.04	-0.01	0.114	0.12
	LTE 17	QPSK10M	Rear Face	0	23800	1	49	w/	1	19.5	19.49	1.00	0.07	0.642	0.64
	LTE 17	QPSK10M	Left Side	0	23800	1	49	w/o	1	23.0	22.85	1.04	0.11	0.102	0.11
	LTE 17	QPSK10M	Right Side	0	23800	1	49	w/o	1	23.0	22.85	1.04	0.00	0.001	0.00
	LTE 17	QPSK10M	Top Side	20	23800	1	49	w/o	1	23.0	22.85	1.04	-0.05	0.05	0.05
	LTE 17	QPSK10M	Top Side	0	23800	1	49	w/	1	19.5	19.49	1.00	0.08	0.228	0.23
	LTE 17	QPSK10M	Bottom Side	0	23800	1	49	w/o	1	23.0	22.85	1.04	0.00	0.001	0.00
	LTE 17	QPSK10M	Rear Face	20	23800	25	25	w/o	1	22.0	21.79	1.05	0.04	0.095	0.10
	LTE 17	QPSK10M	Rear Face	0	23800	25	0	w/	1	19.5	19.40	1.02	-0.06	0.628	0.64
	LTE 17	QPSK10M	Left Side	0	23800	25	25	w/o	1	22.0	21.79	1.05	0.11	0.057	0.06
	LTE 17	QPSK10M	Right Side	0	23800	25	25	w/o	1	22.0	21.79	1.05	0.00	0.001	0.00
	LTE 17	QPSK10M	Top Side	20	23800	25	25	w/o	1	22.0	21.79	1.05	0.00	0.001	0.00
	LTE 17	QPSK10M	Top Side	0	23800	25	0	w/	1	19.5	19.40	1.02	-0.04	0.156	0.16
	LTE 17	QPSK10M	Bottom Side	0	23800	25	25	w/o	1	22.0	21.79	1.05	0.00	0.001	0.00
30	LTE 17	QPSK10M	Rear Face	0	23780	1	49	w/	1	19.5	19.42	1.02	-0.07	0.712	0.73
	LTE 17	QPSK10M	Rear Face	0	23790	1	49	w/	1	19.5	19.40	1.02	0.09	0.685	0.70
	LTE 17	QPSK10M	Rear Face	0	23780	1	49	w/	2	19.5	19.42	1.02	0.05	0.703	0.72
	LTE 17	QPSK10M	Rear Face	0	23780	1	49	w/	3	19.5	19.42	1.02	0.13	0.711	0.72
	LTE 26	QPSK15M	Rear Face	20	26765	1	37	w/o	1	23.0	22.94	1.01	0.01	0.13	0.13
31	LTE 26	QPSK15M	Rear Face	0	26765	1	37	w/	1	20.0	19.66	1.08	0.02	0.585	0.63
	LTE 26	QPSK15M	Left Side	0	26765	1	37	w/o	1	23.0	22.94	1.01	0.07	0.083	0.08
	LTE 26	QPSK15M	Right Side	0	26765	1	37	w/o	1	23.0	22.94	1.01	0.00	0.001	0.00
	LTE 26	QPSK15M	Top Side	20	26765	1	37	w/o	1	23.0	22.94	1.01	-0.05	0.062	0.06
	LTE 26	QPSK15M	Top Side	0	26765	1	37	w/	1	20.0	19.66	1.08	0.09	0.141	0.15
	LTE 26	QPSK15M	Bottom Side	0	26765	1	37	w/o	1	23.0	22.94	1.01	0.00	0.001	0.00
	LTE 26	QPSK15M	Rear Face	20	26765	36	19	w/o	1	22.0	21.98	1.00	0.04	0.106	0.11
	LTE 26	QPSK15M	Rear Face	0	26765	36	0	w/	1	20.0	19.54	1.11	0.10	0.566	0.63
	LTE 26	QPSK15M	Left Side	0	26765	36	19	w/o	1	22.0	21.98	1.00	-0.07	0.07	0.07
	LTE 26	QPSK15M	Right Side	0	26765	36	19	w/o	1	22.0	21.98	1.00	0.00	0.001	0.00
	LTE 26	QPSK15M	Top Side	20	26765	36	19	w/o	1	22.0	21.98	1.00	0.00	0.001	0.00
	LTE 26	QPSK15M	Top Side	0	26765	36	0	w/	1	20.0	19.54	1.11	0.02	0.137	0.15
	LTE 26	QPSK15M	Bottom Side	0	26765	36	19	w/o	1	22.0	21.98	1.00	0.00	0.001	0.00
	LTE 26	QPSK15M	Rear Face	0	26865	1	37	w/	1	20.0	19.57	1.10	0.08	0.566	0.62
	LTE 26	QPSK15M	Rear Face	0	26965	1	37	w/	1	20.0	19.63	1.09	-0.12	0.56	0.61
	LTE 26	QPSK15M	Rear Face	0	26765	1	37	w/	2	20.0	19.66	1.08	0.08	0.566	0.61
	LTE 26	QPSK15M	Rear Face	0	26765	1	37	w/	3	20.0	19.66	1.08	0.13	0.561	0.61

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
32	LTE 30	QPSK10M	Rear Face	20	27710	1	0	w/o	1	23.0	22.55	1.11	0.01	0.770	0.85
	LTE 30	QPSK10M	Rear Face	0	27710	1	0	w/	1	13.0	12.99	1.00	-0.01	0.684	0.69
	LTE 30	QPSK10M	Left Side	0	27710	1	0	w/o	1	23.0	22.55	1.11	0.13	0.197	0.22
	LTE 30	QPSK10M	Right Side	0	27710	1	0	w/o	1	23.0	22.55	1.11	0.00	0.001	0.00
	LTE 30	QPSK10M	Top Side	20	27710	1	0	w/o	1	23.0	22.55	1.11	0.05	0.245	0.27
	LTE 30	QPSK10M	Top Side	0	27710	1	0	w/	1	13.0	12.99	1.00	0.01	0.372	0.37
	LTE 30	QPSK10M	Bottom Side	0	27710	1	0	w/o	1	23.0	22.55	1.11	0.00	0.001	0.00
	LTE 30	QPSK10M	Rear Face	20	27710	25	25	w/o	1	22.0	21.62	1.09	0.06	0.719	0.78
	LTE 30	QPSK10M	Rear Face	0	27710	25	25	w/	1	13.0	12.93	1.02	-0.13	0.577	0.59
	LTE 30	QPSK10M	Left Side	0	27710	25	25	w/o	1	22.0	21.62	1.09	-0.05	0.173	0.19
	LTE 30	QPSK10M	Right Side	0	27710	25	25	w/o	1	22.0	21.62	1.09	0.00	0.001	0.00
	LTE 30	QPSK10M	Top Side	20	27710	25	25	w/o	1	22.0	21.62	1.09	-0.03	0.238	0.26
	LTE 30	QPSK10M	Top Side	0	27710	25	25	w/	1	13.0	12.93	1.02	0.09	0.313	0.32
	LTE 30	QPSK10M	Bottom Side	0	27710	25	25	w/o	1	22.0	21.62	1.09	0.00	0.001	0.00
	LTE 30	QPSK10M	Rear Face	0	27710	50	0	w/	1	22.0	21.69	1.07	-0.04	0.67	0.72
	LTE 30	QPSK10M	Rear Face	20	27710	1	0	w/o	2	23.0	22.55	1.11	0.05	0.708	0.79
	LTE 30	QPSK10M	Rear Face	20	27710	1	0	w/o	3	23.0	22.55	1.11	0.13	0.691	0.77
	LTE 38	QPSK20M	Rear Face	20	38150	1	99	w/o	1	23.0	22.68	1.08	0.03	0.170	0.18
	LTE 38	QPSK20M	Rear Face	0	38150	1	99	w/	1	16.0	15.69	1.07	0.04	1.04	1.12
	LTE 38	QPSK20M	Left Side	0	38150	1	99	w/o	1	23.0	22.68	1.08	-0.11	0.331	0.36
	LTE 38	QPSK20M	Right Side	0	38150	1	99	w/o	1	23.0	22.68	1.08	0.00	0.001	0.00
	LTE 38	QPSK20M	Top Side	20	38150	1	99	w/o	1	23.0	22.68	1.08	0.05	0.065	0.07
	LTE 38	QPSK20M	Top Side	0	38150	1	99	w/	1	16.0	15.69	1.07	-0.03	0.261	0.28
	LTE 38	QPSK20M	Bottom Side	0	38150	1	99	w/o	1	23.0	22.68	1.08	0.00	0.001	0.00
	LTE 38	QPSK20M	Rear Face	20	38150	50	0	w/o	1	22.0	21.73	1.06	0.05	0.157	0.17
	LTE 38	QPSK20M	Rear Face	0	38150	50	50	w/	1	16.0	15.58	1.10	-0.13	1.03	1.13
	LTE 38	QPSK20M	Left Side	0	38150	50	0	w/o	1	22.0	21.73	1.06	0.06	0.261	0.28
	LTE 38	QPSK20M	Right Side	0	38150	50	0	w/o	1	22.0	21.73	1.06	0.00	0.001	0.00
	LTE 38	QPSK20M	Top Side	20	38150	50	0	w/o	1	22.0	21.73	1.06	-0.03	0.060	0.06
	LTE 38	QPSK20M	Top Side	0	38150	50	50	w/	1	16.0	15.58	1.10	0.06	0.208	0.23
	LTE 38	QPSK20M	Bottom Side	0	38150	50	0	w/o	1	22.0	21.73	1.06	0.00	0.001	0.00
33	LTE 38	QPSK20M	Rear Face	0	37850	1	99	w/	1	16.0	15.68	1.08	0.03	1.09	1.17
	LTE 38	QPSK20M	Rear Face	0	38000	1	99	w/	1	16.0	15.67	1.08	-0.03	1.06	1.14
	LTE 38	QPSK20M	Rear Face	0	37850	50	50	w/	1	16.0	15.19	1.21	0.04	0.92	1.11
	LTE 38	QPSK20M	Rear Face	0	38000	50	50	w/	1	16.0	15.31	1.17	0.10	0.93	1.09
	LTE 38	QPSK20M	Rear Face	0	38150	100	0	w/	1	16.0	15.59	1.10	0.13	0.955	1.05
	LTE 38	QPSK20M	Rear Face	0	37850	1	99	w/	2	16.0	15.68	1.08	0.06	1.01	1.09
	LTE 38	QPSK20M	Rear Face	0	38000	1	99	w/	2	16.0	15.67	1.08	0.13	0.959	1.03
	LTE 38	QPSK20M	Rear Face	0	38150	1	99	w/	2	16.0	15.69	1.07	0.08	0.960	1.03
	LTE 38	QPSK20M	Rear Face	0	37850	1	99	w/	3	16.0	15.68	1.08	0.06	0.995	1.07
	LTE 38	QPSK20M	Rear Face	0	38000	1	99	w/	3	16.0	15.67	1.08	0.09	0.941	1.02
	LTE 38	QPSK20M	Rear Face	0	38150	1	99	w/	3	16.0	15.69	1.07	0.08	0.944	1.01
	LTE 38	QPSK20M	Rear Face	0	37850	1	99	w/	1	16.0	15.68	1.18	-0.03	1.03	1.11

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 41	QPSK20M	Rear Face	20	41055	1	0	w/o	1	23.0	22.56	1.11	0.05	0.196	0.22
	LTE 41	QPSK20M	Rear Face	0	41055	1	0	w/	1	14.5	14.26	1.06	0.01	0.672	0.71
	LTE 41	QPSK20M	Left Side	0	41055	1	0	w/o	1	23.0	22.56	1.11	-0.11	0.296	0.33
	LTE 41	QPSK20M	Right Side	0	41055	1	0	w/o	1	23.0	22.56	1.11	0.00	0.001	0.00
	LTE 41	QPSK20M	Top Side	20	41055	1	0	w/o	1	23.0	22.56	1.11	0.06	0.042	0.05
	LTE 41	QPSK20M	Top Side	0	41055	1	0	w/	1	14.5	14.26	1.06	0.03	0.132	0.14
	LTE 41	QPSK20M	Bottom Side	0	41055	1	0	w/o	1	23.0	22.56	1.11	0.00	0.001	0.00
	LTE 41	QPSK20M	Rear Face	20	41055	50	25	w/o	1	22.0	21.52	1.12	0.14	0.156	0.17
	LTE 41	QPSK20M	Rear Face	0	41055	50	0	w/	1	14.5	14.23	1.06	0.11	0.667	0.71
	LTE 41	QPSK20M	Left Side	0	41055	50	25	w/o	1	22.0	21.52	1.12	0.12	0.255	0.28
	LTE 41	QPSK20M	Right Side	0	41055	50	25	w/o	1	22.0	21.52	1.12	0.00	0.001	0.00
	LTE 41	QPSK20M	Top Side	20	41055	50	25	w/o	1	22.0	21.52	1.12	0.00	0.001	0.00
	LTE 41	QPSK20M	Top Side	0	41055	50	0	w/	1	14.5	14.23	1.06	-0.12	0.112	0.12
	LTE 41	QPSK20M	Bottom Side	0	41055	50	25	w/o	1	22.0	21.52	1.12	0.00	0.001	0.00
	LTE 41	QPSK20M	Rear Face	0	39750	1	0	w/	1	14.5	14.09	1.10	0.11	0.966	1.06
34	LTE 41	QPSK20M	Rear Face	0	40185	1	0	w/	1	14.5	14.20	1.07	-0.01	0.993	1.06
	LTE 41	QPSK20M	Rear Face	0	40620	1	0	w/	1	14.5	14.12	1.09	0.16	0.720	0.79
	LTE 41	QPSK20M	Rear Face	0	41490	1	0	w/	1	14.5	14.07	1.10	-0.15	0.602	0.66
	LTE 41	QPSK20M	Rear Face	0	39750	50	0	w/	1	14.5	14.08	1.10	0.05	0.888	0.98
	LTE 41	QPSK20M	Rear Face	0	40185	50	0	w/	1	14.5	14.17	1.08	0.08	0.844	0.91
	LTE 41	QPSK20M	Rear Face	0	40620	50	0	w/	1	14.5	14.09	1.10	-0.15	0.731	0.80
	LTE 41	QPSK20M	Rear Face	0	41490	50	0	w/	1	14.5	14.04	1.11	-0.03	0.613	0.68
	LTE 41	QPSK20M	Rear Face	0	41055	100	0	w/	1	14.5	14.21	1.07	0.07	0.732	0.78
	LTE 41	QPSK20M	Rear Face	0	40185	1	0	w/	2	14.5	14.20	1.07	0.13	0.932	1.00
	LTE 41	QPSK20M	Rear Face	0	39750	1	0	w/	1	14.5	14.09	1.10	0.03	0.925	1.02
	LTE 41	QPSK20M	Rear Face	0	40620	1	0	w/	2	14.5	14.12	1.09	0.06	0.922	1.01
	LTE 41	QPSK20M	Rear Face	0	41055	1	0	w/	2	14.5	14.26	1.06	0.08	0.918	0.97
	LTE 41	QPSK20M	Rear Face	0	41490	1	0	w/	2	14.5	14.07	1.10	0.01	0.911	1.01
	LTE 41	QPSK20M	Rear Face	0	40185	1	0	w/	3	14.5	14.20	1.07	0.02	0.922	0.99
	LTE 41	QPSK20M	Rear Face	0	39750	1	0	w/	1	14.5	14.09	1.10	0.03	0.903	0.99
	LTE 41	QPSK20M	Rear Face	0	40620	1	0	w/	3	14.5	14.12	1.09	0.05	0.913	1.00
	LTE 41	QPSK20M	Rear Face	0	41055	1	0	w/	3	14.5	14.26	1.06	0.01	0.914	0.97
	LTE 41	QPSK20M	Rear Face	0	41490	1	0	w/	3	14.5	14.07	1.10	0.09	0.903	1.00
	LTE 41	QPSK20M	Rear Face	0	40185	1	0	w/	1	14.5	14.20	1.07	-0.01	0.98	1.05

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB#	RB Offset	Power Reduction	EUT Config.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 66	QPSK20M	Rear Face	20	132322	1	0	w/o	1	23.0	22.89	1.03	-0.10	0.357	0.37
	LTE 66	QPSK20M	Rear Face	0	132322	1	0	w/	1	14.5	14.47	1.01	0.03	0.889	0.90
	LTE 66	QPSK20M	Left Side	0	132322	1	0	w/o	1	23.0	22.89	1.03	-0.11	0.166	0.17
	LTE 66	QPSK20M	Right Side	0	132322	1	0	w/o	1	23.0	22.89	1.03	0.00	0.001	0.00
	LTE 66	QPSK20M	Top Side	20	132322	1	0	w/o	1	23.0	22.89	1.03	0.02	0.062	0.06
	LTE 66	QPSK20M	Top Side	0	132322	1	0	w/	1	14.5	14.47	1.01	0.08	0.096	0.10
	LTE 66	QPSK20M	Bottom Side	0	132322	1	0	w/o	1	23.0	22.89	1.03	0.00	0.001	0.00
	LTE 66	QPSK20M	Rear Face	20	132322	50	0	w/o	1	22.0	21.82	1.04	0.05	0.277	0.29
	LTE 66	QPSK20M	Rear Face	0	132322	50	0	w/	1	14.5	14.37	1.03	-0.10	0.868	0.89
	LTE 66	QPSK20M	Left Side	0	132322	50	0	w/o	1	22.0	21.82	1.04	0.06	0.082	0.09
	LTE 66	QPSK20M	Right Side	0	132322	50	0	w/o	1	22.0	21.82	1.04	0.00	0.001	0.00
	LTE 66	QPSK20M	Top Side	20	132322	50	0	w/o	1	22.0	21.82	1.04	0.11	0.058	0.06
	LTE 66	QPSK20M	Top Side	0	132322	50	0	w/	1	14.5	14.47	1.01	-0.03	0.092	0.09
	LTE 66	QPSK20M	Bottom Side	0	132322	50	0	w/o	1	22.0	21.82	1.04	0.00	0.001	0.00
35	LTE 66	QPSK20M	Rear Face	0	132072	1	0	w/	1	14.5	14.40	1.02	0.16	0.933	0.95
	LTE 66	QPSK20M	Rear Face	0	132572	1	0	w/	1	14.5	14.25	1.06	0.08	0.868	0.92
	LTE 66	QPSK20M	Rear Face	0	132072	50	0	w/	1	14.5	14.30	1.05	-0.13	0.881	0.92
	LTE 66	QPSK20M	Rear Face	0	132572	50	0	w/	1	14.5	14.15	1.08	0.08	0.869	0.94
	LTE 66	QPSK20M	Rear Face	0	132322	100	0	w/	1	14.5	14.38	1.03	0.04	0.907	0.93
	LTE 66	QPSK20M	Rear Face	0	132072	1	0	w/	2	14.5	14.40	1.02	0.06	0.908	0.93
	LTE 66	QPSK20M	Rear Face	0	132322	1	0	w/	2	14.5	14.47	1.01	0.12	0.901	0.91
	LTE 66	QPSK20M	Rear Face	0	132572	1	0	w/	2	14.5	14.25	1.06	0.05	0.898	0.95
	LTE 66	QPSK20M	Rear Face	0	132072	1	0	w/	3	14.5	14.40	1.02	0.01	0.906	0.93
	LTE 66	QPSK20M	Rear Face	0	132322	1	0	w/	3	14.5	14.47	1.01	0.09	0.895	0.90
	LTE 66	QPSK20M	Rear Face	0	132572	1	0	w/	3	14.5	14.25	1.06	0.05	0.889	0.94
	LTE 66	QPSK20M	Rear Face	0	132072	1	0	w/	1	14.5	14.40	1.02	-0.10	0.929	0.95

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	EUT Config.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WLAN2.4G	802.11b	Rear Face	0	6	1	Ant 0	17.0	16.96	1.01	-0.11	0.953	0.96
	WLAN2.4G	802.11b	Left Side	0	6	1	Ant 0	17.0	16.96	1.01	0.00	0.001	0.00
	WLAN2.4G	802.11b	Right Side	0	6	1	Ant 0	17.0	16.96	1.01	0.05	0.625	0.63
	WLAN2.4G	802.11b	Top Side	0	6	1	Ant 0	17.0	16.96	1.01	0.11	0.093	0.09
	WLAN2.4G	802.11b	Bottom Side	0	6	1	Ant 0	17.0	16.96	1.01	0.00	0.001	0.00
	WLAN2.4G	802.11b	Rear Face	0	6	1	Ant 1	13.5	13.49	1.00	0.12	1.02	1.02
	WLAN2.4G	802.11b	Left Side	0	6	1	Ant 1	13.5	13.49	1.00	0.00	0.001	0.00
	WLAN2.4G	802.11b	Bottom Side	0	6	1	Ant 1	13.5	13.49	1.00	0.11	0.544	0.55
36	WLAN2.4G	802.11n HT20	Rear Face	0	6	1	Ant 0+1	17.0	16.93	1.02	0.11	1.01	1.03
	WLAN2.4G	802.11n HT20	Left Side	0	6	1	Ant 0+1	17.0	16.93	1.02	0.00	0.001	0.00
	WLAN2.4G	802.11n HT20	Right Side	0	6	1	Ant 0+1	17.0	16.93	1.02	0.12	0.314	0.32
	WLAN2.4G	802.11n HT20	Top Side	0	6	1	Ant 0+1	17.0	16.93	1.02	0.00	0.001	0.00
	WLAN2.4G	802.11n HT20	Bottom Side	0	6	1	Ant 0+1	17.0	16.93	1.02	0.11	0.562	0.57
	WLAN2.4G	802.11b	Rear Face	0	11	1	Ant 0	17.0	16.92	1.02	0.05	0.903	0.92
	WLAN2.4G	802.11b	Rear Face	0	11	1	Ant 1	13.5	13.47	1.01	0.02	0.995	1.00
	WLAN2.4G	802.11n HT20	Rear Face	0	1	1	Ant 0+1	14.0	13.97	1.01	0.12	0.613	0.62
	WLAN2.4G	802.11n HT20	Rear Face	0	11	1	Ant 0+1	14.0	13.97	1.01	0.05	0.596	0.60
	WLAN2.4G	802.11n HT20	Rear Face	0	12	1	Ant 0+1	7.0	6.97	1.01	0.11	0.106	0.11
	WLAN2.4G	802.11n HT20	Rear Face	0	13	1	Ant 0+1	-6.5	-6.54	1.01	0.00	0.001	0.00
	WLAN2.4G	802.11n HT20	Rear Face	0	6	2	Ant 0+1	17.0	16.93	1.02	0.05	0.913	0.93
	WLAN2.4G	802.11n HT20	Rear Face	0	1	2	Ant 0+1	14.0	13.97	1.01	0.01	0.654	0.66
	WLAN2.4G	802.11n HT20	Rear Face	0	11	2	Ant 0+1	14.0	13.97	1.01	0.09	0.565	0.57
	WLAN2.4G	802.11n HT20	Rear Face	0	6	3	Ant 0+1	17.0	16.93	1.02	-0.13	0.911	0.93
	WLAN2.4G	802.11n HT20	Rear Face	0	1	3	Ant 0+1	14.0	13.97	1.01	0.08	0.664	0.67
	WLAN2.4G	802.11n HT20	Rear Face	0	11	3	Ant 0+1	14.0	13.97	1.01	0.04	0.551	0.55
	WLAN2.4G	802.11b	Rear Face	0	6	1	Ant 1	13.5	13.49	1.00	0.02	0.998	1.00

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	EUT Config.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
37	WLAN5G	802.11ac VHT80	Rear Face	0	58	1	Ant 0	8.5	8.43	1.02	-0.11	0.957	0.97
	WLAN5G	802.11ac VHT80	Left Side	0	58	1	Ant 0	8.5	8.43	1.02	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Right Side	0	58	1	Ant 0	8.5	8.43	1.02	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Top Side	0	58	1	Ant 0	8.5	8.43	1.02	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Bottom Side	0	58	1	Ant 0	8.5	8.43	1.02	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Rear Face	0	58	1	Ant 1	7.5	7.47	1.01	0.11	0.546	0.55
	WLAN5G	802.11ac VHT80	Bottom Side	0	58	1	Ant 1	7.5	7.47	1.01	0.11	0.347	0.35
	WLAN5G	802.11ac VHT80	Rear Face	0	58	1	Ant 0+1	11.5	11.39	1.03	0.11	0.88	0.90
	WLAN5G	802.11ac VHT80	Right Side	0	58	1	Ant 0+1	11.5	11.39	1.03	0.12	0.126	0.13
	WLAN5G	802.11ac VHT80	Top Side	0	58	1	Ant 0+1	11.5	11.39	1.03	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Bottom Side	0	58	1	Ant 0+1	11.5	11.39	1.03	0.05	0.459	0.47
	WLAN5G	802.11ac VHT80	Rear Face	0	58	2	Ant 0	8.5	8.43	1.02	0.08	0.911	0.93
	WLAN5G	802.11ac VHT80	Rear Face	0	58	3	Ant 0	8.5	8.43	1.02	0.13	0.909	0.92
	WLAN5G	802.11ac VHT80	Rear Face	0	58	1	Ant 0	8.5	8.43	1.02	0.02	0.897	0.91
	WLAN5G	802.11ac VHT80	Rear Face	0	138	1	Ant 0	6.0	5.96	1.01	-0.17	0.811	0.82
	WLAN5G	802.11ac VHT80	Left Side	0	138	1	Ant 0	6.0	5.96	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Right Side	0	138	1	Ant 0	6.0	5.96	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Top Side	0	138	1	Ant 0	6.0	5.96	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Bottom Side	0	138	1	Ant 0	6.0	5.96	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Rear Face	0	138	1	Ant 1	7.5	7.47	1.01	0.08	0.708	0.71
	WLAN5G	802.11ac VHT80	Bottom Side	0	138	1	Ant 1	7.5	7.47	1.01	0.11	0.214	0.22
	WLAN5G	802.11ac VHT80	Rear Face	0	138	1	Ant 0+1	11.5	11.47	1.01	0.11	0.88	0.89
	WLAN5G	802.11ac VHT80	Right Side	0	138	1	Ant 0+1	11.5	11.47	1.01	0.04	0.114	0.11
	WLAN5G	802.11ac VHT80	Top Side	0	138	1	Ant 0+1	11.5	11.47	1.01	0.11	0.001	0.00
	WLAN5G	802.11ac VHT80	Bottom Side	0	138	1	Ant 0+1	11.5	11.47	1.01	0.15	0.31	0.31
	WLAN5G	802.11ac VHT80	Rear Face	0	106	1	Ant 0	6.0	5.92	1.02	0.05	0.29	0.30
	WLAN5G	802.11ac VHT80	Rear Face	0	122	1	Ant 0	6.0	5.95	1.01	0.04	0.411	0.42
38	WLAN5G	802.11ac VHT80	Rear Face	0	106	1	Ant 0+1	11.5	11.45	1.01	0.11	0.915	0.93
	WLAN5G	802.11ac VHT80	Rear Face	0	122	1	Ant 0+1	11.5	11.40	1.02	0.12	0.91	0.93
	WLAN5G	802.11ac VHT80	Rear Face	0	106	2	Ant 0+1	11.5	11.45	1.01	0.14	0.783	0.79
	WLAN5G	802.11ac VHT80	Rear Face	0	106	3	Ant 0+1	11.5	11.45	1.01	0.14	0.779	0.79
	WLAN5G	802.11ac VHT80	Rear Face	0	106	1	Ant 0+1	11.5	11.45	1.01	0.05	0.911	0.92
	WLAN5G	802.11ac VHT80	Rear Face	0	155	1	Ant 0	6.0	5.97	1.01	-0.11	0.536	0.54
	WLAN5G	802.11ac VHT80	Left Side	0	155	1	Ant 0	6.0	5.97	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Right Side	0	155	1	Ant 0	6.0	5.97	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Top Side	0	155	1	Ant 0	6.0	5.97	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Bottom Side	0	155	1	Ant 0	6.0	5.97	1.01	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Rear Face	0	155	1	Ant 1	8.0	7.95	1.01	0.18	0.904	0.91
	WLAN5G	802.11ac VHT80	Bottom Side	0	155	1	Ant 1	8.0	7.95	1.01	0.11	0.326	0.33
39	WLAN5G	802.11ac VHT80	Rear Face	0	155	1	Ant 0+1	12.0	11.73	1.06	0.15	0.868	0.92
	WLAN5G	802.11ac VHT80	Right Side	0	155	1	Ant 0+1	12.0	11.73	1.06	0.14	0.107	0.11
	WLAN5G	802.11ac VHT80	Top Side	0	155	1	Ant 0+1	12.0	11.73	1.06	0.00	0.001	0.00
	WLAN5G	802.11ac VHT80	Bottom Side	0	155	1	Ant 0+1	12.0	11.73	1.06	0.14	0.273	0.29
	WLAN5G	802.11ac VHT80	Rear Face	0	155	2	Ant 0+1	12.0	11.73	1.06	0.19	0.832	0.89
	WLAN5G	802.11ac VHT80	Rear Face	0	155	3	Ant 0+1	12.0	11.73	1.06	0.12	0.811	0.86
	WLAN5G	802.11ac VHT80	Rear Face	0	155	1	Ant 0+1	12.0	11.73	1.06	0.11	0.865	0.92

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	EUT Config.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
40	BT	BR/EDR	Rear Face	0	39	1	Ant 1	13.0	12.82	1.04	0.02	0.351	0.37
	BT	BR/EDR	Left Side	0	39	1	Ant 1	13.0	12.82	1.04	0.00	0.001	0.00
	BT	BR/EDR	Right Side	0	39	1	Ant 1	13.0	12.82	1.04	0.00	0.001	0.00
	BT	BR/EDR	Top Side	0	39	1	Ant 1	13.0	12.82	1.04	0.00	0.001	0.00
	BT	BR/EDR	Bottom Side	0	39	1	Ant 1	13.0	12.82	1.04	-0.09	0.194	0.20
	BT	BR/EDR	Rear Face	0	0	1	Ant 1	13.0	12.70	1.07	0.01	0.331	0.35
	BT	BR/EDR	Rear Face	0	78	1	Ant 1	13.0	12.65	1.08	-0.03	0.321	0.35
	BT	BR/EDR	Rear Face	0	39	2	Ant 1	13.0	12.82	1.04	0.06	0.319	0.33
	BT	BR/EDR	Rear Face	0	39	3	Ant 1	13.0	12.82	1.04	0.01	0.311	0.32

Note: The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

FCC SAR Test Report

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
LTE 5	QPSK10M	Bottom	20525	0.84	0.82	1.02	N/A	N/A	N/A	N/A
LTE 12	QPSK10M	Bottom	23095	0.886	0.878	1.01	N/A	N/A	N/A	N/A
LTE 13	QPSK10M	Bottom	23230	0.934	0.931	1.00	N/A	N/A	N/A	N/A
LTE 17	QPSK10M	Bottom	23800	0.847	0.843	1.00	N/A	N/A	N/A	N/A
LTE 26	QPSK15M	Bottom	26865	0.819	0.813	1.01	N/A	N/A	N/A	N/A
LTE 30	QPSK10M	Bottom	27710	0.807	0.801	1.01	N/A	N/A	N/A	N/A
WLAN2.4G	802.11b	Bottom	6	1.11	1.08	1.03	N/A	N/A	N/A	N/A
WLAN5G	802.11n HT40	Bottom	54	1.09	1.05	1.04	N/A	N/A	N/A	N/A
WLAN5G	802.11n HT40	Bottom	126	1.15	1.11	1.04	N/A	N/A	N/A	N/A
WLAN5G	802.11n HT40	Bottom	151	1.07	1.03	1.04	N/A	N/A	N/A	N/A
WCDMA II	RMC 12.2K	Rear Face	9538	1.13	1.11	1.02	N/A	N/A	N/A	N/A
WCDMA IV	RMC 12.2K	Rear Face	1312	0.857	0.855	1.00	N/A	N/A	N/A	N/A
LTE 2	QPSK20M	Rear Face	19100	1.07	1.05	1.02	N/A	N/A	N/A	N/A
LTE 4	QPSK20M	Rear Face	20300	1.18	1.13	1.04	N/A	N/A	N/A	N/A
LTE 7	QPSK20M	Rear Face	20850	1.11	1.05	1.06	N/A	N/A	N/A	N/A
LTE 38	QPSK20M	Rear Face	37850	1.09	1.03	1.06	N/A	N/A	N/A	N/A
LTE 41	QPSK20M	Rear Face	40185	0.993	0.980	1.01	N/A	N/A	N/A	N/A
LTE 66	QPSK20M	Rear Face	132072	0.933	0.929	1.00	N/A	N/A	N/A	N/A
WLAN2.4G	802.11b	Rear Face	6	1.02	0.998	1.02	N/A	N/A	N/A	N/A
WLAN5G	802.11ac VHT80	Rear Face	58	0.957	0.897	1.07	N/A	N/A	N/A	N/A
WLAN5G	802.11ac VHT80	Rear Face	106	0.915	0.911	1.00	N/A	N/A	N/A	N/A
WLAN5G	802.11ac VHT80	Rear Face	155	0.868	0.865	1.00	N/A	N/A	N/A	N/A

4.7.4 Simultaneous Multi-band Transmission Evaluation

<Possibilities of Simultaneous Transmission>

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
1	WCDMA + WLAN 2.4G	Yes
2	WCDMA + WLAN 5G	Yes
3	WCDMA + BT	Yes
4	LTE + WLAN 2.4G	Yes
5	LTE + WLAN 5G	Yes
6	LTE + BT	Yes
7	WiFi 2.4GHz Ant0 + BT Ant1	Yes
8	WiFi 5GHz Ant0 + BT Ant1	Yes
9	WWAN + WiFi2.4GHz Ant0+ BT Ant1	Yes
10	WWAN + WiFi5GHz Ant0 + BT Ant1	Yes

Note :

1. The WLAN 2.4G and WLAN 5G cannot transmit simultaneously.

FCC SAR Test Report

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

Laptop PC Mode

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	WCDMA II + WLAN (DTS)	Body	Bottom Side	0.46	1.16	-	1.62	Analyzed as below
2	WCDMA II + WLAN (NII)	Body	Bottom Side	0.46	1.16	-	1.62	Analyzed as below
3	WCDMA II + BT (DSS)	Body	Bottom Side	0.46	0.03	-	0.49	Σ SAR < 1.6, Not required
4	WCDMA II + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.46	1.16	0.03	1.65	Analyzed as below
5	WCDMA II + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.46	0.77	0.03	1.26	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
6	WCDMA IV + WLAN (DTS)	Body	Bottom Side	0.60	1.16	-	1.76	Analyzed as below
7	WCDMA IV + WLAN (NII)	Body	Bottom Side	0.60	1.16	-	1.76	Analyzed as below
8	WCDMA IV + BT (DSS)	Body	Bottom Side	0.60	0.03	-	0.63	Σ SAR < 1.6, Not required
9	WCDMA IV + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.60	1.16	0.03	1.79	Analyzed as below
10	WCDMA IV + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.60	0.77	0.03	1.40	Σ SAR < 1.6, Not required

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
11	WCDMA V + WLAN (DTS)	Body	Bottom Side	0.74	1.16	-	1.90	Analyzed as below
12	WCDMA V + WLAN (NII)	Body	Bottom Side	0.74	1.16	-	1.90	Analyzed as below
13	WCDMA V + BT (DSS)	Body	Bottom Side	0.74	0.03	-	0.77	Σ SAR < 1.6, Not required
14	WCDMA V + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.74	1.16	0.03	1.93	Analyzed as below
15	WCDMA V + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.74	0.77	0.03	1.54	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
16	LTE 2 + WLAN (DTS)	Body	Bottom Side	0.42	1.16	-	1.58	Σ SAR < 1.6, Not required
17	LTE 2 + WLAN (NII)	Body	Bottom Side	0.42	1.16	-	1.58	Σ SAR < 1.6, Not required
18	LTE 2 + BT (DSS)	Body	Bottom Side	0.42	0.03	-	0.45	Σ SAR < 1.6, Not required
19	LTE 2 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.42	1.16	0.03	1.61	Analyzed as below
20	LTE 2 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.42	0.77	0.03	1.22	Σ SAR < 1.6, Not required

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
21	LTE 4 + WLAN (DTS)	Body	Bottom Side	0.60	1.16	-	1.76	Analyzed as below
22	LTE 4 + WLAN (NII)	Body	Bottom Side	0.60	1.16	-	1.76	Analyzed as below
23	LTE 4 + BT (DSS)	Body	Bottom Side	0.60	0.03	-	0.63	Σ SAR < 1.6, Not required
24	LTE 4 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.60	1.16	0.03	1.79	Analyzed as below
25	LTE 4 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.60	0.77	0.03	1.40	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
26	LTE 5 + WLAN (DTS)	Body	Bottom Side	0.88	1.16	-	2.04	Analyzed as below
27	LTE 5 + WLAN (NII)	Body	Bottom Side	0.88	1.16	-	2.04	Analyzed as below
28	LTE 5 + BT (DSS)	Body	Bottom Side	0.88	0.03	-	0.91	Σ SAR < 1.6, Not required
29	LTE 5 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.88	1.16	0.03	2.07	Analyzed as below
30	LTE 5 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.88	0.77	0.03	1.68	Analyzed as below

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
31	LTE 7 + WLAN (DTS)	Body	Bottom Side	0.62	1.16	-	1.78	Analyzed as below
32	LTE 7 + WLAN (NII)	Body	Bottom Side	0.62	1.16	-	1.78	Analyzed as below
33	LTE 7 + BT (DSS)	Body	Bottom Side	0.62	0.03	-	0.65	Σ SAR < 1.6, Not required
34	LTE 7 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.62	1.16	0.03	1.81	Analyzed as below
35	LTE 7 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.62	0.77	0.03	1.42	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
36	LTE 12 + WLAN (DTS)	Body	Bottom Side	0.93	1.16	-	2.09	Analyzed as below
37	LTE 12 + WLAN (NII)	Body	Bottom Side	0.93	1.16	-	2.09	Analyzed as below
38	LTE 12 + BT (DSS)	Body	Bottom Side	0.93	0.03	-	0.96	Σ SAR < 1.6, Not required
39	LTE 12 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.93	1.16	0.03	2.12	Analyzed as below
40	LTE 12 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.93	0.77	0.03	1.73	Analyzed as below

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
41	LTE 13 + WLAN (DTS)	Body	Bottom Side	1.01	1.16	-	2.17	Analyzed as below
42	LTE 13 + WLAN (NII)	Body	Bottom Side	1.01	1.16	-	2.17	Analyzed as below
43	LTE 13 + BT (DSS)	Body	Bottom Side	1.01	0.03	-	1.04	Σ SAR < 1.6, Not required
44	LTE 13 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	1.01	1.16	0.03	2.20	Analyzed as below
45	LTE 13 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	1.01	0.77	0.03	1.81	Analyzed as below

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
46	LTE 17 + WLAN (DTS)	Body	Bottom Side	0.85	1.16	-	2.01	Analyzed as below
47	LTE 17 + WLAN (NII)	Body	Bottom Side	0.85	1.16	-	2.01	Analyzed as below
48	LTE 17 + BT (DSS)	Body	Bottom Side	0.85	0.03	-	0.88	Σ SAR < 1.6, Not required
49	LTE 17 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.85	1.16	0.03	2.04	Analyzed as below
50	LTE 17 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.85	0.77	0.03	1.65	Analyzed as below

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
51	LTE 26 + WLAN (DTS)	Body	Bottom Side	0.90	1.16	-	2.06	Analyzed as below
52	LTE 26 + WLAN (NII)	Body	Bottom Side	0.90	1.16	-	2.06	Analyzed as below
53	LTE 26 + BT (DSS)	Body	Bottom Side	0.90	0.03	-	0.93	Σ SAR < 1.6, Not required
54	LTE 26 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.90	1.16	0.03	2.09	Analyzed as below
55	LTE 26 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.90	0.77	0.03	1.70	Analyzed as below

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
56	LTE 30 + WLAN (DTS)	Body	Bottom Side	0.81	1.16	-	1.97	Analyzed as below
57	LTE 30 + WLAN (NII)	Body	Bottom Side	0.81	1.16	-	1.97	Analyzed as below
58	LTE 30 + BT (DSS)	Body	Bottom Side	0.81	0.03	-	0.84	Σ SAR < 1.6, Not required
59	LTE 30 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.81	1.16	0.03	2.00	Analyzed as below
60	LTE 30 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.81	0.77	0.03	1.61	Analyzed as below

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
61	LTE 38 + WLAN (DTS)	Body	Bottom Side	0.76	1.16	-	1.92	Analyzed as below
62	LTE 38 + WLAN (NII)	Body	Bottom Side	0.76	1.16	-	1.92	Analyzed as below
63	LTE 38 + BT (DSS)	Body	Bottom Side	0.76	0.03	-	0.79	Σ SAR < 1.6, Not required
64	LTE 38 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.76	1.16	0.03	1.95	Analyzed as below
65	LTE 38 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.76	0.77	0.03	1.56	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
66	LTE 41 + WLAN (DTS)	Body	Bottom Side	0.62	1.16	-	1.78	Analyzed as below
67	LTE 41 + WLAN (NII)	Body	Bottom Side	0.62	1.16	-	1.78	Analyzed as below
68	LTE 41 + BT (DSS)	Body	Bottom Side	0.62	0.03	-	0.65	Σ SAR < 1.6, Not required
69	LTE 41 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.62	1.16	0.03	1.81	Analyzed as below
70	LTE 41 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.62	0.77	0.03	1.42	Σ SAR < 1.6, Not required

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
71	LTE 66 + WLAN (DTS)	Body	Bottom Side	0.58	1.16	-	1.74	Analyzed as below
72	LTE 66 + WLAN (NII)	Body	Bottom Side	0.58	1.16	-	1.74	Analyzed as below
73	LTE 66 + BT (DSS)	Body	Bottom Side	0.58	0.03	-	0.61	Σ SAR < 1.6, Not required
74	LTE 66 + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.58	1.16	0.03	1.77	Analyzed as below
75	LTE 66 + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Bottom Side	0.58	0.77	0.03	1.38	Σ SAR < 1.6, Not required

FCC SAR Test Report

Tablet PC Mode

No.	Conditions (SAR1+SAR2+SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	WCDMA II + WLAN (DTS)	Body	Rear Face	1.16	1.03	-	2.19	Analyzed as below
			Left Side	0.20	0.00	-	0.20	Σ SAR < 1.6, Not required
			Right Side	0.00	0.63	-	0.63	Σ SAR < 1.6, Not required
			Top Side	0.12	0.09	-	0.21	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.57	-	0.57	Σ SAR < 1.6, Not required
2	WCDMA II + WLAN (NII)	Body	Rear Face	1.16	0.97	-	2.13	Analyzed as below
			Left Side	0.20	0.00	-	0.20	Σ SAR < 1.6, Not required
			Right Side	0.00	0.15	-	0.15	Σ SAR < 1.6, Not required
			Top Side	0.12	0.00	-	0.12	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.47	-	0.47	Σ SAR < 1.6, Not required
3	WCDMA II + BT (DSS)	Body	Rear Face	1.16	0.37	-	1.53	Σ SAR < 1.6, Not required
			Left Side	0.20	0.00	-	0.20	Σ SAR < 1.6, Not required
			Right Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Top Side	0.12	0.00	-	0.12	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.20	-	0.20	Σ SAR < 1.6, Not required
4	WCDMA II + WLAN (DTS) Ant0 + BT (DSS) Ant1	Body	Rear Face	1.16	0.96	0.37	2.49	Analyzed as below
			Left Side	0.20	0.00	0.00	0.20	Σ SAR < 1.6, Not required
			Right Side	0.00	0.63	0.00	0.63	Σ SAR < 1.6, Not required
			Top Side	0.12	0.09	0.00	0.21	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	0.20	0.20	Σ SAR < 1.6, Not required
5	WCDMA II + WLAN (NII) Ant0 + BT (DSS) Ant1	Body	Rear Face	1.16	0.97	0.37	2.50	Analyzed as below
			Left Side	0.20	0.00	0.00	0.20	Σ SAR < 1.6, Not required
			Right Side	0.00	0.15	0.00	0.15	Σ SAR < 1.6, Not required
			Top Side	0.12	0.00	0.00	0.12	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	0.20	0.20	Σ SAR < 1.6, Not required