FCC ID: ZMOL831  Section 15.212 Modular Transmitters  Request for Modular Approval Request for Limited Modular Approval	
Request for Modular Approval Request for Limited Modular Approval	
Requirements EUT Conditions	Comply (Y/N)
Single Modular Approval Requirements	
1 The radio elements of the modular The radio portion of this module has	Y
transmitter must have their own been shielded, please see exhibition	
shielding. The physical crystal and external photos.	
tuning capacitors may be located	
external to the shielded radio elements.	
2 The modular transmitter must have Buffered data inputs stage has been	Y
buffered modulation/data inputs (if such integrated in chip PMB5740+PMB9920	
inputs are provided) to ensure that the	
module will comply with Part 15	
requirements under conditions of	
excessive data rates or over-modulation.	
The modular transmitter must have its  The part number of the power regulator	Y
own power supply regulation.  is RF8081. Please see the schem.pdf	
4 The modular transmitter must comply The requirements of antenna connector	Y
with the antenna and transmission and spurious emission have been	
system requirements of Sections 15.203, fulfilled, please refer to the Test Report	
15.204(b) and 15.204(c). The antenna exhibition.	
must either be permanently attached or	
employ a "unique" antenna coupler (at	
all connections between the module and	
the antenna, including the cable). The	
"professional installation" provision of	
Section 15.203 is not applicable to	
modules but can apply to limited	
modular approvals under paragraph (b)	
of this section.	*7
The modular transmitter must be tested Please refer to the Setup Photo	Y
in a stand-alone configuration, <i>i.e.</i> , the exhibition for the stand-alone test	
module must not be inside another configuration.	
device during testing for compliance	
with Part 15 requirements. Unless the transmitter module will be battery	
powered, it must comply with the AC	
line conducted requirements found in	
Section 15.207. AC or DC power lines	
and data input/output lines connected to	
the module must not contain ferrites,	
unless they will be marketed with the	
module (see Section 15.27(a)). The	
length of these lines shall be the length	
typical of actual use or, if that length is	
unknown, at least 10 centimeters to	
insure that there is no coupling between	
the case of the module and supporting	

	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	The GSM/GPRS/EGPRS+WCDMA+	Y
	equipped with either a permanently	LTE Module will be labeled with its	
	affixed label or must be capable of	own FCC ID, and the instruction on the	
	electronically displaying its FCC	labeling rule of the end product has been	
	identification number.	stated in the User Manual of this	
	(A) If using a permanently affixed label, the	module. Please refer to the Label and	
	modular transmitter must be labeled with its own	User Manual exhibition.	
	FCC identification number, and, if the FCC identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains		
	Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate instructions along with the module which explain		
	this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following: "Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same		
	meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for equipment authorization.		
7	The modular transmitter must comply	The required FCC rule has been fulfilled	Y
_ ′	with any specific rules or operating	and all the instructions for maintaining	
	requirements that	compliance have been clearly stated in	
	ordinarily apply to a complete	the User Manual.	
	transmitter and the manufacturer must	THE COOL TRANSMIT	
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		
	approation for equipment authorization.		

8	The modular transmitter must comply	Please refer exhibition RF Exposure for	Y
	with any applicable RF exposure	the compliance of MPE RF exposure	
	requirements in its final configuration.	rule.	

Tao Zhu

Tao Zhu