

Add Wi-Fi Devices to the Network

Do these steps for all Wi-Fi devices that you want connect-
ed to the Wireless Extender's Wi-Fi network.

- Push and hold the WPS button on the back of the Wireless Extender until its Link Quality light turns red.
- The WPS button on your gateway or modem's network front of the Extender will turn red.
- Push the WPS button on your Wi-Fi device for two seconds.
- Push the WPS button on your Wi-Fi device.



Devices to the Network.

After the Extender is ready, you can add new Wi-Fi devices to it as described in **Add Wi-Fi**.

Manage and Secure Your Extender

The Extender has a set of web management tools for monitoring and controlling the Extender.

- Connect a computer to one of the Extender's LAN ports with an Ethernet wire.
- Open a web browser on the computer.
- Type 192.168.1.253 in the browser address bar.
- Type your user name and password in the login fields. The Extender is set with an account name of **admin** and a password of **admin** when manufactured.
- Click or tap the word **Password** below the **New Password** and **Confirm Password** lines. You can use the management tools to set up your network, control the Wi-Fi channels, and change your management tools password.

Change Management Tools Password

Do not make it easy for someone else to control your network! You should change the password you use to open the web interface to change or control your Wi-Fi network.

- turning the Extender off and on again, while keeping all your settings.
- erasing all your settings.
- erasing all your settings so that you can begin much easier for someone else to change or control your Wi-Fi network.
- pushing the Extender up again.
- restarting the Extender power must be on to reset or erase in.
- can be pushed down with the tip of a pen or pencil.
- The Extender switch is protected by the plastic case, and have not changed it in the **Current Password** line.
- Type the password you are using now (admin if you have not changed it) in the **Current Password** line.
- Find **System** in the left column of the management tools page. Click or tap the word **Password** below **System** and the password tools appear.
- Type your user name and password in the login fields. The Extender is set with an account name of **admin** and a password of **admin** when manufactured.

Reset or Erase the Wireless Extender

The Extender has two functions:

- turning the Extender off and on again, while keeping all your settings.
- erasing all your settings.
- erasing all your settings so that you can begin much easier for someone else to change or control your Wi-Fi network.
- pushing the Extender up again.
- restarting the Extender power must be on to reset or erase in.
- can be pushed down with the tip of a pen or pencil.
- The Extender switch is protected by the plastic case, and have not changed it in the **Current Password** line.
- Type the password you are using now (admin if you have not changed it) in the **Current Password** line.
- Find **System** in the left column of the management tools page. Click or tap the word **Password** below **System** and the password tools appear.
- Type your user name and password in the login fields. The Extender is set with an account name of **admin** and a password of **admin** when manufactured.

Set Up as a REPEATER

Wireless Extender. Connect the Power Supply to a power outlet near your internet gateway or network hub. Extend the On/Off switch to turn the light to flash, then stay on blue. Push the WPS button on the Extender. The light below means it is waiting for other Wi-Fi devices. The light stays yellow below. The light on the front of the Extender is yellow below. The light on the front of the Extender is green. Push the WPS button on your internet gateway or Wi-Fi router. After the Extender is in a good location, you can add new Wi-Fi devices to it as described in **Add Wi-Fi**.

Devices to the Network.

After the Extender is in a good location, you can add new Wi-Fi devices to it as described in **Add Wi-Fi**.

Set Up as an ACCESS POINT

Did the Gateway link light keep flashing yellow? The Extender did not join your gateway or modem's network. Try restarting the internet gateway or modem's network. Did the Gateway link light stay on green? The Extender connected to your internet gateway or modem's network. Try restarting the internet gateway or modem's network.

Devices to the Network.

After the Extender is in a good location, you can add new Wi-Fi devices to it as described in **Add Wi-Fi**.

Set Up as an ACCESS POINT

1. Connect the Power from the cord from the Power Supply to the **POWER +12 V DC** socket on the back of the Extender. Extend the On/Off switch to turn the light to flash, then stay on blue. Push the WPS button on the Extender. The light below means it is waiting for other Wi-Fi devices. The light stays yellow below. The light on the front of the Extender is yellow below. The light on the front of the Extender is green. Push the WPS button on your internet gateway or Wi-Fi router.

Devices to the Network.

After the Extender is in a good location, you can add new Wi-Fi devices to it as described in **Add Wi-Fi**.

Set Up as an ACCESS POINT

1. Connect the Power from the cord from the Power Supply to the **POWER +12 V DC** socket on the back of the Extender. Extend the On/Off switch to turn the light to flash, then stay on blue. Push the WPS button on the Extender. The light below means it is waiting for other Wi-Fi devices. The light stays yellow below. The light on the front of the Extender is yellow below. The light on the front of the Extender is green. Push the WPS button on your internet gateway or Wi-Fi router.

Devices to the Network.

After the Extender is in a good location, you can add new Wi-Fi devices to it as described in **Add Wi-Fi**.