

**FCC PART 15.247  
TEST REPORT**

For

**Imobiile Technology, L.L.C**

8227 NW 68 ST., MIAMI, FLORIDA 33166, USA

**FCC ID: ZOTKOOL**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Mobile Phone
<b>Test Engineer:</b> Eric Lee	<i>Eric Lee</i>
<b>Report Number:</b> RSZ120109001-00B	
<b>Report Date:</b> 2012-02-28	
<b>Reviewed By:</b> Alvin Huang EMC Engineer	<i>Alvin Huang</i>
<b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
CONFIGURATION OF TEST SETUP .....	6
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>FCC §15.247 (i) &amp; §2.1093 – RF EXPOSURE .....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
RESULT: .....	9
<b>FCC §15.203 – ANTENNA REQUIREMENT .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
MEASUREMENT UNCERTAINTY .....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE .....	12
TEST RESULTS SUMMARY .....	12
TEST DATA .....	12
<b>FCC §15.205, §15.209 &amp; §15.247(d) – RADIATED EMISSIONS.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
MEASUREMENT UNCERTAINTY .....	15
EUT SETUP .....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	16
TEST PROCEDURE .....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY .....	17
TEST DATA .....	17
<b>FCC §15.247(a) (1)-CHANNEL SEPARATION TEST .....</b>	<b>19</b>
APPLICABLE STANDARD .....	19
TEST PROCEDURE .....	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA .....	19
<b>FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH TESTING .....</b>	<b>26</b>
APPLICABLE STANDARD .....	26

TEST PROCEDURE .....	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA .....	26
<b>FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>32</b>
APPLICABLE STANDARD .....	32
TEST PROCEDURE .....	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA .....	32
<b>FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>35</b>
APPLICABLE STANDARD .....	35
TEST PROCEDURE .....	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST DATA .....	35
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>51</b>
APPLICABLE STANDARD .....	51
TEST PROCEDURE .....	51
TEST EQUIPMENT LIST AND DETAILS.....	51
TEST DATA .....	51
<b>FCC §15.247(d) - BAND EDGES TESTING .....</b>	<b>57</b>
APPLICABLE STANDARD .....	57
TEST PROCEDURE .....	57
TEST EQUIPMENT LIST AND DETAILS.....	57
TEST DATA .....	58

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Imobiile Technology, L.L.C*'s product, model number: *KOOL (FCC ID: ZOTKOOL)* or the "EUT" in this report was a *Mobile Phone*, which was measured approximately: 10.38 cm (L) x 5.5 cm (W) x 1.345 cm (H), rated input voltage: DC 3.7 V battery.

*\* All measurement and test data in this report was gathered from production sample serial number: 1201015 (Assigned by BACL, Shenzhen). The EUT was received on 2012-01-09.*

### Objective

This test report is prepared on behalf of *Imobiile Technology, L.L.C* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 22H/24E PCE and Part 15B JBP submission with FCC ID: ZOTKOOL

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3<sup>rd</sup> Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION


### Description of Test Configuration

The system was configured for testing in engineering mode.


### Equipment Modifications

No modification was made to the unit tested.

### Configuration of Test Setup



### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

## FCC §15.247 (i) & §2.1093 – RF EXPOSURE

### Applicable Standard

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Table 2 – Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters**

	Individual Transmitter	Simultaneous Transmission
<b>Licensed Transmitters</b>	<u>Routine evaluation required</u>	<b>SAR not required:</b> <u>Unlicensed only</u> <ul style="list-style-type: none"> <li>when stand-alone 1-g SAR is not required and antenna is <math>\geq 5</math> cm from other antennas</li> </ul> <b>Licensed &amp; Unlicensed</b> <ul style="list-style-type: none"> <li>when the sum of the 1-g SAR is <math>&lt; 1.6</math> W/kg for all simultaneous transmitting antennas</li> <li>when SAR to peak location separation ratio of simultaneous transmitting antenna pair is <math>&lt; 0.3</math></li> </ul> <b>SAR required:</b> <u>Licensed &amp; Unlicensed</u> antenna pairs with SAR to peak location separation ratio $\geq 0.3$ ; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition <b>Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply</b>
<b>Unlicensed Transmitters</b>	<p><b>When there is no simultaneous transmission –</b></p> <ul style="list-style-type: none"> <li>output <math>\leq 60</math> f: SAR not required</li> <li>output <math>&gt; 60</math> f: stand-alone SAR required</li> </ul> <p><b>When there is simultaneous transmission –</b> <u>Stand-alone SAR not required when</u></p> <ul style="list-style-type: none"> <li>output <math>\leq 2 \cdot P_{Ref}</math> and antenna is <math>\geq 5.0</math> cm from other antennas</li> <li>output <math>\leq P_{Ref}</math> and antenna is <math>\geq 2.5</math> cm from other antennas</li> <li>output <math>\leq P_{Ref}</math> and antenna is <math>&lt; 2.5</math> cm from other antennas, each with either output power <math>\leq P_{Ref}</math> or 1-g SAR <math>&lt; 1.2</math> W/kg</li> </ul> <p><u>Otherwise stand-alone SAR is required</u></p> <p><b>When stand-alone SAR is required</b></p> <ul style="list-style-type: none"> <li>test SAR on highest output channel for each wireless mode and exposure condition</li> <li>if SAR for highest output channel is <math>&gt; 50\%</math> of SAR limit, evaluate all channels according to normal procedures</li> </ul>	
<b>Jaw, Mouth and Nose</b>	<p><u>Flat phantom SAR required</u></p> <ul style="list-style-type: none"> <li>when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues</li> <li>position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations</li> </ul>	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.



- 1) GSM can transmit simultaneously with Bluetooth.
- 2) The distance between BT and GSM antenna is  $3.0\text{cm} > 2.5\text{cm}$ . The max output power of Bluetooth antenna is  $6.52(\text{dBm}) - 0(\text{dBi}) (4.487\text{ mW}) < P_{\text{Ref}} (12\text{mW})$ . According to KDB648474, stand-alone SAR is not required for BT antenna and simultaneous SAR evaluation is not required for Bluetooth and GSM antennas.

**Result:**

The SAR measurement is exempt.

---

## **FCC §15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has a integral antenna, which in accordance to section 15.203; please refer to the internal photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard


FCC §15.207

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is 2.4 dB (k=2, 95% level of confidence).

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<b><i>Frequency Range</i></b>	<b><i>IF B/W</i></b>
150 kHz – 30 MHz	9 kHz

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08
Rohde & Schwarz	Pulse limiter	ESH3Z2	DE25985	2011-07-08	2012-07-07

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**5.75 dB at 29.225 MHz in the Neutral conducted mode**

## Test Data


### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa


*The testing was performed by Eric Lee on 2012-02-06*

Test Mode: Charging & Transmitting

AC 120 V, 60 Hz, Line:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.155	52.88	10.10	65.86	12.98	QP
0.155	41.86	10.10	55.86	14.00	Ave.
0.230	45.90	10.10	63.71	17.81	QP
0.460	35.91	10.10	57.14	21.23	QP
0.230	31.39	10.10	53.71	22.32	Ave.
29.505	31.87	10.10	60.00	28.13	QP
0.460	15.76	10.10	47.14	31.38	Ave.
28.225	18.59	10.10	50.00	31.41	Ave.
29.460	17.97	10.10	50.00	32.03	Ave.
26.895	14.96	10.10	50.00	35.04	Ave.
28.085	15.87	10.10	60.00	44.13	QP
26.775	14.97	10.10	60.00	45.03	QP

**AC 120V, 60 Hz, Neutral:**

Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
29.225	54.25	10.10	60.00	5.75	QP
23.050	50.79	10.10	60.00	9.21	QP
0.475	45.25	10.10	56.71	11.46	QP
0.150	52.30	10.10	66.00	13.70	QP
0.230	47.26	10.10	63.71	16.45	QP
0.270	43.56	10.10	62.57	19.01	QP
0.150	35.75	10.10	56.00	20.25	Ave.
0.230	26.99	10.10	53.71	26.72	Ave.
0.475	19.36	10.10	46.71	27.35	Ave.
29.430	21.02	10.10	50.00	28.98	Ave.
23.110	17.59	10.10	50.00	32.41	Ave.
0.270	15.66	10.10	52.57	36.91	Ave.

## FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

### Applicable Standard

FCC §15.205; §15.209; §15.247(d)


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB. ( $k=2$ , 95% level of confidence).

### EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

### EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i><b>Frequency Range</b></i>	<i><b>RBW</b></i>	<i><b>Video B/W</b></i>	<i><b>Detector</b></i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$



**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-02
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-08
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Agilent	Spectrum Analyzer	8564E	3943A01781	2011-04-12	2012-04-11
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2011-05-05	2012-05-04

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

**9.84 dB at 4960 MHz in the Horizontal polarization in high channel**

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100 kPa

*The testing was performed by Eric Lee on 2012-02-06*

*Test mode: Transmitting (BDR mode is worst case)*

**30MHz ~25 GHz:**

Frequency (MHz)	Receiver Reading (dBμV)	Detector (PK/QP/Ave)	Direction (Degree)	Test Antenna			Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	FCC Part 15.247/205/209		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	Comment
Low Channel (2402 MHz)												
2402	99.24	PK	156	1.3	H	30.5	3.03	26.54	106.23	/	/	fundamental
2402	87.15	Ave.	182	1.2	H	30.5	3.03	26.54	94.14	/	/	fundamental
2402	98.36	PK	236	1.4	V	30.2	3.03	26.54	105.05	/	/	fundamental
2042	85.28	Ave.	254	1.6	V	30.2	3.03	26.54	91.97	/	/	fundamental
4804	30.23	Ave.	244	2.1	H	36	4.3	26.87	43.66	54	10.34	harmonic
4804	29.62	Ave.	311	1.6	V	34.5	4.3	26.87	41.55	54	12.45	harmonic
2320	28.51	Ave.	190	1.5	V	30.3	2.98	26.84	34.95	54	19.05	spurious
2320	27.52	Ave.	120	1.2	H	30.3	2.98	26.84	33.96	54	20.04	spurious
4804	39.56	PK	244	1.4	H	36	4.3	26.87	52.99	74	21.01	harmonic
4804	38.65	PK	311	1.6	V	34.5	4.3	26.87	50.58	74	23.42	harmonic
7206	21.86	Ave.	323	1.4	H	39.2	5.22	26.64	39.64	66.23	26.36	harmonic
2320	39.32	PK	120	1.2	H	30.3	2.98	26.84	45.76	74	28.24	spurious
2320	38.52	PK	190	1.9	V	30.3	2.98	26.84	44.96	74	29.04	spurious
7206	20.48	Ave.	255	1.6	V	37.8	5.22	26.64	36.86	66.23	29.14	harmonic
7206	32.25	PK	268	1.5	H	39.2	5.22	26.64	50.03	86.23	35.97	harmonic
7206	32.79	PK	49	1.8	V	37.8	5.22	26.64	49.17	86.23	36.83	harmonic
Middle Channel (2441 MHz)												
2441	97.48	PK	201	1.5	H	30.8	3.05	26.61	104.72	/	/	fundamental
2441	84.69	Ave.	142	1.2	H	30.8	3.05	26.61	91.93	/	/	fundamental
2441	98.02	PK	196	1.1	V	30.5	3.05	26.61	104.96	/	/	fundamental
2441	85.35	Ave.	255	1.4	V	30.5	3.05	26.61	92.29	/	/	fundamental
7323	24.59	Ave.	296	1.8	H	39.3	5.32	26.73	42.48	54	11.52	harmonic
4882	30.14	Ave.	152	1.8	V	34.7	4.36	26.87	42.33	54	11.67	harmonic
4882	28.52	Ave.	163	1.2	H	36.2	4.36	26.87	42.21	54	11.79	harmonic
7323	24.08	Ave.	253	1.2	V	37.9	5.32	26.73	40.57	54	13.43	harmonic
7323	34.26	PK	329	1.5	H	39.3	5.32	26.73	52.15	74	21.85	harmonic
4882	38.36	PK	190	1.2	H	36.2	4.36	26.87	52.05	74	21.95	harmonic
7323	33.72	PK	147	1.6	V	37.9	5.32	26.73	50.21	74	23.79	harmonic
4882	37.52	PK	180	1.4	V	34.7	4.36	26.87	49.71	74	24.29	harmonic
High Channel (2480 MHz)												
2480	98.19	PK	254	1.2	H	30.6	3.06	26.82	105.03	/	/	fundamental
2480	86.43	Ave.	342	1.6	H	30.6	3.06	26.82	93.27	/	/	fundamental
2480	96.77	PK	130	1.4	V	30.7	3.06	26.82	103.71	/	/	fundamental
2480	85.71	Ave.	155	1.4	V	30.7	3.06	26.82	92.65	/	/	fundamental
4960	30.23	Ave.	175	1.2	H	36.4	4.4	26.87	44.16	54	9.84	harmonic
4960	29.24	Ave.	148	1.5	V	35	4.4	26.87	41.77	54	12.23	harmonic
7440	23.57	Ave.	236	1.8	H	39.3	5.22	26.71	41.38	54	12.62	harmonic
7440	22.47	Ave.	346	1.6	V	37.9	5.22	26.71	38.88	54	15.12	harmonic
2492	29.34	Ave.	120	1.2	H	30.6	3.06	26.82	36.18	54	17.82	spurious
2492	29.04	Ave.	190	1.5	V	30.7	3.06	26.82	35.98	54	18.02	spurious
7440	37.42	PK	254	1.4	H	39.3	5.22	26.71	55.23	74	18.77	harmonic
4960	40.12	PK	236	1.9	H	36.4	4.4	26.87	54.05	74	19.95	harmonic
4960	40.09	PK	180	1.6	V	35	4.4	26.87	52.62	74	21.38	harmonic
7440	35.92	PK	121	1.2	V	37.9	5.22	26.71	52.33	74	21.67	harmonic
2492	42.48	PK	142	1.2	H	30.6	3.06	26.82	49.32	74	24.68	spurious
2492	39.77	PK	176	1.9	V	30.7	3.06	26.82	46.71	74	27.29	spurious

**FCC §15.247(a) (1)-CHANNEL SEPARATION TEST****Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

**Test Procedure**

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another true
3. Measure the channel separation.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa

\* The testing was performed by Eric Lee on 2012-02-09

**Test Result:** Compliance.


Please refer to following tables and plots

*Test Mode: Transmitting*


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	$\geq$ Limit (MHz)	Result
<b>BDR (GFSK)</b>	Low	2402	1.076	0.616	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.627	Pass
	Adjacent	2442			
	High	2480	1.000	0.624	Pass
	Adjacent	2479			
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	1.004	0.832	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.861	Pass
	Adjacent	2442			
	High	2480	1.008	0.872	Pass
	Adjacent	2479			
<b>EDR (8DPSK)</b>	Low	2402	1.004	0.837	Pass
	Adjacent	2403			
	Middle	2441	1.008	0.843	Pass
	Adjacent	2442			
	High	2480	1.004	0.845	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth \*2/3


BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




10 20 30 40 50 60

EDR ( $\pi/4$ -DQPSK): Low Channel




10 20 30 40 50 60


EDR ( $\pi/4$ -DQPSK): Middle Channel




EDR ( $\pi/4$ -DQPSK): High Channel



EDR (8DPSK): Low Channel




EDR (8DPSK): Middle Channel





### EDR (8DPSK): High Channel



## FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH TESTING

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa


\* The testing was performed by Eric Lee on 2012-02-27

**Test Result:** Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
<b>BDR (GFSK)</b>	Low	2402	0.924
	Middle	2441	0.940
	High	2480	0.936
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	1.248
	Middle	2441	1.292
	High	2480	1.308
<b>EDR (8DPSK)</b>	Low	2402	1.256
	Middle	2441	1.264
	High	2480	1.268


**BDR (GFSK): Low Channel**

BDR (GFSK): Middle Channel




File: 07\_FDR\_0010\_16\_06\_25

BDR (GFSK): High Channel




File: 07\_FDR\_0010\_16\_06\_25


EDR ( $\pi/4$ -DQPSK): Low Channel




EDR ( $\pi/4$ -DQPSK): Middle Channel




### EDR ( $\pi/4$ -DQPSK): High Channel




### EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



**FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST****Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa

*The testing was performed by Eric Lee on 2012-02-09*


**Test Result:** Compliance.

Please refer to following table and plots




*Test Mode: Transmitting*


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2402-2480	79	≥15
EDR (π/4-DQPSK)	2402-2480	79	≥15
EDR (8DPSK)	2402-2480	79	≥15

**BDR (GFSK): Number of Hopping Channels**

### EDR ( $\pi/4$ -DQPSK): Number of Hopping Channels



### EDR (8DPSK): Number of Hopping Channels



**FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)****Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell time = Pulse time\*hop rate/number of hopping channels\*31.6S

Hop rate=1600/S

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101 kPa

\* The testing was performed by Eric Lee on 2012-02-09.

**Test Result:** Compliance.


Please refer to following table and plots

Test Mode: Transmitting


Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.412	0.132	0.4	Pass
		Middle	0.412	0.132	0.4	Pass
		High	0.412	0.132	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.692	0.271	0.4	Pass
		Middle	1.692	0.271	0.4	Pass
		High	1.682	0.270	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.940	0.314	0.4	Pass
		Middle	2.940	0.314	0.4	Pass
		High	2.956	0.316	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ( $\pi/4$ -DQPSK)	DH 1	Low	0.416	0.133	0.4	Pass
		Middle	0.416	0.133	0.4	Pass
		High	0.416	0.133	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.685	0.270	0.4	Pass
		Middle	1.685	0.270	0.4	Pass
		High	1.685	0.270	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.949	0.315	0.4	Pass
		Middle	2.949	0.315	0.4	Pass
		High	2.965	0.317	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	DH 1	Low	0.420	0.135	0.4	Pass
		Middle	0.420	0.135	0.4	Pass
		High	0.416	0.133	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.696	0.272	0.4	Pass
		Middle	1.696	0.272	0.4	Pass
		High	1.696	0.272	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.960	0.316	0.4	Pass
		Middle	2.976	0.318	0.4	Pass
		High	2.960	0.316	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				

**BDR (GFSK):**


**Pulse time, Low Channel, DH1**




**Pulse time, Middle Channel, DH1**




Pulse time, High Channel, DH1




Pulse time, Low Channel, DH3




Pulse time, Middle Channel, DH3




Pulse time, High Channel, DH3



Pulse time, Low Channel, DH5




Pulse time, Middle Channel, DH5






Pulse time, High Channel, DH5




EDR ( $\pi/4$ -DQPSK):


Pulse time, Low Channel, DH1




Pulse time, Middle Channel, DH1




Pulse time, High Channel, DH1




Pulse time, Low Channel, DH3




Pulse time, Middle Channel, DH3




Pulse time, High Channel, DH3




Pulse time, Low Channel, DH5



Pulse time, Middle Channel, DH5




Pulse time, High Channel, DH5




**EDR (8DPSK):**


**Pulse time, Low Channel, DH1**




**Pulse time, Middle Channel, DH1**




Pulse time, High Channel, DH1




Pulse time, Low Channel, DH3



Pulse time, Middle Channel, DH3




Pulse time, High Channel, DH3







Pulse time, Low Channel, DH5



Pulse time, Middle Channel, DH5



Pulse time, High Channel, DH5




## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101 kPa

\* The testing was performed by Eric Lee on 2012-02-27


**Test Result:** Compliance.

Please refer to following table and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Conducted Output Power		Limit (mW)
			(dBm)	(mW)	
<b>BDR (GFSK)</b>	Low	2402	5.44	3.50	1000
	Middle	2441	6.09	4.06	1000
	High	2480	6.52	4.49	1000
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	4.98	3.15	1000
	Middle	2441	5.83	3.83	1000
	High	2480	6.29	4.26	1000
<b>EDR (8DPSK)</b>	Low	2402	5.19	3.30	1000
	Middle	2441	6.08	4.06	1000
	High	2480	6.51	4.48	1000


### BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR( $\pi/4$ -DQPSK): Low Channel




EDR( $\pi/4$ -DQPSK): Middle Channel




EDR( $\pi/4$ -DQPSK): High Channel




EDR(8DPSK): Low Channel



EDR(8DPSK): Middle Channel



EDR(8DPSK): High Channel





## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1 MHz, VBW=3 MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101 kPa

*\*The testing was performed by Eric Lee on 2012-02-27.*


**Test Result:** Compliance

Please refer to the following table and plots.


*Test Mode: Transmitting*

<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Delta Peak to Band Emission (dBc)</b>	<b>≥Limit (dBc)</b>
<b>BDR (GFSK)</b>	2390.0	63.05	20
	2483.5	58.96	20
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	2390.0	62.61	20
	2483.5	58.18	20
<b>EDR (8DPSK)</b>	2390.0	60.92	20
	2483.5	59.90	20


### BDR (GFSK): Band Edge-Left Side




### BDR (GFSK): Band Edge-Right Side




### EDR ( $\pi/4$ -DQPSK): Band Edge-Left Side




### EDR ( $\pi/4$ -DQPSK): Band Edge-Right Side



### EDR (8DPSK): Band Edge-Left Side



### BDR (8DPSK): Band Edge-Right Side



\*\*\*\*\* END OF REPORT \*\*\*\*\*