

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Digital video recorder, computer for law enforcement
Model No. : M700 series-VMDC,MDC
Brand Name : COBAN
Filing Type : New Application
Applicant : Coban Technologies, Inc.
COBAN Technologies,12503 Exchange Drive, Suite
536,Stafford, Texas 77477
Manufacturer : PEGATRON CORPORATION Taoyuan Mfg.
No.5,Shing Yeh St,Kwei Shan Hsiang,Taoyuan Hsien 333
TAIWAN
FCC ID : ZPJM700SERIESVMDC
Received Date : Apr. 29, 2011
Final Test Date : May 19, 2011

Statement

Test result included is only for the 802.11a/b/g (5725~5850 MHz / 2400~2483.5MHz) part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT	2
2 GENERAL INFORMATION.....	3
2.1 Product Details.....	3
2.2 Accessories.....	3
2.3 Table for Filed Antenna.....	3
2.4 Table for Carrier Frequencies	3
2.5 Table for Test Modes	4
2.6 Table for Testing Locations.....	4
2.7 Table for Supporting Units	4
2.8 Table for Parameters of Test Software Setting.....	4
2.9 EUT Operation during Test	4
2.10 Test Configuration.....	5
3 TEST RESULT	6
3.1 AC Power Line Conducted Emissions Measurement	6
3.2 Peak Output Power Measurement.....	8
3.3 Power Spectral Density Measurement.....	10
3.4 6dB Spectrum Bandwidth Measurement	18
3.5 Radiated Emissions Measurement	26
3.6 Band Edge and Fundamental Emissions Measurement.....	52
3.7 Antenna Requirements	59
4 LIST OF MEASURING EQUIPMENTS.....	60
5 TEST LOCATION.....	61
6 TAF CERTIFICATE OF ACCREDITATION.....	62
APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE	A1 ~ A3
APPENDIX B. TEST PHOTOS	B1 ~ B6
APPENDIX C. PHOTOGRAPHS OF EUT	C1 ~ C41

History of This Test Report

Original Issue Date: Jun. 27, 2011

Report No.: FR110801AC

■ No additional attachment.

□ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Digital video recorder, computer for law enforcement

Model No. : M700 series-VMDC,MDC

Brand Name : COBAN

Applicant : Coban Technologies, Inc.

COBAN Technologies,12503 Exchange Drive, Suite
536,Stafford, Texas 77477

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Apr. 29, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Wayne Hsu / Assistant Manager

SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	-	-
3.2	15.247(b)(3)	Maximum Peak Output Power	Complies	13.63 dB
3.3	15.247(e)	Power Spectral Density	Complies	18.89 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	3.31 dB
3.6	15.247(d)	Band Edge and Fundamental Emissions	Complies	4.52 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7℃	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

Only the radio detail of IEEE 802.11a/b/g is shown in this report. For more detailed features description, please refer to the specifications or user's manual.

Items	Description
Power Type	12V DC source
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (DBPSK / DQPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11a: 5 ; 11b/g: 11
Channel Band Width (99%)	5G-11a: 16.44 MHz ; 2.4G-11b: 14.48 MHz ; 11g: 16.28 MHz
Peak Output Power	5G-11a: 16.37 dBm ; 2.4G-11b: 16.23 dBm ; 11g: 16.28 dBm

2.2 Accessories

Please refer to the specifications or user's manual.

2.3 Table for Filed Antenna

Antenna & Bandwidth

Antenna Mode	Single Chain	
Bandwidth Mode	20 MHz	40 MHz
802.11a (5725~5850 MHz)	V	X
802.11b/g (2400~2483.5MHz)	V	X

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Monopole Antenna	Reversed-SMA	0	TX / RX
B	Monopole Antenna	Reversed-SMA	0	TX / RX

Note:

1. IEEE 802.11a/b/g used one antenna is for signal transmitting and receiving.

2.4 Table for Carrier Frequencies

Frequency Allocation for 802.11a

Frequency Band	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz
	153	5765 MHz
	157	5785 MHz
	161	5805 MHz
	165	5825 MHz

Frequency Allocation for 802.11b/g

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

2.5 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	-	-	-	-
Maximum Peak Output Power Power Spectral Density	11a/BPSK	6 Mbps	149/157/165	A
	11b/CCK	11 Mbps	1/6/11	B
	11g/BPSK	54 Mbps	1/6/11	A
6dB Spectrum Bandwidth	11a/BPSK	6 Mbps	149/157/165	A
	11b/CCK	11 Mbps	1/6/11	B
	11g/BPSK	54 Mbps	1/6/11	A
Radiated Emissions Below 1GHz	11a/BPSK	6 Mbps	149	A
	11g/BPSK	54 Mbps	6	A
Radiated Emissions Above 1GHz Fundamental Emissions	11a/BPSK	6 Mbps	149/157/165	A
	11b/CCK	11 Mbps	1/6/11	B
	11g/BPSK	54 Mbps	1/6/11	A
Band Edge Emissions	11a/BPSK	6 Mbps	149/165	A
	11b/CCK	11 Mbps	1/11	B
	11g/BPSK	54 Mbps	1/11	A

2.6 Table for Testing Locations

Test Site No.	Site Category	Location
TH01-HY	OVEN Room	Hwa Ya
03CH03-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

2.7 Table for Supporting Units

Support Unit	Brand	Model	FCC ID	Remark
LCD Monitor	DELL	1703FPt	DoC	Radiated
Mouse	Logitech	M-BE58	DoC	

2.8 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11a

Test Software Version	CRTU		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a (Ant. A)	9	9.5	9.5

Power Parameters of IEEE 802.11b/g

Test Software Version	CRTU		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b (Ant. B)	14.5	14.5	15
IEEE 802.11g (Ant. A)	5.5	6.5	6


2.9 EUT Operation during Test

Only Radiated used:


- Executed "CRTU" to keep transmitting signals at fixed frequency.

2.10 Test Configuration

Radiation Emissions Test Configuration For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz



3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Class B

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.2 Peak Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-multipoint antenna reduction operation, the limit has to be reduced by 1dB for every dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Peak Output Power

Final Test Date	Apr. 29, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11a/b/g

Configuration IEEE 802.11a Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	16.23	30.00	Complies
157	5785 MHz	16.37	30.00	Complies
165	5825 MHz	16.15	30.00	Complies

Configuration IEEE 802.11b Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.21	30.00	Complies
6	2437 MHz	16.07	30.00	Complies
11	2462 MHz	16.23	30.00	Complies

Configuration IEEE 802.11g Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	15.05	30.00	Complies
6	2437 MHz	16.28	30.00	Complies
11	2462 MHz	15.26	30.00	Complies

3.3 Power Spectral Density Measurement

3.3.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3 kHz and VBW to 30 kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of Power Spectral Density

Final Test Date	Apr. 29, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11a/b/g

Configuration IEEE 802.11a Ant. A

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-19.01	8.00	Complies
157	5785 MHz	-19.18	8.00	Complies
165	5825 MHz	-19.84	8.00	Complies


Configuration IEEE 802.11b Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-11.27	8.00	Complies
6	2437 MHz	-11.07	8.00	Complies
11	2462 MHz	-10.89	8.00	Complies

Configuration IEEE 802.11g Ant. A


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-21.87	8.00	Complies
6	2437 MHz	-19.00	8.00	Complies
11	2462 MHz	-20.85	8.00	Complies

Power Density Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 29.APR.2011 21:24:22

Power Density Plot on Configuration IEEE 802.11a Ant. A / 5785 MHz




Date: 29.APR.2011 21:26:58

Power Density Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz




Date: 29.APR.2011 22:20:48

Power Density Plot on Configuration IEEE 802.11b Ant. B / 2412 MHz




Date: 29.APR.2011 14:49:11

Power Density Plot on Configuration IEEE 802.11b Ant. B / 2437 MHz




Date: 29.APR.2011 16:02:29

Power Density Plot on Configuration IEEE 802.11b Ant. B / 2462 MHz




Date: 29.APR.2011 16:09:59

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 29.APR.2011 18:19:51

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz



Date: 29.APR.2011 18:23:38

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 29.APR.2011 18:27:05

3.4 6dB Spectrum Bandwidth Measurement

3.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of 6dB Spectrum Bandwidth

Final Test Date	Apr. 29, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11a/b/g

Configuration IEEE 802.11a Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	16.44	500	Complies
157	5785 MHz	16.40	16.40	500	Complies
165	5825 MHz	16.40	16.40	500	Complies


Configuration IEEE 802.11b Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	11.56	14.44	500	Complies
6	2437 MHz	11.88	14.44	500	Complies
11	2462 MHz	11.96	14.48	500	Complies

Configuration IEEE 802.11g Ant. A


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.16	16.28	500	Complies
6	2437 MHz	15.16	16.28	500	Complies
11	2462 MHz	15.16	16.28	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 29.APR.2011 21:22:02

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5785 MHz




Date: 29.APR.2011 21:25:56

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz




Date: 29.APR.2011 21:28:21

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. B / 2412 MHz




Date: 29.APR.2011 14:45:59

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. B / 2437 MHz




Date: 29.APR.2011 16:00:58

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. B / 2462 MHz




Date: 29.APR.2011 16:04:44

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 29.APR.2011 18:17:37

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz



Date: 29.APR.2011 18:21:47

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 29.APR.2011 18:25:26

3.5 Radiated Emissions Measurement

3.5.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBUV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	May 19, 2011	Test Site No.	03CH03-HY
Temperature	23℃	Humidity	55%
Test Engineer	Streak		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:


The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


3.5.8 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	May 19, 2011	Test Site No.	03CH03-HY
Temperature	23℃	Humidity	55%
Test Engineer	Streak	Configuration	802.11a Ch. 149 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	198.780	25.12	-18.38	43.50	42.25	9.61	1.25	27.98	Peak
2	272.500	30.09	-15.91	46.00	43.09	13.40	1.72	28.13	Peak
3	288.020	27.98	-18.02	46.00	41.01	13.37	1.82	28.22	Peak
4	490.750	19.27	-26.73	46.00	27.49	18.02	2.68	28.92	QP
5	506.270	23.41	-22.59	46.00	31.41	18.26	2.71	28.97	QP
6	528.580	40.26	-5.74	46.00	47.82	18.78	2.83	29.17	QP

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	30.000	29.73	-10.27	40.00	39.62	18.48	-0.91	27.46	QP
2	39.700	21.58	-18.42	40.00	37.17	12.58	-0.71	27.46	QP
3	128.940	36.66	-6.84	43.50	50.85	12.40	1.02	27.61	Peak
4	490.750	38.78	-7.22	46.00	47.00	18.02	2.68	28.92	Peak
5	506.270	41.41	-4.59	46.00	49.41	18.26	2.71	28.97	Peak
6	532.460	41.75	-4.25	46.00	49.23	18.88	2.85	29.21	Peak


Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	May 12, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11g Ch. 6 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	102.750	38.83	-4.67	43.50	53.80	11.56	0.89	27.42	Peak
2	168.710	38.11	-5.39	43.50	54.88	9.78	1.29	27.85	Peak
3	198.780	31.97	-11.53	43.50	49.10	9.61	1.25	27.98	Peak
4	339.430	29.49	-16.51	46.00	41.02	14.73	2.16	28.42	Peak
5	497.540	27.97	-18.03	46.00	36.13	18.08	2.67	28.91	Peak
6	959.260	29.41	-16.59	46.00	31.97	21.25	5.36	29.17	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	30.000	36.07	-3.93	40.00	45.96	18.48	-0.91	27.46	QP
2	98.870	36.40	-7.10	43.50	51.93	11.03	0.85	27.41	Peak
3	179.380	32.60	-10.90	43.50	50.05	9.10	1.34	27.90	Peak
4	339.430	26.26	-19.74	46.00	37.79	14.73	2.16	28.42	Peak
5	808.910	28.78	-17.22	46.00	33.03	20.77	4.45	29.46	Peak
6	960.230	29.00	-25.00	54.00	31.57	21.24	5.36	29.17	Peak

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10th Harmonic)


Final Test Date	May 14, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11a Ch. 149 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8485.000	55.19	-8.35	63.54	43.64	38.18	6.42	33.05	PK
2	11490.000	56.05	-7.49	63.54	41.43	39.88	7.33	32.58	PK
3	17235.000	66.56			46.29	43.49	8.48	31.70	Peak

Note: The items 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8947.000	54.32			42.57	38.55	6.40	33.20 Peak
2	11490.000	55.63	-7.91	63.54	41.01	39.88	7.33	32.58 PK
3	17235.000	66.92			46.65	43.49	8.48	31.70 Peak

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 14, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11a Ch. 157 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8386.000	54.07			42.66	38.06	6.40	33.05	PK
2	11570.000	56.17	-7.37	63.54	41.57	39.83	7.36	32.59	PK
3	17355.000	66.35			44.97	44.59	8.52	31.73	Peak

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8562.000	54.53			42.93	38.25	6.42	33.08	Peak
2	11570.000	56.20	-7.34	63.54	41.60	39.83	7.36	32.59	PK
3	17355.000	66.46			45.08	44.59	8.52	31.73	Peak

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 14, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11a Ch. 165 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8606.000	53.84			42.23	38.28	6.42	33.08 Peak
2	11650.000	56.87	-6.67	63.54	42.32	39.76	7.39	32.60 PK
3	17475.000	66.83			44.35	45.69	8.55	31.76 Peak

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8518.000	54.24			42.66	38.21	6.42	33.06 Peak
2	11650.000	57.10	-6.44	63.54	42.55	39.76	7.39	32.60 PK
3	17475.000	66.61			44.13	45.69	8.55	31.76 Peak

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 07, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11b Ch. 1 (Ant. B)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	
	MHz	dBuV/m	dB	dBuV/m	Level	Factor	Loss	Factor
					dBuV	dB/m	dB	dB
1	4824.000	47.89	-6.11	54.00	42.03	33.06	5.43	32.63 PK
2	7236.000	49.89			42.10	35.53	5.14	32.89 Peak
3	9648.000	54.11			42.34	38.41	6.70	33.34 Peak

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4824.000	47.71	-6.29	54.00	41.85	33.06	5.43	32.63 PK
2	7236.000	49.52			41.73	35.53	5.14	32.89 Peak
3	9648.000	54.44			42.67	38.41	6.70	33.34 Peak

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 07, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11b Ch. 6 (Ant. B)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	
	MHz	dBuV/m	dB	dBuV/m	Level	Factor	Loss	Factor Remark
					dBuV	dB/m	dB	dB
1	4874.000	47.76	-6.24	54.00	41.80	33.16	5.43	32.62 PK
2	7311.000	49.89	-4.11	54.00	41.75	35.68	5.36	32.90 PK
3	9748.000	55.52			43.50	38.62	6.74	33.34 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	
	MHz	dBuV/m	dB	dBuV/m	Level	Loss	Factor	Remark
					dBuV	dB	dB	
1	4874.000	49.15	-4.85	54.00	43.19	33.16	5.43	32.62 PK
2	7311.000	50.14	-3.86	54.00	42.00	35.68	5.36	32.90 PK
3	9748.000	54.86			42.84	38.62	6.74	33.34 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 07, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11b Ch. 11 (Ant. B)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4924.000	48.22	-5.78	54.00	42.16	33.26	5.41	32.61 PK
2	7386.000	50.69	-3.31	54.00	42.17	35.87	5.57	32.92 PK
3	9848.000	54.67			42.41	38.79	6.80	33.33 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	4924.000	48.77	-5.23	54.00	42.71	33.26	5.41	32.61	PK
2 @	7386.000	49.96	-4.04	54.00	41.44	35.87	5.57	32.92	PK
3	9848.000	55.36			43.10	38.79	6.80	33.33	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 07, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11g Ch. 1 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4824.000	47.22	-6.78	54.00	41.36	33.06	5.43	32.63 PK
2	7236.000	49.88			42.09	35.53	5.14	32.89 Peak
3	9648.000	54.99			43.22	38.41	6.70	33.34 Peak

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4824.000	47.80	-6.20	54.00	41.94	33.06	5.43	32.63 PK
2	7236.000	49.61			41.82	35.53	5.14	32.89 Peak
3	9648.000	54.87			43.10	38.41	6.70	33.34 Peak

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 07, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11g Ch. 6 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1 @	4874.000	48.46	-5.54	54.00	42.50	33.16	5.43	32.62 PK
2 @	7311.000	50.52	-3.48	54.00	42.38	35.68	5.36	32.90 PK
3	9748.000	55.47			43.45	38.62	6.74	33.34 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4874.000	48.37	-5.63	54.00	42.41	33.16	5.43	32.62 PK
2	7311.000	49.95	-4.05	54.00	41.81	35.68	5.36	32.90 PK
3	9748.000	54.67			42.65	38.62	6.74	33.34 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 07, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11g Ch. 11 (Ant. A)

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4924.000	48.13	-5.87	54.00	42.07	33.26	5.41	32.61 PK
2	7386.000	50.21	-3.79	54.00	41.69	35.87	5.57	32.92 PK
3	9848.000	54.40			42.14	38.79	6.80	33.33 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4924.000	48.89	-5.11	54.00	42.83	33.26	5.41	32.61 PK
2	7386.000	50.60	-3.40	54.00	42.08	35.87	5.57	32.92 PK
3	9848.000	54.91			42.65	38.79	6.80	33.33 Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6 Band Edge and Fundamental Emissions Measurement

3.6.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

3.6.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

Final Test Date	May 13, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11a Ch. 149, 157, 165 (Ant. A)

Channel 149

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	5725.000	75.08	-8.46	83.54	35.05	34.80	5.23	0.00	Peak
2 @	5741.700	111.09			71.08	34.80	5.21	0.00	Peak
1 @	5724.970	59.02	-4.52	63.54	18.99	34.80	5.23	0.00	Average
2 @	5737.780	100.17			60.14	34.80	5.23	0.00	Average

The item 2 is fundamental emissions and the item 1 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Channel 157

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	5702.550	71.53	-12.01	83.54	31.50	34.80	5.23	0.00	Peak
2 @	5781.430	111.17			71.18	34.80	5.19	0.00	Peak
3	5863.540	70.81	-12.73	83.54	30.87	34.80	5.14	0.00	Peak
1 @	5716.660	58.00	-5.54	63.54	17.97	34.80	5.23	0.00	Average
2 @	5782.620	99.96			59.97	34.80	5.19	0.00	Average
3	5851.980	57.62	-5.92	63.54	17.66	34.80	5.16	0.00	Average

The item 2 is fundamental emissions and the items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Channel 165

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	5830.350	110.70			70.74	34.80	5.16	0.00	Peak
2	5853.450	71.56	-11.98	83.54	31.60	34.80	5.16	0.00	Peak
1 @	5827.210	99.42			59.46	34.80	5.16	0.00	Average
2	5851.850	57.56	-5.98	63.54	17.60	34.80	5.16	0.00	Average

The item 1 is fundamental emissions and the item 2 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	May 06, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11b Ch. 1, 6, 11 (Ant. B)

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	2381.060	59.64	-14.36	74.00	26.94	28.11	4.59	0.00	Peak
2 ☺	2413.170	104.80			71.99	28.16	4.65	0.00	Peak
1	2389.610	46.14	-7.86	54.00	13.35	28.13	4.65	0.00	Average
2 ☺	2410.700	96.62			63.81	28.16	4.65	0.00	Average

The item 2 is fundamental emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 X	2434.260	103.91			71.01	28.19	4.71	0.00	Peak
1 ☺	2435.210	95.72			62.82	28.19	4.71	0.00	Average

The item 1 is fundamental emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 ☺	2459.340	105.14			72.19	28.24	4.71	0.00	Peak
2	2494.490	59.87	-14.13	74.00	26.80	28.30	4.77	0.00	Peak
1 ☺	2460.290	96.93			63.98	28.24	4.71	0.00	Average
2	2483.660	46.52	-7.48	54.00	13.48	28.27	4.77	0.00	Average

The item 1 is fundamental emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	May 06, 2011	Test Site No.	03CH03-HY
Temperature	23°C	Humidity	55%
Test Engineer	Streak	Configuration	802.11g Ch. 1, 6, 11 (Ant. A)

Channel 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	2346.860	61.38	-12.62	74.00	28.73	28.05	4.59	0.00	Peak
2 @	2408.610	100.72			67.91	28.16	4.65	0.00	Peak
1	2387.900	48.07	-5.93	54.00	15.28	28.13	4.65	0.00	Average
2 @	2409.370	90.78			57.97	28.16	4.65	0.00	Average

The item 2 is fundamental emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2433.500	98.71			65.81	28.19	4.71	0.00	Peak
1 @	2433.690	88.34			55.44	28.19	4.71	0.00	Average

The item 1 is fundamental emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2463.330	98.38			65.37	28.24	4.77	0.00	Peak
2	2485.370	61.39	-12.61	74.00	28.35	28.27	4.77	0.00	Peak
1 @	2464.660	88.27			55.26	28.24	4.77	0.00	Average
2 @	2498.100	48.73	-5.27	54.00	15.66	28.30	4.77	0.00	Average

The item 1 is fundamental emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	Apr. 29, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11a/b/g

Low Band Edge Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 29.APR.2011 21:23:16

High Band Edge Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz




Date: 29.APR.2011 21:29:28

Low Band Edge Plot on Configuration IEEE 802.11b Ant. B / 2412 MHz




Date: 29.APR.2011 14:47:55

High Band Edge Plot on Configuration IEEE 802.11b Ant. B / 2462 MHz




Date: 29.APR.2011 16:07:26

Low Band Edge Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz



Date: 29.APR.2011 18:18:52

High Band Edge Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 29.APR.2011 18:26:05

3.7 Antenna Requirements

3.7.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.7.2 Antenna Connector Construction

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Jan. 06, 2011	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Apr. 15, 2011	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Oct. 22, 2010	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 02, 2010	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 02, 2010	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 29, 2011	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz~40GHz	Jan. 06, 2011	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz~40GHz	Jan. 06, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 26, 2010*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 18, 2010	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 25, 2011	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Aug. 02, 2010	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Nov. 17, 2010	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz - 1 GHz	Oct. 16, 2010	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 20, 2010	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.13, 2011	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 18, 2011	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 18, 2011	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION


財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate No. : L1190-110111

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 11, 2011

PI, total 24 pages