

Produkte Products

> Seite 28 von 33 Prüfbericht - Nr.: 50145995 001 Page 28 of 33

Test Report No.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: Passed

Test standard FCC KDB Publication 447498 D01 v06

> 47CFR 1.1310 47CFR 2.1091

RSS-102 issue 5, Table 4

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied

Maximum Exposure:

| Power to Antenna (mW) | 2.3496 mW |
|------------------------|---------------|
| Power to Antenna (dBm) | 3.7 dBm |
| Antenna Gain | 2.5 dBi |
| Power+Ant Gain | 4.2 mW |
| Distance | 20 cm |
| S= | 0.001 mW/cm^2 |

Limit FCC:

0.3-1.34 MHz (100) mW/cm² 0.3-1.34 MHz (100) mW/cm² 1.34-30 MHz (180/f2) mW/cm² 30-300 MHz 0.2 mW/cm² 300-1500 MHz f/1500 mW/cm² (180/f2) mW/cm² 1500-100,000 MHz 1.0 mW/cm²

Limit Canada: 0.542 mW/cm²

---End---