

FCC C2PC Test Report

FCC ID : ZQ6-AP6234A

Equipment : Wifi Dual Band + BT combo module

Model No. : AP6234A, AP6234AL

Brand Name : Ampak

Applicant : Ampak Technology Inc

Address : No.1 Jen Al Road, Hsinchu Industrial Park,

Hukou, Hsinchu, Taiwan, 30352

Standard : 47 CFR FCC Part 15.247

Received Date : May 21, 2014

Tested Date : May 21 ~ Jun. 04, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Iac-MRA



Report No.: FR440102-07AD Report Version: Rev. 01 Page : 1 of 46



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	
1.5	Test Standards	g
1.6	Measurement Uncertainty	g
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	Unwanted Emissions into Restricted Frequency Bands	14
3.3	Unwanted Emissions into Non-Restricted Frequency Bands	30
3.4	Conducted Output Power	35
3.5	Number of Hopping Frequency	37
3.6	20dB and Occupied Bandwidth	39
3.7	Channel Separation	41
3.8	Number of Dwell Time	43
4	TEST LABORATORY INFORMATION	46



Release Record

Report No.	Version	Description	Issued Date
FR440102-07AD	Rev. 01	Initial issue	Jun. 16, 2014

Report No.: FR440102-07AD Page: 3 of 46



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.154MHz 46.25 (Margin -9.53dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions		Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: BR: 7.45 EDR: 6.99	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR440102-07AD Page: 4 of 46



1 General Description

1.1 Information

This report is prepared for FCC class II change.

This report is issued as a duplicate report to original ICC report no. FR440102AD. The modification is adding SAW filter for 2.4G RF part, so only the 2.4G related tests will be re-evaluated. It this test report, all test items has been re-tested and only its data was recorded in the following sections.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz) Bluetooth Ch. Frequency Channel Number Data Rate							
2400-2483.5	BR V2.1	2402-2480	0-78 [79]	1 Mbps			
2400-2483.5	EDR V2.1	2402-2480	0-78 [79]	2 Mbps			
2400-2483.5	EDR V2.1	2402-2480	0-78 [79]	3 Mbps			

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

Note 2: Bluetooth BR uses a GFSK.

Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.

1.1.2 Antenna Details

Ant. No.	Туре	Gain (dBi)	Connector	Remark
1	Dipole	2	UFL	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3.3Vdc from host.

1.1.4 Accessories

N/A

Report No.: FR440102-07AD Page: 5 of 46



1.1.5 Channel List

	Frequency	band (MHz)		2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

1.1.6 Test Tool and Duty Cycle

Test Tool	Brocom Blue Tool, V.1.7.3.3
-----------	-----------------------------

Report No.: FR440102-07AD Page: 6 of 46




1.1.7 Power Setting

Modulation Mode		Test Frequency (MHz)	
Modulation Mode	2402	2441	2480
GFSK/1Mbps	255,63	255,63	255,63
π/4 DQPSK	255,63	255,63	255,63
8DPSK/3Mbps	255,63	255,63	255,63

1.2 Local Support Equipment List

	Support Equipment List							
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)		
1	Notebook	DELL	E6430		DoC	USB 1.0m shielded cable w/o core.		

1.3 Test Setup Chart



Report No.: FR440102-07AD Page: 7 of 46



1.4 The Equipment List

Test Item	Conducted Emission								
Test Site	Conduction room 1 / (Conduction room 1 / (CO01-WS)							
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014				
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014				
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014				
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 23, 2014	Apr. 22, 2015				
50 ohm terminal (Support Unit)	NA	50	04	Apr. 18, 2014	Apr. 17, 2015				

Test Item	Radiated Emission	Radiated Emission							
Test Site	966 chamber1 / (03C	H01-WS)							
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
Spectrum Analyzer	R&S	FSV40	101498	Jan. 25, 2014	Jan. 24, 2015				
Receiver	R&S	ESR3	101658	Jan. 10, 2014	Jan. 09, 2015				
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 02, 2014	Jan. 01, 2015				
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 13, 2014	Feb. 12, 2015				
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014				
Preamplifier	Burgeon	BPA-530	SN:100219	Nov. 28, 2013	Nov. 27, 2014				
Preamplifier	Agilent	83017A	MY39501308	Dec. 16, 2013	Dec. 15, 2014				
Preamplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2014				
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 16, 2013	Dec. 15, 2014				
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 16, 2013	Dec. 15, 2014				
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 16, 2013	Dec. 15, 2014				
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 16, 2013	Dec. 15, 2014				
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 16, 2013	Dec. 15, 2014				
Note: Calibration Inter	val of instruments liste	d above is one year.							

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until	
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014	
Note: Calibration Interv						

Report No.: FR440102-07AD Page: 8 of 46



Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014
Note: Calibration Inter	rval of instruments listed	d above is one year.			

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 FCC Public notice DA 00-705 ANSI C63.10-2009

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Frequency error	±34.134 Hz
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.92 dB
Radiated emission < 1GHz	±3.26 dB
Radiated emission > 1GHz	±4.94 dB

Report No.: FR440102-07AD Page: 9 of 46



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 72%	Skys Huang
Radiated Emissions	03CH01-WS	22°C / 66%	Anderson Hung
RF Conducted	TH01-WS	21°C / 66%	Felix Sung

FCC site registration No.: 657002IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	GFSK	2441	1Mbps	-
Radiated Emissions < 1GHz	GFSK	2441	1Mbps	-
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	-
Conducted Output Power	GFSK π/4-DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	-
Number of Hopping Channels	GFSK 8DPSK	2402~2480 2402~2480	1Mbps 3Mbps	-
Hopping Channel Separation	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	-
Dwell Time	GFSK 8DPSK	2402 2402	1Mbps 3Mbps	-

NOTE: The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.

Report No.: FR440102-07AD Page: 10 of 46



3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

	Conducted Emissions Limit	
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarith	m of the frequency.	•

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR440102-07AD Page: 11 of 46




Test Result of Conducted Emissions 3.1.4



Report No.: FR440102-07AD Page: 12 of 46





Report No.: FR440102-07AD Page: 13 of 46



3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

	Restricted Band	Emissions Limit	
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. Radiated emission above 1GHz / Peak value RBW=1MHz, VBW=3MHz and Peak detector

Radiated emission above 1GHz / Average value for harmonics

The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:


3.
$$20\log \text{ (Duty cycle)} = 20\log \frac{1\text{s} / 1600 * 5}{100 \text{ ms}} = -30.1 \text{dB}$$

4. Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=1/T and Peak detector

Report No.: FR440102-07AD Page: 14 of 46




3.2.3 Test Setup



Report No.: FR440102-07AD Page: 15 of 46



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR440102-07AD Page: 16 of 46





*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR440102-07AD Page: 17 of 46



3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 18 of 46



Modulation			GF	SK			Test Fred	q. (MHz)		2402	
Polarization			Ver	tical					•		
	90	Level	(dBuV/m)								
	80										
	70									FCC CLAS	S-B
	60								FCC	CLASS-B (A	VG)
	50	1	4 6						100	CLNJJ-D (A	
	40		3								
	30										
	20		5								
	10										
	0	1000	4000.	6000. 80	000. 100). 14000. 1 ency (MHz)	16000. 180	00. 20000.	22000.	25000
			Freq.	Emission	Limit	_	SA	Factor	Remark	ANT	Turn
			MHz	level dBuV/m	dBuV/	m dB	reading dBuV	dB		High cm	Table deg
	1		1534.00	44.87	54.00	-9.13	51.88	-7.01	Average		
	2		1534.00	50.78	74.00	-23.22	57.79		Peak		
	3		2390.00	36.24	54.00	-17.76	39.92	-3.68	Average		

53.11

-3.68

4.96

4.96

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

2390.00 49.43 74.00 -24.57 53.11 4804.00 15.75 54.00 -38.25 10.79 4804.00 45.85 74.00 -28.15 40.89

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 19 of 46

Report Version: Rev. 01

4

5

6



Modulation			GFS	SK			Test Fred	q. (MHz)	2	441				
Polarization			Horizontal											
	90 <mark>1</mark>	evel	(dBuV/m)											
	80													
	80									FCC CLAS	S-B			
	70	\rightarrow												
	60													
	ļ	2		6					FCC C	LASS-B (A	(VG)			
	50	1	4	ΤŤ										
	40	$+\!\!+\!\!\!+$												
	20													
	30													
	20	+	3	- 1										
	10													
	O,	1000	4000.	6000. 80	000. 100	000. 12000). 14000. 1	16000. 180	00. 20000. 2	22000.	25000			
						Freque	ency (MHz)							
			Freq. 1		Limit	Margir		Factor	Remark	ANT	Turn			
				level			reading			High	Table			
			MHz	dBuV/m	dBuV/	m dB	dBuV	dB		CM	deg			
	1		1534.00	48.19	54.00	-5.81	55.20	-7.01	Average					
	2		1534.00			-21.38	59.63	-7.01	Peak					
3	3		4882.00				10.34	5.12	Average					
	4		4882.00					5.12	Peak					
!	5		7323.00	19.64	54.00	-34.36	10.30	9.34	Average					

9.34

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

7323.00 49.74 74.00 -24.26 40.40

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 20 of 46



Modulation		GFS	K		,	Test Fred	q. (MHz)	2	2441				
Polarization		Vertical											
Le	vel (dBu	V/m)											
90		T .											
80—									500 01 40				
									FCC CLAS	S-B			
70—													
60										<u> </u>			
	2		6					FCC	CLASS-B (A	WG)			
50	1	4											
40													
30—													
20													
23		1											
10													
0													
°10	00 4	000.	6000. 80	000. 100). 14000. 1 ency (MHz)	16000. 180	00. 20000.	22000.	25000			
	Fr	req. E	mission	Limit	Margin	s SA	Factor	Remark	ANT	Turn			
		•	level		5	reading			High	Table			
	N	1Hz	dBuV/m	dBuV/	m dB	dBuV	dB		cm	deg			
1					-9.68	51.33	-7.01	Average					
2					-23.59	57.42	-7.01	Peak					
3					-38.14		5.12	Average					
4			45.96		-28.04	40.84	5.12	Peak					

9.34

9.34

Average

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

7323.00 18.84 54.00 -35.16 9.50 7323.00 48.94 74.00 -25.06 39.60


*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 21 of 46

Report Version: Rev. 01

5





*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 22 of 46



3

4

5

Modulation			GFS	SK			Test	Freq	. (MHz)		24	80		
Polarization			Vertical											
	90	Level	(dBuV/m)								1			
	80										F	CC CLAS	S-B	
	70													
	60										FCC CL	ASS-B (A	WG)	
	50	2	4 6											
	40		llĭ											
	40		3											
	30													
	20													
	20		5											
	10	++												
	0													
		1000	4000.	6000. 80	000. 100)0. 140 iency (N		6000. 180	00. 20	000. 22	000.	25000	
			Freq. 6	Emission	Limit	Margi	n S	А	Factor	Rem	ark	ANT	Turn	
				level				ding				High	Tabl	
			MHz	d Bu V/m	dBuV/ı	n dB	dB	uV ¯	dB			cm	deg	
_	1		1534.00								rage			
4	2		1534.00	50.36	74.00	-23.64	5/	.3/	-/.01	Pea	K			

2483.50 36.99 54.00 -17.01 40.29

2483.50 48.86 74.00 -25.14 52.16 4960.00 15.44 54.00 -38.56 10.16 4960.00 45.54 74.00 -28.46 40.26 Average

Average

Peak

Peak

-3.30

-3.30

5.28

5.28


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 23 of 46



3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR440102-07AD Page: 24 of 46



Modulation			8DPSI	<		Test	Freq.	(MHz)	ı	240	02	
Polarization			Vertica	al								
	Leve	el (dBu\	//m)									
	30											
•	00									FC	CC CLAS	S-B




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1534.00	44.35	54.00	-9.65	51.36	-7.01	Average		
2	1534.00	50.26	74.00	-23.74	57.27	-7.01	Peak		
3	2390.00	36.16	54.00	-17.84	39.84	-3.68	Average		
4	2390.00	48.74	74.00	-25.26	52.42	-3.68	Peak		
5	4804.00	15.35	54.00	-38.65	10.39	4.96	Average		
6	4804.00	45.45	74.00	-28.55	40.49	4.96	Peak		

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 25 of 46






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 26 of 46



Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical		
oo Level (dBu	V/m)		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m		SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1534.00	44.63	54.00	-9.37	51.64	-7.01	Average		
2		50.76			57.77	-7.01	Peak		
3	4882.00	15.27	54.00	-38.73	10.15	5.12	Average		
4	4882.00	45.37	74.00	-28.63	40.25	5.12	Peak		
5	7323.00	18.97	54.00	-35.03	9.63	9.34	Average		
6	7323.00	49.07	74.00	-24.93	39.73	9.34	Peak		

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 27 of 46






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 28 of 46



Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		
90 Level (dBu	V/m)		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1534.00	44.68	54.00	-9.32	51.69	-7.01	Average		
2	1534.00	50.62	74.00	-23.38	57.63	-7.01	Peak		
3	2483.50	36.73	54.00	-17.27	40.03	-3.30	Average		
4	2483.50	50.06	74.00	-23.94	53.36	-3.30	Peak		
5	4960.00	15.28	54.00	-38.72	10.00	5.28	Average		
6	4960.00	45.38	74.00	-28.62	40.10	5.28	Peak		

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR440102-07AD Page: 29 of 46



3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference Level Measurement

- Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.3.3 Test Setup




Report No.: FR440102-07AD Page: 30 of 46




3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands

GFSK



Report No.: FR440102-07AD Page: 31 of 46






Report No.: FR440102-07AD Page: 32 of 46




8DPSK



Report No.: FR440102-07AD Page: 33 of 46





Report No.: FR440102-07AD Page: 34 of 46



3.4 Conducted Output Power

3.4.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

1 Watt For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
0.125 Watt For all other frequency hopping systems in the 2400–2483.5 MHz band.
0.125 Watt For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

- A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
- 2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



Report No.: FR440102-07AD Page: 35 of 46



3.4.4 Test Result of Conducted Output Power

Modulation Mode	Freq. (MHz)	Output Power (mW)	Output Power (dBm)	Limit (mW)
GFSK	2402	4.28	6.31	21
GFSK	2441	5.56	7.45	21
GFSK	2480	4.89	6.89	21
π/4-DQPSK	2402	3.57	5.53	21
π/4-DQPSK	2441	4.72	6.74	21
π/4-DQPSK	2480	3.79	5.79	21
8DPSK	2402	3.73	5.72	21
8DPSK	2441	5.00	6.99	21
8DPSK	2480	4.02	6.04	21

Modulation Mode	Freq. (MHz)	AV Output Power (mW)	AV Output Power (dBm)
GFSK	2402	4.14	6.17
GFSK	2441	5.42	7.34
GFSK	2480	4.73	6.75
π/4-DQPSK	2402	2.12	3.26
π/4-DQPSK	2441	2.73	4.36
π/4-DQPSK	2480	2.15	3.33
8DPSK	2402	2.11	3.24
8DPSK	2441	2.74	4.37
8DPSK	2480	2.15	3.32

Note: Average power is for reference only

Report No.: FR440102-07AD Page: 36 of 46



3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

- 1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
- 2 Allow trace to stabilize.


3.5.3 Test Setup



Report No.: FR440102-07AD Page: 37 of 46



3.5.4 Test Result of Number of Hopping Frequency



Report No.: FR440102-07AD Page: 38 of 46




3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures

- 1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use N dB function of spectrum analyzer to measuring 20 dB bandwidth
- 4. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup




Report No.: FR440102-07AD Page: 39 of 46



3.6.3 Test result of 20dB and Occupied Bandwidth

Modulation Mode	Freq. (MHz)	20dB Bandwidth (MHz)	Occupied Bandwidth (MHz)
GFSK	2402	1.009	0.916
GFSK	2441	1.022	0.916
GFSK	2480	1.026	0.916
8DPSK	2402	1.322	1.203
8DPSK	2441	1.326	1.203
8DPSK	2480	1.322	1.203



Report No.: FR440102-07AD Page: 40 of 46



3.7 Channel Separation


3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

- 1. Set RBW=100kHz, VBW=300kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup




Report No.: FR440102-07AD Page: 41 of 46



3.7.4 Test result of Channel Separation

Modulation Mode	Freq. (MHz)	Channel Separation (MHz)	20dB Bandwidth (MHz)	Minimum Limit (MHz)
GFSK	2402	1.003	1.009	0.672
GFSK	2441	1.003	1.022	0.681
GFSK	2480	1.003	1.026	0.684
8DPSK	2402	1.003	1.322	0.881
8DPSK	2441	1.003	1.326	0.884
8DPSK	2480	1.003	1.322	0.881



Report No.: FR440102-07AD Page: 42 of 46



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

- Set RBW=100kHz,VBW=300kHz,Sweep time = 500us(DH1),2ms(DH3),4ms(DH5), Detector=Peak, Span=0Hz,Trace max hold
- 2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
- 3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds, or 0.625ms. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.
- 4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds, or 1.875ms. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

3.8.3 Test Setup




Report No.: FR440102-07AD Page: 43 of 46




3.8.4 Test Result of Dwell Time

Modulation Mode	Freq. (MHz)	No. of Pulse in a 31.6 (79Hopping*0.4)	Length of Pulse Time (msec)	Result (sec)	Limit (sec)
GFSK	2402	320	0.43191	0.138	0.4
GFSK	2441	160	1.70872	0.273	0.4
GFSK	2480	106.6	2.96814	0.316	0.4
8DPSK	2402	320	0.44785	0.143	0.4
8DPSK	2441	160	1.73480	0.278	0.4
8DPSK	2480	106.6	2.96234	0.316	0.4



Report No.: FR440102-07AD Page: 44 of 46





Report No.: FR440102-07AD Page: 45 of 46



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR440102-07AD Page: 46 of 46