# FCC PART 15.239 EMI MEASUREMENT AND TEST REPORT For

# CAMI (HK) COMPANY LIMITED

Room 903, 9/F, New Commerce Centre, 19 On Sum Street, Shatin, N.T. Hong Kong

FCC ID: ZR6-M2-20-3F

July 24, 2011

This Report Concerns:		Equipment Type:		
Original Report		Car Mount for iPad - ENHANCED and		
	DELUXE version			
Test Engineer:	Davis Ma	Davis ma		
Report No.:	PTS1107244	17E		
Receive EUT				
Date/Test Date:	July 15, 2011 / July 15-24, 2011			
Reviewed By:	Lisa Zhu	lim shu		
	PTS	DongGuan Precise Testing Service Co.,Ltd. F616A Room, 6th Floor, Meixin Business		
Prepared By:	PRECISE TESTING Center, Dongcheng Middle Road,			
	Dongguan, Guangdong, China			
	TEL: +86-769-23368601			
		FAX: +86-769-23368602		

**Note:** The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of DongGuan Precise Testing Service Co.,Ltd. This report must not be used by the client to claim product certification,approval,or endorsement by NVLAP, NIST or any agency of the US Government.

# TABLE OF CONTENTS

1.	GEN	ERAL INFORMATION	.3
	1.1.	Report information	.3
	1.2.	Measurement Uncertainty	
2.	PRO	DUCT DESCRIPTION	.4
	2.1.	EUT Description	
	2.2.	Block Diagram of EUT Configuration	
	2.3.	Support Equipment List	
	2.4.	Test Conditions	
3.	FCC	ID LABEL	
4.		RESULTS SUMMARY	
		fications	
5.		EQUIPMENT USED	
٥.	11201	EQUI MENT OSED	• /
_	DAD		^
6.		IATED EMISSIONS	
6.	6.1.	Test Equipment	.8
6.	6.1. 6.2.	Test Equipment	.8 .8
6.	6.1. 6.2. 6.3.	Test Equipment Test Procedure Radiated Test Setup	.8 .8 .8
6.	6.1. 6.2. 6.3. 6.4.	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit	.8 .8 .8
	6.1. 6.2. 6.3. 6.4. 6.5.	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result	.8 .8 .8 .8
<ul><li>7.</li></ul>	6.1. 6.2. 6.3. 6.4. 6.5.	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit	.8 .8 .8 .8
	6.1. 6.2. 6.3. 6.4. 6.5.	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result	.8 .8 .8 .9
	6.1. 6.2. 6.3. 6.4. 6.5. <b>OCC</b>	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result  UPIED BANDWIDTH	.8 .8 .8 .9 12
	6.1. 6.2. 6.3. 6.4. 6.5. OCC	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result  UPIED BANDWIDTH  Test Equipment	.8 .8 .8 .9 12
	6.1. 6.2. 6.3. 6.4. 6.5. OCC 7.1. 7.2.	Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result  UPIED BANDWIDTH  Test Equipment Test Procedure	.8 .8 .8 .9 12 12

#### 1. GENERAL INFORMATION

# 1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that PTS approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that PTS in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, PTS therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through PTS, unless the applicant has authorized PTS in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of

World Standardization Certification&TestingCO.,LTD

(FCC Registered Test Site Number: 131628) on

Building A, Baoshi Road, Baoshi Science & Technology Park, Bao'an District, Shenzhen, Guangdong, China The Test Site is constructed and calibrated to meet the FCC requirements.

### 1.2. Measurement Uncertainty

Available upon request.

# 2. PRODUCT DESCRIPTION

# 2.1. EUT Description

Description : Car Mount for iPad - ENHANCED and DELUXE version

Applicant : CAMI (HK) COMPANY LIMITED

Room 903, 9/F, New Commerce Centre, 19 On Sum Street,

Shatin, N.T. Hong Kong

Model Number : M2-20-3F, MI-20-3R, MI-20-3F, M2-20-3R

Model different : All models have the same constructions, circuit diagram and PCB


layout. Only model name and color are different.

**Additional Information** 

Frequency: 88.1-107.9MHz

Power Supply : DC 12V

# 2.2. Block Diagram of EUT Configuration



# 2.3. Support Equipment List

1. iPad player FCC DOC

#### 2.4. Test Conditions

Temperature:  $23\sim25^{\circ}$ C Relative Humidity:  $55\sim63^{\circ}$  %

PTS FCC ID REPORT : PTS11072447E

Page 4/16

# 3. FCC ID LABEL

FCC ID: ZR6-M2-20-3F

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference, and
- 2. This device must accept any interference received, including interference that may cause undesired operation.

**Label Location on EUT** 

**EUT Bottom View/FCC ID Label Location** 

20 24 1 22 1 1 22 1 1 1 2 1 1 2 3 4 5 6 7 8 9 20 1

PTS FCC ID REPORT: PTS11072447E

# 4. TEST RESULTS SUMMARY

FCC 15 Subpart C,Paragraph 15.239

Test Standards	Test Items	Test Results
FCC Part 15 Subpart C, Paragraph 15.239	Radiated Emission (30MHz to 1000MHz)	Pass
FCC Part 15 Subpart C, Paragraph 15.239	Occupied Bandwidth	Pass

Remark: "N/A" means "Not applicable."

# **Modifications**

No modification was made.

# 5. TEST EQUIPMENT USED

EQUIPMENT/FACILITIES	MANUFACTU RER	MODEL #	SERIAL NO.	DATE OF CAL.	CAL. INTERVAL
Cable	Resenberger	N/A	NO.1	Mar 10, 2011	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Mar 10, 2011	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Mar 10, 2011	1 Year
LISN	Rohde & Schwarz	ESH3-Z5	100305	Mar 10, 2011	1 Year
50 Ω Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Mar 10, 2011	1 Year
EMI Test Receiver	Rohde & Schwarz	ESP13	100180	Oct.18,2010	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSP40	100273	Sep.10,2010	1 Year
3m Semi-Anechoic Chamber	Albatross Projects	9m×6m×6m	N/A	Feb.20,2011	1 Year
Signal Generator	FLUKE	PM5418 + Y/C	LO747012	Feb.20,2011	1 Year
Signal Generator	FLUKE	PM5418TX	LO738007	Feb.20,2011	1 Year
Loop Antenna	SCHWARZBECK	FMZB1516	113	Jan.30,2011	1 Year
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	9161-4079	Sep.22,2010	1 Year
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-564	Sep.22,2010	1 Year
Ultra Broadband Antenna	Rohde & Schwarz	HL-562	100110	June.15,2011	1 Year
AMN	Rohde & Schwarz	ESH3-Z5	100196	Oct.11,2010	1 Year
AMN	Rohde & Schwarz	ESH3-Z5	100197	Oct.11,2010	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
Power Meter	Rohde & Schwarz	NRVD	100041	Feb.20,2011	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	Feb.20,2011	1 Year
Coaxial Cable with N-connectors	SCHWARZBECK	AK9515H	95549	Sep.22,2010	1 Year
Radio Communication Test Set	Rohde & Schwarz	CMS 54	846621/024	Feb.20,2011	1 Year
Modulation Analyzer	Hewlett-Packard	8901B	2303A00362	Feb.20,2011	1 Year
Absorbing clamp	Rohde & Schwarz	MDS-21	N/A	Oct.29,2010	1 Year

# 6. RADIATED EMISSIONS


# 6.1. Test Equipment

Please refer to section 4 this report.

#### **6.2. Test Procedure**

The out of band emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part Subpart C limits.

# 6.3. Radiated Test Setup



For the accrual test configuration, pleas refer to the related items-photos of Testing.

# 6.4. Radiated Emission Limit

CARRIER FREQUENCY WILL NOT EXCEEDS 48.0 dBuV/m AT 3M. OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

Frequency	Distance	Field Strength	
(MHz)	(m)	(dBuV/m)	
30-88	3	40.0	
88-216	3	43.5	
216-960	3	46.0	
ABOVE 960	3	54.0	

# **6.5. Radiated Emission Test Result**

FREQ. (MHZ)	POL V/H	LEVEL (DBµV)		LIMIT (DBµV)		MARGIN (DB)	
		AV	PK	AV	PK	AV	PK
88.1	Н	42.12	47.89	48	68	-5.88	-20.11
88.1	V	44.15	49.25	48	68	-3.85	-18.75
98.0	Н	41.42	48.25	48	68	-6.58	-19.75
98.0	V	45.28	52.36	48	68	-2.72	-15.64
107.9	Н	42.13	49.35	48	68	-5.87	-18.65
107.9	V	43.32	51.37	48	68	-4.68	-16.63

FREQ.	POL	LEVEL	LIMIT	MARGIN			
(MHZ)	V/H	(DBµV)	(DBµV)	(DB)			
For 88.0MHz							
176.2	Н	25.32	43.5	18.18			
176.2	V	23.26	43.5	20.24			
264.3	Н	22.38	46	23.62			
264.3	V	19.65	46	26.35			
352.4	Н	19.76	46	26.24			
352.4	V	20.65	46	25.35			
440.5	Н	-	46				
440.5	V		46				
528.6	Н	-	46				
528.6	V	-	46				
616.7	Н	-	46				
616.7	V	-	46				
704.8	Н	-	46				
704.8	V		46				
792.9	Н		54				
792.9	V		54				
881.0	Н		54				
881.0	V		54				

FREQ. (MHZ)	POL V/H	LEVEL (DBµV)	LIMIT (DBµV)	MARGIN (DB)				
For 98.0MH	For 98.0MHz							
196.0	Н	25.35	43.5	18.15				
196.0	V	28.76	43.5	14.74				
294.0	Н	19.67	46	26.33				
294.0	V	21.25	46	24.75				
392.0	Н	18.67	46	27.33				
392.0	V	19.77	46	26.23				
490.0	Н		46					
490.0	V		46					
588.0	Н		46					
588.0	V		46					
686.0	Н		46					
686.0	V		46					
784.0	Н		46					
784.0	V		46					
882.0	Н		54					
882.0	V		54					
980.0	Н		54					
980.0	V		54					

FREQ. (MHZ)	POL V/H	LEVEL (DBµV)	LIMIT (DBµV)	MARGIN (DB)			
(WITIZ)	V/11	(ΔΔμν)	(DBμ V)	(DB)			
For 107.9MH:	For 107.9MHz						
215.8	Н	22.56	43.5	20.94			
215.8	V	23.71	43.5	19.79			
323.7	Н	23.79	46	22.21			
323.7	V	25.13	46	20.87			
431.6	Н	21.26	46	24.74			
431.6	V	23.45	46	22.55			
539.5	Н		46				
539.5	V		46				
647.4	Н		46				
647.4	V		46				
755.3	Н		46				
755.3	V		46				
863.2	Н		46				
863.2	V		46				
971.1	Н		54				
971.1	V		54				
1079.0	Н		54				
1079.0	V		54				

Note: The frequency will not be recorded if the level of the spurious emission is very weak(no harmonic or spurious emissions were higher than 20dB below the limits of 47 CFR Part 15.209).

#### 7. OCCUPIED BANDWIDTH

# 7.1. Test Equipment

Please refer to Section 4 this report.

#### 7.2. Test Procedure

- 1. The EUT was tested according C63.4-2003. The test was performed with Spectrum Analyzer at FCC Registration laboratory .
- 2. Based on FCC Part15 C Section 15.239.

Operation within the band 88MHz – 108MHz

### 7.3. Requirements


Intentional radiators operating under the alternative provisions to the geneql emission limits, as Emissions from the device shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz.


#### 7.4. Test Result


Method of measurement:

The bandwidth was properly tested with maximum audio input(such as MP3 Player)

- 1. Set both RBW and VBW of spectrum analyzer to 10 kHz and 30kHz respectively with a convenient frequency span including 200kHz bandwidth of the emission.
- 2. Mark the bandwidth of 200kHz points and plot the graph on spectrum analyzer.







# 8. ANTENNA REQUIREMENT

# 8.1. Standard applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator

shall be designed to ensure that no antenna other than that furnished by the responsible

party shall be used with the device.

# 8.2. Antenna connected construction

The antenna used in this product is cable antenna solder to PCB and no consideration of replacement.

PTS FCC ID REPORT : PTS11072447E

# FCC ID LABEL

FCC ID: ZR6-M2-20-3F

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation.

Label Location on EUT
EUT Bottom View/ FCC ID Label Location

# RADIATED EMISSION TEST








Appearance photograph of EUT



Appearance photograph of EUT



Appearance photograph of EUT



Inside photograph of EUT



Main PCB photograph of EUT

ar 22 23 2 2 2 2 2 2 3 4 5 6 7 8 9 70 1

antenna

Main PCB photograph of EUT

