

FCC PART 15 CLASS B
EMI MEASUREMENT AND TEST REPORT
For

Suzhou CoreRise Electronics Co., Ltd.
Rm 208, Bldg Xingzheng, #166, Ren'ai Rd, Industrial Park, Suzhou City, P.R.China

FCC ID: ZSQ-PLUTO

July 27, 2011

This Report Concerns: Original Report		Equipment Type: Solid State Drive	
Test Engineer:		Jack Liu	
Report No.:		SHBST2011062907Y-1ER-3	
Receive EUT Date/Test Date:		July 20, 2011/ July 21-27, 2011	
Reviewed By:		Christina 	
Prepared By:		 Shenzhen BST Technology Co.,Ltd. 3F, Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District, Shenzhen, Guangdong, China Tel: 0755-26747751 ~ 3 Fax: 0755-26747751 ~ 3 ext.826	

Note: The test report is specially limited to the above company and this particular sample only.
It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd.
This report must not be used by the client to claim product certification, approval, or
endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1.	Report information.....	3
1.2.	Measurement Uncertainty	3
2.	PRODUCT DESCRIPTION	4
2.1.	EUT Description	4
2.2.	Block Diagram of EUT Configuration	4
2.3.	Support Equipment List	4
2.4.	Test Conditions	4
3.	FCC ID LABEL.....	5
4.	TEST RESULTS SUMMARY	6
	Modifications	6
5.	TEST EQUIPMENT USED	7
5.1.	For Conducted Emission Test.....	7
5.2.	For Radiated Emission Measurement	7
6.	CONDUCTED EMISSION TEST	8
6.1.	Block Diagram of Test Setup.....	8
6.2.	Test Standard	8
6.3.	Conducted Emission Limit(Class B)	9
6.4.	EUT Configuration on Test	9
6.5.	Operating Condition of EUT	9
6.6.	Test Procedure	9
6.7.	Test Result	10
7.	RADIATED EMISSION MEASUREMENT	12
7.1.	Block Diagram of EUT Configuration	12
7.2.	Test Standard	12
7.3.	Radiated Emission Limit(Class B)	13
7.4.	EUT Configuration on Test	13
7.5.	Operating Condition of EUT	13
7.6.	Test Procedure	13
7.7.	Test Result	13

1. GENERAL INFORMATION

1.1. Report information

1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.

1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of emitel (Shenzhen) Limited

(FCC Registered Test Site Number: 746887) on

Building 2, 171 Meihua Road, Futian District, Shenzhen, 518049 China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

Available upon request.

2. PRODUCT DESCRIPTION

2.1. EUT Description

Applicant : Suzhou CoreRise Electronics Co., Ltd.

Address : Rm 208, Bldg Xingzheng, #166, Ren'ai Rd, Industrial Park,
Suzhou City, P.R.China

Manufacturer : Suzhou CoreRise Electronics Co., Ltd.

Address : Rm 208, Bldg Xingzheng, #166, Ren'ai Rd, Industrial Park,
Suzhou City, P.R.China


EUT Description : Solid State Drive

Trade Name : Comay科美 CoreRise

Model Number : Pluto SV 2, Pluto PP 2, Pluto SP 2, Pluto SW 2, Venus 2,
Venus Pro 2, Pluto PP 3, Pluto SP 3, Pluto SV 3, Pluto SW 3,
Venus 3, Venus Pro 3

Power Supply : DC 5V (Powered by PC)

2.2. Block Diagram of EUT Configuration



2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used “ ”
Notebook	PP10L	X1247 A01	DELL	
Router	TL-WR841ND	09789401323	TP-LINK	

2.4. Test Conditions

Temperature: 20~25

Relative Humidity: 50~63 %

3. FCC ID LABEL

FCC ID: ZSQ-PLUTO

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. This device must accept any interference received, including interference that may cause undesired operation.

Label Location on EUT

EUT Bottom View/ FCC ID Label Location



4. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	Test Results
Conducted disturbance	Pass
Radiated disturbance	Pass

Remark: “N/A” means “Not applicable.”

Modifications

No modification was made.

5. TEST EQUIPMENT USED

5.1. For Conducted Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Jun. 01, 11	1 Year
2.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Jun. 01, 11	1 Year
3.	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Jun. 01, 11	1 Year
4.	Conical	Emtek	N/A	N/A	N/A	N/A
5.	Voltage Probe	Schwarzbeck	TK9416	N/A	Jun. 01, 11	1 Year
6.	Coaxial Switch	Anritsu	MP59B	6100214550	Jun. 01, 11	1 Year


5.2. For Radiated Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	ANRITSU	MS2661C	6200140915	Jun. 01, 11	1 Year
2.	Test Receiver	Rohde&Schwarz	ESC830	828982/018	Jun. 01, 11	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	142	Jun. 01, 11	1 Year
4.	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	Jun. 01, 11	1 Year
5.	Cable	Schwarzbeck	AK9513	ACRX1	Jun. 01, 11	1 Year
6.	Cable	Rosenberger	N/A	FR2RX2	Jun. 01, 11	1 Year
7.	Cable	Schwarzbeck	AK9513	CRRX2	Jun. 01, 11	1 Year
8.	Cable	Schwarzbeck	AK9513	CRRX2	Jun. 01, 11	1 Year
9.	Single Phase Power Line Filter	MPE	23332C	N/A	Jun. 01, 11	1 Year
10.	Single Phase Power Line Filter	MPE	23333C	N/A	Jun. 01, 11	1 Year
11.	Signal Generator	HP	864A	3625U00573	Jun. 01, 11	1 Year


6. CONDUCTED EMISSION TEST

6.1. Block Diagram of Test Setup

6.1.1. Block Diagram of connection between the EUT and the simulators



6.1.2. Test Setup Diagram



6.2. Test Standard

FCC Part 15 CLASS B

ANSI C63.4 2003

6.3. Conducted Emission Limit(Class B)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

6.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet FCC Part 15 requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

6.4.1.EUT Information

Model Number: MW0812

Serial Number: N/A

6.5. Operating Condition of EUT

6.5.1.Setup the EUT and simulators as shown in Section 6.1.

6.5.2.Turn on the power of all equipments.

6.5.3.Let the EUT work in test mode (EUT Working) and test it.

6.6. Test Procedure


The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

6.7. Test Result**Pass**


Date of Test:	<u>July 24, 2011</u>	Temperature:	<u>25°C</u>
EUT:	<u>Solid State Drive</u>	Humidity:	<u>52%</u>
		<u>DC 5V power by PC</u>	
Model No.:	<u>Pluto SV 2</u>	Power Supply:	<u>PC power: AC120V/60Hz</u>
Test Mode:	<u>Working</u>	Test Engineer:	<u>Jack Liu</u>

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.186000	41.10	11.2	64	23.1	QP	N	GND
0.618000	31.00	11.9	56	25.0	QP	N	GND
0.865500	32.00	11.9	56	24.0	QP	N	GND
Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.186000	39.90	11.2	54	14.3	AV	N	GND
0.618000	30.40	11.9	46	15.6	AV	N	GND
0.865500	31.10	11.9	46	14.9	AV	N	GND
Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	43.50	11.0	66	22.5	QP	L1	GND
0.618000	32.60	11.9	56	23.4	QP	L1	GND
0.865500	32.20	11.9	56	23.8	QP	L1	GND
Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.186000	43.00	11.2	54	11.2	AV	L1	GND
0.370500	34.50	11.8	49	14.0	AV	L1	GND
0.618000	32.40	11.9	46	13.6	AV	L1	GND

N Line




L Line




7. RADIATED EMISSION MEASUREMENT

7.1. Block Diagram of EUT Configuration

7.1.1. Block Diagram of connection between the EUT and the simulators



7.1.2. Semi-anechoic Chamber Test Setup Diagram



7.2. Test Standard

FCC Part 15 CLASS B
ANSI C63.4 2003

7.3. Radiated Emission Limit(Class B)

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB μ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
Above 1000	3	54.0

Note:(1) The smaller limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or system.

7.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Measurement to meet the Commission requirements and operating regulations in a manner which tends to maximize Its emission characteristics in normal application.

7.5. Operating Condition of EUT

7.5.1.Setup the EUT as shown on Section 7.1

7.5.2.Turn on the power of all equipments.

7.5.3.Let the EUT work in test mode (EUT working) and measure it.

7.6. Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.



The bandwidth of test receiver is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The EUT is tested in Semi-anechoic Chamber. The frequency range from 30MHz to 6000MHz is checked.All the test results are listed in Section 7.7.

7.7. Test Result

PASS

Horizontal polarization



Vertical polarization

