FCC PART 15 SUBPART C TEST REPORT

for

High Power AC1750 Wi-Fi Router

Model No.: RTA1750

FCC ID: ZTT-RTA1750

of

Applicant: Amped Wireless
Address: 13089 Peyton Dr. #C307 Chino Hills, California 91709
United State

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

A2LA Accredited No.: 2732.01





Report No.: W6M21410-14564-C-1-R1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C. TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com

FCC ID: ZTT-RTA1750

TABLE OF CONTENTS

l	GE.	NERAL INFORMATION	2
	1.1	Notes	2
	1.2	TESTING LABORATORY	3
	1.2.	1 Location	3
	1.2.	2 Details of accreditation status	3
	1.3	DETAILS OF APPROVAL HOLDER	3
	1.4	APPLICATION DETAILS	4
	1.5	GENERAL INFORMATION OF TEST ITEM	4
	1.6	TEST STANDARDS	7
2	TE	CHNICAL TEST	8
	2.1	SUMMARY OF TEST RESULTS	8
	2.2	TEST ENVIRONMENT	8
	2.3	TEST EQUIPMENT LIST	9
	2.4	GENERAL TEST PROCEDURE	11
3	TES	ST RESULTS (ENCLOSURE)	13
	3.1	PEAK OUTPUT POWER (TRANSMITTER)	14
	3.2	EQUIVALENT ISOTROPIC RADIATED POWER	34
	3.3	RF Exposure Compliance Requirements	34
	3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	35
	3.5	Spurious Emissions (TX)	36
	3.6	RADIATED EMISSION ON THE BAND EDGE	39
	3.7	MINIMUM 6 DB BANDWIDTH	52
	3.8	PEAK POWER SPECTRAL DENSITY	71
	3.9	RADIATED EMISSION FROM DIGITAL PART	91
	3.10	POWER LINE CONDUCTED EMISSION	92
	APPEN	IDIX	96

FCC ID: ZTT-RTA1750

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

0 1 01

The test sample is able to work according IEEE 802.11 b/g/n.

This report is related to FCC Part 15 C (DSSS and OFDM device).

	'ester:	
_	CSICI.	

January 30, 2015		Rick Chen	PICK Chen.
Date	WTS-Lab.	Name	Signature

Technical responsibility for area of testing:

January 30, 2015		Kevin Wang	Kevir Wang
Date	WTS	Name	Signature

FCC ID: ZTT-RTA1750

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207,

Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228 FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd. 6F, NO. 58, LANE 188, RUEY-KUANG RD. NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877 Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1





Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd.:

 Name:
 ./.

 Accredited number:
 ./.

 Street:
 ./.

 Town:
 ./.

 Country:
 ./.

 Telephone:
 ./.

 Fax:
 ./.

1.3 Details of approval holder

Name: Amped Wireless

Street: 13089 Peyton Dr. #C307 Town: Chino Hills, California 91709

Country: United State
Telephone: (909) 217-3229
Fax: (909) 580-8883

FCC ID: ZTT-RTA1750

1.4 Application details

Date of receipt of test item: November 04, 2014

Date of test: from November 05, 2014 to January 30, 2015

1.5 General information of Test item

Type of test item: High Power AC1750 Wi-Fi Router

Model Number: RTA1750

Brand Name: Amped Wireless

Multi-listing model number: RE1750A

Photos: see Appendix

Technical data

Frequency band: 2.4 GHz - 2.4835 GHz

802.11b, g, n 20MHz

Frequency (ch 1 or A): 2.412 GHz
Frequency (ch 6 or B): 2.437 GHz
Frequency (ch 11 or C): 2.462 GHz

802.11n 40MHz

Frequency (ch 1 or A): 2.422 GHz
Frequency (ch 4 or B): 2.437 GHz
Frequency (ch 7 or C): 2.452 GHz

Number of Channels: 802.11b, g, n 20MHz: 11

802.11n 40MHz: 7

Operation modes: duplex

Modulation Type: DSSS / OFDM Fixed point-to-point operation: \square Yes / \square No

Type of Antenna: DualBand Omni Antenna

Antenna gain: ANT0: 5 dBi / ANT1: 5 dBi / ANT2: 5dBi

Directional gain: 9.77 dBi

According to KDB 662911, If any transmit signals are correlated with each other,

Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi

FCC ID: ZTT-RTA1750

Power supply: Adapter (I/P: 100-240Vac, 50/60Hz, MAX 0.5A

O/P: 12Vdc, 1.5A)

Emission designator: Mode A (802.11b): DSSS: 16M2G1D

Mode B (802.11g): OFDM: 17M6D1D

Mode C (802.11n 20MHz): OFDM: 19M4D1D Mode D (802.11n 40MHz): OFDM: 38M0D1D

Host device: none

Classification:

Fixed Device	
Mobile Device (Human Body distance > 20cm)	
Portable Device (Human Body distance < 20cm)	
Modular Radio Device	

<u>Transmitter</u>	<u>Unom</u>
--------------------	-------------

ANT0

Mode A (DSSS)

Power (ch 1 or A): Conducted: 21.02 dBm Power (ch 6 or B): Conducted: 17.46 dBm Power (ch 11 or C): Conducted: 17.80 dBm

Mode B (OFDM)

Power (ch 1 or A): Conducted: 22.53 dBm Power (ch 6 or B): Conducted: 22.60 dBm Power (ch 11 or C): Conducted: 22.06 dBm

Mode C (OFDM)

Power (ch 1 or A): Conducted: 21.47 dBm
Power (ch 6 or B): Conducted: 21.80 dBm
Power (ch 11 or C): Conducted: 21.08 dBm

Mode D (OFDM)

Power (ch 1 or A): Conducted: 21.78 dBm
Power (ch 4 or B): Conducted: 21.52 dBm
Power (ch 7 or C): Conducted: 21.03 dBm



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ANT1

Mode A (DSSS)

Power (ch 1 or A): Conducted: 23.20 dBm Power (ch 6 or B): Conducted: 23.22 dBm Power (ch 11 or C): Conducted: 22.92 dBm

Mode B (OFDM)

Power (ch 1 or A): Conducted: 22.29 dBm Power (ch 6 or B): Conducted: 22.65 dBm Power (ch 11 or C): Conducted: 21.72 dBm

Mode C (OFDM)

Power (ch 1 or A): Conducted: 20.92 dBm Power (ch 6 or B): Conducted: 21.71 dBm Power (ch 11 or C): Conducted: 21.48 dBm

Mode D (OFDM)

Power (ch 1 or A): Conducted: 22.01 dBm Power (ch 4 or B): Conducted: 21.87 dBm Power (ch 7 or C): Conducted: 21.30 dBm

ANT2

Mode A (DSSS)

Power (ch 1 or A): Conducted: 24.07 dBm Power (ch 6 or B): Conducted: 23.13 dBm Power (ch 11 or C): Conducted: 23.50 dBm

Mode B (OFDM)

Power (ch 1 or A): Conducted: 21.42 dBm
Power (ch 6 or B): Conducted: 21.97 dBm
Power (ch 11 or C): Conducted: 21.42 dBm

Mode C (OFDM)

Power (ch 1 or A): Conducted: 20.89 dBm Power (ch 6 or B): Conducted: 20.58 dBm Power (ch 11 or C): Conducted: 20.75 dBm

Mode D (OFDM)

Power (ch 1 or A): Conducted: 20.81 dBm Power (ch 4 or B): Conducted: 20.73 dBm Power (ch 7 or C): Conducted: 20.65 dBm

FCC ID: ZTT-RTA1750

Combine		mW			dBm	
Combine	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	386.61	413.90	387.68	25.87	26.17	25.88
802.11n 40MHz	430.01	414.03	377.81	26.33	26.17	25.77

Manufacturer: (if applicable)

Name: Loopcomm Technology,.Inc.

Street: 6F., No.236, Bo'ai St., Shulin Dist.,

Town: New Taipei City 23845

Country: Taiwan

1.6 Test standards

Technical standard: FCC RULES PART 15 SUBPART C § 15.247 (2013-10)

FCC ID: ZTT-RTA1750

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.	×
or	
The deviations as specified in 2.5 were ascertained in the course of the tests performed.	

2.2 Test environment

Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Power supply: Adapter (I/P: 100-240Vac, 50/60Hz, MAX 0.5A

O/P: 12Vdc, 1.5A)

Extreme conditions parameters: ./.



FCC ID: ZTT-RTA1750

2.3 Test Equipment List

No.	Test equipment	Туре	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2014/9/2	2015/9/1
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function	on Test
ETSTW-CE 008	HF-EICHLEITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Functio	on Test
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2014/7/8	2015/7/7
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2014/10/13	2015/10/12
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2014/9/2	2015/9/1
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2014/9/2	2015/9/1
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function	on Test
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Functio	on Test
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2014/10/15	2015/10/14
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2014/7/01	2015/6/30
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2014/2/25	2015/2/24
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-te	st Use
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2014/2/18	2015/2/17
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2014/6/05	2015/6/04
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2014/3/3	2015/3/2
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2014/11/26	2015/11/25
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Functio	on Test
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function	on Test
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2014/10/9	2015/10/8
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2014/9/22	2015/9/21
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 106	Humidity Temperature Meter	TES-1366	091011113	TES	2014/11/7	2015/11/6
ETSTW-RE 111	TRILOG Super Broadband test Antenna	VULB 9160	9160-3309	Schwarz beck	2014/12/5	2015/12/4
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	None	T-Power	Functi	on test
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2015/1/7	2016/1/6
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Functi	on test
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2014/6/11	2015/6/10
ETSTW-RE 125	5GHz Notch filter	5NSL11- 5200/E221.3-O/O	1	K&L Microwave	2014/8/12	2015/8/11



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ETSTW-RE 126	5GHz Notch filter	5NSL11- 5800/E221.3-O/O	1	K&L Microwave	2014/8/12	2015/8/11
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2014/3/3	2015/3/2
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circits	2014/8/12	2015/8/11
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circits	2014/8/12	2015/8/11
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-te	st Use
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2014/10/20	2015/10/19
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849- 822/851-40 /12+9SS	3	WI	2015/1/7	2016/1/6
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748- 1743/1752-32/5SS	1	WI	2015/1/7	2016/1/6
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5 -1875.5/1884.5- 32/5SS	3	WI	2015/1/7	2016/1/6
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1- 904.25-50/8SS	1	WI	2015/1/7	2016/1/6
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2014/9/17	2015/9/16
ETSTW-Cable 010	BNC Cable	5 M BNC Cable	None	JYE BAO CO.,LTD.	2014/10/15	2015/10/14
ETSTW-Cable 011	BNC Cable	BNC Cable 1	None	JYE BAO CO.,LTD.	Pre-test I	Jse NCR
ETSTW-Cable 012	N TYPE To SMA Cable	Cable 012	None	JYE BAO CO.,LTD.	2014/10/15	2015/10/14
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 022	N TYPE Cable	5006	0002	JYE BAO CO.,LTD.	2014/2/19	2015/2/18
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2014/3/3	2015/3/2
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2014/3/3	2015/3/2
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2015/1/16	2016/1/15
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2014/9/22	2015/9/21
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2014/3/3	2015/3/2
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S_Cable 10)	238092	HUBER+SUHNER	2014/11/26	2015/11/25
ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2014/11/26	2015/11/25
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325518	HUBER+SUHNER	2014/11/26	2015/11/25
ETSTW-Cable 053	N TYPE To SMA Cable	RG142	None	JYE BAO CO.,LTD.	2014/2/19	2015/2/18
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2014/2/19	2015/2/18
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version E	ETS-03A1

FCC ID: ZTT-RTA1750

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2014 5.2 using a 50µH LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2014 6.4 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of $dB\mu V$) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS(to the receiver) = FS

 $20 \text{ dB}\mu\text{V} + 10.36 \text{ dB} + 6 \text{ dB} = 36.36 \text{ dB}\mu\text{V/m} \text{ @3m}$

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2014 6.3.1. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services(Taiwan) Co., Ltd. at the registered open field test site located at No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207, Taiwan (R.O.C.). The Registration Number: 930600.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

FCC ID: ZTT-RTA1750

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = 20 log (dwell time/T)

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.4-2014 10.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	×	×	
Equivalent isotropically radiated Power	15.247(b)(3)	×	×	
Spurious Emissions radiated – Transmitter	15.247(c):	×	×	
operating	15.209			
Band Edge Measurement	15.247(c)	×	×	
Minimum 6 dB Bandwidth	15.247(d)	×	×	
Peak Power Spectral Density	15.247(e)	×	×	
Radiated Emission from Digital Part	15.109			
Power Line Conducted Emission	15.207	×	×	

Note:

- 1. This EUT incorporates a MIMO function with IEEE 802.11b, 802.11g, and 802.11n. Physically, this EUT includes two transmitters and two receivers with two incoherent streams. This device uses multiplexing and also employ cyclic delay diversity to improve range and throughput, and this device simultaneously operates on two adjacent channels.
- 2. This EUT is 3*3 spatial MIMO (3Tx&3Rx) without beam forming function. That operates dual chain configuration. The Pre-test was performed to determine the worst case mode from all possible combinations between all available modulations, data rates, bandwidths, and spatial stream modes.
- 3. The detail of chosen mode for full testing are as below:

Mode	Available	Chosen	Modulation	Modulation	Data Rate
Mode	channel	Channel	Technology	Type	(Mbps)
802.11b	1 to 11	1,6,11	DSSS	DBPSK,	1
				DQPSK, CCK	
802.11g	1 to 11	1,6,11	OFDM	BPSK, QPSK,	6
				16QAM,	
				64QAM	
802.11n (20MHz)	1 to 11	1,6,11	OFDM	BPSK, QPSK,	6.5
				16QAM,	
				64QAM	
802.11n (40MHz)	1 to 7	1,4,7	OFDM	BPSK, QPSK,	13.5
				16QAM,	
				64QAM	

FCC ID: ZTT-RTA1750


3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).


ANT0




MAX OUTPUT POWER 802.11B CH01 Date: 30.JAN.2015 14:00:39

Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11B CH06 Date: 30.JAN.2015 14:01:30




MAX OUTPUT POWER 802.11B CH11 Date: 30.JAN.2015 14:02:14




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11G CH01 Date: 20.NOV.2014 15:53:14




MAX OUTPUT POWER 802.11G CH06 Date: 20.NOV.2014 15:54:07




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11G CH11 Date: 20.NOV.2014 15:54:49




MAX OUTPUT POWER 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:08:55




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:09:56




MAX OUTPUT POWER 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:11:07




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:12:17




MAX OUTPUT POWER 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:14:28




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:15:21

ANT1




MAX OUTPUT POWER 802.11B CH01 Date: 30.JAN.2015 14:12:49




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11B CH06 Date: 30.JAN.2015 14:13:36




MAX OUTPUT POWER 802.11B CH11 Date: 30.JAN.2015 14:14:26




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11G CH01 Date: 20.NOV.2014 16:05:09




MAX OUTPUT POWER 802.11G CH06 Date: 20.NOV.2014 16:03:02




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11G CH11 Date: 20.NOV.2014 16:03:56




MAX OUTPUT POWER 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:19:18




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:20:01




MAX OUTPUT POWER 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:20:41




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:21:28




MAX OUTPUT POWER 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:22:38




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:24:12

ANT2




MAX OUTPUT POWER 802.11B CH01 Date: 30.JAN.2015 14:06:55




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11B CH06 Date: 30.JAN.2015 14:07:44




MAX OUTPUT POWER 802.11B CH11 Date: 30.JAN.2015 14:08:56




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11G CH01 Date: 20.NOV.2014 16:16:07




MAX OUTPUT POWER 802.11G CH06 Date: 20.NOV.2014 16:16:58




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11G CH11 Date: 20.NOV.2014 16:18:09




MAX OUTPUT POWER 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:27:45




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:28:27




MAX OUTPUT POWER 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:29:41




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:30:53




MAX OUTPUT POWER 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:31:49



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



MAX OUTPUT POWER 802.11N 40MHZ CH07

Date: 26.NOV.2014 00:32:39

ANT0	mW			dBm		
	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	140.28	151.36	128.23	21.47	21.80	21.08
802.11n 40MHz	150.66	141.91	126.77	21.78	21.52	21.03
ANT1	mW			dBm		
	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	123.59	148.25	140.60	20.92	21.71	21.48
802.11n 40MHz	158.85	153.82	134.90	22.01	21.87	21.30
ANT2	mW		dBm			
802.11n 20MHz	122.74	114.29	118.85	20.89	20.58	20.75
802.11n 40MHz	120.50	118.30	116.14	20.81	20.73	20.65
Combine	mW			dBm		
	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	386.61	413.90	387.68	25.87	26.17	25.88
802.11n 40MHz	430.01	414.03	377.81	26.33	26.17	25.77

FCC ID: ZTT-RTA1750

Limits:

Frequency	Power
MHz	dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider \$15.247 (b)(4)

Test equipment used: ETSTW-RE 055, ETSTW-RE 050

FCC ID: ZTT-RTA1750

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

For systems using digital modulation in the 2.4 GHz – 2.4835 GHz bands: 1 Watt.

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.25 m normally can be maintained between the user and the device.

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a "worst case" or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	429.53	Peak value
D	dB		
AG	dBi	9.77	
G		9.4842	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.8104	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure			
Frequency (MHz)	Power Density (mW/cm ²)		
1500 – 100.000	1.0		

FCC ID: ZTT-RTA1750

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency ≤ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements) Frequency > 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements) Frequency > 1 GHz, RBW:1 MHz, VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission	Field strength	Field Strength
(MHz)	(microvolts/meter)	(dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:

"If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation."

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = 20 log (dwell time/ 100ms)

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: See attached diagrams in Appendix.

FCC ID: ZTT-RTA1750

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies above 1GHz (Peak measurements). Modified Limit for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

Max. reading - 20 dB

Guidance on Measurement of Digit Transmission Systems:

"If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation."

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = 20 log (dwell time/100ms)

Note: No duty cycle correction was added to the reading of EUT.

FCC ID: ZTT-RTA1750

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Correction Factor".

Summary table with radiated data of the test plots

Model: RTA1750 Date: --

Mode: Temperature: -- °C Engineer: --

Polarization: Horizontal Humidity: -- %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Frequency	Rea	ding	Factor	Re	sult	Lir	nit	Margin	Table	Ant.
	(dB	uV)	(dB)	(dBı	uV/m)	(dBu	V/m)		Degree	High
(MHz)	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.	(dB)	(Deg.)	(cm)
		1					1			
		-								

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Frequency		ding uV)	Factor (dB)		esult uV/m)		mit V/m)	Margin	Table Degree	Ant. High
(MHz)	Peak	Äve.	Corr.	Peak	Ave.	Peak	Äve.	(dB)	(Deg.)	(cm)
									-	

FCC ID: ZTT-RTA1750

Note

- 1. Correction Factor = Antenna factor + Cable loss Preamplifier
- 2. The formula of measured value as: Test Result = Reading + Correction Factor
- 3. Detector function in the form: PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.
- 5. Measurement uncertainty for 3m measurement: $30\text{-}1000 \text{ MHz} = \pm 3.68 \text{ dB}$, $1\text{-}18 \text{ GHz} = \pm 5.37 \text{ dB}$, $18\text{-}40 \text{ GHz} = \pm 3.43 \text{ dB}$; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
- 6. See attached diagrams in appendix.

TEST RESULT (**Transmitter**): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 111,

ETSTW-RE 088, ETSTW-RE 018


FCC ID: ZTT-RTA1750

3.6 Radiated Emission on the band edge

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

ANT₀




BANDEDGE 802.11B CH01
Date: 20.NOV.2014 15:49:29




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11B CH11
Date: 20.NOV.2014 15:50:57




BANDEDGE 802.11G CH01
Date: 20.NOV.2014 15:53:36




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11G CH11
Date: 20.NOV.2014 15:55:11




BANDEDGE 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:09:17




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:11:29




BANDEDGE 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:12:42




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:15:46

ANT1




BANDEDGE 802.11B CH01
Date: 20.NOV.2014 15:37:07




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11B CH11
Date: 20.NOV.2014 15:38:41




BANDEDGE 802.11G CH01
Date: 20.NOV.2014 16:05:31




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11G CH11
Date: 20.NOV.2014 16:04:18




BANDEDGE 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:19:40




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:21:03




BANDEDGE 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:21:52




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:24:36

ANT2




BANDEDGE 802.11B CH01
Date: 20.NOV.2014 15:42:33




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11B CH11
Date: 20.NOV.2014 15:43:56




BANDEDGE 802.11G CH01
Date: 20.NOV.2014 16:16:29




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11G CH11
Date: 20.NOV.2014 16:18:31




BANDEDGE 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:28:06




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:30:03




BANDEDGE 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:31:18



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



BANDEDGE 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:33:04

Limit:

Frequency Range / MHz	Limit			
902 –928				
2400 – 2483.5	- 20 dB			
5725 - 5850				


Test equipment used: ETSTW-RE 055, ETSTW-RE 050

FCC ID: ZTT-RTA1750

3.7 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.

ANT0




6DB BANDWIDTH 802.11B CH01 Date: 20.NOV.2014 15:49:15




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11B CH06
Date: 20.NOV.2014 15:50:00




6DB BANDWIDTH 802.11B CH11 Date: 20.NOV.2014 15:50:43




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11G CH01 Date: 20.NOV.2014 15:53:22




6DB BANDWIDTH 802.11G CH06 Date: 20.NOV.2014 15:54:15




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11G CH11 Date: 20.NOV.2014 15:54:57




6DB BANDWIDTH 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:09:03




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:10:04




6DB BANDWIDTH 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:11:15




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:12:25




6DB BANDWIDTH 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:14:35




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:15:29

ANT1




6DB BANDWIDTH 802.11B CH01 Date: 20.NOV.2014 15:36:53




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11B CH06
Date: 20.NOV.2014 15:37:48




6DB BANDWIDTH 802.11B CH11
Date: 20.NOV.2014 15:38:27




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11G CH01 Date: 20.NOV.2014 16:05:17




6DB BANDWIDTH 802.11G CH06
Date: 20.NOV.2014 16:03:10




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11G CH11 Date: 20.NOV.2014 16:04:04




6DB BANDWIDTH 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:19:26




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:20:09




6DB BANDWIDTH 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:20:49




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:21:35




6DB BANDWIDTH 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:22:46




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:24:19

ANT2




6DB BANDWIDTH 802.11B CH01 Date: 20.NOV.2014 15:42:19




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11B CH06
Date: 20.NOV.2014 15:43:04




6DB BANDWIDTH 802.11B CH11
Date: 20.NOV.2014 15:43:42




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11G CH01 Date: 20.NOV.2014 16:16:15




6DB BANDWIDTH 802.11G CH06 Date: 20.NOV.2014 16:17:06




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11G CH11 Date: 20.NOV.2014 16:18:17




6DB BANDWIDTH 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:27:52




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:28:34




6DB BANDWIDTH 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:29:49




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:31:01




6DB BANDWIDTH 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:31:57



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



6DB BANDWIDTH 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:32:47

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055, ETSTW-RE 050.


FCC ID: ZTT-RTA1750

3.8 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

ANT₀




POWER DENSITY 802.11B CH01 Date: 20.NOV.2014 15:49:24




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11B CH06
Date: 20.NOV.2014 15:50:09




POWER DENSITY 802.11B CH11
Date: 20.NOV.2014 15:50:52




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11G CH01 Date: 20.NOV.2014 15:53:31




POWER DENSITY 802.11G CH06
Date: 20.NOV.2014 15:54:24




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11G CH11
Date: 20.NOV.2014 15:55:06




POWER DENSITY 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:09:12




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:10:13




POWER DENSITY 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:11:24




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:12:37




POWER DENSITY 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:14:47




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:15:41

ANT1




POWER DENSITY 802.11B CH01 Date: 20.NOV.2014 15:37:02




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11B CH06
Date: 20.NOV.2014 15:37:57




POWER DENSITY 802.11B CH11
Date: 20.NOV.2014 15:38:36




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11G CH01
Date: 20.NOV.2014 16:05:26




POWER DENSITY 802.11G CH06
Date: 20.NOV.2014 16:03:19




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11G CH11
Date: 20.NOV.2014 16:04:13




POWER DENSITY 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:19:35




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:20:18




POWER DENSITY 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:20:58




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:21:47




POWER DENSITY 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:22:58




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:24:31

ANT2




POWER DENSITY 802.11B CH01 Date: 20.NOV.2014 15:42:28




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11B CH06
Date: 20.NOV.2014 15:43:13




POWER DENSITY 802.11B CH11
Date: 20.NOV.2014 15:43:51




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11G CH01 Date: 20.NOV.2014 16:16:24




POWER DENSITY 802.11G CH06 Date: 20.NOV.2014 16:17:15




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11G CH11
Date: 20.NOV.2014 16:18:26




POWER DENSITY 802.11N 20MHZ CH01 Date: 26.NOV.2014 00:28:01




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 20MHZ CH06 Date: 26.NOV.2014 00:28:43




POWER DENSITY 802.11N 20MHZ CH11 Date: 26.NOV.2014 00:29:58




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 40MHZ CH01 Date: 26.NOV.2014 00:31:13




POWER DENSITY 802.11N 40MHZ CH04 Date: 26.NOV.2014 00:32:09



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



POWER DENSITY 802.11N 40MHZ CH07 Date: 26.NOV.2014 00:32:59



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ANT0		mW			dBm	
ANIU	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	0.054	0.058	0.055	-12.66	-12.35	-12.59
802.11n 40MHz	0.03	0.025	0.023	-15.30	-16.02	-16.36
ANT1		mW			dBm	
ANTI	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	0.167	0.063	0.053	-7.76	-11.98	-12.76
802.11n 40MHz	0.071	0.040	0.029	-11.46	-14.01	-15.31
ANT2		Mw			dBm	
ANIZ	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	0.045	0.045	0.048	-13.43	-13.51	-13.19
802.11n 40MHz	0.042	0.086	0.068	-13.74	-10.64	-11.66
Combine		mW			dBm	
Comonie	Ch Low	Ch Mid	Ch High	Ch Low	Ch Mid	Ch High
802.11n 20MHz	0.266	0.166	0.156	-5.75	-7.80	-8.07
802.11n 40MHz	0.143	0.151	0.120	-8.45	-8.21	-9.21

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055, ETSTW-RE 050

Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

3.9 Radiated Emission from Digital Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission	Field Strength	Field Strength
(MHz)	(microvolts/meter)	(dBmicrovolts/meter)
30 - 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 055, ETSTW-RE 064, ETSTW-RE 004, ETSTW-RE 030 ETSTW-RE 111

Explanation: The test results are listed in the separated test report no.: W6M21410-14564-P-15B.




Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

3.10 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.



Phase:

Condition: FCC Part 15 Class B Conduction (QP)

EUT: W6M21410-14564 Power: 120 Va.c.

M/N: Test Mode: Note:

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1526	30.45	QP	9.76	40.21	65.86	-25.65	
	0.1526	2.46	AVG	9.76	12.22	55.86	-43.64	
	0.1890	29.83	QP	9.76	39.59	64.08	-24.49	
	0.1890	16.10	AVG	9.76	25.86	54.08	-28.22	
	0.2226	28.66	QP	9.76	38.42	62.72	-24.30	
	0.2226	13.65	AVG	9.76	23.41	52.72	-29.31	
	0.4167	39.62	QP	9.77	49.39	57.51	-8.12	
	0.4167	26.14	AVG	9.77	35.91	47.51	-11.60	
	0.7384	31.52	QP	9.78	41.30	56.00	-14.70	
	0.7384	18.87	AVG	9.78	28.65	46.00	-17.35	
*	1.2065	39.67	QP	9.80	49.47	56.00	-6.53	
	1.2065	26.93	AVG	9.80	36.73	46.00	-9.27	
	1.5777	34.12	QP	9.81	43.93	56.00	-12.07	
	1.5777	19.99	AVG	9.81	29.80	46.00	-16.20	
	1.9197	33.37	QP	9.82	43.19	56.00	-12.81	
	1.9197	20.63	AVG	9.82	30.45	46.00	-15.55	



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

Site: Chamber_03

Condition: FCC Part 15 Class B Conduction (QP) Phase: N
EUT: W6M21410-14564 Power: 120 Va.c.

M/N:


Test Mode : Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	2.6938	32.92	QP	9.85	42.77	56.00	-13.23	
	2.6938	20.43	AVG	9.85	30.28	46.00	-15.72	
	4.6085	33.87	QP	9.95	43.82	56.00	-12.18	
	4.6085	22.44	AVG	9.95	32.39	46.00	-13.61	
	6.2875	32.88	QP	10.03	42.91	60.00	-17.09	
	6.2875	22.20	AVG	10.03	32.23	50.00	-17.77	
	15.4125	31.56	QP	10.17	41.73	60.00	-18.27	
	15.4125	24.71	AVG	10.17	34.88	50.00	-15.12	



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750



Site: Chamber_03

Condition: FCC Part 15 Class B Conduction (QP)

Phase: L1

EUT: W6M21410-14564

Power: 120 Va.c.

M/N:

Test Mode:

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1900	-2.91	QP	9.70	6.79	64.04	-57.25	
	0.1900	14.61	AVG	9.70	24.31	54.04	-29.73	
	0.2380	31.54	QP	9.70	41.24	62.17	-20.93	
	0.2380	16.04	AVG	9.70	25.74	52.17	-26.43	
	0.4141	40.16	QP	9.70	49.86	57.57	-7.71	
	0.4141	28.12	AVG	9.70	37.82	47.57	-9.75	
*	1.2110	40.63	QP	9.73	50.36	56.00	-5.64	
	1.2110	26.38	AVG	9.73	36.11	46.00	-9.89	
	1.5192	32.00	QP	9.74	41.74	56.00	-14.26	
	1.5192	19.37	AVG	9.74	29.11	46.00	-16.89	
	2.0120	32.28	QP	9.75	42.03	56.00	-13.97	
	2.0120	18.92	AVG	9.75	28.67	46.00	-17.33	
	2.3158	32.94	QP	9.76	42.70	56.00	-13.30	
	2.3158	19.96	AVG	9.76	29.72	46.00	-16.28	
	2.9323	32.92	QP	9.79	42.71	56.00	-13.29	
	2.9323	18.36	AVG	9.79	28.15	46.00	-17.85	



Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750 Site : Chamber_03

> Condition: FCC Part 15 Class B Conduction (QP) Phase: EUT: W6M21410-14564 Power: 120 Va.c.

M/N:

Test Mode: Note:

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	4.0505	33.53	QP	9.84	43.37	56.00	-12.63	
	4.0505	21.69	AVG	9.84	31.53	46.00	-14.47	
	4.6963	32.57	QP	9.87	42.44	56.00	-13.56	
	4.6963	19.16	AVG	9.87	29.03	46.00	-16.97	
	6.1750	31.89	QP	9.94	41.83	60.00	-18.17	
	6.1750	21.54	AVG	9.94	31.48	50.00	-18.52	

Note: 1. The formula of measured value as: Test Result = Reading + Correction Factor

- 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.
- 5. Measurement uncertainty = ± 1.41 dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
- 6. Up Line: QP Limit Line, Down Line: Ave Limit Line.

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)			
	Quasi Peak	Average		
0.15-0.5	66 to 56	56 to 46		
0.5-5	56	46		
5-30	60	50		

Test equipment used:ETSTW-CE 001, ETSTW-CE 016, ETSTW-RE 045

Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

Appendix

Measurement diagrams

Spurious Emissions radiated


Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ANT0



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.44	QP	18.01	45.45	46.00	100	125	-0.55	
*	624.8297	21.69	QP	23.98	45.67	46.00	100	60	-0.33	
	900.8617	17.06	QP	28.38	45.44	46.00	100	170	-0.56	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4817.635	50.49	peak	0.68	51.17	74.00	100	90	-22.83	
	7236.000	41.43	peak	4.30	45.73	74.00	100	185	-28.27	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	34.87	peak	7.46	42.33	74.00	100	220	-31.67	
*	12060.000	34.62	peak	13.20	47.82	74.00	100	175	-26.18	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	25.42	peak	13.24	38.66	40.00	100	220	-1.34	
	74.7094	27.37	peak	11.03	38.40	40.00	100	155	-1.60	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4823.845	54.79	peak	0.68	55.47	74.00	100	178	-18.53	
*	4823.845	53.14	AVG	0.68	53.82	54.00	100	178	-0.18	
	7236.000	44.31	peak	4.30	48.61	74.00	100	223	-25.39	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.40	peak	7.46	42.86	74.00	100	85	-31.14	
*	12060.000	35.46	peak	13.20	48.66	74.00	100	130	-25.34	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.30	QP	18.01	45.31	46.00	100	120	-0.69	
*	624.8297	21.51	QP	23.98	45.49	46.00	100	35	-0.51	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4873.748	49.19	peak	0.73	49.92	74.00	100	155	-24.08	
	7311.000	40.93	peak	4.39	45.32	74.00	100	120	-28.68	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.05	peak	7.58	42.63	74.00	100	95	-31.37	
*	12185.000	32.80	peak	13.77	46.57	74.00	100	230	-27.43	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.43	QP	13.24	39.67	40.00	100	75	-0.33	
	74.7094	28.63	QP	11.03	39.66	40.00	100	90	-0.34	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4873.882	54.05	peak	0.73	54.78	74.00	100	180	-19.22	
*	4873.882	52.90	AVG	0.73	53.63	54.00	100	180	-0.37	
	7310.621	44.00	peak	4.39	48.39	74.00	100	155	-25.61	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.07	peak	7.58	42.65	74.00	100	75	-31.35	
*	12185.000	32.73	peak	13.77	46.50	74.00	100	160	-27.50	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.50	QP	18.01	45.51	46.00	100	125	-0.49	
	624.8297	21.55	QP	23.98	45.53	46.00	100	90	-0.47	
*	900.8617	17.25	QP	28.38	45.63	46.00	100	130	-0.37	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4921.844	50.28	peak	0.80	51.08	74.00	100	170	-22.92	
	7386.000	40.59	peak	4.71	45.30	74.00	100	245	-28.70	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.06	peak	7.96	43.02	74.00	100	195	-30.98	
*	12310.000	34.29	peak	13.60	47.89	74.00	100	60	-26.11	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.42	QP	13.24	39.66	40.00	100	95	-0.34	
	74.7094	28.26	QP	11.03	39.29	40.00	100	50	-0.71	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4923.878	55.93	peak	0.81	56.74	74.00	100	188	-17.26	
*	4923.878	53.01	AVG	0.81	53.82	54.00	100	188	-0.18	
	7390.782	43.69	peak	4.73	48.42	74.00	100	235	-25.58	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.52	peak	7.96	43.48	74.00	100	175	-30.52	
*	12310.000	34.62	peak	13.60	48.22	74.00	100	250	-25.78	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.47	QP	18.01	45.48	46.00	100	35	-0.52	
*	624.8297	21.60	QP	23.98	45.58	46.00	100	60	-0.42	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.32	peak	0.68	43.00	74.00	100	175	-31.00	
*	7236.000	40.85	peak	4.30	45.15	74.00	100	160	-28.85	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.19	peak	7.46	42.65	74.00	100	220	-31.35	
*	12060.000	34.74	peak	13.20	47.94	74.00	100	195	-26.06	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	25.63	peak	13.24	38.87	40.00	100	95	-1.13	
*	74.7094	28.41	QP	11.03	39.44	40.00	100	55	-0.56	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.72	peak	0.68	43.40	74.00	100	205	-30.60	
*	7236.000	40.89	peak	4.30	45.19	74.00	100	170	-28.81	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.52	peak	7.46	42.98	74.00	100	95	-31.02	
*	12060.000	34.22	peak	13.20	47.42	74.00	100	240	-26.58	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	376.0120	27.63	QP	18.01	45.64	46.00	100	15	-0.36	
	624.8297	21.46	QP	23.98	45.44	46.00	100	110	-0.56	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	41.72	peak	0.73	42.45	74.00	100	235	-31.55	
*	7311.000	41.40	peak	4.39	45.79	74.00	100	220	-28.21	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.13	peak	7.58	42.71	74.00	100	150	-31.29	
*	12185.000	32.90	peak	13.77	46.67	74.00	100	190	-27.33	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	25.96	QP	13.24	39.20	40.00	100	125	-0.80	
	74.7094	27.93	peak	11.03	38.96	40.00	100	90	-1.04	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH6

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.82	peak	0.73	43.55	74.00	100	245	-30.45	
*	7311.000	41.35	peak	4.39	45.74	74.00	100	210	-28.26	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.97	peak	7.58	42.55	74.00	100	220	-31.45	
*	12185.000	33.76	peak	13.77	47.53	74.00	100	165	-26.47	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.33	QP	18.01	45.34	46.00	100	130	-0.66	
*	624.8297	21.37	QP	23.98	45.35	46.00	100	120	-0.65	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.33	peak	0.81	42.14	74.00	100	145	-31.86	
*	7386.000	40.32	peak	4.71	45.03	74.00	100	130	-28.97	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.30	peak	7.96	43.26	74.00	100	250	-30.74	
*	12310.000	34.06	peak	13.60	47.66	74.00	100	210	-26.34	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	25.95	QP	13.24	39.19	40.00	100	70	-0.81	
	74.7094	27.44	peak	11.03	38.47	40.00	100	165	-1.53	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH11

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	42.06	peak	0.81	42.87	74.00	100	245	-31.13	
*	7386.000	40.07	peak	4.71	44.78	74.00	100	260	-29.22	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	36.07	peak	7.96	44.03	74.00	100	220	-29.97	
*	12310.000	34.56	peak	13.60	48.16	74.00	100	195	-25.84	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	


Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ANT1



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.37	QP	18.01	45.38	46.00	100	45	-0.62	
*	624.8297	21.43	QP	23.98	45.41	46.00	100	120	-0.59	
	900.8617	16.93	QP	28.38	45.31	46.00	100	165	-0.69	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4817.635	51.58	peak	0.68	52.26	74.00	100	80	-21.74	
	7238.477	44.77	peak	4.30	49.07	74.00	100	175	-24.93	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9646.794	38.70	peak	7.46	46.16	74.00	100	230	-27.84	
*	12060.000	34.82	peak	13.20	48.02	74.00	100	245	-25.98	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	74.7094	28.25	QP	11.03	39.28	40.00	100	115	-0.72	
	624.8297	20.07	peak	23.98	44.05	46.00	100	210	-1.95	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4817.635	53.77	peak	0.68	54.45	74.00	100	275	-19.55	
*	4817.635	52.75	AVG	0.68	53.43	54.00	100	275	-0.57	
	7238.477	49.63	peak	4.30	53.93	74.00	100	230	-20.07	
	7238.477	48.95	AVG	4.30	53.25	54.00	100	230	-0.75	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9647.654	47.62	peak	7.46	55.08	74.00	100	202	-18.92	
*	9647.654	45.73	AVG	7.46	53.19	54.00	100	202	-0.81	
	12083.667	35.22	peak	13.36	48.58	74.00	100	155	-25.42	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.40	QP	18.01	45.41	46.00	100	85	-0.59	
*	624.8297	21.71	QP	23.98	45.69	46.00	100	160	-0.31	
	900.8617	17.09	QP	28.38	45.47	46.00	100	125	-0.53	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4873.748	49.74	peak	0.73	50.47	74.00	100	210	-23.53	
	7318.637	43.06	peak	4.42	47.48	74.00	100	245	-26.52	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.43	peak	7.58	43.01	74.00	100	175	-30.99	
*	12185.000	33.29	peak	13.77	47.06	74.00	100	90	-26.94	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	26.10	QP	13.24	39.34	40.00	100	30	-0.66	
*	74.7094	28.41	QP	11.03	39.44	40.00	100	65	-0.56	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4873.748	53.29	peak	0.73	54.02	74.00	100	257	-19.98	
*	4873.748	52.35	AVG	0.73	53.08	54.00	100	257	-0.92	
	7310.621	51.65	peak	4.39	56.04	74.00	100	219	-17.96	
	7310.621	48.60	AVG	4.39	52.99	54.00	100	219	-1.01	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9741.984	45.96	peak	7.55	53.51	74.00	100	245	-20.49	
*	9741.984	44.99	AVG	7.55	52.54	54.00	100	245	-1.46	
	12185.000	32.87	peak	13.77	46.64	74.00	100	175	-27.36	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.42	QP	18.01	45.43	46.00	100	220	-0.57	
*	624.8297	21.55	QP	23.98	45.53	46.00	100	195	-0.47	
	900.8617	17.02	QP	28.38	45.40	46.00	100	60	-0.60	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4921.844	49.85	peak	0.80	50.65	74.00	100	210	-23.35	
	7386.000	42.06	peak	4.71	46.77	74.00	100	145	-27.23	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.43	peak	7.96	43.39	74.00	100	75	-30.61	
*	12310.000	35.28	peak	13.60	48.88	74.00	100	160	-25.12	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.31	QP	13.24	39.55	40.00	100	130	-0.45	
	74.7094	28.22	QP	11.03	39.25	40.00	100	125	-0.75	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4923.830	55.13	peak	0.81	55.94	74.00	100	114	-18.06	
*	4923.830	52.26	AVG	0.81	53.07	54.00	100	114	-0.93	
	7390.782	44.20	peak	4.73	48.93	74.00	100	235	-25.07	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.75	peak	7.96	43.71	74.00	100	245	-30.29	
*	12310.000	34.79	peak	13.60	48.39	74.00	100	225	-25.61	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.23	QP	18.01	45.24	46.00	100	75	-0.76	
*	624.8297	21.35	QP	23.98	45.33	46.00	100	85	-0.67	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.09	peak	0.68	42.77	74.00	100	235	-31.23	
*	7236.000	41.11	peak	4.30	45.41	74.00	100	170	-28.59	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	36.50	peak	7.46	43.96	74.00	100	95	-30.04	
*	12060.000	34.87	peak	13.20	48.07	74.00	100	140	-25.93	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	25.96	QP	13.24	39.20	40.00	100	105	-0.80	
*	74.7094	28.37	QP	11.03	39.40	40.00	100	90	-0.60	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	41.97	peak	0.68	42.65	74.00	100	230	-31.35	
*	7236.000	41.08	peak	4.30	45.38	74.00	100	195	-28.62	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.38	peak	7.46	42.84	74.00	100	85	-31.16	
*	12060.000	34.52	peak	13.20	47.72	74.00	100	110	-26.28	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.10	QP	18.01	45.11	46.00	100	75	-0.89	
*	624.8297	21.72	QP	23.98	45.70	46.00	100	135	-0.30	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.31	peak	0.73	43.04	74.00	100	165	-30.96	
*	7311.000	41.51	peak	4.39	45.90	74.00	100	190	-28.10	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.24	peak	7.58	42.82	74.00	100	220	-31.18	
*	12185.000	34.25	peak	13.77	48.02	74.00	100	130	-25.98	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	25.93	QP	13.24	39.17	40.00	100	95	-0.83	
	74.7094	27.99	QP	11.03	39.02	40.00	100	130	-0.98	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.40	peak	0.73	43.13	74.00	100	75	-30.87	
*	7311.000	41.27	peak	4.39	45.66	74.00	100	135	-28.34	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.87	peak	7.58	42.45	74.00	100	180	-31.55	
*	12185.000	33.57	peak	13.77	47.34	74.00	100	225	-26.66	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	376.0120	27.66	QP	18.01	45.67	46.00	100	145	-0.33	
	624.8297	21.26	QP	23.98	45.24	46.00	100	70	-0.76	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.92	peak	0.81	42.73	74.00	100	155	-31.27	
*	7386.000	40.34	peak	4.71	45.05	74.00	100	120	-28.95	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.10	peak	7.96	43.06	74.00	100	210	-30.94	
*	12310.000	35.40	peak	13.60	49.00	74.00	100	175	-25.00	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	26.15	QP	13.24	39.39	40.00	100	95	-0.61	
*	74.7094	28.46	QP	11.03	39.49	40.00	100	120	-0.51	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.75	peak	0.81	42.56	74.00	100	190	-31.44	
*	7386.000	40.40	peak	4.71	45.11	74.00	100	175	-28.89	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	34.85	peak	7.96	42.81	74.00	100	220	-31.19	
*	12310.000	34.56	peak	13.60	48.16	74.00	100	155	-25.84	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l


Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ANT2



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	376.0120	27.36	QP	18.01	45.37	46.00	100	125	-0.63	
	624.8297	21.26	QP	23.98	45.24	46.00	100	40	-0.76	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4817.635	49.75	peak	0.68	50.43	74.00	100	90	-23.57	
	7236.000	41.34	peak	4.30	45.64	74.00	100	175	-28.36	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.36	peak	7.46	42.82	74.00	100	225	-31.18	
*	12060.000	34.47	peak	13.20	47.67	74.00	100	140	-26.33	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	25.97	QP	13.24	39.21	40.00	100	60	-0.79	
*	74.7094	28.41	QP	11.03	39.44	40.00	100	175	-0.56	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4817.635	54.31	peak	0.68	54.99	74.00	100	227	-19.01	
*	4817.635	52.36	AVG	0.68	53.04	54.00	100	227	-0.96	
	7238.477	44.31	peak	4.30	48.61	74.00	100	135	-25.39	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9646.794	37.91	peak	7.46	45.37	74.00	100	215	-28.63	
*	12060.000	34.74	peak	13.20	47.94	74.00	100	240	-26.06	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.05	QP	18.01	45.06	46.00	100	15	-0.94	
*	624.8297	21.39	QP	23.98	45.37	46.00	100	90	-0.63	
	900.8617	16.85	QP	28.38	45.23	46.00	100	35	-0.77	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4873.748	49.32	peak	0.73	50.05	74.00	100	120	-23.95	
	7311.000	41.00	peak	4.39	45.39	74.00	100	135	-28.61	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.07	peak	7.58	42.65	74.00	100	95	-31.35	
*	12185.000	33.39	peak	13.77	47.16	74.00	100	170	-26.84	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.36	QP	13.24	39.60	40.00	100	75	-0.40	
	74.7094	28.01	QP	11.03	39.04	40.00	100	135	-0.96	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2359.939	59.44	peak	-4.90	54.54	74.00	100	285	-19.46	
*	2359.939	57.89	AVG	-4.90	52.99	54.00	100	285	-1.01	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4873.748	53.75	peak	0.73	54.48	74.00	100	243	-19.52	
*	4873.748	52.57	AVG	0.73	53.30	54.00	100	243	-0.70	
	7310.621	43.68	peak	4.39	48.07	74.00	100	210	-25.93	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9741.984	39.06	peak	7.55	46.61	74.00	100	170	-27.39	
*	12185.000	33.97	peak	13.77	47.74	74.00	100	95	-26.26	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	376.0120	27.64	QP	18.01	45.65	46.00	100	75	-0.35	
	624.8297	21.32	QP	23.98	45.30	46.00	100	110	-0.70	
	900.8617	16.79	QP	28.38	45.17	46.00	100	50	-0.83	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4921.844	50.44	peak	0.80	51.24	74.00	100	175	-22.76	
	7386.000	40.63	peak	4.71	45.34	74.00	100	150	-28.66	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.60	peak	7.96	43.56	74.00	100	210	-30.44	
*	12310.000	35.77	peak	13.60	49.37	74.00	100	235	-24.63	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	25.34	peak	13.24	38.58	40.00	100	160	-1.42	
*	74.7094	28.42	QP	11.03	39.45	40.00	100	210	-0.55	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2358.717	57.71	peak	-4.90	52.81	74.00	100	237	-21.19	
*	2358.717	57.32	AVG	-4.90	52.42	54.00	100	237	-1.58	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4921.844	53.30	peak	0.80	54.10	74.00	100	267	-19.90	
*	4921.844	52.19	AVG	0.80	52.99	54.00	100	267	-1.01	
	7386.000	44.62	peak	4.71	49.33	74.00	100	155	-24.67	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.25	peak	7.96	43.21	74.00	100	185	-30.79	
*	12310.000	35.03	peak	13.60	48.63	74.00	100	220	-25.37	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11b CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.33	QP	18.01	45.34	46.00	100	45	-0.66	
	624.8297	21.29	QP	23.98	45.27	46.00	100	110	-0.73	
*	900.8617	17.13	QP	28.38	45.51	46.00	100	65	-0.49	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	41.73	peak	0.68	42.41	74.00	100	125	-31.59	
*	7236.000	41.03	peak	4.30	45.33	74.00	100	190	-28.67	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	36.02	peak	7.46	43.48	74.00	100	220	-30.52	
*	12060.000	34.92	peak	13.20	48.12	74.00	100	145	-25.88	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.08	QP	13.24	39.32	40.00	100	35	-0.68	
	74.7094	28.17	QP	11.03	39.20	40.00	100	110	-0.80	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH1

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.43	peak	0.68	43.11	74.00	100	105	-30.89	
*	7236.000	41.16	peak	4.30	45.46	74.00	100	160	-28.54	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.46	peak	7.46	42.92	74.00	100	220	-31.08	
*	12060.000	35.25	peak	13.20	48.45	74.00	100	135	-25.55	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.05	QP	18.01	45.06	46.00	100	75	-0.94	
*	624.8297	21.37	QP	23.98	45.35	46.00	100	145	-0.65	
	900.8617	16.89	QP	28.38	45.27	46.00	100	30	-0.73	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.43	peak	0.73	43.16	74.00	100	145	-30.84	
*	7311.000	41.11	peak	4.39	45.50	74.00	100	230	-28.50	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.65	peak	7.58	42.23	74.00	100	220	-31.77	
*	12185.000	32.87	peak	13.77	46.64	74.00	100	175	-27.36	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.23	QP	13.24	39.47	40.00	100	95	-0.53	
	74.7094	28.20	QP	11.03	39.23	40.00	100	135	-0.77	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	41.89	peak	0.73	42.62	74.00	100	235	-31.38	
*	7311.000	40.67	peak	4.39	45.06	74.00	100	190	-28.94	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.72	peak	7.58	43.30	74.00	100	170	-30.70	
*	12185.000	32.55	peak	13.77	46.32	74.00	100	225	-27.68	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.47	QP	18.01	45.48	46.00	100	75	-0.52	
	624.8297	21.47	QP	23.98	45.45	46.00	100	220	-0.55	
*	900.8617	17.19	QP	28.38	45.57	46.00	100	15	-0.43	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.77	peak	0.81	42.58	74.00	100	245	-31.42	
*	7386.000	41.13	peak	4.71	45.84	74.00	100	130	-28.16	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	34.73	peak	7.96	42.69	74.00	100	115	-31.31	
*	12310.000	34.59	peak	13.60	48.19	74.00	100	90	-25.81	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.29	QP	13.24	39.53	40.00	100	55	-0.47	
	74.7094	28.02	QP	11.03	39.05	40.00	100	90	-0.95	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.60	peak	0.81	42.41	74.00	100	220	-31.59	
*	7386.000	40.57	peak	4.71	45.28	74.00	100	195	-28.72	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	36.17	peak	7.96	44.13	74.00	100	175	-29.87	
*	12310.000	34.51	peak	13.60	48.11	74.00	100	140	-25.89	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l


Registration number: W6M21410-14564-C-1-R1

FCC ID: ZTT-RTA1750

ANT0 + ANT1 + ANT2



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	376.0120	27.21	QP	18.01	45.22	46.00	100	35	-0.78	
	624.8297	21.22	QP	23.98	45.20	46.00	100	110	-0.80	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.14	peak	0.68	42.82	74.00	100	155	-31.18	
*	7236.000	41.15	peak	4.30	45.45	74.00	100	220	-28.55	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	37.10	peak	7.46	44.56	74.00	100	215	-29.44	
*	12060.000	35.34	peak	13.20	48.54	74.00	100	170	-25.46	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.17	QP	13.24	39.41	40.00	100	135	-0.59	
	74.7094	28.20	QP	11.03	39.23	40.00	100	60	-0.77	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	43.36	peak	0.68	44.04	74.00	100	235	-29.96	
*	7236.000	41.00	peak	4.30	45.30	74.00	100	190	-28.70	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.69	peak	7.46	43.15	74.00	100	85	-30.85	
*	12060.000	36.00	peak	13.20	49.20	74.00	100	150	-24.80	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.14	QP	18.01	45.15	46.00	100	85	-0.85	
*	624.8297	21.42	QP	23.98	45.40	46.00	100	50	-0.60	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.77	peak	0.73	43.50	74.00	100	75	-30.50	
*	7311.000	40.93	peak	4.39	45.32	74.00	100	190	-28.68	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.51	peak	7.58	43.09	74.00	100	145	-30.91	
*	12185.000	34.91	peak	13.77	48.68	74.00	100	210	-25.32	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	74.7094	27.74	peak	11.03	38.77	40.00	100	35	-1.23	
	624.8297	20.59	peak	23.98	44.57	46.00	100	170	-1.43	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.54	peak	0.73	43.27	74.00	100	215	-30.73	
*	7311.000	41.30	peak	4.39	45.69	74.00	100	160	-28.31	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.69	peak	7.58	42.27	74.00	100	220	-31.73	
*	12185.000	32.86	peak	13.77	46.63	74.00	100	70	-27.37	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH6

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.24	QP	18.01	45.25	46.00	100	50	-0.75	
*	624.8297	21.64	QP	23.98	45.62	46.00	100	125	-0.38	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	42.26	peak	0.81	43.07	74.00	100	215	-30.93	
*	7386.000	40.56	peak	4.71	45.27	74.00	100	160	-28.73	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.66	peak	7.96	43.62	74.00	100	220	-30.38	
*	12310.000	34.91	peak	13.60	48.51	74.00	100	190	-25.49	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	26.09	QP	13.24	39.33	40.00	100	10	-0.67	
	74.7094	28.25	QP	11.03	39.28	40.00	100	35	-0.72	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11n 20M CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	42.13	peak	0.81	42.94	74.00	100	165	-31.06	
*	7386.000	40.74	peak	4.71	45.45	74.00	100	240	-28.55	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.28	peak	7.96	43.24	74.00	100	195	-30.76	
*	12310.000	35.33	peak	13.60	48.93	74.00	100	230	-25.07	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 20M CH11

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.11	QP	18.01	45.12	46.00	100	95	-0.88	
*	624.8297	21.68	QP	23.98	45.66	46.00	100	10	-0.34	
	900.8617	17.09	QP	28.38	45.47	46.00	100	60	-0.53	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4844.000	42.10	peak	0.70	42.80	74.00	100	245	-31.20	
*	7266.000	41.51	peak	4.32	45.83	74.00	100	210	-28.17	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9688.000	35.90	peak	7.36	43.26	74.00	100	175	-30.74	
*	12110.000	33.92	peak	13.50	47.42	74.00	100	190	-26.58	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	26.07	QP	13.24	39.31	40.00	100	55	-0.69	
*	74.7094	28.40	QP	11.03	39.43	40.00	100	60	-0.57	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2380.941	62.07	peak	-4.80	57.27	74.00	100	285	-16.73	
*	2380.941	57.15	AVG	-4.80	52.35	54.00	100	285	-1.65	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4844.000	42.24	peak	0.70	42.94	74.00	100	245	-31.06	
*	7266.000	41.73	peak	4.32	46.05	74.00	100	160	-27.95	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9688.000	35.81	peak	7.36	43.17	74.00	100	225	-30.83	
*	12110.000	34.67	peak	13.50	48.17	74.00	100	180	-25.83	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

NA I-	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH1

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	376.0120	27.03	QP	18.01	45.04	46.00	100	65	-0.96	
*	624.8297	21.67	QP	23.98	45.65	46.00	100	90	-0.35	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.03	peak	0.73	42.76	74.00	100	215	-31.24	
*	7311.000	41.17	peak	4.39	45.56	74.00	100	160	-28.44	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.82	peak	7.58	42.40	74.00	100	220	-31.60	
*	12185.000	33.26	peak	13.77	47.03	74.00	100	235	-26.97	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1583	25.42	peak	13.24	38.66	40.00	100	245	-1.34	
*	74.7094	27.87	peak	11.03	38.90	40.00	100	170	-1.10	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11n 40M CH4

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.77	peak	0.73	43.50	74.00	100	235	-30.50	
*	7311.000	40.87	peak	4.39	45.26	74.00	100	160	-28.74	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.02	peak	7.58	42.60	74.00	100	245	-31.40	
*	12185.000	33.01	peak	13.77	46.78	74.00	100	190	-27.22	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH4

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	376.0120	27.29	QP	18.01	45.30	46.00	100	75	-0.70	
	624.8297	21.26	QP	23.98	45.24	46.00	100	130	-0.76	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4904.000	41.63	peak	0.77	42.40	74.00	100	230	-31.60	
*	7356.000	41.39	peak	4.58	45.97	74.00	100	175	-28.03	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9808.000	35.44	peak	7.88	43.32	74.00	100	175	-30.68	
*	12260.000	34.28	peak	13.64	47.92	74.00	100	150	-26.08	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	59.1583	25.89	QP	13.24	39.13	40.00	100	85	-0.87	
	74.7094	27.95	peak	11.03	38.98	40.00	100	110	-1.02	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11n 40M CH7

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4904.000	42.04	peak	0.77	42.81	74.00	100	185	-31.19	
*	7356.000	41.66	peak	4.58	46.24	74.00	100	210	-27.76	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9808.000	36.78	peak	7.88	44.66	74.00	100	230	-29.34	
*	12260.000	33.75	peak	13.64	47.39	74.00	100	215	-26.61	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical


EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21410-14564 Power: 120 Va.c. M/N: Distance: 3m

Test Mode: TX 802.11n 40M CH7

	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	1
Mk.	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l