



RF Exposure Evaluation Report

Equipment : High Power AC2200 Tri-Band Wi-Fi Router
Brand Name : amped wireless
Model No. : RTA2200T
FCC ID : ZTT-RTA2200T
Standard : 47 CFR Part 2.1091
Applicant : Amped Wireless
13089 Peyton Dr. #C307 Chino Hills, CA 91709 USA
Manufacturer : Amped Wireless
13089 Peyton Dr. #C307 Chino Hills, CA 91709 USA

The product sample received on Nov. 09, 2016 and completely tested on Dec. 13, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Cliff Chang
SPORTON INTERNATIONAL INC.





TABLE OF CONTENTS

1	GENERAL DESCRIPTION	4
1.1	EUT General Information	4
1.2	Testing Location	4
2	MAXIMUM PERMISSIBLE EXPOSURE	5
2.1	Limit of Maximum Permissible Exposure	5
2.2	MPE Calculation Method	5
2.3	Calculated Result and Limit.....	6

REVISION HISTORY

[illegible]

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D (Radio 1)	4.23	27.65	31.88	1.5417	20	0.30671	1	0.30671
5.2G;D1D (Radio 1)	7.30	24.34	31.64	1.45881	20	0.29022	1	0.29022
5.8G;D1D (Radio 2)	5.69	25.26	30.95	1.24451	20	0.24759	1	0.24759
							Sum Ratio	0.84452
							Ratio Limit	1