



SGS-CSTC Standards Technical Services Co., Ltd.

198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology
Development District, Guangzhou, China 510663
Tel: +86 20 82155555 Fax: +86 20 82075059
Email: sgs_internet_operations@sgs.com
FEDERAL COMMUNICATIONS COMMISSION
Registration number: 282399

Report No.: GZEM110700265901

Page: 1 of 16

FCC ID: ZU7138294427778

TEST REPORT

Application No.:	GZEM1107002659RF
Applicant:	DONGLIN TOYS FACTORY
FCC ID:	ZU7138294427778
Product Name:	R/C CAR SERIES
Product Description:	Radio toys with 27.145MHz as a carrier.
Model No.:	DL904, DL904L, DL9004, DL9004L, DL905, DL905L, DL9005, DL9005L, DL906, DL906L, DL9006, DL9006L, DL907, DL907L, DL9007, DL9007L, DL908, DL908L, DL9008, DL9008L, DL909, DL909L, DL9009, DL9009L, DL910, DL910L, DL9010, DL9010L, DL901L, DL902. ♣
♣	Please refer to section 3 of this report for details
Standards:	FCC PART 15 SUBPART C:2010 section 15.227 ANSI C63.10:2009
Date of Receipt:	2011-07-19
Date of Test:	2011-07-22 to 2011-07-27
Date of Issue:	2011-08-15
Test Result :	PASS *

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.
Please refer to section 3 of this report for further details.

Strong Yao
2011 Aug.

Strong Yao

Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2011-08-15		Original

Authorized for issue by:			
Tested By	 (Storm Shu) /Project Engineer	2011-07-22 to 2011-07-27 Date	
Prepared By	 (Millie Li) /Clerk	2011-08-15 Date	
Checked By	 (Strong Yao)/Reviewer	2011-08-15 Date	



3 Test Summary

Test	Test Requirement	Test method	Result
Radiated Emission (30 MHz to 1 GHz)	FCC PART 15 C section 15.227	ANSI C 63.10: Clasue 6.4, 6.5	PASS **
Occupied Bandwidth	FCC PART 15 C section 15.215	ANSI C 63.10 Clasue 6.9	PASS
Label Requirement	FCC PART 15 C section 15.19	N/A	N/A
Remark:			
N/A: not applicable. Refer to the relative section for the details.			
Tx: In this whole report Tx (or tx) means Transmitter.			
Rx: In this whole report Rx (or rx) means Receiver.			
RF: In this whole report RF means Radio Frequency.			
♣Model No.: DL904, DL904L, DL9004, DL9004L, DL905, DL905L, DL9005, DL9005L, DL906, DL906L, DL9006, DL9006L, DL907, DL907L, DL9007, DL9007L, DL908, DL908L, DL9008, DL9008L, DL909, DL909L , DL9009, DL9009L, DL910, DL910L, DL9010, DL9010L, DL901L, DL902.			
According to the confirmation from the applicant, all models are identical in interior structure, electrical circuits, components and appearance with different model names for the marketing requirement.			
Therefore only one item DL909L was tested in this report.			
** The EUT passed Radiated Emission (30 MHz to 1 GHz) test after retest.			



4 Contents

1	COVER PAGE	1
2	VERSION	2
3	TEST SUMMARY	3
4	CONTENTS	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION.....	5
5.2	GENERAL DESCRIPTION OF E.U.T.....	5
5.3	DETAILS OF E.U.T.	5
5.4	DESCRIPTION OF SUPPORT UNITS.....	5
5.5	DEVIATION FROM STANDARDS	5
5.6	ABNORMALITIES FROM STANDARD CONDITIONS	5
5.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5.8	TEST LOCATION	5
5.9	TEST FACILITY	6
6	EQUIPMENT USED DURING TEST.....	7
7	TEST RESULTS	8
7.1	E.U.T. TEST CONDITIONS	8
7.2	ANTENNA REQUIREMENT	9
7.3	RADIATED EMISSIONS.....	10
7.4	OCCUPIED BANDWIDTH.....	15



5 General Information

5.1 Client Information

Applicant: DONGLIN TOYS FACTORY
Address of Applicant: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA

5.2 General Description of E.U.T.

Product Name: R/C CAR SERIES
Model No.: DL904, DL904L, DL9004, DL9004L, DL905, DL905L, DL9005, DL9005L, DL906, DL906L, DL9006, DL9006L, DL907, DL907L, DL9007, DL9007L, DL908, DL908L, DL9008, DL9008L, DL909, DL909L, DL9009, DL9009L, DL910, DL910L, DL9010, DL9010L, DL901L, DL902.

5.3 Details of E.U.T.

Modulation and Antenna Type: The Tx is a ASK modulation by internal signal with an dedicated antenna.
Power Supply: DC 3.0 V (2 x 1.5 V size 'AA' batteries)
Power cord: N/A

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Deviation from Standards

None.

5.6 Abnormalities from Standard Conditions

The EUT passed Radiated Emission (30 MHz to 1 GHz) test after retest.

5.7 Other Information Requested by the Customer

None.

5.8 Test Location

All tests were performed at:
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663
Tel: +86 20 82155555 Fax: +86 20 82075059
No tests were sub-contracted.



5.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460 and C-2584)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460 and C-2584 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully complies with the requirements of ISO/IEC 17025:2005, the Basic Rules, IEC 61010-1:2006-10 and Rule of procedure IEC 61010-2:2006-10, and the relevant IEC 61010-2 Scheme Operational documents.



6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2011-09-06	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2012-01-17	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	10036	2012-06-01	1Y
EMC0514	Coaxial cable	SGS	N/A	N/A	2011-12-08	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9163	9163-450	2011-10-28	1Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2011-12-20	1Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2011-12-20	1Y
EMC2026	Horn Antenna 1-18GHz	R&S	BBHA 9120D	9120D-841	2011-10-28	1Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2011-09-11	1Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2012-01-17	1Y
EMC0049	Amplifier	Agilent	8447D	2944A10862	2012-04-21	1Y
EMC0075	310N Amplifier	Sonama	310N	272683	2011-10-25	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2011-11-17	1Y
EMC2041	Broad-Band Horn Antenna(14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9170	9170-375	2012-06-01	1Y
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	2012-05-10	2Y

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0006	DMM	Fluke	73	70681569	2011-12-16	1Y
EMC0007	DMM	Fluke	73	70671122	2011-12-16	1Y



7 Test Results

7.1 E.U.T. test conditions

Power supply:	DC 3.0 V (new battery)
Requirements:	15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.
Type of antenna:	Integral
Operating Environment:	
Temperature:	22-25.0 °C
Humidity:	48-55% RH
Atmospheric Pressure:	1001-1010 mbar
Test frequencies and frequency range:	<p>According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:</p> <p>According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:</p>

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

Remark: Test frequency is 27.145 MHz.

7.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna

The antenna is an monopole Antenna integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.



Test result: The unit does meet the FCC requirements.



7.3 Radiated Emissions

Test Requirement: FCC Part 15 C section 15.227
Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6
Measurement Distance: 3 m (Semi-Anechoic Chamber)
Test Status: Test in transmitting mode.

Requirements:

the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

15.227(a): The field strength of any emission within this band shall not exceed 10,000 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in Section 15.35 for limiting peak emissions apply.

15.227(b) : The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.

Out of band emissions shall not exceed:

Frequency range(MHz)	Quasi-peak limits dB (μV/m)
30 to 88	40
88 to 216	43.5
216 to 960	46
Above 960	54

At transitional frequencies the lower limit applies.

Test Procedure:

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna. The center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2) 30 MHz to 1 GHz emissions:


For testing performed with the bi-log type antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

Detector:


Test Receiver test setup	Detector	
	Peak	Average
RBW	120 kHz for $f < 1$ GHz	120 kHz for $f < 1$ GHz
VBW	\geq RBW	\geq RBW
Sweep	auto	auto
Detector function	peak	AV
Trace	max hold	max hold

Test Configuration:

- 1) 9 kHz to 30 MHz emissions:



- 2) 30 MHz to 1 GHz emissions:



**1) Fundamental emission:****Antenna polarization: Horizontal:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark
27.145	80.45	9.50	0.60	70.35	100.0	-29.65	Peak
27.145	77.78	9.50	0.60	67.68	80.0	-12.32	Average

Antenna polarization: Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark
27.145	88.35	9.50	0.60	78.25	100.0	-21.75	Peak
27.145	85.73	9.50	0.60	75.63	80.0	-4.37	Average

Y: rotate EUT by 90° vertically.

X: rotate EUT by 90° clockwise.

Z: EUT as Radiated Emission test setup photograph in section 8 of this report.

Remark: Radiated Emission test setup photograph in section 8 of this report is the worst case and reported.

2) other emissions:

The receive was scanned from 30 MHz to 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. The worst case emissions were reported.

An initial pre-scan was performed in the 3 m chamber using the spectrum analyzer in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bilog antenna with 2 orthogonal polarities.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Peramplifier Factor.




The following test results were performed on the EUT.

Test the EUT in transmitting mode:

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq	Read	Antenna	Cable	Preamp	Limit	Over	
MHz	Level	Factor	Loss	Factor	Level	Line	Limit
MHz	dB μ V	dB/m	dB	dB	dB μ V/m	dB μ V/m	dB
54.290	47.03	4.42	0.70	27.86	24.29	40.00	-15.71
81.435	30.67	6.68	0.90	27.74	10.51	40.00	-29.49
108.580	31.02	11.81	1.04	27.63	16.25	43.50	-27.25
135.725	31.13	11.62	1.15	27.49	16.41	43.50	-27.09
162.870	29.72	8.90	1.23	27.37	12.48	43.50	-31.02
190.015	30.78	8.40	1.28	27.27	13.19	43.50	-30.31

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Read Antenna								
Freq	Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
54.290	34.02	4.42	0.70	27.86	11.28	40.00	-28.72	QP
81.435	30.17	6.68	0.90	27.74	10.01	40.00	-29.99	QP
108.580	31.20	11.81	1.04	27.63	16.43	43.50	-27.07	QP
135.725	29.64	11.62	1.15	27.49	14.93	43.50	-28.57	QP
162.870	31.26	8.90	1.23	27.37	14.01	43.50	-29.49	QP
190.015	30.46	8.40	1.28	27.27	12.87	43.50	-30.63	QP

Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.



7.4 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.215

Test Method: ANSI C63.10: Clause 6.9

Test Status: Test in transmitting mode.

Requirements:

15.215(c), Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure:

The useful radiated emission from the EUT was detected by the spectrum analyzer with peak detector. Record the 20 dB bandwidth of the carrier.

The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector. The vertical Scale is set to 10dB per division. The horizontal scale is set to 20KHz per division. Read the down 20dB bandwidth of the carrier.

Set the spectrum analyzer: start at 26.96MHz and stop at 27.28MHz


Set the spectrum analyzer: RBW = 1 kHz, VBW = 3 kHz

Sweep = auto; Detector Function = Peak. Trace = Max Hold.

Mark the peak frequency and -20dB points bandwidth.



Test plot as below:



Date: 29.JUL.2011 11:33:49

20dB bandwidth lower frequency : 27.14220441MHz

20dB bandwidth upper frequency : 27.14861723MHz

--The End of Report--