

IEEE C95.1**KDB 447498 D03****47 C.F.R. Part 1, Subpart I, Section 1.1310****47 C.F.R. Part 2, Subpart J, Section 2.1091****RF EXPOSURE REPORT****For****PANEL PC****Model: VT1020-ABCXXXXXX**

(A for power input voltage: can be "L" or "H", B for touch screen type: can be "R" or blank, C for defrost function: can be "D" or blank, X for marketing used only : can be alphanumeric or blank)

Trade Name: Ubiquconn**Issued for****Ubiquconn Technology, Inc.****8F, No. 300, Yang Guang St., NeiHu. Taipei, Taiwan, 11491****Issued by****Compliance Certification Services Inc.****Hsinchu Lab.****NO. 989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)****<http://www.ccsrf.com>****service@ccsrf.com****Issued Date: December 08, 2015**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	12/08/2015	Initial Issue	All Page	Gloria Chang

TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION.....	4
3. TEST RESULTS	6
4. MAXIMUM PERMISSIBLE EXPOSURE.....	7

1. Limit

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT Specification

Product Name	PANEL PC
Model Number	VT1020-ABCXXXXXX (A for power input voltage: can be "L" or "H", B for touch screen type: can be "R" or blank, C for defrost function: can be "D" or blank, X for marketing used only: can be alphanumeric or blank)
Identify Number	T151020D04
Received Date	October 20, 2015
Frequency band (Operating)	<input checked="" type="checkbox"/> 802.11b/g/gn HT20: 2412MHz ~ 2462MHz 802.11gn HT40: 2422MHz ~ 2452MHz 802.11a, 802.11ac VHT20: 5180 MHz ~ 5240 MHz / 5260 MHz ~ 5320 MHz / 5500 MHz ~ 5700 MHz / 5745 MHz ~ 5825 MHz 802.11ac VHT40: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795 MHz 802.11ac VHT80: 5210 MHz / 5290 MHz / 5530 MHz / 5775 MHz Bluetooth 2.1 + EDR / 4.0: 2402 ~ 2480 MHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna Specification	Dipole Antenna × 2 (External), 5GHz: Antenna 1(Chain A), Antenna Gain 5.50 dBi (Numeric gain: 3.55) 5GHz: Antenna 2(Chain B), Antenna Gain 5.50 dBm (Numeric gain: 3.55) 2.4GHz: Antenna 1(Chain A), Antenna Gain 5.00 dBi (Numeric gain: 3.16) 2.4GHz: Antenna 2(Chain B), Antenna Gain 5.00 dBm (Numeric gain: 3.16) PCB Antenna × 2 (Internal), 5GHz: Antenna 1(Chain A), Antenna Gain 4.73 dBi (Numeric gain: 2.97) 5GHz: Antenna 2(Chain B), Antenna Gain 5.39 dBm (Numeric gain: 3.46) 2.4GHz: Antenna 1(Chain A), Antenna Gain 3.17 dBi (Numeric gain: 2.07) 2.4GHz: Antenna 2(Chain B), Antenna Gain 3.21 dBm (Numeric gain: 2.09)

Maximum Peak output power	2.4G	
	Bluetooth 3.0 Mode :	2.65 dBm (1.841 mW)
	Bluetooth 4.0 Mode :	5.47 dBm (3.524 mW)
	IEEE 802.11b Mode:	18.46 dBm (70.146 mW)
	IEEE 802.11g Mode:	20.50 dBm (112.202 mW)
	IEEE 802.11gn HT 20 Mode:	23.24 dBm (210.863 mW)
	IEEE 802.11gn HT 40 Mode:	18.98 dBm (79.068 mW)
	5G UNII Band 1	
	IEEE 802.11a Mode:	14.73 dBm (29.717 mW)
	IEEE 802.11ac VHT20 Mode:	16.71 dBm (46.881 mW)
	IEEE 802.11ac VHT40 Mode:	16.35 dBm (43.152 mW)
	IEEE 802.11ac VHT80 Mode:	10.43 dBm (11.041 mW)
	5G UNII Band 2A	
	IEEE 802.11a Mode:	15.77 dBm (37.757 mW)
	IEEE 802.11ac VHT20 Mode:	17.70 dBm (58.884 mW)
	IEEE 802.11ac VHT40 Mode:	17.18 dBm (52.240 mW)
	IEEE 802.11ac VHT80 Mode:	11.80 dBm (15.136 mW)
	5G UNII Band 2C	
	IEEE 802.11a Mode:	15.51 dBm (35.563 mW)
	IEEE 802.11ac VHT20 Mode:	16.75 dBm (47.315 mW)
	IEEE 802.11ac VHT40 Mode:	17.25 dBm (53.088 mW)
	IEEE 802.11ac VHT80 Mode:	12.88 dBm (19.409 mW)
	5G UNII Band 3	
	IEEE 802.11a Mode:	15.01 dBm (31.696 mW)
	IEEE 802.11ac VHT20 Mode:	16.79 dBm (47.753 mW)
	IEEE 802.11ac VHT40 Mode:	16.64 dBm (46.132 mW)
	IEEE 802.11ac VHT80 Mode:	10.67 dBm (11.668 mW)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation*	
	<input type="checkbox"/> SAR Evaluation	
	<input type="checkbox"/> N/A	

3. Test Results

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in watts / meter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2462	70.146	3.16	20	0.0441	1

IEEE 802.11g mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	112.202	3.16	20	0.0706	1

IEEE 802.11gn HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	210.863	3.16	20	0.1326	1

IEEE 802.11gn HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2452	79.068	3.16	20	0.0497	1

Bluetooth 2.1+EDR mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2480	1.841	3.16	20	0.0012	1

Bluetooth 4.0 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2480	3.524	3.16	20	0.0022	1

UNII Band 1**IEEE 802.11a mode:**

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5240	29.717	3.55	20	0.0210	1

IEEE 802.11ac VHT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5240	46.881	3.55	20	0.0331	1

IEEE 802.11ac VHT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5230	43.152	3.55	20	0.0305	1

IEEE 802.11ac VHT80 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5210	11.041	3.55	20	0.0078	1

UNII Band 2A**IEEE 802.11a mode:**

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5300	37.757	3.55	20	0.0267	1

IEEE 802.11ac VHT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5300	58.884	3.55	20	0.0416	1

IEEE 802.11ac VHT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5270	52.24	3.55	20	0.0369	1

IEEE 802.11ac VHT80 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5290	15.136	3.55	20	0.0107	1

UNII Band 2C**IEEE 802.11a mode:**

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5580	35.563	3.55	20	0.0251	1

IEEE 802.11ac VHT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5580	47.315	3.55	20	0.0334	1

IEEE 802.11ac VHT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5550	53.088	3.55	20	0.0375	1

IEEE 802.11ac VHT80 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5530	19.409	3.55	20	0.0137	1

UNII Band 3**IEEE 802.11a mode:**

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5785	31.696	3.55	20	0.0224	1

IEEE 802.11ac VHT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5785	47.753	3.55	20	0.0337	1

IEEE 802.11ac VHT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5795	46.132	3.55	20	0.0326	1

IEEE 802.11ac VHT80 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5775	11.668	3.55	20	0.0082	1