Report No.: FR180348

4 Maximum Permissible Exposure

4.1 Maximum Permissible Exposure

4.1.1 Limit of Maximum Permissible Exposure

| Limits for Occupational / Controlled Exposure | | | | | | | |
|---|--------------------------------------|--------------------------------------|--------------------------------|---|--|--|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm²) | Averaging Time E ², H ² or S (minutes) | | | |
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 | | | |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 | | | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 | | | |
| 300-1500 | | | F/300 | 6 | | | |
| 1500-100,000 | | | 5 | 6 | | | |

Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm²) | Averaging Time E ² , H ² or S (minutes) | | |
|--------------------------|--------------------------------------|--------------------------------------|--------------------------------|--|--|--|
| 0.3-1.34 | 614 1.63 | | (100)* | 30 | | |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | | |
| 300-1500 | | | F/1500 | 30 | | |
| 1500-100,000 | | | 1.0 | 30 | | |

NOTE 1: f = frequency in MHz; *Plane-wave equivalent power density

NOTE 2: For the applicable limit, see FCC 1.1310

4.1.2 MPE Calculation Method

E (V/m) =
$$\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: Pd (W/m²) = $\frac{E^2}{377}$

E = Electric field (V/m) **P** = RF output power (W)

G = EUT Antenna numeric gain (numeric) **d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

SPORTON INTERNATIONAL INC. : 42 of 46 TEL: 886-2-2696-2468 Report Version : Rev. 01

FAX: 886-2-2696-2255 FCC ID : ZXJ-G3-SPP-06



Report No.: FR180348

4.1.3 Result of Maximum Permissible Exposure

| MPE | 30 MHz-QPSK | | | | | |
|----------------|--------------|--------------------|--------------|---------------|--|--|
| MPE Limit | 5 | mW/cm ² | | | | |
| RF Power (dBm) | Antenna Gain | EIRP (dBm) | EIRP (mW) | Distance (cm) | | |
| 28.79 | 56.21 | 85 | 316227766.02 | 2243.99 | | |
| 28.79 | 38 | 66.79 | 4775292.74 | 275.75 | | |

| Directional antennas | | | | | | | | | | |
|----------------------|----------|-----------|-----------------|---|--------|--------|--------|--------|---------|---------|
| Frequency | Cotogony | Maximum | Min. antenna | Minimum radiation suppression to angle in degree from centerline of main beam in decibels | | | | _ | | |
| (MHz) | Category | beamwidth | gain | 5° to | 10° to | 15° to | 20° to | 30° to | 100° to | 140° to |
| | | | (dBi) | 10° | 15° | 20° | 30° | 100° | 140° | 180° |
| 5925 ~ | А | 2.2 | 38 | 25 | 29 | 33 | 36 | 42 | 55 | 55 |
| 6425MHz | В | 2.2 | 38 | 21 | 25 | 29 | 32 | 35 | 39 | 45 |
| 6525 ~ | А | 2.2 | 38 | 25 | 29 | 33 | 36 | 42 | 55 | 55 |
| 6875MHz | В | 2.2 | 38 | 21 | 25 | 29 | 32 | 35 | 39 | 45 |

SPORTON INTERNATIONAL INC. Page No. : 43 of 46
TEL: 886-2-2696-2468 Report Version : Rev. 01

FAX: 886-2-2696-2255 FCC ID : ZXJ-G3-SPP-06