

EMC TEST REPORT for Intentional Radiator (Wi-Fi Function) No. 140401227SHA-001

Applicant : G-Lab GmbH

Schiffbaustrasse 10, 8005, Zurich, Switzerland

Factory: Hansong(Nanjing) Technology Ltd

8th Kangping Road, Jiangning Economy&Technology

Daniel . Those

Development Zone, Nanjing, 211106, China

Product Name : GENEVA

Product description : Amplified speaker

Type/Model: A010

TEST RESULT : PASS

SUMMARY

The equipment complies with the requirements according to the following standard(s):

47CFR Part 15 (2013): Radio Frequency Devices

ANSI C63.4 (2009): American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

RSS-210 Issue 8 (December 2010): Low-power Licence-exempt Radio communication Devices (All Frequency Bands): Category I Equipment

RSS-Gen Issue 3 (December 2010): General Requirements and Information for the Certification of Radio communication Equipment

Date of issue: Sep 09, 2014

Wade zhang

Prepared by: Reviewed by:

Wade Zhang (*Project Engineer*) Daniel Zhao (*Reviewer*)



Description of Test Facility

Name: Intertek Testing Services Limited Shanghai


Address: Building 86, No. 1198 Qinzhou Rd., North, Shanghai 200233, P.R. China

FCC Registration Number: 236597

IC Assigned Code: 2042B-1

Name of contact: Jonny Jing

Tel: +86 21 61278271 Fax: +86 21 54262353





Content

SUMMARY	
DESCRIPTION OF TEST FACILITY	2
1. GENERAL INFORMATION	
1.1 Applicant Information	
1.2 Identification of the EUT	4
1.3 Technical specification	
1.4 Mode of operation during the test / Test peripherals used	5
2. TEST SPECIFICATION	6
2.1 Instrument list	6
2.2 Test Standard	6
2.3 Test Summary	7
3. MINIMUM 6DB BANDWIDTH	8
3.1 Limit	8
3.2 Test Configuration	8
3.3 Test Procedure and test setup	8
3.4 Test Protocol	9
4. MAXIMUM PEAK OUTPUT POWER	13
4.1 Test limit	13
4.2 Test Configuration	
4.3 Test procedure and test setup	13
4.4 Test protocol	
5. POWER SPECTRUM DENSITY	15
5.1 Test limit	15
5.2 Test Configuration	15
5.3 Test procedure and test setup	15
5.4 Test Protocol	
6. RADIATED EMISSION	20
6.1 Test limit	20
6.2 Test Configuration	20
6.3 Test procedure and test setup	21
6.4 Test protocol	22
7. EMISSION OUTSIDE THE FREQUENCY BAND	27
7.1 Limit	27
7.2 Test Configuration	27
7.3 Test procedure and test setup	27
7.4 Test protocol	
8. POWER LINE CONDUCTED EMISSION	41
8.1 Limit	41
8.2 Test configuration	
8.3 Test procedure and test set up	
8.4 Test protocol	43



1. General Information

1.1 Applicant Information

Applicant : G-Lab GmbH

Schiffbaustrasse 10, 8005, Zurich, Switzerland

Name of contact : Frank Joosten

Tel: +41 43 205 2570

Fax : +41 43 205 2572

Factory: Hansong(Nanjing) Technology Ltd

8th Kangping Road, Jiangning Economy&Technology

Development Zone, Nanjing, 211106, China

1.2 Identification of the EUT

Equipment : GENEVA

Product description : Amplified speaker

Trade name : GENEVA

Type/model : A010

FCC ID : ZXX-A010

IC: 10107A-A010



1.3 Technical specification

Operation Frequency : 2412~2462 MHz

Band

Type of Modulation : CCK,BPSK,QPSK,DSSS,OFDM

EUT Modes of : 802.11b/g

Modulation

Channel Number : 11Channel

Gain of Antenna : 4.2dBi

Description of EUT: The EUT is a wireless device, and its support 802.11b/g mode.

Port identification : power port 1;

Audio In port 1.

Rating : AC100-240V, 50/60Hz, 60W, Class II apparatus

Declared : $5^{\circ}\text{C} \sim 40^{\circ}\text{C}$

Temperature range

Category of EUT : Class B

EUT type : Table top Floor standing

Sample received date : 2014.04.16

Sample Identification : 0140416-04-001

No

Date of test : 2014.04.16~2014.06.13

1.4 Mode of operation during the test / Test peripherals used

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

The lowest, middle and highest channel were tested as representatives. For 802.11b/g ---- lowest, 2412MHz; middle, 2437MHz; highest, 2462MHz.

The test setting software for 802.11b/g is offered by the manufactory.

The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

After this pre-scan, we choose the following table of the data rata as the worst case. 802.11b: 1Mbps; 802.11g: 11Mbps;

Test Peripherals:

PC: HP ProBook 6470b



2. Test Specification

2.1 Instrument list

				T	1
Equipment	Туре	Manu.	Internal no.	Cal. Date	Due date
Test Receiver	ESCS 30	R&S	EC 2107	2013-10-21	2014-10-20
Test Receiver	ESIB 26	R&S	EC 3045	2013-10-20	2014-10-19
Test Receiver	ESCI 7	R&S	EC4501	2013-12-29	2014-12-28
Spectrum Analyzer	N9010	Agilent	EC4890	2013-10-21	2014-10-20
Spectrum Analyzer	E4446	Agilent	/	2013-10-21	2014-10-20
Power meter	ML 2495A	Anritsu	EC 4895	2013-10-21	2014-10-20
A.M.N.	ESH2-Z5	R&S	EC 3119	2014-1-9	2015-1-8
Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2014-5-15	2015-5-14
Horn antenna	HF 906	R&S	EC 3049	2014-5-12	2015-5-11
Pre-amplifier	Pre-amp 18	R&S	EC 3222	2014-4-11	2015-4-10
Pre-amplifier	Tpa0118-40	R&S	EC 4792-2	2014-4-11	2015-4-10
Log-period antenna	AT 1080	AR	EC 3044-7	2014-5-21	2015-5-20
Biconical antenna	3109PX	ETS	EC3564	2013-8-25	2014-8-24
Semi-anechoic chamber	-	Albatross project	EC 3048	2014-5-20	2015-5-19
Shielded room	-	Zhongyu	EC 2838	2014-1-12	2015-1-9
Shielded room	-	Zhongyu	EC 2839	2014-1-12	2015-1-9
High Pass Filter	WHKX 1.0/15G- 10SS	Wainwright	EC4297-1	2014-2-1	2015-1-31
High Pass Filter	WHKX 2.8/18G- 12SS	Wainwright	EC4297-2	2014-2-1	2015-1-31
High Pass Filter	WHKX 7.0/1.8G- 8SS	Wainwright	EC4297-3	2014-2-1	2015-1-31
Loop Antenna	9230-1	Schwarzbeck	086814	2013-12-16	2014-12-15

2.2 Test Standard

47CFR Part 15 (2013); ANSI C63.4 (2009); KDB 558074 (V03R02); RSS-210 Issue 8 (December 2010); RSS-Gen Issue 3 (December 2010).



2.3 Test Summary

This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

		1	
TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	RSS-210 Issue 8 Annex 8	Pass
Maximum peak output power	15.247(b)	RSS-210 Issue 8 Annex 8	Pass
Power spectrum density	15.247(e)	RSS-210 Issue 8 Annex 8	Pass
Radiated emission	15.205 & 15.209	RSS-210 Issue 8 Clause 2	Pass
Emission outside the frequency band	15.247(d)	RSS-210 Issue 8 Annex 8	Pass
Power line conducted emission	15.207	RSS-Gen Issue 3 Clause 7.2.4	Pass




3. Minimum 6dB Bandwidth

Test result: **PASS**

3.1 Limit

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2 Test Configuration



Antenna connector

3.3 Test Procedure and test setup

The minimum 6dB bandwidth per FCC §15.247(a)(2) is measured using the Spectrum Analyzer according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance v03r02" for compliance to FCC 47CFR 15.247 requirements (clause 8.2).

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) \geq 3RBW.
- c) Detector = Peak.
- d) Trace mode = \max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




3.4 Test Protocol


Temperature : 25°C Relative Humidity : 55 %


Mode	СН	Bandwidth (MHz)	Limit (MHz)
	L	13.02	
802.11b	M	13.02	≥0.5
	Н	13.02	

Channel L











Page 10 of 44







Mode	СН	Bandwidth (MHz)	Limit (MHz)
	L	16.44	
802.11g	M	16.44	≥0.5
	Н	16.44	

Channel L









Page 12 of 44



4. Maximum peak output power


Test result: **PASS**

4.1 Test limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing a	t
least 75 non-overlapping hopping channels, and all frequency hopping systems in the 572	25
5850 MHz band: 1 watt	
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts	
For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and	
5725-5850 MHz bands: 1 Watt.	

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Test Configuration



4.3 Test procedure and test setup

The EUT was tested according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance v03r02" for compliance to FCC 47CFR 15.247 requirements (clause 9.1.2).



4.4 Test protocol

Temperature : 25°C Relative Humidity : 55 %

Mode	СН	Conducted Power (dBm)	Limit (dBm)
	L	20.69	
802.11b	M	20.57	≤30
	Н	20.66	
	L	24.91	
802.11g	M	24.66	≤30
	Н	24.62	

The maximum EIRP of the EUT = 24.91dBm + 4.20dBi = 29.11dBm = 814.70mW which is lower than the EIRP limit of RSS-210.




5. Power spectrum density

Test result: **PASS**

5.1 Test limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Configuration



5.3 Test procedure and test setup

The power output per FCC § 15.247(e) was tested according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance v03r02" (clause 10.2) for compliance to FCC 47CFR 15.247 requirements.




5.4 Test Protocol


Temperature : 25°C Relative Humidity : 55 %

Mode	СН	Spectrum Density (dBm/100kHz)	Limit (dBm/3kHz)
	L	7.74	
802.11b	M	7.78	≤8.00
	Н	7.73	

802.11b Channel L




Date: 28.APR.2014 15:10:25











Date: 28.APR.2014 15:12:40

802.11b Channel H



Date: 28.APR.2014 15:14:26







Mode	СН	Spectrum Density (dBm/100kHz)	Limit (dBm/3kHz)
	L	5.80	
802.11g	M	5.68	≤8.00
	Н	5.57	

Date: 28.APR.2014 15:17:41





Date: 28.APR.2014 15:19:29



Date: 28.APR.2014 15:21:10



6. Radiated emission


Test result: PASS

6.1 Test limit

The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

6.2 Test Configuration





6.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, if applied, the pre-amplifier would be equipped just at the output terminal of the antenna.

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1 meter to 4 meters to find out the maximum emission level.

The EUT was tested according to DTS test procedure of KDB558074 D01 DTS "Meas Guidance v03r02" (clause 12) for compliance to FCC 47CFR 15.247 requirements.

Use the following spectrum analyzer settings:

- (1) Span shall wide enough to fully capture the emission being measured;
- (2) Set RBW=100 kHz for f < 1 GHz; VBW \ge RBW; Sweep = auto; Detector function = peak; Trace = max hold;
- (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement.

For average measurement:

- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




6.4 Test protocol


Temperature : 25°C Relative Humidity : 55 %

Below 1GHz:

30MHz~1GHz, Horizontal









Test data:

Polarization	Frequency	Measured level	Limits	Margin	Factor	Detector
Folalization	(MHz)	$(dB\mu V/m)$	$(dB\mu V/m)$	(dB)	(dB)	Detector
	30.00	23.80	40.00	16.20	22.00	PK
	74.71	16.50	40.00	23.50	9.80	PK
Н	105.81	23.20	43.50	20.30	15.10	PK
11	218.56	27.70	46.00	18.30	12.30	PK
	364.35	31.80	46.00	14.20	17.30	PK
	930.02	32.10	46.00	13.90	25.30	PK
	49.44	31.80	40.00	8.20	11.30	PK
	59.16	31.40	40.00	8.60	8.40	PK
V	105.81	37.10	43.50	6.40	15.10	PK
· ·	272.99	35.90	46.00	10.10	14.40	PK
	519.86	32.90	46.00	13.10	20.90	PK
	564.57	35.10	46.00	10.90	21.80	PK

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



Above 1GHz:

802.11b:

Polarity	Frequenc y (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
	2390	63.20	74	-7.80	100	190	10.80	PK
	2390	45.30	54	-7.80	100	190	8.70	AV
Van/Han	V /II 2412	109.50	-	-7.80	100	190	-	PK
Ver/Hor 2412	103.10	-	-7.80	100	190	-	AV	
	4924	47.40	74	-2.10	100	190	26.60	PK
	4824	36.60	54	-2.10	100	190	17.40	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequenc y (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
	2427	107.20	-	-7.80	100	190	-	PK
	2437	102.30	-	-7.80	100	190	-	AV
Ver/Hor	4874	47.70	74	-2.10	100	190	26.30	PK
Ver/Hor		37.40	54	-2.10	100	190	16.60	AV
	7311	49.50	74	6.50	100	190	24.50	PK
		40.50	54	6.50	100	190	13.50	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequenc y (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
	2462	108.90	-	-7.80	100	190	-	PK
	2462	102.00	-	-7.80	100	190	-	AV
	2483.5	62.50	74	-7.50	100	190	11.50	PK
37 /11		49.80	54	-7.50	100	190	14.20	AV
Ver/Hor	4924	47.90	74	-2.10	100	190	26.10	PK
		38.60	54	-2.10	100	190	15.40	AV
	7386	50.60	74	6.50	100	190	23.40	PK
	/380	40.90	54	6.50	100	190	13.10	AV
Note:	2462MHz	is fundament	al signal.					



802.11g:

Polarity	Frequenc y (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark	
	2200	65.60	74	-7.80	100	190	8.40	PK	
	2390	47.80	54	-7.80	100	190	6.20	AV	
Ver/Hor	2412	106.20	-	-7.80	100	190	-	PK	
		101.70	-	-7.80	100	190	-	AV	
	4824	46.20	74	-2.10	100	190	27.80	PK	
		39.40	54	-2.10	100	190	14.60	AV	
Note:	2412MHz is fundamental signal.								

Polarity	Frequenc y (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark	
	2437	105.80	-	-7.80	100	190	-	PK	
		99.70	-	-7.80	100	190	-	AV	
Ver/Hor	4874	48.60	74	-2.10	100	190	25.40	PK	
		39.70	54	-2.10	100	190	14.30	AV	
	7311	48.20	74	6.50	100	190	25.80	PK	
		41.40	54	6.50	100	190	12.60	AV	
Note:	2437MHz is fundamental signal.								

Polarity	Frequenc y (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
	2462	108.60	-	-7.80	100	190	-	PK
	2402	102.30	-	-7.80	100	190	-	AV
	2483.5	67.80	74	-7.50	100	190	6.20	PK
X7 /II		46.50	54	-7.50	100	190	7.50	AV
Ver/Hor	4924	48.10	74	-2.10	100	190	25.90	PK
		39.70	54	-2.10	100	190	14.30	AV
	7386	45.30	74	6.50	100	190	28.70	PK
		38.40	54	6.50	100	190	15.60	AV
Note:	2462MHz	is fundament	al signal.					_



Remark:

- 1. Factor = Antenna Factor + Cable Loss (-Amplifier, is employed);
- 2. Measured level = Original Receiver Reading + Correct Factor;
- 3. Margin = limit Measured level;
- 4. If the PK reading is lower than AV limit, the AV testing is omitted.

Example:

Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV, Then Factor = 30.20 + 2.00 - 32.00 = 0.20dB/m, Measured level = 10 dBuV + 0.20 dB/m = 10.20 dBuV/m, Assuming limit = 54dBuV/m, Measured level = 10.20dBuV/m, Then Margin = 54 - 10.20 = 43.80 dBuV/m.




7. Emission outside the frequency Band

Test result: PASS

7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Test procedure and test setup

The Emission outside the frequency Band per FCC § 15.247(d) is measured using the Spectrum Analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 300kHz, and the SPAN>>RBW.

The EUT was tested according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance v03r02" (clause 11.0) for compliance to FCC 47CFR 15.247 requirements.




7.4 Test protocol

Temperature : 25°C Relative Humidity : 55 %

802.11b Out-of-Band Emissions:


Mode	СН	Result	Limit (dB)
	L	Pass	
802.11b	M	Pass	≥20
	Н	Pass	

Spurious Emission 1MHz $\sim 2.3 GHz$ - Frequency L




Date: 28.APR.2014 16:38:12







Date: 28.APR.2014 15:48:03



Date: 28.APR.2014 16:39:26









Date: 14.MAY.2014 17:10:49

Spurious Emission 1MHz ~ 2.3GHz - Frequency M




Date: 28.APR.2014 16:48:13







Date: 28.APR.2014 16:01:28



Date: 28.APR.2014 16:41:36









Date: 14.MAY.2014 17:12:14

Spurious Emission 1MHz ~ 2.3GHz - Frequency H



Date: 28.APR.2014 16:37:14






20 MHz/

Stop 2.5 GHz

Date: 28.APR.2014 16:17:19


Start 2.3 GHz



Date: 28.APR.2014 16:36:13

Stop 25 GHz





1.8 GHz/

Date: 14.MAY.2014 17:16:30


802.11g Out-of-Band Emissions:


-80

Start 7 GHz

Mode	СН	Result	Limit (dB)
	L	Pass	
802.11g	M	Pass	≥20
	Н	Pass	









Date: 28.APR.2014 16:52:48


Low Band Edge - Frequency L



Date: 28.APR.2014 16:54:21









Date: 28.APR.2014 16:57:47


Spurious Emission 7GHz \sim 25GHz - Frequency L



Date: 14.MAY.2014 17:14:32








Date: 28.APR.2014 16:59:46


Band Edge - Frequency M



Date: 28.APR.2014 17:00:54









Date: 28.APR.2014 16:58:57


Spurious Emission 7GHz ~ 25GHz - Frequency M



Date: 14.MAY.2014 17:14:56








Date: 28.APR.2014 17:09:54


High Band Edge - Frequency H



Date: 28.APR.2014 17:11:51








Date: 28.APR.2014 17:41:03

Spurious Emission 7GHz ~ 25GHz - Frequency H



Date: 14.MAY.2014 17:16:58




8. Power line conducted emission

Test result: PASS

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)				
	QP	AV			
0.15-0.5	66 to 56*	56 to 46 *			
0.5-5	56	46			
5-30	60	50			
* Decreases with the logarithm of the frequency.					

8.2 Test configuration



- ☑ For table top equipment, wooden support is 0.8m height table
- ☐ For floor standing equipment, wooden support is 0.1m height rack.



8.3 Test procedure and test set up


The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a $50\Omega/50uH$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\Omega/50uH$ coupling impedance with 50Ω termination.


Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement. The bandwidth of the test receiver is set at 9 kHz.

Intertek FCC ID: ZXX-A010 IC: 10107A-A010

8.4 Test protocol

Temperature : 25°C Relative Humidity : 55 %





Page 43 of 44



Test data:

1 CSt uata	Test data.								
Line	Frequency	Corrected Reading (dBuV)		Limit (dBuV)		Margin (dB)			
		QP	AV	QP	AV	QP	AV		
	0.156	49.69	34.32	65.67	55.67	15.98	21.35		
	0.354	39.27	37.60	58.87	48.87	19.60	11.27		
L	1.057	31.89	31.50	56.00	46.00	24.11	14.50		
L	1.761	27.71	27.51	56.00	46.00	28.29	18.49		
	2.473	23.59	23.21	56.00	46.00	32.41	22.79		
	3.882	23.27	22.21	56.00	46.00	32.73	23.79		
	0.152	50.56	33.48	65.87	55.87	15.31	22.39		
	0.352	36.94	35.35	58.90	48.90	21.96	13.55		
N	0.703	25.54	22.34	56.00	46.00	30.46	23.66		
IN .	1.057	26.21	24.66	56.00	46.00	29.79	21.34		
	3.882	23.95	22.30	56.00	46.00	32.05	23.70		
	5.998	21.87	20.79	60.00	50.00	38.13	29.21		

Remark: Margin (dB) = Limit - Corrected Reading.