



# RF TEST REPORT

Report No.: SET2015-03041

Product Name: Xtreamer Mini Android PC

FCC ID: ZYAPRODIGY4K

Model No.: Xtreamer Prodigy 4k

**Applicant:** XTREAMER LIMITED

Flat A,15/F Hiller Commercial Building 65-67 Bonham Strand East, Address:

Sheung Wan, HongKong

Issued by: CCIC-SET

Lab Location: Electronic Testing Building, Shahe Road, Xili, Nanshan District,

Shenzhen, 518055, P. R. China

**Tel**: 86 755 26627338 **Fax**: 86 755 26627238

This test report consists of 69 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 20 days since the date when the report is received. It will not be taken into consideration beyond this limit.

CCIC-SET/T (00) Page 1 of 69





# **Test Report**

Product Name .....: Xtreamer Mini Android PC

Model No. ..... Xtreamer Prodigy 4k

Brand Name .....: Xtreamer

Trade Name .....: Xtreamer

Applicant .....: XTREAMER LIMITED

Applicant Address .....: Flat A,15/F Hiller Commercial Building 65-67 Bonham

Strand East, Sheung Wan, HongKong

Manufacturer....: XTREAMER LIMITED

Manufacturer Address ......: Flat A,15/F Hiller Commercial Building 65-67 Bonham

Strand East, Sheung Wan, HongKong

ANSI C63.10:2009: American National Standard for

**Testing Unlicensed Wireless Devices** 

KDB558074 D01 DTS Meas Guidance v03r02

Test Result .....: PASS

Tested by .....:

2015.03.12

Haigang He, Test Engineer

Reviewed by....:: Zhu Q:

2015.03.12

Zhu Qi, Senior Egineer

Approved by ....::

2015.03.12

Wu Li'an, Manager

CCIC-SET/T (00) Page 2 of 69




# TABLE OF CONTENTS

| GEN   | ERAL INFORMATION5              |
|-------|--------------------------------|
| 1.1   | EUT Description5               |
| 1.2   | Test Standards and Results6    |
| 1.3   | Facilities and Accreditations  |
| 1.3.1 | Facilities7                    |
| 1.3.2 | Test Environment Conditions    |
| 2.    | 47 CFR PART 15C REQUIREMENTS8  |
| 2.1   | Antenna requirement8           |
| 2.1.1 | Applicable Standard8           |
| 2.1.2 | Antenna Information8           |
| 2.1.3 | Result: comply8                |
| 2.2   | Peak Output Power9             |
| 2.2.1 | Requirement9                   |
| 2.2.2 | Test Description9              |
| 2.2.3 | Test Result9                   |
| 2.3   | Bandwidth11                    |
| 2.3.1 | Requirement                    |
| 2.3.2 | Test Description               |
| 2.3.3 | Test Result                    |
| 2.4   | Conducted Spurious Emissions20 |
| 2.4.1 | Requirement                    |
| 2.4.2 | Test Description               |
| 2.4.3 | Test Result                    |
| 2.5   | Power spectral density (PSD)35 |
| 2.5.1 | Requirement35                  |
| 2.5.2 | Test Description               |
| 2.5.3 | Test Result36                  |
| 2.6   | Band Edge44                    |
| 2.6.1 | Requirement44                  |
| 2.6.2 | Test Description44             |



| 2.6.3  | Test Procedure                             | <del>1</del> 5 |
|--------|--|----------------|
| 2.6.4  | Test Result                                | <del>1</del> 5 |
| 2.7    | Conducted Emission5                        | 52             |
| 2.7.1  | Requirement5                               | 52             |
| 2.7.2  | Test Description5                          | 52             |
| 2.7.3  | Test Result5                               | 53             |
| 2.8    | Radiated Emission                          | 55             |
| 2.8.1  | Requirement5                               | 55             |
| 2.8.2  | Test Description5                          | 56             |
| 2.8.3  | Test Result5                               | 58             |
| 2.9    | RF exposure evaluation6                    | <b>58</b>      |
| 2.9.1  | . Limits For Maximum Permissible Exposure6 | 58             |
| 2.9.2. | Test Result6                               | 58             |
| 2.9.3. | Conclusion                                 | 59             |
|        |  |                |

|       | Change History |                   |  |  |  |
|-------|----------------|-------------------|--|--|--|
| Issue | Date           | Reason for change |  |  |  |
| 1.0   | Mar 12,2015    | First edition     |  |  |  |
|       |                |                   |  |  |  |
|       |                |                   |  |  |  |





#### GENERAL INFORMATION

## 1.1 EUT Description

EUT Type .....: Xtreamer Mini Android PC

FCC ID.....: ZYAPRODIGY4K

Hardware Version .....: MS0918-M34H-V1.10-0

Software Version .....: V5.1.30

Frequency Range.....: 802.11b/g/n-20MHz: 2.412GHz - 2.462GHz

802.11n-40MHz:2.422GHz – 2.452GHz

Channel Number .....: 802.11b/g/n-20MHz: 11

802.11n-40MHz:7

Modulation Type .....: DSSS (802.11b), OFDM (802.11g/n)

Antenna Type .....: Exposed antenna

Antenna Gain ...... 5 dBi

Note 1: The EUT is a Mini Android PC, it contains WIFI operating at 2.4GHz ISM band; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

Note 2: The frequencies allocated is F (MHz) =2412+5\*(n-1) (1<=n<=11). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz) for 802.11b/g/n-20MHz and 3(2422MHz), 6 (2437MHz) and 9 (2452MHz) for 802.11n-40MHz

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 3: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

CCIC-SET/T (00) Page 5 of 69



## 1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Wi-Fi, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

| No. | Identity                         | Document Title  |
|-----|----------------------------------|---|
| 1   | 47 CFR Part 15<br>Subpart C 2012 | Radio Frequency Devices   |
| 2   | ANSI C63.10 2009                 | American National Standard for Testing<br>Unlicensed Wireless Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section           | Description                  | Result |
|-----|-------------------|------------------------------|--------|
| 1   | 15.203            | Antenna Requirement          | PASS   |
| 2   | 15.247(b)         | Peak Output Power            | PASS   |
| 3   | 15.247(a)         | Bandwidth                    | PASS   |
| 4   | 15.247(d)         | Conducted Spurious Emission  | PASS   |
| 5   | 15.247(d)         | Band Edge                    | PASS   |
| 6   | 15.207            | Conducted Emission           | PASS   |
| 7   | 15.209 ,15.247(c) | Radiated Emission            | PASS   |
| 8   | 15.247(e)         | Power spectral density (PSD) | PASS   |

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10 2009.

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                           | Mode            | Data Rate | Channel |
|--------------------------------------|-----------------|-----------|---------|
| Peak Conducted Output Power          | 11b/DSSS        | 11 Mbps   | 1/6/11  |
| Power Spectral Density               |                 | 1         |         |
| 6dB Bandwidth                        | 11g/OFDM        | 54 Mbps   | 1/6/11  |
| Spurious RF conducted emission       | 11n(20MHz)/OFDM | 72Mbps    | 1/6/11  |
| Radiated Emission 9kHz~1GHz&         | , , ,           |           |         |
| Radiated Emission 1GHz~10th Harmonic | 11n(40MHz)/OFDM | 150Mbps   | 3/6/9   |
| Band Edge                            | 11b/DSSS        | 11 Mbps   | 1/11    |
|                                      | 11g/OFDM        | 54 Mbps   | 1/11    |
|                                      | 11n(20MHz)/OFDM | 72Mbps    | 1/11    |
|                                      | 11n(40MHz)/OFDM | 150 Mbps  | 3/9     |

CCIC-SET/T (00) Page 6 of 69



## 1.3 Facilities and Accreditations

#### 1.3.1 Facilities

#### CNAS-Lab Code: L1659

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659. A 12.8\*6.8\*6.4 (m) fully anechoic chamber was used for the radiated spurious emissions test.

#### FCC-Registration No.: 406086

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 406086, valid time is until October 28, 2017.

#### IC-Registration No.: 11185A-1

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on July. 15, 2013, valid time is until July. 15, 2016.

#### **1.3.2** Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

| Temperature ( $^{\circ}$ C): | 15 ℃ - 35 ℃  |
|------------------------------|--------------|
| Relative Humidity (%):       | 30% -60%     |
| Atmospheric Pressure (kPa):  | 86KPa-106KPa |

CCIC-SET/T (00) Page 7 of 69



## 2. 47 CFR PART 15C REQUIREMENTS

## 2.1 Antenna requirement

## 2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### 2.1.2 Antenna Information

Antenna Category: External antenna

An External antenna was connected to the antenna port of EUT, can be removed.

#### **Antenna General Information:**

| No. | EUT Model                   | Ant. Cat. | Ant. Type       | Gain(dBi) |
|-----|-----------------------------|-----------|-----------------|-----------|
| 1   | Xtreamer<br>Mini Android PC | External  | Exposed antenna | 5         |

## 2.1.3 Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

CCIC-SET/T (00) Page 8 of 69



# 2.2 Peak Output Power

## 2.2.1 Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

## 2.2.2 Test Description



The measured output power was calculated by the reading of the spectrum analyzer and calibration.

#### A. Test Setup:

The EUT was directly connected to the power meter by 20dB Atten and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

#### **B.** Equipments List:

| Description  | Manufacturer | Model  | Serial No.   | Cal. Date  | Cal. Due Date |
|--------------|--------------|--------|--------------|------------|---------------|
| Power Meter  | R&S          | NRVS   | 1020.1809.02 | 2014.06.07 | 2015.06.06    |
| Power Sensor | R&S          | NRV-Z4 | 823.3618.03  | 2014.06.07 | 2015.06.06    |

#### 2.2.3 Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

#### 2.2.3.1 802.11b Test mode

#### **Test Verdict:**

| Channel | Frequency (MHz) | Measured Output<br>Peak Power(dBm) | Limits (dBm) | Result |
|---------|-----------------|------------------------------------|--------------|--------|
| 1       | 2412            | 17.75                              | 30           | PASS   |
| 6       | 2437            | 17.53                              | 30           | PASS   |
| 11      | 2462            | 17.24                              | 30           | PASS   |

Note:

1. For 802.11b mode at finial test to get the worst-case emission at 11Mbps.

2. The test results including the cable lose.

CCIC-SET/T (00) Page 9 of 69





#### 2.2.3.2 802.11g Test mode

#### **Test Verdict:**

| Channel | Frequency (MHz) | Measured Output<br>Peak Power (dBm) | Limits (dBm) | Result |
|---------|-----------------|-------------------------------------|--------------|--------|
| 1       | 2412            | 15.21                               | 30           | PASS   |
| 6       | 2437            | 15.46                               | 30           | PASS   |
| 11      | 2462            | 15.67                               | 30           | PASS   |

Note:

- 1. For 802.11g mode at finial test to get the worst-case emission at 54Mbps.
- 2. The test results including the cable lose.

#### 2.2.3.3 802.11n-20MHz Test mode

#### **Test Verdict:**

| Channel | Frequency (MHz) | Measured Output<br>Peak Power(dBm) | Limits (dBm) | Result |
|---------|-----------------|------------------------------------|--------------|--------|
| 1       | 2412            | 13.97                              | 30           | PASS   |
| 6       | 2437            | 14.37                              | 30           | PASS   |
| 11      | 2462            | 14.01                              | 30           | PASS   |

Note:

- 1. For 802.11n-20 mode at finial test to get the worst-case emission at 72Mbps.
- 2. The test results including the cable lose.

#### 2.2.3.4 802.11n-40MHz Test mode

#### **Test Verdict:**

| Channel | Frequency (MHz) | Measured Output<br>Peak Power(dBm) | Limits (dBm) | Result |
|---------|-----------------|------------------------------------|--------------|--------|
| 3       | 2422            | 12.60                              | 30           | PASS   |
| 6       | 2437            | 12.72                              | 30           | PASS   |
| 9       | 2452            | 13.21                              | 30           | PASS   |

Note:

- 1. For 802.11n-40 mode at finial test to get the worst-case emission at 150Mbps.
- 2. The test results including the cable lose.

CCIC-SET/T (00) Page 10 of 69




#### 2.3 Bandwidth

## 2.3.1 Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

## 2.3.2 Test Description

#### A. Test Set:



The EUT which is powered by the AC adapter, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 500hm; the path loss and Atten as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

#### **B.** Equipments List:

| Description       | Manufacturer | Model | Serial No.   | Cal. Date  | Cal. Due Date |
|-------------------|--------------|-------|--------------|------------|---------------|
| Spectrum Analyzer | R&S          | FSP40 | 1164.4391.40 | 2014.07.07 | 2015.07.06    |

#### 2.3.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.

CCIC-SET/T (00) Page 11 of 69




## 2.3.3.1 802.11b Test mode

## A. Test Verdict:

| Channel | Frequency (MHz) | 6 dB Bandwidth<br>(MHz) | Refer to Plot | Limits(kHz) | Result |
|---------|-----------------|-------------------------|---------------|-------------|--------|
| 1       | 2412            | 8.75                    | Plot 2.3 A    | ≥500        | PASS   |
| 6       | 2437            | 7.50                    | Plot 2.3 B    | ≥500        | PASS   |
| 11      | 2462            | 8.75                    | Plot 2.3 C    | ≥500        | PASS   |


#### **B.** Test Plots:



(Plot 2.3 A: Channel 1: 2412MHz @ 802.11b)

CCIC-SET/T (00) Page 12 of 69





CCIC-SET/T (00) Page 13 of 69




## 2.3.3.2 802.11g Test mode

## A. Test Verdict:

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Refer to Plot | Limits (kHz) | Result |
|---------|-----------------|----------------------|---------------|--------------|--------|
| 1       | 2412            | 16.50                | Plot 2.3 D    | ≥500         | PASS   |
| 6       | 2437            | 16.45                | Plot 2.3 E    | ≥500         | PASS   |
| 11      | 2462            | 16.55                | Plot 2.3 F    | ≥500         | PASS   |


#### **B.** Test Plots:



(Plot 2.3 D: Channel 1: 2412MHz @ 802.11g)

CCIC-SET/T (00) Page 14 of 69





(Plot 2.3 F: Channel 11: 2462MHz @ 802.11g)

CCIC-SET/T (00) Page 15 of 69

Center 2.462 GHz




## 2.3.3.3 802.11n-20 Test mode

## A. Test Verdict:

| Channel | Frequency<br>(MHz) | 6 dB Bandwidth (MHz) | Refer to Plot | Limits (kHz) | Result |
|---------|--------------------|----------------------|---------------|--------------|--------|
| 1       | 2412               | 17.65                | Plot 2.3 G    | ≥500         | PASS   |
| 6       | 2437               | 17.70                | Plot 2.3 H    | ≥500         | PASS   |
| 11      | 2462               | 17.75                | Plot 2.3 I    | ≥500         | PASS   |


#### **B.** Test Plots:




(Plot 2.3 G: Channel 1: 2412MHz @ 802.11n-20)

CCIC-SET/T (00) Page 16 of 69





(Plot 2.3 H: Channel 6: 2437MHz @ 802.11n-20)



(Plot 2.3 I: Channel 11: 2462MHz @ 802.11n-20)

CCIC-SET/T (00) Page 17 of 69




## 2.3.3.4 802.11n-40 Test mode

## A. Test Verdict:

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Refer to Plot | Limits (kHz) | Result |
|---------|-----------------|----------------------|---------------|--------------|--------|
| 3       | 2422            | 35.91                | Plot 2.3 J    | ≥500         | PASS   |
| 6       | 2437            | 36.27                | Plot 2.3 K    | ≥500         | PASS   |
| 9       | 2452            | 35.73                | Plot 2.3 L    | ≥500         | PASS   |


#### **B.** Test Plots:




(Plot 2.3 J: Channel 3: 2422MHz @ 802.11n-40)

CCIC-SET/T (00) Page 18 of 69







(Plot 2.3 L: Channel 9: 2452MHz @ 802.11n-40)

CCIC-SET/T (00) Page 19 of 69




## 2.4 Conducted Spurious Emissions

## 2.4.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

## 2.4.2 Test Description

## A. Test Set:



The EUT which is powered by the AC adapter, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 500hm; the path loss and Atten as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

#### **B.** Equipments List:

| Description       | Manufacturer | Model | Serial No.   | Cal. Date  | Cal. Due Date |
|-------------------|--------------|-------|--------------|------------|---------------|
| Spectrum Analyzer | R&S          | FSP40 | 1164.4391.40 | 2014.07.07 | 2015.07.06    |

#### 2.4.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

#### 2.4.3.1 802.11b Test mode

CCIC-SET/T (00) Page 20 of 69




#### A. Test Verdict:

| Channel | Frequency (MHz) | Refer to Plot | Limit (dBc) | Verdict |
|---------|-----------------|---------------|-------------|---------|
| 1       | 2412            | Plot 2.4 A    | -20         | PASS    |
| 6       | 2437            | Plot 2.4 B    | -20         | PASS    |
| 11      | 2462            | Plot 2.4 C    | -20         | PASS    |


#### **B.** Test Plots:

Note: the power of the Module transmitting frequency should be ignored.




CCIC-SET/T (00) Page 21 of 69






CCIC-SET/T (00) Page 22 of 69





CCIC-SET/T (00) Page 23 of 69





(Plot 2.4 C: Channel = 11, 30MHz to 25GHz@ 802.11b)

## 2.4.3.2 802.11g Test mode

#### A. Test Verdict:


| Channel | Frequency (MHz) | Refer to Plot | Limit<br>(dBc) | Verdict |
|---------|-----------------|---------------|----------------|---------|
| 1       | 2412            | Plot 2.4 D    | -20            | PASS    |
| 6       | 2437            | Plot 2.4 E    | -20            | PASS    |
| 11      | 2462            | Plot 2.4 F    | -20            | PASS    |

#### **B.** Test Plots:

Note: the power of the Module transmitting frequency should be ignored.


CCIC-SET/T (00) Page 24 of 69






CCIC-SET/T (00) Page 25 of 69





CCIC-SET/T (00) Page 26 of 69





CCIC-SET/T (00) Page 27 of 69




#### 2.4.3.3 802.11n -20MHz Test mode

## A. Test Verdict:

| Channel | Frequency (MHz) | Refer to Plot | Limit<br>(dBc) | Verdict |
|---------|-----------------|---------------|----------------|---------|
| 1       | 2412            | Plot 2.4 G    | -20            | PASS    |
| 6       | 2437            | Plot 2.4 H    | -20            | PASS    |
| 11      | 2462            | Plot 2.4 I    | -20            | PASS    |


#### **B.** Test Plots:


Note: the power of the Module transmitting frequency should be ignored.



CCIC-SET/T (00) Page 28 of 69









CCIC-SET/T (00) Page 29 of 69





CCIC-SET/T (00) Page 30 of 69





(Plot 2.4 I: Channel = 11, 30MHz to 25GHz@ 802.11n-20)

## 2.4.3.4 802.11n -40MHz Test mode

#### A. Test Verdict:


| Channel | Frequency (MHz) | Refer to Plot | Limit (dBc) | Verdict |
|---------|-----------------|---------------|-------------|---------|
| 3       | 2422            | Plot 2.4 J    | -20         | PASS    |
| 6       | 2437            | Plot 2.4 K    | -20         | PASS    |
| 9       | 2452            | Plot 2.4 L    | -20         | PASS    |

#### **B.** Test Plots:

Note: the power of the Module transmitting frequency should be ignored.


CCIC-SET/T (00) Page 31 of 69






CCIC-SET/T (00) Page 32 of 69





CCIC-SET/T (00) Page 33 of 69





CCIC-SET/T (00) Page 34 of 69




## 2.5 Power spectral density (PSD)

## 2.5.1 Requirement

According to FCC section 15.247(d), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

## 2.5.2 Test Description

#### A. Test Set:



The EUT which is powered by the AC adapter, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 500hm; the path loss and Atten as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

#### **B.** Test Procedure

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS channel bandwidth.
- 3. Set the RBW  $\geq$  3 kHz.
- 4. Set the VBW  $\geq$  3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### C. Equipments List:

| Description       | Manufacturer | Model | Serial No.   | Cal. Date  | Cal. Due Date |
|-------------------|--------------|-------|--------------|------------|---------------|
| Spectrum Analyzer | R&S          | FSP40 | 1164.4391.40 | 2014.07.07 | 2015.07.06    |

CCIC-SET/T (00) Page 35 of 69



#### 2.5.3 Test Result

The lowest, middle and highest channels are tested to verify the band edge emissions.

#### 2.5.3.1 802.11b Test mode


#### A. Test Verdict:

| Spectral power density (dBm/3kHz) |                 |                    |               |                  |         |
|-----------------------------------|-----------------|--------------------|---------------|------------------|---------|
| Channel                           | Frequency (MHz) | Measured PSD (dBm) | Refer to Plot | Limit (dBm/3kHz) | Verdict |
| 1                                 | 2412            | 3.85               | Plot 2.5 A    | 8                | PASS    |
| 6                                 | 2437            | 3.09               | Plot 2.5 B    | 8                | PASS    |
| 11                                | 2462            | 3.66               | Plot 2.5 C    | 8                | PASS    |
| Measurement uncertainty: ±1.3dB   |                 |                    |               |                  |         |

Note: 1. For 802.11b mode at finial test to get the worst-case emission at 11Mbps.

2. The test results including the cable lose.


#### **B.** Test Plots:



(Plot 2.5 A: Channel = 1 @ 802.11b)

CCIC-SET/T (00) Page 36 of 69





CCIC-SET/T (00) Page 37 of 69



## 2.5.3.2 802.11g Test mode

## A. Test Verdict:


| Spectral power density (dBm/3kHz) |                 |                         |               |                     |         |  |
|-----------------------------------|-----------------|-------------------------|---------------|---------------------|---------|--|
| Channel                           | Frequency (MHz) | Measured PSD (dBm/3kHz) | Refer to Plot | Limit<br>(dBm/3kHz) | Verdict |  |
| 1                                 | 2412            | -2.92                   | Plot 2.5 D    | 8                   | PASS    |  |
| 6                                 | 2437            | -2.59                   | Plot 2.5 E    | 8                   | PASS    |  |
| 11                                | 2462            | -2.39                   | Plot 2.5 F    | 8                   | PASS    |  |

Measurement uncertainty: ±1.3dB

Note: 1. For 802.11g mode at finial test to get the worst-case emission at 54 Mbps.

2. The test results including the cable lose.


## **B.** Test Plots:



(Plot 2.5 D: Channel = 1 @ 802.11g)

CCIC-SET/T (00) Page 38 of 69





CCIC-SET/T (00) Page 39 of 69



## 2.5.3.3 802.11n-20 Test mode

## A. Test Verdict:


| Spectral power density (dBm/3kHz)  |      |       |           |   |      |  |  |
|--|------|-------|-----------|---|------|--|--|
| Channel Frequency (MHz) Measured PSD (dBm/3kHz) Refer to Plot Limit (dBm/3kHz) Verdice |      |       |           |   |      |  |  |
| 1  | 2412 | -4.33 | Plot2.5 G | 8 | PASS |  |  |
| 6  | 2437 | -4.08 | Plot2.5 H | 8 | PASS |  |  |
| 11   | 2462 | -4.33 | Plot2.5 I | 8 | PASS |  |  |

Measurement uncertainty: ±1.3dB

Note: 1. For 802.11n(20MHz) mode at finial test to get the worst-case emission at 72 Mbps.

2. The test results including the cable lose.


## **B.** Test Plots:



(Plot 2.5 G: Channel = 1 @ 802.11n-20

CCIC-SET/T (00) Page 40 of 69





CCIC-SET/T (00) Page 41 of 69



## 2.5.3.4 802.11n-40 Test mode


## A. Test Verdict:

|         | Spectral power density (dBm/3kHz) |                    |               |                  |         |  |  |  |
|---------|-----------------------------------|--------------------|---------------|------------------|---------|--|--|--|
| Channel | Frequency (MHz)                   | Measured PSD (dBm) | Refer to Plot | Limit (dBm/3kHz) | Verdict |  |  |  |
| 3       | 2422                              | -8.43              | Plot 2.5 J    | 8                | PASS    |  |  |  |
| 6       | 2437                              | -8.20              | Plot 2.5 K    | 8                | PASS    |  |  |  |
| 9       | 9 2452 -8.06 Plot 2.5 L 8 PASS    |                    |               |                  |         |  |  |  |
| Measur  | Measurement uncertainty: ±1.3dB   |                    |               |                  |         |  |  |  |

Note: 1. For 802.11n-40 mode at finial test to get the worst-case emission at 150Mbps.

2. The test results including the cable lose.


## **B.** Test Plots:



(Plot 2.5 J: Channel = 3 @ 802.11n-40

CCIC-SET/T (00) Page 42 of 69





CCIC-SET/T (00) Page 43 of 69




## 2.6 Band Edge

## 2.6.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

## 2.6.2 Test Description

## A. Test Setup



The EUT is powered by the AC Adapter. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

#### For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

CCIC-SET/T (00) Page 44 of 69



## **B.** Equipments List:

| Description            | Manufacturer | Model      | Serial No. | Cal. Date  | Cal. Due Date |  |
|------------------------|--------------|------------|------------|------------|---------------|--|
| Receiver               | R&S          | ESIB26     | A0304218   | 2014.06.07 | 2015.06.06    |  |
| Full-Anechoic          | Albatross    | 12.8m*6.8m | A0412372   | 2014.06.07 | 2015.06.06    |  |
| Chamber                | Albanoss     | *6.4m      | A0412372   | 2014.00.07 | 2013.00.00    |  |
| Double ridge horn      | D %-C        | HF906      | 100150     | 2014.06.10 | 2015.06.09    |  |
| antenna                | R&S          | пгэоо      | 100130     | 2014.00.10 | 2013.00.09    |  |
| Ultra-wideband antenna | R&S          | HL562      | 100089     | 2014.06.10 | 2015.06.09    |  |
|                        |              | MITEQ      |            |            |               |  |
| Ampilier 1G~18GHz      | R&S          | AFS42-001  | 25-S-42    | 2014.06.05 | 2015.06.04    |  |
|                        |              | 01800      |            |            |               |  |
| Cable                  | SUNHNER      | SUCOFLE    | /          | 2014.06.05 | 2015.06.04    |  |
| Cable                  | SUNHINER     | X 100      | /          | 2014.06.05 | 2015.06.04    |  |
| Cabla                  | CHIMILINED   | SUCOFLE    | /          | 2014.06.05 | 2015 06 04    |  |
| Cable                  | SUNHNER      | X 104      | /          | 2014.06.03 | 2015.06.04    |  |
|                        |              |            |            |            |               |  |

#### 2.6.3 Test Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation

For radiated test

RBW =1MHz, VBW=3MHz PK detector for PK value,

RBW=1MHz VBW=10Hz, PK detector for AV value

Trace = max hold

Allow the trace to stabilize

#### 2.6.4 Test Result

Band edge were measurement for 802.11b,802.11g, 802.11n(20MHz) and 802.11n(40MHz) mode at difference date, recording worst case in test report.

#### Radiated band edge Measurement:

The lowest and highest channels are tested to verify the band edge emissions.

The measurement results are obtained as below:

 $E\left[dB\mu\ V/m\right] = U_R + A_T + A_{\text{Factor}}\left[dB\right]; A_T = L_{\text{Cable loss}}\left[dB\right] - G_{\text{preamp}}\left[dB\right]$ 

A<sub>T</sub>: Total correction Factor except Antenna

CCIC-SET/T (00) Page 45 of 69



U<sub>R</sub>: Receiver Reading

G<sub>preamp</sub>: Preamplifier Gain

A<sub>Factor</sub>: Antenna Factor at 3m

NOTE 1: The red vertical lines "F1" in the following charts is to indicate the frequencies 2400MHz and 2483.5MHz respectively


NOTE 2: Both horizontal and vertical polarity direction of the test antenna has been performed, only the worst case recorded in this report.

#### 802.11b

## A. Test Verdict:

| Channel | Frequency (MHz) | Detector PK/ AV | Receiver<br>Reading<br>UR<br>(dBuV) | AT (dB) | AFactor (dB@3m) | Max. Emission E (dB µV/m) | Limit<br>(dB µV/m) | Verdict |
|---------|-----------------|-----------------|-------------------------------------|---------|-----------------|---------------------------|--------------------|---------|
| 1       | 2388.479        | PK              | 50.33                               | -31.70  | 28.30           | 46.93                     | 74.00              | Pass    |
| 1       | 2388.479        | AV              | 39.67                               | -31.70  | 28.30           | 36.27                     | 54.00              | Pass    |
| 11      | 2493.262        | PK              | 50.82                               | -29.45  | 29.20           | 50.57                     | 74.00              | Pass    |
| 11      | 2493.262        | AV              | 40.04                               | -29.45  | 29.20           | 39.79                     | 54.00              | Pass    |


## **B.** Test Plots:



(Plot 2.6 A1: Channel = 1 @ 802.11b)

CCIC-SET/T (00) Page 46 of 69





(Plot 2.6 A2: Channel = 11 @ 802.11b)

## 802.11g


## A. Test Verdict:

| Channel | Frequency (MHz) | Detector PK/AV | Receiver<br>Reading<br>UR<br>(dBuV) | AT (dB) | AFactor (dB@3m) | Max. Emission E (dB µV/m) | Limit<br>(dB µV/m) | Verdict |
|---------|-----------------|----------------|-------------------------------------|---------|-----------------|---------------------------|--------------------|---------|
| 1       | 2373.679        | PK             | 51.07                               | -31.70  | 28.30           | 47.67                     | 74.00              | Pass    |
| 1       | 2373.679        | AV             | 40.28                               | -31.70  | 28.30           | 36.88                     | 54.00              | Pass    |
| 11      | 2495.137        | PK             | 50.29                               | -29.45  | 29.20           | 50.04                     | 74.00              | Pass    |
| 11      | 2495.137        | AV             | 40.37                               | -29.45  | 29.20           | 40.12                     | 54.00              | Pass    |

## **B.** Test Plots:

CCIC-SET/T (00) Page 47 of 69





CCIC-SET/T (00) Page 48 of 69




## 802.11n-20

## A. Test Verdict:

| Channel | Frequency (MHz) | Detector PK/ AV | Receiver<br>Reading<br>UR<br>(dBuV) | AT (dB) | AFactor (dB@3m) | Max. Emission E (dB µV/m) | Limit<br>(dB µV/m) | Verdict |
|---------|-----------------|-----------------|-------------------------------------|---------|-----------------|---------------------------|--------------------|---------|
| 1       | 2388.276        | PK              | 50.97                               | -31.70  | 28.30           | 47.57                     | 74.00              | Pass    |
| 1       | 2388.276        | AV              | 40.23                               | -31.70  | 28.30           | 36.83                     | 54.00              | Pass    |
| 11      | 2496.159        | PK              | 50.23                               | -29.45  | 29.20           | 49.98                     | 74.00              | Pass    |
| 11      | 2496.159        | AV              | 39.93                               | -29.45  | 29.20           | 39.68                     | 54.00              | Pass    |


## **B.** Test Plots:



(Plot 2.6 C1: Channel = 1 @ 802.11n-20)

CCIC-SET/T (00) Page 49 of 69





(Plot 2.6 C2: Channel = 11 @ 802.11n-20)

## 802.11n-40


## A. Test Verdict:

| Channel | Frequency (MHz) | Detector | Receiver<br>Reading<br>UR | AT (dB) | AFactor (dB@3m) | Max.<br>Emission<br>E | Limit (dB µV/m) | Verdict |
|---------|-----------------|----------|---------------------------|---------|-----------------|-----------------------|-----------------|---------|
|         | , ,             | PK/ AV   | (dBuV)                    | ` ′     | ,               | $(dB\mu V/m)$         | ` ' /           |         |
| 3       | 2355.60         | PK       | 51.07                     | -31.70  | 28.30           | 47.67                 | 74.00           | Pass    |
| 3       | 2355.60         | AV       | 40.93                     | -31.70  | 28.30           | 37.53                 | 54.00           | Pass    |
| 9       | 2489.97         | PK       | 50.95                     | -29.45  | 29.20           | 50.70                 | 74.00           | Pass    |
| 9       | 2489.97         | AV       | 39.89                     | -29.45  | 29.20           | 39.64                 | 54.00           | Pass    |

## **B.** Test Plots:

CCIC-SET/T (00) Page 50 of 69





CCIC-SET/T (00) Page 51 of 69



## 2.7 Conducted Emission

## 2.7.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a  $50\mu H/50\Omega$  line impedance stabilization network (LISN).


| Frequency range (MHz)  | Conducted Lin | mit (dB μV) |  |  |
|------------------------|---------------|-------------|--|--|
| riequency range (WIHZ) | Quai-peak     | Average     |  |  |
| 0.15 - 0.50            | 66 to 56      | 56 to 46    |  |  |
| 0.50 - 5               | 56            | 46          |  |  |
| 5 - 30                 | 60            | 50          |  |  |

#### NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 0.50MHz.

## 2.7.2 Test Description

#### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

The EUT is powered by a PC. The factors of the site are calibrated to correct the reading. During the measurement, the EUT is activated and controlled by the Wi-Fi Service Supplier (SS) via a Common Antenna.

CCIC-SET/T (00) Page 52 of 69





## **B.** Equipments List:

| Description   | Manufacturer  | Model   | Serial No. | Cal. Date  | Cal. Due Date |
|---------------|---------------|---------|------------|------------|---------------|
| Test Receiver | ROHDE&SCHWARZ | ESCS30  | A0304260   | 2014.06.10 | 2015.06.09    |
| LISN          | ROHDE&SCHWARZ | ESH2-Z5 | A0304221   | 2014.06.10 | 2015.06.09    |
| Cable         | MATCHING PAD  | W7      | /          | 2014.06.05 | 2015.06.04    |


## 2.7.3 Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

#### **A.** Test setup:

The EUT configuration of the emission tests is EUT + PC.


## **B.** Test Plots:



(Plot A: L Phase)

CCIC-SET/T (00) Page 53 of 69





(Plot B: N Phase)

**Test Result: PASS** 

CCIC-SET/T (00) Page 54 of 69



## 2.8 Radiated Emission

## 2.8.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (µV/m) | Field Strength (dB µV/m)   | Measurement<br>Distance (m) |
|-----------------|-----------------------|----------------------------|-----------------------------|
| 0.009 - 0.490   | 2400/F(kHz)           | 20log(2400/F(KHz))+80      | 300                         |
| 0.490 - 1.705   | 24000/F(kHz)          | 20log(24000/F(KHz))+4<br>0 | 30                          |
| 1.705 - 30.0    | 30                    | 20log(30)+40               | 30                          |
| 30 - 88         | 100                   | 40.0                       | 3                           |
| 88 - 216        | 150                   | 43.5                       | 3                           |
| 216 - 960       | 200                   | 46.0                       | 3                           |
| Above 960       | 500                   | 54.0                       | 3                           |

#### Note:

- 1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
- 2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


CCIC-SET/T (00) Page 55 of 69




# 2.8.2 Test Description

## A. Test Setup:

(1) For radiated emissions from 9kHz to 30MHz




(2) For radiated emissions from 30MHz to1GHz



CCIC-SET/T (00) Page 56 of 69



## (3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The EUT was powered by the AC adapter. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, the EUT is activated and controlled by the PC, set to operate under WIFI test mode.

#### For the Test Antenna:

- (a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

CCIC-SET/T (00) Page 57 of 69



## **B.** Equipments List:

| Description           | Manufacturer | Model       | Serial No.  | Cal. Date  | Cal. Due Date |  |
|-----------------------|--------------|-------------|-------------|------------|---------------|--|
| Receiver              | R&S          | ESIB26      | A0304218    | 2014.06.07 | 2015.06.06    |  |
| Full-Anechoic         | Albatross    | 12.8m*6.8m* | A0412372    | 2014.06.07 | 2015.06.06    |  |
| Chamber               | Albanoss     | 6.4m        | A0412372    | 2014.00.07 | 2013.00.00    |  |
| Test Antenna - Bi-Log | Schwarzbeck  | VULB 9163   | 9163-274    | 2014.06.09 | 2015.06.08    |  |
| Test Antenna - Horn   | R&S          | BBHA        | 9120C-963   | 2014.06.09 | 2015.06.08    |  |
| 168t Antenna - 110m   | K&S          | 9120D       | 9120C-903   | 2014.00.09 | 2013.00.00    |  |
| Test Antenna - Horn   | R&S          | HF960       | 100150      | 2014.06.09 | 2015.06.08    |  |
| Test Antenna – Horn   | ETS          | UG-596A/U   | A0902607    | 2014.06.05 | 2015.06.04    |  |
| (18-25GHz)            | EIS          | UG-390A/U   | A0902007    | 2014.00.03 | 2013.00.04    |  |
| Test Antenna -Loop    | Schwarzbeck  | HFH2-Z2     | 100047      | 2014.06.02 | 2015.06.01    |  |
|                       |              | MITEQ       |             |            |               |  |
| Ampilier 1G~18GHz     | R&S          | AFS42-0010  | 25-S-42     | 2014.06.05 | 2015.06.04    |  |
|                       |              | 1800        |             |            |               |  |
| Ampilier              | R&S          | JS42-180026 | 12111.0980. | 2014.06.05 | 2015.06.04    |  |
| 18G~40GHz             | Kas          | 00-28-5A    | 00          | 2014.00.03 | 2013.00.04    |  |
| amplifier 20M~3GHz    | R&S          | PAP-0203H   | 22018       | 2014.06.10 | 2015.06.09    |  |
| Cable                 | SUNHNER      | SUCOFLEX    | ,           | 2014 06 05 | 2015 06 04    |  |
| Cable                 | SUNHINEK     | 100         | /           | 2014.06.05 | 2015.06.04    |  |
| Cabla                 | CHMILINED    | SUCOFLEX    | /           | 2014 06 05 | 2015 06 04    |  |
| Cable                 | SUNHNER      | 104         | /           | 2014.06.05 | 2015.06.04    |  |
|                       |              |             |             |            |               |  |

## 2.8.3 Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

 $E[dB\mu V/m] = U_R + A_T + A_{Factor}[dB]; A_T = L_{Cable loss}[dB] - G_{preamp}[dB]$ 

A<sub>T</sub>: Total correction Factor except Antenna

U<sub>R</sub>: Receiver Reading
G<sub>preamp</sub>: Preamplifier Gain
A<sub>Factor</sub>: Antenna Factor at 3m

Lcable loss: Cable loss

During the test, the total correction Factor AT and A<sub>Factor</sub> were built in test software.

Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The minimum clock frequency was 24MHz, the radiated frequency range from 9KHz to 25GHz.

CCIC-SET/T (00) Page 58 of 69



Note: 1.The radiated measurement are performed the each test mode (b/g/n) and channel (low/mid/high), the datum recorded below (802.11b mode, the middle channel) is the worst case for all the test mode and channel.


- 2. ULTRA-BROADBAND ANTENNA for the radiation emission test below 1G.
- 3. HORN ANTENNA for the radiation emission test above 1G.

Test plots for the whole measurement frequency range:

#### For 9KHz to 30MHz

The test has been performed, and the Radiated Emission level is too low to the limit.

#### For 30MHz to 1000 MHz




(Plot A: 30MHz to 1GHz, Antenna Vertical)

| Frequency<br>(MHz) | QuasiPeak<br>(dBµ V/m) | Bandwidth<br>(kHz) | Antenna<br>height<br>(cm) | Limit<br>(dBµ V/m) | Antenna  | Verdict |
|--------------------|------------------------|--------------------|---------------------------|--------------------|----------|---------|
| 37.4900            | 30.41                  | 120.000            | 100.0                     | 40.0               | Vertical | Pass    |
| 189.1500           | 29.43                  | 120.000            | 100.0                     | 43.5               | Vertical | Pass    |

CCIC-SET/T (00) Page 59 of 69





(Plot B: 30MHz to 1GHz, Antenna Horizontal)

| Frequency<br>(MHz) | QuasiPeak<br>(dΒμV/m) | Bandwidth<br>(kHz) | Antenna<br>height<br>(cm) | Limit<br>(dBµV/m) | Antenna    | Verdict |
|--------------------|-----------------------|--------------------|---------------------------|-------------------|------------|---------|
| 133.0200           | 33.17                 | 120.000            | 100.0                     | 43.5              | Horizontal | Pass    |
| 263.2500           | 30.47                 | 120.000            | 100.0                     | 46.0              | Horizontal | Pass    |

## For 1GHz to 25GHz

802.11b Mode

| AN  | ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b2412MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |  |
|-----|--|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|--|
| N   | Frequency  | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |  |
| No. | (MHz)  | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |  |
| 1   | *2412.00   | 108.88 | PK   | /        | /      | 1.00 H  | 118   | 112.28 | 28.30   | 4.90   | -36.60    |  |  |  |  |
| 1   | *2412.00   | 98.22  | AV   | /        | /      | 1.00 H  | 118   | 101.62 | 28.30   | 4.90   | -36.60    |  |  |  |  |
| 2   | 4824.00  | 52.08  | PK   | 74.00    | 21.92  | 1.00 H  | 24    | 48.88  | 32.70   | 7.00   | -36.50    |  |  |  |  |
| 2   | 4824.00  | 46.31  | AV   | 54.00    | 7.69   | 1.00 H  | 24    | 43.11  | 32.70   | 7.00   | -36.50    |  |  |  |  |
| 3   | 7236.00  | 50.86  | PK   | 74.00    | 23.14  | 1.00 H  | 107   | 41.46  | 35.80   | 8.90   | -35.30    |  |  |  |  |
| 3   | 7236.00  | 43.62  | AV   | 54.00    | 10.38  | 1.00 H  | 107   | 34.22  | 35.80   | 8.90   | -35.30    |  |  |  |  |
| 4   | 9648.00  | 50.64  | PK   | 74.00    | 23.36  | 1.00 H  | 39    | 38.04  | 37.20   | 10.20  | -34.80    |  |  |  |  |
| 4   | 9648.00  | 44.53  | AV   | 54.00    | 9.47   | 1.00 H  | 39    | 31.93  | 37.20   | 10.20  | -34.80    |  |  |  |  |

CCIC-SET/T (00) Page 60 of 69





| A   | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b2412MHz) |        |    |                   |             |                   |                |              |                   |                 |                   |  |  |  |  |
|-----|--|--------|----|-------------------|-------------|-------------------|----------------|--------------|-------------------|-----------------|-------------------|--|--|--|--|
| No. | Frequency (MHz)  | Emss   |    | Limit<br>(dBuV/m) | Margin (dB) | Antenna<br>Height | Table<br>Angle | Raw<br>Value | Antenna<br>Factor | Cable<br>Factor | Pre-<br>amplifier |  |  |  |  |
| 1   | *2412.00   | 109.43 | PK | /                 | /           | 1.00 V            | 109            | 112.83       | 28.30             | 4.90            | -36.60            |  |  |  |  |
| 1   | *2412.00   | 98.74  | AV | /                 | /           | 1.00 V            | 109            | 102.14       | 28.30             | 4.90            | -36.60            |  |  |  |  |
| 2   | 4824.00  | 52.23  | PK | 74.00             | 21.77       | 1.00 V            | 62             | 49.03        | 32.70             | 7.00            | -36.50            |  |  |  |  |
| 2   | 4824.00  | 45.76  | AV | 54.00             | 8.24        | 1.00 V            | 62             | 42.56        | 32.70             | 7.00            | -36.50            |  |  |  |  |
| 3   | 7236.00  | 51.35  | PK | 74.00             | 22.65       | 1.00 V            | 349            | 41.95        | 35.80             | 8.90            | -35.30            |  |  |  |  |
| 3   | 7236.00  | 44.07  | AV | 54.00             | 9.93        | 1.00 V            | 349            | 34.67        | 35.80             | 8.90            | -35.30            |  |  |  |  |
| 4   | 9648.00  | 55.18  | PK | 74.00             | 18.82       | 1.00 V            | 211            | 42.58        | 37.20             | 10.20           | -34.80            |  |  |  |  |
| 4   | 9648.00  | 46.11  | AV | 54.00             | 7.89        | 1.00 V            | 211            | 33.51        | 37.20             | 10.20           | -34.80            |  |  |  |  |

| AN  | TENNA PO  | DLARI  | TY 8 | TEST D   | ISTANO | CE: HORI | ZONTAI | LAT 3 M | (802.11 | b2437  | MHz)      |
|-----|-----------|--------|------|----------|--------|----------|--------|---------|---------|--------|-----------|
| NT  | Frequency | Emss   | sion | Limit    | Margin | Antenna  | Table  | Raw     | Antenna | Cable  | Pre-      |
| No. | (MHz)     | Lev    | /el  | (dBuV/m) | (dB)   | Height   | Angle  | Value   | Factor  | Factor | amplifier |
| 1   | *2437.00  | 107.54 | PK   | /        | /      | 1.00 H   | 202    | 110.74  | 28.30   | 5.10   | -36.60    |
| 1   | *2437.00  | 99.89  | AV   | /        | /      | 1.00 H   | 202    | 103.09  | 28.30   | 5.10   | -36.60    |
| 2   | 4874.00   | 53.62  | PK   | 74.00    | 20.38  | 1.00 H   | 187    | 50.22   | 32.30   | 7.60   | -36.50    |
| 2   | 4874.00   | 47.41  | AV   | 54.00    | 6.59   | 1.00 H   | 187    | 44.01   | 32.30   | 7.60   | -36.50    |
| 3   | 7311.00   | 54.09  | PK   | 74.00    | 19.91  | 1.00 H   | 107    | 44.69   | 36.10   | 8.60   | -35.30    |
| 3   | 7311.00   | 47.61  | AV   | 54.00    | 6.39   | 1.00 H   | 107    | 38.21   | 36.10   | 8.60   | -35.30    |
| 4   | 9748.00   | 49.44  | PK   | 74.00    | 24.56  | 1.00 H   | 144    | 36.84   | 37.20   | 10.20  | -34.80    |
| 4   | 9748.00   | 43.49  | AV   | 54.00    | 10.51  | 1.00 H   | 144    | 30.89   | 37.20   | 10.20  | -34.80    |

| A   | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802,11b2437MHz) |        |     |          |        |         |       |        |         |        |           |  |  |  |  |
|-----|--|--------|-----|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|--|
| No. | Frequency  | Emss   |     | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |  |
|     | (MHz)  | Lev    | /el | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |  |
| 1   | *2437.00   | 108.01 | PK  | /        | /      | 1.00 V  | 104   | 111.21 | 28.30   | 5.10   | -36.60    |  |  |  |  |
| 1   | *2437.00   | 97.82  | AV  | /        | /      | 1.00 V  | 104   | 101.02 | 28.30   | 5.10   | -36.60    |  |  |  |  |
| 2   | 4874.00  | 51.12  | PK  | 74.00    | 22.88  | 1.00 V  | 304   | 47.72  | 32.30   | 7.60   | -36.50    |  |  |  |  |
| 2   | 4874.00  | 46.92  | AV  | 54.00    | 7.08   | 1.00 V  | 304   | 43.52  | 32.30   | 7.60   | -36.50    |  |  |  |  |
| 3   | 7311.00  | 49.84  | PK  | 74.00    | 24.16  | 1.00 V  | 203   | 40.44  | 36.10   | 8.60   | -35.30    |  |  |  |  |
| 3   | 7311.00  | 47.41  | AV  | 54.00    | 6.59   | 1.00 V  | 203   | 38.01  | 36.10   | 8.60   | -35.30    |  |  |  |  |
| 4   | 9748.00  | 49.38  | PK  | 74.00    | 24.62  | 1.00 V  | 172   | 36.78  | 37.20   | 10.20  | -34.80    |  |  |  |  |
| 4   | 9748.00  | 44.39  | AV  | 54.00    | 9.61   | 1.00 V  | 172   | 31.79  | 37.20   | 10.20  | -34.80    |  |  |  |  |

| AN  | TENNA PO  | <b>DLARI</b> | TY & | TEST D   | ISTANC | CE: HORI | ZONTAI | LAT 3 M | (802.11 | b2462  | 2MHz)     |
|-----|-----------|--------------|------|----------|--------|----------|--------|---------|---------|--------|-----------|
| N.  | Frequency | Emss         | sion | Limit    | Margin | Antenna  | Table  | Raw     | Antenna | Cable  | Pre-      |
| No. | (MHz)     | Lev          | el   | (dBuV/m) | (dB)   | Height   | Angle  | Value   | Factor  | Factor | amplifier |
| 1   | *2462.00  | 110.57       | PK   | /        | /      | 1.00 H   | 325    | 113.87  | 28.60   | 4.70   | -36.60    |

CCIC-SET/T (00) Page 61 of 69





| 1 | *2462.00 | 99.81 | AV | /     | /     | 1.00 H | 325 | 103.11 | 28.60 | 4.70  | -36.60 |
|---|----------|-------|----|-------|-------|--------|-----|--------|-------|-------|--------|
| 2 | 4924.00  | 52.64 | PK | 74.00 | 21.36 | 1.00 H | 311 | 48.84  | 33.00 | 7.00  | -36.20 |
| 2 | 4924.00  | 47.46 | AV | 54.00 | 6.54  | 1.00 H | 311 | 43.66  | 33.00 | 7.00  | -36.20 |
| 3 | 7386.00  | 50.36 | PK | 74.00 | 23.64 | 1.00 H | 330 | 40.96  | 36.20 | 8.50  | -35.30 |
| 3 | 7386.00  | 46.79 | AV | 54.00 | 7.21  | 1.00 H | 330 | 37.39  | 36.20 | 8.50  | -35.30 |
| 4 | 9848.00  | 51.80 | PK | 74.00 | 22.20 | 1.00 H | 42  | 39.20  | 37.20 | 10.20 | -34.80 |
| 4 | 9848.00  | 48.49 | AV | 54.00 | 5.51  | 1.00 H | 42  | 35.89  | 37.20 | 10.20 | -34.80 |

| A   | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b2462MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |  |
|-----|--|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|--|
|     | Frequency  | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |  |
| No. | (MHz)  | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |  |
| 1   | *2462.00   | 112.47 | PK   | /        | /      | 1.00 V  | 34    | 115.77 | 28.60   | 4.70   | -36.60    |  |  |  |  |
| 1   | *2462.00   | 99.89  | AV   | /        | /      | 1.00 V  | 34    | 103.19 | 28.60   | 4.70   | -36.60    |  |  |  |  |
| 2   | 4924.00  | 50.76  | PK   | 74.00    | 23.24  | 1.00 V  | 55    | 46.96  | 33.00   | 7.00   | -36.20    |  |  |  |  |
| 2   | 4924.00  | 43.52  | AV   | 54.00    | 10.48  | 1.00 V  | 55    | 39.72  | 33.00   | 7.00   | -36.20    |  |  |  |  |
| 3   | 7386.00  | 51.57  | PK   | 74.00    | 22.43  | 1.00 V  | 258   | 42.17  | 36.20   | 8.50   | -35.30    |  |  |  |  |
| 3   | 7386.00  | 47.87  | AV   | 54.00    | 6.13   | 1.00 V  | 258   | 38.47  | 36.20   | 8.50   | -35.30    |  |  |  |  |
| 4   | 9848.00  | 50.25  | PK   | 74.00    | 23.75  | 1.00 V  | 254   | 37.65  | 37.20   | 10.20  | -34.80    |  |  |  |  |
| 4   | 9848.00  | 48.56  | AV   | 54.00    | 5.44   | 1.00 V  | 254   | 35.96  | 37.20   | 10.20  | -34.80    |  |  |  |  |

## 802.11g Mode

| AIN                   | ITENNA PO  | OLARI   | TY 8           | TEST D                       | ISTANO                  | CE: HORI                                       | ZONTAI                  | LAT 3 M   | (802.11                              | g2412                                | 2MHz)  |
|-----------------------|--|---|----------------|------------------------------|-------------------------|--|-------------------------|---|--------------------------------------|--------------------------------------|--|
| No.                   | Frequency  | Emss  |                | Limit                        | Margin                  | Antenna  | Table                   | Raw   | Antenna                              | Cable                                | Pre-   |
|                       | (MHz)  | Lev   | /ei            | (dBuV/m)                     | (dB)                    | Height   | Angle                   | Value   | Factor                               | Factor                               | amplifier                                    |
| 1                     | *2412.00   | 109.21  | PK             | /                            | /                       | 1.00 H   | 19                      | 112.51  | 28.30                                | 5.00                                 | -36.60                                       |
| 1                     | *2412.00   | 99.03   | AV             | /                            | /                       | 1.00 H   | 19                      | 102.33  | 28.30                                | 5.00                                 | -36.60                                       |
| 2                     | 4824.00  | 52.84   | PK             | 74.00                        | 21.16                   | 1.00 H   | 321                     | 49.04   | 32.70                                | 7.30                                 | -36.20                                       |
| 2                     | 4824.00  | 47.60   | AV             | 54.00                        | 6.40                    | 1.00 H   | 321                     | 43.80   | 32.70                                | 7.30                                 | -36.20                                       |
| 3                     | 7236.00  | 51.57   | PK             | 74.00                        | 22.43                   | 1.00 H   | 207                     | 42.17   | 35.80                                | 8.90                                 | -35.30                                       |
| 3                     | 7236.00  | 47.47   | AV             | 54.00                        | 6.53                    | 1.00 H   | 207                     | 38.07   | 35.80                                | 8.90                                 | -35.30                                       |
| 4                     | 9648.00  | 50.96   | PK             | 74.00                        | 23.04                   | 1.00 H   | 304                     | 38.36   | 37.20                                | 10.20                                | -34.80                                       |
| 4                     | 9648.00  | 44.38   | AV             | 54.00                        | 9.62                    | 1.00 H   | 304                     | 31.78   | 37.20                                | 10.20                                | -34.80                                       |
| A                     | NTENNA I   | POLAI   | RITY           | & TEST                       | DISTA                   | NCE: VER                                       | TICAL A                 | AT 3 M  | (802.11g-                            | 2412N                                | (Hz)   |
|                       | Frequency  | Emss  | sion           | Limit                        | Monoin                  | Antonno  | T-1-1-                  | ъ   |                                      | ~                                    |  |
| No.                   |  | Lino  | 31011          | Lilliit                      | Margin                  | Antenna  | Table                   | Raw   | Antenna                              | Cable                                | Pre-   |
| 110.                  | (MHz)  | Lev   |                | (dBuV/m)                     | _                       | Height   | Angle                   | Value   | Factor                               | Cable<br>Factor                      | Pre-<br>amplifier                            |
| 1                     |  |   | vel            |                              | _                       |  |                         |   |                                      |                                      |  |
|                       | (MHz)  | Lev   | vel            |                              | _                       | Height   | Angle                   | Value   | Factor                               | Factor                               | amplifier                                    |
| 1                     | (MHz)<br>*2412.00  | Lev<br>106.98                                     | vel<br>PK      |                              | _                       | Height<br>1.00 V                               | Angle 174               | Value 110.28  | Factor 28.30                         | Factor 5.00                          | amplifier -36.60                             |
| 1 1                   | (MHz)<br>*2412.00<br>*2412.00                                  | Lev<br>106.98<br>96.40                            | PK<br>AV       | (dBuV/m) /                   | (dB) /                  | Height<br>1.00 V<br>1.00 V                     | Angle<br>174<br>174     | Value<br>110.28<br>99.70                            | Factor 28.30 28.30                   | 5.00<br>5.00                         | amplifier -36.60 -36.60                      |
| 1<br>1<br>2           | (MHz)<br>*2412.00<br>*2412.00<br>4824.00                       | Lev<br>106.98<br>96.40<br>53.40                   | PK AV PK       | (dBuV/m) / 74.00             | (dB) / 20.60            | Height 1.00 V 1.00 V 1.00 V                    | Angle 174 174 68        | Value<br>110.28<br>99.70<br>49.60                   | Factor 28.30 28.30 32.70             | 5.00<br>5.00<br>7.30                 | -36.60<br>-36.60<br>-36.20                   |
| 1<br>1<br>2<br>2      | (MHz)<br>*2412.00<br>*2412.00<br>4824.00<br>4824.00            | Lev<br>106.98<br>96.40<br>53.40<br>47.77          | PK AV PK AV    | (dBuV/m) / 74.00 54.00       | (dB) / / 20.60 6.23     | Height  1.00 V  1.00 V  1.00 V  1.00 V         | Angle 174 174 68 68     | Value<br>110.28<br>99.70<br>49.60<br>43.97          | Factor 28.30 28.30 32.70 32.70       | 5.00<br>5.00<br>7.30<br>7.30         | amplifier -36.60 -36.60 -36.20 -36.20        |
| 1<br>1<br>2<br>2<br>3 | (MHz)<br>*2412.00<br>*2412.00<br>4824.00<br>4824.00<br>7236.00 | Lev<br>106.98<br>96.40<br>53.40<br>47.77<br>52.35 | PK AV PK AV PK | (dBuV/m) / 74.00 54.00 74.00 | (dB) / 20.60 6.23 21.65 | Height  1.00 V  1.00 V  1.00 V  1.00 V  1.00 V | Angle 174 174 68 68 169 | Value<br>110.28<br>99.70<br>49.60<br>43.97<br>42.95 | Factor 28.30 28.30 32.70 32.70 35.80 | 5.00<br>5.00<br>7.30<br>7.30<br>8.90 | amplifier -36.60 -36.60 -36.20 -36.20 -35.30 |

Page 62 of 69 CCIC-SET/T (00)





| AN  | ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g2437MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|-----|--|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
|     | Frequency  | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| No. | (MHz)  | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1   | *2437.00   | 108.54 | PK   | /        | /      | 1.00 H  | 54    | 111.74 | 28.30   | 5.10   | -36.60    |  |  |  |
| _11 | *2437.00   | 97.75  | AV   | /        | /      | 1.00 H  | 54    | 100.95 | 28.30   | 5.10   | -36.60    |  |  |  |
| 2   | 4874.00  | 51.24  | PK   | 74.00    | 22.76  | 1.00 H  | 117   | 47.84  | 32.80   | 7.10   | -36.50    |  |  |  |
| 2   | 4874.00  | 46.37  | AV   | 54.00    | 7.63   | 1.00 H  | 117   | 42.97  | 32.80   | 7.10   | -36.50    |  |  |  |
| 3   | 7311.00  | 50.20  | PK   | 74.00    | 23.80  | 1.00 H  | 328   | 40.80  | 36.10   | 8.60   | -35.30    |  |  |  |
| 3   | 7311.00  | 45.14  | AV   | 54.00    | 8.86   | 1.00 H  | 328   | 35.74  | 36.10   | 8.60   | -35.30    |  |  |  |
| 4   | 9748.00  | 51.16  | PK   | 74.00    | 22.84  | 1.00 H  | 19    | 38.56  | 37.20   | 10.20  | -34.80    |  |  |  |
| 4   | 9748.00  | 45.31  | AV   | 54.00    | 8.69   | 1.00 H  | 19    | 32.71  | 37.20   | 10.20  | -34.80    |  |  |  |

| A    | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g2437MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|------|--|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
| No.  | Frequency  | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| 110. | (MHz)  | Lev    | vel  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1    | *2437.00   | 108.12 | PK   | /        | /      | 1.00 V  | 122   | 111.32 | 28.30   | 5.10   | -36.60    |  |  |  |
| 1    | *2437.00   | 97.60  | AV   | /        | /      | 1.00 V  | 122   | 100.80 | 28.30   | 5.10   | -36.60    |  |  |  |
| 2    | 4874.00  | 51.90  | PK   | 74.00    | 22.10  | 1.00 V  | 156   | 48.50  | 32.80   | 7.10   | -36.50    |  |  |  |
| 2    | 4874.00  | 47.34  | AV   | 54.00    | 6.66   | 1.00 V  | 156   | 43.94  | 32.80   | 7.10   | -36.50    |  |  |  |
| 3    | 7311.00  | 50.24  | PK   | 74.00    | 23.76  | 1.00 V  | 98    | 40.84  | 36.10   | 8.60   | -35.30    |  |  |  |
| 3    | 7311.00  | 46.23  | AV   | 54.00    | 7.77   | 1.00 V  | 98    | 36.83  | 36.10   | 8.60   | -35.30    |  |  |  |
| 4    | 9748.00  | 49.31  | PK   | 74.00    | 24.69  | 1.00 V  | 197   | 36.71  | 37.20   | 10.20  | -34.80    |  |  |  |
| 4    | 9748.00  | 45.21  | AV   | 54.00    | 8.79   | 1.00 V  | 197   | 32.61  | 37.20   | 10.20  | -34.80    |  |  |  |

| AN  | ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g2462MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|-----|--|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
| N   | Frequency  | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| No. | (MHz)  | Lev    | el   | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1   | *2462.00   | 107.23 | PK   | /        | /      | 1.00 V  | 103   | 110.53 | 28.20   | 5.10   | -36.60    |  |  |  |
| 1   | *2462.00   | 99.78  | AV   | /        | /      | 1.00 V  | 103   | 103.08 | 28.20   | 5.10   | -36.60    |  |  |  |
| 2   | 4924.00  | 50.92  | PK   | 74.00    | 23.08  | 1.00 V  | 342   | 47.12  | 33.00   | 7.00   | -36.20    |  |  |  |
| 2   | 4924.00  | 44.21  | AV   | 54.00    | 9.79   | 1.00 V  | 342   | 40.41  | 33.00   | 7.00   | -36.20    |  |  |  |
| 3   | 7386.00  | 51.03  | PK   | 74.00    | 22.97  | 1.00 V  | 179   | 41.63  | 36.20   | 8.50   | -35.30    |  |  |  |
| 3   | 7386.00  | 46.11  | AV   | 54.00    | 7.89   | 1.00 V  | 179   | 36.71  | 36.20   | 8.50   | -35.30    |  |  |  |
| 4   | 9848.00  | 50.59  | PK   | 74.00    | 23.41  | 1.00 V  | 293   | 37.99  | 37.30   | 10.10  | -34.80    |  |  |  |
| 4   | 9848.00  | 46.10  | AV   | 54.00    | 7.90   | 1.00 V  | 293   | 33.50  | 37.30   | 10.10  | -34.80    |  |  |  |

| A   | NTENNA I  | POLARITY | & TEST   | DISTAN | NCE: VER | RTICAL | AT 3 M | (802.11g | 2462N  | IHz)      |
|-----|-----------|----------|----------|--------|----------|--------|--------|----------|--------|-----------|
| NI- | Frequency | Emssion  | Limit    | Margin | Antenna  | Table  | Raw    | Antenna  | Cable  | Pre-      |
| No. | (MHz)     | Level    | (dBuV/m) | (dB)   | Height   | Angle  | Value  | Factor   | Factor | amplifier |

CCIC-SET/T (00) Page 63 of 69





| 1 | *2462.00 | 107.69 | PK | /     | /     | 1.00 H | 220 | 110.99 | 28.20 | 5.10  | -36.60 |
|---|----------|--------|----|-------|-------|--------|-----|--------|-------|-------|--------|
| 1 | *2462.00 | 98.24  | AV | /     | /     | 1.00 H | 220 | 101.54 | 28.20 | 5.10  | -36.60 |
| 2 | 4924.00  | 52.30  | PK | 74.00 | 21.70 | 1.00 H | 343 | 48.50  | 33.00 | 7.00  | -36.20 |
| 2 | 4924.00  | 47.17  | AV | 54.00 | 6.83  | 1.00 H | 343 | 43.37  | 33.00 | 7.00  | -36.20 |
| 3 | 7386.00  | 50.34  | PK | 74.00 | 23.66 | 1.00 H | 135 | 40.94  | 36.20 | 8.50  | -35.30 |
| 3 | 7386.00  | 46.45  | AV | 54.00 | 7.55  | 1.00 H | 135 | 37.05  | 36.20 | 8.50  | -35.30 |
| 4 | 9848.00  | 48.24  | PK | 74.00 | 25.76 | 1.00 H | 177 | 35.64  | 37.30 | 10.10 | -34.80 |
| 4 | 9848.00  | 44.44  | AV | 54.00 | 9.56  | 1.00 H | 177 | 31.84  | 37.30 | 10.10 | -34.80 |

## 802.11n-20 Mode

9648.00

45.60 AV

54.00

8.40

| ANT | ENNA POI  | LARIT  | Y & ' | TEST DIS | STANCI | E: HORIZ | ONTAL  | <b>AT 3 M</b> | (802.11n  | -2024  | 12MHz)    |
|-----|-----------|--------|-------|----------|--------|----------|--------|---------------|-----------|--------|-----------|
|     | Frequency | Emss   | sion  | Limit    | Margin | Antenna  | Table  | Raw           | Antenna   | Cable  | Pre-      |
| No. | (MHz)     | Lev    | /el   | (dBuV/m) | (dB)   | Height   | Angle  | Value         | Factor    | Factor | amplifier |
| 1   | *2412.00  | 106.50 | PK    | /        | /      | 1.00 H   | 71     | 109.80        | 28.30     | 5.00   | -36.60    |
| 1   | *2412.00  | 97.15  | AV    | /        | /      | 1.00 H   | 71     | 100.45        | 28.30     | 5.00   | -36.60    |
| 2   | 4824.00   | 51.85  | PK    | 74.00    | 22.15  | 1.00 H   | 150    | 48.05         | 32.70     | 7.30   | -36.20    |
| 2   | 4824.00   | 45.83  | AV    | 54.00    | 8.17   | 1.00 H   | 150    | 42.03         | 32.70     | 7.30   | -36.20    |
| 3   | 7236.00   | 51.01  | PK    | 74.00    | 22.99  | 1.00 H   | 337    | 41.61         | 35.80     | 8.90   | -35.30    |
| 3   | 7236.00   | 47.23  | AV    | 54.00    | 6.77   | 1.00 H   | 337    | 37.83         | 35.80     | 8.90   | -35.30    |
| 4   | 9648.00   | 50.42  | PK    | 74.00    | 23.58  | 1.00 H   | 12     | 37.82         | 37.20     | 10.20  | -34.80    |
| 4   | 9648.00   | 45.02  | AV    | 54.00    | 8.98   | 1.00 H   | 12     | 32.42         | 37.20     | 10.20  | -34.80    |
| AN  | TENNA PO  | OLARI  | TY 8  | & TEST D | ISTAN  | CE: VERT | TICALA | Г3М (8        | 302.11n-2 | 02412  | MHz)      |
| No. | Frequency | Emss   | sion  | Limit    | Margin | Antenna  | Table  | Raw           | Antenna   | Cable  | Pre-      |
| No. | (MHz)     | Lev    | /el   | (dBuV/m) | (dB)   | Height   | Angle  | Value         | Factor    | Factor | amplifier |
| 1   | *2412.00  | 109.89 | PK    | /        | /      | 1.00 V   | 189    | 113.19        | 28.30     | 5.00   | -36.60    |
| 1   | *2412.00  | 98.27  | AV    | /        | /      | 1.00 V   | 189    | 101.57        | 28.30     | 5.00   | -36.60    |
| 2   | 4824.00   | 50.65  | PK    | 74.00    | 23.35  | 1.00 V   | 96     | 46.85         | 32.70     | 7.30   | -36.20    |
| 2   | 4824.00   | 44.66  | AV    | 54.00    | 9.34   | 1.00 V   | 96     | 40.86         | 32.70     | 7.30   | -36.20    |
| 3   | 7236.00   | 51.63  | PK    | 74.00    | 22.37  | 1.00 V   | 233    | 42.23         | 35.80     | 8.90   | -35.30    |
| 3   | 7236.00   | 47.33  | AV    | 54.00    | 6.67   | 1.00 V   | 233    | 37.93         | 35.80     | 8.90   | -35.30    |
| 4   | 9648.00   | 49.30  | PK    | 74.00    | 24.70  | 1.00 V   | 304    | 36.70         | 37.20     | 10.20  | -34.80    |

| ANT | ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n-202437MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|-----|---|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
|     | Frequency   | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| No. | (MHz)   | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1   | *2437.00  | 108.19 | PK   | /        | /      | 1.00 H  | 349   | 111.39 | 28.30   | 5.10   | -36.60    |  |  |  |
| 1   | *2437.00  | 99.71  | AV   | /        | /      | 1.00 H  | 349   | 102.91 | 28.30   | 5.10   | -36.60    |  |  |  |
| 2   | 4874.00   | 52.56  | PK   | 74.00    | 21.44  | 1.00 H  | 309   | 49.16  | 32.30   | 7.60   | -36.50    |  |  |  |
| 2   | 4874.00   | 48.67  | AV   | 54.00    | 5.33   | 1.00 H  | 309   | 45.27  | 32.30   | 7.60   | -36.50    |  |  |  |
| 3   | 7311.00   | 51.58  | PK   | 74.00    | 22.42  | 1.00 H  | 188   | 42.18  | 36.10   | 8.60   | -35.30    |  |  |  |
| 3   | 7311.00   | 47.56  | AV   | 54.00    | 6.44   | 1.00 H  | 188   | 38.16  | 36.10   | 8.60   | -35.30    |  |  |  |

1.00 V

304

33.00

37.20

10.20

-34.80

CCIC-SET/T (00) Page 64 of 69



| 4 | 9748.00 | 50.17 | PK | 74.00 | 23.83 | 1.00 H | 74 | 37.57 | 37.20 | 10.20 | -34.80 |
|---|---------|-------|----|-------|-------|--------|----|-------|-------|-------|--------|
| 4 | 9748.00 | 46.49 | AV | 54.00 | 7.51  | 1.00 H | 74 | 33.89 | 37.20 | 10.20 | -34.80 |

| AN  | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n-202437MHz) |        |    |                   |             |                   |                |              |                   |                 |                   |  |  |  |
|-----|---|--------|----|-------------------|-------------|-------------------|----------------|--------------|-------------------|-----------------|-------------------|--|--|--|
| No. | Frequency (MHz)   | Emss   |    | Limit<br>(dBuV/m) | Margin (dB) | Antenna<br>Height | Table<br>Angle | Raw<br>Value | Antenna<br>Factor | Cable<br>Factor | Pre-<br>amplifier |  |  |  |
| 1   | *2437.00  | 109.52 | PK | /                 | /           | 1.00 V            | 205            | 112.72       | 28.30             | 5.10            | -36.60            |  |  |  |
| 1   | *2437.00  | 99.08  | AV | /                 | /           | 1.00 V            | 205            | 102.28       | 28.30             | 5.10            | -36.60            |  |  |  |
| 2   | 4874.00   | 53.44  | PK | 74.00             | 20.56       | 1.00 V            | 262            | 50.04        | 32.30             | 7.60            | -36.50            |  |  |  |
| 2   | 4874.00   | 49.24  | AV | 54.00             | 4.76        | 1.00 V            | 262            | 45.84        | 32.30             | 7.60            | -36.50            |  |  |  |
| 3   | 7311.00   | 51.94  | PK | 74.00             | 22.06       | 1.00 V            | 338            | 42.54        | 36.10             | 8.60            | -35.30            |  |  |  |
| 3   | 7311.00   | 46.31  | AV | 54.00             | 7.69        | 1.00 V            | 338            | 36.91        | 36.10             | 8.60            | -35.30            |  |  |  |
| 4   | 9748.00   | 50.55  | PK | 74.00             | 23.45       | 1.00 V            | 152            | 37.95        | 37.20             | 10.20           | -34.80            |  |  |  |
| 4   | 9748.00   | 42.55  | AV | 54.00             | 11.45       | 1.00 V            | 152            | 29.95        | 37.20             | 10.20           | -34.80            |  |  |  |

| ANT | ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n-202462MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|-----|---|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
| No. | Frequency   | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| NO. | (MHz)   | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1   | *2462.00  | 108.88 | PK   | /        | /      | 1.00 H  | 235   | 112.18 | 28.20   | 5.10   | -36.60    |  |  |  |
| 1   | *2462.00  | 100.03 | AV   | /        | /      | 1.00 H  | 235   | 103.33 | 28.20   | 5.10   | -36.60    |  |  |  |
| 2   | 4924.00   | 51.93  | PK   | 74.00    | 22.07  | 1.00 H  | 104   | 48.13  | 33.00   | 7.00   | -36.20    |  |  |  |
| 2   | 4924.00   | 46.86  | AV   | 54.00    | 7.14   | 1.00 H  | 104   | 43.06  | 33.00   | 7.00   | -36.20    |  |  |  |
| 3   | 7386.00   | 51.95  | PK   | 74.00    | 22.05  | 1.00 H  | 329   | 42.55  | 36.20   | 8.50   | -35.30    |  |  |  |
| 3   | 7386.00   | 46.81  | AV   | 54.00    | 7.19   | 1.00 H  | 329   | 37.41  | 36.20   | 8.50   | -35.30    |  |  |  |
| 4   | 9848.00   | 52.69  | PK   | 74.00    | 21.31  | 1.00 H  | 190   | 40.09  | 37.30   | 10.10  | -34.80    |  |  |  |
| 4   | 9848.00   | 46.93  | AV   | 54.00    | 7.07   | 1.00 H  | 190   | 34.33  | 37.30   | 10.10  | -34.80    |  |  |  |

| AN  | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n-202462MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|-----|---|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
|     | Frequency   | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| No. | (MHz)   | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1   | *2462.00  | 109.82 | PK   | /        | /      | 1.00 V  | 176   | 113.12 | 28.20   | 5.10   | -36.60    |  |  |  |
| 1   | *2462.00  | 99.87  | AV   | /        | /      | 1.00 V  | 176   | 103.17 | 28.20   | 5.10   | -36.60    |  |  |  |
| 2   | 4924.00   | 50.59  | PK   | 74.00    | 23.41  | 1.00 V  | 117   | 46.79  | 33.00   | 7.00   | -36.20    |  |  |  |
| 2   | 4924.00   | 44.47  | AV   | 54.00    | 9.53   | 1.00 V  | 117   | 40.67  | 33.00   | 7.00   | -36.20    |  |  |  |
| 3   | 7386.00   | 51.94  | PK   | 74.00    | 22.06  | 1.00 V  | 294   | 42.54  | 36.20   | 8.50   | -35.30    |  |  |  |
| 3   | 7386.00   | 47.73  | AV   | 54.00    | 6.27   | 1.00 V  | 294   | 38.33  | 36.20   | 8.50   | -35.30    |  |  |  |
| 4   | 9848.00   | 50.02  | PK   | 74.00    | 23.98  | 1.00 V  | 84    | 37.42  | 37.30   | 10.10  | -34.80    |  |  |  |
| 4   | 9848.00   | 44.18  | AV   | 54.00    | 9.82   | 1.00 V  | 84    | 31.58  | 37.30   | 10.10  | -34.80    |  |  |  |

CCIC-SET/T (00) Page 65 of 69





802.11n-40 Mode

| ANT  | ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n-402422MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|------|---|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
| N.T. | Frequency   | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| No.  | (MHz)   | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1    | *2422.00  | 106.91 | PK   | /        | /      | 1.00 H  | 71    | 110.21 | 28.30   | 5.00   | -36.60    |  |  |  |
| 1    | *2422.00  | 96.75  | AV   | /        | /      | 1.00 H  | 71    | 100.05 | 28.30   | 5.00   | -36.60    |  |  |  |
| 2    | 4844.00   | 51.96  | PK   | 74.00    | 22.04  | 1.00 H  | 150   | 48.16  | 32.70   | 7.30   | -36.20    |  |  |  |
| 2    | 4844.00   | 46.36  | AV   | 54.00    | 7.64   | 1.00 H  | 150   | 42.56  | 32.70   | 7.30   | -36.20    |  |  |  |
| 3    | 7266.00   | 51.50  | PK   | 74.00    | 22.50  | 1.00 H  | 337   | 42.10  | 35.80   | 8.90   | -35.30    |  |  |  |
| 3    | 7266.00   | 46.95  | AV   | 54.00    | 7.05   | 1.00 H  | 337   | 37.55  | 35.80   | 8.90   | -35.30    |  |  |  |
| 4    | 9688.00   | 50.14  | PK   | 74.00    | 23.86  | 1.00 H  | 12    | 37.54  | 37.20   | 10.20  | -34.80    |  |  |  |
| 4    | 9688.00   | 45.04  | AV   | 54.00    | 8.96   | 1.00 H  | 12    | 32.44  | 37.20   | 10.20  | -34.80    |  |  |  |

| AN  | ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n-402422MHz) |        |      |          |        |         |       |        |         |        |           |  |  |  |
|-----|---|--------|------|----------|--------|---------|-------|--------|---------|--------|-----------|--|--|--|
|     | Frequency   | Emss   | sion | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |  |  |  |
| No. | (MHz)   | Lev    | /el  | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |  |  |  |
| 1   | *2422.00  | 109.80 | PK   | /        | /      | 1.00 V  | 189   | 113.10 | 28.30   | 5.00   | -36.60    |  |  |  |
| 1   | *2422.00  | 98.72  | AV   | /        | /      | 1.00 V  | 189   | 102.02 | 28.30   | 5.00   | -36.60    |  |  |  |
| 2   | 4844.00   | 51.23  | PK   | 74.00    | 22.77  | 1.00 V  | 96    | 47.43  | 32.70   | 7.30   | -36.20    |  |  |  |
| 2   | 4844.00   | 45.03  | AV   | 54.00    | 8.97   | 1.00 V  | 96    | 41.23  | 32.70   | 7.30   | -36.20    |  |  |  |
| 3   | 7266.00   | 51.28  | PK   | 74.00    | 22.72  | 1.00 V  | 233   | 41.88  | 35.80   | 8.90   | -35.30    |  |  |  |
| 3   | 7266.00   | 47.63  | AV   | 54.00    | 6.37   | 1.00 V  | 233   | 38.23  | 35.80   | 8.90   | -35.30    |  |  |  |
| 4   | 9688.00   | 49.45  | PK   | 74.00    | 24.55  | 1.00 V  | 304   | 36.85  | 37.20   | 10.20  | -34.80    |  |  |  |
| 4   | 9688.00   | 46.00  | AV   | 54.00    | 8.00   | 1.00 V  | 304   | 33.40  | 37.20   | 10.20  | -34.80    |  |  |  |

| ANT | ENNA POI  | LARIT  | Y & ' | TEST DIS | STANCI | E: HORIZ | ONTAL | <b>AT 3 M</b> | (802.11n | -4024  | 37MHz)    |
|-----|-----------|--------|-------|----------|--------|----------|-------|---------------|----------|--------|-----------|
| N   | Frequency | Emss   | sion  | Limit    | Margin | Antenna  | Table | Raw           | Antenna  | Cable  | Pre-      |
| No. | (MHz)     | Lev    | /el   | (dBuV/m) | (dB)   | Height   | Angle | Value         | Factor   | Factor | amplifier |
| 1   | *2437.00  | 108.17 | PK    | /        | /      | 1.00 H   | 349   | 111.37        | 28.30    | 5.10   | -36.60    |
| 1   | *2437.00  | 100.18 | AV    | /        | /      | 1.00 H   | 349   | 103.38        | 28.30    | 5.10   | -36.60    |
| 2   | 4874.00   | 52.70  | PK    | 74.00    | 21.30  | 1.00 H   | 309   | 49.30         | 32.30    | 7.60   | -36.50    |
| 2   | 4874.00   | 47.67  | AV    | 54.00    | 6.33   | 1.00 H   | 309   | 44.27         | 32.30    | 7.60   | -36.50    |
| 3   | 7311.00   | 52.10  | PK    | 74.00    | 21.90  | 1.00 H   | 188   | 42.70         | 36.10    | 8.60   | -35.30    |
| 3   | 7311.00   | 47.49  | AV    | 54.00    | 6.51   | 1.00 H   | 188   | 38.09         | 36.10    | 8.60   | -35.30    |
| 4   | 9748.00   | 50.55  | PK    | 74.00    | 23.45  | 1.00 H   | 74    | 37.95         | 37.20    | 10.20  | -34.80    |
| 4   | 9748.00   | 45.92  | AV    | 54.00    | 8.08   | 1.00 H   | 74    | 33.32         | 37.20    | 10.20  | -34.80    |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n-402437MHz) |           |                  |    |          |        |         |       |        |         |        |           |
|---|-----------|------------------|----|----------|--------|---------|-------|--------|---------|--------|-----------|
| N 1   | Frequency | Emssion<br>Level |    | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |
| No.   | (MHz)     |                  |    | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |
| 1   | *2437.00  | 109.55           | PK | /        | /      | 1.00 V  | 205   | 112.75 | 28.30   | 5.10   | -36.60    |

CCIC-SET/T (00) Page 66 of 69





| 1 | *2437.00 | 98.93 | AV | /     | /     | 1.00 V | 205 | 102.13 | 28.30 | 5.10  | -36.60 |
|---|----------|-------|----|-------|-------|--------|-----|--------|-------|-------|--------|
| 2 | 4874.00  | 53.89 | PK | 74.00 | 20.11 | 1.00 V | 262 | 50.49  | 32.30 | 7.60  | -36.50 |
| 2 | 4874.00  | 49.45 | AV | 54.00 | 4.55  | 1.00 V | 262 | 46.05  | 32.30 | 7.60  | -36.50 |
| 3 | 7311.00  | 52.24 | PK | 74.00 | 21.76 | 1.00 V | 338 | 42.84  | 36.10 | 8.60  | -35.30 |
| 3 | 7311.00  | 46.77 | AV | 54.00 | 7.23  | 1.00 V | 338 | 37.37  | 36.10 | 8.60  | -35.30 |
| 4 | 9748.00  | 51.81 | PK | 74.00 | 22.19 | 1.00 V | 152 | 39.21  | 37.20 | 10.20 | -34.80 |
| 4 | 9748.00  | 43.34 | AV | 54.00 | 10.66 | 1.00 V | 152 | 30.74  | 37.20 | 10.20 | -34.80 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n-402452MHz) |           |                  |    |          |        |         |       |        |         |        |           |
|---|-----------|------------------|----|----------|--------|---------|-------|--------|---------|--------|-----------|
|   | Frequency | Emssion<br>Level |    | Limit    | Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |
| No.   | (MHz)     |                  |    | (dBuV/m) | (dB)   | Height  | Angle | Value  | Factor  | Factor | amplifier |
| 1   | *2452.00  | 109.28           | PK | /        | /      | 1.00 H  | 235   | 112.58 | 28.20   | 5.10   | -36.60    |
| 1   | *2452.00  | 99.75            | AV | /        | /      | 1.00 H  | 235   | 103.05 | 28.20   | 5.10   | -36.60    |
| 2   | 4904.00   | 52.41            | PK | 74.00    | 21.59  | 1.00 H  | 104   | 48.61  | 33.00   | 7.00   | -36.20    |
| 2   | 4904.00   | 47.01            | AV | 54.00    | 6.99   | 1.00 H  | 104   | 43.21  | 33.00   | 7.00   | -36.20    |
| 3   | 7356.00   | 51.91            | PK | 74.00    | 22.09  | 1.00 H  | 329   | 42.51  | 36.20   | 8.50   | -35.30    |
| 3   | 7356.00   | 47.05            | AV | 54.00    | 6.95   | 1.00 H  | 329   | 37.65  | 36.20   | 8.50   | -35.30    |
| 4   | 9808.00   | 53.23            | PK | 74.00    | 20.77  | 1.00 H  | 190   | 40.63  | 37.30   | 10.10  | -34.80    |
| 4   | 9808.00   | 47.38            | AV | 54.00    | 6.62   | 1.00 H  | 190   | 34.78  | 37.30   | 10.10  | -34.80    |

| ANTENNA POLARITY & TEST DISTANCE: VERTICALAT 3 M (802.11n-402452MHz) |           |                  |    |          |              |         |       |        |         |        |           |
|--|-----------|------------------|----|----------|--------------|---------|-------|--------|---------|--------|-----------|
|  | Frequency | Emssion<br>Level |    | Limit    | Limit Margin | Antenna | Table | Raw    | Antenna | Cable  | Pre-      |
| No.  | (MHz)     |                  |    | (dBuV/m) | (dB)         | Height  | Angle | Value  | Factor  | Factor | amplifier |
| 1  | *2452.00  | 109.74           | PK | /        | /            | 1.00 V  | 176   | 113.04 | 28.20   | 5.10   | -36.60    |
| 1  | *2452.00  | 100.07           | AV | /        | /            | 1.00 V  | 176   | 103.37 | 28.20   | 5.10   | -36.60    |
| 2  | 4904.00   | 50.81            | PK | 74.00    | 23.19        | 1.00 V  | 117   | 47.01  | 33.00   | 7.00   | -36.20    |
| 2  | 4904.00   | 45.31            | AV | 54.00    | 8.69         | 1.00 V  | 117   | 41.51  | 33.00   | 7.00   | -36.20    |
| 3  | 7356.00   | 52.06            | PK | 74.00    | 21.94        | 1.00 V  | 294   | 42.66  | 36.20   | 8.50   | -35.30    |
| 3  | 7356.00   | 47.05            | AV | 54.00    | 6.95         | 1.00 V  | 294   | 37.65  | 36.20   | 8.50   | -35.30    |
| 4  | 9808.00   | 50.10            | PK | 74.00    | 23.90        | 1.00 V  | 84    | 37.50  | 37.30   | 10.10  | -34.80    |
| 4  | 9808.00   | 44.19            | AV | 54.00    | 9.81         | 1.00 V  | 84    | 31.59  | 37.30   | 10.10  | -34.80    |

- **REMARKS**: 1. Emission level (dBuV/m) =Raw Value (dBuV) +Antenna Factor (dB/m) + Cable Factor (dB) +Pre-amplifier Factor
  - 2. The other emission levels were very low against the limit.
  - 3. The other emission levels were very low against the limit.
  - 4. Margin value = Limit value- Emission level.
  - 5. The limit value is defined as per 15.247
  - 6. " \* ": Fundamental frequency

CCIC-SET/T (00) Page 67 of 69



# 2.9 RF exposure evaluation

Equation from page 8 of OET Bulletin 65, Edition 97-01.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S=power density

P=power input to the antenna

G=numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the centre of radiation of the antenna

## 2.9.1 . Limits For Maximum Permissible Exposure

According to FCC Part 1.1307, system operation under the provisions of this section shall be operated in a Manner the ensures that the pulic is not exposed to radio frequency energy level in excess of the commission's guidelines.

According to FCC Part 1.1310 RF exposure is calculated.

| Limits for Occupational/controlled Exposure |                                      |                                   |                           |  |  |  |  |  |  |
|---|--------------------------------------|-----------------------------------|---------------------------|--|--|--|--|--|--|
| Frequency Range(MHz)                        | Electric Field<br>Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density(S) (mW/cm2) |  |  |  |  |  |  |
| 0.3-1.34                                    | 614                                  | 1.63                              | (100)*                    |  |  |  |  |  |  |
| 1.34-30                                     | 1842/f                               | 2.19/f                            | (180/f2)*                 |  |  |  |  |  |  |
| 30-300                                      | 27.5                                 | 0.073                             | 0.2                       |  |  |  |  |  |  |
| 300-1500                                    |                                      |                                   | f/1500                    |  |  |  |  |  |  |
| 1500-100,000                                |                                      |                                   | 1.0                       |  |  |  |  |  |  |

## 2.9.2. Test Result

CCIC-SET/T (00) Page 68 of 69





| 17.75 |   |
|-------|---|
| 59.57 |   |
|       |   |
| 20    |   |
| 2412  |   |
| 5.0   |   |
| 0.037 |   |
| 1.0   |   |
|       | 59.57<br><br>20<br>2412<br>5.0<br>0.037 |

# 2.9.3. Conclusion

Since the test result is passed.

\*\* END OF REPORT \*\*

CCIC-SET/T (00) Page 69 of 69