9. RADIO FREQUENCY EXPOSURE

9.1 Limit

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

9.2 EUT Specification

EO I Specification		
EUT	Controller	
Frequency Band (Operating)	 WLAN: 2.412GHz ~ 2.462GHz WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz WLAN: 5.745GHz ~ 5.825GHz ✓ Others: Bluetooth: 2.402GHz ~ 2.480GHz 	
Device Category	Portable (<20cm separation) Mobile (>20cm separation) Others	
Exposure Classification	Occupational/Controlled exposure $(S = 5mW/cm^2)$ Seneral Population/Uncontrolled exposure $(S=1mW/cm^2)$	
Antenna Diversity	Single antenna ☐ Multiple antennas ☐ Tx diversity☐ Rx diversity ☐ Tx/Rx diversity	
Max. Output Power	1.92 dBm (1.56mW)	
Antenna Gain (Max)	1.5 dBi	
Evaluation Applied		
2. DTS device is not subject compliance.3. For mobile or fixed loc	cower is 1.92dBm (1.56mW) at 2441MHz. ect to routine RF evaluation; MPE estimate is used to justify the ration transmitters, no SAR consideration applied. The minimum used is at least 20 cm, even if the calculations indicate that the lesser.	
		

9.3 Test Results

Compliance.

(SAR evaluation is not required for the portable device while its maximum output power is lower than the general population low threshold: 60/f (GHz)=60/2.441=24.58mW)

 END REPORT	