

FCC - TEST REPORTReport Number : **60.790.15.022.01R02** Date of Issue : September 21, 2015Model : **VBLE**Product Type : **HEART RATE MONITOR STRAP-ON**Applicant : 4iiii Innovations Inc.Address : 228 RIVER AVE. COCHRANE, AB CANADAProduction Facility : Kendy Electronics Co. Ltd.Address : Xin Si Huang Tang Village, Hengli Town, Dongguan City,
Guangdong, ChinaTest Result : ☒ **Positive** ☐ **Negative**Total pages
including
Appendices : 29

TÜV SÜD HONG KONG LTD. is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025. TÜV SÜD HONG KONG LTD. reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD HONG KONG LTD. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD HONG KONG LTD. issued reports. This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1 Table of Contents.....	2
2 Description of Equipment Under Test	3
3 Summary of Test Standards	4
4 Details about the Test Laboratory	5
4.1 Test Equipment Site List	6
4.2 Measurement System Uncertainty	7
5 Summary of Test Results.....	8
6 General Remarks.....	9
7 Emission Test Results	10
7.1 Radiated Emission.....	10
7.2 20dB & 99% Bandwidth	16
7.3 Bandedge Emission	22
8 Appendix A - Photographs of EUT	24
9 Appendix B - Setup Photographs of EUT.....	28
10 Appendix C - General Product Information	29

2 Description of Equipment Under Test

Description of the Equipment Under Test

Product:	HEART RATE MONITOR STRAP-ON
Model no.:	VBLE
FCC ID:	ZZNVBLE
Rating:	3.0VDC (1 x 3.0VDC size "CR2032" batteries)
Frequency:	2457MHz, 2410MHz, 2473MHz
Antenna gain:	-1.0 dBi
Number of operated channel:	1
Modulation:	GFSK

3 Summary of Test Standards

Test Standards

FCC Part 15 Subpart C 10-1-13 Edition Federal Communications Commission, PART 15 — Radio Frequency Devices, Subpart C — Unintentional Radiators

4 Details about the Test Laboratory

Site 1

Company name: TÜV SÜD Hong Kong Ltd.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin, Hong Kong

Site 2

Company name: TÜV SÜD China Ltd.
Building 12&13 Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Shenzhen 518052, P.R.China
FCC Registration Number: 502708

Emission Tests	
Test Item	Test Site
FCC Part 15 Subpart C	
FCC Title 47 Part 15.249 & 15.209 Radiated Emission	Site 2
FCC Title 47 Part 15.249 & 15.207 Conduct Emission	NIL
FCC Title 47 Part 15.215 20dB & 99% Bandwidth	Site 2
FCC Title 47 Part 15.249 Bandedge Emission	Site 2

4.1 Test Equipment Site List

Radiated emission Test, Bandedge Emission – Site 3

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	17-Aug-16
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	17-Aug-17
Horn Antenna	Rohde & Schwarz	HF907	102294	17-Aug-17
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	17-Aug-16
3m Semi-anechoic chamber	TDK	9X6X6	----	29-May-19

20dB & 99% Bandwidth – Site 3

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Generator	Rohde & Schwarz	SMB100A	108272	17-Aug-16
Signal Analyzer	Rohde & Schwarz	FSV40	101030	17-Aug-16
Vector Signal Generator	Rohde & Schwarz	SMU 200A	105324	17-Aug-16
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157	101226/100851	17-Aug-16

4.2 Measurement System Uncertainty

Measurement System Uncertainty Emissions

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.54dB
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-25000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted RF test	2.04dB

5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
FCC Title 47 Part 15.249 & 15.209 Radiated Emission	10-15	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
FCC Title 47 Part 15.249 & 15.207 Conduct Emission	NIL	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FCC Title 47 Part 15.215 20dB & 99% Bandwidth	16-21	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
FCC Title 47 Part 15.249 Bandedge Emission	22-23	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

6 General Remarks

Remarks

NIL

SUMMARY:

- All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

- The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: August 21, 2015

Testing Start Date: August 24, 2015

Testing End Date: September 4, 2015

- TÜV SÜD HONG KONG LTD. -

Reviewed by:



TSENG Chi Kit
EMC Project Engineer



Prepared by:



CHAN Kwong Ngai
EMC Test Engineer

7 Emission Test Results

7.1 Radiated Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2457MHz)
 Test Specification: FCC15.249 & 15.209, Antenna: Horizontal
 Comment: 3.0VDC
 Remark: 9kHz to 25GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
49.885	17.71	40	-22.29	Quasi Peak
93.103	10.21	43.5	-33.29	Quasi Peak
281.661	19.92	46	-26.08	Quasi Peak
847.925	26.36	46	-19.64	Quasi Peak
1584.416	36.18	74	-37.82	Peak
1584.416	34.52	54	-19.84	Average
2457.000	88.42	114	-25.58	Peak
2457.000	86.17	94	-7.83	Average
2720.083	40.07	74	-33.93	Peak
4914.375	55.72	74	-18.28	Peak
4914.375	37.18	54	-16.82	Average
7458.750	41.45	74	-32.55	Peak
7458.750	39.03	54	-14.97	Average

Radiated Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2457MHz)
 Test Specification: FCC15.249 & 15.209, Antenna: Vertical
 Comment: 3.0VDC
 Remark: 9kHz to 25GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
48.807	13.13	40	-26.87	Quasi Peak
103.073	15.46	43.5	-28.04	Quasi Peak
279.559	17.66	46	-28.34	Quasi Peak
700.000	20.64	46	-25.36	Quasi Peak
1584.250	35.74	74	-38.26	Peak
1584.250	34.02	54	-19.98	Average
2457.166	76.93	114	-37.07	Peak
2457.166	74.15	94	-19.85	Average
2857.833	39.96	74	-34.04	Peak
4914.375	55.25	74	-18.75	Peak
4914.375	37.48	54	-16.52	Average
7330.625	41.13	74	-32.87	Peak
7330.625	39.13	54	-14.87	Average

Radiated Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2410MHz)
 Test Specification: FCC15.249 & 15.209, Antenna: Horizontal
 Comment: 3.0VDC
 Remark: 9kHz to 25GHz

Test Result

☒ Passed

☐ Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
49.885	17.71	40	-22.29	Quasi Peak
93.103	10.21	43.5	-33.29	Quasi Peak
281.661	19.92	46	-26.08	Quasi Peak
847.925	26.36	46	-19.64	Quasi Peak
1585.645	36.85	74	-37.15	Peak
1585.645	34.73	54	-19.27	Average
2410.125	86.72	114	-27.28	Peak
2410.125	84.16	94	-9.84	Average
2700.435	39.58	74	-34.42	Peak
4820.250	53.12	74	-20.88	Peak
4820.250	36.55	54	-17.45	Average
7230.000	41.04	74	-32.96	Peak
7230.000	38.59	54	-15.41	Average

Radiated Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2410MHz)
 Test Specification: FCC15.249 & 15.209, Antenna: Vertical
 Comment: 3.0VDC
 Remark: 9kHz to 25GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
48.807	13.13	40	-26.87	Quasi Peak
103.073	15.46	43.5	-28.04	Quasi Peak
279.559	17.66	46	-28.34	Quasi Peak
700.000	20.64	46	-25.36	Quasi Peak
1585.135	34.93	74	-38.26	Peak
1585.135	34.12	54	-34.12	Average
2410.000	78.56	114	-35.44	Peak
2410.000	76.13	94	-17.87	Average
2702.125	38.33	74	-35.67	Peak
4820.000	54.17	74	-19.83	Peak
4820.000	38.48	54	-15.52	Average
7230.000	42.52	74	-31.48	Peak
7230.000	40.17	54	-13.83	Average

Radiated Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2473MHz)
 Test Specification: FCC15.249 & 15.209, Antenna: Horizontal
 Comment: 3.0VDC
 Remark: 9kHz to 25GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
49.885	17.71	40	-22.29	Quasi Peak
93.103	10.21	43.5	-33.29	Quasi Peak
281.661	19.92	46	-26.08	Quasi Peak
847.925	26.36	46	-19.64	Quasi Peak
1613.472	35.82	74	-38.18	Peak
1613.472	34.26	54	-19.74	Average
2473.120	80.64	114	-33.36	Peak
2473.120	78.22	94	-15.78	Average
2733.000	38.59	74	-35.41	Peak
4946.500	52.53	74	-21.47	Peak
4946.500	40.48	54	-13.52	Average
7419.650	41.22	74	-32.78	Peak
7419.650	40.39	54	-13.61	Average

Radiated Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2473MHz)
 Test Specification: FCC15.249 & 15.209, Antenna: Vertical
 Comment: 3.0VDC
 Remark: 9kHz to 25GHz


Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
48.807	13.13	40	-26.87	Quasi Peak
103.073	15.46	43.5	-28.04	Quasi Peak
279.559	17.66	46	-28.34	Quasi Peak
700.000	20.64	46	-25.36	Quasi Peak
1612.560	36.02	74	-37.98	Peak
1612.560	35.23	54	-18.77	Average
2473.120	78.88	114	-35.12	Peak
2473.120	76.12	94	-17.88	Average
2732.500	40.12	74	-33.88	Peak
4946.500	53.56	74	-20.44	Peak
4946.500	38.37	54	-15.63	Average
7419.650	42.22	74	-31.78	Peak
7419.650	40.15	54	-13.85	Average

7.2 20dB & 99% Bandwidth

EUT: VBLE
Op Condition: Operated, TX Mode (2457MHz)
Test Specification: FCC15.215, 20dB Bandwidth
Comment: 3.0VDC

Test Result


☒ Passed☐ Not Passed**20dB bandwidth**

100.75 kHz

20dB & 99% Bandwidth

EUT: VBLE
Op Condition: Operated, TX Mode (2457MHz)
Test Specification: FCC15.215, 99% Bandwidth
Comment: 3.0VDC

Test Result


☒ Passed☐ Not Passed**99% bandwidth**

165.485 kHz

20dB & 99% Bandwidth

EUT: VBLE
Op Condition: Operated, TX Mode (2410MHz)
Test Specification: FCC15.215, 20dB Bandwidth
Comment: 3.0VDC

Test Result


☒ Passed☐ Not Passed**20dB bandwidth**

101.07 kHz

20dB & 99% Bandwidth

EUT: VBLE
Op Condition: Operated, TX Mode (2410MHz)
Test Specification: FCC15.215, 99% Bandwidth
Comment: 3.0VDC

Test Result


☒ Passed☐ Not Passed**99% bandwidth**

163.465 kHz

20dB & 99% Bandwidth

EUT: VBLE
Op Condition: Operated, TX Mode (2473MHz)
Test Specification: FCC15.215, 20dB Bandwidth
Comment: 3.0VDC

Test Result


☒ Passed☐ Not Passed**20dB bandwidth**

101.30 kHz

20dB & 99% Bandwidth

EUT: VBLE
Op Condition: Operated, TX Mode (2473MHz)
Test Specification: FCC15.215, 99% Bandwidth
Comment: 3.0VDC

Test Result

☒ Passed☐ Not Passed**99% bandwidth**


164.445 kHz

7.3 Bandedge Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2457/2410/2473MHz)
 Test Specification: FCC15.247, Antenna: Horizontal
 Comment: 3.0VDC

Test Result

☒ Passed

☐ Not Passed



Band	Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
Low	2396.000	34.53	74	-39.47	Peak
Low	2396.000	30.98	54	-23.02	Average
High	2491.000	36.17	74	-37.83	Peak
High	2491.000	31.87	54	-22.13	Average

Bandedge Emission

EUT: VBLE
 Op Condition: Operated, TX Mode (2457/2410/2473MHz)
 Test Specification: FCC15.247, Antenna: Vertical
 Comment: 3.0VDC

Test Result

☒ Passed
☐ Not Passed



Band	Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
Low	2396.000	33.54	74	-40.46	Peak
Low	2396.000	30.21	54	-23.79	Average
High	2491.000	34.55	74	-39.45	Peak
High	2491.000	31.92	54	-23.08	Average


8 Appendix A - Photographs of EUT




Appendix A



Appendix A



Appendix A



9 Appendix B - Setup Photographs of EUT

Radiated Emission / Bandedge Emission



20dB & 99% Bandwidth



10 Appendix C - General Product Information

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v05r02 section 4.3.1,

>> The 1-g SAR test exclusion thresholds for 100MHz to 6GHz, at test separation distances ≤ 50 mm are determined by:

Power at 2457MHz = 0.0946 mW EIRP

Power at 2410MHz = 0.0928 mW EIRP

Power at 2473MHz = 0.0941 mW EIRP

$[(0.0946 \text{ mW}) / (5 \text{ mm})] \cdot [\text{sqrt}(2.457 \text{ GHz})] = 0.0296$ which is ≤ 3.0 for 1-g SAR.

$[(0.0928 \text{ mW}) / (5 \text{ mm})] \cdot [\text{sqrt}(2.410 \text{ GHz})] = 0.0288$ which is ≤ 3.0 for 1-g SAR.

$[(0.0941 \text{ mW}) / (5 \text{ mm})] \cdot [\text{sqrt}(2.473 \text{ GHz})] = 0.0295$ which is ≤ 3.0 for 1-g SAR.

Therefore the device is exempt from stand-alone SAR test requirements.

>> The fundamental frequency of the EUT is 2457MHz, 2410MHz, 2473MHz, the test separation distance is $< 50\text{mm}$. (Manufacturer Specification distance is $< 5\text{mm}$)

>> The power of EUT measured is:

- For 2457MHz: $0.0946\text{mW} = 10 \log(0.0946) \text{ dBm} \sim -10.24\text{dBm}$
- For 2410MHz: $0.0928\text{mW} = 10 \log(0.0928) \text{ dBm} \sim -10.32\text{dBm}$
- For 2473MHz: $0.0941\text{mW} = 10 \log(0.0941) \text{ dBm} \sim -10.26\text{dBm}$