

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594 Email: ee.shenzhen@sgs.com Report No.: SZEM161100948203

Page: 1 of 6

SAR Evaluation Report

Application No.: SZEM1611009482CR

Applicant:Camino International LimitedManufacturer:Camino International Limited

Factory: Camino Industrial (Huizhou) Co. Ltd.

Product Name: 1.IRONMAN MARK XLVI Helmet Bluetooth Wireless Speaker

2. STAR WARS- Darth Vader Bluetooth Wireless Speaker

3. STAR WARS- Rogue One K-2SO Helmet Mini Bluetooth Wireless Speaker

STAR WARS- Deathtrooper Bluetooth Wireless Speaker
STAR WARS - Stormtrooper Bluetooth Wireless Speaker

Model No.(EUT): 761555

Add Model No.: 761566,761554, 761568,761567

Trade Mark: Disney FCC ID: ZZX555

Standards: 47 CFR Part 1.1307 (2015)

47 CFR Part 2.1093 (2015)

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2016-11-10

Date of Test: 2016-11-21 to 2016-11-25

Date of Issue: 2016-11-28

Test Result : PASS*

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/rerms-en-Countinos/terms-en-Co

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM161100948203

Page: 2 of 6

2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2016-11-28		Original	

Authorized for issue by:		
Tested By	Peter Gene	2016-11-25
	(Bill Chen) /Project Engineer	Date
Checked By	Eric Fu	2016-11-28
	(Eric Fu) /Reviewer	Date



Report No.: SZEM161100948203

Page: 3 of 6

3 Contents

12 VERSION			Page
3 CONTENTS 3 4 GENERAL INFORMATION 4 4.1 CLIENT INFORMATION 4 4.2 GENERAL DESCRIPTION OF EUT 4 4.3 TEST LOCATION 5 4.4 TEST FACILITY 5 4.5 DEVIATION FROM STANDARDS 5 4.6 ABNORMALITIES FROM STANDARD CONDITIONS 5 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER 5 5 SAR EVALUATION 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6			1
4 GENERAL INFORMATION 4 4.1 CLIENT INFORMATION 4 4.2 GENERAL DESCRIPTION OF EUT 4 4.3 TEST LOCATION 5 4.4 TEST FACILITY 5 4.5 DEVIATION FROM STANDARDS 5 4.6 ABNORMALITIES FROM STANDARD CONDITIONS 5 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER 5 5 SAR EVALUATION 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6	2	VERSION	2
4.1 CLIENT INFORMATION	3	CONTENTS	3
4.2 GENERAL DESCRIPTION OF EUT. 4 4.3 TEST LOCATION. 5 4.4 TEST FACILITY. 5 4.5 DEVIATION FROM STANDARDS. 5 4.6 ABNORMALITIES FROM STANDARD CONDITIONS. 5 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER. 5 5 SAR EVALUATION. 6 5.1.1 Standard Requirement. 6 5.1.2 Limits. 6	4	GENERAL INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT. 4 4.3 TEST LOCATION. 5 4.4 TEST FACILITY. 5 4.5 DEVIATION FROM STANDARDS. 5 4.6 ABNORMALITIES FROM STANDARD CONDITIONS. 5 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER. 5 5 SAR EVALUATION. 6 5.1.1 Standard Requirement. 6 5.1.2 Limits. 6		4.1 CLIENT INFORMATION	4
4.3 TEST LOCATION 5 4.4 TEST FACILITY 5 4.5 DEVIATION FROM STANDARDS 5 4.6 ABNORMALITIES FROM STANDARD CONDITIONS 5 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER 5 5 SAR EVALUATION 6 5.1 RF Exposure Compliance Requirement 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6		4.2 GENERAL DESCRIPTION OF EUT	4
4.5 Deviation from Standards 5 4.6 Abnormalities from Standard Conditions 5 4.7 Other Information Requested by the Customer 5 5 SAR EVALUATION 6 5.1 RF Exposure Compliance Requirement 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6		4.3 Test Location	5
4.5 Deviation from Standards 5 4.6 Abnormalities from Standard Conditions 5 4.7 Other Information Requested by the Customer 5 5 SAR EVALUATION 6 5.1 RF Exposure Compliance Requirement 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6		4.4 Test Facility	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS 5 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER 5 5 SAR EVALUATION 6 5.1 RF Exposure Compliance Requirement 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6		4.5 DEVIATION FROM STANDARDS	5
5 SAR EVALUATION 6 5.1 RF Exposure Compliance Requirement 6 5.1.1 Standard Requirement 6 5.1.2 Limits 6		4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
5.1 RF Exposure Compliance Requirement65.1.1 Standard Requirement65.1.2 Limits6		4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5.1.1Standard Requirement65.1.2Limits6	5	SAR EVALUATION	6
5.1.2 Limits		5.1 RF Exposure Compliance Requirement	6
5.1.2 Limits			
		5.1.2 Limits	6



Report No.: SZEM161100948203

Page: 4 of 6

4 General Information

4.1 Client Information

Applicant:	Camino International Limited	
Address of Applicant:	Flat A, 3rd Floor, International Industrial Building, 501-503 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong	
Manufacturer:	Camino International Limited	
Address of Manufacturer:	Flat A, 3rd Floor, International Industrial Building, 501-503 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong	
Factory:	Camino Industrial (Huizhou) Co. Ltd.	
Address of Factory:	Lidong Industrial Estate, Jiutan, Yuanzhou, Boluo, Huizhou, Guangdong, China	

4.2 General Description of EUT

Product Name:	1.IRONMAN MARK XLVI Helmet Bluetooth Wireless Speaker 2. STAR WARS- Darth Vader Bluetooth Wireless Speaker 3. STAR WARS- Rogue One K-2SO Helmet Mini Bluetooth Wireless Speaker 4. STAR WARS- Deathtrooper Bluetooth Wireless Speaker 5. STAR WARS - Stormtrooper Bluetooth Wireless Speaker
Model No.:	76155
Trade Mark:	Disney
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth 4.1 single
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Antenna Type:	Chip Antenna
Antenna Gain:	0dBi
Power Supply	DC 3.7V, 850mAh rechargeable battery which charged by AC adapter

Remark:

Model No.: 761555, 761566,761554, 761568,761567

Only the model 761555 was tested, since the circuit design, PCB layout, electrical components used, internal wiring and functions were identical for the above models, only different on model number and exterior.



Report No.: SZEM161100948203

Page: 5 of 6

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

· A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



Report No.: SZEM161100948203

Page: 6 of 6

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation ¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max Conducted Peak Output Power is 0.11dBm in highest channel(2.480GHz);

0.11dBm logarithmic terms convert to numeric result is nearly 1.03mW

According to the formula. calculate the test exclusion thresholds:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$]

General RF Exposure = $(1.03 \text{mW} / 5 \text{ mm}) \times \sqrt{2.480 \text{GHz}} = 0.324 \text{ }\bigcirc$

SAR requirement:

S= 3.0 ②;

(1) < (2).

So the SAR report is not required.