
Pre-tutorial setup: Tailscale

Programming SmartNICs: From Packet Processing to Programmable Transport

ACM SIGCOMM 2026

Fernando Ramos  Muhammad Shahbaz[†] Mina Tahmasbi Arashloo  Mario Baldi 

Francisco Pereira  Bilal Saleem  Tyler Liu  Chenxingyu Zhao 

 INESC-ID, Instituto Superior Técnico, University of Lisbon [†] University of Michigan  University of Waterloo
 NVIDIA  Purdue University  University of Washington

The BlueField-3 cards you will be programming live in racks at five sites across four universities and NVIDIA. They are not reachable from the public internet, and no SmartNIC will be physically provided during the tutorial.

Tailscale closes that gap. It is a VPN that will put your laptop and the BlueField cards on the same small private network, as if they were on the same LAN. We ask you to **install the tailscale client and join the tutorial network before you arrive**. Doing it at home takes about five minutes; doing it in the room, forty people at once on the conference Wi-Fi, takes considerably longer.

You do **not** need a Tailscale account, and you will not be asked to sign in with Google, GitHub, or anything else. Your laptop joins with a key we send you.

You will get access to the cards at the start of the session, not before

Joining the network and reaching the cards are two different things. This guide gets you onto the network. Access to the cards is opened at the start of the tutorial and closed again afterwards — they are shared lab machines at several institutions, so they are reachable for the session and to the people in the room.

So when you finish this guide, **you will see no tutorial machines, and that is the correct result** — not a sign that something went wrong. You will also never see other participants' laptops, before or during the session; the network is configured so that participants can reach the cards and nothing else.

What you need

- Your laptop, with permission to install software on it.
- The **join key** we email you before the tutorial. It looks like `tskey-auth-...`. If it has not arrived by the day before, check your spam folder and then email us.

Step 1 — Install the client

Pick your platform.

macOS

Install with Homebrew, or download it from tailscale.com/download/mac:

```
brew install --cask tailscale
```

Launch Tailscale from Applications once, so it can install its system components. It runs as a menu-bar

icon.

The tailscale command lives inside the app bundle and may not be on your path. Link it, so step 2 works:

```
sudo ln -s /Applications/Tailscale.app/Contents/MacOS/Tailscale /usr/local/bin/tailscale
```

Windows

Download and run the installer from tailscale.com/download/windows. Tailscale then lives in the system tray, and tailscale is available in a terminal.

Linux

The install script covers every mainstream distribution:

```
curl -fsSL https://tailscale.com/install.sh | sh
```

It installs the client and enables the tailscaled service.

Step 2 — Join the tutorial network

Run the command for your platform, with the key we emailed you in place of the one below.

On **Linux**:

```
sudo tailscale up --auth-key=tskey-auth-PLACEHOLDER-NOT-A-REAL-KEY
```

On **macOS** and **Windows**:

```
tailscale up --auth-key=tskey-auth-PLACEHOLDER-NOT-A-REAL-KEY
```

Your operating system will ask you to allow a VPN configuration. Say yes. This is the step that is worth doing at home: on a managed or work-issued laptop it can require an administrator, and it is the one part of this that occasionally needs someone else's help.

Step 3 — Check that it worked

```
tailscale status
```

You should see your own laptop listed with a `100.x.y.z` address. There will be no other machines. That is exactly right — see the second section above. If your own machine is there, you are done.

On the day

Bring the laptop as you left it. At the start of the session we open access to the cards, and they will appear in `tailscale status` within a few seconds without you doing anything. We will hand out machine assignments and connection details then.

If something goes wrong

You cannot install software on your laptop. Some managed or work-issued machines block it, and so do some VPN-configuration policies. Find out now rather than at 08:30 — email us and we will sort out an alternative.

The key is rejected, or has expired. Join keys have a lifetime and we may have rotated it. Email us and we will send a fresh one.

Your employer's VPN is already running. Corporate VPNs and Tailscale often compete over routes. Disconnecting the other one while you run step 2 is usually enough; if it is not, tell us at the start of the session rather than debugging it alone.

tailscale: command not found. On macOS, the symlink at the end of step 1 is what fixes this. On Linux, the install script needs sudo and a systemd-based distribution — if yours is neither, the manual packages at tailscale.com/download cover the rest.

Anything else. Email us before the tutorial, or find us in the room a few minutes early. We would much rather fix it then than at 08:30.