

# Package ‘flamingos’

July 29, 2019

**Type** Package

**Title** Functional Latent Data Models for Clustering Heterogeneous Time-Series (FLaMingoS)

**Version** 0.1.0

**Description** Provides a variety of original and flexible user-friendly statistical latent variable models for the simultaneous clustering (or classification) and segmentation of heterogeneous functional data (i.e time series or more generally longitudinal data), fitted by unsupervised algorithms, including EM algorithms.

**URL** <https://github.com/fchamroukhi/FLaMingoS>

**BugReports** <https://github.com/fchamroukhi/FLaMingoS/issues>

**License** GPL (>= 3)

**Depends** R (>= 2.10)

**Imports** methods,  
stats,  
Rcpp

**Suggests** knitr,  
rmarkdown

**LinkingTo** Rcpp,  
RcppArmadillo

**Collate** flamingos-package.R  
RcppExports.R  
utils.R  
kmeans.R  
mkStochastic.R  
FData.R  
ParamMixHMM.R  
ParamMixHMMR.R  
ParamMixRHLP.R  
StatMixHMM.R  
StatMixHMMR.R  
StatMixRHLP.R  
ModelMixHMMR.R  
ModelMixHMM.R  
ModelMixRHLP.R  
emMixHMM.R  
emMixHMMR.R

```
emMixRHLP.R
cemMixRHLP.R
data-toydataset.R
```

**VignetteBuilder** knitr

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 6.1.1

## R topics documented:

flamingos-package	2
cemMixRHLP	4
emMixHMM	5
emMixHMMR	7
emMixRHLP	8
FData-class	9
mkStochastic	10
ModelMixHMM-class	10
ModelMixHMMR-class	11
ModelMixRHLP-class	12
ParamMixHMM-class	13
ParamMixHMMR-class	15
ParamMixRHLP-class	16
StatMixHMM-class	17
StatMixHMMR-class	18
StatMixRHLP-class	19
toydataset	20

<b>Index</b>	<b>22</b>
--------------	-----------

---

flamingos-package	<i>FLaMingoS: Functional Latent data Models for clusterING heterogeneous time-Series</i>
-------------------	--

---

## Description

flamingos is a toolbox for the simultaneous clustering (or classification) and segmentation of heterogeneous functional data (i.e time-series or more generally longitudinal data), with original and flexible functional latent variable models, fitted by unsupervised algorithms, including EM algorithms.

flamingos contains the following time series segmentation models:

- mixRHLP;
- mixHMM;
- mixHMMR.

For the advantages/differences of each of them, the user is referred to our mentioned paper references.

To learn more about flamingos, start with the vignettes: `browseVignettes(package = "flamingos")`

**Author(s)**

**Maintainer:** Florian Lecocq <florian.lecocq@outlook.com>

Authors:

- Faicel Chamroukhi <faicel.chamroukhi@unicaen.fr> (0000-0002-5894-3103)
- Marius Bartcus <marius.bartcus@gmail.com>

**References**

- Chamroukhi, Faicel, and Hien D. Nguyen. 2019. *Model-Based Clustering and Classification of Functional Data*. Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery. <https://chamroukhi.com/papers/MBCC-FDA.pdf>.
- Chamroukhi, F. 2016. *Unsupervised Learning of Regression Mixture Models with Unknown Number of Components*. Journal of Statistical Computation and Simulation 86 (November): 2308–34. <https://chamroukhi.com/papers/Chamroukhi-JSCS-2015.pdf>.
- Chamroukhi, Faicel. 2016. *Piecewise Regression Mixture for Simultaneous Functional Data Clustering and Optimal Segmentation*. Journal of Classification 33 (3): 374–411. <https://chamroukhi.com/papers/Chamroukhi-PWRM-JournalClassif-2016.pdf>.
- Chamroukhi, F. 2015. *Statistical Learning of Latent Data Models for Complex Data Analysis*. Habilitation Thesis (HDR), Universite de Toulon. <https://chamroukhi.com/Dossier/FChamroukhi-Habilitation.pdf>.
- Chamroukhi, F., H. Glotin, and A. Same. 2013. *Model-Based Functional Mixture Discriminant Analysis with Hidden Process Regression for Curve Classification*. Neurocomputing 112: 153–63. [https://chamroukhi.com/papers/chamroukhi\\_et\\_al\\_neucomp2013a.pdf](https://chamroukhi.com/papers/chamroukhi_et_al_neucomp2013a.pdf).
- Chamroukhi, F., and H. Glotin. 2012. *Mixture Model-Based Functional Discriminant Analysis for Curve Classification*. In Proceedings of the International Joint Conference on Neural Networks (IJCNN), IEEE, 1–8. Brisbane, Australia. <https://chamroukhi.com/papers/Chamroukhi-ijcnn-2012.pdf>.
- Same, A., F. Chamroukhi, Gerard Govaert, and P. Aknin. 2011. *Model-Based Clustering and Segmentation of Time Series with Changes in Regime*. Advances in Data Analysis and Classification 5 (4): 301–21. <https://chamroukhi.com/papers/adac-2011.pdf>.
- Chamroukhi, F., A. Same, P. Aknin, and G. Govaert. 2011. *Model-Based Clustering with Hidden Markov Model Regression for Time Series with Regime Changes*. In Proceedings of the International Joint Conference on Neural Networks (IJCNN), IEEE, 2814–21. <https://chamroukhi.com/papers/Chamroukhi-ijcnn-2011.pdf>.
- Chamroukhi, F., A. Same, G. Govaert, and P. Aknin. 2010. *A Hidden Process Regression Model for Functional Data Description. Application to Curve Discrimination*. Neurocomputing 73 (7-9): 1210–21. [https://chamroukhi.com/papers/chamroukhi\\_neucomp\\_2010.pdf](https://chamroukhi.com/papers/chamroukhi_neucomp_2010.pdf).
- Chamroukhi, F. 2010. *Hidden Process Regression for Curve Modeling, Classification and Tracking*. Ph.D. Thesis, Universite de Technologie de Compiègne. <https://chamroukhi.com/papers/FChamroukhi-Thesis.pdf>.

**See Also**

Useful links:

- <https://github.com/fchamroukhi/FLaMingoS>
- Report bugs at <https://github.com/fchamroukhi/FLaMingoS/issues>

---

cemMixRHLP	<i>cemMixRHLP implements the CEM algorithm to fit a MixRHLP model.</i>
------------	--

---

## Description

cemMixRHLP implements the maximum complete likelihood parameter estimation of mixture of RHLP models by the Classification Expectation-Maximization algorithm (CEM algorithm).

## Usage

```
cemMixRHLP(X, Y, K, R, p = 3, q = 1,
  variance_type = c("heteroskedastic", "homoskedastic"),
  init_kmeans = TRUE, n_tries = 1, max_iter = 100,
  threshold = 1e-05, verbose = FALSE, verbose_IRLS = FALSE)
```

## Arguments

X	Numeric vector of length $m$ representing the covariates/inputs $x_1, \dots, x_m$ .
Y	Matrix of size $(n, m)$ representing the observed responses/outputs. Y consists of $n$ functions of X observed at points $1, \dots, m$ .
K	The number of clusters (Number of RHLP models).
R	The number of regimes (RHLP components) for each cluster.
p	Optional. The order of the polynomial regression. By default, p is set at 3.
q	Optional. The dimension of the logistic regression. For the purpose of segmentation, it must be set to 1 (which is the default value).
variance_type	Optional character indicating if the model is "homoskedastic" or "heteroskedastic". By default the model is "heteroskedastic".
init_kmeans	Optional. A logical indicating whether or not the curve partition should be initialized by the K-means algorithm. Otherwise the curve partition is initialized randomly.
n_tries	Optional. Number of runs of the EM algorithm. The solution providing the highest log-likelihood will be returned. If $n\_tries > 1$ , then for the first run, parameters are initialized by uniformly segmenting the data into R segments, and for the next runs, parameters are initialized by randomly segmenting the data into R contiguous segments.
max_iter	Optional. The maximum number of iterations for the EM algorithm.
threshold	Optional. A numeric value specifying the threshold for the relative difference of log-likelihood between two steps of the EM as stopping criteria.
verbose	Optional. A logical value indicating whether or not values of the log-likelihood should be printed during EM iterations.
verbose_IRLS	Optional. A logical value indicating whether or not values of the criterion optimized by IRLS should be printed at each step of the EM algorithm.

## Details

cemMixRHLP function implements the CEM algorithm. This function starts with an initialization of the parameters done by the method `initParam` of the class [ParamMixRHLP](#), then it alternates between the E-Step, the C-Step (methods of the class [StatMixRHLP](#)), and the CM-Step (method of the class [ParamMixRHLP](#)) until convergence (until the relative variation of log-likelihood between two steps of the EM algorithm is less than the threshold parameter).

## Value

EM returns an object of class [ModelMixRHLP](#).

## See Also

[ModelMixRHLP](#), [ParamMixRHLP](#), [StatMixRHLP](#)

## Examples

```
data(toydataset)

#' # Let's fit a mixRHLP model on a dataset containing 2 clusters:
data <- toydataset[1:190,1:21]

mixrhlp <- cemMixRHLP(data$x, t(data[,2:ncol(data)]),
                      K = 2, R = 2, p = 1, verbose = TRUE)

mixrhlp$summary()

mixrhlp$plot()
```

---

emMixHMM

*emMixHMM implements the EM (Baum-Welch) algorithm to fit a mixture of HMM models.*

---

## Description

emMixHMM implements the maximum-likelihood parameter estimation of a mixture of HMM models by the Expectation-Maximization (EM) algorithm, known as Baum-Welch algorithm in the context of mixHMM.

## Usage

```
emMixHMM(Y, K, R, variance_type = c("heteroskedastic", "homoskedastic"),
         order_constraint = TRUE, init_kmeans = TRUE, n_tries = 1,
         max_iter = 1000, threshold = 1e-06, verbose = FALSE)
```

## Arguments

Y	Matrix of size $(n, m)$ representing the observed responses/outputs. Y consists of $n$ functions of X observed at points $1, \dots, m$ .
K	The number of clusters (Number of HMM models).
R	The number of regimes (HMM components) for each cluster.

variance_type	Optional character indicating if the model is "homoskedastic" or "heteroskedastic". By default the model is "heteroskedastic".
order_constraint	Optional. A logical indicating whether or not a mask of order one should be applied to the transition matrix of the Markov chain. For the purpose of segmentation, it must be set to TRUE (which is the default value).
init_kmeans	Optional. A logical indicating whether or not the curve partition should be initialized by the K-means algorithm. Otherwise the curve partition is initialized randomly.
n_tries	Optional. Number of runs of the EM algorithm. The solution providing the highest log-likelihood will be returned.  If <code>n_tries &gt; 1</code> , then for the first run, parameters are initialized by uniformly segmenting the data into K segments, and for the next runs, parameters are initialized by randomly segmenting the data into K contiguous segments.
max_iter	Optional. The maximum number of iterations for the EM algorithm.
threshold	Optional. A numeric value specifying the threshold for the relative difference of log-likelihood between two steps of the EM as stopping criteria.
verbose	Optional. A logical value indicating whether or not values of the log-likelihood should be printed during EM iterations.

## Details

emMixHMM function implements the EM algorithm. This function starts with an initialization of the parameters done by the method `initParam` of the class [ParamMixHMM](#), then it alternates between the E-Step (method of the class [StatMixHMM](#)) and the M-Step (method of the class [ParamMixHMM](#)) until convergence (until the relative variation of log-likelihood between two steps of the EM algorithm is less than the threshold parameter).

## Value

EM returns an object of class [ModelMixHMM](#).

## See Also

[ModelMixHMM](#), [ParamMixHMM](#), [StatMixHMM](#)

## Examples

```
data(toydataset)

mixhmm <- emMixHMM(t(toydataset[,2:ncol(toydataset)]), K = 3, R = 3, verbose = TRUE)

mixhmm$summary()

mixhmm$plot()
```

---

emMixHMMR	<i>emMixHMMR implements the EM algorithm to fit a mixture of HMMR models.</i>
-----------	---

---

## Description

emMixHMMR implements the maximum-likelihood parameter estimation of a mixture of HMMR models by the Expectation-Maximization (EM) algorithm.

## Usage

```
emMixHMMR(X, Y, K, R, p = 3, variance_type = c("heteroskedastic",
  "homoskedastic"), order_constraint = TRUE, init_kmeans = TRUE,
  n_tries = 1, max_iter = 1000, threshold = 1e-06, verbose = FALSE)
```

## Arguments

X	Numeric vector of length $m$ representing the covariates/inputs $x_1, \dots, x_m$ .
Y	Matrix of size $(n, m)$ representing the observed responses/outputs. Y consists of $n$ functions of X observed at points $1, \dots, m$ .
K	The number of clusters (Number of HMMR models).
R	The number of regimes (HMMR components) for each cluster.
p	Optional. The order of the polynomial regression. By default, p is set at 3.
variance_type	Optional. character indicating if the model is "homoskedastic" or "heteroskedastic". By default the model is "heteroskedastic".
order_constraint	Optional. A logical indicating whether or not a mask of order one should be applied to the transition matrix of the Markov chain. For the purpose of segmentation, it must be set to TRUE (which is the default value).
init_kmeans	Optional. A logical indicating whether or not the curve partition should be initialized by the K-means algorithm. Otherwise the curve partition is initialized randomly.
n_tries	Optional. Number of runs of the EM algorithm. The solution providing the highest log-likelihood will be returned. If $n\_tries > 1$ , then for the first run, parameters are initialized by uniformly segmenting the data into K segments, and for the next runs, parameters are initialized by randomly segmenting the data into K contiguous segments.
max_iter	Optional. The maximum number of iterations for the EM algorithm.
threshold	Optional. A numeric value specifying the threshold for the relative difference of log-likelihood between two steps of the EM as stopping criteria.
verbose	Optional. A logical value indicating whether or not values of the log-likelihood should be printed during EM iterations.

## Details

emMixHMMR function implements the EM algorithm. This function starts with an initialization of the parameters done by the method `initParam` of the class [ParamMixHMMR](#), then it alternates between the E-Step (method of the class [StatMixHMMR](#)) and the M-Step (method of the class [ParamMixHMMR](#)) until convergence (until the relative variation of log-likelihood between two steps of the EM algorithm is less than the threshold parameter).

**Value**

EM returns an object of class [ModelMixHMMR](#).

**See Also**

[ModelMixHMMR](#), [ParamMixHMMR](#), [StatMixHMMR](#)

**Examples**

```
data(toydataset)

mixhmmr <- emMixHMMR(toydataset$x, t(toydataset[,2:ncol(toydataset)]),
                     K = 3, R = 3, p = 1, verbose = TRUE)

mixhmmr$summary()

mixhmmr$plot()
```

---

emMixRHLP

*emMixRHLP implements the EM algorithm to fit a mixture of RHLP models.*

---

**Description**

emMixRHLP implements the maximum-likelihood parameter estimation of a mixture of RHLP models by the Expectation-Maximization (EM) algorithm.

**Usage**

```
emMixRHLP(X, Y, K, R, p = 3, q = 1,
          variance_type = c("heteroskedastic", "homoskedastic"),
          init_kmeans = TRUE, n_tries = 1, max_iter = 1000,
          threshold = 1e-05, verbose = FALSE, verbose_IRLS = FALSE)
```

**Arguments**

X	Numeric vector of length $m$ representing the covariates/inputs $x_1, \dots, x_m$ .
Y	Matrix of size $(n, m)$ representing the observed responses/outputs. Y consists of $n$ functions of X observed at points $1, \dots, m$ .
K	The number of clusters (Number of RHLP models).
R	The number of regimes (RHLP components) for each cluster.
p	Optional. The order of the polynomial regression. By default, p is set at 3.
q	Optional. The dimension of the logistic regression. For the purpose of segmentation, it must be set to 1 (which is the default value).
variance_type	Optional character indicating if the model is "homoskedastic" or "heteroskedastic". By default the model is "heteroskedastic".
init_kmeans	Optional. A logical indicating whether or not the curve partition should be initialized by the K-means algorithm. Otherwise the curve partition is initialized randomly.



n_tries	Optional. Number of runs of the EM algorithm. The solution providing the highest log-likelihood will be returned. If n_tries > 1, then for the first run, parameters are initialized by uniformly segmenting the data into R segments, and for the next runs, parameters are initialized by randomly segmenting the data into R contiguous segments.
max_iter	Optional. The maximum number of iterations for the EM algorithm.
threshold	Optional. A numeric value specifying the threshold for the relative difference of log-likelihood between two steps of the EM as stopping criteria.
verbose	Optional. A logical value indicating whether or not values of the log-likelihood should be printed during EM iterations.
verbose_IRLS	Optional. A logical value indicating whether or not values of the criterion optimized by IRLS should be printed at each step of the EM algorithm.

### Details

emMixRHLP function implements the EM algorithm. This function starts with an initialization of the parameters done by the method `initParam` of the class [ParamMixRHLP](#), then it alternates between the E-Step (method of the class [StatMixRHLP](#)) and the M-Step (method of the class [ParamMixRHLP](#)) until convergence (until the relative variation of log-likelihood between two steps of the EM algorithm is less than the threshold parameter).

### Value

EM returns an object of class [ModelMixRHLP](#).

### See Also

[ModelMixRHLP](#), [ParamMixRHLP](#), [StatMixRHLP](#)

### Examples

```
data(toydataset)

# Let's fit a mixRHLP model on a dataset containing 2 clusters:
data <- toydataset[1:190,1:21]

mixrhlp <- emMixRHLP(data$x, t(data[,2:ncol(data)]),
                     K = 2, R = 2, p = 1, verbose = TRUE)

mixrhlp$summary()

mixrhlp$plot()
```

---

FData-class

*A Reference Class which represents functional data.*


---

### Description

FData is a reference class which represents general independent and identically distributed (i.i.d.) functional objects. The data can be ordered by time (functional time series). In the last case, the field `X` represents the time.

**Fields**

$X$  Numeric vector of length  $m$  representing the covariates/inputs.

$Y$  Matrix of size  $(n, m)$  representing the observed responses/outputs.  $Y$  consists of  $n$  functions of  $X$  observed at points  $1, \dots, m$ .

---

mkStochastic	<i>mkStochastic ensures that it is a stochastic vector, matrix or array.</i>
--------------	--

---

**Description**

mkStochastic ensures that it is a stochastic vector, matrix or array.

**Usage**

```
mkStochastic(M)
```

**Arguments**

$M$  A vector, matrix or array to transform.

**Details**

mkStochastic ensures that the giving argument is a stochastic vector, matrix or array, i.e., that the sum over the last dimension is 1.

**Value**

A vector, matrix or array for which the sum over the last dimension is 1.

---

ModelMixHMM-class	<i>A Reference Class which represents a fitted Mixture of HMM models.</i>
-------------------	---

---

**Description**

ModelMixHMM represents an estimated mixture of HMM models.

**Fields**

param A [ParamMixHMM](#) object. It contains the estimated values of the parameters.

stat A [StatMixHMM](#) object. It contains all the statistics associated to the MixHMM model.

## Methods

`plot(what = c("clustered", "smoothed", "loglikelihood"), ...)` Plot method

`what` The type of graph requested:

- "clustered" = Clustered curves (field `klas` of class [StatMixHMM](#)).
- "smoothed" = Smoothed signal (field `smoothed` of class [StatMixHMM](#)).
- "loglikelihood" = Value of the log-likelihood for each iteration (field `stored_loglik` of class [StatMixHMM](#)).

`...` Other graphics parameters.

`summary(digits = getOption("digits"))` Summary method.

`digits` The number of significant digits to use when printing.

## See Also

[ParamMixHMM](#), [StatMixHMM](#)

## Examples

```
data(toydataset)

mixhmm <- emMixHMM(t(toydataset[,2:ncol(toydataset)]), K = 3, R = 3, verbose = TRUE)

# mixhmm is a ModelMixHMM object. It contains some methods such as 'summary' and 'plot'
mixhmm$summary()
mixhmm$plot()

# mixhmm has also two fields, stat and param which are reference classes as well

# Log-likelihood:
mixhmm$stat$loglik

# Means
mixhmm$param$mu
```

---

ModelMixHMMR-class	<i>A Reference Class which represents a fitted mixture of HMMR models.</i>
--------------------	--

---

## Description

ModelMixHMMR represents an estimated mixture of HMMR models.

## Fields

`param` A [ParamMixHMMR](#) object. It contains the estimated values of the parameters.

`stat` A [StatMixHMMR](#) object. It contains all the statistics associated to the MixHMMR model.

## Methods

`plot(what = c("clustered", "smoothed", "loglikelihood"), ...)` Plot method

`what` The type of graph requested:

- "clustered" = Clustered curves (field `klas` of class [StatMixHMMR](#)).
- "smoothed" = Smoothed signal (field `smoothed` of class [StatMixHMMR](#)).
- "loglikelihood" = Value of the log-likelihood for each iteration (field `stored_loglik` of class [StatMixHMMR](#)).

`...` Other graphics parameters.

`summary(digits = getOption("digits"))` Summary method.

`digits` The number of significant digits to use when printing.

## See Also

[ParamMixHMMR](#), [StatMixHMMR](#)

## Examples

```
data(toydataset)

mixhmmr <- emMixHMMR(toydataset$x, t(toydataset[,2:ncol(toydataset)]),
                     K = 3, R = 3, p = 1, verbose = TRUE)

# mixhmmr is a ModelMixHMMR object. It contains some methods such as 'summary' and 'plot'
mixhmmr$summary()
mixhmmr$plot()

# mixhmmr has also two fields, stat and param which are reference classes as well

# Log-likelihood:
mixhmmr$stat$loglik

# Parameters of the polynomial regressions:
mixhmmr$param$beta
```

---

ModelMixRHLP-class	<i>A Reference Class which represents a fitted mixture of RHLP models.</i>
--------------------	--

---

## Description

ModelMixRHLP represents an estimated mixture of RHLP models.

## Fields

`param` A [ParamMixRHLP](#) object. It contains the estimated values of the parameters.

`stat` A [StatMixRHLP](#) object. It contains all the statistics associated to the MixRHLP model.

## Methods

`plot(what = c("estimatedsignal", "regressors", "loglikelihood"), ...)` Plot method.

`what` The type of graph requested:

- `"estimatedsignal"` = Estimated signal (field `Ex` of class [StatMixRHLP](#)).
- `"regressors"` = Polynomial regression components (fields `polynomials` and `pi_jgk` of class [StatMixRHLP](#)).
- `"loglikelihood"` = Value of the log-likelihood for each iteration (field `stored_loglik` of class [StatMixRHLP](#)).

`...` Other graphics parameters.

By default, all the above graphs are produced.

`summary(digits = getOption("digits"))` Summary method.

`digits` The number of significant digits to use when printing.

## See Also

[ParamMixRHLP](#), [StatMixRHLP](#)

## Examples

```
data(toydataset)

# Let's fit a mixRHLP model on a dataset containing 2 clusters:
data <- toydataset[1:190,1:21]

mixrhlp <- cemMixRHLP(data$x, t(data[,2:ncol(data)]),
                      K = 2, R = 2, p = 1, verbose = TRUE)

# mixrhlp is a ModelMixRHLP object. It contains some methods such as 'summary' and 'plot'
mixrhlp$summary()
mixrhlp$plot()

# mixrhlp has also two fields, stat and param which are reference classes as well

# Log-likelihood:
mixrhlp$stat$loglik

# Parameters of the polynomial regressions:
mixrhlp$param$beta
```

---

ParamMixHMM-class	<i>A Reference Class which contains parameters of a mixture of HMM models.</i>
-------------------	--

---

## Description

ParamMixHMM contains all the parameters of a mixture of HMM models.

## Fields

- fData [FData](#) object representing the sample (covariates/inputs  $X$  and observed responses/outputs  $Y$ ).
- K The number of clusters (Number of HMM models).
- R The number of regimes (HMM components) for each cluster.
- variance\_type Character indicating if the model is homoskedastic (variance\_type = "homoskedastic") or heteroskedastic (variance\_type = "heteroskedastic"). By default the model is heteroskedastic.
- order\_constraint A logical indicating whether or not a mask of order one should be applied to the transition matrix of the Markov chain. For the purpose of segmentation, it must be set to TRUE (which is the default value).
- alpha Cluster weights. Matrix of dimension  $(K, 1)$ .
- prior The prior probabilities of the Markov chains. prior is a matrix of dimension  $(R, K)$ . The k-th column represents the prior distribution of the Markov chain associated to the cluster k.
- trans\_mat The transition matrices of the Markov chains. trans\_mat is an array of dimension  $(R, R, K)$ .
- mask Mask applied to the transition matrices trans\_mat. By default, a mask of order one is applied.
- mu Means. Matrix of dimension  $(R, K)$ . The k-th column gives represents the k-th cluster and gives the means for the R regimes.
- sigma2 The variances for the K clusters. If MixHMM model is heteroskedastic (variance\_type = "heteroskedastic") then sigma2 is a matrix of size  $(R, K)$  (otherwise MixHMM model is homoskedastic (variance\_type = "homoskedastic") and sigma2 is a matrix of size  $(1, K)$ ).
- nu The degree of freedom of the MixHMM model representing the complexity of the model.

## Methods

- initGaussParamHmm( $Y, k, R, \text{variance\_type}, \text{try\_algo}$ ) Initialize the means  $\mu$  and  $\sigma^2$  for the cluster k.
- initParam(init\_kmeans = TRUE, try\_algo = 1) Method to initialize parameters alpha, prior, trans\_mat,  $\mu$  and  $\sigma^2$ .  
 If init\_kmeans = TRUE then the curve partition is initialized by the K-means algorithm. Otherwise the curve partition is initialized randomly.  
 If try\_algo = 1 then  $\mu$  and  $\sigma^2$  are initialized by segmenting the time series  $Y$  uniformly into R contiguous segments. Otherwise,  $\mu$  and  $\sigma^2$  are initialized by segmenting randomly the time series  $Y$  into R segments.
- MStep(statMixHMM) Method which implements the M-step of the EM algorithm to learn the parameters of the MixHMM model based on statistics provided by the object statMixHMM of class [StatMixHMM](#) (which contains the E-step).

---

ParamMixHMMR-class	<i>A Reference Class which contains parameters of a mixture of HMMR models.</i>
--------------------	---

---

## Description

ParamMixHMMR contains all the parameters of a mixture of HMMR models.

## Fields

- fData [FData](#) object representing the sample (covariates/inputs X and observed responses/outputs Y).
- K The number of clusters (Number of HMMR models).
- R The number of regimes (HMMR components) for each cluster.
- p The order of the polynomial regression.
- variance\_type Character indicating if the model is homoskedastic (variance\_type = "homoskedastic") or heteroskedastic (variance\_type = "heteroskedastic"). By default the model is heteroskedastic.
- order\_constraint A logical indicating whether or not a mask of order one should be applied to the transition matrix of the Markov chain. For the purpose of segmentation, it must be set to TRUE (which is the default value).
- alpha Cluster weights. Matrix of dimension  $(K, 1)$ .
- prior The prior probabilities of the Markov chains. prior is a matrix of dimension  $(R, K)$ . The k-th column represents the prior distribution of the Markov chain asociated to the cluster k.
- trans\_mat The transition matrices of the Markov chains. trans\_mat is an array of dimension  $(R, R, K)$ .
- mask Mask applied to the transition matrices trans\_mat. By default, a mask of order one is applied.
- beta Parameters of the polynomial regressions. beta is an array of dimension  $(p + 1, R, K)$ , with p the order of the polynomial regression. p is fixed to 3 by default.
- sigma2 The variances for the K clusters. If MixHMMR model is heteroskedastic (variance\_type = "heteroskedastic") then sigma2 is a matrix of size  $(R, K)$  (otherwise MixHMMR model is homoskedastic (variance\_type = "homoskedastic") and sigma2 is a matrix of size
- nu The degree of freedom of the MixHMMR model representing the complexity of the model.
- phi A list giving the regression design matrices for the polynomial and the logistic regressions.

## Methods

- initParam(init\_kmeans = TRUE, try\_algo = 1) Method to initialize parameters alpha, prior, trans\_mat, beta and sigma2.  
If init\_kmeans = TRUE then the curve partition is initialized by the K-means algorithm. Otherwise the curve partition is initialized randomly.  
If try\_algo = 1 then beta and sigma2 are initialized by segmenting the time series Y uniformly into R contiguous segments. Otherwise, beta and sigma2 are initialized by segmenting randomly the time series Y into R segments.
- initRegressionParam(Y, k, R, phi, variance\_type, try\_algo) Initialize beta and sigma2 for the cluster k.

MStep(statMixHMMR) Method which implements the M-step of the EM algorithm to learn the parameters of the MixHMMR model based on statistics provided by the object statMixHMMR of class [StatMixHMMR](#) (which contains the E-step).

---

ParamMixRHLP-class	<i>A Reference Class which contains parameters of a mixture of RHLP models.</i>
--------------------	---

---

## Description

ParamMixRHLP contains all the parameters of a mixture of RHLP models.

## Fields

- fData [FData](#) object representing the sample (covariates/inputs X and observed responses/outputs Y).
- K The number of clusters (Number of RHLP models).
- R The number of regimes (RHLP components) for each cluster.
- p The order of the polynomial regression.
- q The dimension of the logistic regression. For the purpose of segmentation, it must be set to 1.
- variance\_type Character indicating if the model is homoskedastic (variance\_type = "homoskedastic") or heteroskedastic (variance\_type = "heteroskedastic"). By default the model is heteroskedastic.
- alpha Cluster weights. Matrix of dimension  $(1, K)$ .
- W Parameters of the logistic process.  $\mathbf{W} = (\mathbf{w}_1, \dots, \mathbf{w}_K)$  is an array of dimension  $(q + 1, R - 1, K)$ , with  $\mathbf{w}_g = (\mathbf{w}_{g,1}, \dots, \mathbf{w}_{g,R-1})$ ,  $g = 1, \dots, K$ , and q the order of the logistic regression. q is fixed to 1 by default.
- beta Parameters of the polynomial regressions.  $\beta = (\beta_1, \dots, \beta_K)$  is an array of dimension  $(p + 1, R, K)$ , with  $\beta_g = (\beta_{g,1}, \dots, \beta_{g,R})$ ,  $g = 1, \dots, K$ , p the order of the polynomial regression. p is fixed to 3 by default.
- sigma2 The variances for the K clusters. If MixRHLP model is heteroskedastic (variance\_type = "heteroskedastic") then sigma2 is a matrix of size  $(R, K)$  (otherwise MixRHLP model is homoskedastic (variance\_type = "homoskedastic") and sigma2 is a matrix of size  $(K, 1)$ ).
- nu The degree of freedom of the MixRHLP model representing the complexity of the model.
- phi A list giving the regression design matrices for the polynomial and the logistic regressions.

## Methods

CMStep(statMixRHLP, verbose\_IRLS = FALSE) Method which implements the M-step of the CEM algorithm to learn the parameters of the MixRHLP model based on statistics provided by the object statMixRHLP of class [StatMixRHLP](#) (which contains the E-step and the C-step).

initParam(init\_kmeans = TRUE, try\_algo = 1) Method to initialize parameters alpha, W, beta and sigma2.

If init\_kmeans = TRUE then the curve partition is initialized by the R-means algorithm. Otherwise the curve partition is initialized randomly.

If try\_algo = 1 then beta and sigma2 are initialized by segmenting the time series Y uniformly into R contiguous segments. Otherwise, W, beta and sigma2 are initialized by segmenting randomly the time series Y into R segments.



`initRegressionParam(Xg, g, try_algo = 1)` Initialize the matrix of polynomial regression coefficients `beta_g` for the cluster `g`.

`MStep(statMixRHLP, verbose_IRLS = FALSE)` Method which implements the M-step of the EM algorithm to learn the parameters of the MixRHLP model based on statistics provided by the object `statMixRHLP` of class [StatMixRHLP](#) (which contains the E-step).

---

StatMixHMM-class	<i>A Reference Class which contains statistics of a mixture of HMM models.</i>
------------------	--

---

## Description

StatMixHMM contains all the statistics associated to a [MixHMM](#) model.

## Fields

`tau_ik` Matrix of size  $(n, K)$  giving the posterior probabilities that the curve  $Y_i$  originates from the  $k$ -th HMM model.

`gamma_ikjr` Array of size  $(nm, R, K)$  giving the posterior probabilities that the observation  $Y_{ij}$  originates from the  $r$ -th regime of the  $k$ -th HMM model.

`loglik` Numeric. Log-likelihood of the MixHMM model.

`stored_loglik` Numeric vector. Stored values of the log-likelihood at each iteration of the EM algorithm.

`klas` Row matrix of the labels issued from `tau_ik`. Its elements are  $klas(i) = k, i = 1, \dots, n$ .

`z_ik` Hard segmentation logical matrix of dimension  $(n, K)$  obtained by the Maximum a posteriori (MAP) rule:  $z_{ik} = 1$  if  $z_{ik} = \arg \max_s P(z_{is} = 1 | Y_i; \Psi) = tau_{tk}$ ; 0 otherwise,  $k = 1, \dots, K$ .

`smoothed` Matrix of size  $(m, K)$  giving the estimated mean series. The  $k$ -th column gives the estimated mean series of cluster  $k$ .

`mean_curve` To define.

`BIC` Numeric. Value of BIC (Bayesian Information Criterion).

`AIC` Numeric. Value of AIC (Akaike Information Criterion).

`ICL1` Numeric. Value of ICL (Integrated Completed Likelihood Criterion).

`log_w_k_fyi` Private. Only defined for calculations.

`exp_num_trans` Private. Only defined for calculations.

`exp_num_trans_from_l` Private. Only defined for calculations.

## Methods

`computeStats(paramMixHMM)` Method used in the EM algorithm to compute statistics based on parameters provided by the object `paramMixHMM` of class [ParamMixHMM](#).

`EStep(paramMixHMM)` Method used in the EM algorithm to update statistics based on parameters provided by the object `paramMixHMM` of class [ParamMixHMM](#) (prior and posterior probabilities).

`MAP()` MAP calculates values of the fields `z_ik` and `klas` by applying the Maximum A Posteriori Bayes allocation rule.

$z_{ik} = 1$  if  $z_{ik} = \arg \max_s P(z_{is} = 1 | Y_i; \Psi) = tau_{ik}$ ; 0 otherwise,  $k = 1, \dots, K$ .

**See Also**

[ParamMixHMM](#)

---

StatMixHMMR-class	<i>A Reference Class which contains statistics of a mixture of HMMR models.</i>
-------------------	---

---

**Description**

StatMixHMMR contains all the statistics associated to a [MixHMMR](#) model.

**Fields**

`tau_ik` Matrix of size  $(n, K)$  giving the posterior probabilities that the curve  $Y_i$  originates from the  $k$ -th HMMR model.

`gamma_ikjr` Array of size  $(nm, R, K)$  giving the posterior probabilities that the observation  $Y_{ij}$  originates from the  $r$ -th regime of the  $k$ -th HMM model.

`loglik` Numeric. Log-likelihood of the MixHMMR model.

`stored_loglik` Numeric vector. Stored values of the log-likelihood at each iteration of the EM algorithm.

`klas` Row matrix of the labels issued from `tau_ik`. Its elements are  $klas(i) = k, i = 1, \dots, n$ .

`z_ik` Hard segmentation logical matrix of dimension  $(n, K)$  obtained by the Maximum a posteriori (MAP) rule:  $z_{ik} = 1$  if  $z_{ik} = \arg \max_s P(z_{is} = 1 | \mathbf{Y}_i; \Psi) = tau_{ik}$ ; 0 otherwise,  $k = 1, \dots, K$ .

`smoothed` Matrix of size  $(m, K)$  giving the estimated mean series. The  $k$ -th column gives the estimated mean series of cluster  $k$ .

`mean_curve` To define.

`BIC` Numeric. Value of BIC (Bayesian Information Criterion).

`AIC` Numeric. Value of AIC (Akaike Information Criterion).

`ICL1` Numeric. Value of ICL (Integrated Completed Likelihood Criterion).

`log_w_k_fyi` Private. Only defined for calculations.

`exp_num_trans` Private. Only defined for calculations.

`exp_num_trans_from_1` Private. Only defined for calculations.

**Methods**

`computeStats(paramMixHMMR)` Method used in the EM algorithm to compute statistics based on parameters provided by the object `paramMixHMMR` of class [ParamMixHMMR](#).

`EStep(paramMixHMMR)` Method used in the EM algorithm to update statistics based on parameters provided by the object `paramMixHMMR` of class [ParamMixHMMR](#) (prior and posterior probabilities).

`MAP()` MAP calculates values of the fields `z_ik` and `klas` by applying the Maximum A Posteriori Bayes allocation rule.  
 $z_{ik} = 1$  if  $z_{ik} = \arg \max_s P(z_{is} = 1 | \mathbf{Y}_i; \Psi) = tau_{ik}$ ; 0 otherwise

**See Also**

[ParamMixHMMR](#)

---

StatMixRHLP-class	<i>A Reference Class which contains statistics of a mixture of RHLP models.</i>
-------------------	---

---

## Description

StatMixRHLP contains all the statistics associated to a [MixRHLP](#) model.

## Fields

- pi\_jgk Array of size  $(nm, R, K)$  representing the logistic proportion for cluster  $g$ .
- h\_ig Matrix of size  $(n, K)$  giving the posterior probabilities (fuzzy segmentation matrix) that the curve  $Y_i$  originates from the  $g$ -th RHLP model.
- c\_ig Hard segmentation logical matrix of dimension  $(n, K)$  obtained by the Maximum a posteriori (MAP) rule:  $c_{ig} = 1$  if  $c_{ig} = \arg \max_s h_{is}$ ; 0 otherwise,  $g = 1, \dots, K$ .
- klas Column matrix of the labels issued from c\_ig. Its elements are  $klas(i) = g, i = 1, \dots, n$ .
- tau\_ijgk Array of size  $(nm, R, K)$  giving the posterior probabilities that the observation  $Y_{ij}$  originates from the  $R$ -th regime of the  $g$ -th RHLP model.
- polynomials Array of size  $(m, R, K)$  giving the values of the estimated polynomial regression components.
- weighted\_polynomials Array of size  $(m, R, K)$  giving the values of the estimated polynomial regression components weighted by the prior probabilities pi\_jgk.
- Ex Matrix of size  $(m, K)$ . Ex is the curve expectation (estimated signal): sum of the polynomial components weighted by the logistic probabilities pi\_jgk.
- loglik Numeric. Observed-data log-likelihood of the MixRHLP model.
- com\_loglik Numeric. Complete-data log-likelihood of the MixRHLP model.
- stored\_loglik Numeric vector. Stored values of the log-likelihood at each EM iteration.
- stored\_com\_loglik Numeric vector. Stored values of the Complete log-likelihood at each EM iteration.
- BIC Numeric. Value of BIC (Bayesian Information Criterion).
- ICL Numeric. Value of ICL (Integrated Completed Likelihood).
- AIC Numeric. Value of AIC (Akaike Information Criterion).
- log\_fg\_xij Matrix of size  $(n, K)$  giving the values of the probability density function  $f(y_i | h_i g = 1, \mathbf{x}, \Psi), i = 1, \dots, n$ .
- log\_alphag\_fg\_xij Matrix of size  $(n, K)$  giving the values of the logarithm of the joint probability density function  $f(y_i, h_i = g | \mathbf{x}, \Psi), i = 1, \dots, n$ .
- log\_tau\_ijgk Array of size  $(nm, R, K)$  giving the logarithm of tau\_ijgk.

## Methods

- computeStats(paramMixRHLP) Method used in the EM algorithm to compute statistics based on parameters provided by the object paramMixRHLP of class [ParamMixRHLP](#).
- CStep(reg\_irls) Method used in the CEM algorithm to update statistics.
- EStep(paramMixRHLP) Method used in the EM algorithm to update statistics based on parameters provided by the object paramMixRHLP of class [ParamMixRHLP](#) (prior and posterior probabilities).

MAP() MAP calculates values of the fields `c_ig` and `klas` by applying the Maximum A Posteriori Bayes allocation rule.

$$c_{ig} = 1 \text{ if } c_{ig} = \arg \max_s h_{is}; 0 \text{ otherwise, } g = 1, \dots, K.$$

### See Also

[ParamMixRHLP](#)

---

toydataset	<i>A dataset composed of simulated time series with regime changes.</i>
------------	---

---

### Description

A dataset composed of 30 simulated time series with regime changes.

### Usage

toydataset

### Format

A data frame with 350 rows and 31 variables:

**x** The covariate variable which is the time in that case.

**y1** Times series with a wave form shape and for which a normally distributed random noise has been added.

**y2** Same as y1.

**y3** Same as y1.

**y4** Same as y1.

**y5** Same as y1.

**y6** Same as y1.

**y7** Same as y1.

**y8** Same as y1.

**y9** Same as y1.

**y10** Same as y1.

**y11** Time series generated as follows:

- First regime: 120 values of Normally distributed random numbers with mean 5.
- Second regime: 70 values of Normally distributed random numbers with mean 7.
- Third regime: 160 values of Normally distributed random numbers with mean 5.

**y12** Same as y11.

**y13** Same as y11.

**y14** Same as y11.

**y15** Same as y11.

**y16** Same as y11.

**y17** Same as y11.

**y18** Same as y11.

**y19** Same as y11.

**y20** Same as y11.

**y21** Time series generated as follows:

- First regime: 80 values of Normally distributed random numbers with mean 7.
- Second regime: 130 values of Normally distributed random numbers with mean 5.
- Third regime: 140 values of Normally distributed random numbers with mean 4.

**y22** Same as y21.

**y23** Same as y21.

**y24** Same as y21.

**y25** Same as y21.

**y26** Same as y21.

**y27** Same as y21.

**y28** Same as y21.

**y29** Same as y21.

**y30** Same as y21.

# Index

## \*Topic **datasets**

toydataset, [20](#)

cemMixRHLP, [4](#)

emMixHMM, [5](#)

emMixHMMR, [7](#)

emMixRHLP, [8](#)

FData, [14–16](#)

FData (FData-class), [9](#)

FData-class, [9](#)

flamingos (flamingos-package), [2](#)

flamingos-package, [2](#)

MixHMM, [17](#)

MixHMMR, [18](#)

MixRHLP, [19](#)

mkStochastic, [10](#)

ModelMixHMM, [6](#)

ModelMixHMM (ModelMixHMM-class), [10](#)

ModelMixHMM-class, [10](#)

ModelMixHMMR, [8](#)

ModelMixHMMR (ModelMixHMMR-class), [11](#)

ModelMixHMMR-class, [11](#)

ModelMixRHLP, [5, 9](#)

ModelMixRHLP (ModelMixRHLP-class), [12](#)

ModelMixRHLP-class, [12](#)

ParamMixHMM, [6, 10, 11, 17, 18](#)

ParamMixHMM (ParamMixHMM-class), [13](#)

ParamMixHMM-class, [13](#)

ParamMixHMMR, [7, 8, 11, 12, 18](#)

ParamMixHMMR (ParamMixHMMR-class), [15](#)

ParamMixHMMR-class, [15](#)

ParamMixRHLP, [5, 9, 12, 13, 19, 20](#)

ParamMixRHLP (ParamMixRHLP-class), [16](#)

ParamMixRHLP-class, [16](#)

StatMixHMM, [6, 10, 11, 14](#)

StatMixHMM (StatMixHMM-class), [17](#)

StatMixHMM-class, [17](#)

StatMixHMMR, [7, 8, 11, 12, 16](#)

StatMixHMMR (StatMixHMMR-class), [18](#)

StatMixHMMR-class, [18](#)

StatMixRHLP, [5, 9, 12, 13, 16, 17](#)

StatMixRHLP (StatMixRHLP-class), [19](#)

StatMixRHLP-class, [19](#)

toydataset, [20](#)